

Subqueries

CMPE 2400
Databases


Subqueries

- ▶ A subquery is a query that is nested within a parent query.
- ▶ We generally use a subquery when we want to pull most data from one table and one item of data from a different table.
- ▶ Suppose we want the product Id, the product name, the price and the category name for a particular category of product.
 - ▶ While most of the required information is available from the product table, the category name has to be pulled from the category table



Subqueries

- ▶ The key to writing a proper subquery is to remember what is expected by the parent query in the spot in which the subquery is placed.
 - ▶ For example, if a subquery is to be included in a select list, the subquery must produce exactly one result, or the parent query will cease up.
 - ▶ Also make sure to remember that data types can also be mismatched even if the number of records returned by the subquery is acceptable.



Subqueries

Busted on number of records mismatch.

```
query1.sql - be...rs (skelemen1 (78))* X
select (select CategoryName from Categories where CategoryID = 6) as 'Category Name',
       ProductName as 'Product Name'
from   NorthwindTraders.dbo.Products
where  CategoryID = 6
```

%

Results

Category Name	Product Name
Meat/Poultry	Mishi Kobe Niku
Meat/Poultry	Alice Mutton
Meat/Poultry	Thüringer Rostbratwurst
Meat/Poultry	Perth Pasties
Meat/Poultry	Tourtière
Meat/Poultry	Pâté chinois


(6 row(s) affected)

Subqueries

This one is contrived but at least it works...

Filtering with Subqueries

- ▶ Using a subquery is one way in which two entities in the database may interact.
- ▶ The results of a query which interrogates one entity, or table, may be used to filter the results obtained by querying a second entity from which we are actually interested in retrieving information.



Filtering using in Subqueries


- ▶ The **in** operator is often used to create the subquery bridge between entities.
 - ▶ Recall that the **in** operator is used when creating filters, using the where clause, that compare a set of discrete values to a column or calculation.
 - ▶ A subquery returns a set of discrete values just like any other select statement.
 - ▶ Because the values retrieved by the subquery are discrete, the **in** operator is quite happy to use the returned results to filter the rows returned from the parent select statement.

Filtering using in Subqueries

- ▶ As the in operator works upon a *LIST* of values, not a multiple columned table of values, only one column may be chosen by the subquery to form that list.

Filtering using in Subqueries

- ▶ Suppose that you need a list of company names that have a shipping address within the USA.
 - ▶ First, a unique list of customers linked to orders shipped to the USA must be identified.



Filtering using in Subqueries

- ▶ The Company Name is stored in the customer table, so we may use the in operator, and embed the previous as a subquery.
 - ▶ Note that, quite conveniently, the CustomerID provides a link between the two tables.
 - ▶ Also, column aliasing will only be required on the outermost query.

Filtering using in Subqueries

- ▶ Voila! Company names for orders shipped to the USA.

```
select CompanyName as 'Company Name'
from NorthwindTraders.dbo.Customers
where CustomerID in ( select distinct CustomerID
                      from NorthwindTraders.dbo.Orders
                      where ShipCountry = 'USA' )
```

100 %

Results

Company Name

Great Lakes Food Market
Hungry Coyote Import Store
Lazy K Kountry Store
Let's Stop N Shop
Lonesome Pine Restaurant
Old World Delicatessen
Rattlesnake Canyon Grocery
Save-a-lot Markets
Split Rail Beer & Ale
The Big Cheese
The Cracker Box
Trail's Head Gourmet Provisioners
White Clover Markets

(13 row(s) affected)

Filtering using in Subqueries

- ▶ Just to show a glimpse of the possibilities, realize:
 - ▶ Double nesting, or more, is perfectly legal.
 - ▶ Negative logic works nicely.
 - ▶ Combinational logic will still work just fine.
 - ▶ Remember that the `in` operator is merely a comparison operator in the `where` clause.
 - ▶ Eg. Make a list of meat products that have *never* been sold to the company with the CustomerID *ALFKI*

Filtering using in Subqueries

- Retrieve a list of seafood products that have *never* been sold to the company with a customer ID of ALFKI.

```
select ProductID as 'Product ID',
       ProductName as 'Product Name'
from   NorthwindTraders.dbo.Products
where  ProductID not in ( select distinct ProductID
                        from   NorthwindTraders.dbo.[Order Details]
                        where   OrderID in ( select distinct OrderID
                                           from NorthwindTraders.dbo.Orders
                                           where CustomerID = 'ALFKI' ) )

and CategoryID in ( select CategoryID
                   from   NorthwindTraders.dbo.Categories
                   where   CategoryName = 'Seafood' )
```

00 %

Results

Product ID	Product Name
10	Ikura
13	Konbu
18	Carnarvon Tigers
30	Nord-Ost Matjeshering
36	Inlagd Sill
37	Gravad lax
40	Boston Crab Meat
41	Jack's New England Clam Chowder
45	Rogede sild
73	Röd Kaviar

(10 row(s) affected)

Exercise 1

- ▶ Write a query to display the first name and last name of all authors from the Publishers database who write business books

Filtering using `exists` Subqueries

- The **`exists`** operator is a Boolean operator that tests for the existence of at least one record from the contained subquery.
- **`exists`** is sometimes more efficient to use than **`in`**
 - Consider the operation of `exists` to be similar to a nested for loop in C#. Each parent query table record is sequentially compared to the child query table records, with a true returned on the first match.

Filtering using `exists` Subqueries

- In the following example, the information from the *parent* query is used in the *subquery*
 - The subquery results are based on the information from the current row of the parent query
- The *child* select can see the *parent* select information
- The parent select can only see the results of the child select, but not the individual column values
 - You may look upon this behaviour as somewhat akin to scoping in C#. Any variables created in a scope are local to that scope and are invisible to any encapsulating scopes.

Filtering using exists Subqueries

- Provide a list of company names in the USA who have made orders

```
SQLQuery1.sql - Query (Microsoft SQL Server)
--
select CompanyName as 'Company Name'
from NorthwindTraders.dbo.Customers
where exists ( select CustomerID
               from NorthwindTraders.dbo.Orders
               where ShipCountry = 'USA'
                 and Orders.CustomerID = Customers.CustomerID )
```

100 %

Results

Company Name

Great Lakes Food Market
Hungry Coyote Import Store
Lazy K Kountry Store
Let's Stop N Shop
Lonesome Pine Restaurant
Old World Delicatessen
Rattlesnake Canyon Grocery
Save-a-lot Markets
Split Rail Beer & Ale
The Big Cheese
The Cracker Box
Trail's Head Gourmet Provisioners
White Clover Markets

(13 row(s) affected)

Filtering using exists Subqueries

- Retrieve a list of seafood products that have *never* been sold to the company with a customer ID of ALFKI

```
QLQuery1.sql - be...rs (skelemen1 (78))  
select ProductID as 'Product ID',  
       ProductName as 'Product Name'  
from   NorthwindTraders.dbo.Products  
where  not exists ( select ProductID  
                   from   NorthwindTraders.dbo.[Order Details]  
                   where   Products.ProductID = [Order Details].ProductID  
                   and exists ( select OrderID  
                               from   NorthwindTraders.dbo.Orders  
                               where   [Order Details].OrderID = Orders.OrderID  
                               and CustomerID = 'ALFKI' ) )  
  
and exists ( select CategoryID  
            from   NorthwindTraders.dbo.Categories  
            where  Products.CategoryID = Categories.CategoryID  
            and   CategoryName = 'Seafood' )
```

100 %

Results

Product ID	Product Name
10	Ikura
13	Konbu
18	Carnarvon Tigers
30	Nord-Ost Matjeshering
36	Inlagd Sill
37	Gravad lax
40	Boston Crab Meat
41	Jack's New England Clam Chowder
45	Rogede sild
73	Röd Kaviar

(10 row(s) affected)

Performance Consideration: IN vs EXISTS



The EXISTS clause is much faster than IN when the subquery results is very large. Conversely, the IN clause is faster than EXISTS when the subquery results is very small.



Also, the IN clause can't compare anything with NULL values, but the EXISTS clause can compare everything with NULLs.



Reference: [Burleson Consulting](#)

Exercise 2

- ▶ Write a query using **exists** subquery to display the first name and last name of all authors who have written a business book