Testcases for Swagger Petstore , module Store . URL:

Env Postman v10.7.0

Functional API testcases

ID	Priority	Summary	Preconditions	Testdata	Steps	Excepted result	Actual result
1	HIGH	Place an order for a pet	Headers request: Content-Type: application/json Accept: application/json	Method :POST URL: https://petstore3. swagger. io/api/v3/store/order Postman->body->RAW->JSON { "id": 0, "petId": 0, "quantity": 0, "shipDate": "2023-01-15T16:05:34.288Z", "status": "placed", "complete": true }	1.Send POST est 2. Verify TUS CODE 3. Verify body resonse	1. Succesful sending 2. Status CODE is 200 3. Body in JSON format { "id": 0, "petId": 0, "quantity": 0, "shipDate": "2023-01-15T16:06:33.419Z", "status": "placed", "complete": true }	
2	HIGH	Place an invalid order for a pet	Headers request: Content-Type: application/json Accept: application/json	Method :POST URL: https://petstore3. swagger. io/api/v3/store/order Postman->body->RAW->JSON { "id": ADT, "petId": 0, "quantity": 0, "shipDate": "2023-01-15T16:05:34.288Z", "status": "placed", "complete": true }	1.Send POST est 2. Verify TUS CODE 3. Verify body resonse	1. Succesful sending 2. Status CODE is 400 INVALID ORDER 3. Message "Order not placed please try again"	

3	HIGH	Delete an order in the store	Path Variables : [value]	Method DELETE URL: https://petstore3.swagger.io/api/v3/store/order/:orderId 2. Put ID of placed order in the store	1.Send DELETE est 2. Verify TUS CODE 3. Verify that the order is deleted	1. Succesful sending 2. Status CODE is 200 3. Message Order is deleted	
4	HIGH	Delete an unexistend o	Path Variables : [value]	1. Method DELETE URL: https://petstore3.swagger.io/api/v3/store/order/:orderId 2. put Id of unexistend order in the store	1.Send DELETE est 2. Verify TUS CODE 3. Verify that the correct messege returns in the responde	1. Succesful sending 2. Status CODE is 404 Order not find 3. Message " Incorrect ID , THis order is not placed in the store"	