

numpy and scipy (1/2)

Computing Methods for Experimental Physics and Data Analysis

L. Baldini

luca.baldini@pi.infn.it

Università and INFN-Pisa

Compiled on October 13, 2019



Introduction

- ▷ Python is notorious for coming *with batteries included* . . .
- ▷ . . . but as a data scientist numpy and and scipy will be your best friends!
- ▷ Among (many) other things, numpy offers:
 - ▷ a powerful n-dimensional array object
 - ▷ mathematical functions that interoperate natively with arrays
- ▷ And scipy provides:
 - ▷ integration
 - ▷ optimization (a.k.a. fitting)
 - ▷ interpolation
 - ▷ signal processing



numpy arrays

https://bitbucket.org/lbaldini/programming/src/tip/snippets/numpy_arrays.py

```
1  import numpy as np
2
3  # Initialization from a list
4  a1 = np.array([1., 2., 3])
5  print(a1)
6
7  # Zeros, ones, and fixed values
8  a2 = np.zeros(10)
9  a3 = np.ones((2, 2))
10 a4 = np.full(7, 3.)
11 print(a2)
12 print(a3)
13 print(a4)
14
15 # Grids
16 a5 = np.linspace(0., 10., 11)
17 a6 = np.logspace(0., 1., 11)
18 print(a5)
19 print(a6)
20
21 [Output]
22 [1. 2. 3.]
23 [0. 0. 0. 0. 0. 0. 0. 0. 0. 0.]
24 [[1. 1.]
25  [1. 1.]]
26 [3. 3. 3. 3. 3. 3. 3.]
27 [ 0.  1.  2.  3.  4.  5.  6.  7.  8.  9. 10.]
28 [ 1.          1.25892541  1.58489319  1.99526231  2.51188643  3.16227766
29  3.98107171  5.01187234  6.30957344  7.94328235 10.          ]
```



numpy arrays vs. Python lists

https://bitbucket.org/lbaldini/programming/src/tip/snippets/numpy_arrays_vs_lists.py

```
1  import numpy as np
2
3  # arrays and lists seem similar...
4  l = [1., 2., 3.]
5  a = np.array(l)
6  print(l)
7  print(a)
8
9  # ...but they support basic arithmetic in a different fashion
10 print(l + l)
11 print(a + a)
12
13 [Output]
14 [1.0, 2.0, 3.0]
15 [1. 2. 3.]
16 [1.0, 2.0, 3.0, 1.0, 2.0, 3.0]
17 [2. 4. 6.]
```

- ▷ arrays and lists are fundamentally different objects
 - ▷ different footprint in memory, operate at different speed
 - ▷ arrays are homogeneous, lists don't need to
 - ▷ arrays offer a much more powerful indexing/slicing
 - ▷ arrays interoperate with numpy mathematical functions

https://bitbucket.org/lbaldini/programming/src/tip/snippets/numpy_arrays_broadcasting.py

```
1  import numpy as np
2
3  a1 = np.array([1., 2.])
4  a2 = np.array([[1., 2.], [3., 4.]])
5  c = np.pi
6
7  print(a1)
8  print(a2)
9  print(c)
10 print(a1 * a1)
11 print(a1 * c)
12 print(a1 * a2)
13
14 [Output]
15 [1. 2.]
16 [[1. 2.]
17  [3. 4.]]
18 3.141592653589793
19 [1. 4.]
20 [3.14159265 6.28318531]
21 [[1. 4.]
22  [3. 8.]]
```

- ▷ Under certain conditions, numpy can make operations on arrays of different shape
- ▷ This is extremely useful when vectorizing problems



Mathematical functions in numpy

https://bitbucket.org/lbaldini/programming/src/tip/snippets/numpy_functions.py

```
1  import numpy as np
2  import math
3
4  a = np.array([0.1, 1., 10.])
5
6  print(np.log10(a))
7  print(np.exp(a))
8  print(np.sin(a))
9
10 print(np.log10(0.1))
11
12 print(math.log10(a))
13
14 [Output]
15 [-1.  0.  1.]
16 [1.10517092e+00 2.71828183e+00 2.20264658e+04]
17 [ 0.09983342  0.84147098 -0.54402111]
18 -1.0
19 Traceback (most recent call last):
20   File "snippets/numpy_functions.py", line 12, in <module>
21     print(math.log10(a))
22   TypeError: only size-1 arrays can be converted to Python scalars
```

- ▷ numpy mathematical functions interoperate natively with arrays
 - ▷ (and work on plain old numbers, too)



Digression: pseudo-random number generators

```
1 import random
2 x = random.random()
```

- ▷ Every programming language comes with a Pseudo Random Number Generator (PRNG)
 - ▷ Python is no exception:
<https://docs.python.org/3/library/random.html>
 - ▷ Mersenne-Twister, 53-bit precision, period of $2^{19937} - 1$.
- ▷ PRNGs are an interesting (and fun) subject by themselves:
 - ▷ Donald E. Knuth, *The Art of Computer Programming, Volume 2: Seminumerical Algorithms*, 3rd Edition
 - ▷ M. Matsumoto and T. Nishimura, *Mersenne Twister: A 623-dimensionally equidistributed uniform pseudorandom number generator*, ACM Transactions on Modeling and Computer Simulation Vol. 8, No. 1, January pp.3–30 1998.
- ▷ A PRNG produces random floats uniformly in $[0.0, 1.0)$.



Vectorization

a.k.a. avoid explicit for loops in Python whenever you can

<https://bitbucket.org/lbaldini/programming/src/tip/snippets/vectorization.py>

```
1 import random
2 import time
3 import numpy as np
4
5 # How many random numbers (uniformly distributed between 0 and 1) do you
6 # want to throw?
7 n = 1000000
8
9 # The slow way: explicit for loop in Python.
10 t0 = time.time()
11 x = []
12 for i in range(n):
13     x.append(random.random())
14 dt = time.time() - t0
15 print('Elapsed time: %.3f s' % dt)
16
17 # The quick way: vectorizing in numpy
18 t0 = time.time()
19 x = np.random.random(size=n)
20 dt = time.time() - t0
21 print('Elapsed time: %.3f s' % dt)
22
23 [Output]
24 Elapsed time: 0.131 s
25 Elapsed time: 0.015 s
```





How does vectorization work?

- ▷ Python is known to be slooow
 - ▷ This is the price you pay for being so beautiful and flexible
- ▷ Does it matter? It depends. . .
 - ▷ If you are parsing a text file or fetching a web page probably not
 - ▷ If you are performing a CPU-intensive processing on a TB of data probably yes
- ▷ What's so magic in using numpy?
- ▷ numpy is written in C as a Python extension
 - ▷ Routines are highly optimized to crunch numbers
 - ▷ When you perform an array operation in Python you are actually executing optimized C code
- ▷ **Basic message: avoid for loops in pure Python when crunching numbers**

How do I throw PRN with arbitrary pdf?

Hit or miss



- ▷ Hit or miss, aka acceptance/rejection method:
 - ▷ Enclose your pdf in a rectangle
 - ▷ Throw a x and a y
 - ▷ Accept x if $y \leq f(x)$
- ▷ This is horrible—please don't use it!



How do I throw PRN with arbitrary pdf?

Inverse transform

- ▷ Probability density function (pdf)

$$p(x) \quad (\geq 0)$$

- ▷ Cumulative function (cf)


$$F(x) = \int_{-\infty}^x p(x') dx'$$

- ▷ Percent-point function (ppf)

$$x = F^{-1}(q)$$

- ▷ Awesome fact: if q is uniformly distributed in $[0, 1]$, then $x = F^{-1}(q)$ is distributed according to $p(x)$!

An interesting object: splines



- ▷ Defined piecewise by polynomials of degree k ($k = 3$ fairly popular)
 - ▷ Interpolating: passing through a set of pre-defined points
 - ▷ First $k - 1$ derivatives continuous at the control points
- ▷ Superior to polynomial interpolation or curve fitting in many cases

Splines: construction and properties

<https://bitbucket.org/lbaldini/programming/src/tip/snippets/spline.py>

```
1 import numpy as np
2 from scipy.interpolate import InterpolatedUnivariateSpline
3
4 x = np.linspace(0., 1., 10)
5 y = np.exp(3. * x) * np.sin(3. * x)
6
7 s1 = InterpolatedUnivariateSpline(x, y, k=1)
8 s3 = InterpolatedUnivariateSpline(x, y, k=3)
9
10 print(s1(0.234))
11 print(s1.integral(0.2, 0.8))
12
13 [Output]
14 1.3192110648078448
15 2.6659857771053925
```

- ▷ Evaluation is fairly inexpensive
 - ▷ If the input x-array is sorted can do a binary search in $O(\log(N))$ complexity
- ▷ Derivatives and integrals are easy
 - ▷ Can be calculated *exactly* by means of elementary arithmetic operations



References

- ▷ <https://numpy.org/>
- ▷ <https://www.scipy.org/>
- ▷ <https://docs.scipy.org/doc/numpy/reference/arrays.indexing.html>
- ▷ <https://docs.scipy.org/doc/numpy/user/basics.broadcasting.html>
- ▷ <https://docs.scipy.org/doc/scipy/reference/interpolate.html>