MIPS operands

Name	Example	Comments
32 registers	`$s0-$s7, $t0-$t9, $zero, $a0-$a3, $v0-$v1, $gp, $fp, $sp, $ra, $at`	Fast locations for data. In MIPS, data must be in registers to perform arithmetic, register `$zero` always equals 0, and register `$at` is reserved by the assembler to handle large constants.
2^{30} memory words	Memory[0], Memory[4], . . . , Memory[4294967292]	Accessed only by data transfer instructions. MIPS uses byte addresses, so sequential word addresses differ by 4. Memory holds data structures, arrays, and spilled registers.

MIPS assembly language

Category	Instruction	Example	Meaning	Comments
Arithmetic	add	`add $s1,$s2,$s3`	$s1 = $s2 + $s3	Three register operands
	subtract	`sub $s1,$s2,$s3`	$s1 = $s2 – $s3	Three register operands
	add immediate	`addi $s1,$s2,20`	$s1 = $s2 + 20	Used to add constants
Data transfer	load word	`lw $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Word from memory to register
	store word	`sw $s1,20($s2)`	Memory[$s2 + 20] = $s1	Word from register to memory
	load half	`lh $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Halfword memory to register
	load half unsigned	`lhu $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Halfword memory to register
	store half	`sh $s1,20($s2)`	Memory[$s2 + 20] = $s1	Halfword register to memory
	load byte	`lb $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Byte from memory to register
	load byte unsigned	`lbu $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Byte from memory to register
	store byte	`sb $s1,20($s2)`	Memory[$s2 + 20] = $s1	Byte from register to memory
	load linked word	`ll $s1,20($s2)`	$s1 = Memory[$s2 + 20]	Load word as 1st half of atomic swap
	store condition. word	`sc $s1,20($s2)`	Memory[$s2+20]=$s1;$s1=0 or 1	Store word as 2nd half of atomic swap
	load upper immed.	`lui $s1,20`	$s1 = 20 * 2^{16}	Loads constant in upper 16 bits
Logical	and	`and $s1,$s2,$s3`	$s1 = $s2 & $s3	Three reg. operands; bit-by-bit AND
	or	`or $s1,$s2,$s3`	$s1 = $s2 | $s3	Three reg. operands; bit-by-bit OR
	nor	`nor $s1,$s2,$s3`	$s1 = ~ ($s2 | $s3)	Three reg. operands; bit-by-bit NOR
	and immediate	`andi $s1,$s2,20`	$s1 = $s2 & 20	Bit-by-bit AND reg with constant
	or immediate	`ori $s1,$s2,20`	$s1 = $s2 | 20	Bit-by-bit OR reg with constant
	shift left logical	`sll $s1,$s2,10`	$s1 = $s2 << 10	Shift left by constant
	shift right logical	`srl $s1,$s2,10`	$s1 = $s2 >> 10	Shift right by constant
Conditional branch	branch on equal	`beq $s1,$s2,25`	if ($s1 == $s2) go to PC + 4 + 100	Equal test; PC-relative branch
	branch on not equal	`bne $s1,$s2,25`	if ($s1!= $s2) go to PC + 4 + 100	Not equal test; PC-relative
	set on less than	`slt $s1,$s2,$s3`	if ($s2 < $s3) $s1 = 1; else $s1 = 0	Compare less than; for `beq`, `bne`
	set on less than unsigned	`sltu $s1,$s2,$s3`	if ($s2 < $s3) $s1 = 1; else $s1 = 0	Compare less than unsigned
	set less than immediate	`slti $s1,$s2,20`	if ($s2 < 20) $s1 = 1; else $s1 = 0	Compare less than constant
	set less than immediate unsigned	`sltiu $s1,$s2,20`	if ($s2 < 20) $s1 = 1; else $s1 = 0	Compare less than constant unsigned
Unconditional jump	jump	`j 2500`	go to 10000	Jump to target address
	jump register	`jr $ra`	go to $ra	For switch, procedure return
	jump and link	`jal 2500`	$ra = PC + 4; go to 10000	For procedure call

FIGURE 2.1 MIPS assembly language revealed in this chapter. This information is also found in Column 1 of the MIPS Reference Data Card at the front of this book.

op(31:26)								
28–26 31–29	0(000)	1(001)	2(010)	3(011)	4(100)	5(101)	6(110)	7(111)
0(000)	R-format	Bltz/gez	jump	jump & link	branch eq	branch ne	blez	bgtz
1(001)	add immediate	addiu	set less than imm.	set less than imm. unsigned	andi	ori	xori	load upper immediate
2(010)	TLB	FlPt						
3(011)								
4(100)	load byte	load half	lwl	load word	load byte unsigned	load half unsigned	lwr	
5(101)	store byte	store half	swl	store word			swr	
6(110)	load linked word	lwc1						
7(111)	store cond. word	swc1						

op(31:26)=010000 (TLB), rs(25:21)								
23–21 25–24	0(000)	1(001)	2(010)	3(011)	4(100)	5(101)	6(110)	7(111)
0(00)	mfc0		cfc0		mtc0		ctc0	
1(01)								
2(10)								
3(11)								

op(31:26)=000000 (R-format), funct(5:0)								
2–0 5–3	0(000)	1(001)	2(010)	3(011)	4(100)	5(101)	6(110)	7(111)
0(000)	shift left logical		shift right logical	sra	sllv		srlv	srav
1(001)	jump register	jalr			syscall	break		
2(010)	mfhi	mthi	mflo	mtlo				
3(011)	mult	multu	div	divu				
4(100)	add	addu	subtract	subu	and	or	xor	not or (nor)
5(101)			set l.t.	set l.t. unsigned				
6(110)								
7(111)								

FIGURE 2.19 MIPS instruction encoding. This notation gives the value of a field by row and by column. For example, the top portion of the figure shows **load word** in row number 4 (100_{two} for bits 31–29 of the instruction) and column number 3 (011_{two} for bits 28–26 of the instruction), so the corresponding value of the op field (bits 31–26) is 100011_{two}. Underscore means the field is used elsewhere. For example, R-format in row 0 and column 0 (op = 000000_{two}) is defined in the bottom part of the figure. Hence, subtract in row 4 and column 2 of the bottom section means that the funct field (bits 5–0) of the instruction is 100010_{two} and the op field (bits 31–26) is 000000_{two}. The floating point value in row 2, column 1 is defined in Figure 3.18 in Chapter 3. Bltz/gez is the opcode for four instructions found in Appendix A: bltz, bgez, bltzal, and bgezal. This chapter describes instructions given in full name using color, while Chapter 3 describes instructions given in mnemonics using color. Appendix A covers all instructions.

Name	Fields						Comments
Field size	6 bits	5 bits	5 bits	5 bits	5 bits	6 bits	All MIPS instructions are 32 bits long
R-format	op	rs	rt	rd	shamt	funct	Arithmetic instruction format
I-format	op	rs	rt	address/immediate			Transfer, branch, imm. format
J-format	op	target address					Jump instruction format

FIGURE 2.20 MIPS instruction formats.