



Machine Intelligence



Assignment 3

(Chapters Slides)



Team 1

Mohamed Shawky Zaky, Sec : **2**, BN : **15**

Remonda Talaat Eskarous, Sec : **1**, BN : **19**

Mohamed Ahmed Mohamed Ahmed, Sec : **2**, BN : **10**

Mohamed Ramzy Helmy, Sec : **2**, BN : **13**

Chapter 13

- **Why may agents be uncertain of their state ?**

1- Partial Observability 2- Nondeterminism 3- Laziness 4- Ignorance

- **Why is probability theory is the best way to summarize uncertainty ?**

1- Numeric 2- Easily updatable 3- Vectorization 4- basic component of Decision Theory

- **Why is full joint probability distribution ineffective at all ? And how to solve this problem ?**

Not scalable with number of RVs of interest (exponential complexity). Solution: the concept of independence between RVs to factor the full joint distribution into separate joint distributions.

- **Why is Bayes' Rule important ?**

1- Evaluates diagnostic based on causal and prior knowledge of cause existence in an online fashion.

2- Combines evidences to evaluate posteriors.

Chapter 14

- Bayesian Networks represents independence relationships between random variables.
- Each variable has a conditional distribution that is represented in a table CPT.
- Each CPT entry has conditional probability for at most k parents.
- Exact inference methods use enumeration to calculate $P(\text{Query} \mid \text{event})$
- Variable elimination is applied to speedup exact inference in multiply connected trees.
- Approximate inference using direct sampling, rejection sampling and Monte carlo methods is used to eliminate the complexity of exact inference.
- First order logic and Relational Probability models are used to construct well-defined distributions.
- Other methods can be used for probabilistic reasoning, such as rule-based systems and fuzzy logic.

Chapter 15

- Representation of probabilistic temporal (dynamic) processes :
 - 1) States and observations.
 - 2) Transition and sensor models.
- Inference in probabilistic temporal (dynamic) processes :
 - 1) Filtering.
 - 2) prediction.
 - 3) Smoothing.
 - 4) Most likely explanation.
- Three families of temporal models :
 - 1) Hidden Markov Models (HMMs).
 - 2) Kalman Filters.
 - 3) Dynamic Bayesian Networks (DBNs).
- Data association : keeping track of many objects.

Chapter 21

- Reinforcement Learning uses feedback (reward) from environment to learn and take actions.
- Passive Reinforcement Learning can be done through :
 - 1) Direct Utility Estimation.
 - 2) Adaptive Dynamic Programming.
 - 3) Temporal-Difference (TD) Learning.
- Active Reinforcement Learning :
 - 1) Exploration vs. Exploitation.
 - 2) Q-Learning & SARSA.
- Function Approximation for generalization and dealing with large state spaces.
- Policy Search through policy gradient (differentiable) or empirical gradient (hill climbing).
- Reinforcement Learning for game playing and robot control.