



Thermal Receipt Printer


M804L

- Wall mount available;
- Support IAP update online (Except USB/Lan/USB+Serial);
- Support QRcode, PDF417 (Except USB/Lan/USB+Serial);
- Support print prompt and error alarm;
- Option interface:Bluetooth/WIFI



M804L

Thermal Receipt Printer



| Model | | | |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|---------------------------|
| Printing method | Direct thermal | | |
| Paper width | 79.5±0.5mm | | |
| Print width | 72mm | | |
| Column capacity | 576 dots/line or 512 dots/line | | |
| Printing speed | 160 mm/s Max | 200 mm/s | 260 mm/s |
| Interface | USB/LAN | USB+Lan/USB+Serial | USB+Serial+Lan |
| Line spacing | 3.75mm (Adjustable by commands) | | |
| Column number | 80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Simplified/Traditional Chinese - 21 columns or 24 columns | | |
| Character size | ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots) | | |
| Cutter | | | |
| Auto cutter | Partial | | |
| Barcode Character | | | |
| Extension character sheet | PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251) | | |
| 1D Barcode | UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128 | | |
| 2D Barcode | QR CODE / PDF417(Except USB/Lan/USB+Serial) | | |
| Input buffer | 64 Kbytes | USB+Lan:128 Kbytes USB+Serial:64 Kbytes | USB+Serial+Lan:128 Kbytes |
| NV Flash | 256 Kbytes | | |
| Power | | | |
| Power adaptor | Input: AC 100~240V, 50 ~ 60Hz, Output: DC 24V/2.5A | | |
| Printer Input | DC 24V/2.5A | | |
| Cash drawer | DC 24V/1A | | |
| Physical characteristics | | | |
| Weight | 1.0 Kg | | |
| Dimensions | 190.16*140*134.64mm(D*W*H) | | |
| Environmental Requirements | | | |
| Work environment | Temperature (0 ~ 45℃) humidity(10 ~ 80%) | | |
| Storage environment | Temperature(-10 ~ 60℃) humidity(10 ~ 90%) | | |
| Reliability | | | |
| Cutter life | 1.5 million cuts | | |
| Printer head life | 150Km | | |
| Software | | | |
| Emulation | ESC/POS | | |
| Driver | Windows/OPOS/Android/Mac | | |
| Utility | Windows & Linux test Utility | | |
| SDK | iOS, Android, Windows | | |

