```
#!/bin/bash
#
#
                   add user.sh
   Name:
#
   Author:
                   Chris Fedun 29/01/2017
                  MYSQL Email User Setup Script
   Description:
                   ./add user.sh <username> <Password> <Domain>
   Copyright (C) 2017 Christopher Fedun
   This program is free software: you can redistribute it and/or modify
#
   it under the terms of the GNU General Public License as published by
#
   the Free Software Foundation, either version 3 of the License, or
   (at your option) any later version.
   This program is distributed in the hope that it will be useful,
   but WITHOUT ANY WARRANTY; without even the implied warranty of
   MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the
   GNU General Public License for more details.
   You should have received a copy of the GNU General Public License
   along with this program. If not, see <a href="http://www.gnu.org/licenses/">http://www.gnu.org/licenses/</a>>.
#Arquements
MINPARAMS=3
function usage
   echo "usage: ./add user.sh [[-u user ] [-p password] [-d domain] | [-h]]"
##### Main
UserName=
UserPass=
domain name=
while [ "$1" != "" ]; do
   case $1 in
       -u | --user )
                              shift
                              UserName=$1
       -p | --password )
                              shift
                              UserPass=$1
                              ;;
       -d | --domain )
                              shift
                              domain name=$1
                              ;;
       -h | --help )
                              usage
                              exit
                              ;;
       * )
                              usage
                              exit 1
   esac
   shift
done
user pass hash=$(doveadm pw -s SHA256-CRYPT -p $UserPass)
mysql <<ADD USER MYSQL SCRIPT
USE mailserver;
INSERT INTO \`mailserver\`.\`virtual users\` ( \`id\` , \`domain id\` , \`password\` ,
\`email\` )
```

```
VALUES ('NULL', '1', "$user_pass_hash" , "$UserName\@$domain_name");

REPLACE INTO \`mailserver\`.\`virtual_aliases\` (\`id\`, \`domain_id\`, \`source\`, \`destination\`)
  VALUES ('NULL', '1', "$UserName@$domain_name", "$UserName@$domain_name");

ADD_USER_MYSQL_SCRIPT

exit
######END :) #######
```