


C++ I/O streams

Acknowledgment: A few on text file I/O are adapted from material developed and taught in older versions of ENGG 233. by Dr. Mark Petevello (Fall 2014 and before).

The C++ I/O Library - Continued

- Input/output facilities are not defined within the C++ language.
- Its implemented in C++ and provided as a component of a C++ standard library.
- As its lowest level, a file is interpreted simply as a sequence, or stream of bytes. One aspect of the I/O library is to manage the transfer of these bytes.
- At the user level a file consists of a sequence of possibly intermixed data types.

Simplified I/O Class Hierarchy



Stream Basics

- In C++ a ***stream*** represents a flow of data; more specifically, it is a sequence of bytes
 - What the bytes mean or how they are to be interpreted is not important to the stream
- A stream is an *object* – an instance of a *class*
- Using streams, you can...
 - Read data into your program and write from your program
 - Communicate with external media
- The above is accomplished by *connecting* streams to things such as files, memory, or the terminal

Stream Basics

- You have already used streams in your programs:
 - Input stream object/variable: `cin`
 - Output stream object/variable: `cout`
- The `cout` object also has several *member functions* (manipulators) that allow you to format the data (these are found in `iomanip`)

`setiosflags()` `setprecision()` `setw()`

- In C++, all I/O is performed using streams into which you place data you wish to output, and from which you extract information from the user
- There are two general classes of streams:
 - Input stream class (data flows into your program): `istream`
 - Output stream class (data flows out of your program): `ostream`

Stream Basics

- For any stream, the first step is to connect the stream with the device (e.g., keyboard, monitor, file, etc.) with which you want to communicate
- For standard I/O (**cin** and **cout**) these connections are already made with the keyboard and monitor respectively
 - This means you can just use these streams directly in your programs and functions
- For other types of streams, this connection needs to be done explicitly

File Streams

- File I/O is basically treated the same as standard I/O
 - Once a file stream is *connected* to a file, then the operations to actually manipulate the data are the same as with standard streams (because they are both streams)
- Files must be connected to streams within your program by ***opening*** a file
- You must define a stream object for *each* file you wish to use *simultaneously*
- The file stream classes are contained in the library **fstream**

File Streams

- There are three steps associated with using files for I/O:
 - Step 1: Declare the file stream objects – create the streams
 - Step 2: Connect the objects to files – open the files
 - Step 3: Disconnect the objects from files – close the files
- Between steps 2 and 3, you can use the stream in much the same way as you use **cin** and **cout** except that instead of reading from the keyboard and writing the screen, you will be reading and writing from file
 - Details on using file streams are presented below

File Streams

- As with any other variable, file streams must be declared before they can be used
- Use the `ifstream` and `ofstream` types for input and output, respectively

```
ifstream in_stream;    // used for input
ofstream out_stream;   // used for output
```

- The above code declares two variables; one for input and one for output
 - However, these variables are **not yet** connected to any files

File Streams

- Once the objects are declared, we can connect them to files using the `open()` member function as follows

```
in_stream.open( "input.txt" );  
out_stream.open( "output.txt" );
```

- You can also connect to a file when you declare it (similar to initializing a variable)

```
ifstream in_stream( "input.txt" );  
ofstream out_stream( "output.txt" );
```

- For now, this is the approach we will use
 - You can also use strings to specify the file name at runtime (e.g. prompt the user), but more on that later


File Streams

- To understand what is happening when we open a file, consider the following code segment

```
ifstream in_stream;  
ofstream out_stream;
```


```
in_stream.open( "input.txt" );  
out_stream.open( "output.txt" );
```

- Before opening the file, there is no link (connection) between the stream objects and the files



File Streams

- After opening the file, there is now a link (connection) between the stream objects and the files



- We can now read information (i.e., bytes) from `input.txt` and we can write information (i.e., bytes) to `output.txt`
 - By analogy to standard I/O, `input.txt` is like the keyboard (`cin`), whereas `output.txt` is like the monitor

File Streams


- When you are finished getting the input, or sending the output, you should close the file
 - This *disconnects* the stream from the file
 - Use the `close()` member function to do this

```
in_stream.close();    // no input arguments needed  
out_stream.close();  // no input arguments needed
```

- If your program ends normally, the objects will automatically disconnect themselves from the files, even if the `close()` function is not called
 - However, if the program ends abnormally, the file may be corrupted
- In ENGG 233 you are expected to **always** close your files using the `close()` member function!

File Streams

- By closing a file stream, you break the connection that was made when you opened the file
- Returning to our example from a few slides ago, after closing the two files, there is no connection between the streams and the files



Testing for Proper Connection

- When connecting to a file for input, it is a good idea to make sure that the connection was successful before trying to read the data
 - For example, what if the file does not exist on your computer?
- Checking that the connection was successful is done using the `fail()` member function
 - This function returns a value of type `bool` which can be used to take appropriate actions
 - A return value of `true` means that a problem occurred

```
ifstream in_file( "input.dat" );

if( in_file.fail() )
{
    cout << "Error opening file..." << endl;

    // other statements to deal with the error
    // (e.g. prompt for new file name)
}
```

Testing for Proper Connection

- If an input file does not exist, you can do one of the following
 - Allow the user to enter a new file name
 - Terminate the program with an appropriate message
- You can exit a program at any time using the `exit()` function
 - The input argument is an integer
 - By convention, a value of 1 is used in the case of an error, and 0 otherwise
 - To use `exit()`, you must include the `cstdlib` library in your program

```
ifstream in_file( "input.dat" );  
  
if( in_file.fail() )  
{  
    cout << "Error opening file...quitting\n";  
    exit(1);  
}
```

- Only use `exit()` when there is no other alternative!

Testing for Proper Connection

- If you are opening a file for output that does not exist, the file will automatically be created
- However, if it already exists, then the existing file will be emptied and **any data that was in that file will be lost!**
- If you don't want to lose existing data in a file, you can append the output to the end of the file
 - This may screw up your formatting, but at least you keep your data!

```
ofstream out_file( "output.dat", ios::app );
```

- In this context, **app** is short for “append”



**Specifies that the
files should be
appended to**

Testing for Proper Connection

- The `clear()` member function clears all the flags associated with a stream (e.g., `fail`)

```
// assume "BadFileName.txt" does NOT exist on your machine
ifstream in( "BadFileName.txt" );
```

```
if( in.fail() )
{
    cout << "The Stream Failed\n";
```

```
    in.clear(); // needed to clear the failure flag
```

```
    // assume "GoodFileName.txt" DOES exist on your machine
    in.open( "GoodFileName.txt" );
```

```
    if( in.fail() )
        cout << "Doesn't Work\n";
    else
        cout << "Hurray!!!!\n";
```

```
}
```

- Note: member function `fail` can be used for test other operations such as failure in reading**

Testing for End of File

- There are often times when you do not know how many input records you will encounter
 - Ideally, you want to stop reading at the end of the file
 - The `ifstream` and `ofstream` classes have a flag that is set when the end of file (EOF) is reached
 - To access this flag, use the `eof()` member function
- `eof()` returns `true` if the end of file was reached or `false` otherwise

```
ifstream infile( "input.dat" );  
int a;  
  
// read until the end of the file...  
while( !infile.eof() )  
{  
    infile >> a;  
    cout << a << " was read from file\n";  
}
```

Prompting for File Names

```
void main()
{
    string input_file_name;
    string output_file_name;

    cout << "Enter input file name: " << endl;
    cin >> input_file_name;
    cout << "You entered " << input_file_name << endl;

    ifstream in_file( input_file_name );
    // check that the file was opened properly (omitted)

    cout << "Enter output file name: " << endl;
    cin >> output_file_name;
    cout << "You entered " << output_file_name << endl;

    ofstream out_file( output_file_name.c_str(), ios::app );
    // check that the file was opened properly (omitted)

    // use the streams here

    // close the streams
    in_file.close();
    out_file.close();
}
```

Note: member function `bad` can be used for testing if stream is corrupted.

Reading a Full Line

- We saw that you could read multi-word input from the keyboard using `cin`

```
string line_of_text;  
cout << "Enter a line of text: ";  
getline( cin, line_of_text, '\n' );
```

- As you might expect you can also read a full line from file using

```
ifstream infile( "input.dat" );  
// check that file opened properly here  
  
string line_of_text;  
getline( infile, line_of_text );  
// default delimiter is newline
```

Streams – Example 1

```
#include <fstream>          // why not <iostream>?
#include <cstdlib>
using namespace std;

void main()
{
    int num1, num2, num3, num4;

    ifstream infile( "input.dat" );
    // check that input file was opened properly HERE!

    ofstream outfile( "output.dat" );

    infile >> num1 >> num2 >> num3 >> num4;

    outfile << "The four numbers read were:\n"
              << num1 << endl << num2 << endl
              << num3 << endl << num4 << endl;

    infile.close();
    outfile.close();
}
```

Streams – Example 1 con't

- The “input.dat” file may look like any of the following

3	OR	3 6 -1 10	OR	3 6
6				-1 10
-1				14
10				

- As written, the program does not care about the format of the input, it will just read four consecutive numbers
 - However, the file format can be very important in some cases
- In contrast, the “output.dat” file will always look as follows

The four numbers read were:

3
6
-1
10

Part II

More I/O Functions

More I/O Stream Functions

- Member functions such as **get**, should be used for reading single characters (including white spaces), or a string of character (including white spaces). The following code reads from a stream (file or keyboard), until hits end of the file:

```
char ch = streamObject.get();  
while ( !streamObject.eof() )  
{  
    streamObject << ch;  
    char ch = streamObject.get();  
}
```

- Also member function **getline** can be used for reading string of characters (including white spaces) into an array of character.

```
char s[50];  
  
streamObject.getline(s, 50, '\n');  
while ( !streamObject.eof() )  
{  
    ...  
}
```

More I/O Stream Functions

- The statement: `streamObject.getline(s, 50, '\n');` does the followings:
 - Removes at most 49 characters from the input stream up to and including the first occurrence of a newline but not beyond.
 - Stores all of the characters removed from the stream except the newline in `s`.
 - Places a null character, `'\0'`, at the end of the characters stored in `s`.
- Other extraction operators
 - **Putback(ch)**: pushes back a character into the istream.
 - **peek()**: returns next character but does not extract it.
 - **Ignore(int limit =1, int delim=EOF)**, discards up to *limit* characters and stops if encounters *delim* character.
- The `put(char ch)` member function can be used as an alternative method of inserting a character into the output stream.
`streamObject.put(ch);`

Part III

Binary File I/O

What is a Binary File

- Binary files are usually thought of as being a sequence of bytes.
 - In fact the data will not be interpreted as a sequence of single characters like in a text file.
 - The data will be stored in the same format and sequence of bytes when used in your program.
 - A variable stored into double on the computer memory will be stored into a binary file in the same order and sequence of bytes.
- Example:
 - `double x = 0.00887776665551`, will be stored in an 8-bytes memory space. The same data in a text file will be stored in a 16-byte memory space.

What is a Binary File (continued)

- A binary file is normally more compressed than a text file.
 - Most digital data are stored in binary files
- Reading and writing data from and into file are faster, using binary data.
- Binary file can be viewed or read properly like a text file using a text editor. Here is an example of a binary file that I opened by an editor on a Mac computer:

```
oe`.+8!.[__text__TEXT#.a(.__debug_frame__DWARF$|
%0cdebug_info__DWARF+.K`dc__debug_abbrev__DWARF.P.EW__debug_aranges__DWARFT
Z__debug_machinfo__DWARFT<Z__debug_loc__DWARFT<Z__debug_pubnames__DWARFT.<Z__debug_pubtypes__DWARF>T$S[__debug
_str__DWARF0T.[__debug_ranges__DWARF0T.[__data__DATA0T.
[__StallInit__TEXT+T{+{<d.__bss__DATA[__cstring__TEXT[UCÄ__mod_init_func__DATA+U`Ä
```

Associating an Stream Object to a Binary File

- To connect a binary file to the program for input and/or output, you need to open the file in binary mode.
- Example:
 - `ofstream outfile("myoutput.bin", ios::out | ios::binary);`
 - `ifstream infile("input.bin", ios::in | ios::binary);`
- An `fstream` class object can be also used to open a file for both reading and writing:
 - `fstream in_outfile("myfile.bin", ios::in | ios::out | ios::binary);`

Writing into a binary file:

- 'write' member function from ostream library class can be used to read a sequence of bytes. Here is the prototype of the member function:
`ostream& write (char* address, streamsize n);` // streamsize is long int
- Notice that in the following example the name of the array which is an address is passed to the function write. The `reinterpret_cast` operator convert the a double* to a char*.

```
#include <iostream>
```

```
#include <fstream>
```

```
using namespace std;
```

```
int main(void)
```

```
{
```

```
    ofstream os ("test.bin", ios::binary);
```

```
    double a []= { 2.3, 3, 10, 44};
```

```
    os.write (reinterpret_cast <char*> (a), sizeof(a)); // writes 32 bytes
```

```
    if (os)
```

```
        std::cout << "All 4 element of array a, 32 bytes, are written into test.bin.";
```

```
    else
```

```
        os.close();
```

```
    return 0;
```

```
}
```

- Instead of `reinterpret_cast <char*> ()` you can simply use cast operator (char*)

Writing into a binary file

You may also write the data in an array using a loop (one element at a time).

In the following example example, notice how the address of each element is used:

```
int main(void)
{
    ofstream os ("test.bin", ios::binary);
    double a []= { 2.3, 3, 10, 44};

    for(int i =0; i < 4; i++)
    {
        os.write (reinterpret_cast <char*> (&a[i]), sizeof(double)); // Writes 8 bytes in each iteration
        if(!os)
            cerr << "Sorry! failed to write into the the output file...\n";
    }

    os.close();
    return 0;
}
```


Reading from binary file

- To read from a binary file you can use member function 'read'. Here is the prototype of this function:

```
istream& read (char* address, streamsize n); // streamsize is a long int
```

- Reads n bytes from input stream and stores them in the memory space starting at the given address. Notice that member function **gcount** returns the number of bytes read from stream
- Example:

```
int main(void)
```

```
{
```

```
    ifstream is ("test.bin", ios::binary);
```

```
    double a [4];
```

```
    is.read (reinterpret_cast <char*>(a), sizeof(a))
```

```
    long int g = is.gcount(); // library function gcount returns number bytes read from input stream
```

```
    if (is)
```

```
        std::cout << "Values of 4 element of array are read from binary file test.bin\n" <<
```

```
        "Number of bytes read from test.bin is: " << g << endl;
```

```
    else
```

```
        is.close();
```

```
    return 0;
```

```
}
```

Program output:

Values of 4 element of array are read from binary file
test.bin

Number of bytes read from test.bin is: 32

Reading from binary file

You may also read the data in an array using a loop, and read one element at a time. In the following example example, notice how the address of each element is used:

```
int main(void)
{
    ifstream is ("test.bin", ios::binary);
    double a [4];

    for(int i = 0; i < 4; i++){
        is.read (reinterpret_cast <char*>(&a[i]), sizeof(double));
        long int g = is.gcount(); // returns 8 bytes in each read
        cout << "i = " << i << " and g = " << g << endl;
    }

    for(int i =0; i < 4; i++)
        cout << a[i] << endl;

    is.close();
    return 0;
}
```

Program output:

```
i = 0 and g = 8
i = 1 and g = 8
i = 2 and g = 8
i = 3 and g = 8
```

```
2.3
3
10
44
```

Random Access in a File

- *The following member function can be used to help random access to the data in a file:*
- ***seekg()*** member function repositions the get pointer
seekg(7L, ios::beg);
- ***Seekp()*** member function repositions the put pointer
seekp(7L, ios::beg);
 - ios::beg, the beginning of the file
 - ios:: cur, the current position in the file
 - ios::end, the end of the file.
- ***tellg()*** member function:
 - Returns the current position of get pointer.
- ***tellp()*** member function:
 - Returns the current position of the put pointer.
- ***gcount()*** member function
 - Returns the number of bytes read successfully during the last input operation.

Simple Example:

```
struct Student
{
    char name[50];
    char gender;
    int id;
    double marks;
};
```

```
int main(void) {
    Student students[100];
    // fills array of students with user inputs. The
    // Implementation is not given in this set of slides
    int n = fillArray(students);

    // Saves student records from array into a binary file
    save_binary_data(students, n);

    // Retrieves data from a binary file and displays on the screen
    display_binary_data();

    return 0;
}
```

Example Continued

```
void save_binary_data(Student *x, int n)
{
    char fileName[100];
    cout << "enter the file name to save your data: ";
    cin >> fileName;

    ofstream out(fileName, ios::out | ios::binary);
    if(!out) {
        cout << "Error: File cannot be opened...";
        exit(0);
    }

    // Write n records of size students starting at address x
    out.write((char* ) x , sizeof(Student)*n);
    out.close();
}
```

Example continued

<pre>void display_binary_data() { Student x [100]; int n; char fileName[30]; cout << "enter the file name to read records : "; cin >> fileName; ifstream in(fileName, ios::in ios::binary); if(!in) { cout << "Error: File cannot be opened..." ; exit(0); } // CONTINUED ON THE RIGHT</pre>	<pre>// move the file cursor to the end of the file in.seekg(0L, ios::end); // calculate the number of student records ns = in.tellg()/sizeof(Student); // move the file cursor to the beginning in.seekg(0L, ios::beg); in.read((char*) x , sizeof(Student)*n); in.close(); cout << "There are " << n << " records in the file."; int i =0; while(i < n){ cout << endl<< setw(40) << x[i].name << "\t" << setw(14) << x[i].id << setw(3) << x[i].gender ; i++; } }</pre>
------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------