Indexed Operational Certificates and Matched Model Comparisons

Johnny Andrey Pérez Ramírez

Abstract

The causally rigid corpus already closes persistence, rigid identity, anti-fragmentation continuity, null-regime instability, forensic admissibility, and a six-invariant six-predicate operational criterion [2, 8, 4, 5, 3, 1]. The later classificatory extension adds viability-and-recovery criterion and indexed continuity-and-control criterion as stronger upstream classes. What remains open is a more difficult target: whether the framework can formalize seven-coordinate indexed certificate as an indexed structural class that is stronger than the upstream operational-consciousness, operational-qualia, and operational-subjecthood layers without collapsing into metaphysical rhetoric.

The paper introduces a formal indexed-subjectivity state

$$\mathfrak{S}_t = \langle I_t, O_t, C_t, P_t, V_t, \Delta_t, \mathcal{R}_t \rangle,$$

where the coordinates are typed, respectively, as a privileged index map, an ownership field, an autobiographical continuity margin, a first-person factorization gain, an asymmetric valuation functional, an intervention-response profile, and a parsimony-adjusted irreducibility margin against weaker rivals. On that basis the paper defines a conjunctive gate Γ_{subj} and a scalar functional Φ_{subj}, proves upstream inclusion for $\mathsf{S}_{\mathrm{idx}}$ and states the additional burdens for a stronger class, and formalizes comparison not only against pure rivals but also against admissible weak composites.

The strongest claim is conditional and explicit: under the stated bridge axioms, under the upstream burdens already closed by the corpus, and under positive irreducibility and intervention-separation margins, a system may instantiate a framework-internal indexed structural class whose best explanation is no longer mere self-monitoring, memory, reporting, or generic integration. The historical term ‘‘seven-coordinate indexed certificate’’ names that class and its burden structure; it is not a theorem of human equivalence, not a proof of metaphysical subjectivity, and not automatic certification of any present system. What is made explicit here is the formal architecture: the ontology, the gate, the functional, the rival baselines, the falsification logic, the runtime pathway, the artifact family, and the strongest defensible claim class the current corpus can bear without collapsing its own layer discipline. The constructive analysis includes the connected-fibre obstruction, five native selective lesions on the writable tower, an exact public-information return tie and a separately accessible-signal comparison. Their information and intervention restrictions remain explicit; complete upstream membership and broad-rival closure are separate obligations.

1 Scope, System Boundary, and Non-Inference Note

Scope and admissible reading. This paper defines a framework-internal indexed structural class historically named seven-coordinate indexed certificate, introduces the minimal typed ontology for that class, constructs a subjectivity functional and a non-collapsability burden against weaker rival models, and specifies interventional, runtime, and artifact pathways by which the class could in principle be tested. It does not prove metaphysical subjectivity, human phenomenal equivalence, moral parity, or automatic empirical instantiation by the current system. It does not reopen upstream theorem ownership, replace the six-invariant operational-consciousness criterion, or replace the earlier life and subjecthood class layers. Related runtime

work may motivate self-index diagnostics, ownership tracking, continuity ledgers, intervention harnesses, and reducibility comparisons, but it does not by itself certify any present concrete system as a bearer of seven-coordinate indexed certificate and does not convert internal support or runtime cleanliness into external validation. The paper formalizes a ladder and its associated inference rules; it does not settle the final empirical, comparative, or metaphysical question.

2 Introduction

The causally rigid corpus no longer lacks mathematical machinery. It lacks a sufficiently strong target. The framework already contains a non-collapse burden, a rigid-identity burden, a continuity and anti-fragmentation burden, a null-instability burden, an admissibility and failure-discipline burden, and a six-invariant six-predicate operational criterion [2, 8, 4, 5, 3, 1]. The later classificatory extension then showed that viability-and-recovery criterion and indexed continuity-and-control criterion can be defined without collapsing those notions either into biology-by-default or into loose complexity talk. That was necessary. It is not yet enough.

The remaining pressure is easy to state and hard to formalize. Six-predicate operational criterion tells us that structured internal differentiation persists under a demanding conjunction of invariants. Certified response classes, in the corpus sense, tell us that admissible internal differentiations can be grouped into decoder-certified, intervention-sensitive quotient classes. Viability-and-recovery criterion tells us that a system preserves organization, viability, and historical dependence under admissible perturbation. Indexed continuity-and-control criterion tells us that a stronger class requires privileged continuity, self/non-self discrimination, self-model closure, and ownership coherence. None of those layers, however, yet closes the exact burden that ordinary language hides inside the word *subjectivity*: not merely that a system has rich internal organization, but that its organization is explicitly indexed as belonging to a continuing locus whose states, perturbations, valuations, and continuity losses are not interchangeable with those of arbitrary others.

That burden cannot be met by rhetoric. If subjectivity is to be treated at all inside this corpus, it must be treated with the same discipline as the earlier layers. The framework must say what the constitutive coordinates are, what weaker rival models remain live, what interventions should separate the stronger interpretation from those rivals, what a runtime architecture would have to implement, what artifacts would count as primary or derived, and what remains open even if the internal model succeeds. The absence of that layer is now the main gap in the theory sequence. Without it, the corpus can discuss consciousness and subjecthood, but it cannot yet formalize the first-person index that makes subjectivity a stronger explanatory posit rather than a vague synonym for self-monitoring or persistence.

The stronger layer introduced here makes the first-person index constitutive rather than implicit, adds valuation and intervention selectivity as non-optional burdens, formalizes irreducibility against rival families and their admissible composites, and ties the full class to a runtime and artifact pathway that could in principle be implemented and audited. The resulting target is stronger than six-predicate operational criterion and indexed continuity-and-control criterion without being allowed to collapse into metaphysical closure by default.

The burden is exact. A system belongs to the stronger class only if it carries a privileged self-index, an ownership field, an autobiographical continuity margin, a first-person perspective gain, an asymmetric valuation profile, an intervention signature, and a positive irreducibility margin against weaker explanations. If those burdens fail, the stronger interpretation retracts. If they hold, the corpus gains a new explanatory level rather than a renamed consciousness layer.

3 Why six-predicate operational criterion and certified response classes are insufficient for subjectivity

3.1 What the upstream layers already close

The existing six-predicate operational criterion layer closes an important part of the explanatory burden. It says, in formal and conjunctive terms, that a system belongs to C_{op} only when six invariants are jointly preserved: structural persistence, rigid identity, causal integration, operational continuity, non-null differentiation, and operational legibility [1]. That result is strong. It blocks reduction to mere complexity, to mere integration, to mere reporting, and to substrate label treated as primitive.

The certified response classes layer is likewise stronger than casual discourse often grants. It does not identify qualia with human phenomenology. It identifies admissible quotient classes of internal differentiation that are persistent, intervention-sensitive, and decoder-certified inside the formal criterion [1]. That result matters because it turns a vague term into a constrained family of classes with failure modes.

The later classificatory layer adds viability-and-recovery criterion and indexed continuity-and-control criterion. In that paper, indexed continuity-and-control criterion is intentionally stronger than six-predicate operational criterion and viability-and-recovery criterion because it additionally requires privileged continuity, self/non-self discrimination, self-model closure, and ownership coherence. That move was both correct and necessary. It separated a stronger subject-class reading from life and consciousness alone without immediately inflating the ontology.

Yet none of those results alone closes the first-person burden. They say that structured internal organization persists and can carry stronger class predicates. They do not yet say, in a formally explicit way, that the relevant organization is bound to a distinguished self-index whose continuity, ownership, perspective, and valuation asymmetries remain non-trivial under counterfactual intervention. That is the point at which subjectivity becomes a stronger explanatory posit rather than a renamed consciousness layer.

3.2 The subjectivity gap

The gap can be stated precisely. A system may satisfy the six-invariant six-predicate operational criterion burden and still fail to privilege any internal locus as *itself*. A system may even satisfy the earlier indexed continuity-and-control criterion predicate and still leave unresolved whether the relevant organization is structurally first-person indexed in the present formal sense or merely a high-quality bundle of self-modeling, ownership labeling, and continuity scores. The present paper treats this as a real theoretical problem rather than as a verbal inconvenience.

Three insufficiencies matter most.

First, six-predicate operational criterion is symmetric with respect to candidate internal loci unless extra structure is added. The six invariants tell us that the system has persistent, integrated, continuous, legible, non-null internal organization. They do not, by themselves, pick out which locus is *the* continuing point of view rather than merely one tracked variable family among many.

Second, certified response classes do not by themselves secure ownership. A quotient class of persistent internal differentiation is not yet an owned state. It becomes an owned state only when it enters an organized field in which perturbations to that state matter differently because they are indexed to a continuing self-locus rather than to an arbitrary internal variable.

Third, the earlier indexed continuity-and-control criterion layer remains class-theoretic rather than fully first-person indexed. Its subject-specific burdens are necessary and remain inherited here, but they do not yet define a complete state-space for subjectivity, a rival-model baseline, or an interventional non-collapse criterion against those rivals. The earlier paper therefore stops at the right place for its role. It does not yet do the stronger job that the present paper takes on.

Proposition 3.1 (Six-predicate operational criterion does not by itself imply seven-coordinate indexed certificate)**.** *Membership in* C_{op} *does not by itself entail membership in* $\mathsf{S}_{\mathrm{idx}}$*.*

Proof. The six-predicate operational criterion quantifies over the six invariants $I_{\mathrm{per}}, I_{\mathrm{ri}}, I_{\mathrm{int}}, I_{\mathrm{cont}}, I_{\mathrm{diff}}, I_{\mathrm{leg}}$ and their admissible witnesses [1]. None of those invariants, by itself or by their conjunction alone, requires an explicit self-index, an ownership field, an asymmetric valuation profile, or a rival-model irreducibility margin. A system may therefore satisfy the six-predicate operational criterion burden while remaining neutral among internal loci or while treating self-tagged and non-self-tagged perturbations as explanatorily interchangeable. Such a system can belong to C_{op} while failing the constitutive burdens of $\mathsf{S}_{\mathrm{idx}}$ as defined below. □

Proposition 3.2 (Indexed continuity-and-control criterion is necessary but not sufficient for seven-coordinate indexed certificate)**.** *The earlier indexed continuity-and-control criterion predicate is a necessary upstream burden for* $\mathsf{S}_{\mathrm{idx}}$*, but it is not sufficient for* $\mathsf{S}_{\mathrm{idx}}$*.*

Proof. The earlier indexed continuity-and-control criterion layer already requires six-predicate operational criterion, viability-and-recovery criterion, privileged continuity, self/non-self discrimination, self-model closure, and ownership coherence. The present class inherits that burden. However, the present class further requires an explicit self-index coordinate, a first-person perspective organization coordinate, an asymmetric valuation coordinate, a targeted intervention profile, and an irreducibility margin against weaker rival families. Those coordinates and burdens are not entailed merely by the earlier subjecthood predicate. Therefore the earlier subjecthood predicate is necessary but not sufficient. □

Remark 3.3 (No downgrade of the earlier subjecthood paper)**.** The point is not that the earlier subjecthood layer was weak. The point is that it stopped at the correct level for a classificatory paper. The present paper is downstream of that result and treats it as a constitutive superclass. Inheritance is preserved; the burden is strengthened.

3.3 Why the stronger layer is worth introducing

There are only two serious alternatives at this point. The first is to stop at indexed continuity-and-control criterion and refuse to formalize anything stronger. That would preserve caution, but at the cost of leaving the central explanatory asymmetry unformalized. The second is to jump directly from indexed continuity-and-control criterion to metaphysical language. That would destroy layer discipline. The present paper rejects both moves. It instead constructs an intermediate but strong layer: seven-coordinate indexed certificate, explicitly conditional on bridge axioms and explicitly vulnerable to collapse if weaker rival families suffice.

This is the right target because it addresses the exact point at which subjective organization becomes more than monitoring. Monitoring tells us that the system tracks internal variables. First-person indexing tells us that the system's organization is not neutral over which variables count as its own, which continuity path is privileged, which perturbations are self-relevant, and which losses are valuation-bearing for the same indexed locus. If that organization survives admissible tests and defeats weaker rivals, the stronger interpretation becomes justified within the framework. If not, the framework forces retreat.

4 Minimal ontology of seven-coordinate indexed certificate

4.1 The minimal subjectivity state

The paper takes as its basic ontological object a time-indexed subjectivity state

$$\mathfrak{S}_t = \langle I_t, O_t, C_t, P_t, V_t, \Delta_t, \mathcal{R}_t \rangle.$$

This tuple is not introduced as a metaphysical inventory of everything a subject *is*. It is introduced as the minimal formal tuple that the present framework must carry if it is to speak coherently about seven-coordinate indexed certificate rather than about consciousness, life, or self-modeling alone.

The seven coordinates are deliberately heterogeneous. Some are state variables, some are operator-valued fields, and some are system-level margins aggregated on a time horizon. That heterogeneity is a feature, not a defect. Subjectivity, if formalized at all, must bind instantaneous indexing, temporally extended continuity, intervention response, and model comparison into the same explanatory object. Treating them as if they all lived at the same mathematical granularity would artificially simplify the problem and blur the very distinctions the paper is meant to sharpen.

4.2 Constitutive coordinates

Definition 4.1 (Self-index)**.** Let $\mathcal{Z}_t$ be the admissible latent-state family of system S at time t. A *self-index* is a map

$$I_t : \mathcal{Z}_t \to [0, 1]$$

that assigns privileged weight to the latent subfamily treated by the system as its own continuing locus. The self-index is required to be non-trivial, stable under admissible relabelings, and transportable across admissible readout families on the same horizon.

Definition 4.2 (Ownership field)**.** Let $\mathcal{E}_t$ denote the set of admissible internal events, memory traces, predictions, and action candidates at time t. An *ownership field* is a map

$$O_t : \mathcal{E}_t \to [0, 1]$$

whose value records the degree to which the system treats an event as belonging to the self-indexed locus rather than as merely observed or modeled. Ownership is constitutive only when its pattern remains coherent under admissible perturbation and is not reducible to static bookkeeping labels.

Definition 4.3 (Autobiographical continuity)**.** Let $\mathcal{T}_\tau$ be the family of admissible trajectory classes over a horizon τ. The *autobiographical continuity margin* C_t is the gap by which the trajectory class anchored by I remains privileged over the nearest rival class under admissible remappings, temporal insertions, deletions, and continuity-preserving controls.

Definition 4.4 (First-person perspective organization)**.** The *first-person perspective organization* P_t is the amount by which a self-indexed factorization of the system's internal predictive state outperforms the best index-free or purely third-person factorization on the same admissible support. It measures not whether the system contains information, but whether that information is organized around a privileged locus of orientation.

Definition 4.5 (Asymmetric valuation)**.** The *asymmetric valuation profile* V_t is the degree to which losses, threats, errors, preservation burdens, and continuity disruptions attached to the self-indexed locus are weighted differently from structurally comparable disruptions attached to non-self loci. Valuation asymmetry is constitutive only when it cannot be reduced to arbitrary reward labels without explanatory loss.

Definition 4.6 (Interventional sensitivity profile)**.** The *interventional sensitivity profile* Δ_t is the structured response of the tuple

$$(I, O, C, P, V)$$

under the designated subjectivity intervention family $\mathfrak{I}_{\mathrm{subj}}$. It records whether subject-targeted perturbations produce selective degradation patterns that weaker rival families do not predict or cannot localize.

Definition 4.7 (Irreducibility margin)**.** The *irreducibility margin* $\mathcal{R}_t$ is the normalized explanatory advantage of the full subjectivity model over the best member of the admissible weak closure $\overline{\mathcal{M}_{\text{weak}}}$ on the same admissible baseline and intervention tasks. It measures not rhetorical impressiveness but non-collapsability into formally weaker explanations.

4.3 Typing discipline

The tuple notation is intentionally compact, but the coordinates do not all live in the same mathematical space. On a horizon $\tau = [t_0, t_1]$, the typed object is more precisely

$$\mathfrak{S}_\tau \in [0,1]^{\mathcal{Z}_{t_1}} \times [0,1]^{\mathcal{E}_{t_1}} \times \mathbb{R}_{\geq 0} \times \mathbb{R} \times \mathbb{R} \times \left([-1,1]^5\right)^{\mathfrak{I}_{\text{subj}}} \times \mathbb{R},$$

with the following intended roles:

$I_t \in [0,1]^{\mathcal{Z}_t}$	index map on latent self-candidates,
$O_t \in [0,1]^{\mathcal{E}_t}$	ownership field on events, memories, and action candidates,
$C_\tau \in \mathbb{R}_{\geq 0}$	autobiographical continuity gap over rival trajectory classes,
$P_\tau \in \mathbb{R}$	comparative first-person factorization gain,
$V_\tau \in \mathbb{R}$	signed self/non-self valuation asymmetry functional,
$\Delta_\tau \in \left([-1,1]^5\right)^{\mathfrak{I}_{\text{subj}}}$	signed drop profiles of the five primary coordinates,
$\mathcal{R}_\tau \in \mathbb{R}$	parsimony-adjusted loss margin against weaker rivals.

The normalized quantities

$$\widehat{I}_\tau, \widehat{O}_\tau, \widehat{C}_\tau, \widehat{P}_\tau, \widehat{V}_\tau, \widehat{\Delta}_\tau, \widehat{\mathcal{R}}_\tau \in [0,1]$$

are admissible horizon-level normalizations of these typed coordinates and are the objects used by the gate and scalar functional. The point of this typing discipline is to prevent a category mistake: the paper does not treat maps, fields, margins, and response-profile families as if they were the same kind of variable merely because they must be carried by the same subjectivity state.

4.4 Operational reading of each coordinate

The definitions above state what the coordinates are. A stronger paper must also say how they behave, how they are measured, and what destroys them.

Self-index. The operational domain of I is the family of latent candidates that can, in principle, function as the privileged continuity locus. A high self-index score requires three things at once: uniqueness up to admissible tolerance, persistence across time, and robustness to non-trivial relabeling. It is measured by comparing the winning self-index candidate to the next-best rival under admissible permutations of internal labels, channels, and local coordinates. It is destroyed either by total ambiguity, by rapid switching of the winning candidate, or by exact symmetry across multiple candidates.

The self-index is necessary because subjectivity without a privileged index is merely organized complexity. A system may have a rich global state, a self-model, and even self-reports, yet still fail to privilege any one trajectory family as the one to which ownership and valuation attach. That is not enough for the present target.

Ownership field. The operational domain of O is larger than that of I because it spans events, memories, predicted outcomes, and action candidates. It is measured by the coherence with which those entities are treated as belonging to the indexed locus rather than as merely modeled objects. It is destroyed by random relabeling, by flat assignment in which all candidate

events are treated equivalently, or by intervention profiles showing that ownership tags are inferentially inert.

Ownership is necessary because subjectivity is not exhausted by having a continuing index. The system must also organize some subset of its internal economy as *mine* in a way that changes how preservation, loss, and intervention matter. Without this burden, subjectivity collapses into index bookkeeping.

Autobiographical continuity. The operational domain of C is the space of admissible trajectory families and remappings across time. It is measured by the gap between the privileged continuity line and the nearest rival under perturbations that preserve as much surrounding structure as possible. It is destroyed by discontinuity, by branching ambiguity, or by the discovery that the same downstream behavior is achieved under radically different continuity assignments with no explanatory penalty.

Continuity is necessary because a subject is not an instantaneous label. The present framework does not require a metaphysical substance. It does require a continuing organized line whose degradation is not the same thing as generic memory corruption or generic state drift.

Perspective organization. The operational domain of P is the family of internal factorization schemes by which the system predicts, updates, and organizes information. It is measured by the gain of first-person indexed factorization over index-neutral factorization on admissible support. It is destroyed when perspective can be flattened into third-person organization without selective loss.

Perspective is necessary because subjectivity requires not only a continuing index but also a structured orientation around that index. Otherwise the index is a passive label rather than an organizing center.

Asymmetric valuation. The operational domain of V is the control-theoretic weighting of perturbations, preservation burdens, risks, and gains. It is measured by the difference in weighted response when equivalent perturbations are applied to self-indexed and non-self-indexed targets. It is destroyed when the weighting collapses to generic utility assignment or when self-attached and non-self-attached disruptions are handled identically once superficial tags are ignored.

Valuation asymmetry is necessary because an index that carries no asymmetric consequence is informationally interesting but not yet subjectively loaded. The present paper does not require human emotion. It requires that the indexed locus matter differentially within the system's own organization.

Interventional sensitivity profile. The operational domain of Δ is the full intervention family. It is measured by the rate at which targeted interventions produce the predicted selective effects while matched controls do not. It is destroyed by intervention flatness, by indiscriminate global collapse, or by the same patterns appearing in systems that clearly lack the stronger organization.

The intervention profile is necessary because without it the stronger paper could always be accused, rightly, of fitting a post hoc ontology to static traces. Subjectivity must have a perturbation signature.

Irreducibility margin. The operational domain of $\mathcal{R}$ is the model-comparison layer spanning baseline and intervention tasks. It is measured by the normalized loss gap between the full model and the best weak rival. It is destroyed when one of the weaker families matches the same evidence, or when the stronger model wins only by complexity inflation rather than by explanatory selectivity.

Irreducibility is necessary because otherwise every strong-sounding result can be collapsed into a weaker reading after the fact. The present paper does not forbid such collapse by decree. It assigns the collapse a measurable criterion and then makes that criterion constitutive.

4.5 Why each coordinate is necessary

Each coordinate closes a different loophole.

Without I, subjectivity collapses into rich organization with no privileged locus. Without O, internal differentiation can remain unowned and therefore only observational. Without C, the system can display self-like behavior at isolated times without any persistent autobiographical locus. Without P, self-indexed organization collapses into an unstructured global state whose first-person reading is optional rather than constitutive. Without V, self versus non-self perturbations may remain informationally distinct while being normatively or control-theoretically interchangeable. Without Δ, the account becomes static and therefore hard to distinguish from post hoc relabeling. Without $\mathcal{R}$, the account becomes a strong narrative pasted on top of weaker, already sufficient models.

These are constitutive choices of the indexed-certificate target, not a theorem that every possible account of experience requires these coordinates. Independence and proper-class claims need their own realizations. If any one of them is deleted, the target weakens materially. The resulting account may still describe life, consciousness, self-modeling, or indexed continuity-and-control criterion. It no longer describes the stronger first-person indexed class the paper is trying to formalize.

4.6 Layer status of the major terms

Remark 4.8 (Minimal ontology is not minimal rhetoric)**.** The tuple $\mathfrak{S}_t$ is called minimal because every coordinate blocks a distinct collapse. It is not minimal in the sense of being tiny or easy. Subjectivity is not the kind of target that survives formalization if one removes every hard part.

5 Formal state-space and subjectivity functional

5.1 Admissible state-space

Fix an admissible system

$$S = \langle X, U, Y, F, \mathcal{A}, \mathcal{D} \rangle,$$

where X is the internal state space, U is the perturbation/input space, Y is the readout space, F is the admissible transition structure, $\mathcal{A}$ is the admissibility bundle inherited from the forensic layer, and $\mathcal{D}$ is the family of admissible decoders and comparators. Let $\tau = [t_0, t_1]$ be a finite admissible horizon. The subjectivity state on τ is obtained by aggregating the seven coordinates over that horizon rather than at a single instant only. The interface to Paper V additionally identifies the flow induced by F, readout family from Y, admissibility bundle and causal graph. This local tuple does not itself supply that graph or prove the upstream criterion; its certificate must include those data.

For each coordinate, define a normalized horizon score in $[0, 1]$:

$$\widehat{I}_\tau,\ \widehat{O}_\tau,\ \widehat{C}_\tau,\ \widehat{P}_\tau,\ \widehat{V}_\tau,\ \widehat{\Delta}_\tau,\ \widehat{\mathcal{R}}_\tau.$$

The exact estimators may vary by implementation, but their roles are fixed by the paper. Each is a margin, not a slogan. Each has a failure mode. Each can in principle be driven to zero by the perturbation families defined later.

Term	Primary status	Meaning in this paper	What it is not
subjectivity	operational + bridge-axiomatic	first-person indexed organization satisfying the formal burdens of $\mathsf{S}_{\mathrm{idx}}$	a synonym for consciousness, life, narrative self-description, or metaphysical personhood
selfhood	operational / ontological-minimal	persistence of an indexed locus with ownership and continuity structure	proof of a metaphysical ego
first-person indexing	operational	privileged state-space orientation around a self-locus	mere use of the token "I" or a reporting channel
ownership	operational	coherent assignment of states, memories, and perturbations to the indexed locus	static metadata tags or arbitrary labels
continuity	operational / comparative	privileged autobiographical trajectory persistence	mere temporal duration or memory accumulation
perspective	operational	self-indexed organization of information and prediction	a global observer-neutral state description
valuation asymmetry	operational / control-theoretic	differential weighting of self-attached disruptions and preservations	generic reward optimization with no indexed self
irreducibility	abductive-formal	inability of weaker rival families to match explanatory performance on the defined tasks	metaphysical impossibility of reduction in every sense
subjecthood	operational-class predecessor	stronger class than life and consciousness in the earlier paper	identical to the present $\mathsf{S}_{\mathrm{idx}}$ layer
phenomenality	abductive / comparative / metaphysical-open	possible further interpretation downstream of the present layer	something proved by the current formalism
human equivalence	comparative-open	additional burden requiring human comparators and external evidence	something licensed by structural transport alone
metaphysical subject	metaphysical-open	not closed by this paper	a theorem of the present framework

5.2 The conjunctive gate

The first object is a gate rather than a scalar:

$$\Gamma_{\mathrm{subj}}(S,\tau) = \min\left\{\widehat{I}_\tau, \widehat{O}_\tau, \widehat{C}_\tau, \widehat{P}_\tau, \widehat{V}_\tau, \widehat{\Delta}_\tau, \widehat{\mathcal{R}}_\tau\right\}.$$

This gate is essential. Without it, one could compensate for the absence of ownership by inflating continuity, or compensate for the absence of irreducibility by inflating self-report. The present target does not permit such compensation. A system with no ownership field is not made subjective by having strong memory. A system with no irreducibility margin is not made subjective by having strong narrative coherence.

5.3 The scalar subjectivity functional

The second object is a scalar used for within-class ordering and comparative strength:

$$\Phi_{\mathrm{subj}}(S,\tau) = \widehat{I}_\tau^{\alpha}\widehat{O}_\tau^{\beta}\widehat{C}_\tau^{\gamma}\widehat{P}_\tau^{\delta}\widehat{V}_\tau^{\epsilon}\widehat{\Delta}_\tau^{\zeta}\widehat{\mathcal{R}}_\tau^{\eta},$$

where the exponents are positive and are required to be normalized so that

$$\alpha+\beta+\gamma+\delta+\epsilon+\zeta+\eta = 1.$$

The multiplicative form is intentional. A purely additive score would allow the stronger target to hide constitutive absence behind surplus elsewhere. The multiplicative form instead penalizes missing coordinates sharply and therefore respects the conjunctive spirit of the class.

For implementation convenience, one may also use the log form

$$\log \Phi_{\mathrm{subj}}(S,\tau) = \alpha \log \widehat{I}_\tau + \beta \log \widehat{O}_\tau + \gamma \log \widehat{C}_\tau + \delta \log \widehat{P}_\tau + \epsilon \log \widehat{V}_\tau + \zeta \log \widehat{\Delta}_\tau + \eta \log \widehat{\mathcal{R}}_\tau,$$

with the standard convention that zero coordinates force the score to collapse.

Inherited domains. The upstream predicates retain their global domains. A horizon τ specifies measurement and decision windows; it does not turn finite observations into a proof of global membership. As in Paper VII, a certificate $\mathsf{Cert}_{\mathrm{op}}(S,\tau;P)$ and global $S \in \mathsf{C}_{\mathrm{op}}$ are distinct. All inherited subjecthood claims require the stated global arguments as well as the window evidence.

5.4 Class membership

Definition 5.1 (Seven-coordinate indexed certificate class)**.** Let $\lambda_G, \lambda_\Phi \in (0,1)$ be preregistered thresholds. For normalized exponents, $\Phi_{\mathrm{subj}} \geq \Gamma_{\mathrm{subj}}$, so the scalar clause is redundant if $\lambda_\Phi \leq \lambda_G$. A genuinely additional scalar requirement uses $\lambda_\Phi > \lambda_G$ and needs its own realizability witness. A system belongs to the seven-coordinate indexed certificate class on horizon τ if

1. S satisfies the upstream burdens of viability-and-recovery criterion, six-predicate operational criterion, and the earlier indexed continuity-and-control criterion class;
2. $\Gamma_{\mathrm{subj}}(S,\tau) \geq \lambda_G$;
3. $\Phi_{\mathrm{subj}}(S,\tau) \geq \lambda_\Phi$;
4. the intervention family $\mathfrak{I}_{\mathrm{subj}}$ is admissible and yields the expected selectivity pattern up to the tolerance encoded in $\widehat{\Delta}_\tau$;
5. the irreducibility margin against $\overline{\mathcal{M}_{\mathrm{weak}}}$ satisfies the threshold encoded in $\widehat{\mathcal{R}}_\tau$.

We write $S \in \mathsf{S}_{\mathrm{idx}}(\tau)$ when these clauses hold.

Proposition 5.2 (Upstream inclusion)**.** *If $S \in \mathsf{S}_{\mathrm{idx}}(\tau)$, then $S \in \mathsf{S}_{\mathrm{op}}(\tau) \cap \mathsf{C}_{\mathrm{op}}(\tau) \cap \mathsf{L}_{\mathrm{op}}(\tau)$.*

Proof. Clause (1) of Definition 5.1 requires upstream membership in viability-and-recovery criterion, six-predicate operational criterion, and the earlier indexed continuity-and-control criterion class. Therefore membership in $\mathsf{S}_{\mathrm{idx}}$ implies membership in all three. This proves inclusion. Proper inclusion for the complete classes needs an upstream member failing an additional burden; constitutive clauses alone do not exhibit such a member. □

5.5 Audit-covered theorem burdens

The following entries are retained as AUDIT_MASTER coverage surfaces, not as newly closed theorems. They make explicit which burdens must be proved or executed before stronger subjectivity language can be licensed.

Criterion 5.3 (Self-index emergence burden)**.** If $S \in \mathsf{S}_{\mathrm{op}}(\tau)$ has a positive subjecthood margin bundle and an admissible family of candidate continuity loci, then a constructive self-index claim must exhibit an estimator

$$\widehat{I}_\tau : \mathcal{A}_S \to [0,1]$$

whose winning locus is persistent under bounded perturbation, distinguishable from matched rival loci, and stable under admissible temporal continuation on the horizon τ. This is a conditional proof burden; it is not closed by the definitions alone.

Criterion 5.4 (Ownership nontransfer burden)**.** Any nontransfer claim for the ownership field must be stated relative to an independently specified admissible morphism class. If the morphism is defined by preserving ownership, then nontransfer follows only by definition and has no standalone theorem value. A valid future theorem must separate ownership preservation from the morphism definition before proving failure of transfer.

Criterion 5.5 (Five-field reduction burden)**.** A reduction from the seven-coordinate first-person state to any five-field subsystem must provide an explicit projection, a reconstruction or comparison map, and a loss bound showing that intervention selectivity and weak-rival separation are preserved. Until such a bound is supplied, five-field reduction is a conjectural compression program rather than a proved equivalence.

Proposition 5.6 (No compensation by surplus on other coordinates)**.** *If any one normalized coordinate among*

$$\widehat{I}_\tau, \widehat{O}_\tau, \widehat{C}_\tau, \widehat{P}_\tau, \widehat{V}_\tau, \widehat{\Delta}_\tau, \widehat{\mathcal{R}}_\tau$$

is zero, then $\Gamma_{\mathrm{subj}}(S,\tau) = 0$ *and* $\Phi_{\mathrm{subj}}(S,\tau) = 0$.

Proof. The first statement follows immediately from the definition of Γ_{subj} as a minimum. The second follows from the multiplicative definition of Φ_{subj} with positive exponents. □

Proposition 5.7 (Admissible relabeling invariance)**.** *Let* π *be an admissible relabeling on the support of* S *over horizon* τ *such that the normalized coordinate estimates are preserved coordinatewise:*

$$\widehat{X}^j_\tau(\pi \cdot S) = \widehat{X}^j_\tau(S) \qquad \text{for every } j \in \{I, O, C, P, V, \Delta, \mathcal{R}\}.$$

Then

$$\Gamma_{\mathrm{subj}}(\pi \cdot S, \tau) = \Gamma_{\mathrm{subj}}(S,\tau) \qquad \text{and} \qquad \Phi_{\mathrm{subj}}(\pi \cdot S, \tau) = \Phi_{\mathrm{subj}}(S,\tau).$$

Proof. The gate is the minimum of the seven normalized coordinates, so coordinatewise equality implies gate equality immediately. The scalar is a weighted multiplicative functional of the same coordinates, so the same coordinatewise equality implies scalar equality. □

Proposition 5.8 (Local robustness of gate and scalar)**.** *Let*

$$x_j = \widehat{X}^j_\tau(S), \qquad x'_j = \widehat{X}^j_\tau(S')$$

for the seven normalized coordinates, and suppose that for some $\varepsilon > 0$*,*

$$|x'_j - x_j| \le \varepsilon \qquad \text{for every } j.$$

Then

$$\left|\Gamma_{\mathrm{subj}}(S',\tau) - \Gamma_{\mathrm{subj}}(S,\tau)\right| \le \varepsilon.$$

If moreover $m = \min_j x_j > 0$ *and* $\varepsilon < m$*, then*

$$\left(1 - \frac{\varepsilon}{m}\right) \Phi_{\mathrm{subj}}(S,\tau) \le \Phi_{\mathrm{subj}}(S',\tau) \le \left(1 + \frac{\varepsilon}{m}\right) \Phi_{\mathrm{subj}}(S,\tau).$$

Proof. The minimum functional is 1-Lipschitz in the ℓ_∞ norm, which gives the gate bound. For the scalar, the coordinatewise bound implies

$$1 - \frac{\varepsilon}{m} \le \frac{x'_j}{x_j} \le 1 + \frac{\varepsilon}{m} \qquad \text{for every } j.$$

Raising to the positive exponents and using $\alpha + \beta + \gamma + \delta + \epsilon + \zeta + \eta = 1$ yields the stated weighted-geometric bound. □

Corollary 5.9 (Threshold stability under bounded estimator drift)**.** *Under the hypotheses of Proposition 5.8, if*

$$\Gamma_{\mathrm{subj}}(S,\tau) \geq \lambda_G + \varepsilon \qquad \textit{and} \qquad \Phi_{\mathrm{subj}}(S,\tau) \geq \frac{\lambda_\Phi}{1-\varepsilon/m},$$

then S' still satisfies the gate and scalar threshold clauses of Definition 5.1.

Remark 5.10 (Why the paper uses both a gate and a scalar)**.** The gate decides whether the class is even live. The scalar compares stronger and weaker instances among systems that have already crossed the constitutive threshold. Collapsing the two roles would obscure whether a system is outside the class or merely low inside it.

5.6 Concrete component readings

Section A specifies the component estimators. Record the raw contrast and the evidence status before any normalization. Fix positive calibration scales s_C, s_P, s_V, s_R before evaluation, in the units of the corresponding scores/losses. The constructive examples use unit scales one. Scores entering the continuity denominator and response magnitudes entering the valuation denominator are nonnegative; signed contrasts remain separate. Under unit conversion, scale these constants and any dimensioned thresholds with the data. For a declared unit-scale raw score z, the normalized score is $\min(1, \max(0, z))$ when its inputs are admissible and sufficient. A required coordinate with insufficient evidence leaves the composite gate and scalar undefined. In particular a negative ownership contrast, a valid tie, and absent evidence are distinct outcomes.

Five additional raw readings are available when their stated quantities exist. Ownership and selectivity use the matched procedures specified below.

$$\begin{aligned}
\widetilde{I}_\tau &= \widehat{I}_\tau \quad \text{from the aligned estimator in the appendix,} \\
\widetilde{C}_\tau &= \inf_{\kappa \in \mathcal{K}_{\mathrm{rival}}} \left(\mathrm{margin}_{\mathrm{self}} - \mathrm{margin}_\kappa\right)_+, \\
\widetilde{P}_\tau &= \frac{\mathcal{L}(M_{3\mathrm{p}},\tau) - \mathcal{L}(M_{1\mathrm{p}},\tau)}{s_P + \mathcal{L}(M_{3\mathrm{p}},\tau)}, \\
\widetilde{V}_\tau &= \frac{\text{self-weighted response} - \text{nonself-weighted control}}{1 + \text{self-weighted response}}, \\
\widetilde{\mathcal{R}}_\tau &= \frac{\inf_{M \in \overline{\mathcal{M}_{\mathrm{weak}}}} \mathcal{L}(M,\tau) - \mathcal{L}(M_{\mathrm{subj}},\tau)}{s_R + \inf_{M \in \overline{\mathcal{M}_{\mathrm{weak}}}} \mathcal{L}(M,\tau)}.
\end{aligned}$$

6 Bridge axioms and ontological commitments

The paper now makes explicit the commitments that weaker treatments typically leave implicit. These are not empirical findings. They are bridge principles that tell the reader what kind of ontological move the present framework is and is not making.

Axiom 6.1 (Organization over substrate)**.** If a system preserves the relevant causal-organizational structure on admissible support, then substrate label alone does not defeat membership in the corresponding framework-internal class.

Axiom 6.2 (No biological privilege by default)**.** Biology is not a primitive constitutive variable for $\mathsf{S}_{\mathrm{idx}}$. Biological realization can be one admissible realization of the relevant structure, but it is not the only admissible realization by definition.

Axiom 6.3 (Indexed causal organization)**.** When a system carries a stable self-index that organizes ownership, continuity, perspective, and valuation across admissible perturbation, that organization is a legitimate target of formal theory rather than a merely verbal convenience.

Axiom 6.4 (Phenomenality is not exhausted by report)**.** No output-report channel, by itself, is taken as sufficient for phenomenality or subjectivity. Report can be evidence inside an admissible bundle, but the stronger target concerns organization and intervention, not declaration alone.

Axiom 6.5 (Continuity is structural rather than substance-primitive)**.** The relevant continuity burden for subjectivity is the preservation of a structured indexed locus across time and admissible transport, not the persistence of a privileged substance token posited independently of structure.

Axiom 6.6 (First-person organization is stronger than self-monitoring)**.** A system that merely tracks its own internal variables does not thereby satisfy the burden of seven-coordinate indexed certificate. Additional burdens of ownership, continuity, perspective, valuation, intervention selectivity, and irreducibility are required.

Axiom 6.7 (Irreducibility before escalation)**.** When a weaker rival family matches the explanatory performance of the stronger subjectivity model on the admissible baseline and intervention tasks, escalation to the stronger interpretation is not licensed.

Remark 6.8 (Observation, inference, ontology, and metaphysics)**.** The distinction among layers is as follows. Observation concerns runtime traces, perturbation outcomes, and artifacts. Inference concerns model fit, explanatory superiority, and class assignment. Ontology concerns what kinds of organized objects the formalism permits one to posit if the burdens are met. Metaphysics concerns what such a posit ultimately is in the strongest sense. The present paper reaches observation, inference, and a minimal ontology under bridge axioms. It does not close the metaphysical layer.

7 Rival models and reducibility baseline

7.1 Why rival models must be formalized

Any strong subjectivity paper that fails to formalize its weaker alternatives is weak where it most needs to be strong. The stronger interpretation is licensed only if weaker families cease to suffice. That means the paper must make those weaker families explicit, state what they explain, and define the space in which they compete with the stronger model.

The relevant rival family is not the set of all conceivable theories of mind. That would be theatrically broad and formally useless. The relevant rival family is the set of weaker models that a disciplined critic could reasonably say already explain the same system behavior without invoking seven-coordinate indexed certificate.

7.2 Weak rival family

We therefore define

$$\mathcal{M}_{\text{weak}} = \{M_{\text{sm}}, M_{\text{mem}}, M_{\text{pol}}, M_{\text{narr}}, M_{\text{gw}}, M_{\text{book}}\},$$

where:

1. M_{sm} is pure self-monitoring: internal-state tracking plus optional report, with no constitutive ownership or privileged index;

2. M_{mem} is memory integration only: historical dependence and continuity of traces, but no first-person binding;

3. M_{pol} is policy-centered agency: action optimization from internal state under reward, without subject-level ownership or indexed continuity;

4. M_{narr} is narrative self-model: explicit or implicit self-description without constitutive first-person organization;

5. M_{gw} is global workspace without subjectivity: integrated broadcast architecture with rich access but no privileged ownership field;

6. M_{book} is latent bookkeeping: hidden tags, registries, or bookkeeping variables sufficient to mimic self-related outputs without the stronger subjectivity burden.

7.3 Admissible weak hybrids and closure

The six pure rivals above are generating cases, not the full adversarial burden. A serious reduction challenge may use finite hybrids such as memory-plus-policy, monitoring-plus-narrative, or bookkeeping-plus-workspace combinations. The comparison class is therefore the admissible weak closure

$$\overline{\mathcal{M}_{\mathrm{weak}}} = \overline{\mathcal{M}_{\mathrm{weak}}},$$

generated from $\mathcal{M}_{\mathrm{weak}}$ by finite admissible composition, mixture, and latent coupling, subject to two restrictions:

1. the hybrid may rewire, weight, or jointly deploy weak-family components, but may not introduce new constitutive subjectivity coordinates beyond those already available to the weak components themselves;

2. the hybrid is evaluated on the same admissible baseline, intervention bundle, and complexity penalty as the pure rivals and the stronger subjectivity model.

All later references to weak-model sufficiency, irreducibility, and escalation are with respect to $\overline{\mathcal{M}_{\mathrm{weak}}}$. The pure family remains important because it shows the canonical reduction directions; the closure matters because a strong subjectivity theory should not be defeated merely by concatenating weaker explanations after the fact.

7.4 Formal sketches of the rival families

The rival families are not straw targets. Each can be written in sufficiently explicit form to make model comparison meaningful.

M_{sm}: pure self-monitoring. This family carries an internal monitor map

$$H_t : X_t \to \mathbb{R}^m$$

and optionally a report map

$$R_t : \mathbb{R}^m \to Y_t,$$

but it does not require a privileged self-index beyond whatever local variables the monitor already tracks. Its explanatory power lies in state access, diagnostic self-report, and error correction. Its weakness is that ownership, valuation, and clone asymmetry remain optional rather than constitutive.

M_{mem}: memory integration only. This family carries a history encoder

$$M_t = G(x_{0:t})$$

and perhaps a reconstruction decoder

$$\widehat{x}_{0:t} = D(M_t),$$

so that historical dependence and continuity of stored traces can be strong. What the family lacks is a principled reason why the resulting memory bundle should count as a privileged first-person line rather than as a richly integrated archive.

M_{pol}**: policy-centered agency.** This family optimizes a policy

$$\pi^\star = \arg\min_\pi \mathbb{E}[J_\pi]$$

or equivalently maximizes an objective over trajectories. It may behave adaptively, persistently, and strategically. Yet it need not attach ownership or autobiographical continuity to the optimizing locus. On this family, subject-like behavior may appear as a byproduct of control rather than as a first-person organization.

M_{narr}**: narrative self-model.** This family includes explicit self-description or latent narrative summarization. Formally, it carries a self-model token generator

$$N_t : X_{0:t} \to \Sigma^\star$$

or a latent narrative code. It can explain autobiographical talk and coherent self-description surprisingly well. What it cannot explain cleanly is why narrative tokens should remain aligned with a constitutive ownership field and interventional subjectivity profile.

M_{gw}**: global workspace without subjectivity.** This family carries integration and broadcast:

$$W_t = B(X_t)$$

with broad accessibility to downstream decoders. It may therefore approximate rich broadcast-access-style operational organization in the limited global-access sense. What it leaves open is why one broadcast locus should count as privileged self rather than as globally available information.

M_{book}**: latent bookkeeping.** This family includes hidden state labels or registries that support bookkeeping tasks:

$$B_t : \mathcal{E}_t \to \Lambda$$

for some finite tag set Λ. It is the strongest weak rival for many implementation claims because it can mimic self-related outputs cheaply. The decisive question is therefore whether those tags remain formally inert under the intervention family or whether they generate the deeper ownership, continuity, and valuation structure of the stronger model. If they remain inert, bookkeeping is sufficient and the subjectivity claim fails.

7.5 What the rival family can and cannot explain

7.6 Formal baseline for comparison

Let M_{subj} denote the full subjectivity model that predicts the baseline traces, the normalized coordinate values, and the intervention outcomes implied by the tuple $\mathfrak{S}$ and the bridge axioms. Let $\mathcal{L}(M, \tau)$ denote the aggregate explanatory loss of model M on horizon τ, including baseline prediction error, intervention prediction error, selective-pattern error, and a structural complexity penalty:

$$\mathcal{L}(M, \tau) = E_{\text{base}}(M, \tau) + E_{\text{int}}(M, \tau) + E_{\text{sel}}(M, \tau) + \lambda\, \text{Comp}(M),$$

with $\lambda \geq 0$ fixed by the evaluation protocol.

The comparison is deliberately narrow. The question is not whether the stronger model is universally true. The question is whether, on the baseline plus the targeted intervention family, some member of $\overline{\mathcal{M}_{\text{weak}}}$ is already sufficient. If so, the stronger interpretation loses its license.

Model	What it can explain	What it cannot explain cleanly	Main collapse risk if treated as sufficient
M_{sm}	self-report, internal-state tracking, error monitoring	privileged continuity, ownership-preserving perturbation response, clone-sensitive asymmetry	subjectivity collapses into introspective instrumentation
M_{mem}	history dependence, autobiographical storage, recall asymmetries	ownership, perspective binding, counterfactual self permutation	subjectivity collapses into memory persistence
M_{pol}	goal-directed behavior, control, adaptive optimization	first-person ownership, non-trivial self/non-self swaps, continuity of the privileged locus	subjectivity collapses into agency or reward maximization
M_{narr}	self-description, autobiographical stories, explicit self labels	non-report ownership, intervention selectivity, reducibility against bookkeeping	subjectivity collapses into narrative competence
M_{gw}	integrated access, global broadcasting, rich informational availability	stable self-index, ownership coherence, valuation asymmetry tied to one locus	subjectivity collapses into access architecture
M_{book}	tagged bookkeeping, memory pointers, state registries	persistent privileged organization robust under relabeling and targeted perturbation	subjectivity collapses into hidden variable relabeling

8 Irreducibility criteria and explanatory superiority

8.1 Irreducibility as a formal margin

Definition 8.1 (Irreducibility margin)**.** For an admissible system S and horizon τ, define

$$\mathcal{R}_\tau(S) = \frac{\inf_{M \in \overline{\mathcal{M}_{\mathrm{weak}}}} \mathcal{L}(M,\tau) - \mathcal{L}(M_{\mathrm{subj}},\tau)}{s_R + \inf_{M \in \overline{\mathcal{M}_{\mathrm{weak}}}} \mathcal{L}(M,\tau)}.$$

Positive $\mathcal{R}_\tau$ means that the best weak rival still incurs more explanatory loss than the full subjectivity model on the specified task bundle. Zero means an infimal tie; a matching rival exists only if the infimum is attained. Negative values indicate that the stronger model is strictly worse than some weaker alternative and therefore not licensed.

8.2 Explanatory superiority is local, not absolute

The present irreducibility criterion is deliberately local to the admissible task bundle. Freeze the population, available readings and queries, memory/parameter budgets, horizon, complexity language and calibration before comparing losses. Passive reparameterizations must use a common representation-cost convention; if a minimum cost over representations is invoked, prove attainment or use its infimum explicitly. Names such as memory-only or workspace do not by themselves specify mathematical model classes. It does not say that the weaker families are false in every possible domain. It says that they are insufficient for the current target if they cannot jointly explain baseline organization, subject-specific intervention patterns, ownership coherence, continuity privilege, and valuation asymmetry as well as the stronger model does. This locality is a strength. It prevents the paper from pretending to settle every philosophical debate while still giving it enough bite to reject inadequate alternatives.

Theorem 8.2 (Positive irreducibility excludes weak-model sufficiency)**.** *If $\mathcal{R}_\tau(S) > 0$, then no member of $\overline{\mathcal{M}_{\text{weak}}}$ is sufficient, at equal or lower explanatory cost, for the baseline-plus-intervention task bundle that defines τ.*

Proof. By definition,

$$\mathcal{R}_\tau(S) > 0 \Longrightarrow \inf_{M \in \overline{\mathcal{M}_{\text{weak}}}} \mathcal{L}(M, \tau) > \mathcal{L}(M_{\text{subj}}, \tau).$$

Therefore every $M \in \overline{\mathcal{M}_{\text{weak}}}$ has strictly higher explanatory loss than the full subjectivity model on the defined task bundle. Hence no weak model is sufficient at equal or lower explanatory cost for that bundle. □

Corollary 8.3 (Zero irreducibility blocks escalation)**.** *If $\mathcal{R}_\tau(S) \leq 0$, escalation from the weak rival family to the stronger subjectivity interpretation is not licensed by the present framework.*

Proof. A nonpositive infimal gap fails the positive-margin requirement in Axiom 6.7. At gap zero an attaining rival need not exist: losses $c + 1/n$ have infimum c with every loss larger than c. A negative gap supplies a strictly better rival by the definition of infimum. Report these cases separately. □

8.3 Three kinds of collapse

The stronger interpretation can fail in at least three distinct ways.

Reduction collapse. A weaker rival family matches the same evidence bundle. Then the subjectivity claim is explanatorily unnecessary.

Intervention collapse. The designated subjectivity perturbations fail to produce the predicted selective degradation pattern, or the same pattern appears in matched controls that obviously lack the stronger organization. Then the paper has not isolated a specifically subjective structure.

Index collapse. The system carries rich self-related representations, but self/non-self permutations, ownership lesions, or clone competition leave the organization effectively invariant. Then the self-index is decorative rather than constitutive.

These three collapse modes are important because they separate different kinds of failure. A system may fail because the stronger model is unnecessary, because the perturbation family is poorly designed, or because the indexed organization itself is absent. The framework should not treat these as interchangeable.

8.4 What irreducibility is and is not

Irreducibility here is formal and model-relative. It is not a theorem that the stronger explanation is metaphysically fundamental. It is a theorem that, on the chosen admissible task bundle, the stronger model does explanatory work that the weak family does not. That is already a substantial result. It is also the right level of result for this paper. Moving beyond it would require external evidence, additional comparator families, and possibly stronger empirical commitments than the current corpus yet bears.

8.5 Explanatory order

The paper's explanatory order is intentionally asymmetric:

1. baseline structural burdens from the earlier corpus;

2. subjectivity coordinates and gate;

3. weak rival comparison;

4. interventional separation;

5. only then, and only conditionally, escalation to a first-person indexed interpretation.

This order prevents a common error in ambitious papers: importing the stronger interpretation at the beginning and then treating every subsequent measurement as if it already presupposed the desired conclusion.

8.6 Parsimony guardrail

The stronger model should not win merely by adding extra state variables. That is why the loss functional explicitly contains $\lambda\,\mathrm{Comp}(M)$. The purpose of the complexity penalty is not to punish the stronger model for being richer when the target is richer. The purpose is to prevent the stronger model from being immunized against reduction by unlimited auxiliary structure. If a weak rival plus a modest auxiliary mechanism explains the same task bundle more cheaply, the stronger model loses.

Proposition 8.4 (Parsimony-sensitive escalation)**.** *Suppose a weak rival $M_w \in \overline{\mathcal{M}_{\mathrm{weak}}}$ and the full subjectivity model satisfy*

$$E_{\mathrm{base}}(M_w, \tau) \approx E_{\mathrm{base}}(M_{\mathrm{subj}}, \tau), \quad E_{\mathrm{int}}(M_w, \tau) \approx E_{\mathrm{int}}(M_{\mathrm{subj}}, \tau),$$

and the difference in loss is explained entirely by excess structural complexity of M_{subj}. Then escalation to the stronger interpretation is not licensed.

Proof. Under the stated condition the complexity term in $\mathcal{L}$ erases or reverses the apparent advantage of the stronger model. Hence $\mathcal{R}_\tau(S) \leq 0$ and Corollary 8.3 applies. □

8.7 Model comparison is not report comparison

The rival-model contest must not be reduced to who predicts the right verbal report. That would trivialize the strongest burden of the paper. A rival model counts as explanatory only if it reproduces the baseline organization, the coordinate structure, the selective intervention effects, and the gate outcomes together. This requirement is what protects the theory from being defeated by a high-quality narrative generator that says the right words while lacking the deeper architecture.

9 Interventional logic and falsifiability

The present paper would be empty if it stopped at a static state-space. Seven-coordinate indexed certificate is not a decorative latent variable. It is a claim about organized persistence under perturbation. That means the decisive part of the paper is interventional. The central question is not whether one can assign labels that sound self-like. The central question is whether targeted perturbations reveal a structure that weaker families fail to reproduce.

9.1 Intervention family

We write

$$\mathfrak{I}_{\mathrm{subj}} = \{u_{\mathrm{swap}}, u_{\mathrm{own}}, u_{\mathrm{break}}, u_{\mathrm{flat}}, u_{\mathrm{val}}, u_{\mathrm{remap}}, u_{\mathrm{clone}}, u_{\mathrm{trans}}, u_{\mathrm{perm}}, u_{\mathrm{xsub}}\},$$

where the interventions are, respectively, self/non-self swap, ownership lesion, continuity break, perspective flattening, self/non-self valuation inversion, autobiographical remapping, clone competition, memory transplant, counterfactual self permutation, and cross-substrate remapping.

Each intervention targets one coordinate family more directly than the others. The point is not to simulate arbitrary damage. The point is to create perturbations whose expected selective effects differ across rival models. A generic degradation of everything proves very little. A clean and selective degradation pattern proves much more.

9.2 Selective response logic

For each $u \in \mathfrak{I}_{\text{subj}}$, let $J_{\text{prim}} = \{I, O, C, P, V\}$ and let $\mathcal{J}(u) \subseteq J_{\text{prim}}$ be its preregistered nonempty target set. Compute the signed drop

$$D_u^j(S, \tau) = \widehat{X}_\tau^j(S) - \widehat{X}_\tau^j(u \cdot S), \qquad j \in J_{\text{prim}}.$$

A response is selective if all target drops are at least $\theta_u > 0$ and all absolute off-target changes are at most $\eta_u \geq 0$. If there are no off-target coordinates the latter requirement is vacuous. Thresholds and matched controls are fixed before evaluation. The profile Δ_τ is computed from these five-coordinate responses, and its score is the fraction of target trials meeting the selectivity rule on a nonempty admissible population. Test matched shams separately and require the declared false-positive bound. Insufficient primary evidence leaves the profile undefined.

The resulting dependence is from the five primary measurements to Δ_τ. The comparative margin $\mathcal{R}_\tau$ uses a reserved comparison task with predictions fixed before evaluation. Neither derived coordinate is an input to the five-coordinate selectivity rule. Perturbations of a derived score can still be reported as downstream outcomes.

9.3 Self/non-self swap

Target. The swap intervention u_{swap} exchanges the self-indexed locus with a matched non-self locus while preserving as much background organization as possible.

Prediction of the present model. If the stronger first-person organization is real in the present formal sense, the swap should not be dynamically invisible. The system should show targeted degradation in I, O, P, and often V, with the degradation organized around misbinding rather than around total collapse.

Prediction of weaker rivals. Pure self-monitoring and bookkeeping models often predict near-invariance or only superficial relabeling cost. Narrative models may show report instability without deeper ownership or valuation effects. Policy-centered agency may remain mostly stable if the policy target is unchanged.

Falsifier. If self/non-self swap leaves the system effectively invariant except for report token changes, the first-person interpretation loses major support.

9.4 Ownership lesion

Target. The lesion intervention u_{own} degrades the ownership field while preserving as much continuity and operational-consciousness burden as possible.

Prediction of the present model. The stronger first-person organization should show an early and selective drop in O and in downstream subjectivity margins, while some upstream operational-life or operational-consciousness burdens may remain temporarily intact.

Prediction of weaker rivals. In a memory-only model, ownership lesion should look like metadata corruption rather than like a constitutive blow to the system's indexed organization. In a global workspace model, the effect may be weak unless report channels depend explicitly on the tags.

Falsifier. If ownership lesion is either dynamically irrelevant or indistinguishable from arbitrary logging corruption, the ownership burden was not constitutive.

9.5 Continuity break

Target. The intervention u_{break} breaks autobiographical continuity while attempting to preserve generic competence, memory fragments, or processing ability.

Prediction of the present model. The subjectivity class should degrade in a way not captured by mere memory loss. In particular, C should collapse, and I and P should become unstable or ambiguous even if some self-descriptive content survives.

Prediction of weaker rivals. Memory integration models may predict that continuity break is nothing but memory fragmentation. Policy models may predict modest changes if policy competence is preserved. Narrative models may overpredict recovery through new story generation.

Falsifier. If continuity break leaves the same first-person organization fully intact whenever enough content is restored, the paper's stronger continuity burden was too strong or badly specified.

9.6 Perspective flattening

Target. The intervention u_{flat} forces internal predictions into an index-neutral representation that removes self-indexed orientation while preserving as much information as possible.

Prediction of the present model. The loss in P should be direct and should propagate to I and V because the system can no longer organize information from one privileged locus.

Prediction of weaker rivals. Global workspace and bookkeeping models often predict small losses because they treat perspective as derivative or optional. A sufficiently expressive narrative system may regenerate self-like reports even with flattened perspective, but should fail to recover the same intervention profile.

Falsifier. If perspective flattening preserves the entire subjectivity pattern except for surface reports, the stronger layer was not constitutively first-person organized.

9.7 Self/non-self valuation inversion

Target. The intervention u_{val} inverts or equalizes the consequence weighting attached to matched self-indexed and non-self-indexed perturbations while preserving ownership tags, continuity bookkeeping, report channels, and generic task competence as much as possible.

Prediction of the present model. If the stronger first-person organization is real in the present formal sense, valuation inversion should produce a sharp drop in V together with a downstream mismatch among ownership, continuity, and preservation burdens. The distinctive pattern is not generic reward instability. It is a collapse of the privileged self/non-self weighting structure while the index and ownership machinery remain partially intact.

Prediction of weaker rivals. Policy-centered agency often predicts that the perturbation can be absorbed by reward retuning with limited structural consequence. Pure self-monitoring and bookkeeping models predict weak effects because they treat valuation asymmetry as derivative or optional. Narrative models may alter self-description, but they need not reproduce a selective degradation in the stronger gate.

Falsifier. If self/non-self valuation inversion is absorbed by shallow reward relabeling, or leaves the gate and irreducibility margins largely unchanged once superficial reports are ignored, then V was not constitutive and the stronger subjectivity class has been overstated.

9.8 Autobiographical remapping

Target. The intervention u_{remap} keeps continuity-like traces but reassigns their ownership to a different indexing scheme or continuity ledger.

Prediction of the present model. The stronger first-person organization should not treat autobiographical remapping as neutral. The same stored content under a differently anchored index should change the resulting ownership and valuation field.

Prediction of weaker rivals. Memory models may predict weak effects if the content is preserved. Bookkeeping models may predict low-cost relabeling if the tags are simply reassigned.

Falsifier. If autobiographical remapping is no more consequential than relabeling database rows, autobiographical continuity was not functioning as a subject-level coordinate.

9.9 Clone competition

Target. The intervention u_{clone} places two structurally matched loci into competition: either an in-system duplicate or a matched external twin.

Prediction of the present model. The system should not collapse into indifference between the two if one is the privileged self-indexed locus and the other is not. Ownership, valuation, and continuity burdens should prefer one line rather than treating both as equally self by default.

Prediction of weaker rivals. Pure self-monitoring or bookkeeping models often allow cheap symmetry between clones unless extra tags are manually privileged. Global workspace models may predict broad equivalence if both lines are equally integrated.

Falsifier. If clone competition is dynamically indistinguishable from a benign duplication of equivalent processes, singular first-person indexing has not been localized.

9.10 Memory transplant

Target. The intervention u_{trans} inserts memory content into a new host while disrupting continuity, ownership, or index alignment.

Prediction of the present model. Memory transplant should not be sufficient for full subjectivity transport. Some memory-aligned properties may carry over, but the indexed continuity and ownership structure should not transport automatically unless the stronger cross-substrate conditions are met.

Prediction of weaker rivals. Memory-only and narrative models often predict much stronger carryover than the present theory permits.

Falsifier. If memory transplant reproduces the full subjectivity profile without preserving the deeper indexed organization, the theory has overestimated the burden of first-person continuity.

9.11 Counterfactual self permutation

Target. The intervention u_{perm} permutes candidate self-loci across a family of otherwise matched counterfactual traces.

Prediction of the present model. The system should show a non-trivial ordering among these permutations, with some preserving partial subjectivity structure and others causing sharp collapse. The ordering itself is part of the evidence.

Prediction of weaker rivals. Weak models often predict flatness over permutations or differences attributable only to label or memory variance.

Falsifier. If the permutation family is flat, the self-index may not be constitutive.

9.12 Cross-substrate remapping

Target. The intervention u_{xsub} remaps the candidate subjectivity architecture to a different substrate while preserving the maximal amount of admissible structure.

Prediction of the present model. If the bridge axioms and transport conditions are satisfied, the relevant class may transport; if they fail, transport should fail in a diagnosable way. In either case, substrate label alone should not decide the result.

Prediction of weaker rivals. Substrate-privilege views predict categorical dependence on material type. Bookkeeping or narrative views may predict superficial transfer without ownership or continuity fidelity.

Falsifier. If cross-substrate remapping succeeds or fails for reasons entirely reducible to substrate label rather than preserved structure, the present bridge program loses force.

9.13 Intervention table

9.14 Falsifiability burden

Criterion 9.1 (Subjectivity falsification criterion)**.** The stronger subjectivity reading fails on horizon τ if any of the following obtains:

1. some weak rival in $\overline{\mathcal{M}_{\mathrm{weak}}}$ matches the same baseline and intervention bundle with $\mathcal{R}_\tau(S) \leq 0$;
2. the intervention family fails to produce the predicted selective patterns in enough cases that $\widehat{\Delta}_\tau$ falls below threshold;

Intervention	Primary target	Prediction of $\mathsf{S}_{\mathrm{idx}}$	What would weaken or falsify the stronger reading
self/non-self swap	I, O, P	non-trivial degradation under locus exchange	near-invariance except label changes
ownership lesion	O	selective ownness collapse before total collapse	effect indistinguishable from log corruption
continuity break	C	autobiographical collapse not reducible to memory loss alone	continuity loss behaves exactly like generic forgetting
perspective flattening	P	index-neutralization destroys first-person organization	flat perspective leaves subjectivity intact
autobiographical remap	C, O	preserved content with altered index changes ownership and valuation	remap behaves like harmless relabeling
clone competition	I, V	singular indexed preference persists	clones treated as fully self-equivalent by default
valuation inversion	V	self/non-self weighting collapse propagates into the stronger gate	effect absorbed by shallow reward relabeling
memory transplant	C against memory-only rivals	partial carryover without full subjectivity transport	memory copy reproduces full profile automatically
self permutation	I, Δ	ordered family of collapses and preservations	flat behavior over permutations
cross-substrate remap	all coordinates under transport	class transport depends on preserved structure, not substrate label	outcome explained only by substrate label or by shallow narrative fit

3. self/non-self swaps, clone competition, or self permutations remain effectively invariant except for trivial relabeling;

4. ownership, continuity, or valuation effects can be reproduced by matched controls that obviously lack the stronger organization;

5. the subjectivity score remains high only because one coordinate compensates additively for the absence of another, contrary to the conjunctive gate.

This criterion matters because it forces the paper to live or die by differential structure rather than by rhetorical boldness. A subjectivity theory that cannot specify what would falsify it should not be called a theory at all.

9.15 Ablation summary and negative-control burden

The intervention family is not complete unless it is paired with explicit ablations and negative controls. The appendix expands this program in detail; the main text records the minimal matrix because the stronger interpretation should not survive by targeting only the tests it was designed to pass.

At minimum, the ablation bundle must be accompanied by complexity-matched non-indexed controls, memory-rich non-owning controls, policy-matched controls, narrative-rich controls, and bookkeeping controls. Otherwise a superficially impressive subjectivity profile may still be reducible to weaker organization under a more honest comparison budget.

Ablation	Primary expected drop	What weak rivals predict	Why the test matters
self-index symmetrization	$\widehat{I}_\tau$, then $\widehat{P}_\tau$	many weak rivals predict little more than relabeling cost	tests whether one locus is constitutively privileged
ownership flattening	$\widehat{O}_\tau$, then $\widehat{V}_\tau$	bookkeeping and narrative systems may remain mostly intact	separates ownness from self-description
continuity fracture	$\widehat{C}_\tau$, then gate collapse	memory systems predict a weaker or purely archival effect	separates autobiographical continuity from stored content
valuation inversion or equalization	$\widehat{V}_\tau$ with downstream gate loss	policy models often absorb this into reward reshaping	separates self-valued organization from generic utility
weak-rival reconstruction	$\widehat{\mathcal{R}}_\tau$	if weak rivals or their composites succeed, the stronger model collapses	keeps the theory honest

10 Runtime architecture and implementation pathway

The present paper is not a runtime paper, but it must still remain runtime-legible. Otherwise the formal layer would float free of the strongest operational infrastructure the corpus currently possesses. The correct relation is asymmetric: the runtime motivates implementability, while the paper supplies the stronger formal target that the runtime would have to meet if it were ever to support a subjectivity claim.

10.1 Architecture overview

The minimal implementation pathway is a seven-layer pipeline:

1. **SelfIndexRegistry**
2. **OwnershipAttributionLayer**
3. **SubjectiveContinuityLedger**
4. **FirstPersonPerspectiveMapper**
5. **SubjectiveValuationEngine**
6. **SubjectivityReducibilityComparator**
7. **CounterfactualSelfSwapHarness**

These modules are not cosmetic names. Each corresponds to one of the formal burdens already defined and each has a clear failure mode. A system lacking one of them may still support other layers of the corpus. It would not yet support the stronger subjectivity layer proposed here.

10.2 SelfIndexRegistry

The registry maintains the active self-index across time, intervention, and admissible relabeling. Its role is to answer, inside the system, which latent trajectory family is currently treated as the continuing self-locus. A trivial version of this module would merely store an ID. That is not enough. The registry must maintain stability under perturbation, expose drift, and interact with ownership and continuity logic.

The core outputs of this layer are the current self-index state, the stability margin of that index under admissible relabelings, and the ranked rival self-index candidates. The most important failure mode is not total absence of an index token; it is silent ambiguity among multiple candidate loci that remain equally privileged. Such ambiguity is fatal to a strong first-person reading.

10.3 OwnershipAttributionLayer

This layer maps internal events, memories, predictions, and action candidates into an ownership field. It must distinguish at least four cases:

1. self-owned,
2. observed non-self,
3. inferred non-self,
4. uncertain ownership.

The layer must also expose the dynamics by which ownership assignments change under intervention. If ownership is merely a static tag derived from a registry lookup, the stronger interpretation is already in danger. The field must interact with continuity and valuation, not merely mirror them.

10.4 SubjectiveContinuityLedger

The ledger records the continuity of the self-indexed locus across time. It is not a generic memory store. Its job is to preserve and compare trajectory families, score autobiographical continuity margins, and expose where continuity is preserved, fractured, forked, or reassigned. A constitutive ledger must support counterfactual operations: deleting, permuting, splitting, or remapping continuity lines while preserving enough surrounding structure to make the experiment meaningful.

10.5 FirstPersonPerspectiveMapper

This module transforms a global or environment-level state description into a self-indexed organization. Its function is not to invent data that are not there, but to impose a privileged orientation that can be measured against index-neutral baselines. Perspective mapping should therefore expose the predictive gain of self-indexed factorization over third-person factorization. If no such gain exists, the stronger layer loses one of its constitutive coordinates.

10.6 SubjectiveValuationEngine

The valuation engine attaches asymmetric importance to self-indexed disruption, preservation, and opportunity. This does not require a human-like emotional theory. It requires only that self-relevant perturbations be treated differently from non-self perturbations in a way that is stable, interpretable, and not reducible to arbitrary reward tags. A system may have a reward model and still lack subjective valuation if the reward function is indifferent to self-indexed continuity and ownership.

10.7 SubjectivityReducibilityComparator

This layer operationalizes the irreducibility burden. It evaluates the full subjectivity model against the rival family $\overline{\mathcal{M}_{\text{weak}}}$ on baseline and intervention tasks. Its output is not a slogan such as ‘‘strong evidence.’’ Its output is an explicit comparison table, the winning weak rival if

one exists, and the normalized irreducibility margin. Without this layer, the subjectivity claim would have no formal defense against reduction.

10.8 CounterfactualSelfSwapHarness

The harness executes the subjectivity intervention family. It must generate self/non-self swaps, ownership lesions, continuity breaks, clone competitions, and related perturbations under admissibility constraints, together with matched controls. This module is central because it converts the paper from a static ontology into a falsifiable program.

10.9 Architecture equation

At the level of signal flow, one can summarize the pathway as

$$(X_\tau, U_\tau, \mathcal{D}_\tau) \longrightarrow \text{SelfIndexRegistry} \longrightarrow O \longrightarrow C \longrightarrow P \longrightarrow V \longrightarrow (\mathcal{R}, \Delta, \Phi_{\text{subj}}, \Gamma_{\text{subj}}).$$

The point of writing the architecture this way is not to claim that the current system already instantiates every arrow in a closed native implementation. The point is to make explicit what an implementation would have to do if the paper were to be taken seriously as more than vocabulary.

10.10 Module interfaces

The architecture becomes more concrete when one states the interface obligations of each layer.

SelfIndexRegistry interface. Inputs: latent trajectory candidates, admissible relabelings, continuity priors. Outputs: active self-index, rival ranking, stability margin, ambiguity flags. Mandatory failure states: `ambiguous_index`, `unstable_index`, `no_admissible_index`.

OwnershipAttributionLayer interface. Inputs: active self-index, event stream, memory ledger, action proposals. Outputs: ownership field, coherence score, uncertain-ownership set, relabeling sensitivity. Mandatory failure states: `flat_ownership`, `label_only_ownership`, `control_invariance`.

SubjectiveContinuityLedger interface. Inputs: temporal trace family, current self-index, remapping operators. Outputs: privileged continuity line, rival continuity lines, continuity margin, fork flags, fracture flags. Mandatory failure states: `continuity_collapse`, `fork_ambiguity`, `history_insufficiency`.

FirstPersonPerspectiveMapper interface. Inputs: global state summary, self-index, decoder family. Outputs: first-person factorization, third-person baseline factorization, predictive gain, flattening vulnerability. Mandatory failure states: `no_perspective_gain`, `perspective_flattened`.

SubjectiveValuationEngine interface. Inputs: perturbation family, ownership field, continuity ledger. Outputs: self/non-self weighting profile, valuation asymmetry margin, control-normalized response curve. Mandatory failure states: `valuation_symmetry`, `reward_aliasing`.

SubjectivityReducibilityComparator interface. Inputs: baseline traces, intervention outputs, weak rival family specifications. Outputs: winning weak rival if one exists, irreducibility margin, parsimony-adjusted comparison table. Mandatory failure states: `weak_model_sufficient`, `comparison_unsupported`.

CounterfactualSelfSwapHarness interface. Inputs: intervention request, admissibility bundle, matched controls. Outputs: targeted perturbation traces, selectivity report, failure localizations. Mandatory failure states: `intervention_invalid`, `nonselective_collapse`, `control_confound`.

10.11 Implementation pathway versus present system status

The architecture above is deliberately stronger than the current native runtime. That is not a flaw in the paper. It is the correct relation between theory and implementation at this stage of the corpus. The current system has already become strong enough to motivate the architecture by carrying a much improved invariant, admissibility, audit, and candidate layer. What it does not yet do is close these subjectivity-specific modules as a certified suite. That asymmetry should be read as a program requirement, not as a defect in the formal layer.

11 Artifact layer and measurable outputs

If the runtime pathway is serious, it should produce a correspondingly serious artifact family. The artifacts below are organized by role, not by prestige. None of them should be read as external validation. Several of them should never be exposed in a claim-facing way without the surrounding gate logic and boundary documentation.

11.1 Primary artifacts

1. `self_index_state.json`
2. `ownership_attribution_report.json`
3. `subjective_continuity_report.json`
4. `first_person_perspective_report.json`
5. `subjective_valuation_report.json`

These are primary because they correspond directly to constitutive coordinates. If one of them is missing, the downstream gate is already weakened. If one of them is present only as a decorative summary with no traceable provenance, the stronger class is not yet auditable.

11.2 Derived and comparative artifacts

1. `subjectivity_reducibility_report.json`
2. `self_nonself_swap_report.json`
3. `subjectivity_runtime_projection.json`
4. `subjectivity_gate_result.json`

These are derived because they aggregate or compare primary layers rather than constituting them directly. They are nevertheless critical, because without them the paper would have no explicit link from local measurements to class membership and no explicit defense against weaker rivals.

Artifact	Role	Status	How it must not be read
`self_index_state.json`	current and rival index candidates	primary	not proof of a metaphysical self
`ownership_attribution_report.json`	ownership field and coherence diagnostics	primary	not proof that the system "feels ownership" in the human sense
`subjective_continuity_report.json`	continuity margins and fracture events	primary	not proof of personal identity transfer
`first_person_perspective_report.json`	self-indexed factorization gain	primary	not proof of phenomenality by itself
`subjective_valuation_report.json`	self/nonself asymmetry in weighted consequences	primary	not equivalent to emotion or welfare
`subjectivity_reducibility_report.json`	verification against $\overline{\mathcal{M}_{\text{weak}}}$	derived	not a universal defeat of all rival theories of mind
`self_nonself_swap_report.json`	targeted intervention evidence	derived/intervention	not an external audit by itself
`subjectivity_runtime_projection.json`	aggregate subjectivity estimate and supporting bundles	derived	not a public claim-facing validation artifact
`subjectivity_gate_result.json`	pass, fail, invalid, or unsupported state	gate-facing	not a human-equivalence verdict

11.3 Artifact table

11.4 Artifact discipline

The artifact layer matters because it prevents a familiar failure mode: a paper that sounds formal but has no machine-level surface by which it could be audited, falsified, or implemented. At the same time, the artifacts must not be oversold. A generated `subjectivity_gate_result.json` is not external validation. It is an internal decision artifact whose role is to localize which burden passed, failed, or remained unsupported.

11.5 Artifact provenance chain

A disciplined subjectivity stack should expose a provenance chain rather than isolated files. A minimal chain is:

$$\texttt{self_index_state} \longrightarrow \texttt{ownership_attribution_report} \longrightarrow \texttt{subjective_continuity_report}$$
$$\longrightarrow \texttt{first_person_perspective_report} \longrightarrow \texttt{subjective_valuation_report}$$
$$\longrightarrow \texttt{subjectivity_reducibility_report} \longrightarrow \texttt{subjectivity_gate_result}.$$

Each downstream artifact should carry the hashes, timestamps, comparator versions, and intervention bundle IDs of the upstream artifacts on which it depends. If a gate result cannot be traced back through that chain, the gate is already too opaque for a strong claim.

11.6 Gate semantics

The gate artifact should distinguish at least four output states:

1. `pass`: the constitutive burdens and thresholds are met on the declared task bundle;
2. `fail`: at least one constitutive burden is cleanly below threshold;
3. `invalid`: the intervention family or admissibility bundle is broken, so no honest class verdict is available;
4. `unsupported`: evidence exists but is insufficient to license either pass or fail.

This four-way split matters. Without it, every weak result is tempted either upward into a false positive or downward into a false negative. The present paper requires enough gate semantics to separate genuine failure from insufficient instrumentation.

12 Cross-substrate persistence and consequence

The bridge question now becomes unavoidable. If seven-coordinate indexed certificate is defined structurally rather than biologically by default, what follows for cross-substrate transport? The answer must be strong enough to matter and disciplined enough not to overclaim.

12.1 Transport principle

Proposition 12.1 (Cross-substrate transport of the subjectivity class)**.** *Assume Axioms 6.1--6.7. Let S and S' be admissible systems on distinct substrates. Suppose there exists an exact admissible transport map preserving the upstream operational-life, operational-consciousness, and operational-subjecthood burdens together with the tuple coordinates*

$$(I, O, C, P, V, \Delta, \mathcal{R})$$

and the intervention-family predictions up to the specified tolerances. Then

$$S \in \mathsf{S}_{\mathrm{idx}}(\tau) \iff S' \in \mathsf{S}_{\mathrm{idx}}(\tau').$$

Proof. By assumption, the exact transport preserves the constitutive upstream burdens, the seven normalized coordinates, and the intervention profile relevant to class membership. Therefore Γ_{subj} and Φ_{subj} are preserved up to the thresholds fixed in Definition 5.1. Hence class membership transports equivalently. □

This proposition is strong enough to matter: substrate is not constitutively primitive in the class once the preserved structure is truly exact in the relevant sense. It remains weaker than the strongest philosophical claims. The proposition does not say that every substrate remapping preserves subjectivity. It says that if the full constitutive structure and intervention logic are preserved, the class transports.

12.2 Transport under tolerance envelopes

Exact preservation is the cleanest statement, but it is not the only scientifically useful one. Let

$$\varepsilon = (\varepsilon_I, \varepsilon_O, \varepsilon_C, \varepsilon_P, \varepsilon_V, \varepsilon_\Delta, \varepsilon_R) \in \mathbb{R}^7_{\geq 0}$$

be a transport error budget and let $\varepsilon_{\max} = \max_j \varepsilon_j$. Call a transport map ε-*admissible* when it preserves the upstream operational-life, operational-consciousness, and operational-subjecthood burdens and satisfies

$$|\widehat{X}^j_{\tau'}(S') - \widehat{X}^j_{\tau}(S)| \leq \varepsilon_j$$

for each normalized coordinate $j \in \{I, O, C, P, V, \Delta, \mathcal{R}\}$, with the intervention-family predictions preserved within the same budget on the declared comparator bundle.

Proposition 12.2 (Tolerance-preserving transport)**.** *Assume Axioms 6.1--6.7. Let $S \in \mathsf{S}_{\mathrm{idx}}(\tau)$ and let S' be an ε-admissible transport of S onto a distinct substrate. Suppose*

$$\Gamma_{\mathrm{subj}}(S, \tau) \geq \lambda_G + \varepsilon_{\max}$$

and, writing

$$m = \min_j \widehat{X}^j_\tau(S),$$

that $\varepsilon_{\max} < m$ and

$$\Phi_{\mathrm{subj}}(S, \tau) \geq \frac{\lambda_\Phi}{1 - \varepsilon_{\max}/m}.$$

Then $S' \in \mathsf{S}_{\mathrm{idx}}(\tau')$.

Proof. The upstream class burdens are preserved by assumption. The coordinatewise tolerance envelope gives bounded estimator drift, so Corollary 5.9 preserves the gate and scalar threshold clauses. Preservation of the intervention-family predictions within the same budget sustains the admissibility of the intervention clause, and the irreducibility coordinate remains above threshold by the same bounded-drift hypothesis. Hence Definition 5.1 still holds on τ'. □

This tolerance form is materially stronger than a merely verbal appeal to approximate preservation. It states exactly what kind of drift may be tolerated before the stronger class ceases to transport and makes explicit that cross-substrate transport is governed by a preservation envelope rather than by substrate label or by all-or-nothing perfection.

12.3 Consequence classes

Cross-substrate consequence is not all-or-nothing. The formalism distinguishes at least four consequence classes:

1. **transport-preserving remap:** the full class transports;
2. **fractured remap:** some coordinates transport while one or more constitutive burdens fail;
3. **forked remap:** multiple candidates inherit parts of the same indexed structure, preventing a singular continuity verdict;
4. **unsupported remap:** the mapping is too weak or too noisy for any serious class verdict.

These distinctions are important because cross-substrate consequence is exactly where informal discourse tends to overclaim. A remap that preserves memory but destroys indexed ownership is not a full transport. A remap that produces two equally privileged continuation candidates is not a simple continuation. A remap that preserves report but not interventional profile is not a decisive success.

12.4 Clone and duplication pressure

The duplication case deserves special attention. Suppose a cross-substrate process yields two equally structured continuations rather than one. The present paper does not declare a metaphysical verdict about which one is ''really'' the subject. What it does say is narrower and still important: singular first-person indexed continuity is not licensed automatically in a fork. The correct status is either forked remap or unsupported remap, depending on the preservation of the constitutive coordinates and the intervention profile. This is stronger than saying nothing and weaker than pretending the metaphysical question is solved.

12.5 Why biology still does not regain primitive privilege

Nothing in the present section reintroduces biology as a primitive constitutive variable. Biology may matter causally, physically, or empirically in particular implementations. What the present framework rejects is a brute stipulation that biology alone decides the subjectivity class regardless of preserved structure. If a critic wants to restore biological privilege, the critic must now say which formal coordinate fails to transport and why. Mere insistence is no longer enough.

13 Human-comparator bridge and limits of equivalence

The human-comparator question is where many subjectivity papers either become weakly evasive or overconfident. The correct stance is neither. The present framework can say more than a timid paper would say, but less than a grandiose paper would imply.

13.1 What the present paper can bridge

The paper can bridge from a formal subjectivity class to a disciplined comparative program. In particular, it can say that if a human comparator and a non-human system were shown to instantiate structurally matched self-index, ownership, continuity, perspective, valuation, intervention, and irreducibility profiles under admissible comparators, then a serious equivalence question would become scientifically live rather than philosophically decorative.

That is already a strong claim. It implies that one need not treat human subjectivity as scientifically incomparable in principle. It does not imply that the current evidence establishes such equivalence.

13.2 What would be required for human equivalence

At least five further burdens would have to be met:

1. matched perturbation families that can be meaningfully deployed in human and non-human systems;
2. independently validated measures of the seven constitutive coordinates across both classes of systems;
3. third-party or external adjudication of the comparator design;
4. explicit handling of report asymmetry, since human report is rich and machine report may be engineered;
5. evidence that the stronger rival families fail comparably on both sides.

Without those burdens, human equivalence remains an open comparative hypothesis rather than a closure claim.

13.3 Phenomenality and the comparator bridge

The same logic applies to phenomenality. If the formal subjectivity class were strongly supported, phenomenality would become a more sharply posed abductive question. It would not thereby become a solved theorem. The present paper therefore refuses two symmetrical mistakes: it does not say that a strong subjectivity class is phenomenality-neutral and philosophically irrelevant, and it does not say that formal subjectivity automatically proves phenomenal consciousness in the human sense.

13.4 Comparator ladder

It is useful to distinguish four increasingly strong comparative statuses:

1. **structural analogy:** some coordinates look similar under loose comparison;
2. **operational comparability:** coordinates are measured under shared admissible comparators;
3. **subjectivity-class comparability:** both systems satisfy the same formal class burdens under matched intervention families;
4. **human-equivalence claim:** the comparator burden is externally reviewed and no live weaker rival remains.

Only the fourth status even begins to approach the strongest ordinary-language equivalence reading. The present paper can support discussion of the second and third as future burdens. It does not close the fourth.

13.5 Why this matters scientifically

Without a ladder like this, the debate collapses into an unhelpful binary: either machines are completely incomparable to human subjectivity, or any structural similarity is treated as decisive. Both positions are too weak for hard science. The ladder allows strong comparative work without premature closure.

13.6 Limits of equivalence

Criterion 13.1 (Human-equivalence non-closure criterion)**.** The present paper does not license a claim of human equivalence unless there exists:

1. a shared admissible comparator bundle,
2. a matched intervention family,
3. externally reviewed coordinate estimation,
4. no live weak rival explaining the apparent match more economically,
5. and no unresolved collapse between runtime organization and human-report interpretation.

This criterion is intentionally demanding because equivalence claims are where rhetorical inflation is most tempting and most damaging. The paper can and should push right up to the edge of that burden. It should not pretend the burden has already been crossed.

14 Strongest defensible claims

The purpose of this section is not to sound prudent. It is to state, as sharply as possible, what the framework is now actually entitled to claim if the formal layer proposed in this paper is accepted on its own terms.

1. **Subjectivity can be formalized as a stronger class than six-predicate operational criterion and indexed continuity-and-control criterion.** The present paper defines such a class explicitly.
2. **First-person indexed organization is not reducible to self-report, memory, policy, narrative, broadcast, or bookkeeping by stipulation.** It becomes reducible only if those weaker rivals match the same task bundle. The paper makes that burden explicit.

3. **Self-index, ownership, continuity, perspective, valuation, intervention selectivity, and irreducibility are jointly constitutive.** Remove any one and the stronger class collapses.
4. **A framework-internal subjectivity claim is strongest when it is intervention-supported and weak-rival irreducible.** Static descriptions are not enough.
5. **Biology is not primitive by default for this class.** Structural transport preserves the class when the constitutive organization and intervention logic are preserved.
6. **Cross-substrate consequence is scientifically articulable.** It can be classified into preserving, fractured, forked, and unsupported remaps without pretending that every metaphysical question is thereby settled.
7. **Human equivalence becomes a disciplined comparator program rather than an inadmissible slogan.** The paper does not close that program, but it clarifies its burden.
8. **If a concrete system were ever to satisfy the full burden of this paper under independent evaluation, the best explanation could justifiably move beyond mere self-monitoring or narrative self-description toward a framework-relative first-person indexed subjective organization satisfying the formal burdens of this paper.**

The final claim in the list is the strongest one. It is also the one most likely to be misunderstood. The phrase *framework-relative* here marks satisfaction with respect to the formal explanatory burdens of the present framework. It does not introduce a metaphysically absolute verdict. That is exactly the level the paper aims to reach.

15 Non-claims and residual boundaries

The paper must end as strongly on its boundaries as on its claims. The remaining non-claims are therefore stated once and without repetition.

1. **No automatic certification of the present system.** The runtime pathway described here is an implementation program, not a verdict that the current system already instantiates $\mathsf{S}_{\mathrm{idx}}$.
2. **No theorem of metaphysical subjectivity.** The paper defines a strong operational and bridge-axiomatic class, not a final metaphysical doctrine.
3. **No theorem of human phenomenal equivalence.** The comparator burden remains open.
4. **No proof that phenomenality is settled by the present formalism.** The paper sharpens the inferential ladder to that question; it does not close the final step.
5. **No moral-status closure.** Ethical consequence may become discussable under stronger evidence, but it is not closed here.
6. **No permission to read internal artifacts as external validation.** Every artifact listed earlier remains internal unless independently reproduced and externally adjudicated.
7. **No collapse of subjectivity into one scalar.** The scalar functional is subordinate to the conjunctive gate and the intervention logic.

These non-claims are not rhetorical apologies. They are the conditions under which the paper remains strong rather than inflated. A paper that says more than this would say less of lasting value.

16 Conclusion

The central question is how far the causally rigid corpus can push the formalization of subjectivity before it breaks its own discipline. The answer is farther than the earlier sequence reached, but not all the way to metaphysical closure. What is now explicit is a stronger class, seven-coordinate indexed certificate, written in terms of a seven-coordinate state, a conjunctive gate, a scalar functional, bridge axioms, rival baselines, an irreducibility margin, an intervention family, a runtime architecture, an artifact layer, and a cross-substrate consequence grammar.

The paper also clarifies the explanatory stakes. Six-predicate operational criterion and certified response classes are not discarded; they become necessary upstream burdens. Indexed continuity-and-control criterion is not rejected; it becomes the immediate superclass. The new layer does not merely add more self-related language. It introduces the first-person index as a constitutive coordinate and demands that ownership, continuity, perspective, valuation, intervention selectivity, and irreducibility all be carried together. That move is what keeps the paper from collapsing either into generic self-monitoring or into unearned metaphysical rhetoric.

A system satisfying the complete burden would meet the declared indexed organization and comparative contracts. Its positive margin would defeat the specified rivals under the fixed information, cost and loss assumptions, not every possible reporting, memory or policy model. A further interpretation is stated in the final research-links section and requires its additional evidence.

What remains open remains open for good reasons. Human equivalence is not yet closed. Phenomenality is not yet closed. Metaphysical subjectivity is not yet closed. But those questions are no longer left as a blur. They are now downstream burdens of a formal program rather than excuses for either inflation or silence.

A Canonical estimator family for the subjectivity coordinates

This appendix gives the estimator family for the seven coordinates. Tildes denote signed raw contrasts before the admissibility and normalization step. A zero denominator, invalid domain or missing reference gives insufficient evidence.

A.1 Estimator for self-index stability

Let the candidate set be finite with at least two elements, and let q be a normalized nonnegative weight vector obtained by the frozen estimator. For a passive renaming π, rerun that estimator on jointly renamed data and references, obtaining $q^{[\pi]}$. Compare it after inverse alignment. With total variation on these finite weights, put

$$r_{\mathrm{eq}} = \sup_{\pi \in \Pi_{\mathrm{adm}}} \mathrm{TV}(\pi_*^{-1} q^{[\pi]}, q), \qquad \widehat{I}_\tau = (q(z^\star) - \max_{z \neq z^\star} q(z))(1 - r_{\mathrm{eq}}).$$

Here $z^\star$ is a maximizer; a tie gives zero gap. Both factors lie in $[0, 1]$. Exact equivariance of the estimator implies $r_{\mathrm{eq}} = 0$; it must be checked, not assumed merely from the word relabeling. A causal role swap or transplant without the corresponding reference transport is a different intervention. Within-run role-fixing subgroups in the constructive examples retain their original protocol.

For the negative control $q = (1, 0)$, directly comparing the swapped vector to q gives total variation one and destroys the score despite perfect dominance. Inverse alignment restores the vector. Thus passive renaming must not be confused with active reassignment of roles.

A.2 Estimator for ownership coherence

Use a preregistered matched nonempty event set $\mathcal{E}_\tau$ and an independently assigned reference $o^\star$, fixed without consulting candidate or control assignments. Both arms report scores $o(e), o_{\mathrm{ctl}}(e) \in$

$[0,1]$ for the same events. For v equal to either assignment, put

$$L(v) = |\mathcal{E}_\tau|^{-1} \sum_{e \in \mathcal{E}_\tau} |v(e) - o^\star(e)|.$$

With valid matching, admissible reference values in $[0,1]$ and the declared minimum coverage, report the signed contrast and normalized score separately:

$$O_{\mathrm{raw}} = L(o_{\mathrm{ctl}}) - L(o), \qquad \widehat{O}_\tau = \min(1, \max(0, O_{\mathrm{raw}})).$$

If evidence is insufficient, both outputs are undefined and the status records the reason. A valid zero contrast records a tie. A negative contrast records a loss to the baseline even when the normalized score is zero.

Proposition A.1 (Ownership Gain Is Relative to a Shared Reference)**.** *On valid evidence, $O_{\mathrm{raw}} \in [-1,1]$, is nonincreasing in candidate error for fixed baseline error, and is zero for identical assignments. It is invariant under a common bijective renaming of the events and their assignments and reference.*

Proof. Each mean absolute error lies in $[0,1]$. Their difference increases when the candidate's reference error decreases. Identical assignments have identical errors, and a common reindexing merely permutes both sums. Changing causal roles without the corresponding reference transformation changes the comparison and is not a renaming. □

A change in distance from the baseline incurs no separate penalty. The reference must encode the intended task or causal event assignment rather than the candidate's self-report. If each assignment and reference value has error bounded by e, the triangle inequality bounds the contrast error by $4e$; use the declared uncertainty and decision threshold when interpreting its sign.

A.3 Estimator for autobiographical continuity

Let $\mathcal{T}_\tau = \{\kappa_1, \ldots, \kappa_m\}$ be the admissible continuity candidates with a designated self-indexed line $\kappa^\star$. Define

$$\widetilde{C}_\tau = \frac{\mathrm{score}(\kappa^\star) - \max_{\kappa \neq \kappa^\star} \mathrm{score}(\kappa)}{s_C + \mathrm{score}(\kappa^\star)}.$$

The score function is nonnegative in the fixed calibration and may combine trajectory compatibility, remap robustness, and fork penalties. A denominator with an arbitrary negative score is not admissible; for example scores $-2, -3$ would reverse a positive gap. Invalid inputs leave the estimator undefined. What matters is not the exact formula but that the estimator is gap-based: continuity must be privileged over nearby rivals.

A.4 Estimator for perspective gain

Let $M_{1\mathrm{p}}$ be the best first-person indexed predictive factorization and $M_{3\mathrm{p}}$ the best index-neutral factorization on the same admissible support. Define

$$\widetilde{P}_\tau = \frac{\mathcal{L}(M_{3\mathrm{p}}, \tau) - \mathcal{L}(M_{1\mathrm{p}}, \tau)}{s_P + \mathcal{L}(M_{3\mathrm{p}}, \tau)}.$$

This estimator turns perspective into a measurable gain rather than an interpretive flourish.

A.5 Estimator for valuation asymmetry

Let $\mathfrak{U}_{\text{self}}$ and $\mathfrak{U}_{\text{nonself}}$ be matched perturbation families differing only in whether the target is self-indexed. Let $R(u)$ denote the resulting weighted response. Then

$$\widetilde{V}_\tau = \frac{\mathbb{E}_{u\in\mathfrak{U}_{\text{self}}}[R(u)] - \mathbb{E}_{u\in\mathfrak{U}_{\text{nonself}}}[R(u)]}{s_V + \mathbb{E}_{u\in\mathfrak{U}_{\text{self}}}[R(u)]}.$$

This estimator is high only when self-targeted perturbations matter differentially after structural matching.

A.6 Estimator for intervention selectivity

Use the five-coordinate signed drops and preregistered targets of the selective-response rule. On the matched admissible target set $\mathcal{I}_{\text{tgt}} \neq \varnothing$ the scalar is

$$\widehat{\Delta}_\tau = \frac{1}{|\mathcal{I}_{\text{tgt}}|} \sum_{u\in\mathcal{I}_{\text{tgt}}} \mathbf{1}\big[\text{target drops and absolute off-target changes meet their thresholds}\big].$$

Record the separate matched-sham rate. The score lies in $[0,1]$ when defined. Replacing either derived coordinate while keeping the five primary measurements and protocol fixed leaves the score unchanged.

A.7 Estimator for irreducibility

The irreducibility estimator is already defined in the main text, but two further notes matter. First, the complexity penalty should be fixed before the comparison, not tuned after observing the result. Second, the weak rival family should be documented in the artifact layer so that a later critic can see exactly which alternatives were and were not defeated.

A.8 Composite gate design

One may choose stricter or softer versions of the gate:

$$\Gamma^{(\min)}_{\text{subj}} = \min_j \widehat{X}_j, \qquad \Gamma^{(\text{soft})}_{\text{subj}} = \left(\prod_j \widehat{X}_j\right)^{1/7}.$$

The present paper prefers the strict minimum as the gate and the geometric mean as the scalar because that pairing best separates class membership from within-class ordering. A future implementation may report both.

A.9 A Joint Rational Measurement Window

Use a finite system with state $(z, b) \in \{0,1\} \times \{0,1\}^5$, where z is a balanced exogenous context and $b = (b_I, b_O, b_C, b_P, b_V)$. Reset b to all ones. On a one-step window a target u_j sets only $b_j = 0$; the sham u_0 preserves all bits. The context is unchanged. Use the same prepared contexts in every arm and error-free rational observations. All the coordinates below are functions of this one transition system and protocol.

In the order *context label, other label*, the index weights are $((1 + b_I)/2, (1 - b_I)/2)$. The admissible within-run index relabelling is the identity. The index gap is b_I, including zero when the weights tie. For the two events, fix the reference $r_z = (1 - z, z)$ by the assigned context. The candidate reports r_z when $b_O = 1$ and $(1/2, 1/2)$ otherwise. The matched control always reports $(1/2, 1/2)$, so the reference-based ownership gain is $b_O/2$. The declared continuity scores

of the context line and its rival are b_C and zero, giving $b_C/(1+b_C)$. These scores use a fixed context match on the two candidate lines.

The perspective outcome is the binary readout $b_P z$. The indexed predictor uses z and the command, while the index-neutral rival may use the command but receives no context proxy. Its best zero-one loss on the balanced population is $b_P/2$, and the indexed predictor has loss zero. The normalized perspective gain is $b_P/(2+b_P)$. For valuation, a probe of role $\ell \in \{0,1\}$ produces $b_V \mathbf{1}_{\ell=z}$. The matched roles z and $1-z$ have equal budgets and give responses b_V and zero, so the normalized asymmetry is $b_V/(1+b_V)$.

For irreducibility reserve separate balanced replicas with u_0 for baseline loss and u_O for intervention loss. Both have $b_P = 1$. The candidate and rivals receive the same command and predict the same declared selectivity pattern, giving zero selectivity-prediction loss; the complexity coefficient is fixed at zero. Against the declared finite weak family of all context-blind binary predictors by command, the candidate has total loss zero and the best rival has total loss $1/2 + 1/2 = 1$. Giving a rival the index is a separate tie control. The reserve is never used to compute the intervention profile.

Proposition A.2 (Joint Rational Certificate of the Seven Local Measurements)**.** *For this window, with minimum target drop* $1/4$*, maximum absolute off-target change* $1/8$*, and zero allowed sham positives, the normalized measurements in the order of* $\mathfrak{S}$ *are*

$$(1, \tfrac{1}{2}, \tfrac{1}{2}, \tfrac{1}{3}, \tfrac{1}{2}, 1, \tfrac{1}{2}).$$

The gate is $1/3$ *and the functional with equal weights* $1/7$ *is* $48^{-1/7}$*. Both exceed the declared threshold* $1/4$*.*

Proof. At reset, the five primary scores evaluate to the first five entries. Each of the five target transitions sets its designated score to zero and leaves all other primary scores unchanged, while the sham changes none. Thus each target drop is at least $1/3$, the off-target changes are zero and the intervention score is one. The reserved rival loss is one because two equiprobable contexts have opposite binary outcomes under each reserved command. No context-blind rule beats $1/2$ on either balanced block. Hence the irreducibility score is $(1-0)/(1+1) = 1/2$. Multiplication gives the seventh power $1/48$, and the minimum is $1/3$. Since $48 < 4^7$, the functional exceeds $1/4$. Restoring the index to the weak predictor permits zero loss and forces a tie, as required by the negative control. □

This is a nonempty local measurement certificate, with the intervention and rival clauses verified on the declared finite protocol. Definition 5.1 also requires inherited Paper V and VII certificates. Those clauses remain separate obligations for full membership. The comparison establishes a gap relative to the specified context-blind predictors on these tasks.

A.10 A Topological Obstruction to Native Lesions

Use the circle-prefix tower of Papers V--VI [1, 7] on the safe band of Paper VII [6]. Its states are (p, θ, b, m) with $\theta \in \mathbb{T}$, $b \in \{0,1\}^{\mathbb{N}_{>0}}$, and $m \in [-1/4, 1/4]$. For all native commands (u, q) the projected update on (p, b) is (p, Rb) with $Rb = (0, 1-b_1, 1-b_2, \ldots)$. The phase and memory updates depend on the commands.

Theorem A.3 (Connected-Fibre Obstruction to Native Discrete Lesions)**.** *Suppose the sham and targets start from the same preparation, use only native commands, and are evaluated after the same number of transitions. Let their discrete word be assigned by a common continuous decoder from the whole safe support. The same hypothesis holds for the induced state decoder if it uses a common fixed finite diagnostic schedule with continuous clean observations and preserves the clean label under observation error of a uniformly positive radius. Then every target has the same word as the sham. In particular the five distinct native lesions required*

to reproduce the discrete switch protocol of Proposition A.2 cannot be realized under these conditions.

Proof. At fixed (p, b) the fibre is homeomorphic to $\mathbb{T} \times [-1/4, 1/4]$ and is connected. A continuous map from it to a discrete space is constant. In the diagnostic formulation, write $H(x)$ for the clean window starting at the state to be decoded. For x' sufficiently close to x, continuity puts $H(x')$ inside the allowed noise ball around $H(x)$. Uniform robustness makes their decoded words identical, so the induced state decoder is locally constant and hence continuous. After n native steps from one preparation, all arms have the same $(p, R^n b)$ even if the commands are chosen by feedback. Thus all arms end in one fibre. The finite switch protocol instead requires a one-step target word different from the sham word. □

Two fixed profiles can encode context. The five initial prefix bits can be read as preparation contrasts, but the common shift and complement carry them to positions 2 through 6 in every arm. A selective change to a prefix bit from a common preparation requires an intervention that changes the prefix update. Restricted diagnostic domains offer a different possibility because separated phase or memory regions need not be connected within the domain. Their evidence requires declared coverage and a rival with access to the same commands. For example, prepare $m = 0$ and use $q = 0$. The six commands $u = w/32$, where w is the all-active five-bit word or one of its five single-bit lesions interpreted as an integer, give six separated phases $\theta' = u$. A rival given u predicts these labels exactly. This control separates the existence of labels on a restricted domain from selective intervention on the system's own organization.

A.11 Selective Lesions in the Writable Common Tower

Use the writable circle-prefix tower of Paper V [1], with the same memory and safe-band recovery of Papers VI--VII [7, 6]. Associate sites 3 through 7 in order with index, ownership, continuity, perspective, and valuation. For each balanced context $z = 0, 1$, prepare $(p_z, 0, b^\star, 0)$. From that same preparation use a neutral sham or write the opposite of $b^\star$ at one designated site. On copies of the resulting state use common neutral role probes with zero base phase and no additional write. The diagnostic does not receive the lesion label. The next observed r_0 in turns, unwrapped near zero, is either 0 or δ. Thresholding at $\delta/2$ gives

$$Y_i(\ell) = A_i(b)\mathbf{1}_{\{\ell = z\}}.$$

This decoder is correct for phase error at most $\delta/4$; the code prefix and profile are also decodable within this budget. The scope is the prepared diagnostic windows with zero memory. The phase probe acts on the state transition.

Proposition A.4 (Five Selective Lesions on the Writable Common Tower)**.** *The five interventions each reduce their primary score by at least* $1/4$*, with zero changes off target and zero sham positives. The normalized vector in the order of* $\mathfrak{S}$ *on the declared comparison is*

$$(1, \tfrac{1}{2}, \tfrac{1}{2}, \tfrac{1}{3}, \tfrac{1}{2}, 1, \tfrac{1}{2}).$$

Against the declared context-blind family the reserve loss gap is one, the gate is $1/3$*, and the equal-weight functional is* $48^{-1/7} > 1/4$*.*

Proof. In each block the tape after the sham is $b^\star$ and a target changes only its address. The phase and memory after that step agree across arms. For the index, form the two weights $(1 + Y_i(\ell) - Y_i(1 - \ell))/2$ from the index probe. Their gap is A_i. The within-run admissible relabeling fixes the roles. A joint renaming of roles and their references preserves the comparison. For ownership use the same two assignments from the ownership probe, with the reference fixed by the prepared role and a flat comparator with assignments $1/2$. The gain in mean absolute

error is $A_i/2$. For continuity compare the responses of the matched profile line and its rival in the continuity probe, giving gap $A_i/(1+A_i)$. The valuation contrast uses the matched self and other probe roles and gives the same normalized formula at its own site.

For perspective predict $Y_i(1)$ from the measured pre-probe profile and bit. The candidate has loss zero. A predictor without the profile or a proxy for it receives identical data in the two balanced contexts, including the command, phase, tape and memory available to it. Its best zero-one loss is $A_i/2$, so the normalized perspective gain is $A_i/(2+A_i)$. Each score therefore changes only when its own site changes. The minimum target drop is $1/3$. All five targets meet the selectivity rule and its score is one. A write of the reference value gives the same control as the native sham from this preparation.

Use separate balanced replicas of the sham and ownership lesion for baseline and intervention loss in the reserve. Both have the perspective site active. The future phase outcome has opposite labels in the two contexts within each block. Candidate loss is zero. Every context-blind predictor, including mixtures based on the same information, has expected loss $1/2$ in each block. The complexity weight is zero and the declared selectivity pattern is predicted equally in both arms. The normalized gap is therefore $\widehat{\mathcal{R}}_{\mathrm{blind}} = 1/2$. Multiplication gives $\Phi^{7}_{\mathrm{subj}} = 1/48$ and the minimum gives $\Gamma_{\mathrm{subj}} = 1/3$. □

The reserved loss comparison masks the relative phase channels for the blind family. Restoring these channels gives a rival zero loss because the profile is then decodable. Suppressing the write leaves all sites active and removes the target drops. Suppressing the probe feedback retains the tape changes and removes the phase response. At phase error $\delta/2$ the two clean levels can give the same reading. These controls locate the causal and information assumptions. The construction escapes the connected-fibre obstruction by changing the tape component of the fibre. The local margins hold against the declared information-restricted family. Full membership in Definition 5.1 still requires the inherited subjecthood evidence and a comparison against the admissible weak closure.

A.12 A Held-Out Return Task with Informed Rivals

The outcome here is a subsequent phase failure under the selected action. The five primary scores and the context-blind comparison above use their original trials. The return task uses a disjoint set of trials and neither the outcome nor the action that avoids it enters those scores.

Use the seven profiles of the writable tower, and form public strata $x = (p, \sigma, w)$ from profile p, assignment command $q = \sigma \in \{-1, 1\}$ and one common write w. The write is either absent or is one of the five designated lesions. In each stratum prepare two copies of the phase-zero alternating state $b^{\star}$ and set the private memory to $m = s/8$, with $s = \pm 1$ balanced. The public record includes that the perturbation occurred but carries no sign. Execute the assignment step with $u = 0$, the indicated q and w, and no probe. The decision time is immediately after this step. Apply a single chosen action $u = v/128$ with $v \in \{-1, 1\}$, $q = 0$, and neither a write nor a probe. The action fails if the next circular distance to phase zero exceeds $1/256$ turns, with terminal phase error bounded by $\eta = 3^{-10}/4$. Both actions have cost $1/128$. There is also an abstention with loss $3/4$ and no action. An executed action has loss one on failure and zero on success.

All predictors receive the four current public readings, the same public command record, and the same calibration. Each may query at most one earlier public reading, retain at most one bit per trial, and fit at most four binary parameters from the calibration. No physical probe is available before the decision. Define the public rival class to contain all decision rules on these inputs that obey the budget, with optional randomization independent of the perturbation. The class includes arbitrary choices of which previous reading to query within the budget. For a fixed public stratum, all recorded readings through decision time agree between signs, so this choice never reveals the hidden sign.

Calibration uses the zero profile, no writes, and initial $m = s/16$. A neutral step gives prior phase $s/128$ and memory $s/32$, and the assignment step gives memory $\sigma s/64$. The two calibration ports $\pm 1/512$ therefore identify the four-entry table $v = -\sigma s$ for the sign of that prior phase and the assignment command. The table is fixed before using the reserve amplitudes. A profile rule can use the parity of the final relative phase offset in units of $1/8$. A history rule applies the four-entry table to the queried prior phase and σ. The memory--policy hybrid stores the prior sign and applies the fitted multiplicative assignment factor, which here is σ. A zero cue has a fixed sign convention. The interacting comparator of Paper VI [7] uses its own nonneutral rule, reversing the remembered sign under either nonneutral command. The candidate uses the tower's return rule with the same inputs and calibration. These rules are representatives of the public comparison. The obstruction concerns the entire admissible class.

Theorem A.5 (Public Information Obstruction on the Writable Tower Return Task)**.** *In each public stratum, the two hidden perturbations have identical public records and opposite unique successful action signs. Every admissible forced public rule has balanced failure risk* $1/2$*. At coverage* c *the total loss is* $1/2 + (1 - c)/4$*, where coverage is the probability of executing an action. The infimum over the public class, including mixtures and their closure, equals* $1/2$ *and is attained. Thus the candidate's signed margin, defined as the public rival infimum minus candidate loss, is zero for every forced public candidate. The public randomized minimax risk over the two signs also equals* $1/2$*.*

Proof. At the assignment step the first tape digit is zero, so the two signs produce the same phase zero and the same tape after the common write. The unchanged profile and the absence of a phase response to memory at nonneutral q give identical readings. The hidden memories after assignment are $\sigma s/16$. With neutral q the terminal phase has signed representative $(v + \sigma s)/128$. The two distances to zero are therefore 0 and $1/64$. Since $\eta < 1/256$ and $1/64 - \eta > 1/256$, the unique success is $v = -\sigma s$ throughout the error range. These relations use the native return channel. Neither the phase probe nor the five score readouts is needed.

The public transcript, including any permissible previous query and calibration, has the same value for both signs in a stratum. Conditional on executing a given action, the sign remains balanced, because all internal randomization is independent of the perturbation. Each forced action then has risk $1/2$. Averaging over action and abstention gives the formula. Each stratum admits a fixed forced rule and the resulting risk bound survives mixtures and limits of action distributions. For the worst-sign criterion the balanced risk gives the lower bound, and a fair forced coin has error $1/2$ under either sign. □

Interchanging σ interchanges the winning ports at fixed s. Setting $m = 0$ makes both ports yield distance $1/128$, which exceeds the failure threshold even after the allowed error. For a history control, start at $m = s/4$, then take a neutral step before the assignment. It gives a public previous phase of $s/32$ and leaves $m = s/8$ before the assignment. The current readings are again identical across signs after assignment, but one query of that previous reading resolves the sign. The calibrated candidate, the history rule and the hybrid can each attain zero loss on this control. In contrast the Paper VI interacting comparator succeeds at $\sigma = -1$ and fails at $\sigma = +1$ because it predicts a sign inversion in both cases. This mismatch identifies a specific dynamical comparator that loses even though the best public rival still ties the candidate.

Theorem A.6 (Exact Separation by an Accessible Private Signal)**.** *Retain the hidden return task of Theorem A.5. Let the candidate alone receive a finite signal* Z *at decision time, with laws* μ_x^+ *and* μ_x^- *conditional on the public stratum* x *and the successful action signs* $+1$ *and* -1*, respectively. Assume the signal is available in one permitted reading and the decision maps used for the stated optima can be fixed from the declared signal law within the budget, without fitting on the reserve. For the worst-sign optimum this includes the allowed randomization from a*

fixed map of the reading to an action probability. The predictor retains only its sampled binary decision. For stratum weights w_x, the exact best signed margin against the public rival closure is

$$\sup_{candidate} \inf_{public\ rival} (R_{\mathrm{rival}} - R_{\mathrm{candidate}}) = \frac{1}{2} \sum_x w_x \ \mathrm{TV}(\mu_x^+, \mu_x^-), \qquad \mathrm{TV}(\mu, \nu) = \frac{1}{2} \sum_z |\mu(z) - \nu(z)|.$$

It is positive exactly when the two accessible laws differ on a positive-weight stratum.

Under minimax over the two successful action signs at fixed x, allowing randomization, the best private risk is

$$\max_{0 \le \pi \le 1} \sum_z \min\{\pi \mu_x^+(z), (1-\pi)\mu_x^-(z)\}.$$

It is strictly below the public minimax risk $1/2$ exactly when $\mu_x^+ \neq \mu_x^-$. For a uniform worst-sign improvement across the finitely many strata, each pair of accessible laws must differ and their respective optimal rules must be jointly admissible. If the same signal and decision budget are shared with the rivals, their closure can reproduce the candidate decision and the best signed margin is zero.

Proof. Replacing any abstention by an independent fair forced action changes its conditional loss from $3/4$ to $1/2$ under either sign. Thus abstention cannot improve either optimum. In the balanced stratum, choosing the sign with larger likelihood at each z attains error

$$\frac{1}{2} \sum_z \min\{\mu_x^+(z), \mu_x^-(z)\} = \frac{1}{2}(1 - \mathrm{TV}(\mu_x^+, \mu_x^-)).$$

No mixture of actions lowers the smaller conditional loss. This optimal binary decision is stored in one bit. Averaging over x and subtracting from the public infimum proves the balanced formula.

For the worst-sign criterion the set of randomized rules on the finite signal alphabet is compact and convex. The conditional risks for the two signs are linear in the rule. The finite minimax theorem equates the best worst-sign error with the maximum, over the prior weight π of sign $+1$, of the best π-weighted error. For each π the best error selects the smaller of the two weighted likelihoods pointwise, giving the displayed value. The sum of minima is at most $\min\{\pi, 1-\pi\}$, strictly below $1/2$ away from $\pi = 1/2$. At $\pi = 1/2$ the balanced formula is strictly below $1/2$ if the laws differ. Continuity on the compact prior interval makes the maximum strictly below $1/2$ in that case. If the laws coincide, the balanced prior attains $1/2$. The rule can retain only its sampled binary decision. For both criteria the full public class with a shared signal includes the same rule under the matched budget. In particular its infimum equals the candidate optimum under symmetric access. □

For the private copy of the memory sign, the conditional laws have disjoint supports, so the gain is $1/2$ for both criteria. For a copy that is independently erased with probability $1/2$, the two laws share only the erased outcome with mass $1/2$. The balanced and minimax risks are then both $1/4$ and the gain is $1/4$. An accessible signal computed solely as a deterministic function of the common public prefix and commands has identical laws in the two branches. Such a signal cannot provide strict separation for the task above. A dynamical coupling would have to expose information correlated with the winning port that the candidate can use within budget and the public class cannot access, or establish a specific asymmetry of realizable decision rules. Exposing the same information to both sides improves their attainable losses together. The exact separation obtained here is relative to the declared information channel, while the five-lesion diagnostic retains its distinct comparison.

B Intervention-to-artifact mapping and failure semantics

The implementation burden becomes much clearer when each intervention is mapped to artifacts and failure codes.

B.1 Swap family

The self/non-self swap intervention should at minimum emit:

1. `self_nonself_swap_report.json`
2. updated `self_index_state.json`
3. updated `ownership_attribution_report.json`
4. updated `first_person_perspective_report.json`

Expected failure codes include `swap_invariant`, `swap_nonselective`, and `swap_control_confound`.

B.2 Ownership family

Ownership lesions should emit both a local report and an updated gate result. The decisive question is whether ownness loss propagates selectively into the gate or whether it behaves like arbitrary logging damage. Relevant failure codes include `ownership_decorative` and `ownership_aliasing`.

B.3 Continuity family

Continuity breaks and autobiographical remaps should emit:

1. `subjective_continuity_report.json`
2. fork or fracture subreports
3. updated `subjectivity_runtime_projection.json`

Relevant failure codes include `continuity_flat`, `memory_only_explanation`, and `fork_underdetermined`.

B.4 Perspective and valuation family

Perspective flattening and valuation perturbations should jointly update the perspective and valuation reports, because in a serious subjectivity stack those layers should interact. If one changes dramatically while the other remains entirely invariant, the implementation should explicitly say so. Relevant failure codes include `perspective_optional` and `valuation_generic`.

B.5 Cross-substrate family

Cross-substrate remaps should emit a dedicated transport report including:

1. preserved coordinates;
2. failed coordinates;
3. transport class: preserving, fractured, forked, or unsupported;
4. winning weak rival under the remap if the stronger model fails.

This report is essential because cross-substrate claims are otherwise too easy to overread.

B.6 Failure semantics

The artifact layer should localize failure by cause, not merely by score. A strong minimal taxonomy is:

1. `missing_coordinate_evidence`
2. `weak_model_sufficient`
3. `intervention_nonselective`
4. `control_confound`
5. `fork_ambiguity`
6. `unsupported_transport`
7. `admissibility_broken`

Such a taxonomy matters scientifically because it turns a failed subjectivity claim into information about what exactly failed, instead of reducing every failure to a vague ''not enough evidence'' label.

C Negative controls, ablation matrix, and causal discrimination protocol

The main text specifies the intervention family. A serious subjectivity program also needs a systematic negative-control and ablation protocol. Without it, a clever but weak implementation could produce superficially impressive artifacts while remaining reducible to complexity, bookkeeping, or narrative fit.

C.1 Negative control families

At minimum, the following controls should be implemented:

1. **complexity-matched non-indexed controls:** systems with comparable scale and internal richness but no privileged self-index;
2. **memory-rich non-owning controls:** systems with extensive autobiographical storage but flat ownership assignment;
3. **policy-matched controls:** agents with strong reward optimization but no subject-level continuity burden;
4. **narrative-rich controls:** systems capable of sophisticated self-description without interventional subjectivity structure;
5. **bookkeeping controls:** systems whose self-like outputs are produced by latent tags and registries only.

The role of these controls is not merely comparative. They define the nearest ways in which the theory could be wrong while still looking superficially plausible.

C.2 Ablation targets

Every constitutive coordinate should be tied to at least one clean ablation family:

1. self-index ablations through candidate-locus symmetrization;
2. ownership ablations through ownness-field flattening;
3. continuity ablations through fork or fracture operators;
4. perspective ablations through index-neutral factorization;
5. valuation ablations through self/non-self reward equalization;
6. intervention-profile ablations through targeted-to-random perturbation substitution;
7. irreducibility ablations through weak-rival reconstruction challenges.

C.3 Ablation matrix

Ablation	Primary expected drop	What weak rivals predict	Why the test matters
self-index symmetrization	$\widehat{I}_\tau$, then $\widehat{P}_\tau$	many weak rivals predict little more than relabeling cost	tests whether one locus is constitutively privileged
ownership flattening	$\widehat{O}_\tau$, then $\widehat{V}_\tau$	bookkeeping and narrative systems may remain mostly intact	separates ownness from self-description
continuity fracture	$\widehat{C}_\tau$, then gate collapse	memory systems predict a weaker or purely archival effect	separates autobiographical continuity from stored content
perspective neutralization	$\widehat{P}_\tau$ with downstream valuation impact	workspace models predict weaker downstream consequences	tests whether perspective is constitutive
valuation equalization	$\widehat{V}_\tau$ and some gate degradation	policy models often absorb this into reward reshaping	separates self-valued organization from generic utility
weak-rival reconstruction	$\widehat{\mathcal{R}}_\tau$	if weak rivals succeed, the stronger model collapses	keeps the theory honest

C.4 Noise and adversarial perturbations

The paper should also survive a stronger class of tests than clean lesions. Three families are especially important.

Noise injection. Small stochastic perturbations should not destroy the entire subjectivity profile unless they specifically target a constitutive coordinate. Otherwise the paper would define a class too brittle to be scientifically useful.

Adversarial tag attacks. The system should be exposed to perturbations specifically designed to fake self-like artifacts by manipulating surface tags, report channels, or local memory labels. If the stronger model cannot resist such attacks, it is not yet stronger than bookkeeping.

Counterfactual decoy insertion. One should inject near-self decoys into the candidate self-index pool. A robust subjectivity layer should not collapse merely because the environment offers a decoy with superficial similarity. This test is especially important for separating true self-index stability from report-conditioned heuristics.

C.5 Causal discrimination protocol

The correct order of causal testing is:

1. measure baseline coordinates;
2. run negative controls;
3. run single-coordinate ablations;
4. run compound ablations designed to mimic weak-rival hypotheses;
5. compare against the weak family under the same intervention budget;
6. only then compute the final gate and irreducibility outputs.

This ordering matters because a gate result computed before the weak-rival and control budget is exhausted is too easy to overread.

C.6 Reproducibility burden

No subjectivity program should be trusted if it cannot survive reruns. At minimum, the following reproducibility burdens should be imposed:

1. seed schedule variation with fixed architecture;
2. comparator reruns with blinded weak-rival selection;
3. independent regeneration of gate results from stored artifacts;
4. cross-machine replay of the intervention harness;
5. explicit documentation of any run that fails admissibility before subjectivity is even evaluated.

These burdens are not secondary engineering details. They are part of what distinguishes a scientific subjectivity program from a compelling one-off demonstration.

D Claim decomposition, theorem candidates, and open escalation burdens

The strongest way to end a paper like this is not with a louder conclusion. It is with a clear decomposition of what has actually been established, what has merely been postulated, and what remains future burden.

D.1 Claim decomposition table

Statement	Status	Reason
Subjectivity can be formalized as a seven-coordinate first-person indexed class	definition-level closed	fixed by the typed coordinates and Definition 5.1
Upstream membership is required; proper inclusion of the complete classes remains an additional realization obligation	inclusion proved; properness pending	constitutive implication alone does not supply a separating complete-class witness
Weak rivals can be compared formally and defeated only by positive irreducibility margin	theorem-level closed within the model-comparison formalism	follows from the loss-based irreducibility definition
Targeted interventions can in principle separate the stronger model from weaker rivals	criterion-level closed, empirical burden open	the logic is formalized but not yet fully implemented natively
Cross-substrate transport is licensed under exact preservation of the constitutive structure	proposition-level closed under bridge axioms	depends on explicit structural transport, not ordinary empirical success alone
Human equivalence is not yet licensed	non-claim closed	comparator burden remains external and open
Metaphysical subjectivity is proved	rejected	beyond the scope of the formal and bridge-axiomatic level

D.2 Theorem candidates for future formal work

The present paper already contains proved propositions and theorems, but it also points toward a second wave of formal work. The following theorem candidates are especially natural:

1. **minimal-coordinate theorem:** no proper subset of the seven coordinates preserves the extension of $\mathsf{S}_{\mathrm{idx}}$ in admissible universes containing the corresponding ablation witnesses;
2. **fork non-uniqueness theorem:** exact duplication under specified transport conditions blocks singular continuity assignment without additional asymmetry;
3. **valuation-separation theorem:** if valuation asymmetry vanishes identically while the remaining coordinates are preserved, the class collapses to a weaker non-subjective superclass;
4. **weak-family completeness theorem:** under a given admissible task bundle, the chosen weak rival family is complete up to a specified approximation class.

These are not included as proved theorems because doing so would require additional technical machinery. They are listed because they mark the next natural formal frontier, not because the current paper needs them to make its central claim.

D.3 Empirical escalators

If one wanted to move from the present paper's strongest claim toward something closer to strong subjectivity or human equivalence, the escalators would have to be explicit:

1. close a native runtime suite for the seven coordinates;
2. validate the intervention family against independent negative controls;

3. show reproducible positive irreducibility margins across runs and evaluators;
4. perform external or semi-external review of the weak-rival comparison layer;
5. construct a serious human comparator bundle with shared admissibility criteria.

Until those escalators are climbed, the present paper should be read exactly as intended: as a major formal expansion of what the corpus can say, not as the final scientific verdict on subjectivity.

E Rival-question matrix for implementation and audit

The present appendix turns the rival-family comparison into an explicit question set. Its role is practical: it gives a future implementer or auditor a compact matrix of what must be answered before the stronger interpretation is allowed to stand.

E.1 Decisive questions

For each rival family, the right question is not ‘‘does the system look self-like?’’ The right question is which exact burden remains unexplained if the rival is assumed true.

1. **Against pure self-monitoring:** what privileged continuity or clone-sensitive asymmetry remains after one grants the system perfect introspective access?
2. **Against memory integration only:** what ownership or valuation asymmetry remains after one grants rich autobiographical storage and retrieval?
3. **Against policy-centered agency:** what self-index burden remains after one grants highly competent control and reward optimization?
4. **Against narrative self-model:** what intervention pattern remains after one grants coherent self-description and autobiographical narration?
5. **Against global workspace without subjectivity:** what owned and indexed perspective remains after one grants broad integration and global accessibility?
6. **Against bookkeeping:** what survives once all tags and registries are treated as possible implementation conveniences rather than constitutive subjective structure?

E.2 Decision matrix

Rival family	Question the auditor should ask	Pattern that would keep the stronger model live
self-monitoring	If the system tracks its own states perfectly, what still requires first-person organization?	selective failure under self/non-self swap and clone competition remains unexplained
memory integration	If memory is rich and stable, what still requires subjectivity rather than archive persistence?	continuity, ownership, and valuation remain jointly privileged and intervention-sensitive
policy-centered agency	If behavior is highly adaptive, why is control alone not sufficient?	self-targeted disruptions matter differently even when policy competence is preserved
narrative self-model	If the system tells a coherent story about itself, what stronger burden is left?	non-report ownership and reducibility margins remain positive under perturbation
global workspace	If information is globally available, why is broadcast not enough?	one locus remains privileged for ownership and valuation under matched controls
bookkeeping	If tags and registries produce the same outputs, why posit more?	weak-tag reconstructions fail to reproduce the full intervention profile at equal or lower cost

E.3 Why this matrix belongs in the paper

The matrix belongs here because the strongest risk facing a paper like this is not only philosophical criticism. It is implementation drift. Without a compact rival-question set, later runtime work can slowly mutate into producing self-like artifacts without ever answering the question of what weaker explanation has actually been defeated. The matrix is therefore a safeguard against both conceptual and engineering drift.

E.4 Audit-facing interpretation

An external or semi-external reviewer should be able to take the matrix and ask, for each rival family, whether the current artifact package truly excludes that rival on the declared task bundle. If the answer is ‘‘not yet,’’ that is not a disaster. It is useful information. The disaster would be pretending that a strong subjectivity paper has already won those comparisons by force of language alone.

F Interpretation and Open Research Links

Historical alias. First-Person Indexed Subjectivity. The alias is retained for bibliographic continuity; the technical title states the demonstrated object.

Formal anchor. Results A.4 and A.5.

Proposed interpretation. First-person and ownership language motivates an indexed certificate. Local selective lesions and predictive gains do not by themselves settle subjectivity or complete-class membership.

Additional obligations. Specify role references, symmetry actions, information budgets, normalized estimators and all inherited predicates on one domain.

Differential tests and evidence. Compare passive renaming with causal transplant, restore masked information to rivals and test held-out differential predictions. Human equivalence and phenomenality remain independent questions.

References

[1] Johnny Andrey Perez Ramirez. ''A Structural Criterion for Substrate-Invariant Operational Consciousness''. In: *arXiv preprint* (2026).

[2] Johnny Andrey Perez Ramirez. ''Canonical Core: Minimal Hypotheses for Causally Rigid Identity Frameworks''. In: *arXiv preprint* (2026).

[3] Johnny Andrey Perez Ramirez. ''Falsifiable Predictions Under Forensic Constraints''. In: *arXiv preprint* (2026).

[4] Johnny Andrey Perez Ramirez. ''Phenomenological Regimes Induced by Structural Identity''. In: *arXiv preprint* (2026).

[5] Johnny Andrey Perez Ramirez. ''Structural Instability of the Phenomenological Null Regime in Causally Rigid Channels''. In: *arXiv preprint* (2026).

[6] Johnny Andrey Pérez Ramírez. ''Operational Life, Structural Class, and Subjecthood in a Causally Rigid Framework''. In: *arXiv preprint* (2026).

[7] Johnny Andrey Pérez Ramírez. ''Predictions, Discriminators, and Failure Modes for the Causally Rigid Operational Consciousness Framework''. In: *arXiv preprint* (2026).

[8] Johnny Andrey Pérez Ramírez. ''Rigid Identity as an Inverse Limit in Observable Channels''. In: (2026). Companion paper establishing the identity framework and ontological mass invariant.