
arch Documentation

Release 5.5.0

Kevin Sheppard

Apr 26, 2023

CONTENTS

1	Univariate Volatility Models	3
1.1	Introduction to ARCH Models	3
1.2	ARCH Modeling	6
1.3	Forecasting	20
1.4	Volatility Forecasting	26
1.5	Value-at-Risk Forecasting	35
1.6	Volatility Scenarios	37
1.7	Forecasting with Exogenous Regressors	44
1.8	Mean Models	53
1.9	Volatility Processes	113
1.10	Using the Fixed Variance process	204
1.11	Distributions	209
1.12	Model Results	236
1.13	Utilities	253
1.14	Theoretical Background	254
2	Bootstrapping	255
2.1	Bootstrap Examples	255
2.2	Confidence Intervals	262
2.3	Covariance Estimation	267
2.4	Low-level Interfaces	268
2.5	Semiparametric Bootstraps	270
2.6	Parametric Bootstraps	271
2.7	Independent, Identical Distributed Data (i.i.d.)	272
2.8	Independent Samples	283
2.9	Time-series Bootstraps	294
2.10	References	327
3	Multiple Comparison Procedures	329
3.1	Multiple Comparisons	329
3.2	Module Reference	336
3.3	References	344
4	Unit Root Testing	345
4.1	Introduction	345
4.2	Unit Root Testing	346
4.3	The Unit Root Tests	356
5	Cointegration Analysis	383
5.1	Cointegration Testing	383

5.2	Cointegration Tests	390
5.3	Cointegrating Vector Estimation	393
6	Long-run Covariance Estimation	417
6.1	Long-run Covariance Estimators	417
6.2	Results	458
7	API Reference	461
7.1	Volatility Modeling	461
7.2	Unit Root Testing	462
7.3	Cointegration Testing	462
7.4	Cointegrating Relationship Estimation	462
7.5	Bootstraps	462
7.6	Testing with Multiple-Comparison	463
7.7	Long-run Covariance (HAC) Estimation	463
8	Change Logs	465
8.1	Version 5	465
8.2	Version 4	467
8.3	Version 3	470
8.4	Version 2	471
8.5	Version 1	471
9	Citation	473
10	Index	475
	Bibliography	477
	Python Module Index	479
	Index	481

Note

[Stable documentation](#) for the latest release is located at [doc](#). Documentation for [recent developments](#) is located at [devel](#).

The ARCH toolbox contains routines for:

- Univariate volatility models;
- Bootstrapping;
- Multiple comparison procedures;
- Unit root tests;
- Cointegration Testing and Estimation; and
- Long-run covariance estimation.

Future plans are to continue to expand this toolbox to include additional routines relevant for the analysis of financial data.

UNIVARIATE VOLATILITY MODELS

`arch.univariate` provides both high-level ([`arch_model\(\)`](#)) and low-level methods (see [Mean Models](#)) to specify models. All models can be used to produce forecasts either analytically (when tractable) or using simulation-based methods (Monte Carlo or residual Bootstrap).

1.1 Introduction to ARCH Models

ARCH models are a popular class of volatility models that use observed values of returns or residuals as volatility shocks. A basic GARCH model is specified as

$$r_t = \mu + \epsilon_t \quad (1.1)$$

$$\epsilon_t = \sigma_t e_t \quad (1.2)$$

$$\sigma_t^2 = \omega + \alpha \epsilon_{t-1}^2 + \beta \sigma_{t-1}^2 \quad (1.3)$$

A complete ARCH model is divided into three components:

- a *mean model*, e.g., a constant mean or an [ARX](#);
- a *volatility process*, e.g., a [GARCH](#) or an [EGARCH](#) process; and
- a *distribution* for the standardized residuals.

In most applications, the simplest method to construct this model is to use the constructor function [`arch_model\(\)`](#)

```
import datetime as dt

import pandas_datareader.data as web

from arch import arch_model

start = dt.datetime(2000, 1, 1)
end = dt.datetime(2014, 1, 1)
sp500 = web.DataReader('^GSPC', 'yahoo', start=start, end=end)
returns = 100 * sp500['Adj Close'].pct_change().dropna()
am = arch_model(returns)
```

Alternatively, the same model can be manually assembled from the building blocks of an ARCH model

```
from arch import ConstantMean, GARCH, Normal

am = ConstantMean(returns)
am.volatility = GARCH(1, 0, 1)
am.distribution = Normal()
```

In either case, model parameters are estimated using

```
res = am.fit()
```

with the following output

```
Iteration:      1,   Func. Count:      6,   Neg. LLF: 5159.58323938
Iteration:      2,   Func. Count:     16,   Neg. LLF: 5156.09760149
Iteration:      3,   Func. Count:     24,   Neg. LLF: 5152.29989336
Iteration:      4,   Func. Count:     31,   Neg. LLF: 5146.47531817
Iteration:      5,   Func. Count:     38,   Neg. LLF: 5143.86337547
Iteration:      6,   Func. Count:     45,   Neg. LLF: 5143.02096168
Iteration:      7,   Func. Count:     52,   Neg. LLF: 5142.24105141
Iteration:      8,   Func. Count:     60,   Neg. LLF: 5142.07138907
Iteration:      9,   Func. Count:     67,   Neg. LLF: 5141.416653
Iteration:     10,   Func. Count:     73,   Neg. LLF: 5141.39212288
Iteration:     11,   Func. Count:     79,   Neg. LLF: 5141.39023885
Iteration:     12,   Func. Count:     85,   Neg. LLF: 5141.39023359
Optimization terminated successfully.      (Exit mode 0)
Current function value: 5141.39023359
Iterations: 12
Function evaluations: 85
Gradient evaluations: 12
```

```
print(res.summary())
```

yields

```

Constant Mean - GARCH Model Results
=====
Dep. Variable:      Adj Close   R-squared:          -0.001
Mean Model:         Constant Mean   Adj. R-squared:     -0.001
Vol Model:          GARCH          Log-Likelihood:     -5141.39
Distribution:       Normal          AIC:                10290.8
Method:             Maximum Likelihood   BIC:                10315.4
                                           No. Observations:   3520
Date:              Fri, Dec 02 2016   Df Residuals:       3516
Time:              22:22:28           Df Model:           4
                                           Mean Model
=====
              coef    std err          t      P>|t|      95.0% Conf. Int.
-----
mu           0.0531  1.487e-02      3.569  3.581e-04  [2.392e-02, 8.220e-02]
Volatility Model
=====
              coef    std err          t      P>|t|      95.0% Conf. Int.
-----
omega        0.0156  4.932e-03      3.155  1.606e-03  [5.892e-03, 2.523e-02]
alpha[1]     0.0879  1.140e-02      7.710  1.260e-14  [6.554e-02,  0.110]
beta[1]      0.9014  1.183e-02     76.163  0.000      [ 0.878,  0.925]
=====
Covariance estimator: robust

```


1.1.1 Model Constructor

While models can be carefully specified using the individual components, most common specifications can be specified using a simple model constructor.

```
arch.univariate.arch_model(y, x=None, mean='Constant', lags=0, vol='GARCH', p=1, o=0, q=1,
                           power=2.0, dist='normal', hold_back=None, rescale=None)
```

Initialization of common ARCH model specifications

Parameters

y : {ndarray, Series, None}

The dependent variable

x : {np.array, DataFrame}, optional

Exogenous regressors. Ignored if model does not permit exogenous regressors.

mean : str, optional

Name of the mean model. Currently supported options are: 'Constant', 'Zero', 'LS', 'AR', 'ARX', 'HAR' and 'HARX'

lags : int or list (int), optional

Either a scalar integer value indicating lag length or a list of integers specifying lag locations.

vol : str, optional

Name of the volatility model. Currently supported options are: 'GARCH' (default), 'ARCH', 'EGARCH', 'FIGARCH', 'APARCH' and 'HARCH'

p : int, optional

Lag order of the symmetric innovation

o : int, optional

Lag order of the asymmetric innovation

q : int, optional

Lag order of lagged volatility or equivalent

power : float, optional

Power to use with GARCH and related models

dist : int, optional

Name of the error distribution. Currently supported options are:

- Normal: 'normal', 'gaussian' (default)
- Student's t: 't', 'studentst'
- Skewed Student's t: 'skewstudent', 'skewt'
- Generalized Error Distribution: 'ged', 'generalized error'

hold_back : int

Number of observations at the start of the sample to exclude when estimating model parameters. Used when comparing models with different lag lengths to estimate on the common sample.

rescale : bool

Flag indicating whether to automatically rescale data if the scale of the data is likely to produce convergence issues when estimating model parameters. If False, the model is estimated on the data without transformation. If True, than y is rescaled and the new scale is reported in the estimation results.

Returns

model – Configured ARCH model

Return type

ARCHModel

Examples

```
>>> import datetime as dt
>>> import pandas_datareader.data as web
>>> djia = web.get_data_fred('DJIA')
>>> returns = 100 * djia['DJIA'].pct_change().dropna()
```

A basic GARCH(1,1) with a constant mean can be constructed using only the return data

```
>>> from arch.univariate import arch_model
>>> am = arch_model(returns)
```

Alternative mean and volatility processes can be directly specified

```
>>> am = arch_model(returns, mean='AR', lags=2, vol='harch', p=[1, 5, 22])
```

This example demonstrates the construction of a zero mean process with a TARCH volatility process and Student t error distribution

```
>>> am = arch_model(returns, mean='zero', p=1, o=1, q=1,
...                 power=1.0, dist='StudentsT')
```

Notes

Input that are not relevant for a particular specification, such as *lags* when *mean='zero'*, are silently ignored.

1.2 ARCH Modeling

This setup code is required to run in an IPython notebook

```
[1]: %matplotlib inline
import matplotlib.pyplot as plt
import seaborn

seaborn.set_style("darkgrid")
plt.rc("figure", figsize=(16, 6))
plt.rc("savefig", dpi=90)
plt.rc("font", family="sans-serif")
plt.rc("font", size=14)
```


1.2.1 Setup

These examples will all make use of financial data from Yahoo! Finance. This data set can be loaded from `arch.data.sp500`.

```
[2]: import datetime as dt

import arch.data.sp500

st = dt.datetime(1988, 1, 1)
en = dt.datetime(2018, 1, 1)
data = arch.data.sp500.load()
market = data["Adj Close"]
returns = 100 * market.pct_change().dropna()
ax = returns.plot()
xlim = ax.set_xlim(returns.index.min(), returns.index.max())
```



1.2.2 Specifying Common Models

The simplest way to specify a model is to use the model constructor `arch.arch_model` which can specify most common models. The simplest invocation of `arch` will return a model with a constant mean, GARCH(1,1) volatility process and normally distributed errors.

$$r_t = \mu + \epsilon_t$$

$$\sigma_t^2 = \omega + \alpha \epsilon_{t-1}^2 + \beta \sigma_{t-1}^2$$

$$\epsilon_t = \sigma_t e_t, \quad e_t \sim N(0, 1)$$

The model is estimated by calling `fit`. The optional inputs `iter` controls the frequency of output from the optimizer, and `disp` controls whether convergence information is returned. The results class returned offers direct access to the estimated parameters and related quantities, as well as a `summary` of the estimation results.

GARCH (with a Constant Mean)

The default set of options produces a model with a constant mean, GARCH(1,1) conditional variance and normal errors.


```
[3]: from arch import arch_model
```

```
am = arch_model(returns)
res = am.fit(update_freq=5)
print(res.summary())
```

```
Iteration:      5,   Func. Count:    35,   Neg. LLF: 6970.2765831170655
Iteration:     10,   Func. Count:    63,   Neg. LLF: 6936.718477482658
Optimization terminated successfully   (Exit mode 0)
      Current function value: 6936.718476988985
      Iterations: 11
      Function evaluations: 68
      Gradient evaluations: 11
      Constant Mean - GARCH Model Results
=====
Dep. Variable:          Adj Close   R-squared:                0.000
Mean Model:             Constant Mean   Adj. R-squared:           0.000
Vol Model:              GARCH          Log-Likelihood:          -6936.72
Distribution:           Normal         AIC:                    13881.4
Method:                Maximum Likelihood   BIC:                    13907.5
                                     No. Observations:        5030
Date:                  Wed, Apr 12 2023   Df Residuals:            5029
Time:                  15:58:55          Df Model:                 1
                                     Mean Model
=====
              coef    std err          t      P>|t|      95.0% Conf. Int.
-----
mu           0.0564    1.149e-02      4.906   9.302e-07   [3.384e-02,7.887e-02]
              Volatility Model
=====
              coef    std err          t      P>|t|      95.0% Conf. Int.
-----
omega        0.0175    4.683e-03      3.738   1.854e-04   [8.328e-03,2.669e-02]
alpha[1]     0.1022    1.301e-02      7.852   4.105e-15   [7.665e-02, 0.128]
beta[1]      0.8852    1.380e-02     64.125   0.000      [ 0.858, 0.912]
=====
Covariance estimator: robust
```

plot() can be used to quickly visualize the standardized residuals and conditional volatility.

```
[4]: fig = res.plot(annualize="D")
```



GJR-GARCH

Additional inputs can be used to construct other models. This example sets `o` to 1, which includes one lag of an asymmetric shock which transforms a GARCH model into a GJR-GARCH model with variance dynamics given by

$$\sigma_t^2 = \omega + \alpha\epsilon_{t-1}^2 + \gamma\epsilon_{t-1}^2 I_{[\epsilon_{t-1} < 0]} + \beta\sigma_{t-1}^2$$

where I is an indicator function that takes the value 1 when its argument is true.

The log likelihood improves substantially with the introduction of an asymmetric term, and the parameter estimate is highly significant.

```
[5]: am = arch_model(returns, p=1, o=1, q=1)
res = am.fit(update_freq=5, disp="off")
print(res.summary())
```

```

=====
Constant Mean - GJR-GARCH Model Results
=====
Dep. Variable:          Adj Close    R-squared:                0.000
Mean Model:            Constant Mean  Adj. R-squared:           0.000
Vol Model:              GJR-GARCH    Log-Likelihood:          -6822.88
Distribution:           Normal        AIC:                     13655.8
Method:                Maximum Likelihood  BIC:                     13688.4
                                     No. Observations:         5030
Date:                  Wed, Apr 12 2023  Df Residuals:           5029
Time:                  15:58:56          Df Model:                1
                                     Mean Model
=====
      coef    std err          t      P>|t|      95.0% Conf. Int.
-----
mu      0.0175  1.145e-02     1.529    0.126  [-4.936e-03, 3.995e-02]
      Volatility Model
=====
      coef    std err          t      P>|t|      95.0% Conf. Int.
-----
omega    0.0196  4.051e-03     4.830  1.362e-06  [1.163e-02, 2.751e-02]

```

(continues on next page)

(continued from previous page)

```

alpha[1]    2.2928e-10  1.026e-02  2.234e-08      1.0000 [-2.011e-02,2.011e-02]
gamma[1]      0.1831  2.266e-02      8.079  6.543e-16      [ 0.139,  0.227]
beta[1]      0.8922  1.458e-02     61.200      0.0000      [ 0.864,  0.921]
=====

```

Covariance estimator: robust

TARCH/ZARCH

TARCH (also known as ZARCH) model the *volatility* using absolute values. This model is specified using `power=1.0` since the default power, 2, corresponds to variance processes that evolve in squares.

The volatility process in a TARCH model is given by

$$\sigma_t = \omega + \alpha |\epsilon_{t-1}| + \gamma |\epsilon_{t-1}| I_{[\epsilon_{t-1} < 0]} + \beta \sigma_{t-1}$$

More general models with other powers (κ) have volatility dynamics given by

$$\sigma_t^\kappa = \omega + \alpha |\epsilon_{t-1}|^\kappa + \gamma |\epsilon_{t-1}|^\kappa I_{[\epsilon_{t-1} < 0]} + \beta \sigma_{t-1}^\kappa$$

where the conditional variance is $(\sigma_t^\kappa)^{2/\kappa}$.

The TARCH model also improves the fit, although the change in the log likelihood is less dramatic.

```

[6]: am = arch_model(returns, p=1, o=1, q=1, power=1.0)
      res = am.fit(update_freq=5)
      print(res.summary())

```

```

Iteration:      5,   Func. Count:      45,   Neg. LLF: 6829.203002130782
Iteration:     10,   Func. Count:      79,   Neg. LLF: 6799.178617397159
Optimization terminated successfully   (Exit mode 0)
      Current function value: 6799.178521515934
      Iterations: 13
      Function evaluations: 96
      Gradient evaluations: 13
      Constant Mean - TARCH/ZARCH Model Results
=====
Dep. Variable:      Adj Close   R-squared:      0.000
Mean Model:      Constant Mean   Adj. R-squared:      0.000
Vol Model:      TARCH/ZARCH   Log-Likelihood:    -6799.18
Distribution:      Normal   AIC:      13608.4
Method:      Maximum Likelihood   BIC:      13641.0
                                     No. Observations:      5030
Date:      Wed, Apr 12 2023   Df Residuals:      5029
Time:      15:58:56   Df Model:      1
      Mean Model
=====
              coef      std err          t      P>|t|      95.0% Conf. Int.
-----
mu           0.0143  1.091e-02      1.311      0.190 [-7.087e-03,3.570e-02]
      Volatility Model
=====
              coef      std err          t      P>|t|      95.0% Conf. Int.
-----

```

(continues on next page)

(continued from previous page)

```

-----
omega      0.0258  4.100e-03    6.299  2.990e-10  [1.779e-02,3.386e-02]
alpha[1]   0.0000  9.156e-03    0.000    1.000 [-1.794e-02,1.794e-02]
gamma[1]   0.1707  1.601e-02   10.664  1.505e-26    [ 0.139,  0.202]
beta[1]    0.9098  9.672e-03   94.066    0.000    [ 0.891,  0.929]
=====

```

Covariance estimator: robust

Student's T Errors

Financial returns are often heavy tailed, and a Student's T distribution is a simple method to capture this feature. The call to `arch` changes the distribution from a Normal to a Student's T.

The standardized residuals appear to be heavy tailed with an estimated degree of freedom near 10. The log-likelihood also shows a large increase.

```

[7]: am = arch_model(returns, p=1, o=1, q=1, power=1.0, dist="Studentst")
res = am.fit(update_freq=5)
print(res.summary())

```

```

Iteration:      5,   Func. Count:      50,   Neg. LLF: 6728.995165345449
Iteration:     10,   Func. Count:      90,   Neg. LLF: 6722.151188120595
Optimization terminated successfully   (Exit mode 0)
      Current function value: 6722.151187386988
      Iterations: 11
      Function evaluations: 97
      Gradient evaluations: 11
      Constant Mean - TARCH/ZARCH Model Results
=====
Dep. Variable:              Adj Close      R-squared:              0.000
Mean Model:                 Constant Mean  Adj. R-squared:         0.000
Vol Model:                  TARCH/ZARCH    Log-Likelihood:        -6722.15
Distribution: Standardized Student's t    AIC:                   13456.3
Method:                     Maximum Likelihood  BIC:                   13495.4
                               No. Observations:              5030
Date:                       Wed, Apr 12 2023  Df Residuals:         5029
Time:                       15:58:56          Df Model:                 1
                               Mean Model
=====
              coef      std err          t      P>|t|      95.0% Conf. Int.
-----
mu           0.0323  2.364e-03    13.650  2.020e-42 [2.763e-02,3.690e-02]
              Volatility Model
=====
              coef      std err          t      P>|t|      95.0% Conf. Int.
-----
omega        0.0201  3.493e-03    5.744  9.249e-09 [1.322e-02,2.691e-02]
alpha[1]     1.4150e-08  8.223e-03  1.721e-06    1.000 [-1.612e-02,1.612e-02]
gamma[1]      0.1721  1.512e-02   11.385  4.978e-30 [ 0.143,  0.202]
beta[1]       0.9139  9.578e-03   95.415    0.000 [ 0.895,  0.933]
              Distribution

```

(continues on next page)

(continued from previous page)

	coef	std err	t	P> t	95.0% Conf. Int.
nu	7.9553	0.881	9.034	1.648e-19	[6.229, 9.681]

Covariance estimator: robust

1.2.3 Fixing Parameters

In some circumstances, fixed rather than estimated parameters might be of interest. A model-result-like class can be generated using the `fix()` method. The class returned is identical to the usual model result class except that information about inference (standard errors, t-stats, etc) is not available.

In the example, I fix the parameters to a symmetric version of the previously estimated model.

```
[8]: fixed_res = am.fix([0.0235, 0.01, 0.06, 0.0, 0.9382, 8.0])
print(fixed_res.summary())
```

```

Constant Mean - TARCH/ZARCH Model Results
=====
Dep. Variable:                Adj Close    R-squared:                --
Mean Model:                  Constant Mean  Adj. R-squared:           --
Vol Model:                   TARCH/ZARCH    Log-Likelihood:          -6908.93
Distribution:                 Standardized Student's t  AIC:                    13829.9
Method:                      User-specified Parameters  BIC:                    13869.0
                               No. Observations:          5030

Date:                        Wed, Apr 12 2023
Time:                        15:58:56


Mean Model
=====
coef
-----
mu                0.0235
Volatility Model
=====
coef
-----
omega            0.0100
alpha[1]         0.0600
gamma[1]         0.0000
beta[1]          0.9382
Distribution
=====
coef
-----
nu                8.0000
=====
```

Results generated with user-specified parameters.
Std. errors not available when the model is not estimated,


```
[9]: import pandas as pd
```

```
df = pd.concat([res.conditional_volatility, fixed_res.conditional_volatility], axis=1)
df.columns = ["Estimated", "Fixed"]
subplot = df.plot()
subplot.set_xlim(xlim)
```

```
[9]: (10596.0, 17896.0)
```



1.2.4 Building a Model From Components

Models can also be systematically assembled from the three model components:

- A mean model (`arch.mean`)
 - Zero mean (`ZeroMean`) - useful if using residuals from a model estimated separately
 - Constant mean (`ConstantMean`) - common for most liquid financial assets
 - Autoregressive (`ARX`) with optional exogenous regressors
 - Heterogeneous (`HARX`) autoregression with optional exogenous regressors
 - Exogenous regressors only (`LS`)
- A volatility process (`arch.volatility`)
 - ARCH (`ARCH`)
 - GARCH (`GARCH`)
 - GJR-GARCH (`GARCH` using `o` argument)
 - TARCH/ZARCH (`GARCH` using `power` argument set to 1)
 - Power GARCH and Asymmetric Power GARCH (`GARCH` using `power`)
 - Exponentially Weighted Moving Average Variance with estimated coefficient (`EWMAVariance`)
 - Heterogeneous ARCH (`HARCH`)
 - Parameterless Models
 - * Exponentially Weighted Moving Average Variance, known as RiskMetrics (`EWMAVariance`)

* Weighted averages of EWMA, known as the RiskMetrics 2006 methodology (RiskMetrics2006)


- A distribution (`arch.distribution`)
 - Normal (`Normal`)
 - Standardized Students’s T (`StudentsT`)

Mean Models

The first choice is the mean model. For many liquid financial assets, a constant mean (or even zero) is adequate. For other series, such as inflation, a more complicated model may be required. These examples make use of Core CPI downloaded from the [Federal Reserve Economic Data](#) site.

```
[10]: import arch.data.core_cpi

core_cpi = arch.data.core_cpi.load()
ann_inflation = 100 * core_cpi.CPILFESL.pct_change(12).dropna()
fig = ann_inflation.plot()
```



All mean models are initialized with constant variance and normal errors. For ARX models, the `lags` argument specifies the lags to include in the model.

```
[11]: from arch.univariate import ARX

ar = ARX(100 * ann_inflation, lags=[1, 3, 12])
print(ar.fit().summary())
```

```

      AR - Constant Variance Model Results
=====
Dep. Variable:          CPILFESL    R-squared:                0.991
Mean Model:              AR        Adj. R-squared:            0.991
Vol Model:      Constant Variance  Log-Likelihood:        -3299.84
Distribution:          Normal      AIC:                      6609.68
Method:      Maximum Likelihood    BIC:                      6632.57
                                           No. Observations:      719
Date:      Wed, Apr 12 2023         Df Residuals:          715
Time:      15:58:57                 Df Model:              4

```

(continues on next page)

(continued from previous page)

Mean Model					
	coef	std err	t	P> t	95.0% Conf. Int.
Const	4.0216	2.030	1.981	4.762e-02	[4.218e-02, 8.001]
CPILFESL[1]	1.1921	3.475e-02	34.306	6.315e-258	[1.124, 1.260]
CPILFESL[3]	-0.1798	4.076e-02	-4.411	1.030e-05	[-0.260,-9.989e-02]
CPILFESL[12]	-0.0232	1.370e-02	-1.692	9.058e-02	[-5.002e-02,3.666e-03]
Volatility Model					
	coef	std err	t	P> t	95.0% Conf. Int.
sigma2	567.4180	64.487	8.799	1.381e-18	[4.410e+02,6.938e+02]

Covariance estimator: White's Heteroskedasticity Consistent Estimator

Volatility Processes

Volatility processes can be added a a mean model using the volatility property. This example adds an ARCH(5) process to model volatility. The arguments `iter` and `disp` are used in `fit()` to suppress estimation output.

```
[12]: from arch.univariate import ARCH, GARCH
```

```
ar.volatility = ARCH(p=5)
res = ar.fit(update_freq=0, disp="off")
print(res.summary())
```

AR - ARCH Model Results					
=====					
Dep. Variable:	CPILFESL	R-squared:	0.991		
Mean Model:	AR	Adj. R-squared:	0.991		
Vol Model:	ARCH	Log-Likelihood:	-3174.60		
Distribution:	Normal	AIC:	6369.19		
Method:	Maximum Likelihood	BIC:	6414.97		
		No. Observations:	719		
Date:	Wed, Apr 12 2023	Df Residuals:	715		
Time:	15:58:57	Df Model:	4		
Mean Model					
=====					
	coef	std err	t	P> t	95.0% Conf. Int.

Const	2.8500	1.883	1.513	0.130	[-0.841, 6.541]
CPILFESL[1]	1.0859	3.534e-02	30.726	2.594e-207	[1.017, 1.155]
CPILFESL[3]	-0.0788	3.855e-02	-2.045	4.085e-02	[-0.154,-3.282e-03]
CPILFESL[12]	-0.0189	1.157e-02	-1.630	0.103	[-4.154e-02,3.820e-03]
Volatility Model					
=====					
	coef	std err	t	P> t	95.0% Conf. Int.

omega	76.8684	16.016	4.799	1.592e-06	[45.477,1.083e+02]

(continues on next page)

(continued from previous page)

```


alpha[1]      0.1345  4.003e-02    3.359  7.827e-04 [5.600e-02,  0.213]
alpha[2]      0.2280  6.284e-02    3.628  2.860e-04 [ 0.105,  0.351]
alpha[3]      0.1838  6.802e-02    2.702  6.894e-03 [5.047e-02,  0.317]
alpha[4]      0.2538  7.826e-02    3.242  1.185e-03 [ 0.100,  0.407]
alpha[5]      0.1954  7.091e-02    2.756  5.856e-03 [5.643e-02,  0.334]
=====

```

Covariance estimator: robust

Plotting the standardized residuals and the conditional volatility shows some large (in magnitude) errors, even when standardized.

```
[13]: fig = res.plot()
```



Distributions

Finally the distribution can be changed from the default normal to a standardized Student's T using the `distribution` property of a mean model.

The Student's t distribution improves the model, and the degree of freedom is estimated to be near 8.

```

[14]: from arch.univariate import StudentsT

ar.distribution = StudentsT()
res = ar.fit(update_freq=0, disp="off")
print(res.summary())

```

```

AR - ARCH Model Results
=====
Dep. Variable:          CPILFESL    R-squared:                0.991
Mean Model:              AR         Adj. R-squared:           0.991
Vol Model:               ARCH       Log-Likelihood:         -3168.25
Distribution: Standardized Student's t AIC:                6358.51
Method:                  Maximum Likelihood BIC:                6408.86
                                     No. Observations:          719
Date:                    Wed, Apr 12 2023 Df Residuals:        715

```

(continues on next page)

(continued from previous page)

Time: 15:58:58 Df Model: 4

Mean Model

	coef	std err	t	P> t	95.0% Conf. Int.
Const	3.1221	1.861	1.678	9.342e-02	[-0.525, 6.770]
CPILFESL[1]	1.0843	3.525e-02	30.762	8.338e-208	[1.015, 1.153]
CPILFESL[3]	-0.0730	3.873e-02	-1.885	5.947e-02	[-0.149, 2.916e-03]
CPILFESL[12]	-0.0236	1.316e-02	-1.791	7.331e-02	[-4.935e-02, 2.224e-03]

Volatility Model

	coef	std err	t	P> t	95.0% Conf. Int.
omega	87.3616	20.628	4.235	2.285e-05	[46.931, 1.278e+02]
alpha[1]	0.1715	5.064e-02	3.386	7.090e-04	[7.221e-02, 0.271]
alpha[2]	0.2202	6.394e-02	3.443	5.743e-04	[9.485e-02, 0.345]
alpha[3]	0.1547	6.327e-02	2.445	1.447e-02	[3.071e-02, 0.279]
alpha[4]	0.2117	7.287e-02	2.905	3.677e-03	[6.884e-02, 0.354]
alpha[5]	0.1959	7.854e-02	2.494	1.261e-02	[4.198e-02, 0.350]

Distribution

	coef	std err	t	P> t	95.0% Conf. Int.
nu	9.0448	3.366	2.687	7.208e-03	[2.447, 15.642]

Covariance estimator: robust

1.2.5 WTI Crude

The next example uses West Texas Intermediate Crude data from FRED. Three models are fit using alternative distributional assumptions. The results are printed, where we can see that the normal has a much lower log-likelihood than either the Standard Student's T or the Standardized Skew Student's T – however, these two are fairly close. The closeness of the T and the Skew T indicate that returns are not heavily skewed.

```
[15]: from collections import OrderedDict

import arch.data.wti

crude = arch.data.wti.load()
crude_ret = 100 * crude.DCOILWTICO.dropna().pct_change().dropna()
res_normal = arch_model(crude_ret).fit(dis="off")
res_t = arch_model(crude_ret, dist="t").fit(dis="off")
res_skewt = arch_model(crude_ret, dist="skewt").fit(dis="off")
lls = pd.Series(
    OrderedDict(
        (
            ("normal", res_normal.loglikelihood),
            ("t", res_t.loglikelihood),
            ("skewt", res_skewt.loglikelihood),
        )
    )
)
```

(continues on next page)

(continued from previous page)

```

    )
)
print(l1s)
params = pd.DataFrame(
    OrderedDict(
        (
            ("normal", res_normal.params),
            ("t", res_t.params),
            ("skewt", res_skewt.params),
        )
    )
)
params

```

```

normal    -18165.858870
t          -17919.643916
skewt     -17916.669052
dtype: float64

```

```

[15]:
      normal      t      skewt
alpha[1]  0.085627  0.064980  0.064889
beta[1]   0.909098  0.927950  0.928215
eta       NaN      NaN    6.186541
lambda    NaN      NaN   -0.036986
mu        0.046682  0.056438  0.040928
nu        NaN      6.178598    NaN
omega     0.055806  0.048516  0.047683


```

The standardized residuals can be computed by dividing the residuals by the conditional volatility. These are plotted along with the (unstandardized, but scaled) residuals. The non-standardized residuals are more peaked in the center indicating that the distribution is somewhat more heavy tailed than that of the standardized residuals.

```

[16]: std_resid = res_normal.resid / res_normal.conditional_volatility
unit_var_resid = res_normal.resid / res_normal.resid.std()
df = pd.concat([std_resid, unit_var_resid], axis=1)
df.columns = ["Std Resids", "Unit Variance Resids"]
subplot = df.plot(kind="kde", xlim=(-4, 4))

```



1.2.6 Simulation

All mean models expose a method to simulate returns from assuming the model is correctly specified. There are two required parameters, `params` which are the model parameters, and `nobs`, the number of observations to produce.

Below we simulate from a GJR-GARCH(1,1) with Skew- t errors using parameters estimated on the WTI series. The simulation returns a `DataFrame` with 3 columns:

- `data`: The simulated data, which includes any mean dynamics.
- `volatility`: The conditional volatility series
- `errors`: The simulated errors generated to produce the model. The errors are the difference between the data and its conditional mean, and can be transformed into the standardized errors by dividing by the volatility.

```
[17]: res = arch_model(crude_ret, p=1, o=1, q=1, dist="skewt").fit(disp="off")
      pd.DataFrame(res.params)
```

```
[17]:      params
mu      0.029365
omega    0.044374
alpha[1] 0.044344
gamma[1] 0.036104
beta[1]   0.931280
eta      6.211281
lambda  -0.041616
```

```
[18]: sim_mod = arch_model(None, p=1, o=1, q=1, dist="skewt")
```

```
sim_data = sim_mod.simulate(res.params, 1000)
sim_data.head()
```

```
[18]:      data  volatility  errors
0  2.729532    2.293291  2.700167
1  1.310209    2.294658  1.280844
2 -3.711848    2.240700 -3.741213
3  2.212867    2.417869  2.183502
4  2.987078    2.387496  2.957713
```

Simulations can be reproduced using a NumPy `RandomState`. This requires constructing a model from components where the `RandomState` instance is passed into to the distribution when the model is created.

The cell below contains code that builds a model with a constant mean, GJR-GARCH volatility and Skew t errors initialized with a user-provided `RandomState`. Saving the initial state allows it to be restored later so that the simulation can be run with the same random values.

```
[19]: import numpy as np
      from arch.univariate import GARCH, ConstantMean, SkewStudent

      rs = np.random.RandomState([892380934, 189201902, 129129894, 9890437])
      # Save the initial state to reset later
      state = rs.get_state()

      dist = SkewStudent(seed=rs)
      vol = GARCH(p=1, o=1, q=1)
      repro_mod = ConstantMean(None, volatility=vol, distribution=dist)
```

(continues on next page)

(continued from previous page)

```
repro_mod.simulate(res.params, 1000).head()
```

```
[19]:      data  volatility  errors
0  1.616836   4.787697  1.587470
1  4.106780   4.637129  4.077415
2  4.530200   4.561457  4.500834
3  2.284833   4.507739  2.255468
4  3.378519   4.381016  3.349153
```

Resetting the state using `set_state` shows that calling `simulate` using the same underlying state in the `RandomState` produces the same objects.

```
[20]: # Reset the state to the initial state
rs.set_state(state)
repro_mod.simulate(res.params, 1000).head()
```

```
[20]:      data  volatility  errors
0  1.616836   4.787697  1.587470
1  4.106780   4.637129  4.077415
2  4.530200   4.561457  4.500834
3  2.284833   4.507739  2.255468
4  3.378519   4.381016  3.349153
```

1.3 Forecasting

Multi-period forecasts can be easily produced for ARCH-type models using forward recursion, with some caveats. In particular, models that are non-linear in the sense that they do not evolve using squares or residuals do not normally have analytically tractable multi-period forecasts available.

All models support three methods of forecasting:

- **Analytical:** analytical forecasts are always available for the 1-step ahead forecast due to the structure of ARCH-type models. Multi-step analytical forecasts are only available for model which are linear in the square of the residual, such as GARCH or HARCH.
- **Simulation:** simulation-based forecasts are always available for any horizon, although they are only useful for horizons larger than 1 since the first out-of-sample forecast from an ARCH-type model is always fixed. Simulation-based forecasts make use of the structure of an ARCH-type model to forward simulate using the assumed distribution of residuals, e.g., a Normal or Student's t .
- **Bootstrap:** bootstrap-based forecasts are similar to simulation based forecasts except that they make use of the standardized residuals from the actual data used in the estimation rather than assuming a specific distribution. Like simulation-base forecasts, bootstrap-based forecasts are only useful for horizons larger than 1. Additionally, the bootstrap forecasting method requires a minimal amount of in-sample data to use prior to producing the forecasts.

This document will use a standard GARCH(1,1) with a constant mean to explain the choices available for forecasting. The model can be described as

$$r_t = \mu + \epsilon_t \quad (1.4)$$

$$\epsilon_t = \sigma_t e_t \quad (1.5)$$

$$\sigma_t^2 = \omega + \alpha \epsilon_{t-1}^2 + \beta \sigma_{t-1}^2 \quad (1.6)$$

$$e_t \sim N(0, 1) \quad (1.7)$$

In code this model can be constructed using data from the S&P 500 using

```
from arch import arch_model
import datetime as dt
import pandas_datareader.data as web
start = dt.datetime(2000,1,1)
end = dt.datetime(2014,1,1)
sp500 = web.get_data_yahoo('^GSPC', start=start, end=end)
returns = 100 * sp500['Adj Close'].pct_change().dropna()
am = arch_model(returns, vol='Garch', p=1, o=0, q=1, dist='Normal')
```

The model will be estimated using the first 10 years to estimate parameters and then forecasts will be produced for the final 5.

```
split_date = dt.datetime(2010,1,1)
res = am.fit(last_obs=split_date)
```

1.3.1 Analytical Forecasts

Analytical forecasts are available for most models that evolve in terms of the squares of the model residuals, e.g., GARCH, HARCH, etc. These forecasts exploit the relationship $E_t[\epsilon_{t+1}^2] = \sigma_{t+1}^2$ to recursively compute forecasts.

Variance forecasts are constructed for the conditional variances as

$$\sigma_{t+1}^2 = \omega + \alpha \epsilon_t^2 + \beta \sigma_t^2 \quad (1.8)$$

$$\sigma_{t+h}^2 = \omega + \alpha E_t[\epsilon_{t+h-1}^2] + \beta E_t[\sigma_{t+h-1}^2] \quad h \geq 2 \quad (1.9)$$

$$= \omega + (\alpha + \beta) E_t[\sigma_{t+h-1}^2] \quad h \geq 2 \quad (1.10)$$

```
forecasts = res.forecast(horizon=5, start=split_date)
forecasts.variance[split_date:].plot()
```

1.3.2 Simulation Forecasts

Simulation-based forecasts use the model random number generator to simulate draws of the standardized residuals, e_{t+h} . These are used to generate a pre-specified number of paths of the variances which are then averaged to produce the forecasts. In models like GARCH which evolve in the squares of the residuals, there are few advantages to simulation-based forecasting. These methods are more valuable when producing multi-step forecasts from models that do not have closed form multi-step forecasts such as EGARCH models.

Assume there are B simulated paths. A single simulated path is generated using

$$\sigma_{t+h,b}^2 = \omega + \alpha \epsilon_{t+h-1,b}^2 + \beta \sigma_{t+h-1,b}^2 \quad (1.11)$$

$$\epsilon_{t+h,b} = e_{t+h,b} \sqrt{\sigma_{t+h,b}^2} \quad (1.12)$$

where the simulated shocks are $e_{t+1,b}, e_{t+2,b}, \dots, e_{t+h,b}$ where b is included to indicate that the simulations are independent across paths. Note that the first residual, ϵ_t , is in-sample and so is not simulated.

The final variance forecasts are then computed using the B simulations

$$E_t[\epsilon_{t+h}^2] = \sigma_{t+h}^2 = B^{-1} \sum_{b=1}^B \sigma_{t+h,b}^2. \quad (1.13)$$

```
forecasts = res.forecast(horizon=5, start=split_date, method='simulation')
```

1.3.3 Bootstrap Forecasts

Bootstrap-based forecasts are virtually identical to simulation-based forecasts except that the standardized residuals are generated by the model. These standardized residuals are generated using the observed data and the estimated parameters as

$$\hat{e}_t = \frac{r_t - \hat{\mu}}{\hat{\sigma}_t} \quad (1.14)$$

The generation scheme is identical to the simulation-based method except that the simulated shocks are drawn (i.i.d., with replacement) from $\hat{e}_1, \hat{e}_2, \dots, \hat{e}_t$. so that only data available at time t are used to simulate the paths.

1.3.4 Forecasting Options

The `forecast()` method is attached to a model fit result.`

- **params** - The model parameters used to forecast the mean and variance. If not specified, the parameters estimated during the call to `fit` the produced the result are used.
- **horizon** - A positive integer value indicating the maximum horizon to produce forecasts.
- **start** - A positive integer or, if the input to the mode is a `DataFrame`, a date (string, `datetime`, `datetime64` or `Timestamp`). Forecasts are produced from `start` until the end of the sample. If not provided, `start` is set to the length of the input data minus 1 so that only 1 forecast is produced.
- **align** - One of 'origin' (default) or 'target' that describes how the forecasts aligned in the output. Origin aligns forecasts to the last observation used in producing the forecast, while target aligns forecasts to the observation index that is being forecast.
- **method** - One of 'analytic' (default), 'simulation' or 'bootstrap' that describes the method used to produce the forecasts. Not all methods are available for all horizons.
- **simulations** - A non-negative integer indicating the number of simulation to use when method is 'simulation' or 'bootstrap'

1.3.5 Understanding Forecast Output

Any call to `forecast()` returns a `ARCHModelForecast` object with has 3 core attributes and 1 which may be useful when using simulation- or bootstrap-based forecasts.

The three core attributes are

- **mean** - The forecast conditional mean.
- **variance** - The forecast conditional variance.
- **residual_variance** - The forecast conditional variance of residuals. This will differ from `variance` whenever the model has dynamics (e.g. an AR model) for horizons larger than 1.

Each attribute contains a `DataFrame` with a common structure.

```
print(forecasts.variance.tail())
```

which returns

	h.1	h.2	h.3	h.4	h.5
Date					
2013-12-24	0.489534	0.495875	0.501122	0.509194	0.518614
2013-12-26	0.474691	0.480416	0.483664	0.491932	0.502419
2013-12-27	0.447054	0.454875	0.462167	0.467515	0.475632
2013-12-30	0.421528	0.430024	0.439856	0.448282	0.457368
2013-12-31	0.407544	0.415616	0.422848	0.430246	0.439451

The values in the columns h.1 are one-step ahead forecast, while values in h.2, ..., h.5 are 2, ..., 5-observation ahead forecasts. The output is aligned so that the Date column is the final data used to generate the forecast, so that h.1 in row 2013-12-31 is the one-step ahead forecast made using data **up to and including** December 31, 2013.

By default forecasts are only produced for observations after the final observation used to estimate the model.

```
day = dt.timedelta(1)
print(forecasts.variance[split_date - 5 * day:split_date + 5 * day])
```

which produces

	h.1	h.2	h.3	h.4	h.5
Date					
2009-12-28	NaN	NaN	NaN	NaN	NaN
2009-12-29	NaN	NaN	NaN	NaN	NaN
2009-12-30	NaN	NaN	NaN	NaN	NaN
2009-12-31	NaN	NaN	NaN	NaN	NaN
2010-01-04	0.739303	0.741100	0.744529	0.746940	0.752688
2010-01-05	0.695349	0.702488	0.706812	0.713342	0.721629
2010-01-06	0.649343	0.654048	0.664055	0.672742	0.681263

The output will always have as many rows as the data input. Values that are not forecast are nan filled.

1.3.6 Output Classes

<code>ARCHModelForecast(index, start_index, mean, ...)</code>	Container for forecasts from an ARCH Model
<code>ARCHModelForecastSimulation(index, values, ...)</code>	Container for a simulation or bootstrap-based forecasts from an ARCH Model

arch.univariate.base.ARCHModelForecast

```
class arch.univariate.base.ARCHModelForecast(index, start_index, mean, variance, residual_variance,
                                              simulated_paths=None, simulated_variances=None,
                                              simulated_residual_variances=None,
                                              simulated_residuals=None, align='origin', *,
                                              reindex=False)
```

Container for forecasts from an ARCH Model

Parameters

index : {list, ndarray}

mean : ndarray

variance : ndarray

`residual_variance` : ndarray
`simulated_paths` : ndarray, optional
`simulated_variances` : ndarray, optional
`simulated_residual_variances` : ndarray, optional
`simulated_residuals` : ndarray, optional
`align` : {'origin', 'target'}

Methods

Properties

<i>mean</i>	Forecast values for the conditional mean of the process
<i>residual_variance</i>	Forecast values for the conditional variance of the residuals
<i>simulations</i>	Detailed simulation results if using a simulation-based method
<i>variance</i>	Forecast values for the conditional variance of the process

`arch.univariate.base.ARCHModelForecast.mean`

property `ARCHModelForecast.mean` : `DataFrame`

Forecast values for the conditional mean of the process

Return type

`DataFrame`

`arch.univariate.base.ARCHModelForecast.residual_variance`

property `ARCHModelForecast.residual_variance` : `DataFrame`

Forecast values for the conditional variance of the residuals

Return type

`DataFrame`

arch.univariate.base.ARCHModelForecast.simulations

property ARCHModelForecast.**simulations** : *ARCHModelForecastSimulation*

Detailed simulation results if using a simulation-based method

Returns

Container for simulation results

Return type

ARCHModelForecastSimulation

arch.univariate.base.ARCHModelForecast.variance

property ARCHModelForecast.**variance** : *DataFrame*

Forecast values for the conditional variance of the process

Return type

DataFrame

arch.univariate.base.ARCHModelForecastSimulation

class arch.univariate.base.**ARCHModelForecastSimulation**(*index, values, residuals, variances, residual_variances*)

Container for a simulation or bootstrap-based forecasts from an ARCH Model

Parameters

index

values

residuals

variances

residual_variances

Methods**Properties**

<i>index</i>	The index aligned to dimension 0 of the simulation paths
<i>residual_variances</i>	Simulated variance of the residuals
<i>residuals</i>	Simulated residuals used to produce the values
<i>values</i>	The values of the process
<i>variances</i>	Simulated variances of the values

arch.univariate.base.ARCHModelForecastSimulation.index

property ARCHModelForecastSimulation.**index** : `Index`

The index aligned to dimension 0 of the simulation paths

Return type

`Index`

arch.univariate.base.ARCHModelForecastSimulation.residual_variances

property ARCHModelForecastSimulation.**residual_variances** : `numpy.ndarray` | `None`

Simulated variance of the residuals

Return type

Optional[`ndarray`]

arch.univariate.base.ARCHModelForecastSimulation.residuals

property ARCHModelForecastSimulation.**residuals** : `numpy.ndarray` | `None`

Simulated residuals used to produce the values

Return type

Optional[`ndarray`]

arch.univariate.base.ARCHModelForecastSimulation.values

property ARCHModelForecastSimulation.**values** : `numpy.ndarray` | `None`

The values of the process

Return type

Optional[`ndarray`]

arch.univariate.base.ARCHModelForecastSimulation.variances

property ARCHModelForecastSimulation.**variances** : `numpy.ndarray` | `None`

Simulated variances of the values

Return type

Optional[`ndarray`]

1.4 Volatility Forecasting

This setup code is required to run in an IPython notebook

```
[1]: %matplotlib inline
import matplotlib.pyplot as plt
import seaborn as sns

sns.set_style("darkgrid")
```

(continues on next page)

(continued from previous page)

```
plt.rc("figure", figsize=(16, 6))
plt.rc("savefig", dpi=90)
plt.rc("font", family="sans-serif")
plt.rc("font", size=14)
```

1.4.1 Future Forecast Shape Changes

WARNING

The future behavior of `forecast` is changing.

Versions of `arch` before 4.19 defaulted to returning forecast values with the same shape as the data used to fit the model. While this is convenient it is also computationally wasteful. This is especially true when using `method` is "simulation" or "bootstrap". In future version of `arch`, the default behavior will change to only returning the minimal `DataFrame` that is needed to contain the forecast results. In the current version of `arch`, calling `forecast()` without the `reindex` keyword argument produces a `FutureWarning`. You can silence the future warning by:

- Using `reindex=False` which uses the future behavior.
- Using `reindex=True` which uses the legacy behavior.
- Importing from `arch.__future__ import reindexing` which will set the default to `False` and silence the warning.

1.4.2 Data

These examples make use of S&P 500 data from Yahoo! that is available from `arch.data.sp500`.

```
[2]: import datetime as dt
import sys

import arch.data.sp500
import numpy as np
import pandas as pd
from arch import arch_model

data = arch.data.sp500.load()
market = data["Adj Close"]
returns = 100 * market.pct_change().dropna()
```

1.4.3 Basic Forecasting

Forecasts can be generated for standard GARCH(p,q) processes using any of the three forecast generation methods:

- Analytical
- Simulation-based
- Bootstrap-based

By default forecasts will only be produced for the final observation in the sample so that they are out-of-sample.

Forecasts start with specifying the model and estimating parameters.

```
[3]: am = arch_model(returns, vol="Garch", p=1, o=0, q=1, dist="Normal")
      res = am.fit(update_freq=5)

Iteration:      5,   Func. Count:    35,   Neg. LLF: 6970.282172935112
Iteration:     10,   Func. Count:    63,   Neg. LLF: 6936.718477483884
Optimization terminated successfully   (Exit mode 0)
      Current function value: 6936.718476988963
      Iterations: 11
      Function evaluations: 68
      Gradient evaluations: 11
```

```
[4]: forecasts = res.forecast(reindex=False)
```

Forecasts are contained in an ARCHModelForecast object which has 4 attributes:

- `mean` - The forecast means
- `residual_variance` - The forecast residual variances, that is $E_t[\epsilon_{t+h}^2]$
- `variance` - The forecast variance of the process, $E_t[r_{t+h}^2]$. The variance will differ from the residual variance whenever the model has mean dynamics, e.g., in an AR process.
- `simulations` - An object that contains detailed information about the simulations used to generate forecasts. Only used if the forecast method is set to 'simulation' or 'bootstrap'. If using 'analytical' (the default), this is None.

The three main outputs are all returned in DataFrames with columns of the form `h.#` where `#` is the number of steps ahead. That is, `h.1` corresponds to one-step ahead forecasts while `h.10` corresponds to 10-steps ahead.

The default forecast only produces 1-step ahead forecasts.

```
[5]: print(forecasts.mean.iloc[-3:])
      print(forecasts.residual_variance.iloc[-3:])
      print(forecasts.variance.iloc[-3:])
```

```

              h.1
Date
2018-12-31    0.056353
              h.1
Date
2018-12-31    3.59647
              h.1
Date
2018-12-31    3.59647
```

Longer horizon forecasts can be computed by passing the parameter `horizon`.


```
[6]: forecasts = res.forecast(horizon=5, reindex=False)
print(forecasts.residual_variance.iloc[-3:])
```

	h.1	h.2	h.3	h.4	h.5
Date					
2018-12-31	3.59647	3.568502	3.540887	3.513621	3.4867

If you fail to set reindex you will see a warning.

```
[7]: forecasts = res.forecast(horizon=5)
```

```
c:\git\arch\arch\__future__\utility.py:11: FutureWarning:
The default for reindex is True. After September 2021 this will change to
False. Set reindex to True or False to silence this message. Alternatively,
you can use the import comment
```

```
from arch.__future__ import reindexing
```

to globally set reindex to True and silence this warning.

```
warnings.warn(
```

When not specified, or if reindex is True, then values that are not computed are nan-filled.

```
[8]: print(forecasts.residual_variance.iloc[-3:])
```

	h.1	h.2	h.3	h.4	h.5
Date					
2018-12-27	NaN	NaN	NaN	NaN	NaN
2018-12-28	NaN	NaN	NaN	NaN	NaN
2018-12-31	3.59647	3.568502	3.540887	3.513621	3.4867

1.4.4 Alternative Forecast Generation Schemes

Fixed Window Forecasting

Fixed-windows forecasting uses data up to a specified date to generate all forecasts after that date. This can be implemented by passing the entire data in when initializing the model and then using `last_obs` when calling `fit`. `forecast()` will, by default, produce forecasts after this final date.

Note `last_obs` follow Python sequence rules so that the actual date in `last_obs` is not in the sample.

```
[9]: res = am.fit(last_obs="2011-1-1", update_freq=5)
forecasts = res.forecast(horizon=5, reindex=False)
print(forecasts.variance.dropna().head())
```

```
Iteration:      5,   Func. Count:      34,   Neg. LLF: 4578.713295409127
Iteration:     10,   Func. Count:      63,   Neg. LLF: 4555.338451419905
Optimization terminated successfully   (Exit mode 0)
      Current function value: 4555.285110045323
      Iterations: 14
      Function evaluations: 83
      Gradient evaluations: 14
      h.1      h.2      h.3      h.4      h.5
```

(continues on next page)

(continued from previous page)

Date					
2010-12-31	0.381757	0.390905	0.399988	0.409008	0.417964
2011-01-03	0.451724	0.460381	0.468976	0.477512	0.485987
2011-01-04	0.428416	0.437236	0.445994	0.454691	0.463326
2011-01-05	0.420554	0.429429	0.438242	0.446993	0.455683
2011-01-06	0.402483	0.411486	0.420425	0.429301	0.438115

Rolling Window Forecasting

Rolling window forecasts use a fixed sample length and then produce one-step from the final observation. These can be implemented using `first_obs` and `last_obs`.

```
[10]: index = returns.index
start_loc = 0
end_loc = np.where(index >= "2010-1-1")[0].min()
forecasts = {}
for i in range(20):
    sys.stdout.write(".")
    sys.stdout.flush()
    res = am.fit(first_obs=i, last_obs=i + end_loc, disp="off")
    temp = res.forecast(horizon=3, reindex=False).variance
    fcast = temp.iloc[0]
    forecasts[fcast.name] = fcast
print()
print(pd.DataFrame(forecasts).T)
```

```
...
          h.1      h.2      h.3
2009-12-31  0.615314  0.621743  0.628133
2010-01-04  0.751747  0.757343  0.762905
2010-01-05  0.710453  0.716315  0.722142
2010-01-06  0.666244  0.672346  0.678411
2010-01-07  0.634424  0.640706  0.646949
2010-01-08  0.600109  0.606595  0.613040
2010-01-11  0.565514  0.572212  0.578869
2010-01-12  0.599561  0.606051  0.612501
2010-01-13  0.608309  0.614748  0.621148
2010-01-14  0.575065  0.581756  0.588406
2010-01-15  0.629890  0.636245  0.642561
2010-01-19  0.695074  0.701042  0.706974
2010-01-20  0.737154  0.742908  0.748627
2010-01-21  0.954167  0.958725  0.963255
2010-01-22  1.253453  1.256401  1.259332
2010-01-25  1.178691  1.182043  1.185374
2010-01-26  1.112205  1.115886  1.119545
2010-01-27  1.051295  1.055327  1.059335
2010-01-28  1.085678  1.089512  1.093324
2010-01-29  1.085786  1.089594  1.093378
```

Recursive Forecast Generation

Recursive is similar to rolling except that the initial observation does not change. This can be easily implemented by dropping the `first_obs` input.

```
[11]: import numpy as np
import pandas as pd

index = returns.index
start_loc = 0
end_loc = np.where(index >= "2010-1-1")[0].min()
forecasts = {}
for i in range(20):
    sys.stdout.write(".")
    sys.stdout.flush()
    res = am.fit(last_obs=i + end_loc, disp="off")
    temp = res.forecast(horizon=3, reindex=False).variance
    fcast = temp.iloc[0]
    forecasts[fcast.name] = fcast
print()
print(pd.DataFrame(forecasts).T)
```

```
...
          h.1      h.2      h.3
2009-12-31  0.615314  0.621743  0.628133
2010-01-04  0.751723  0.757321  0.762885
2010-01-05  0.709956  0.715791  0.721591
2010-01-06  0.666057  0.672146  0.678197
2010-01-07  0.634503  0.640776  0.647011
2010-01-08  0.600417  0.606893  0.613329
2010-01-11  0.565684  0.572369  0.579014
2010-01-12  0.599963  0.606438  0.612874
2010-01-13  0.608558  0.614982  0.621366
2010-01-14  0.575020  0.581639  0.588217
2010-01-15  0.629696  0.635989  0.642244
2010-01-19  0.694735  0.700656  0.706541
2010-01-20  0.736509  0.742193  0.747842
2010-01-21  0.952751  0.957246  0.961713
2010-01-22  1.251145  1.254050  1.256936
2010-01-25  1.176864  1.180162  1.183441
2010-01-26  1.110848  1.114497  1.118124
2010-01-27  1.050102  1.054077  1.058028
2010-01-28  1.084669  1.088454  1.092216
2010-01-29  1.085003  1.088783  1.092541
```

1.4.5 TARCH

Analytical Forecasts

All ARCH-type models have one-step analytical forecasts. Longer horizons only have closed forms for specific models. TARCH models do not have closed-form (analytical) forecasts for horizons larger than 1, and so simulation or bootstrapping is required. Attempting to produce forecasts for horizons larger than 1 using `method='analytical'` results in a `ValueError`.

```
[12]: # TARCH specification
am = arch_model(returns, vol="GARCH", power=2.0, p=1, o=1, q=1)
res = am.fit(update_freq=5)
forecasts = res.forecast(reindex=False)
print(forecasts.variance.iloc[-1])

Iteration:      5,   Func. Count:    40,   Neg. LLF: 6846.496665348549
Iteration:     10,   Func. Count:    75,   Neg. LLF: 6822.883179474602
Optimization terminated successfully   (Exit mode 0)
      Current function value: 6822.882823372691
      Iterations: 13
      Function evaluations: 93
      Gradient evaluations: 13
h.1      3.010188
Name: 2018-12-31 00:00:00, dtype: float64
```


Simulation Forecasts

When using simulation- or bootstrap-based forecasts, an additional attribute of an `ARCHModelForecast` object is meaningful – `simulation`.

```
[13]: import matplotlib.pyplot as plt


fig, ax = plt.subplots(1, 1)
var_2016 = res.conditional_volatility["2016"] ** 2.0
subplot = var_2016.plot(ax=ax, title="Conditional Variance")
subplot.set_xlim(var_2016.index[0], var_2016.index[-1])

[13]: (16804.0, 17165.0)
```



```
[14]: forecasts = res.forecast(horizon=5, method="simulation", reindex=False)
      sims = forecasts.simulations


      x = np.arange(1, 6)
      lines = plt.plot(x, sims.residual_variances[-1, ::5].T, color="#9cb2d6", alpha=0.5)
      lines[0].set_label("Simulated path")
      line = plt.plot(x, forecasts.variance.iloc[-1].values, color="#002868")
      line[0].set_label("Expected variance")
      plt.gca().set_xticks(x)
      plt.gca().set_xlim(1, 5)
      legend = plt.legend()
```



```
[15]: import seaborn as sns

      sns.boxplot(data=sims.variances[-1])

[15]: <AxesSubplot:>
```




Bootstrap Forecasts

Bootstrap-based forecasts are nearly identical to simulation-based forecasts except that the values used to simulate the process are computed from historical data rather than using the assumed distribution of the residuals. Forecasts produced using this method also return an `ARCHModelForecastSimulation` containing information about the simulated paths.

```
[16]: forecasts = res.forecast(horizon=5, method="bootstrap", reindex=False)
      sims = forecasts.simulations

      lines = plt.plot(x, sims.residual_variances[-1, ::5].T, color="#9cb2d6", alpha=0.5)
      lines[0].set_label("Simulated path")
      line = plt.plot(x, forecasts.variance.iloc[-1].values, color="#002868")
      line[0].set_label("Expected variance")
      plt.gca().set_xticks(x)
      plt.gca().set_xlim(1, 5)
      legend = plt.legend()
```



1.5 Value-at-Risk Forecasting

Value-at-Risk (VaR) forecasts from GARCH models depend on the conditional mean, the conditional volatility and the quantile of the standardized residuals,

$$VaR_{t+1|t} = -\mu_{t+1|t} - \sigma_{t+1|t}q_\alpha$$

where q_α is the α quantile of the standardized residuals, e.g., 5%.

The quantile can be either computed from the estimated model density or computed using the empirical distribution of the standardized residuals. The example below shows both methods.

```
[17]: am = arch_model(returns, vol="Garch", p=1, o=0, q=1, dist="skewt")
      res = am.fit(dispatch="off", last_obs="2017-12-31")
```

1.5.1 Parametric VaR

First, we use the model to estimate the VaR. The quantiles can be computed using the `ppf` method of the distribution attached to the model. The quantiles are printed below.

```
[18]: forecasts = res.forecast(start="2018-1-1", reindex=False)
      cond_mean = forecasts.mean["2018":]
      cond_var = forecasts.variance["2018":]
      q = am.distribution.ppf([0.01, 0.05], res.params[-2:])
      print(q)

[-2.64484999 -1.64965918]
```

Next, we plot the two VaRs along with the returns. The returns that violate the VaR forecasts are highlighted.

```
[19]: value_at_risk = -cond_mean.values - np.sqrt(cond_var).values * q[None, :]
      value_at_risk = pd.DataFrame(value_at_risk, columns=["1%", "5%"], index=cond_var.index)
      ax = value_at_risk.plot(legend=False)
      xl = ax.set_xlim(value_at_risk.index[0], value_at_risk.index[-1])
      rets_2018 = returns["2018":].copy()
      rets_2018.name = "S&P 500 Return"
      c = []
      for idx in value_at_risk.index:
          if rets_2018[idx] > -value_at_risk.loc[idx, "5%"]:
              c.append("#000000")
          elif rets_2018[idx] < -value_at_risk.loc[idx, "1%"]:
              c.append("#BB0000")
          else:
              c.append("#BB00BB")
      c = np.array(c, dtype="object")
      labels = {
          "#BB0000": "1% Exceedence",
          "#BB00BB": "5% Exceedence",
          "#000000": "No Exceedence",
      }
      markers = {"#BB0000": "x", "#BB00BB": "s", "#000000": "o"}
      for color in np.unique(c):
          sel = c == color
```


(continues on next page)

(continued from previous page)

```

ax.scatter(
    rets_2018.index[sel],
    -rets_2018.loc[sel],
    marker=markers[color],
    c=c[sel],
    label=labels[color],
)
ax.set_title("Parametric VaR")
leg = ax.legend(frameon=False, ncol=3)

```



1.5.2 Filtered Historical Simulation

Next, we use the empirical distribution of the standardized residuals to estimate the quantiles. These values are very similar to those estimated using the assumed distribution. The plot below is identical except for the slightly different quantiles.

```

[20]: std_rets = (returns["2017"] - res.params["mu"]) / res.conditional_volatility
std_rets = std_rets.dropna()
q = std_rets.quantile([0.01, 0.05])
print(q)

```

```

0.01    -2.668273
0.05    -1.723352
dtype: float64

```

```

[21]: value_at_risk = -cond_mean.values - np.sqrt(cond_var).values * q.values[None, :]
value_at_risk = pd.DataFrame(value_at_risk, columns=["1%", "5%"], index=cond_var.index)
ax = value_at_risk.plot(legend=False)
xl = ax.set_xlim(value_at_risk.index[0], value_at_risk.index[-1])
rets_2018 = returns["2018":].copy()
rets_2018.name = "S&P 500 Return"
c = []
for idx in value_at_risk.index:
    if rets_2018[idx] > -value_at_risk.loc[idx, "5%"]:

```


(continues on next page)

(continued from previous page)

```

        c.append("#000000")
    elif rets_2018[idx] < -value_at_risk.loc[idx, "1%"]:
        c.append("#BB0000")
    else:
        c.append("#BB00BB")
c = np.array(c, dtype="object")
for color in np.unique(c):
    sel = c == color
    ax.scatter(
        rets_2018.index[sel],
        -rets_2018.loc[sel],
        marker=markers[color],
        c=c[sel],
        label=labels[color],
    )
ax.set_title("Filtered Historical Simulation VaR")
leg = ax.legend(frameon=False, ncol=3)

```



1.6 Volatility Scenarios

Custom random-number generators can be used to implement scenarios where shock follow a particular pattern. For example, suppose you wanted to find out what would happen if there were 5 days of shocks that were larger than average. In most circumstances, the shocks in a GARCH model have unit variance. This could be changed so that the first 5 shocks have variance 4, or twice the standard deviation.

Another scenario would be to over sample a specific period for the shocks. When using the standard bootstrap method (filtered historical simulation) the shocks are drawn using iid sampling from the history. While this approach is standard and well-grounded, it might be desirable to sample from a specific period. This can be implemented using a custom random number generator. This strategy is precisely how the filtered historical simulation is implemented internally, only where the draws are uniformly sampled from the entire history.

First, some preliminaries

```
[1]: %matplotlib inline
import matplotlib.pyplot as plt
import numpy as np
import pandas as pd
import seaborn as sns
from arch.univariate import GARCH, ConstantMean, Normal

sns.set_style("darkgrid")
plt.rc("figure", figsize=(16, 6))
plt.rc("savefig", dpi=90)
plt.rc("font", family="sans-serif")
plt.rc("font", size=14)
```

This example makes use of returns from the NASDAQ index. The scenario bootstrap will make use of returns in the run-up to and during the Financial Crisis of 2008.

```
[2]: import arch.data.nasdaq

data = arch.data.nasdaq.load()
nasdaq = data["Adj Close"]
print(nasdaq.head())
```

```
Date
1999-01-04    2208.050049
1999-01-05    2251.270020
1999-01-06    2320.860107
1999-01-07    2326.090088
1999-01-08    2344.409912
Name: Adj Close, dtype: float64
```

Next, the returns are computed and the model is constructed. The model is constructed from the building blocks. It is a standard model and could have been (almost) equivalently constructed using

```
mod = arch_model(rets, mean='constant', p=1, o=1, q=1)
```

The one advantage of constructing the model using the components is that the NumPy RandomState that is used to simulate from the model can be externally set. This allows the generator seed to be easily set and for the state to reset, if needed.

NOTE: It is always a good idea to scale return by 100 before estimating ARCH-type models. This helps the optimizer converge since the scale of the volatility intercept is much closer to the scale of the other parameters in the model.

```
[3]: rets = 100 * nasdaq.pct_change().dropna()

# Build components to set the state for the distribution
random_state = np.random.RandomState(1)
dist = Normal(random_state=random_state)
volatility = GARCH(1, 1, 1)

mod = ConstantMean(rets, volatility=volatility, distribution=dist)
```

```
C:\git\arch\arch\univariate\distribution.py:63: FutureWarning: random_state is
↪ deprecated and will be removed in a future update. Use seed instead.
warnings.warn(
```

Fitting the model is standard.

```
[4]: res = mod.fit(dispatch="off")
res
```

```
[4]:
Constant Mean - GJR-GARCH Model Results
=====
Dep. Variable:          Adj Close    R-squared:                0.000
Mean Model:            Constant Mean  Adj. R-squared:           0.000
Vol Model:             GJR-GARCH     Log-Likelihood:          -8196.75
Distribution:          Normal        AIC:                     16403.5
Method:               Maximum Likelihood  BIC:                     16436.1
                               No. Observations:                5030
Date:                 Wed, Apr 12 2023  Df Residuals:             5029
Time:                 15:59:51         Df Model:                  1
                               Mean Model
=====
              coef    std err          t      P>|t|      95.0% Conf. Int.
-----
mu           0.0376  1.476e-02     2.549  1.081e-02  [8.693e-03,6.656e-02]
Volatility Model
=====
              coef    std err          t      P>|t|      95.0% Conf. Int.
-----
omega        0.0214  5.001e-03     4.281  1.861e-05  [1.161e-02,3.121e-02]
alpha[1]     0.0152  8.442e-03     1.802  7.148e-02  [-1.330e-03,3.176e-02]
gamma[1]     0.1265  2.024e-02     6.250  4.109e-10  [8.684e-02, 0.166]
beta[1]      0.9100  1.107e-02    82.232  0.000      [ 0.888, 0.932]
=====

Covariance estimator: robust
ARCHModelResult, id: 0x1548c0a8850
```

GJR-GARCH models support analytical forecasts, which is the default. The forecasts are produced for all of 2017 using the estimated model parameters.

```
[5]: forecasts = res.forecast(start="1-1-2017", horizon=10, reindex=False)
print(forecasts.residual_variance.dropna().head())
```

	h.01	h.02	h.03	h.04	h.05	h.06
Date						
2017-01-03	0.623295	0.637504	0.651549	0.665431	0.679154	0.692717 \
2017-01-04	0.599455	0.613940	0.628257	0.642408	0.656397	0.670223
2017-01-05	0.567297	0.582153	0.596837	0.611352	0.625699	0.639880
2017-01-06	0.542506	0.557649	0.572616	0.587410	0.602034	0.616488
2017-01-09	0.515452	0.530906	0.546183	0.561282	0.576208	0.590961

	h.07	h.08	h.09	h.10
Date				
2017-01-03	0.706124	0.719376	0.732475	0.745423
2017-01-04	0.683890	0.697399	0.710752	0.723950
2017-01-05	0.653897	0.667753	0.681448	0.694985
2017-01-06	0.630776	0.644899	0.658858	0.672656
2017-01-09	0.605543	0.619957	0.634205	0.648288

All GARCH specification are complete models in the sense that they specify a distribution. This allows simulations to be produced using the assumptions in the model. The forecast function can be made to produce simulations using

the assumed distribution by setting `method='simulation'`.

These forecasts are similar to the analytical forecasts above. As the number of simulation increases towards ∞ , the simulation-based forecasts will converge to the analytical values above.

```
[6]: sim_forecasts = res.forecast(
      start="1-1-2017", method="simulation", horizon=10, reindex=False
    )
print(sim_forecasts.residual_variance.dropna().head())
```

	h.01	h.02	h.03	h.04	h.05	h.06
Date						
2017-01-03	0.623295	0.637251	0.647817	0.663746	0.673404	0.687952 \
2017-01-04	0.599455	0.617539	0.635838	0.649695	0.659733	0.667267
2017-01-05	0.567297	0.583415	0.597571	0.613065	0.621790	0.636180
2017-01-06	0.542506	0.555688	0.570280	0.585426	0.595551	0.608487
2017-01-09	0.515452	0.528771	0.542658	0.559684	0.580434	0.594855

	h.07	h.08	h.09	h.10
Date				
2017-01-03	0.697221	0.707707	0.717701	0.729465
2017-01-04	0.686503	0.699708	0.707203	0.718560
2017-01-05	0.650287	0.663344	0.679835	0.692300
2017-01-06	0.619195	0.638180	0.653185	0.661366
2017-01-09	0.605136	0.621835	0.634091	0.653222

1.6.1 Custom Random Generators

`forecast` supports replacing the generator based on the assumed distribution of residuals in the model with any other generator. A shock generator should usually produce unit variance shocks. However, in this example the first 5 shocks generated have variance 2, and the remainder are standard normal. This scenario consists of a period of consistently surprising volatility where the volatility has shifted for some reason.

The forecast variances are much larger and grow faster than those from either method previously illustrated. This reflects the increase in volatility in the first 5 days.

```
[7]: import numpy as np

random_state = np.random.RandomState(1)

def scenario_rng(size):
    shocks = random_state.standard_normal(size)
    shocks[:, :5] *= np.sqrt(2)
    return shocks

scenario_forecasts = res.forecast(
    start="1-1-2017", method="simulation", horizon=10, rng=scenario_rng, reindex=False
)
print(scenario_forecasts.residual_variance.dropna().head())
```

	h.01	h.02	h.03	h.04	h.05	h.06
Date						

(continues on next page)

(continued from previous page)

2017-01-03	0.623295	0.685911	0.745202	0.821112	0.886289	0.966737	\
2017-01-04	0.599455	0.668181	0.743119	0.811486	0.877539	0.936587	
2017-01-05	0.567297	0.629195	0.691225	0.758891	0.816663	0.893986	
2017-01-06	0.542506	0.596301	0.656603	0.721505	0.778286	0.849680	
2017-01-09	0.515452	0.567086	0.622224	0.689831	0.775048	0.845656	

	h.07	h.08	h.09	h.10
Date				
2017-01-03	0.970796	0.977504	0.982202	0.992547
2017-01-04	0.955295	0.965540	0.966432	0.974248
2017-01-05	0.905952	0.915208	0.930777	0.938636
2017-01-06	0.856175	0.873866	0.886221	0.890002
2017-01-09	0.851104	0.864591	0.874696	0.894397

1.6.2 Bootstrap Scenarios

forecast supports Filtered Historical Simulation (FHS) using `method='bootstrap'`. This is effectively a simulation method where the simulated shocks are generated using iid sampling from the history of the demeaned and standardized return data. Custom bootstraps are another application of `rng`. Here an object is used to hold the shocks. This object exposes a method (`rng`) that acts like a random number generator, except that it only returns values that were provided in the `shocks` parameter.

The internal implementation of the FHS uses a method almost identical to this where `shocks` contain the entire history.

```
[8]: class ScenarioBootstrapRNG(object):
    def __init__(self, shocks, random_state):
        self._shocks = np.asarray(shocks) # 1d
        self._rs = random_state
        self.n = shocks.shape[0]

    def rng(self, size):
        idx = self._rs.randint(0, self.n, size=size)
        return self._shocks[idx]

random_state = np.random.RandomState(1)
std_shocks = res.resid / res.conditional_volatility
shocks = std_shocks["2008-08-01":"2008-11-10"]
scenario_bootstrap = ScenarioBootstrapRNG(shocks, random_state)
bs_forecasts = res.forecast(
    start="1-1-2017",
    method="simulation",
    horizon=10,
    rng=scenario_bootstrap.rng,
    reindex=False,
)
print(bs_forecasts.residual_variance.dropna().head())
```

	h.01	h.02	h.03	h.04	h.05	h.06
Date						
2017-01-03	0.623295	0.676081	0.734322	0.779325	0.828189	0.898202
2017-01-04	0.599455	0.645237	0.697133	0.750169	0.816280	0.888417

(continues on next page)

(continued from previous page)

2017-01-05	0.567297	0.610493	0.665995	0.722954	0.777860	0.840369
2017-01-06	0.542506	0.597387	0.644534	0.691387	0.741206	0.783319
2017-01-09	0.515452	0.561312	0.611026	0.647824	0.700559	0.757398


	h.07	h.08	h.09	h.10
Date				
2017-01-03	0.958215	1.043704	1.124684	1.203893
2017-01-04	0.945120	1.013400	1.084042	1.158148
2017-01-05	0.889032	0.961424	1.022413	1.097192
2017-01-06	0.840667	0.895559	0.957266	1.019497
2017-01-09	0.820788	0.887791	0.938708	1.028614

1.6.3 Visualizing the differences

The final forecast values are used to illustrate how these are different. The analytical and standard simulation are virtually identical. The simulated scenario grows rapidly for the first 5 periods and then more slowly. The bootstrap scenario grows quickly and consistently due to the magnitude of the shocks in the financial crisis.

```
[9]: import pandas as pd
```

```
df = pd.concat(
    [
        forecasts.residual_variance.iloc[-1],
        sim_forecasts.residual_variance.iloc[-1],
        scenario_forecasts.residual_variance.iloc[-1],
        bs_forecasts.residual_variance.iloc[-1],
    ],
    axis=1,
)
df.columns = ["Analytic", "Simulation", "Scenario Sim", "Bootstrap Scenario"]
# Plot annualized vol
subplot = np.sqrt(252 * df).plot(legend=False)
legend = subplot.legend(frameon=False)
```



```
[10]: subplot = np.sqrt(252 * df).plot
```


1.6.4 Comparing the paths

The paths are available on the attribute `simulations`. Plotting the paths shows important differences between the two scenarios beyond the average differences plotted above. Both start at the same point.

```
[11]: fig, axes = plt.subplots(1, 2)
      colors = sns.color_palette("dark")
      # The paths for the final observation
      sim_paths = sim_forecasts.simulations.residual_variances[-1].T
      bs_paths = bs_forecasts.simulations.residual_variances[-1].T

      x = np.arange(1, 11)
      # Plot the paths and the mean, set the axis to have the same limit
      axes[0].plot(x, np.sqrt(252 * sim_paths), color=colors[1], alpha=0.05)
      axes[0].plot(
          x, np.sqrt(252 * sim_forecasts.residual_variance.iloc[-1]), color="k", alpha=1
      )
      axes[0].set_title("Model-based Simulation")
      axes[0].set_xticks(np.arange(1, 11))
      axes[0].set_xlim(1, 10)
      axes[0].set_ylim(20, 100)


      axes[1].plot(x, np.sqrt(252 * bs_paths), color=colors[2], alpha=0.05)
      axes[1].plot(
          x, np.sqrt(252 * bs_forecasts.residual_variance.iloc[-1]), color="k", alpha=1
      )
      axes[1].set_xticks(np.arange(1, 11))
      axes[1].set_xlim(1, 10)
      axes[1].set_ylim(20, 100)
      title = axes[1].set_title("Bootstrap Scenario")
```



1.6.5 Comparing across the year

A hedgehog plot is useful for showing the differences between the two forecasting methods across the year, instead of a single day.

```
[12]: analytic = forecasts.residual_variance.dropna()
bs = bs_forecasts.residual_variance.dropna()
fig, ax = plt.subplots(1, 1)
vol = res.conditional_volatility["2017-1-1":"2019-1-1"]
idx = vol.index
ax.plot(np.sqrt(252) * vol, alpha=0.5)
colors = sns.color_palette()
for i in range(0, len(vol), 22):
    a = analytic.iloc[i]
    b = bs.iloc[i]
    loc = idx.get_loc(a.name)
    new_idx = idx[loc + 1 : loc + 11]
    a.index = new_idx
    b.index = new_idx
    ax.plot(np.sqrt(252 * a), color=colors[1])
    ax.plot(np.sqrt(252 * b), color=colors[2])
labels = ["Annualized Vol.", "Analytic Forecast", "Bootstrap Scenario Forecast"]
legend = ax.legend(labels, frameon=False)
xlim = ax.set_xlim(vol.index[0], vol.index[-1])
```



1.7 Forecasting with Exogenous Regressors

This notebook provides examples of the accepted data structures for passing the expected value of exogenous variables when these are included in the mean. For example, consider an AR(1) with 2 exogenous variables. The mean dynamics are

$$Y_t = \phi_0 + \phi_1 Y_{t-1} + \beta_0 X_{0,t} + \beta_1 X_{1,t} + \epsilon_t.$$

The h -step forecast, $E_T[Y_{t+h}]$, depends on the conditional expectation of $X_{0,T+h}$ and $X_{1,T+h}$,

$$E_T[Y_{T+h}] = \phi_0 + \phi_1 E_T[Y_{T+h-1}] + \beta_0 E_T[X_{0,T+h}] + \beta_1 E_T[X_{1,T+h}]$$

where $E_T[Y_{T+h-1}]$ has been recursively computed.

In order to construct forecasts up to some horizon h , it is necessary to pass $2 \times h$ values (h for each series). If using the features of `forecast` that allow many forecast to be specified, it necessary to supply $n \times 2 \times h$ values.

There are two general purpose data structures that can be used for any number of exogenous variables and any number steps ahead:

- `dict` - The values can be pass using a `dict` where the keys are the variable names and the values are 2-dimensional arrays. This is the most natural generalization of a pandas `DataFrame` to 3-dimensions.
- `array` - The vales can alternatively be passed as a 3-d NumPy array where dimension 0 tracks the regressor index, dimension 1 is the time period and dimension 2 is the horizon.

When a model contains a single exogenous regressor it is possible to use a 2-d array or `DataFrame` where `dim0` tracks the time period where the forecast is generated and dimension 1 tracks the horizon.

In the special case where a model contains a single regressor *and* the horizon is 1, then a 1-d array of pandas Series can be used.

```
[1]: # initial setup
%matplotlib inline

import matplotlib.pyplot as plt
import numpy as np
import pandas as pd
import seaborn
from arch.__future__ import reindexing

seaborn.set_style("darkgrid")
plt.rc("figure", figsize=(16, 6))
plt.rc("savefig", dpi=90)
plt.rc("font", family="sans-serif")
plt.rc("font", size=14)
```

1.7.1 Simulating data

Two X variables are simulated and are assumed to follow independent AR(1) processes. The data is then assumed to follow an ARX(1) with 2 exogenous regressors and GARCH(1,1) errors.

```
[2]: from arch.univariate import ARX, GARCH, ZeroMean, arch_model

burn = 250

x_mod = ARX(None, lags=1)
x0 = x_mod.simulate([1, 0.8, 1], nobs=1000 + burn).data
x1 = x_mod.simulate([2.5, 0.5, 1], nobs=1000 + burn).data

resid_mod = ZeroMean(volatility=GARCH())
resids = resid_mod.simulate([0.1, 0.1, 0.8], nobs=1000 + burn).data

phi1 = 0.7
phi0 = 3
y = 10 + resids.copy()
for i in range(1, y.shape[0]):
```

(continues on next page)

(continued from previous page)

```

y[i] = phi0 + phi1 * y[i - 1] + 2 * x0[i] - 2 * x1[i] + resids[i]

x0 = x0.iloc[-1000:]
x1 = x1.iloc[-1000:]
y = y.iloc[-1000:]
y.index = x0.index = x1.index = np.arange(1000)


```

1.7.2 Plotting the data

```

[3]: ax = pd.DataFrame({"ARX": y}).plot(legend=False)
ax.legend(frameon=False)
_ = ax.set_xlim(0, 999)

```



1.7.3 Forecasting the X values

The forecasts of Y depend on forecasts of X_0 and X_1 . Both of these follow simple AR(1), and so we can construct the forecasts for all time horizons. Note that the value in position $[i, j]$ is the time- i forecast for horizon $j+1$.

```

[4]: x0_oos = np.empty((1000, 10))
x1_oos = np.empty((1000, 10))
for i in range(10):
    if i == 0:
        last = x0
    else:
        last = x0_oos[:, i - 1]
    x0_oos[:, i] = 1 + 0.8 * last
    if i == 0:
        last = x1
    else:
        last = x1_oos[:, i - 1]
    x1_oos[:, i] = 2.5 + 0.5 * last

x1_oos[-1]

```

```
[4]: array([5.32610653, 5.16305327, 5.08152663, 5.04076332, 5.02038166,
          5.01019083, 5.00509541, 5.00254771, 5.00127385, 5.00063693])
```

1.7.4 Fitting the model

Next, the most is fit. The parameters are accurately estimated.

```
[5]: exog = pd.DataFrame({"x0": x0, "x1": x1})
mod = arch_model(y, x=exog, mean="ARX", lags=1)
res = mod.fit(dis="off")
print(res.summary())
```

```

AR-X - GARCH Model Results
=====
Dep. Variable:          data    R-squared:                0.993
Mean Model:            AR-X    Adj. R-squared:           0.993
Vol Model:             GARCH   Log-Likelihood:       -1302.15
Distribution:          Normal   AIC:                2618.31
Method:               Maximum Likelihood   BIC:                2652.65
                                     No. Observations:      999
Date:                 Mon, May 17 2021   Df Residuals:        995
Time:                 16:04:11           Df Model:            4
                                     Mean Model
=====
              coef    std err          t      P>|t|    95.0% Conf. Int.
-----
Const         2.9480      0.149     19.818  2.088e-87 [ 2.656,  3.240]
data[1]        0.6971    3.421e-03    203.759   0.000 [ 0.690,  0.704]
x0             2.0186    2.063e-02     97.827   0.000 [ 1.978,  2.059]
x1            -2.0115    2.483e-02    -81.001   0.000 [-2.060, -1.963]
              Volatility Model
=====
              coef    std err          t      P>|t|    95.0% Conf. Int.
-----
omega         0.1144    5.879e-02     1.946   5.162e-02 [-8.041e-04,  0.230]
alpha[1]      0.0633    2.982e-02     2.123   3.374e-02 [4.866e-03,  0.122]
beta[1]       0.7940    9.035e-02     8.788   1.522e-18 [ 0.617,  0.971]
=====
Covariance estimator: robust

```

1.7.5 Using a dict


The first approach uses a dict to pass the two variables. The key consideration here is the the keys of the dictionary must **exactly** match the variable names (`x0` and `x1` here). The dictionary here contains only the final row of the forecast values since `forecast` will only make forecasts beginning from the final in-sample observation by default.

Using DataFrame

While these examples make use of NumPy arrays, these can be DataFrames. This allows the index to be used to track the forecast origination point, which can be a helpful device.

```
[6]: exog_fcast = {"x0": x0_oos[-1:], "x1": x1_oos[-1:]}
forecasts = res.forecast(horizon=10, x=exog_fcast)
forecasts.mean.T.plot()
```

```
[6]: <AxesSubplot:>
```



1.7.6 Using an array

An array can alternatively be used. This frees the restriction on matching the variable names although the order must match instead. The forecast values are 2 (variables) by 1 (forecast) by 10 (horizon).

```
[7]: exog_fcast = np.array([x0_oos[-1:], x1_oos[-1:]])
print(f"The shape is {exog_fcast.shape}")
array_forecasts = res.forecast(horizon=10, x=exog_fcast)
print(array_forecasts.mean - forecasts.mean)
```

The shape is (2, 1, 10)

	h.01	h.02	h.03	h.04	h.05	h.06	h.07	h.08	h.09	h.10
999	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

1.7.7 Producing multiple forecasts

forecast can produce multiple forecasts using the same fit model. Here the model is fit to the first 500 observations and then forecasting for the remaining values are produced. It must be the case that the x values passed for forecast have the same number of rows as the table of forecasts produced.

```
[8]: res = mod.fit(dis="off", last_obs=500)
exog_fcast = {"x0": x0_oos[-500:], "x1": x1_oos[-500:]}
multi_forecasts = res.forecast(start=500, horizon=10, x=exog_fcast)
multi_forecasts.mean.tail(10)
```


```
[8]:
```

	h.01	h.02	h.03	h.04	h.05	h.06 \
990	0.197255	0.766334	1.577107	2.505601	3.459461	4.377620
991	-1.890108	-1.296009	-0.321045	0.826688	2.010886	3.148451
992	-8.507089	-7.755860	-6.044790	-4.011246	-1.975703	-0.089727
993	-12.095946	-10.869621	-8.890602	-6.627904	-4.352285	-2.211499
994	-10.415586	-8.143577	-5.654791	-3.258179	-1.089347	0.805444
995	-1.921109	1.075917	3.299730	4.950490	6.178127	7.093677
996	-0.935776	1.954178	4.178160	5.832262	7.036522	7.901080
997	2.416878	4.689798	6.409599	7.650164	8.515074	9.101508
998	4.633381	6.555164	8.072909	9.153335	9.864477	10.296675
999	10.573900	12.317818	13.245648	13.612879	13.620680	13.415346

	h.07	h.08	h.09	h.10
990	5.224185	5.981486	6.644090	7.214210
991	4.193448	5.124665	5.936575	6.633031
992	1.584868	3.033252	4.264283	5.297785
993	-0.277740	1.422307	2.888448	4.135017
994	2.424787	3.788488	4.925033	5.865051
995	7.778853	8.293623	8.681971	8.976192
996	8.515904	8.950270	9.255725	9.469814
997	9.488851	9.737583	9.891902	9.983206
998	10.532205	10.636352	10.657221	10.628546
999	13.097526	12.733225	12.363590	12.012647

The plot of the final 5 forecast paths shows the the mean reversion of the process.

```
[9]: _ = multi_forecasts.mean.tail().T.plot()
```



The previous example made use of dictionaries where each of the values was a 500 (number of forecasts) by 10 (horizon) array. The alternative format can be used where `x` is a 3-d array with shape 2 (variables) by 500 (forecasts) by 10 (horizon).

```
[10]: exog_fcast = np.array([x0_oos[-500:], x1_oos[-500:]])
print(exog_fcast.shape)
array_multi_forecasts = res.forecast(start=500, horizon=10, x=exog_fcast)
np.max(np.abs(array_multi_forecasts.mean - multi_forecasts.mean))
```

```
(2, 500, 10)
```

```
[10]: h.01    0.0  
      h.02    0.0  
      h.03    0.0  
      h.04    0.0  
      h.05    0.0  
      h.06    0.0  
      h.07    0.0  
      h.08    0.0  
      h.09    0.0  
      h.10    0.0  
      dtype: float64
```

1.7.8 x input array sizes

While the natural shape of the x data is the number of forecasts, it is also possible to pass an x that has the same shape as the y used to construct the model. This may simplify tracking the origin points of the forecast. Values that are not needed are ignored. In this example, the out-of-sample values are 2 by 1000 (original number of observations) by 10. Only the final 500 are used.

WARNING

Other sizes are not allowed. The size of the out-of-sample data must either match the original data size or the number of forecasts.

```
[11]: exog_fcast = np.array([x0_oos, x1_oos])  
      print(exog_fcast.shape)  
      array_multi_forecasts = res.forecast(start=500, horizon=10, x=exog_fcast)  
      np.max(np.abs(array_multi_forecasts.mean - multi_forecasts.mean))
```

```
(2, 1000, 10)
```

```
[11]: h.01    0.0  
      h.02    0.0  
      h.03    0.0  
      h.04    0.0  
      h.05    0.0  
      h.06    0.0  
      h.07    0.0  
      h.08    0.0  
      h.09    0.0  
      h.10    0.0  
      dtype: float64
```

1.7.9 Special Cases with a single x variable

When a model consists of a single exogenous regressor, then `x` can be a 1-d or 2-d array (or `Series` or `DataFrame`).

```
[12]: mod = arch_model(y, x=exog.iloc[:, :1], mean="ARX", lags=1)
      res = mod.fit(dispatch="off")
      print(res.summary())
```

```

                        AR-X - GARCH Model Results
=====
Dep. Variable:          data    R-squared:                0.949
Mean Model:             AR-X   Adj. R-squared:           0.949
Vol Model:              GARCH  Log-Likelihood:          -2310.31
Distribution:           Normal  AIC:                  4632.63
Method:                Maximum Likelihood  BIC:            4662.07
                                           No. Observations:  999
Date:                  Mon, May 17 2021  Df Residuals:      996
Time:                  16:04:11   Df Model:              3
                        Mean Model
=====
              coef    std err          t      P>|t|  95.0% Conf. Int.
-----
Const         -6.3468      0.283    -22.464  9.346e-112 [ -6.901, -5.793]
data[1]         0.7555   9.631e-03     78.446   0.000 [ 0.737, 0.774]
x0              1.7840   6.195e-02     28.799  2.192e-182 [ 1.663, 1.905]
                        Volatility Model
=====
              coef    std err          t      P>|t|  95.0% Conf. Int.
-----
omega           3.0493      0.753      4.052  5.085e-05 [ 1.574, 4.524]
alpha[1]         0.1626   3.741e-02      4.346  1.385e-05 [8.926e-02, 0.236]
beta[1]          0.3401      0.129      2.631  8.523e-03 [8.670e-02, 0.593]
=====
Covariance estimator: robust
```

These two examples show that both formats can be used.

```
[13]: forecast_1d = res.forecast(horizon=10, x=x0_oos[-1])
      forecast_2d = res.forecast(horizon=10, x=x0_oos[-1:])
      print(forecast_1d.mean - forecast_2d.mean)

## Simulation-forecasting

mod = arch_model(y, x=exog, mean="ARX", lags=1, power=1.0)
res = mod.fit(dispatch="off")
```

```

      h.01 h.02 h.03 h.04 h.05 h.06 h.07 h.08 h.09 h.10
999    0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0  0.0
```

1.7.10 Simulation

forecast supports simulating paths. When forecasting a model with exogenous variables, the same value is used to in all mean paths. If you wish to also simulate the paths of the x variables, these need to be generated and then passed inside a loop.

Static out-of-sample x

This first example shows that variance of the paths when the same x values are used in the forecast. There is a sense the out-of-sample x are treated as deterministic.

```
[14]: x = {"x0": x0_oos[-1], "x1": x1_oos[-1]}
      sim_fixedx = res.forecast(horizon=10, x=x, method="simulation", simulations=100)
      sim_fixedx.simulations.values.std(1)

[14]: array([[0.94510757, 0.97700028, 1.13035701, 1.10824845, 1.26825095,
              1.26590793, 1.23342443, 1.18098812, 1.28265677, 1.2315994 ]])
```

Simulating the out-of-sample x

This example simulates distinct paths for the two exogenous variables and then simulates a single path. This is then repeated 100 times. We see that variance is much higher when we account for variation in the x data.

```
[15]: from numpy.random import RandomState

def sim_ar1(params: np.ndarray, initial: float, horizon: int, rng: RandomState):
    out = np.zeros(horizon)
    shocks = rng.standard_normal(horizon)
    out[0] = params[0] + params[1] * initial + shocks[0]
    for i in range(1, horizon):
        out[i] = params[0] + params[1] * out[i - 1] + shocks[i]
    return out

simulations = []
rng = RandomState(20210301)
for i in range(100):
    x0_sim = sim_ar1(np.array([1, 0.8]), x0.iloc[-1], 10, rng)
    x1_sim = sim_ar1(np.array([2.5, 0.5]), x1.iloc[-1], 10, rng)
    x = {"x0": x0_sim, "x1": x1_sim}
    fcast = res.forecast(horizon=10, x=x, method="simulation", simulations=1)
    simulations.append(fcast.simulations.values)
```

Finally the standard deviation is quite a bit larger. This is a most accurate value for the long-run variance of the forecast residuals which should account for dynamics in the model and any exogenous regressors.

```
[16]: joined = np.concatenate(simulations, 1)
      joined.std(1)

[16]: array([[3.21343234, 4.99297815, 6.29477322, 7.49884207, 8.47501636,
              8.64628226, 8.72478144, 8.78606273, 9.03824963, 9.30368669]])
```


1.8 Mean Models

All ARCH models start by specifying a mean model.

<code>ZeroMean([y, hold_back, volatility, ...])</code>	Model with zero conditional mean estimation and simulation
<code>ConstantMean([y, hold_back, volatility, ...])</code>	Constant mean model estimation and simulation.
<code>ARX([y, x, lags, constant, hold_back, ...])</code>	Autoregressive model with optional exogenous regressors estimation and simulation
<code>HARX([y, x, lags, constant, use_rotated, ...])</code>	Heterogeneous Autoregression (HAR), with optional exogenous regressors, model estimation and simulation
<code>LS([y, x, constant, hold_back, volatility, ...])</code>	Least squares model estimation and simulation

1.8.1 arch.univariate.ZeroMean

```
class arch.univariate.ZeroMean(y=None, hold_back=None, volatility=None, distribution=None,
                               rescale=None)
```

Model with zero conditional mean estimation and simulation

Parameters

y : {ndarray, Series}

nobs element vector containing the dependent variable

hold_back : int

Number of observations at the start of the sample to exclude when estimating model parameters. Used when comparing models with different lag lengths to estimate on the common sample.

volatility : *VolatilityProcess*, optional

Volatility process to use in the model

distribution : *Distribution*, optional

Error distribution to use in the model

rescale : bool, optional

Flag indicating whether to automatically rescale data if the scale of the data is likely to produce convergence issues when estimating model parameters. If False, the model is estimated on the data without transformation. If True, than y is rescaled and the new scale is reported in the estimation results.

Examples

```
>>> import numpy as np
>>> from arch.univariate import ZeroMean
>>> y = np.random.randn(100)
>>> zm = ZeroMean(y)
>>> res = zm.fit()
```

Notes

The zero mean model is described by

$$y_t = \epsilon_t$$

Methods

<code>bounds()</code>	Construct bounds for parameters to use in non-linear optimization
<code>compute_param_cov(params[, backcast, robust])</code>	Computes parameter covariances using numerical derivatives.
<code>constraints()</code>	Construct linear constraint arrays for use in non-linear optimization
<code>fit([update_freq, disp, starting_values, ...])</code>	Estimate model parameters
<code>fix(params[, first_obs, last_obs])</code>	Allows an ARCHModelFixedResult to be constructed from fixed parameters.
<code>forecast(params[, horizon, start, align, ...])</code>	Construct forecasts from estimated model
<code>parameter_names()</code>	List of parameters names
<code>resids(params[, y, regressors])</code>	Compute model residuals
<code>simulate(params, nobs[, burn, ...])</code>	Simulated data from a zero mean model
<code>starting_values()</code>	Returns starting values for the mean model, often the same as the values returned from fit

arch.univariate.ZeroMean.bounds

`ZeroMean.bounds()`

Construct bounds for parameters to use in non-linear optimization

Returns

bounds – Bounds for parameters to use in estimation.

Return type

`list` (2-tuple of float)

arch.univariate.ZeroMean.compute_param_cov

`ZeroMean.compute_param_cov(params, backcast=None, robust=True)`

Computes parameter covariances using numerical derivatives.

Parameters

params : `ndarray`
Model parameters

backcast : `float`
Value to use for pre-sample observations

robust : `bool`, optional
Flag indicating whether to use robust standard errors (True) or classic MLE (False)

Return type

`ndarray`

arch.univariate.ZeroMean.constraints

ZeroMean.constraints()

Construct linear constraint arrays for use in non-linear optimization

Return type

`tuple[ndarray, ndarray]`

Returns

- **a** (*ndarray*) – Number of constraints by number of parameters loading array
- **b** (*ndarray*) – Number of constraints array of lower bounds

Notes

Parameters satisfy $a \cdot \text{parameters} - b \geq 0$

arch.univariate.ZeroMean.fit

```
ZeroMean.fit(update_freq=1, disp='final', starting_values=None, cov_type='robust',
             show_warning=True, first_obs=None, last_obs=None, tol=None, options=None,
             backcast=None)
```

Estimate model parameters

Parameters

update_freq : `int`, optional

Frequency of iteration updates. Output is generated every *update_freq* iterations. Set to 0 to disable iterative output.

disp : {`bool`, "off", "final"}

Either 'final' to print optimization result or 'off' to display nothing. If using a boolean, False is "off" and True is "final"

starting_values : `ndarray`, optional

Array of starting values to use. If not provided, starting values are constructed by the model components.

cov_type : `str`, optional

Estimation method of parameter covariance. Supported options are 'robust', which does not assume the Information Matrix Equality holds and 'classic' which does. In the ARCH literature, 'robust' corresponds to Bollerslev-Wooldridge covariance estimator.

show_warning : `bool`, optional

Flag indicating whether convergence warnings should be shown.

first_obs : {`int`, `str`, `datetime`, `Timestamp`}

First observation to use when estimating model

last_obs : {`int`, `str`, `datetime`, `Timestamp`}

Last observation to use when estimating model

tol : `float`, optional

Tolerance for termination.

options : `dict`, optional

Options to pass to *scipy.optimize.minimize*. Valid entries include 'ftol', 'eps', 'disp', and 'maxiter'.

backcast : {float, ndarray}, optional

Value to use as backcast. Should be measure σ_0^2 since model-specific non-linear transformations are applied to value before computing the variance recursions.

Returns

results – Object containing model results

Return type

ARCHModelResult

Notes

A ConvergenceWarning is raised if SciPy's optimizer indicates difficulty finding the optimum.

Parameters are optimized using SLSQP.

arch.univariate.ZeroMean.fix

`ZeroMean.fix(params, first_obs=None, last_obs=None)`

Allows an ARCHModelFixedResult to be constructed from fixed parameters.

Parameters

params : {ndarray, Series}

User specified parameters to use when generating the result. Must have the correct number of parameters for a given choice of mean model, volatility model and distribution.

first_obs : {int, str, datetime, Timestamp}

First observation to use when fixing model

last_obs : {int, str, datetime, Timestamp}

Last observation to use when fixing model

Returns

results – Object containing model results

Return type

ARCHModelFixedResult

Notes

Parameters are not checked against model-specific constraints.

arch.univariate.ZeroMean.forecast

`ZeroMean.forecast(params, horizon=1, start=None, align='origin', method='analytic', simulations=1000, rng=None, random_state=None, *, reindex=None, x=None)`

Construct forecasts from estimated model

Parameters

params : {ndarray, Series}

Parameters required to forecast. Must be identical in shape to the parameters computed by fitting the model.

horizon : int, optional

Number of steps to forecast

start : {int, datetime, Timestamp, str}, optional

An integer, datetime or str indicating the first observation to produce the forecast for. Date-times can only be used with pandas inputs that have a datetime index. Strings must be convertible to a date time, such as in '1945-01-01'.

align : str, optional

Either 'origin' or 'target'. When set of 'origin', the t-th row of forecasts contains the forecasts for t+1, t+2, ..., t+h. When set to 'target', the t-th row contains the 1-step ahead forecast from time t-1, the 2 step from time t-2, ..., and the h-step from time t-h. 'target' simplified computing forecast errors since the realization and h-step forecast are aligned.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic. The method only affects the variance forecast generation. Not all volatility models support all methods. In particular, volatility models that do not evolve in squares such as EGARCH or TARCH do not support the 'analytic' method for horizons > 1.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable, optional

Custom random number generator to use in simulation-based forecasts. Must produce random samples using the syntax *rng(size)* where size the 2-element tuple (simulations, horizon).

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

reindex : bool, optional

Whether to reindex the forecasts to have the same dimension as the series being forecast. Prior to 4.18 this was the default. As of 4.19 this is now optional. If not provided, a warning is raised about the future change in the default which will occur after September 2021.

New in version 4.19.

x : {dict[label, array_like], array_like}

Values to use for exogenous regressors if any are included in the model. Three formats are accepted:

- 2-d array-like: This format can be used when there is a single exogenous variable. The input must have shape (nforecast, horizon) or (nobs, horizon) where nforecast is the number of forecasting periods and nobs is the original shape of y. For example, if a single series of forecasts are made from the end of the sample with a horizon of 10, then the input can be (1, 10). Alternatively, if the original data had 1000 observations, then the input can be (1000, 10), and only the final row is used to produce forecasts.
- A dictionary of 2-d array-like: This format is identical to the previous except that the dictionary keys must match the names of the exog variables. Requires that the exog variables were passed as a pandas DataFrame.
- A 3-d NumPy array (or equivalent). In this format, each panel (0th axis) is a 2-d array that must have shape (nforecast, horizon) or (nobs,horizon). The array x[j] corresponds to the j-th column of the exogenous variables.

Due to the complexity required to accommodate all scenarios, please see the example notebook that demonstrates the valid formats for x.

New in version 4.19.

Returns

Container for forecasts. Key properties are `mean`, `variance` and `residual_variance`.

Return type

arch.univariate.base.ARCHModelForecast

Examples

```
>>> import pandas as pd
>>> from arch import arch_model
>>> am = arch_model(None, mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> sim_data = am.simulate([0.1, 0.4, 0.3, 0.2, 1.0], 250)
>>> sim_data.index = pd.date_range('2000-01-01', periods=250)
>>> am = arch_model(sim_data['data'], mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> res = am.fit()
>>> fig = res.hedgehog_plot()
```

Notes

The most basic 1-step ahead forecast will return a vector with the same length as the original data, where the t -th value will be the time- t forecast for time $t + 1$. When the horizon is > 1 , and when using the default value for *align*, the forecast value in position $[t, h]$ is the time- t , $h+1$ step ahead forecast.

If model contains exogenous variables (`model.x` is not `None`), then only 1-step ahead forecasts are available. Using horizon > 1 will produce a warning and all columns, except the first, will be nan-filled.

If *align* is 'origin', `forecast[t,h]` contains the forecast made using `y[:t]` (that is, up to but not including t) for horizon $h + 1$. For example, `y[100,2]` contains the 3-step ahead forecast using the first 100 data points, which will correspond to the realization `y[100 + 2]`. If *align* is 'target', then the same forecast is in location `[102, 2]`, so that it is aligned with the observation to use when evaluating, but still in the same column.

arch.univariate.ZeroMean.parameter_names

`ZeroMean.parameter_names()`

List of parameters names

Returns

names – List of variable names for the mean model

Return type

`list (str)`

arch.univariate.ZeroMean.resids

`ZeroMean.resids(params, y=None, regressors=None)`

Compute model residuals

Parameters

params : `ndarray`

Model parameters

y : `ndarray`, optional

Alternative values to use when computing model residuals

regressors : ndarray, optional

Alternative regressor values to use when computing model residuals

Returns

resids – Model residuals

Return type

ndarray

arch.univariate.ZeroMean.simulate

`ZeroMean.simulate(params, nobs, burn=500, initial_value=None, x=None, initial_value_vol=None)`

Simulated data from a zero mean model

Parameters

params : {ndarray, DataFrame}

Parameters to use when simulating the model. Parameter order is [volatility distribution]. There are no mean parameters.

nobs : int

Length of series to simulate

burn : int, optional

Number of values to simulate to initialize the model and remove dependence on initial values.

initial_value : None

This value is not used.

x : None

This value is not used.

initial_value_vol : {ndarray, float}, optional

An array or scalar to use when initializing the volatility process.

Returns

simulated_data – DataFrame with columns data containing the simulated values, volatility, containing the conditional volatility and errors containing the errors used in the simulation

Return type

DataFrame

Examples

Basic data simulation with no mean and constant volatility

```
>>> from arch.univariate import ZeroMean
>>> import numpy as np
>>> zm = ZeroMean()
>>> params = np.array([1.0])
>>> sim_data = zm.simulate(params, 1000)
```

Simulating data with a non-trivial volatility process

```
>>> from arch.univariate import GARCH
>>> zm.volatility = GARCH(p=1, o=1, q=1)
>>> sim_data = zm.simulate([0.05, 0.1, 0.1, 0.8], 300)
```

arch.univariate.ZeroMean.starting_values**ZeroMean.starting_values()**

Returns starting values for the mean model, often the same as the values returned from fit

Returns

sv – Starting values

Return type

ndarray

Properties

<i>distribution</i>	Set or gets the error distribution
<i>name</i>	The name of the model.
<i>num_params</i>	Returns the number of parameters
<i>volatility</i>	Set or gets the volatility process
<i>x</i>	Gets the value of the exogenous regressors in the model
<i>y</i>	Returns the dependent variable

arch.univariate.ZeroMean.distribution**property** ZeroMean.distribution : *Distribution*

Set or gets the error distribution

Distributions must be a subclass of Distribution

Return type

Distribution

arch.univariate.ZeroMean.name**property** ZeroMean.name : str

The name of the model.

Return type

str

arch.univariate.ZeroMean.num_params**property** ZeroMean.num_params : int

Returns the number of parameters

arch.univariate.ZeroMean.volatility**property** ZeroMean.volatility: *VolatilityProcess*

Set or gets the volatility process

Volatility processes must be a subclass of VolatilityProcess

Return type*VolatilityProcess***arch.univariate.ZeroMean.x****property** ZeroMean.x: ndarray | DataFrame | None

Gets the value of the exogenous regressors in the model

Return type

Union[ndarray, DataFrame, None]

arch.univariate.ZeroMean.y**property** ZeroMean.y: ndarray | DataFrame | Series | None

Returns the dependent variable

Return type

Union[ndarray, DataFrame, Series, None]

1.8.2 arch.univariate.ConstantMean**class** arch.univariate.ConstantMean(y=None, hold_back=None, volatility=None, distribution=None, rescale=None)

Constant mean model estimation and simulation.

Parameters**y** : {ndarray, Series}

nobs element vector containing the dependent variable

hold_back : int

Number of observations at the start of the sample to exclude when estimating model parameters. Used when comparing models with different lag lengths to estimate on the common sample.

volatility : *VolatilityProcess*, optional

Volatility process to use in the model

distribution : *Distribution*, optional

Error distribution to use in the model

rescale : bool, optional

Flag indicating whether to automatically rescale data if the scale of the data is likely to produce convergence issues when estimating model parameters. If False, the model is estimated on the data without transformation. If True, than y is rescaled and the new scale is reported in the estimation results.

Examples

```
>>> import numpy as np
>>> from arch.univariate import ConstantMean
>>> y = np.random.randn(100)
>>> cm = ConstantMean(y)
>>> res = cm.fit()
```

Notes

The constant mean model is described by

$$y_t = \mu + \epsilon_t$$

Methods

<code>bounds()</code>	Construct bounds for parameters to use in non-linear optimization
<code>compute_param_cov(params[, backcast, robust])</code>	Computes parameter covariances using numerical derivatives.
<code>constraints()</code>	Construct linear constraint arrays for use in non-linear optimization
<code>fit([update_freq, disp, starting_values, ...])</code>	Estimate model parameters
<code>fix(params[, first_obs, last_obs])</code>	Allows an ARCHModelFixedResult to be constructed from fixed parameters.
<code>forecast(params[, horizon, start, align, ...])</code>	Construct forecasts from estimated model
<code>parameter_names()</code>	List of parameters names
<code>resids(params[, y, regressors])</code>	Compute model residuals
<code>simulate(params, nobs[, burn, ...])</code>	Simulated data from a constant mean model
<code>starting_values()</code>	Returns starting values for the mean model, often the same as the values returned from fit

arch.univariate.ConstantMean.bounds

ConstantMean.**bounds()**

Construct bounds for parameters to use in non-linear optimization

Returns

bounds – Bounds for parameters to use in estimation.

Return type

list (2-tuple of float)

arch.univariate.ConstantMean.compute_param_cov

ConstantMean.compute_param_cov(params, backcast=None, robust=True)

Computes parameter covariances using numerical derivatives.

Parameters

params : ndarray

Model parameters

backcast : float

Value to use for pre-sample observations

robust : bool, optional

Flag indicating whether to use robust standard errors (True) or classic MLE (False)

Return type

ndarray

arch.univariate.ConstantMean.constraints

ConstantMean.constraints()

Construct linear constraint arrays for use in non-linear optimization

Return type

tuple[ndarray, ndarray]

Returns

- **a** (ndarray) – Number of constraints by number of parameters loading array
- **b** (ndarray) – Number of constraints array of lower bounds

Notes

Parameters satisfy $a \cdot \text{parameters} - b \geq 0$

arch.univariate.ConstantMean.fit

ConstantMean.fit(update_freq=1, disp='final', starting_values=None, cov_type='robust', show_warning=True, first_obs=None, last_obs=None, tol=None, options=None, backcast=None)

Estimate model parameters

Parameters

update_freq : int, optional

Frequency of iteration updates. Output is generated every *update_freq* iterations. Set to 0 to disable iterative output.

disp : {bool, "off", "final"}

Either 'final' to print optimization result or 'off' to display nothing. If using a boolean, False is "off" and True is "final"

starting_values : ndarray, optional

Array of starting values to use. If not provided, starting values are constructed by the model components.

cov_type : str, optional

Estimation method of parameter covariance. Supported options are ‘robust’, which does not assume the Information Matrix Equality holds and ‘classic’ which does. In the ARCH literature, ‘robust’ corresponds to Bollerslev-Wooldridge covariance estimator.

show_warning : bool, optional

Flag indicating whether convergence warnings should be shown.

first_obs : {int, str, datetime, Timestamp}

First observation to use when estimating model

last_obs : {int, str, datetime, Timestamp}

Last observation to use when estimating model

tol : float, optional

Tolerance for termination.

options : dict, optional

Options to pass to *scipy.optimize.minimize*. Valid entries include ‘ftol’, ‘eps’, ‘disp’, and ‘maxiter’.

backcast : {float, ndarray}, optional

Value to use as backcast. Should be measure σ_0^2 since model-specific non-linear transformations are applied to value before computing the variance recursions.

Returns

results – Object containing model results

Return type

ARCHModelResult

Notes

A ConvergenceWarning is raised if SciPy’s optimizer indicates difficulty finding the optimum.

Parameters are optimized using SLSQP.

arch.univariate.ConstantMean.fix

ConstantMean.**fix**(params, first_obs=*None*, last_obs=*None*)

Allows an ARCHModelFixedResult to be constructed from fixed parameters.

Parameters**params : {ndarray, Series}**

User specified parameters to use when generating the result. Must have the correct number of parameters for a given choice of mean model, volatility model and distribution.

first_obs : {int, str, datetime, Timestamp}

First observation to use when fixing model

last_obs : {int, str, datetime, Timestamp}

Last observation to use when fixing model

Returns

results – Object containing model results

Return type

ARCHModelFixedResult

Notes

Parameters are not checked against model-specific constraints.

arch.univariate.ConstantMean.forecast

```
ConstantMean.forecast(params, horizon=1, start=None, align='origin', method='analytic',
                        simulations=1000, rng=None, random_state=None, *, reindex=None, x=None)
```

Construct forecasts from estimated model

Parameters

params : {ndarray, Series}

Parameters required to forecast. Must be identical in shape to the parameters computed by fitting the model.

horizon : int, optional

Number of steps to forecast

start : {int, datetime, Timestamp, str}, optional

An integer, datetime or str indicating the first observation to produce the forecast for. Date-times can only be used with pandas inputs that have a datetime index. Strings must be convertible to a date time, such as in '1945-01-01'.

align : str, optional

Either 'origin' or 'target'. When set of 'origin', the t-th row of forecasts contains the forecasts for t+1, t+2, ..., t+h. When set to 'target', the t-th row contains the 1-step ahead forecast from time t-1, the 2 step from time t-2, ..., and the h-step from time t-h. 'target' simplified computing forecast errors since the realization and h-step forecast are aligned.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic. The method only affects the variance forecast generation. Not all volatility models support all methods. In particular, volatility models that do not evolve in squares such as EGARCH or TARCH do not support the 'analytic' method for horizons > 1.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable, optional

Custom random number generator to use in simulation-based forecasts. Must produce random samples using the syntax *rng(size)* where size the 2-element tuple (simulations, horizon).

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

reindex : bool, optional

Whether to reindex the forecasts to have the same dimension as the series being forecast. Prior to 4.18 this was the default. As of 4.19 this is now optional. If not provided, a warning is raised about the future change in the default which will occur after September 2021.

New in version 4.19.

x : {dict[label, array_like], array_like}

Values to use for exogenous regressors if any are included in the model. Three formats are accepted:

- 2-d array-like: This format can be used when there is a single exogenous variable. The input must have shape (nforecast, horizon) or (nobs, horizon) where nforecast is the number of forecasting periods and nobs is the original shape of y. For example, if a single series of forecasts are made from the end of the sample with a horizon of 10, then the input can be (1, 10). Alternatively, if the original data had 1000 observations, then the input can be (1000, 10), and only the final row is used to produce forecasts.
- A dictionary of 2-d array-like: This format is identical to the previous except that the dictionary keys must match the names of the exog variables. Requires that the exog variables were passed as a pandas DataFrame.
- A 3-d NumPy array (or equivalent). In this format, each panel (0th axis) is a 2-d array that must have shape (nforecast, horizon) or (nobs, horizon). The array x[j] corresponds to the j-th column of the exogenous variables.

Due to the complexity required to accommodate all scenarios, please see the example notebook that demonstrates the valid formats for x.

New in version 4.19.

Returns

Container for forecasts. Key properties are `mean`, `variance` and `residual_variance`.

Return type

arch.univariate.base.ARCHModelForecast

Examples

```
>>> import pandas as pd
>>> from arch import arch_model
>>> am = arch_model(None, mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> sim_data = am.simulate([0.1, 0.4, 0.3, 0.2, 1.0], 250)
>>> sim_data.index = pd.date_range('2000-01-01', periods=250)
>>> am = arch_model(sim_data['data'], mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> res = am.fit()
>>> fig = res.hedgehog_plot()
```

Notes

The most basic 1-step ahead forecast will return a vector with the same length as the original data, where the t-th value will be the time-t forecast for time t + 1. When the horizon is > 1, and when using the default value for *align*, the forecast value in position [t, h] is the time-t, h+1 step ahead forecast.

If model contains exogenous variables (model.x is not None), then only 1-step ahead forecasts are available. Using horizon > 1 will produce a warning and all columns, except the first, will be nan-filled.

If *align* is 'origin', forecast[t,h] contains the forecast made using y[:t] (that is, up to but not including t) for horizon h + 1. For example, y[100,2] contains the 3-step ahead forecast using the first 100 data points, which will correspond to the realization y[100 + 2]. If *align* is 'target', then the same forecast is in location [102, 2], so that it is aligned with the observation to use when evaluating, but still in the same column.

arch.univariate.ConstantMean.parameter_names**ConstantMean.parameter_names()**

List of parameters names

Returns**names** – List of variable names for the mean model**Return type**

list (str)

arch.univariate.ConstantMean.resids**ConstantMean.resids**(params, y=None, regressors=None)

Compute model residuals

Parameters**params : ndarray**

Model parameters

y : ndarray, optional

Alternative values to use when computing model residuals

regressors : ndarray, optional

Alternative regressor values to use when computing model residuals

Returns**resids** – Model residuals**Return type**

ndarray

arch.univariate.ConstantMean.simulate**ConstantMean.simulate**(params, nobis, burn=500, initial_value=None, x=None, initial_value_vol=None)

Simulated data from a constant mean model

Parameters**params : array_like**

Parameters to use when simulating the model. Parameter order is [mean volatility distribution]. There is one parameter in the mean model, mu.

nobs : int

Length of series to simulate

burn : int, optional

Number of values to simulate to initialize the model and remove dependence on initial values.

initial_value : None

This value is not used.

x : None

This value is not used.

initial_value_vol : {ndarray, float}, optional

An array or scalar to use when initializing the volatility process.

Returns

simulated_data – DataFrame with columns data containing the simulated values, volatility, containing the conditional volatility and errors containing the errors used in the simulation

Return type

DataFrame

Examples

Basic data simulation with a constant mean and volatility

```
>>> import numpy as np
>>> from arch.univariate import ConstantMean, GARCH
>>> cm = ConstantMean()
>>> cm.volatility = GARCH()
>>> cm_params = np.array([1])
>>> garch_params = np.array([0.01, 0.07, 0.92])
>>> params = np.concatenate((cm_params, garch_params))
>>> sim_data = cm.simulate(params, 1000)
```

arch.univariate.ConstantMean.starting_values

ConstantMean.starting_values()

Returns starting values for the mean model, often the same as the values returned from fit

Returns

sv – Starting values

Return type

ndarray

Properties

<i>distribution</i>	Set or gets the error distribution
<i>name</i>	The name of the model.
<i>num_params</i>	Returns the number of parameters
<i>volatility</i>	Set or gets the volatility process
<i>x</i>	Gets the value of the exogenous regressors in the model
<i>y</i>	Returns the dependent variable

arch.univariate.ConstantMean.distribution

property **ConstantMean.distribution**: *Distribution*

Set or gets the error distribution

Distributions must be a subclass of Distribution

Return type

Distribution

arch.univariate.ConstantMean.name**property** ConstantMean.name : str

The name of the model.

Return type

str

arch.univariate.ConstantMean.num_params**property** ConstantMean.num_params : int

Returns the number of parameters

arch.univariate.ConstantMean.volatility**property** ConstantMean.volatility : *VolatilityProcess*

Set or gets the volatility process

Volatility processes must be a subclass of VolatilityProcess

Return type*VolatilityProcess***arch.univariate.ConstantMean.x****property** ConstantMean.x : ndarray | DataFrame | None

Gets the value of the exogenous regressors in the model

Return type

Union[ndarray, DataFrame, None]

arch.univariate.ConstantMean.y**property** ConstantMean.y : ndarray | DataFrame | Series | None

Returns the dependent variable

Return type

Union[ndarray, DataFrame, Series, None]

1.8.3 arch.univariate.ARX**class** arch.univariate.ARX(y=None, x=None, lags=None, constant=True, hold_back=None, volatility=None, distribution=None, rescale=None)

Autoregressive model with optional exogenous regressors estimation and simulation

Parameters**y** : {ndarray, Series}

nobs element vector containing the dependent variable

x : {ndarray, DataFrame}, optional

nobs by k element array containing exogenous regressors

lags : scalar, 1-d array, optional

Description of lag structure of the HAR. Scalar included all lags between 1 and the value. A 1-d array includes the AR lags lags[0], lags[1], ...

constant : bool, optional

Flag whether the model should include a constant

hold_back : int

Number of observations at the start of the sample to exclude when estimating model parameters. Used when comparing models with different lag lengths to estimate on the common sample.

volatility : *VolatilityProcess*, optional

Volatility process to use in the model

distribution : *Distribution*, optional

Error distribution to use in the model

rescale : bool, optional

Flag indicating whether to automatically rescale data if the scale of the data is likely to produce convergence issues when estimating model parameters. If False, the model is estimated on the data without transformation. If True, than y is rescaled and the new scale is reported in the estimation results.

Examples

```
>>> import numpy as np
>>> from arch.univariate import ARX
>>> y = np.random.randn(100)
>>> arx = ARX(y, lags=[1, 5, 22])
>>> res = arx.fit()
```

Estimating an AR with GARCH(1,1) errors

```
>>> from arch.univariate import GARCH
>>> arx.volatility = GARCH()
>>> res = arx.fit(update_freq=0, disp='off')
```

Notes

The AR-X model is described by

$$y_t = \mu + \sum_{i=1}^p \phi_{L_i} y_{t-L_i} + \gamma' x_t + \epsilon_t$$

Methods

<code>bounds()</code>	Construct bounds for parameters to use in non-linear optimization
<code>compute_param_cov(params[, backcast, robust])</code>	Computes parameter covariances using numerical derivatives.
<code>constraints()</code>	Construct linear constraint arrays for use in non-linear optimization
<code>fit([update_freq, disp, starting_values, ...])</code>	Estimate model parameters
<code>fix(params[, first_obs, last_obs])</code>	Allows an ARCHModelFixedResult to be constructed from fixed parameters.
<code>forecast(params[, horizon, start, align, ...])</code>	Construct forecasts from estimated model
<code>parameter_names()</code>	List of parameters names
<code>resids(params[, y, regressors])</code>	Compute model residuals
<code>simulate(params, nobs[, burn, ...])</code>	Simulates data from a linear regression, AR or HAR models
<code>starting_values()</code>	Returns starting values for the mean model, often the same as the values returned from fit

arch.univariate.ARX.bounds

ARX.bounds()

Construct bounds for parameters to use in non-linear optimization

Returns

bounds – Bounds for parameters to use in estimation.

Return type

list (2-tuple of float)

arch.univariate.ARX.compute_param_cov

ARX.compute_param_cov(params, backcast=None, robust=True)

Computes parameter covariances using numerical derivatives.

Parameters

params : ndarray

Model parameters

backcast : float

Value to use for pre-sample observations

robust : bool, optional

Flag indicating whether to use robust standard errors (True) or classic MLE (False)

Return type

ndarray

arch.univariate.ARX.constraints

ARX.constraints()

Construct linear constraint arrays for use in non-linear optimization

Return type

`tuple[ndarray, ndarray]`

Returns

- **a** (*ndarray*) – Number of constraints by number of parameters loading array
- **b** (*ndarray*) – Number of constraints array of lower bounds

Notes

Parameters satisfy $a \cdot \text{parameters} - b \geq 0$

arch.univariate.ARX.fit

ARX.fit(*update_freq*=1, *disp*='final', *starting_values*=None, *cov_type*=robust, *show_warning*=True, *first_obs*=None, *last_obs*=None, *tol*=None, *options*=None, *backcast*=None)

Estimate model parameters

Parameters

update_freq : int, optional

Frequency of iteration updates. Output is generated every *update_freq* iterations. Set to 0 to disable iterative output.

disp : {bool, "off", "final"}

Either 'final' to print optimization result or 'off' to display nothing. If using a boolean, False is "off" and True is "final"

starting_values : ndarray, optional

Array of starting values to use. If not provided, starting values are constructed by the model components.

cov_type : str, optional

Estimation method of parameter covariance. Supported options are 'robust', which does not assume the Information Matrix Equality holds and 'classic' which does. In the ARCH literature, 'robust' corresponds to Bollerslev-Wooldridge covariance estimator.

show_warning : bool, optional

Flag indicating whether convergence warnings should be shown.

first_obs : {int, str, datetime, Timestamp}

First observation to use when estimating model

last_obs : {int, str, datetime, Timestamp}

Last observation to use when estimating model

tol : float, optional

Tolerance for termination.

options : dict, optional

Options to pass to *scipy.optimize.minimize*. Valid entries include 'ftol', 'eps', 'disp', and 'maxiter'.

backcast : {float, ndarray}, optional

Value to use as backcast. Should be measure σ_0^2 since model-specific non-linear transformations are applied to value before computing the variance recursions.

Returns

results – Object containing model results

Return type

ARCHModelResult

Notes

A ConvergenceWarning is raised if SciPy's optimizer indicates difficulty finding the optimum.

Parameters are optimized using SLSQP.

arch.univariate.ARX.fix

ARX.fix(params, first_obs=*None*, last_obs=*None*)

Allows an ARCHModelFixedResult to be constructed from fixed parameters.

Parameters

params : {ndarray, Series}

User specified parameters to use when generating the result. Must have the correct number of parameters for a given choice of mean model, volatility model and distribution.

first_obs : {int, str, datetime, Timestamp}

First observation to use when fixing model

last_obs : {int, str, datetime, Timestamp}

Last observation to use when fixing model

Returns

results – Object containing model results

Return type

ARCHModelFixedResult

Notes

Parameters are not checked against model-specific constraints.

arch.univariate.ARX.forecast

ARX.forecast(params, horizon=*1*, start=*None*, align='origin', method='analytic', simulations=*1000*, rng=*None*, random_state=*None*, *, reindex=*None*, x=*None*)

Construct forecasts from estimated model

Parameters

params : {ndarray, Series}

Parameters required to forecast. Must be identical in shape to the parameters computed by fitting the model.

horizon : int, optional

Number of steps to forecast

start : {int, datetime, Timestamp, str}, optional

An integer, datetime or str indicating the first observation to produce the forecast for. Date-times can only be used with pandas inputs that have a datetime index. Strings must be convertible to a date time, such as in '1945-01-01'.

align : str, optional

Either 'origin' or 'target'. When set of 'origin', the t-th row of forecasts contains the forecasts for t+1, t+2, ..., t+h. When set to 'target', the t-th row contains the 1-step ahead forecast from time t-1, the 2 step from time t-2, ..., and the h-step from time t-h. 'target' simplified computing forecast errors since the realization and h-step forecast are aligned.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic. The method only affects the variance forecast generation. Not all volatility models support all methods. In particular, volatility models that do not evolve in squares such as EGARCH or TARCH do not support the 'analytic' method for horizons > 1.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable, optional

Custom random number generator to use in simulation-based forecasts. Must produce random samples using the syntax *rng(size)* where size the 2-element tuple (simulations, horizon).

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

reindex : bool, optional

Whether to reindex the forecasts to have the same dimension as the series being forecast. Prior to 4.18 this was the default. As of 4.19 this is now optional. If not provided, a warning is raised about the future change in the default which will occur after September 2021.

New in version 4.19.

x : {dict[label, array_like], array_like}

Values to use for exogenous regressors if any are included in the model. Three formats are accepted:

- 2-d array-like: This format can be used when there is a single exogenous variable. The input must have shape (nforecast, horizon) or (nobs, horizon) where nforecast is the number of forecasting periods and nobs is the original shape of y. For example, if a single series of forecasts are made from the end of the sample with a horizon of 10, then the input can be (1, 10). Alternatively, if the original data had 1000 observations, then the input can be (1000, 10), and only the final row is used to produce forecasts.
- A dictionary of 2-d array-like: This format is identical to the previous except that the dictionary keys must match the names of the exog variables. Requires that the exog variables were passed as a pandas DataFrame.
- A 3-d NumPy array (or equivalent). In this format, each panel (0th axis) is a 2-d array that must have shape (nforecast, horizon) or (nobs,horizon). The array x[j] corresponds to the j-th column of the exogenous variables.

Due to the complexity required to accommodate all scenarios, please see the example notebook that demonstrates the valid formats for x.

New in version 4.19.

Returns

Container for forecasts. Key properties are `mean`, `variance` and `residual_variance`.

Return type

arch.univariate.base.ARCHModelForecast

Examples

```
>>> import pandas as pd
>>> from arch import arch_model
>>> am = arch_model(None, mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> sim_data = am.simulate([0.1, 0.4, 0.3, 0.2, 1.0], 250)
>>> sim_data.index = pd.date_range('2000-01-01', periods=250)
>>> am = arch_model(sim_data['data'], mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> res = am.fit()
>>> fig = res.hedgehog_plot()
```

Notes

The most basic 1-step ahead forecast will return a vector with the same length as the original data, where the t -th value will be the time- t forecast for time $t + 1$. When the horizon is > 1 , and when using the default value for *align*, the forecast value in position $[t, h]$ is the time- t , $h+1$ step ahead forecast.

If model contains exogenous variables (`model.x` is not `None`), then only 1-step ahead forecasts are available. Using horizon > 1 will produce a warning and all columns, except the first, will be nan-filled.

If *align* is 'origin', `forecast[t,h]` contains the forecast made using `y[:t]` (that is, up to but not including t) for horizon $h + 1$. For example, `y[100,2]` contains the 3-step ahead forecast using the first 100 data points, which will correspond to the realization `y[100 + 2]`. If *align* is 'target', then the same forecast is in location `[102, 2]`, so that it is aligned with the observation to use when evaluating, but still in the same column.

arch.univariate.ARX.parameter_names

ARX.parameter_names()

List of parameters names

Returns

names – List of variable names for the mean model

Return type

list (str)

arch.univariate.ARX.resids

ARX.resids(params, y=None, regressors=None)

Compute model residuals

Parameters

params : ndarray

Model parameters

y : ndarray, optional

Alternative values to use when computing model residuals

regressors : ndarray, optional

Alternative regressor values to use when computing model residuals

Returns

resids – Model residuals

Return type

ndarray

arch.univariate.ARX.simulate

ARX.simulate(params, nobs, burn=500, initial_value=None, x=None, initial_value_vol=None)

Simulates data from a linear regression, AR or HAR models

Parameters

params : array_like

Parameters to use when simulating the model. Parameter order is [mean volatility distribution] where the parameters of the mean model are ordered [constant lag[0] lag[1] ... lag[p] ex[0] ... ex[k-1]] where lag[j] indicates the coefficient on the jth lag in the model and ex[j] is the coefficient on the jth exogenous variable.

nobs : int

Length of series to simulate

burn : int, optional

Number of values to simulate to initialize the model and remove dependence on initial values.

initial_value : {ndarray, float}, optional

Either a scalar value or *max(lags)* array set of initial values to use when initializing the model. If omitted, 0.0 is used.

x : {ndarray, DataFrame}, optional

nobs + burn by k array of exogenous variables to include in the simulation.

initial_value_vol : {ndarray, float}, optional

An array or scalar to use when initializing the volatility process.

Returns

simulated_data – DataFrame with columns data containing the simulated values, volatility, containing the conditional volatility and errors containing the errors used in the simulation

Return type

DataFrame

Examples

```
>>> import numpy as np
>>> from arch.univariate import HARX, GARCH
>>> harx = HARX(lags=[1, 5, 22])
>>> harx.volatility = GARCH()
>>> harx_params = np.array([1, 0.2, 0.3, 0.4])
>>> garch_params = np.array([0.01, 0.07, 0.92])
>>> params = np.concatenate((harx_params, garch_params))
>>> sim_data = harx.simulate(params, 1000)
```

Simulating models with exogenous regressors requires the regressors to have nobs plus burn data points


```

>>> nobs = 100
>>> burn = 200
>>> x = np.random.randn(nobs + burn, 2)
>>> x_params = np.array([1.0, 2.0])
>>> params = np.concatenate((harx_params, x_params, garch_params))
>>> sim_data = harx.simulate(params, nobs=nobs, burn=burn, x=x)

```

arch.univariate.ARX.starting_values

ARX.starting_values()

Returns starting values for the mean model, often the same as the values returned from fit

Returns

sv – Starting values

Return type

ndarray

Properties

<i>distribution</i>	Set or gets the error distribution
<i>name</i>	The name of the model.
<i>num_params</i>	Returns the number of parameters
<i>volatility</i>	Set or gets the volatility process
<i>x</i>	Gets the value of the exogenous regressors in the model
<i>y</i>	Returns the dependent variable

arch.univariate.ARX.distribution

property ARX.distribution: *Distribution*

Set or gets the error distribution

Distributions must be a subclass of Distribution

Return type

Distribution

arch.univariate.ARX.name

property ARX.name: str

The name of the model.

Return type

str

arch.univariate.ARX.num_params**property** ARX.num_params : int

Returns the number of parameters

arch.univariate.ARX.volatility**property** ARX.volatility : *VolatilityProcess*

Set or gets the volatility process

Volatility processes must be a subclass of VolatilityProcess

Return type*VolatilityProcess***arch.univariate.ARX.x****property** ARX.x : ndarray | DataFrame | None

Gets the value of the exogenous regressors in the model

Return type

Union[ndarray, DataFrame, None]

arch.univariate.ARX.y**property** ARX.y : ndarray | DataFrame | Series | None

Returns the dependent variable

Return type

Union[ndarray, DataFrame, Series, None]

1.8.4 arch.univariate.HARX

class arch.univariate.HARX(y=None, x=None, lags=None, constant=True, use_rotated=False, hold_back=None, volatility=None, distribution=None, rescale=None)

Heterogeneous Autoregression (HAR), with optional exogenous regressors, model estimation and simulation

Parameters**y** : {ndarray, Series}

nobs element vector containing the dependent variable

x : {ndarray, DataFrame}, optional

nobs by k element array containing exogenous regressors

lags : {scalar, ndarray}, optional

Description of lag structure of the HAR.

- Scalar included all lags between 1 and the value.
- A 1-d n-element array includes the HAR lags 1:lags[0]+1, 1:lags[1]+1, ... 1:lags[n]+1.
- A 2-d (2,n)-element array that includes the HAR lags of the form lags[0,j]:lags[1,j]+1 for all columns of lags.

constant : **bool**, optional

Flag whether the model should include a constant

use_rotated : **bool**, optional

Flag indicating to use the alternative rotated form of the HAR where HAR lags do not overlap

hold_back : **int**

Number of observations at the start of the sample to exclude when estimating model parameters. Used when comparing models with different lag lengths to estimate on the common sample.

volatility : *VolatilityProcess*, optional

Volatility process to use in the model

distribution : *Distribution*, optional

Error distribution to use in the model

rescale : **bool**, optional

Flag indicating whether to automatically rescale data if the scale of the data is likely to produce convergence issues when estimating model parameters. If False, the model is estimated on the data without transformation. If True, than y is rescaled and the new scale is reported in the estimation results.

Examples

Standard HAR with average lags 1, 5 and 22

```
>>> import numpy as np
>>> from arch.univariate import HARX
>>> y = np.random.RandomState(1234).randn(100)
>>> harx = HARX(y, lags=[1, 5, 22])
>>> res = harx.fit()
```

A standard HAR with average lags 1 and 6 but holding back 10 observations

```
>>> from pandas import Series, date_range
>>> index = date_range('2000-01-01', freq='M', periods=y.shape[0])
>>> y = Series(y, name='y', index=index)
>>> har = HARX(y, lags=[1, 6], hold_back=10)
```

Models with equivalent parametrizations of lags. The first uses overlapping lags.

```
>>> harx_1 = HARX(y, lags=[1, 5, 22])
```

The next uses rotated lags so that they do not overlap.

```
>>> harx_2 = HARX(y, lags=[1, 5, 22], use_rotated=True)
```

The third manually specified overlapping lags.

```
>>> harx_3 = HARX(y, lags=[[1, 1, 1], [1, 5, 22]])
```

The final manually specified non-overlapping lags

```
>>> harx_4 = HARX(y, lags=[[1, 2, 6], [1, 5, 22]])
```

It is simple to verify that these are the equivalent by inspecting the R2.

```
>>> models = [harx_1, harx_2, harx_3, harx_4]
>>> print([mod.fit().rsquared for mod in models])
0.085, 0.085, 0.085, 0.085
```

Notes

The HAR-X model is described by

$$y_t = \mu + \sum_{i=1}^p \phi_{L_i} \bar{y}_{t-L_{i,0}:L_{i,1}} + \gamma' x_t + \epsilon_t$$

where $\bar{y}_{t-L_{i,0}:L_{i,1}}$ is the average value of y_t between $t - L_{i,0}$ and $t - L_{i,1}$.

Methods

<code>bounds()</code>	Construct bounds for parameters to use in non-linear optimization
<code>compute_param_cov(params[, backcast, robust])</code>	Computes parameter covariances using numerical derivatives.
<code>constraints()</code>	Construct linear constraint arrays for use in non-linear optimization
<code>fit([update_freq, disp, starting_values, ...])</code>	Estimate model parameters
<code>fix(params[, first_obs, last_obs])</code>	Allows an ARCHModelFixedResult to be constructed from fixed parameters.
<code>forecast(params[, horizon, start, align, ...])</code>	Construct forecasts from estimated model
<code>parameter_names()</code>	List of parameters names
<code>resids(params[, y, regressors])</code>	Compute model residuals
<code>simulate(params, nobs[, burn, ...])</code>	Simulates data from a linear regression, AR or HAR models
<code>starting_values()</code>	Returns starting values for the mean model, often the same as the values returned from fit

arch.univariate.HARX.bounds

HARX.bounds()

Construct bounds for parameters to use in non-linear optimization

Returns

bounds – Bounds for parameters to use in estimation.

Return type

list (2-tuple of float)

arch.univariate.HARX.compute_param_cov

HARX.compute_param_cov(params, backcast=*None*, robust=*True*)

Computes parameter covariances using numerical derivatives.

Parameters

params : ndarray

Model parameters

backcast : float

Value to use for pre-sample observations

robust : bool, optional

Flag indicating whether to use robust standard errors (True) or classic MLE (False)

Return type

ndarray

arch.univariate.HARX.constraints

HARX.constraints()

Construct linear constraint arrays for use in non-linear optimization

Return type

tuple[ndarray, ndarray]

Returns

- **a** (ndarray) – Number of constraints by number of parameters loading array
- **b** (ndarray) – Number of constraints array of lower bounds

Notes

Parameters satisfy $a \cdot \text{parameters} - b \geq 0$

arch.univariate.HARX.fit

HARX.fit(update_freq=1, disp='final', starting_values=*None*, cov_type='robust', show_warning=*True*, first_obs=*None*, last_obs=*None*, tol=*None*, options=*None*, backcast=*None*)

Estimate model parameters

Parameters

update_freq : int, optional

Frequency of iteration updates. Output is generated every *update_freq* iterations. Set to 0 to disable iterative output.

disp : {bool, "off", "final"}

Either 'final' to print optimization result or 'off' to display nothing. If using a boolean, False is "off" and True is "final"

starting_values : ndarray, optional

Array of starting values to use. If not provided, starting values are constructed by the model components.

cov_type : str, optional

Estimation method of parameter covariance. Supported options are ‘robust’, which does not assume the Information Matrix Equality holds and ‘classic’ which does. In the ARCH literature, ‘robust’ corresponds to Bollerslev-Wooldridge covariance estimator.

show_warning : bool, optional

Flag indicating whether convergence warnings should be shown.

first_obs : {int, str, datetime, Timestamp}

First observation to use when estimating model

last_obs : {int, str, datetime, Timestamp}

Last observation to use when estimating model

tol : float, optional

Tolerance for termination.

options : dict, optional

Options to pass to *scipy.optimize.minimize*. Valid entries include ‘ftol’, ‘eps’, ‘disp’, and ‘maxiter’.

backcast : {float, ndarray}, optional

Value to use as backcast. Should be measure σ_0^2 since model-specific non-linear transformations are applied to value before computing the variance recursions.

Returns

results – Object containing model results

Return type

ARCHModelResult

Notes

A ConvergenceWarning is raised if SciPy’s optimizer indicates difficulty finding the optimum.

Parameters are optimized using SLSQP.

arch.univariate.HARX.fix

HARX.fix(params, first_obs=*None*, last_obs=*None*)

Allows an ARCHModelFixedResult to be constructed from fixed parameters.

Parameters**params : {ndarray, Series}**

User specified parameters to use when generating the result. Must have the correct number of parameters for a given choice of mean model, volatility model and distribution.

first_obs : {int, str, datetime, Timestamp}

First observation to use when fixing model

last_obs : {int, str, datetime, Timestamp}

Last observation to use when fixing model

Returns

results – Object containing model results

Return type

ARCHModelFixedResult

Notes

Parameters are not checked against model-specific constraints.

arch.univariate.HARX.forecast

```
HARX.forecast(params, horizon=1, start=None, align='origin', method='analytic', simulations=1000,
               rng=None, random_state=None, *, reindex=None, x=None)
```

Construct forecasts from estimated model

Parameters

params : {ndarray, Series}

Parameters required to forecast. Must be identical in shape to the parameters computed by fitting the model.

horizon : int, optional

Number of steps to forecast

start : {int, datetime, Timestamp, str}, optional

An integer, datetime or str indicating the first observation to produce the forecast for. Date-times can only be used with pandas inputs that have a datetime index. Strings must be convertible to a date time, such as in '1945-01-01'.

align : str, optional

Either 'origin' or 'target'. When set of 'origin', the t-th row of forecasts contains the forecasts for t+1, t+2, ..., t+h. When set to 'target', the t-th row contains the 1-step ahead forecast from time t-1, the 2 step from time t-2, ..., and the h-step from time t-h. 'target' simplified computing forecast errors since the realization and h-step forecast are aligned.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic. The method only affects the variance forecast generation. Not all volatility models support all methods. In particular, volatility models that do not evolve in squares such as EGARCH or TARCH do not support the 'analytic' method for horizons > 1.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable, optional

Custom random number generator to use in simulation-based forecasts. Must produce random samples using the syntax *rng(size)* where size the 2-element tuple (simulations, horizon).

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

reindex : bool, optional

Whether to reindex the forecasts to have the same dimension as the series being forecast. Prior to 4.18 this was the default. As of 4.19 this is now optional. If not provided, a warning is raised about the future change in the default which will occur after September 2021.

New in version 4.19.

x : {dict[label, array_like], array_like}

Values to use for exogenous regressors if any are included in the model. Three formats are accepted:

- 2-d array-like: This format can be used when there is a single exogenous variable. The input must have shape (nforecast, horizon) or (nobs, horizon) where nforecast is the number of forecasting periods and nobs is the original shape of y. For example, if a single series of forecasts are made from the end of the sample with a horizon of 10, then the input can be (1, 10). Alternatively, if the original data had 1000 observations, then the input can be (1000, 10), and only the final row is used to produce forecasts.
- A dictionary of 2-d array-like: This format is identical to the previous except that the dictionary keys must match the names of the exog variables. Requires that the exog variables were passed as a pandas DataFrame.
- A 3-d NumPy array (or equivalent). In this format, each panel (0th axis) is a 2-d array that must have shape (nforecast, horizon) or (nobs, horizon). The array x[j] corresponds to the j-th column of the exogenous variables.

Due to the complexity required to accommodate all scenarios, please see the example notebook that demonstrates the valid formats for x.

New in version 4.19.

Returns

Container for forecasts. Key properties are mean, variance and residual_variance.

Return type

arch.univariate.base.ARCHModelForecast

Examples

```
>>> import pandas as pd
>>> from arch import arch_model
>>> am = arch_model(None, mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> sim_data = am.simulate([0.1, 0.4, 0.3, 0.2, 1.0], 250)
>>> sim_data.index = pd.date_range('2000-01-01', periods=250)
>>> am = arch_model(sim_data['data'], mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> res = am.fit()
>>> fig = res.hedgehog_plot()
```

Notes

The most basic 1-step ahead forecast will return a vector with the same length as the original data, where the t-th value will be the time-t forecast for time t + 1. When the horizon is > 1, and when using the default value for *align*, the forecast value in position [t, h] is the time-t, h+1 step ahead forecast.

If model contains exogenous variables (model.x is not None), then only 1-step ahead forecasts are available. Using horizon > 1 will produce a warning and all columns, except the first, will be nan-filled.

If *align* is 'origin', forecast[t,h] contains the forecast made using y[:t] (that is, up to but not including t) for horizon h + 1. For example, y[100,2] contains the 3-step ahead forecast using the first 100 data points, which will correspond to the realization y[100 + 2]. If *align* is 'target', then the same forecast is in location [102, 2], so that it is aligned with the observation to use when evaluating, but still in the same column.

arch.univariate.HARX.parameter_names**HARX.parameter_names()**

List of parameters names

Returns**names** – List of variable names for the mean model**Return type**

list (str)

arch.univariate.HARX.resids**HARX.resids(params, y=None, regressors=None)**

Compute model residuals

Parameters**params : ndarray**

Model parameters

y : ndarray, optional

Alternative values to use when computing model residuals

regressors : ndarray, optional

Alternative regressor values to use when computing model residuals

Returns**resids** – Model residuals**Return type**

ndarray

arch.univariate.HARX.simulate**HARX.simulate(params, nobs, burn=500, initial_value=None, x=None, initial_value_vol=None)**

Simulates data from a linear regression, AR or HAR models

Parameters**params : array_like**

Parameters to use when simulating the model. Parameter order is [mean volatility distribution] where the parameters of the mean model are ordered [constant lag[0] lag[1] ... lag[p] ex[0] ... ex[k-1]] where lag[j] indicates the coefficient on the jth lag in the model and ex[j] is the coefficient on the jth exogenous variable.

nobs : int

Length of series to simulate

burn : int, optional

Number of values to simulate to initialize the model and remove dependence on initial values.

initial_value : {ndarray, float}, optionalEither a scalar value or *max(lags)* array set of initial values to use when initializing the model. If omitted, 0.0 is used.**x : {ndarray, DataFrame}, optional**

nobs + burn by k array of exogenous variables to include in the simulation.

initial_value_vol : {ndarray, float}, optional

An array or scalar to use when initializing the volatility process.

Returns

simulated_data – DataFrame with columns data containing the simulated values, volatility, containing the conditional volatility and errors containing the errors used in the simulation

Return type

DataFrame

Examples

```
>>> import numpy as np
>>> from arch.univariate import HARX, GARCH
>>> harx = HARX(lags=[1, 5, 22])
>>> harx.volatility = GARCH()
>>> harx_params = np.array([1, 0.2, 0.3, 0.4])
>>> garch_params = np.array([0.01, 0.07, 0.92])
>>> params = np.concatenate((harx_params, garch_params))
>>> sim_data = harx.simulate(params, 1000)
```

Simulating models with exogenous regressors requires the regressors to have nobs plus burn data points

```
>>> nobs = 100
>>> burn = 200
>>> x = np.random.randn(nobs + burn, 2)
>>> x_params = np.array([1.0, 2.0])
>>> params = np.concatenate((harx_params, x_params, garch_params))
>>> sim_data = harx.simulate(params, nobs=nobs, burn=burn, x=x)
```

arch.univariate.HARX.starting_values

HARX.starting_values()

Returns starting values for the mean model, often the same as the values returned from fit

Returns

sv – Starting values

Return type

ndarray

Properties

<i>distribution</i>	Set or gets the error distribution
<i>name</i>	The name of the model.
<i>num_params</i>	Returns the number of parameters
<i>volatility</i>	Set or gets the volatility process
<i>x</i>	Gets the value of the exogenous regressors in the model
<i>y</i>	Returns the dependent variable

arch.univariate.HARX.distribution**property** HARX.distribution : *Distribution*

Set or gets the error distribution

Distributions must be a subclass of Distribution

Return type
*Distribution***arch.univariate.HARX.name****property** HARX.name : str

The name of the model.

Return type
str**arch.univariate.HARX.num_params****property** HARX.num_params : int

Returns the number of parameters

arch.univariate.HARX.volatility**property** HARX.volatility : *VolatilityProcess*

Set or gets the volatility process

Volatility processes must be a subclass of VolatilityProcess

Return type
*VolatilityProcess***arch.univariate.HARX.x****property** HARX.x : ndarray | DataFrame | None

Gets the value of the exogenous regressors in the model

Return type
Union[ndarray, DataFrame, None]**arch.univariate.HARX.y****property** HARX.y : ndarray | DataFrame | Series | None

Returns the dependent variable

Return type
Union[ndarray, DataFrame, Series, None]

1.8.5 arch.univariate.LS

```
class arch.univariate.LS(y=None, x=None, constant=True, hold_back=None, volatility=None,
                        distribution=None, rescale=None)
```

Least squares model estimation and simulation

Parameters

y : {ndarray, DataFrame}, optional

nobs element vector containing the dependent variable

y=None

nobs by k element array containing exogenous regressors

constant : bool, optional

Flag whether the model should include a constant

hold_back : int

Number of observations at the start of the sample to exclude when estimating model parameters. Used when comparing models with different lag lengths to estimate on the common sample.

volatility : *VolatilityProcess*, optional

Volatility process to use in the model

distribution : *Distribution*, optional

Error distribution to use in the model

rescale : bool, optional

Flag indicating whether to automatically rescale data if the scale of the data is likely to produce convergence issues when estimating model parameters. If False, the model is estimated on the data without transformation. If True, then y is rescaled and the new scale is reported in the estimation results.

Examples

```
>>> import numpy as np
>>> from arch.univariate import LS
>>> y = np.random.randn(100)
>>> x = np.random.randn(100, 2)
>>> ls = LS(y, x)
>>> res = ls.fit()
```

Notes

The LS model is described by

$$y_t = \mu + \gamma' x_t + \epsilon_t$$

Methods

<code>bounds()</code>	Construct bounds for parameters to use in non-linear optimization
<code>compute_param_cov(params[, backcast, robust])</code>	Computes parameter covariances using numerical derivatives.
<code>constraints()</code>	Construct linear constraint arrays for use in non-linear optimization
<code>fit([update_freq, disp, starting_values, ...])</code>	Estimate model parameters
<code>fix(params[, first_obs, last_obs])</code>	Allows an ARCHModelFixedResult to be constructed from fixed parameters.
<code>forecast(params[, horizon, start, align, ...])</code>	Construct forecasts from estimated model
<code>parameter_names()</code>	List of parameters names
<code>resids(params[, y, regressors])</code>	Compute model residuals
<code>simulate(params, nobs[, burn, ...])</code>	Simulates data from a linear regression, AR or HAR models
<code>starting_values()</code>	Returns starting values for the mean model, often the same as the values returned from fit

arch.univariate.LS.bounds

LS.bounds()

Construct bounds for parameters to use in non-linear optimization

Returns

bounds – Bounds for parameters to use in estimation.

Return type

list (2-tuple of float)

arch.univariate.LS.compute_param_cov

LS.compute_param_cov(params, backcast=*None*, robust=*True*)

Computes parameter covariances using numerical derivatives.

Parameters

params : ndarray

Model parameters

backcast : float

Value to use for pre-sample observations

robust : bool, optional

Flag indicating whether to use robust standard errors (True) or classic MLE (False)

Return type

ndarray

arch.univariate.LS.constraints

LS.constraints()

Construct linear constraint arrays for use in non-linear optimization

Return type

`tuple[ndarray, ndarray]`

Returns

- **a** (*ndarray*) – Number of constraints by number of parameters loading array
- **b** (*ndarray*) – Number of constraints array of lower bounds

Notes

Parameters satisfy $a \cdot \text{parameters} - b \geq 0$

arch.univariate.LS.fit

`LS.fit(update_freq=1, disp='final', starting_values=None, cov_type='robust', show_warning=True, first_obs=None, last_obs=None, tol=None, options=None, backcast=None)`

Estimate model parameters

Parameters

update_freq : `int`, optional

Frequency of iteration updates. Output is generated every *update_freq* iterations. Set to 0 to disable iterative output.

disp : {`bool`, `"off"`, `"final"`}

Either 'final' to print optimization result or 'off' to display nothing. If using a boolean, False is "off" and True is "final"

starting_values : `ndarray`, optional

Array of starting values to use. If not provided, starting values are constructed by the model components.

cov_type : `str`, optional

Estimation method of parameter covariance. Supported options are 'robust', which does not assume the Information Matrix Equality holds and 'classic' which does. In the ARCH literature, 'robust' corresponds to Bollerslev-Wooldridge covariance estimator.

show_warning : `bool`, optional

Flag indicating whether convergence warnings should be shown.

first_obs : {`int`, `str`, `datetime`, `Timestamp`}

First observation to use when estimating model

last_obs : {`int`, `str`, `datetime`, `Timestamp`}

Last observation to use when estimating model

tol : `float`, optional

Tolerance for termination.

options : `dict`, optional

Options to pass to `scipy.optimize.minimize`. Valid entries include 'ftol', 'eps', 'disp', and 'maxiter'.

backcast : {float, ndarray}, optional

Value to use as backcast. Should be measure σ_0^2 since model-specific non-linear transformations are applied to value before computing the variance recursions.

Returns

results – Object containing model results

Return type

ARCHModelResult

Notes

A ConvergenceWarning is raised if SciPy's optimizer indicates difficulty finding the optimum.

Parameters are optimized using SLSQP.

arch.univariate.LS.fix

LS.fix(params, first_obs=*None*, last_obs=*None*)

Allows an ARCHModelFixedResult to be constructed from fixed parameters.

Parameters

params : {ndarray, Series}

User specified parameters to use when generating the result. Must have the correct number of parameters for a given choice of mean model, volatility model and distribution.

first_obs : {int, str, datetime, Timestamp}

First observation to use when fixing model

last_obs : {int, str, datetime, Timestamp}

Last observation to use when fixing model

Returns

results – Object containing model results

Return type

ARCHModelFixedResult

Notes

Parameters are not checked against model-specific constraints.

arch.univariate.LS.forecast

LS.forecast(params, horizon=*1*, start=*None*, align='origin', method='analytic', simulations=*1000*, rng=*None*, random_state=*None*, *, reindex=*None*, x=*None*)

Construct forecasts from estimated model

Parameters

params : {ndarray, Series}

Parameters required to forecast. Must be identical in shape to the parameters computed by fitting the model.

horizon : int, optional

Number of steps to forecast

start : {int, datetime, Timestamp, str}, optional

An integer, datetime or str indicating the first observation to produce the forecast for. Date-times can only be used with pandas inputs that have a datetime index. Strings must be convertible to a date time, such as in '1945-01-01'.

align : str, optional

Either 'origin' or 'target'. When set of 'origin', the t-th row of forecasts contains the forecasts for t+1, t+2, ..., t+h. When set to 'target', the t-th row contains the 1-step ahead forecast from time t-1, the 2 step from time t-2, ..., and the h-step from time t-h. 'target' simplified computing forecast errors since the realization and h-step forecast are aligned.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic. The method only affects the variance forecast generation. Not all volatility models support all methods. In particular, volatility models that do not evolve in squares such as EGARCH or TARCH do not support the 'analytic' method for horizons > 1.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable, optional

Custom random number generator to use in simulation-based forecasts. Must produce random samples using the syntax *rng(size)* where size the 2-element tuple (simulations, horizon).

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

reindex : bool, optional

Whether to reindex the forecasts to have the same dimension as the series being forecast. Prior to 4.18 this was the default. As of 4.19 this is now optional. If not provided, a warning is raised about the future change in the default which will occur after September 2021.

New in version 4.19.

x : {dict[label, array_like], array_like}

Values to use for exogenous regressors if any are included in the model. Three formats are accepted:

- 2-d array-like: This format can be used when there is a single exogenous variable. The input must have shape (nforecast, horizon) or (nobs, horizon) where nforecast is the number of forecasting periods and nobs is the original shape of y. For example, if a single series of forecasts are made from the end of the sample with a horizon of 10, then the input can be (1, 10). Alternatively, if the original data had 1000 observations, then the input can be (1000, 10), and only the final row is used to produce forecasts.
- A dictionary of 2-d array-like: This format is identical to the previous except that the dictionary keys must match the names of the exog variables. Requires that the exog variables were passed as a pandas DataFrame.
- A 3-d NumPy array (or equivalent). In this format, each panel (0th axis) is a 2-d array that must have shape (nforecast, horizon) or (nobs,horizon). The array x[j] corresponds to the j-th column of the exogenous variables.

Due to the complexity required to accommodate all scenarios, please see the example notebook that demonstrates the valid formats for x.

New in version 4.19.

Returns

Container for forecasts. Key properties are `mean`, `variance` and `residual_variance`.

Return type

arch.univariate.base.ARCHModelForecast

Examples

```
>>> import pandas as pd
>>> from arch import arch_model
>>> am = arch_model(None, mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> sim_data = am.simulate([0.1, 0.4, 0.3, 0.2, 1.0], 250)
>>> sim_data.index = pd.date_range('2000-01-01', periods=250)
>>> am = arch_model(sim_data['data'], mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> res = am.fit()
>>> fig = res.hedgehog_plot()
```

Notes

The most basic 1-step ahead forecast will return a vector with the same length as the original data, where the t -th value will be the time- t forecast for time $t + 1$. When the horizon is > 1 , and when using the default value for *align*, the forecast value in position $[t, h]$ is the time- $t, h+1$ step ahead forecast.

If model contains exogenous variables (`model.x` is not `None`), then only 1-step ahead forecasts are available. Using horizon > 1 will produce a warning and all columns, except the first, will be nan-filled.

If *align* is 'origin', `forecast[t, h]` contains the forecast made using `y[:t]` (that is, up to but not including t) for horizon $h + 1$. For example, `y[100, 2]` contains the 3-step ahead forecast using the first 100 data points, which will correspond to the realization `y[100 + 2]`. If *align* is 'target', then the same forecast is in location `[102, 2]`, so that it is aligned with the observation to use when evaluating, but still in the same column.

arch.univariate.LS.parameter_names**LS.parameter_names()**

List of parameters names

Returns

names – List of variable names for the mean model

Return type

list (str)

arch.univariate.LS.resids**LS.resids(params, y=None, regressors=None)**

Compute model residuals

Parameters

params : ndarray

Model parameters

y : ndarray, optional

Alternative values to use when computing model residuals

regressors : ndarray, optional

Alternative regressor values to use when computing model residuals

Returns

resids – Model residuals

Return type

ndarray

arch.univariate.LS.simulate

LS.simulate(params, nobs, burn=500, initial_value=None, x=None, initial_value_vol=None)

Simulates data from a linear regression, AR or HAR models

Parameters

params : array_like

Parameters to use when simulating the model. Parameter order is [mean volatility distribution] where the parameters of the mean model are ordered [constant lag[0] lag[1] ... lag[p] ex[0] ... ex[k-1]] where lag[j] indicates the coefficient on the jth lag in the model and ex[j] is the coefficient on the jth exogenous variable.

nobs : int

Length of series to simulate

burn : int, optional

Number of values to simulate to initialize the model and remove dependence on initial values.

initial_value : {ndarray, float}, optional

Either a scalar value or *max(lags)* array set of initial values to use when initializing the model. If omitted, 0.0 is used.

x : {ndarray, DataFrame}, optional

nobs + burn by k array of exogenous variables to include in the simulation.

initial_value_vol : {ndarray, float}, optional

An array or scalar to use when initializing the volatility process.

Returns

simulated_data – DataFrame with columns data containing the simulated values, volatility, containing the conditional volatility and errors containing the errors used in the simulation

Return type

DataFrame

Examples

```
>>> import numpy as np
>>> from arch.univariate import HARX, GARCH
>>> harx = HARX(lags=[1, 5, 22])
>>> harx.volatility = GARCH()
>>> harx_params = np.array([1, 0.2, 0.3, 0.4])
>>> garch_params = np.array([0.01, 0.07, 0.92])
>>> params = np.concatenate((harx_params, garch_params))
>>> sim_data = harx.simulate(params, 1000)
```

Simulating models with exogenous regressors requires the regressors to have nobs plus burn data points

```

>>> nobs = 100
>>> burn = 200
>>> x = np.random.randn(nobs + burn, 2)
>>> x_params = np.array([1.0, 2.0])
>>> params = np.concatenate((harx_params, x_params, garch_params))
>>> sim_data = harx.simulate(params, nobs=nobs, burn=burn, x=x)

```

arch.univariate.LS.starting_values

LS.starting_values()

Returns starting values for the mean model, often the same as the values returned from fit

Returns

sv – Starting values

Return type

ndarray

Properties

<i>distribution</i>	Set or gets the error distribution
<i>name</i>	The name of the model.
<i>num_params</i>	Returns the number of parameters
<i>volatility</i>	Set or gets the volatility process
<i>x</i>	Gets the value of the exogenous regressors in the model
<i>y</i>	Returns the dependent variable

arch.univariate.LS.distribution

property LS.distribution : *Distribution*

Set or gets the error distribution

Distributions must be a subclass of Distribution

Return type

Distribution

arch.univariate.LS.name

property LS.name : str

The name of the model.

Return type

str

arch.univariate.LS.num_params**property** LS.num_params : int

Returns the number of parameters

arch.univariate.LS.volatility**property** LS.volatility : *VolatilityProcess*

Set or gets the volatility process

Volatility processes must be a subclass of VolatilityProcess

Return type*VolatilityProcess***arch.univariate.LS.x****property** LS.x : ndarray | DataFrame | None

Gets the value of the exogenous regressors in the model

Return type

Union[ndarray, DataFrame, None]

arch.univariate.LS.y**property** LS.y : ndarray | DataFrame | Series | None

Returns the dependent variable

Return type

Union[ndarray, DataFrame, Series, None]

1.8.6 (G)ARCH-in-mean Models

(G)ARCH-in-mean models allow the conditional variance (or a transformation of it) to enter the conditional mean.

ARCHInMean([y, x, lags, constant, ...])(G)ARCH-in-mean model and simulation

arch.univariate.ARCHInMean**class** arch.univariate.ARCHInMean(y=*None*, x=*None*, lags=*None*, constant=*True*, hold_back=*None*, volatility=*None*, distribution=*None*, rescale=*None*, form='vol')

(G)ARCH-in-mean model and simulation

Parameters**y** : {ndarray, Series}

nobs element vector containing the dependent variable

x : {ndarray, DataFrame}, optional

nobs by k element array containing exogenous regressors

lags : {scalar, 1-d array}, optional

Description of lag structure of the HAR. Scalar included all lags between 1 and the value. A 1-d array includes the AR lags lags[0], lags[1], ...

constant : bool, optional

Flag whether the model should include a constant

hold_back : int, optional

Number of observations at the start of the sample to exclude when estimating model parameters. Used when comparing models with different lag lengths to estimate on the common sample.

volatility : *VolatilityProcess*, optional

Volatility process to use in the model. volatility.updateable must return True.

distribution : *Distribution*, optional

Error distribution to use in the model

rescale : bool, optional

Flag indicating whether to automatically rescale data if the scale of the data is likely to produce convergence issues when estimating model parameters. If False, the model is estimated on the data without transformation. If True, than y is rescaled and the new scale is reported in the estimation results.

form : {"log", "vol", "var", int, float}

The form of the conditional variance that appears in the mean equation. The string names use the log of the conditional variance ("log"), the square-root of the conditional variance ("vol") or the conditional variance. When specified using a float, interpreted as σ_t^{form} so that 1 is equivalent to "vol" and 2 is equivalent to "var". When using a number, must be different from 0.

Examples

```
>>> import numpy as np
>>> from arch.univariate import ARCHInMean, GARCH
>>> from arch.data.sp500 import load
>>> sp500 = load()
>>> rets = 100 * sp500["Adj Close"].pct_change().dropna()
>>> gim = ARCHInMean(rets, lags=[1, 2], volatility=GARCH())
>>> res = gim.fit()
```

Notes

The (G)arch-in-mean model with exogenous regressors (-X) is described by

$$y_t = \mu + \kappa f(\sigma_t^2) + \sum_{i=1}^p \phi_{L,i} y_{t-L_i} + \gamma' x_t + \epsilon_t$$

where $f(\cdot)$ is the function specified by form.

Methods

<code>bounds()</code>	Construct bounds for parameters to use in non-linear optimization
<code>compute_param_cov(params[, backcast, robust])</code>	Computes parameter covariances using numerical derivatives.
<code>constraints()</code>	Construct linear constraint arrays for use in non-linear optimization
<code>fit([update_freq, disp, starting_values, ...])</code>	Estimate model parameters
<code>fix(params[, first_obs, last_obs])</code>	Allows an ARCHModelFixedResult to be constructed from fixed parameters.
<code>forecast(params[, horizon, start, align, ...])</code>	Construct forecasts from estimated model
<code>parameter_names()</code>	List of parameters names
<code>resids(params[, y, regressors])</code>	Compute model residuals
<code>simulate(params, nobs[, burn, ...])</code>	Simulates data from a linear regression, AR or HAR models
<code>starting_values()</code>	Returns starting values for the mean model, often the same as the values returned from fit

arch.univariate.ARCHInMean.bounds

ARCHInMean.**bounds**()

Construct bounds for parameters to use in non-linear optimization

Returns

bounds – Bounds for parameters to use in estimation.

Return type

list (2-tuple of float)

arch.univariate.ARCHInMean.compute_param_cov

ARCHInMean.**compute_param_cov**(params, backcast=**None**, robust=**True**)

Computes parameter covariances using numerical derivatives.

Parameters

params : ndarray

Model parameters

backcast : float

Value to use for pre-sample observations

robust : bool, optional

Flag indicating whether to use robust standard errors (True) or classic MLE (False)

Return type

ndarray

arch.univariate.ARCHInMean.constraints

`ARCHInMean.constraints()`

Construct linear constraint arrays for use in non-linear optimization

Return type

`tuple[ndarray, ndarray]`

Returns

- **a** (*ndarray*) – Number of constraints by number of parameters loading array
- **b** (*ndarray*) – Number of constraints array of lower bounds

Notes

Parameters satisfy $a \cdot \text{parameters} - b \geq 0$

arch.univariate.ARCHInMean.fit

```
ARCHInMean.fit(update_freq=1, disp='final', starting_values=None, cov_type='robust',
               show_warning=True, first_obs=None, last_obs=None, tol=None, options=None,
               backcast=None)
```

Estimate model parameters

Parameters

update_freq : `int`, optional

Frequency of iteration updates. Output is generated every *update_freq* iterations. Set to 0 to disable iterative output.

disp : `{bool, "off", "final"}`

Either 'final' to print optimization result or 'off' to display nothing. If using a boolean, False is "off" and True is "final"

starting_values : `ndarray`, optional

Array of starting values to use. If not provided, starting values are constructed by the model components.

cov_type : `str`, optional

Estimation method of parameter covariance. Supported options are 'robust', which does not assume the Information Matrix Equality holds and 'classic' which does. In the ARCH literature, 'robust' corresponds to Bollerslev-Wooldridge covariance estimator.

show_warning : `bool`, optional

Flag indicating whether convergence warnings should be shown.

first_obs : `{int, str, datetime, Timestamp}`

First observation to use when estimating model

last_obs : `{int, str, datetime, Timestamp}`

Last observation to use when estimating model

tol : `float`, optional

Tolerance for termination.

options : `dict`, optional

Options to pass to *scipy.optimize.minimize*. Valid entries include 'ftol', 'eps', 'disp', and 'maxiter'.

backcast : {float, ndarray}, optional

Value to use as backcast. Should be measure σ_0^2 since model-specific non-linear transformations are applied to value before computing the variance recursions.

Returns

results – Object containing model results

Return type

ARCHModelResult

Notes

A ConvergenceWarning is raised if SciPy's optimizer indicates difficulty finding the optimum.

Parameters are optimized using SLSQP.

arch.univariate.ARCHInMean.fix

ARCHInMean.**fix**(params, first_obs=*None*, last_obs=*None*)

Allows an ARCHModelFixedResult to be constructed from fixed parameters.

Parameters

params : {ndarray, Series}

User specified parameters to use when generating the result. Must have the correct number of parameters for a given choice of mean model, volatility model and distribution.

first_obs : {int, str, datetime, Timestamp}

First observation to use when fixing model

last_obs : {int, str, datetime, Timestamp}

Last observation to use when fixing model

Returns

results – Object containing model results

Return type

ARCHModelFixedResult

Notes

Parameters are not checked against model-specific constraints.

arch.univariate.ARCHInMean.forecast

ARCHInMean.**forecast**(params, horizon=*1*, start=*None*, align='origin', method='analytic', simulations=*1000*, rng=*None*, random_state=*None*, *, reindex=*None*, x=*None*)

Construct forecasts from estimated model

Parameters

params : {ndarray, Series}

Parameters required to forecast. Must be identical in shape to the parameters computed by fitting the model.

horizon : int, optional

Number of steps to forecast

start : {int, datetime, Timestamp, str}, optional

An integer, datetime or str indicating the first observation to produce the forecast for. Date-times can only be used with pandas inputs that have a datetime index. Strings must be convertible to a date time, such as in '1945-01-01'.

align : str, optional

Either 'origin' or 'target'. When set of 'origin', the t-th row of forecasts contains the forecasts for t+1, t+2, ..., t+h. When set to 'target', the t-th row contains the 1-step ahead forecast from time t-1, the 2 step from time t-2, ..., and the h-step from time t-h. 'target' simplified computing forecast errors since the realization and h-step forecast are aligned.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic. The method only affects the variance forecast generation. Not all volatility models support all methods. In particular, volatility models that do not evolve in squares such as EGARCH or TARCH do not support the 'analytic' method for horizons > 1.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable, optional

Custom random number generator to use in simulation-based forecasts. Must produce random samples using the syntax *rng(size)* where size the 2-element tuple (simulations, horizon).

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

reindex : bool, optional

Whether to reindex the forecasts to have the same dimension as the series being forecast. Prior to 4.18 this was the default. As of 4.19 this is now optional. If not provided, a warning is raised about the future change in the default which will occur after September 2021.

New in version 4.19.

x : {dict[label, array_like], array_like}

Values to use for exogenous regressors if any are included in the model. Three formats are accepted:

- 2-d array-like: This format can be used when there is a single exogenous variable. The input must have shape (nforecast, horizon) or (nobs, horizon) where nforecast is the number of forecasting periods and nobs is the original shape of y. For example, if a single series of forecasts are made from the end of the sample with a horizon of 10, then the input can be (1, 10). Alternatively, if the original data had 1000 observations, then the input can be (1000, 10), and only the final row is used to produce forecasts.
- A dictionary of 2-d array-like: This format is identical to the previous except that the dictionary keys must match the names of the exog variables. Requires that the exog variables were passed as a pandas DataFrame.
- A 3-d NumPy array (or equivalent). In this format, each panel (0th axis) is a 2-d array that must have shape (nforecast, horizon) or (nobs, horizon). The array x[j] corresponds to the j-th column of the exogenous variables.

Due to the complexity required to accommodate all scenarios, please see the example notebook that demonstrates the valid formats for `x`.

New in version 4.19.

Returns

Container for forecasts. Key properties are `mean`, `variance` and `residual_variance`.

Return type

arch.univariate.base.ARCHModelForecast

Examples

```
>>> import pandas as pd
>>> from arch import arch_model
>>> am = arch_model(None, mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> sim_data = am.simulate([0.1, 0.4, 0.3, 0.2, 1.0], 250)
>>> sim_data.index = pd.date_range('2000-01-01', periods=250)
>>> am = arch_model(sim_data['data'], mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> res = am.fit()
>>> fig = res.hedgehog_plot()
```

Notes

The most basic 1-step ahead forecast will return a vector with the same length as the original data, where the t -th value will be the time- t forecast for time $t + 1$. When the horizon is > 1 , and when using the default value for `align`, the forecast value in position $[t, h]$ is the time- t , $h+1$ step ahead forecast.

If model contains exogenous variables (model.`x` is not `None`), then only 1-step ahead forecasts are available. Using horizon > 1 will produce a warning and all columns, except the first, will be nan-filled.

If `align` is 'origin', `forecast[t, h]` contains the forecast made using `y[:t]` (that is, up to but not including t) for horizon $h + 1$. For example, `y[100, 2]` contains the 3-step ahead forecast using the first 100 data points, which will correspond to the realization `y[100 + 2]`. If `align` is 'target', then the same forecast is in location `[102, 2]`, so that it is aligned with the observation to use when evaluating, but still in the same column.

`arch.univariate.ARCHInMean.parameter_names`

`ARCHInMean.parameter_names()`

List of parameters names

Returns

names – List of variable names for the mean model

Return type

`list (str)`

arch.univariate.ARCHInMean.resids

`ARCHInMean.resids(params, y=None, regressors=None)`

Compute model residuals

Parameters

params : ndarray

Model parameters

y : ndarray, optional

Alternative values to use when computing model residuals

regressors : ndarray, optional

Alternative regressor values to use when computing model residuals

Returns

resids – Model residuals

Return type

ndarray

arch.univariate.ARCHInMean.simulate

`ARCHInMean.simulate(params, nobs, burn=500, initial_value=None, x=None, initial_value_vol=None)`

Simulates data from a linear regression, AR or HAR models

Parameters

params : array_like

Parameters to use when simulating the model. Parameter order is [mean volatility distribution] where the parameters of the mean model are ordered [constant lag[0] lag[1] ... lag[p] ex[0] ... ex[k-1]] where lag[j] indicates the coefficient on the jth lag in the model and ex[j] is the coefficient on the jth exogenous variable.

nobs : int

Length of series to simulate

burn : int, optional

Number of values to simulate to initialize the model and remove dependence on initial values.

initial_value : {ndarray, float}, optional

Either a scalar value or *max(lags)* array set of initial values to use when initializing the model. If omitted, 0.0 is used.

x : {ndarray, DataFrame}, optional

nobs + burn by k array of exogenous variables to include in the simulation.

initial_value_vol : {ndarray, float}, optional

An array or scalar to use when initializing the volatility process.

Returns

simulated_data – DataFrame with columns data containing the simulated values, volatility, containing the conditional volatility and errors containing the errors used in the simulation

Return type

DataFrame

Examples

```
>>> import numpy as np
>>> from arch.univariate import HARX, GARCH
>>> harx = HARX(lags=[1, 5, 22])
>>> harx.volatility = GARCH()
>>> harx_params = np.array([1, 0.2, 0.3, 0.4])
>>> garch_params = np.array([0.01, 0.07, 0.92])
>>> params = np.concatenate((harx_params, garch_params))
>>> sim_data = harx.simulate(params, 1000)
```

Simulating models with exogenous regressors requires the regressors to have nobs plus burn data points

```
>>> nobs = 100
>>> burn = 200
>>> x = np.random.randn(nobs + burn, 2)
>>> x_params = np.array([1.0, 2.0])
>>> params = np.concatenate((harx_params, x_params, garch_params))
>>> sim_data = harx.simulate(params, nobs=nobs, burn=burn, x=x)
```

arch.univariate.ARCHInMean.starting_values

ARCHInMean.starting_values()

Returns starting values for the mean model, often the same as the values returned from fit

Returns

sv – Starting values

Return type

ndarray

Properties

<i>distribution</i>	Set or gets the error distribution
<i>form</i>	The form of the conditional variance in the mean
<i>name</i>	The name of the model.
<i>num_params</i>	Returns the number of parameters
<i>volatility</i>	Set or gets the volatility process
<i>x</i>	Gets the value of the exogenous regressors in the model
<i>y</i>	Returns the dependent variable

arch.univariate.ARCHInMean.distribution**property** ARCHInMean.distribution : *Distribution*

Set or gets the error distribution

Distributions must be a subclass of Distribution

Return type*Distribution***arch.univariate.ARCHInMean.form****property** ARCHInMean.form : int | float | 'log' | 'vol' | 'var'

The form of the conditional variance in the mean

Return type

Union[int, float, Literal['log', 'vol', 'var']]

arch.univariate.ARCHInMean.name**property** ARCHInMean.name : str

The name of the model.

Return type

str

arch.univariate.ARCHInMean.num_params**property** ARCHInMean.num_params : int

Returns the number of parameters

arch.univariate.ARCHInMean.volatility**property** ARCHInMean.volatility : *VolatilityProcess*

Set or gets the volatility process

Volatility processes must be a subclass of VolatilityProcess

Return type*VolatilityProcess***arch.univariate.ARCHInMean.x****property** ARCHInMean.x : ndarray | DataFrame | None

Gets the value of the exogenous regressors in the model

Return type

Union[ndarray, DataFrame, None]

arch.univariate.ARCHInMean.y

property ARCHInMean.y : ndarray | DataFrame | Series | None

Returns the dependent variable

Return type

Union[ndarray, DataFrame, Series, None]

Special Requirements

Not all volatility processes support application to AIM modeling. Specifically, the property `updateable` must be `True`.

```
In [1]: from arch.univariate import GARCH, EGARCH
```

```
In [2]: GARCH().updateable
```

```
Out[2]: True
```

```
In [3]: EGARCH().updateable
```

```
Out[3]: True
```

1.8.7 Writing New Mean Models

All mean models must inherit from `:class:ARCHModel` and provide all public methods. There are two optional private methods that should be provided if applicable.

ARCHModel([y, volatility, distribution, ...])

Abstract base class for mean models in ARCH processes.

arch.univariate.base.ARCHModel

```
class arch.univariate.base.ARCHModel(y=None, volatility=None, distribution=None, hold_back=None,
                                     rescale=None)
```

Abstract base class for mean models in ARCH processes. Specifies the conditional mean process.

All public methods that raise `NotImplementedError` should be overridden by any subclass. Private methods that raise `NotImplementedError` are optional to override but recommended where applicable.

Methods

<code>bounds()</code>	Construct bounds for parameters to use in non-linear optimization
<code>compute_param_cov(params[, backcast, robust])</code>	Computes parameter covariances using numerical derivatives.
<code>constraints()</code>	Construct linear constraint arrays for use in non-linear optimization
<code>fit([update_freq, disp, starting_values, ...])</code>	Estimate model parameters
<code>fix(params[, first_obs, last_obs])</code>	Allows an ARCHModelFixedResult to be constructed from fixed parameters.
<code>forecast(params[, horizon, start, align, ...])</code>	Construct forecasts from estimated model
<code>parameter_names()</code>	List of parameters names
<code>resids(params[, y, regressors])</code>	Compute model residuals
<code>simulate(params, nobs[, burn, ...])</code>	
rtype DataFrame	
<code>starting_values()</code>	Returns starting values for the mean model, often the same as the values returned from fit

arch.univariate.base.ARCHModel.bounds

ARCHModel.**bounds**()

Construct bounds for parameters to use in non-linear optimization

Returns

bounds – Bounds for parameters to use in estimation.

Return type

list (2-tuple of float)

arch.univariate.base.ARCHModel.compute_param_cov

ARCHModel.**compute_param_cov**(params, backcast=**None**, robust=**True**)

Computes parameter covariances using numerical derivatives.

Parameters

params : ndarray
Model parameters

backcast : float
Value to use for pre-sample observations

robust : bool, optional
Flag indicating whether to use robust standard errors (True) or classic MLE (False)

Return type

ndarray

arch.univariate.base.ARCHModel.constraints

`ARCHModel.constraints()`

Construct linear constraint arrays for use in non-linear optimization

Return type

`tuple[ndarray, ndarray]`

Returns

- **a** (*ndarray*) – Number of constraints by number of parameters loading array
- **b** (*ndarray*) – Number of constraints array of lower bounds

Notes

Parameters satisfy $a \cdot \text{parameters} - b \geq 0$

arch.univariate.base.ARCHModel.fit

`ARCHModel.fit(update_freq=1, disp='final', starting_values=None, cov_type='robust', show_warning=True, first_obs=None, last_obs=None, tol=None, options=None, backcast=None)`

Estimate model parameters

Parameters

update_freq : `int`, optional

Frequency of iteration updates. Output is generated every *update_freq* iterations. Set to 0 to disable iterative output.

disp : `{bool, "off", "final"}`

Either 'final' to print optimization result or 'off' to display nothing. If using a boolean, False is "off" and True is "final"

starting_values : `ndarray`, optional

Array of starting values to use. If not provided, starting values are constructed by the model components.

cov_type : `str`, optional

Estimation method of parameter covariance. Supported options are 'robust', which does not assume the Information Matrix Equality holds and 'classic' which does. In the ARCH literature, 'robust' corresponds to Bollerslev-Wooldridge covariance estimator.

show_warning : `bool`, optional

Flag indicating whether convergence warnings should be shown.

first_obs : `{int, str, datetime, Timestamp}`

First observation to use when estimating model

last_obs : `{int, str, datetime, Timestamp}`

Last observation to use when estimating model

tol : `float`, optional

Tolerance for termination.

options : `dict`, optional

Options to pass to *scipy.optimize.minimize*. Valid entries include 'ftol', 'eps', 'disp', and 'maxiter'.

backcast : {float, ndarray}, optional

Value to use as backcast. Should be measure σ_0^2 since model-specific non-linear transformations are applied to value before computing the variance recursions.

Returns

results – Object containing model results

Return type

ARCHModelResult

Notes

A ConvergenceWarning is raised if SciPy's optimizer indicates difficulty finding the optimum.

Parameters are optimized using SLSQP.

arch.univariate.base.ARCHModel.fix

`ARCHModel.fix(params, first_obs=None, last_obs=None)`

Allows an ARCHModelFixedResult to be constructed from fixed parameters.

Parameters

params : {ndarray, Series}

User specified parameters to use when generating the result. Must have the correct number of parameters for a given choice of mean model, volatility model and distribution.

first_obs : {int, str, datetime, Timestamp}

First observation to use when fixing model

last_obs : {int, str, datetime, Timestamp}

Last observation to use when fixing model

Returns

results – Object containing model results

Return type

ARCHModelFixedResult

Notes

Parameters are not checked against model-specific constraints.

arch.univariate.base.ARCHModel.forecast

abstract `ARCHModel.forecast(params, horizon=1, start=None, align='origin', method='analytic', simulations=1000, rng=None, random_state=None, *, reindex=None, x=None)`

Construct forecasts from estimated model

Parameters

params : {ndarray, Series}

Parameters required to forecast. Must be identical in shape to the parameters computed by fitting the model.

horizon : int, optional

Number of steps to forecast

start : {int, datetime, Timestamp, str}, optional

An integer, datetime or str indicating the first observation to produce the forecast for. Date-times can only be used with pandas inputs that have a datetime index. Strings must be convertible to a date time, such as in '1945-01-01'.

align : str, optional

Either 'origin' or 'target'. When set of 'origin', the t-th row of forecasts contains the forecasts for t+1, t+2, ..., t+h. When set to 'target', the t-th row contains the 1-step ahead forecast from time t-1, the 2 step from time t-2, ..., and the h-step from time t-h. 'target' simplified computing forecast errors since the realization and h-step forecast are aligned.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic. The method only affects the variance forecast generation. Not all volatility models support all methods. In particular, volatility models that do not evolve in squares such as EGARCH or TARCH do not support the 'analytic' method for horizons > 1.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable, optional

Custom random number generator to use in simulation-based forecasts. Must produce random samples using the syntax *rng(size)* where size the 2-element tuple (simulations, horizon).

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

reindex : bool, optional

Whether to reindex the forecasts to have the same dimension as the series being forecast. Prior to 4.18 this was the default. As of 4.19 this is now optional. If not provided, a warning is raised about the future change in the default which will occur after September 2021.

New in version 4.19.

x : {dict[label, array_like], array_like}

Values to use for exogenous regressors if any are included in the model. Three formats are accepted:

- 2-d array-like: This format can be used when there is a single exogenous variable. The input must have shape (nforecast, horizon) or (nobs, horizon) where nforecast is the number of forecasting periods and nobs is the original shape of y. For example, if a single series of forecasts are made from the end of the sample with a horizon of 10, then the input can be (1, 10). Alternatively, if the original data had 1000 observations, then the input can be (1000, 10), and only the final row is used to produce forecasts.
- A dictionary of 2-d array-like: This format is identical to the previous except that the dictionary keys must match the names of the exog variables. Requires that the exog variables were passed as a pandas DataFrame.
- A 3-d NumPy array (or equivalent). In this format, each panel (0th axis) is a 2-d array that must have shape (nforecast, horizon) or (nobs,horizon). The array x[j] corresponds to the j-th column of the exogenous variables.

Due to the complexity required to accommodate all scenarios, please see the example notebook that demonstrates the valid formats for `x`.

New in version 4.19.

Returns

Container for forecasts. Key properties are `mean`, `variance` and `residual_variance`.

Return type

arch.univariate.base.ARCHModelForecast

Examples

```
>>> import pandas as pd
>>> from arch import arch_model
>>> am = arch_model(None, mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> sim_data = am.simulate([0.1, 0.4, 0.3, 0.2, 1.0], 250)
>>> sim_data.index = pd.date_range('2000-01-01', periods=250)
>>> am = arch_model(sim_data['data'], mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> res = am.fit()
>>> fig = res.hedgehog_plot()
```

Notes

The most basic 1-step ahead forecast will return a vector with the same length as the original data, where the t -th value will be the time- t forecast for time $t + 1$. When the horizon is > 1 , and when using the default value for `align`, the forecast value in position $[t, h]$ is the time- $t, h+1$ step ahead forecast.

If model contains exogenous variables (model.`x` is not `None`), then only 1-step ahead forecasts are available. Using horizon > 1 will produce a warning and all columns, except the first, will be nan-filled.

If `align` is 'origin', `forecast[t, h]` contains the forecast made using `y[:t]` (that is, up to but not including t) for horizon $h + 1$. For example, `y[100, 2]` contains the 3-step ahead forecast using the first 100 data points, which will correspond to the realization `y[100 + 2]`. If `align` is 'target', then the same forecast is in location `[102, 2]`, so that it is aligned with the observation to use when evaluating, but still in the same column.

`arch.univariate.base.ARCHModel.parameter_names`

abstract `ARCHModel.parameter_names()`

List of parameters names

Returns

names – List of variable names for the mean model

Return type

`list (str)`

arch.univariate.base.ARCHModel.resids**abstract** ARCHModel.**resids**(params, y=None, regressors=None)

Compute model residuals

Parameters**params** : ndarray

Model parameters

y : ndarray, optional

Alternative values to use when computing model residuals

regressors : ndarray, optional

Alternative regressor values to use when computing model residuals

Returns**resids** – Model residuals**Return type**

ndarray

arch.univariate.base.ARCHModel.simulate**abstract** ARCHModel.**simulate**(params, nobs, burn=500, initial_value=None, x=None, initial_value_vol=None)**Return type**

DataFrame

arch.univariate.base.ARCHModel.starting_valuesARCHModel.**starting_values**()

Returns starting values for the mean model, often the same as the values returned from fit

Returns**sv** – Starting values**Return type**

ndarray

Properties

<i>distribution</i>	Set or gets the error distribution
<i>name</i>	The name of the model.
<i>num_params</i>	Number of parameters in the model
<i>volatility</i>	Set or gets the volatility process
<i>y</i>	Returns the dependent variable

arch.univariate.base.ARCHModel.distribution**property** ARCHModel.distribution : *Distribution*

Set or gets the error distribution

Distributions must be a subclass of Distribution

Return type*Distribution***arch.univariate.base.ARCHModel.name****property** ARCHModel.name : str

The name of the model.

Return type

str

arch.univariate.base.ARCHModel.num_params**property** ARCHModel.num_params : int

Number of parameters in the model

arch.univariate.base.ARCHModel.volatility**property** ARCHModel.volatility : *VolatilityProcess*

Set or gets the volatility process

Volatility processes must be a subclass of VolatilityProcess

Return type*VolatilityProcess***arch.univariate.base.ARCHModel.y****property** ARCHModel.y : ndarray | DataFrame | Series | None

Returns the dependent variable

Return type

Union[ndarray, DataFrame, Series, None]

1.9 Volatility Processes

A volatility process is added to a mean model to capture time-varying volatility.

<i>ConstantVariance</i> ()	Constant volatility process
<i>GARCH</i> ([p, o, q, power])	GARCH and related model estimation
<i>FIGARCH</i> ([p, q, power, truncation])	FIGARCH model
<i>EGARCH</i> ([p, o, q])	EGARCH model estimation
<i>HARCH</i> ([lags])	Heterogeneous ARCH process
<i>MIDASHyperbolic</i> ([m, asym])	MIDAS Hyperbolic ARCH process
<i>ARCH</i> ([p])	ARCH process
<i>APARCH</i> ([p, o, q, delta, common_asym])	Asymmetric Power ARCH (APARCH) volatility process

1.9.1 arch.univariate.ConstantVariance

class arch.univariate.ConstantVariance

Constant volatility process

Notes

Model has the same variance in all periods

Methods

<i>backcast</i> (resids)	Construct values for backcasting to start the recursion
<i>backcast_transform</i> (backcast)	Transformation to apply to user-provided backcast values
<i>bounds</i> (resids)	Returns bounds for parameters
<i>compute_variance</i> (parameters, resids, sigma2, ...)	Compute the variance for the ARCH model
<i>constraints</i> ()	Construct parameter constraints arrays for parameter estimation
<i>forecast</i> (parameters, resids, backcast, ...)	Forecast volatility from the model
<i>parameter_names</i> ()	Names of model parameters
<i>simulate</i> (parameters, nobs, rng[, burn, ...])	Simulate data from the model
<i>starting_values</i> (resids)	Returns starting values for the ARCH model
<i>update</i> (index, parameters, resids, sigma2, ...)	Compute the variance for a single observation
<i>variance_bounds</i> (resids[, power])	Construct loose bounds for conditional variances.

arch.univariate.ConstantVariance.backcast

ConstantVariance.**backcast**(resids)

Construct values for backcasting to start the recursion

Parameters

resids : ndarray

Vector of (approximate) residuals

Returns

backcast – Value to use in backcasting in the volatility recursion

Return type

float

arch.univariate.ConstantVariance.backcast_transform

ConstantVariance.**backcast_transform**(backcast)

Transformation to apply to user-provided backcast values

Parameters

backcast : {float, ndarray}

User-provided backcast that approximates $\sigma^2[0]$.

Returns

backcast – Backcast transformed to the model-appropriate scale

Return type

{float, ndarray}

arch.univariate.ConstantVariance.bounds

ConstantVariance.**bounds**(resids)

Returns bounds for parameters

Parameters

resids : ndarray

Vector of (approximate) residuals

Returns

bounds – List of bounds where each element is (lower, upper).

Return type

list[tuple[float,float]]

arch.univariate.ConstantVariance.compute_variance

ConstantVariance.**compute_variance**(parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for the ARCH model

Parameters

parameters : ndarray

Model parameters

resids : ndarray

Vector of mean zero residuals

sigma2 : ndarray

Array with same size as resids to store the conditional variance

backcast : {float, ndarray}

Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.

var_bounds : ndarray

Array containing columns of lower and upper bounds

Return type

ndarray

arch.univariate.ConstantVariance.constraints

ConstantVariance.constraints()

Construct parameter constraints arrays for parameter estimation

Return type

`tuple[ndarray, ndarray]`

Returns

- **A** (*ndarray*) – Parameters loadings in constraint. Shape is number of constraints by number of parameters
- **b** (*ndarray*) – Constraint values, one for each constraint

Notes

Values returned are used in constructing linear inequality constraints of the form $A \cdot \text{parameters} - b \geq 0$

arch.univariate.ConstantVariance.forecast

ConstantVariance.**forecast**(parameters, resids, backcast, var_bounds, start=*None*, horizon=*1*, method=*'analytic'*, simulations=*1000*, rng=*None*, random_state=*None*)

Forecast volatility from the model

Parameters

parameters : {*ndarray*, *Series*}

Parameters required to forecast the volatility model

resids : *ndarray*

Residuals to use in the recursion

backcast : *float*

Value to use when initializing the recursion

var_bounds : *ndarray*, 2-d

Array containing columns of lower and upper bounds

start : {*None*, *int*}

Index of the first observation to use as the starting point for the forecast. Default is `len(resids)`.

horizon : *int*

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in `[1, horizon]`.

method : {'*analytic*', '*simulation*', '*bootstrap*'}

Method to use when producing the forecast. The default is *analytic*.

simulations : *int*

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is '*simulation*'. Must take a single shape input and return random samples numbers with that shape.

random_state : *RandomState*, optional

NumPy *RandomState* instance to use when method is '*bootstrap*'

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
– If method is not supported
- **ValueError** –
– If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a ValueError.

arch.univariate.ConstantVariance.parameter_names

ConstantVariance.**parameter_names**()

Names of model parameters

Returns

names – Variables names

Return type

list (str)

arch.univariate.ConstantVariance.simulate

ConstantVariance.**simulate**(parameters, nob, rng, burn=500, initial_value=None)

Simulate data from the model

Parameters

parameters : {ndarray, Series}

Parameters required to simulate the volatility model

nobs : int

Number of data points to simulate

rng : callable

Callable function that takes a single integer input and returns a vector of random numbers

burn : int, optional

Number of additional observations to generate when initializing the simulation

initial_value : {float, ndarray}, optional

Scalar or array of initial values to use when initializing the simulation

Return type

tuple[ndarray, ndarray]

Returns

- **resids** (*ndarray*) – The simulated residuals
- **variance** (*ndarray*) – The simulated variance

arch.univariate.ConstantVariance.starting_values

ConstantVariance.starting_values(*resids*)

Returns starting values for the ARCH model

Parameters

resids : *ndarray*

Array of (approximate) residuals to use when computing starting values

Returns

sv – Array of starting values

Return type

ndarray

arch.univariate.ConstantVariance.update

ConstantVariance.update(*index*, *parameters*, *resids*, *sigma2*, *backcast*, *var_bounds*)

Compute the variance for a single observation

Parameters

index : *int*

The numerical index of the variance to compute

parameters : *ndarray*

The variance model parameters

resids

The residual array. Only uses `resids[:index]` when computing `sigma2[index]`

sigma2 : *ndarray*

The array containing the variances. Only uses `sigma2[:index]` when computing `sigma2[index]`. The computed value is stored in `sigma2[index]`.

backcast : {*float*, *ndarray*}

Value to use when initializing the recursion

var_bounds : *ndarray*

Array containing columns of lower and upper bounds

Returns

The variance computed for location `index`

Return type

float

arch.univariate.ConstantVariance.variance_bounds

ConstantVariance.**variance_bounds**(resids, power=2.0)

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters

resids : ndarray

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns

var_bounds – Array containing columns of lower and upper bounds with the same number of elements as resids

Return type

ndarray

Properties

<i>name</i>	The name of the volatility process
<i>num_params</i>	The number of parameters in the model
<i>start</i>	Index to use to start variance subarray selection
<i>stop</i>	Index to use to stop variance subarray selection
<i>updateable</i>	Flag indicating that the volatility process supports update
<i>volatility_updater</i>	Get the volatility updater associated with the volatility process

arch.univariate.ConstantVariance.name

property ConstantVariance.**name** : str

The name of the volatility process

Return type

str

arch.univariate.ConstantVariance.num_params

property ConstantVariance.**num_params** : int

The number of parameters in the model

Return type

int

arch.univariate.ConstantVariance.start

property ConstantVariance.start : int

Index to use to start variance subarray selection

Return type

int

arch.univariate.ConstantVariance.stop

property ConstantVariance.stop : int

Index to use to stop variance subarray selection

Return type

int

arch.univariate.ConstantVariance.updateable

property ConstantVariance.updateable : bool

Flag indicating that the volatility process supports update

Return type

bool

arch.univariate.ConstantVariance.volatility_updater

property ConstantVariance.volatility_updater : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type

VolatilityUpdater

Raises

NotImplementedError – If the process is not updateable

1.9.2 arch.univariate.GARCH

class arch.univariate.GARCH(p=1, o=0, q=1, power=2.0)

GARCH and related model estimation

The following models can be specified using GARCH:

- ARCH(p)
- GARCH(p,q)
- GJR-GARCH(p,o,q)
- AVARCH(p)
- AVGARCH(p,q)
- TARCH(p,o,q)

- Models with arbitrary, pre-specified powers

Parameters

p : `int`

Order of the symmetric innovation

o : `int`

Order of the asymmetric innovation

q : `int`

Order of the lagged (transformed) conditional variance

power : `float`, optional

Power to use with the innovations, $\text{abs}(e) ** \text{power}$. Default is 2.0, which produces ARCH and related models. Using 1.0 produces AVARCH and related models. Other powers can be specified, although these should be strictly positive, and usually larger than 0.25.

Examples

```
>>> from arch.univariate import GARCH
```

Standard GARCH(1,1)

```
>>> garch = GARCH(p=1, q=1)
```

Asymmetric GJR-GARCH process

```
>>> gjr = GARCH(p=1, o=1, q=1)
```

Asymmetric TARCH process

```
>>> tarch = GARCH(p=1, o=1, q=1, power=1.0)
```

Notes

In this class of processes, the variance dynamics are

$$\sigma_t^\lambda = \omega + \sum_{i=1}^p \alpha_i |\epsilon_{t-i}|^\lambda + \sum_{j=1}^o \gamma_j |\epsilon_{t-j}|^\lambda I[\epsilon_{t-j} < 0] + \sum_{k=1}^q \beta_k \sigma_{t-k}^\lambda$$

where λ is the power.

Methods

<i>backcast</i> (resids)	Construct values for backcasting to start the recursion
<i>backcast_transform</i> (backcast)	Transformation to apply to user-provided backcast values
<i>bounds</i> (resids)	Returns bounds for parameters
<i>compute_variance</i> (parameters, resids, sigma2, ...)	Compute the variance for the ARCH model
<i>constraints</i> ()	Construct parameter constraints arrays for parameter estimation
<i>forecast</i> (parameters, resids, backcast, ...)	Forecast volatility from the model
<i>parameter_names</i> ()	Names of model parameters
<i>simulate</i> (parameters, nobs, rng[, burn, ...])	Simulate data from the model
<i>starting_values</i> (resids)	Returns starting values for the ARCH model
<i>update</i> (index, parameters, resids, sigma2, ...)	Compute the variance for a single observation
<i>variance_bounds</i> (resids[, power])	Construct loose bounds for conditional variances.

arch.univariate.GARCH.backcast

GARCH.**backcast**(resids)

Construct values for backcasting to start the recursion

Parameters

resids : ndarray

Vector of (approximate) residuals

Returns

backcast – Value to use in backcasting in the volatility recursion

Return type

float

arch.univariate.GARCH.backcast_transform

GARCH.**backcast_transform**(backcast)

Transformation to apply to user-provided backcast values

Parameters

backcast : {float, ndarray}

User-provided backcast that approximates sigma2[0].

Returns

backcast – Backcast transformed to the model-appropriate scale

Return type

{float, ndarray}

arch.univariate.GARCH.bounds**GARCH.bounds**(resids)

Returns bounds for parameters

Parameters**resids : ndarray**
Vector of (approximate) residuals**Returns****bounds** – List of bounds where each element is (lower, upper).**Return type**

list[tuple[float,float]]

arch.univariate.GARCH.compute_variance**GARCH.compute_variance**(parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for the ARCH model

Parameters**parameters : ndarray**
Model parameters**resids : ndarray**
Vector of mean zero residuals**sigma2 : ndarray**
Array with same size as resids to store the conditional variance**backcast : {float, ndarray}**
Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.**var_bounds : ndarray**
Array containing columns of lower and upper bounds**Return type**

ndarray

arch.univariate.GARCH.constraints**GARCH.constraints**()

Construct parameter constraints arrays for parameter estimation

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Parameters loadings in constraint. Shape is number of constraints by number of parameters
- **b** (ndarray) – Constraint values, one for each constraint

Notes

Values returned are used in constructing linear inequality constraints of the form $A \cdot \text{parameters} - b \geq 0$

arch.univariate.GARCH.forecast

`GARCH.forecast(parameters, resids, backcast, var_bounds, start=None, horizon=1, method='analytic', simulations=1000, rng=None, random_state=None)`

Forecast volatility from the model

Parameters

parameters : {ndarray, Series}

Parameters required to forecast the volatility model

resids : ndarray

Residuals to use in the recursion

backcast : float

Value to use when initializing the recursion

var_bounds : ndarray, 2-d

Array containing columns of lower and upper bounds

start : {None, int}

Index of the first observation to use as the starting point for the forecast. Default is `len(resids)`.

horizon : int

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in `[1, horizon]`.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is 'simulation'. Must take a single shape input and return random samples numbers with that shape.

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
 - If method is not supported
- **ValueError** –
 - If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a `ValueError`.

`arch.univariate.GARCH.parameter_names`

`GARCH.parameter_names()`

Names of model parameters

Returns

names – Variables names

Return type

`list (str)`

`arch.univariate.GARCH.simulate`

`GARCH.simulate(parameters, nobs, rng, burn=500, initial_value=None)`

Simulate data from the model

Parameters

parameters : `{ndarray, Series}`

Parameters required to simulate the volatility model

nobs : `int`

Number of data points to simulate

rng : `callable`

Callable function that takes a single integer input and returns a vector of random numbers

burn : `int, optional`

Number of additional observations to generate when initializing the simulation

initial_value : `{float, ndarray}, optional`

Scalar or array of initial values to use when initializing the simulation

Return type

`tuple[ndarray, ndarray]`

Returns

- **resids** (`ndarray`) – The simulated residuals
- **variance** (`ndarray`) – The simulated variance

`arch.univariate.GARCH.starting_values`

`GARCH.starting_values(resids)`

Returns starting values for the ARCH model

Parameters

resids : `ndarray`

Array of (approximate) residuals to use when computing starting values

Returns

sv – Array of starting values

Return type
ndarray

arch.univariate.GARCH.update

GARCH.**update**(index, parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for a single observation

Parameters

index : int

The numerical index of the variance to compute

parameters : ndarray

The variance model parameters

resids

The residual array. Only uses `resids[:index]` when computing `sigma2[index]`

sigma2 : ndarray

The array containing the variances. Only uses `sigma2[:index]` when computing `sigma2[index]`. The computed value is stored in `sigma2[index]`.

backcast : {float, ndarray}

Value to use when initializing the recursion

var_bounds : ndarray

Array containing columns of lower and upper bounds

Returns

The variance computed for location `index`

Return type

float

arch.univariate.GARCH.variance_bounds

GARCH.**variance_bounds**(resids, power=2.0)

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters

resids : ndarray

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns

var_bounds – Array containing columns of lower and upper bounds with the same number of elements as `resids`

Return type

ndarray

Properties

<i>name</i>	The name of the volatility process
<i>num_params</i>	The number of parameters in the model
<i>start</i>	Index to use to start variance subarray selection
<i>stop</i>	Index to use to stop variance subarray selection
<i>updateable</i>	Flag indicating that the volatility process supports update
<i>volatility_updater</i>	Get the volatility updater associated with the volatility process

arch.univariate.GARCH.name

property GARCH.name : str

The name of the volatility process

Return type

str

arch.univariate.GARCH.num_params

property GARCH.num_params : int

The number of parameters in the model

Return type

int

arch.univariate.GARCH.start

property GARCH.start : int

Index to use to start variance subarray selection

Return type

int

arch.univariate.GARCH.stop

property GARCH.stop : int

Index to use to stop variance subarray selection

Return type

int

arch.univariate.GARCH.updateable**property** GARCH.updateable : bool

Flag indicating that the volatility process supports update

Return type

bool

arch.univariate.GARCH.volatility_updater**property** GARCH.volatility_updater : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type*VolatilityUpdater***Raises****NotImplementedError** – If the process is not updateable

1.9.3 arch.univariate.FIGARCH

class arch.univariate.FIGARCH(p=1, q=1, power=2.0, truncation=1000)

FIGARCH model

Parameters**p** : {0, 1}

Order of the symmetric innovation

q : {0, 1}

Order of the lagged (transformed) conditional variance

power : float, optionalPower to use with the innovations, $\text{abs}(e) ** \text{power}$. Default is 2.0, which produces FI-GARCH and related models. Using 1.0 produces FIAVARCH and related models. Other powers can be specified, although these should be strictly positive, and usually larger than 0.25.**truncation** : int, optionalTruncation point to use in $\text{ARCH}(\infty)$ representation. Default is 1000.**Examples**

```
>>> from arch.univariate import FIGARCH
```

Standard FIGARCH

```
>>> figarch = FIGARCH()
```

FIARCH

```
>>> fiarch = FIGARCH(p=0)
```

FIAVGARCH process

```
>>> fiavarch = FIGARCH(power=1.0)
```

Notes

In this class of processes, the variance dynamics are

$$h_t = \omega + [1 - \beta L - \phi L(1 - L)^d] \epsilon_t^2 + \beta h_{t-1}$$

where L is the lag operator and d is the fractional differencing parameter. The model is estimated using the ARCH(∞) representation,

$$h_t = (1 - \beta)^{-1} \omega + \sum_{i=1}^{\infty} \lambda_i \epsilon_{t-i}^2$$

The weights are constructed using

$$\begin{aligned} \delta_1 &= d \\ \lambda_1 &= d - \beta + \phi \end{aligned}$$

and the recursive equations

$$\begin{aligned} \delta_j &= \frac{j-1-d}{j} \delta_{j-1} \\ \lambda_j &= \beta \lambda_{j-1} + \delta_j - \phi \delta_{j-1}. \end{aligned}$$

When *power* is not 2, the ARCH(∞) representation is still used where ϵ_t^2 is replaced by $|\epsilon_t|^p$ and p is the power.

Methods

<i>backcast</i>(resids)	Construct values for backcasting to start the recursion
<i>backcast_transform</i>(backcast)	Transformation to apply to user-provided backcast values
<i>bounds</i>(resids)	Returns bounds for parameters
<i>compute_variance</i>(parameters, resids, sigma2, ...)	Compute the variance for the ARCH model
<i>constraints</i>()	Construct parameter constraints arrays for parameter estimation
<i>forecast</i>(parameters, resids, backcast, ...)	Forecast volatility from the model
<i>parameter_names</i>()	Names of model parameters
<i>simulate</i>(parameters, nob, rng[, burn, ...])	Simulate data from the model
<i>starting_values</i>(resids)	Returns starting values for the ARCH model
<i>update</i>(index, parameters, resids, sigma2, ...)	Compute the variance for a single observation
<i>variance_bounds</i>(resids[, power])	Construct loose bounds for conditional variances.

arch.univariate.FIGARCH.backcast**FIGARCH.backcast**(*resids*)

Construct values for backcasting to start the recursion

Parameters**resids** : ndarray
Vector of (approximate) residuals**Returns****backcast** – Value to use in backcasting in the volatility recursion**Return type**

float

arch.univariate.FIGARCH.backcast_transform**FIGARCH.backcast_transform**(*backcast*)

Transformation to apply to user-provided backcast values

Parameters**backcast** : {float, ndarray}
User-provided backcast that approximates σ^2_0 .**Returns****backcast** – Backcast transformed to the model-appropriate scale**Return type**

{float, ndarray}

arch.univariate.FIGARCH.bounds**FIGARCH.bounds**(*resids*)

Returns bounds for parameters

Parameters**resids** : ndarray
Vector of (approximate) residuals**Returns****bounds** – List of bounds where each element is (lower, upper).**Return type**

list[tuple[float, float]]

arch.univariate.FIGARCH.compute_variance

FIGARCH.compute_variance(parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for the ARCH model

Parameters

parameters : ndarray

Model parameters

resids : ndarray

Vector of mean zero residuals

sigma2 : ndarray

Array with same size as resids to store the conditional variance

backcast : {float, ndarray}

Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.

var_bounds : ndarray

Array containing columns of lower and upper bounds

Return type

ndarray

arch.univariate.FIGARCH.constraints

FIGARCH.constraints()

Construct parameter constraints arrays for parameter estimation

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Parameters loadings in constraint. Shape is number of constraints by number of parameters
- **b** (ndarray) – Constraint values, one for each constraint

Notes

Values returned are used in constructing linear inequality constraints of the form $A \cdot \text{parameters} - b \geq 0$

arch.univariate.FIGARCH.forecast

FIGARCH.forecast(parameters, resids, backcast, var_bounds, start=None, horizon=1, method='analytic', simulations=1000, rng=None, random_state=None)

Forecast volatility from the model

Parameters

parameters : {ndarray, Series}

Parameters required to forecast the volatility model

resids : ndarray

Residuals to use in the recursion

backcast : float

Value to use when initializing the recursion

var_bounds : ndarray, 2-d

Array containing columns of lower and upper bounds

start : {None, int}

Index of the first observation to use as the starting point for the forecast. Default is `len(resids)`.

horizon : int

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in `[1, horizon]`.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is 'simulation'. Must take a single shape input and return random samples numbers with that shape.

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
 - If method is not supported
- **ValueError** –
 - If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a `ValueError`.

arch.univariate.FIGARCH.parameter_names**FIGARCH.parameter_names()**

Names of model parameters

Returns**names** – Variables names**Return type**

list (str)

arch.univariate.FIGARCH.simulate**FIGARCH.simulate**(parameters, nobs, rng, burn=500, initial_value=None)

Simulate data from the model

Parameters**parameters** : {ndarray, Series}

Parameters required to simulate the volatility model

nobs : int

Number of data points to simulate

rng : callable

Callable function that takes a single integer input and returns a vector of random numbers

burn : int, optional

Number of additional observations to generate when initializing the simulation

initial_value : {float, ndarray}, optional

Scalar or array of initial values to use when initializing the simulation

Return type

tuple[ndarray, ndarray]

Returns

- **resids** (ndarray) – The simulated residuals
- **variance** (ndarray) – The simulated variance

arch.univariate.FIGARCH.starting_values**FIGARCH.starting_values**(resids)

Returns starting values for the ARCH model

Parameters**resids** : ndarray

Array of (approximate) residuals to use when computing starting values

Returns**sv** – Array of starting values**Return type**

ndarray

arch.univariate.FIGARCH.update

FIGARCH.update(index, parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for a single observation

Parameters

index : int

The numerical index of the variance to compute

parameters : ndarray

The variance model parameters

resids

The residual array. Only uses `resids[:index]` when computing `sigma2[index]`

sigma2 : ndarray

The array containing the variances. Only uses `sigma2[:index]` when computing `sigma2[index]`. The computed value is stored in `sigma2[index]`.

backcast : {float, ndarray}

Value to use when initializing the recursion

var_bounds : ndarray

Array containing columns of lower and upper bounds

Returns

The variance computed for location `index`

Return type

float

arch.univariate.FIGARCH.variance_bounds

FIGARCH.variance_bounds(resids, power=2.0)

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters

resids : ndarray

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns

var_bounds – Array containing columns of lower and upper bounds with the same number of elements as `resids`

Return type

ndarray

Properties

<i>name</i>	The name of the volatility process
<i>num_params</i>	The number of parameters in the model
<i>start</i>	Index to use to start variance subarray selection
<i>stop</i>	Index to use to stop variance subarray selection
<i>truncation</i>	Truncation lag for the ARCH-infinity approximation
<i>updateable</i>	Flag indicating that the volatility process supports update
<i>volatility_updater</i>	Get the volatility updater associated with the volatility process

arch.univariate.FIGARCH.name

property FIGARCH.**name** : str

The name of the volatility process

Return type

str

arch.univariate.FIGARCH.num_params

property FIGARCH.**num_params** : int

The number of parameters in the model

Return type

int

arch.univariate.FIGARCH.start

property FIGARCH.**start** : int

Index to use to start variance subarray selection

Return type

int

arch.univariate.FIGARCH.stop

property FIGARCH.**stop** : int

Index to use to stop variance subarray selection

Return type

int

arch.univariate.FIGARCH.truncation**property** FIGARCH.**truncation** : `int`

Truncation lag for the ARCH-infinity approximation

Return type`int`**arch.univariate.FIGARCH.updateable****property** FIGARCH.**updateable** : `bool`

Flag indicating that the volatility process supports update

Return type`bool`**arch.univariate.FIGARCH.volatility_updater****property** FIGARCH.**volatility_updater** : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type*VolatilityUpdater***Raises****NotImplementedError** – If the process is not updateable

1.9.4 arch.univariate.EGARCH

class arch.univariate.**EGARCH**(`p=1`, `o=0`, `q=1`)

EGARCH model estimation

Parameters**p** : `int`

Order of the symmetric innovation

o : `int`

Order of the asymmetric innovation

q : `int`

Order of the lagged (transformed) conditional variance

Examples

```
>>> from arch.univariate import EGARCH
```

Symmetric EGARCH(1,1)

```
>>> egarch = EGARCH(p=1, q=1)
```

Standard EGARCH process

```
>>> egarch = EGARCH(p=1, o=1, q=1)
```

Exponential ARCH process

```
>>> earch = EGARCH(p=5)
```

Notes

In this class of processes, the variance dynamics are

$$\ln \sigma_t^2 = \omega + \sum_{i=1}^p \alpha_i \left(|e_{t-i}| - \sqrt{2/\pi} \right) + \sum_{j=1}^o \gamma_j e_{t-j} + \sum_{k=1}^q \beta_k \ln \sigma_{t-k}^2$$

where $e_t = \epsilon_t / \sigma_t$.

Methods

<i>backcast</i> (resids)	Construct values for backcasting to start the recursion
<i>backcast_transform</i> (backcast)	Transformation to apply to user-provided backcast values
<i>bounds</i> (resids)	Returns bounds for parameters
<i>compute_variance</i> (parameters, resids, sigma2, ...)	Compute the variance for the ARCH model
<i>constraints</i> ()	Construct parameter constraints arrays for parameter estimation
<i>forecast</i> (parameters, resids, backcast, ...)	Forecast volatility from the model
<i>parameter_names</i> ()	Names of model parameters
<i>simulate</i> (parameters, nob, rng[, burn, ...])	Simulate data from the model
<i>starting_values</i> (resids)	Returns starting values for the ARCH model
<i>update</i> (index, parameters, resids, sigma2, ...)	Compute the variance for a single observation
<i>variance_bounds</i> (resids[, power])	Construct loose bounds for conditional variances.

arch.univariate.EGARCH.backcast

EGARCH.**backcast**(*resids*)

Construct values for backcasting to start the recursion

Parameters

resids : ndarray

Vector of (approximate) residuals

Returns

backcast – Value to use in backcasting in the volatility recursion

Return type

float

arch.univariate.EGARCH.backcast_transform

EGARCH.**backcast_transform**(backcast)

Transformation to apply to user-provided backcast values

Parameters

backcast : {float, ndarray}

User-provided backcast that approximates $\sigma^2[0]$.

Returns

backcast – Backcast transformed to the model-appropriate scale

Return type

{float, ndarray}

arch.univariate.EGARCH.bounds

EGARCH.**bounds**(resids)

Returns bounds for parameters

Parameters

resids : ndarray

Vector of (approximate) residuals

Returns

bounds – List of bounds where each element is (lower, upper).

Return type

list[tuple[float, float]]

arch.univariate.EGARCH.compute_variance

EGARCH.**compute_variance**(parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for the ARCH model

Parameters

parameters : ndarray

Model parameters

resids : ndarray

Vector of mean zero residuals

sigma2 : ndarray

Array with same size as resids to store the conditional variance

backcast : {float, ndarray}

Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.

var_bounds : ndarray

Array containing columns of lower and upper bounds

Return type

ndarray

arch.univariate.EGARCH.constraints

EGARCH.constraints()

Construct parameter constraints arrays for parameter estimation

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Parameters loadings in constraint. Shape is number of constraints by number of parameters
- **b** (ndarray) – Constraint values, one for each constraint

Notes

Values returned are used in constructing linear inequality constraints of the form $A \cdot \text{parameters} - b \geq 0$

arch.univariate.EGARCH.forecast

EGARCH.forecast(parameters, resids, backcast, var_bounds, start=None, horizon=1, method='analytic', simulations=1000, rng=None, random_state=None)

Forecast volatility from the model

Parameters

parameters : {ndarray, Series}

Parameters required to forecast the volatility model

resids : ndarray

Residuals to use in the recursion

backcast : float

Value to use when initializing the recursion

var_bounds : ndarray, 2-d

Array containing columns of lower and upper bounds

start : {None, int}

Index of the first observation to use as the starting point for the forecast. Default is len(resids).

horizon : int

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in [1, horizon].

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is ‘simulation’. Must take a single shape input and return random samples numbers with that shape.

random_state : RandomState, optional

NumPy RandomState instance to use when method is ‘bootstrap’

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
 - If method is not supported
- **ValueError** –
 - If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a ValueError.

arch.univariate.EGARCH.parameter_names

EGARCH.**parameter_names**()

Names of model parameters

Returns

names – Variables names

Return type

list (str)

arch.univariate.EGARCH.simulate

EGARCH.**simulate**(parameters, nobs, rng, burn=**500**, initial_value=**None**)

Simulate data from the model

Parameters

parameters : {ndarray, Series}

Parameters required to simulate the volatility model

nobs : int

Number of data points to simulate

rng : callable

Callable function that takes a single integer input and returns a vector of random numbers

burn : `int`, optional

Number of additional observations to generate when initializing the simulation

initial_value : `{float, ndarray}`, optional

Scalar or array of initial values to use when initializing the simulation

Return type

`tuple[ndarray, ndarray]`

Returns

- **resids** (*ndarray*) – The simulated residuals
- **variance** (*ndarray*) – The simulated variance

`arch.univariate.EGARCH.starting_values`

`EGARCH.starting_values(resids)`

Returns starting values for the ARCH model

Parameters

resids : `ndarray`

Array of (approximate) residuals to use when computing starting values

Returns

sv – Array of starting values

Return type

`ndarray`

`arch.univariate.EGARCH.update`

`EGARCH.update(index, parameters, resids, sigma2, backcast, var_bounds)`

Compute the variance for a single observation

Parameters

index : `int`

The numerical index of the variance to compute

parameters : `ndarray`

The variance model parameters

resids

The residual array. Only uses `resids[:index]` when computing `sigma2[index]`

sigma2 : `ndarray`

The array containing the variances. Only uses `sigma2[:index]` when computing `sigma2[index]`. The computed value is stored in `sigma2[index]`.

backcast : `{float, ndarray}`

Value to use when initializing the recursion

var_bounds : `ndarray`

Array containing columns of lower and upper bounds

Returns

The variance computed for location `index`

Return type

float

arch.univariate.EGARCH.variance_bounds**EGARCH.variance_bounds**(resids, power=**2.0**)

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters**resids** : ndarray

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns**var_bounds** – Array containing columns of lower and upper bounds with the same number of elements as resids**Return type**

ndarray

Properties

<i>name</i>	The name of the volatility process
<i>num_params</i>	The number of parameters in the model
<i>start</i>	Index to use to start variance subarray selection
<i>stop</i>	Index to use to stop variance subarray selection
<i>updateable</i>	Flag indicating that the volatility process supports update
<i>volatility_updater</i>	Get the volatility updater associated with the volatility process

arch.univariate.EGARCH.name**property** EGARCH.name : str

The name of the volatility process

Return type

str

arch.univariate.EGARCH.num_params

property EGARCH.num_params : int

The number of parameters in the model

Return type

int

arch.univariate.EGARCH.start

property EGARCH.start : int

Index to use to start variance subarray selection

Return type

int

arch.univariate.EGARCH.stop

property EGARCH.stop : int

Index to use to stop variance subarray selection

Return type

int

arch.univariate.EGARCH.updateable

property EGARCH.updateable : bool

Flag indicating that the volatility process supports update

Return type

bool

arch.univariate.EGARCH.volatility_updater

property EGARCH.volatility_updater : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type

VolatilityUpdater

Raises

NotImplementedError – If the process is not updateable

1.9.5 arch.univariate.HARCH

class arch.univariate.HARCH(lags=1)

Heterogeneous ARCH process

Parameters

lags : {list, array, int}

List of lags to include in the model, or if scalar, includes all lags up the value

Examples

```
>>> from arch.univariate import HARCH
```

Lag-1 HARCH, which is identical to an ARCH(1)

```
>>> harch = HARCH()
```

More useful and realistic lag lengths

```
>>> harch = HARCH(lags=[1, 5, 22])
```

Notes

In a Heterogeneous ARCH process, variance dynamics are

$$\sigma_t^2 = \omega + \sum_{i=1}^m \alpha_{l_i} \left(l_i^{-1} \sum_{j=1}^{l_i} \epsilon_{t-j}^2 \right)$$

In the common case where lags=[1, 5, 22], the model is

$$\sigma_t^2 = \omega + \alpha_1 \epsilon_{t-1}^2 + \alpha_5 \left(\frac{1}{5} \sum_{j=1}^5 \epsilon_{t-j}^2 \right) + \alpha_{22} \left(\frac{1}{22} \sum_{j=1}^{22} \epsilon_{t-j}^2 \right)$$

A HARCH process is a special case of an ARCH process where parameters in the more general ARCH process have been restricted.

Methods

<i>backcast</i> (resids)	Construct values for backcasting to start the recursion
<i>backcast_transform</i> (backcast)	Transformation to apply to user-provided backcast values
<i>bounds</i> (resids)	Returns bounds for parameters
<i>compute_variance</i> (parameters, resids, sigma2, ...)	Compute the variance for the ARCH model
<i>constraints</i> ()	Construct parameter constraints arrays for parameter estimation
<i>forecast</i> (parameters, resids, backcast, ...)	Forecast volatility from the model
<i>parameter_names</i> ()	Names of model parameters
<i>simulate</i> (parameters, nob, rng[, burn, ...])	Simulate data from the model
<i>starting_values</i> (resids)	Returns starting values for the ARCH model
<i>update</i> (index, parameters, resids, sigma2, ...)	Compute the variance for a single observation
<i>variance_bounds</i> (resids[, power])	Construct loose bounds for conditional variances.

arch.univariate.HARCH.backcast**HARCH.backcast**(resids)

Construct values for backcasting to start the recursion

Parameters**resids** : ndarray
Vector of (approximate) residuals**Returns****backcast** – Value to use in backcasting in the volatility recursion**Return type**

float

arch.univariate.HARCH.backcast_transform**HARCH.backcast_transform**(backcast)

Transformation to apply to user-provided backcast values

Parameters**backcast** : {float, ndarray}
User-provided backcast that approximates $\sigma^2[0]$.**Returns****backcast** – Backcast transformed to the model-appropriate scale**Return type**

{float, ndarray}

arch.univariate.HARCH.bounds**HARCH.bounds**(resids)

Returns bounds for parameters

Parameters**resids** : ndarray
Vector of (approximate) residuals**Returns****bounds** – List of bounds where each element is (lower, upper).**Return type**

list[tuple[float, float]]

arch.univariate.HARCH.compute_variance

HARCH.**compute_variance**(parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for the ARCH model

Parameters

parameters : ndarray

Model parameters

resids : ndarray

Vector of mean zero residuals

sigma2 : ndarray

Array with same size as resids to store the conditional variance

backcast : {float, ndarray}

Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.

var_bounds : ndarray

Array containing columns of lower and upper bounds

Return type

ndarray

arch.univariate.HARCH.constraints

HARCH.**constraints**()

Construct parameter constraints arrays for parameter estimation

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Parameters loadings in constraint. Shape is number of constraints by number of parameters
- **b** (ndarray) – Constraint values, one for each constraint

Notes

Values returned are used in constructing linear inequality constraints of the form $A \cdot \text{parameters} - b \geq 0$

arch.univariate.HARCH.forecast

HARCH.**forecast**(parameters, resids, backcast, var_bounds, start=None, horizon=1, method='analytic', simulations=1000, rng=None, random_state=None)

Forecast volatility from the model

Parameters

parameters : {ndarray, Series}

Parameters required to forecast the volatility model

resids : ndarray

Residuals to use in the recursion

backcast : float

Value to use when initializing the recursion

var_bounds : ndarray, 2-d

Array containing columns of lower and upper bounds

start : {None, int}

Index of the first observation to use as the starting point for the forecast. Default is `len(resids)`.

horizon : int

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in `[1, horizon]`.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is 'simulation'. Must take a single shape input and return random samples numbers with that shape.

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
– If method is not supported
- **ValueError** –
– If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a `ValueError`.

arch.univariate.HARCH.parameter_names**HARCH.parameter_names()**

Names of model parameters

Returns**names** – Variables names**Return type**`list (str)`**arch.univariate.HARCH.simulate****HARCH.simulate**(parameters, nobs, rng, burn=500, initial_value=None)

Simulate data from the model

Parameters**parameters** : {ndarray, Series}

Parameters required to simulate the volatility model

nobs : int

Number of data points to simulate

rng : callable

Callable function that takes a single integer input and returns a vector of random numbers

burn : int, optional

Number of additional observations to generate when initializing the simulation

initial_value : {float, ndarray}, optional

Scalar or array of initial values to use when initializing the simulation

Return type`tuple[ndarray, ndarray]`**Returns**

- **resids** (ndarray) – The simulated residuals
- **variance** (ndarray) – The simulated variance

arch.univariate.HARCH.starting_values**HARCH.starting_values**(resids)

Returns starting values for the ARCH model

Parameters**resids** : ndarray

Array of (approximate) residuals to use when computing starting values

Returns**sv** – Array of starting values**Return type**

ndarray

arch.univariate.HARCH.update**HARCH.update**(index, parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for a single observation

Parameters**index** : int

The numerical index of the variance to compute

parameters : ndarray

The variance model parameters

residsThe residual array. Only uses `resids[:index]` when computing `sigma2[index]`**sigma2** : ndarrayThe array containing the variances. Only uses `sigma2[:index]` when computing `sigma2[index]`. The computed value is stored in `sigma2[index]`.**backcast** : {float, ndarray}

Value to use when initializing the recursion

var_bounds : ndarray

Array containing columns of lower and upper bounds

ReturnsThe variance computed for location `index`**Return type**

float

arch.univariate.HARCH.variance_bounds**HARCH.variance_bounds**(resids, power=2.0)

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters**resids** : ndarray

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns**var_bounds** – Array containing columns of lower and upper bounds with the same number of elements as `resids`**Return type**

ndarray

Properties

<code>name</code>	The name of the volatility process
<code>num_params</code>	The number of parameters in the model
<code>start</code>	Index to use to start variance subarray selection
<code>stop</code>	Index to use to stop variance subarray selection
<code>updateable</code>	Flag indicating that the volatility process supports update
<code>volatility_updater</code>	Get the volatility updater associated with the volatility process

`arch.univariate.HARCH.name`

property `HARCH.name` : `str`

The name of the volatility process

Return type

`str`

`arch.univariate.HARCH.num_params`

property `HARCH.num_params` : `int`

The number of parameters in the model

Return type

`int`

`arch.univariate.HARCH.start`

property `HARCH.start` : `int`

Index to use to start variance subarray selection

Return type

`int`

`arch.univariate.HARCH.stop`

property `HARCH.stop` : `int`

Index to use to stop variance subarray selection

Return type

`int`

arch.univariate.HARCH.updateable**property** HARCH.updateable : bool

Flag indicating that the volatility process supports update

Return type

bool

arch.univariate.HARCH.volatility_updater**property** HARCH.volatility_updater : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type*VolatilityUpdater***Raises****NotImplementedError** – If the process is not updateable**1.9.6 arch.univariate.MIDASHyperbolic****class** arch.univariate.MIDASHyperbolic(m=22, asym=False)

MIDAS Hyperbolic ARCH process

Parameters**m : int**

Length of maximum lag to include in the model

asym : bool

Flag indicating whether to include an asymmetric term

Examples

```
>>> from arch.univariate import MIDASHyperbolic
```

22-lag MIDAS Hyperbolic process

```
>>> harch = MIDASHyperbolic()
```

Longer 66-period lag

```
>>> harch = MIDASHyperbolic(m=66)
```

Asymmetric MIDAS Hyperbolic process

```
>>> harch = MIDASHyperbolic(asym=True)
```

Notes

In a MIDAS Hyperbolic process, the variance evolves according to

$$\sigma_t^2 = \omega + \sum_{i=1}^m (\alpha + \gamma I[\epsilon_{t-j} < 0]) \phi_i(\theta) \epsilon_{t-i}^2$$

where

$$\phi_i(\theta) \propto \Gamma(i + \theta) / (\Gamma(i + 1)\Gamma(\theta))$$

where Γ is the gamma function. $\{\phi_i(\theta)\}$ is normalized so that $\sum \phi_i(\theta) = 1$

References

Methods

<code>backcast(resids)</code>	Construct values for backcasting to start the recursion
<code>backcast_transform(backcast)</code>	Transformation to apply to user-provided backcast values
<code>bounds(resids)</code>	Returns bounds for parameters
<code>compute_variance(parameters, resids, sigma2, ...)</code>	Compute the variance for the ARCH model
<code>constraints()</code>	Constraints
<code>forecast(parameters, resids, backcast, ...)</code>	Forecast volatility from the model
<code>parameter_names()</code>	Names of model parameters
<code>simulate(parameters, nobs, rng[, burn, ...])</code>	Simulate data from the model
<code>starting_values(resids)</code>	Returns starting values for the ARCH model
<code>update(index, parameters, resids, sigma2, ...)</code>	Compute the variance for a single observation
<code>variance_bounds(resids[, power])</code>	Construct loose bounds for conditional variances.

arch.univariate.MIDASHyperbolic.backcast

MIDASHyperbolic.**backcast**(*resids*)

Construct values for backcasting to start the recursion

Parameters

resids : ndarray

Vector of (approximate) residuals

Returns

backcast – Value to use in backcasting in the volatility recursion

Return type

float

arch.univariate.MIDASHyperbolic.backcast_transform**MIDASHyperbolic.backcast_transform**(backcast)

Transformation to apply to user-provided backcast values

Parameters**backcast** : {float, ndarray}User-provided backcast that approximates $\sigma_2[0]$.**Returns****backcast** – Backcast transformed to the model-appropriate scale**Return type**

{float, ndarray}

arch.univariate.MIDASHyperbolic.bounds**MIDASHyperbolic.bounds**(resids)

Returns bounds for parameters

Parameters**resids** : ndarray

Vector of (approximate) residuals

Returns**bounds** – List of bounds where each element is (lower, upper).**Return type**

list[tuple[float,float]]

arch.univariate.MIDASHyperbolic.compute_variance**MIDASHyperbolic.compute_variance**(parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for the ARCH model

Parameters**parameters** : ndarray

Model parameters

resids : ndarray

Vector of mean zero residuals

sigma2 : ndarray

Array with same size as resids to store the conditional variance

backcast : {float, ndarray}

Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.

var_bounds : ndarray

Array containing columns of lower and upper bounds

Return type

ndarray

arch.univariate.MIDASHyperbolic.constraints

MIDASHyperbolic.constraints()

Constraints

Notes

Parameters are (omega, alpha, gamma, theta)

$A \cdot \text{parameters} - b \geq 0$

1. $\omega > 0$
2. $\alpha > 0$ or $\alpha + \gamma > 0$
3. $\alpha < 1$ or $\alpha + 0.5 \cdot \gamma < 1$
4. $\theta > 0$
5. $\theta < 1$

Return type

tuple[ndarray, ndarray]

arch.univariate.MIDASHyperbolic.forecast

MIDASHyperbolic.forecast(parameters, resids, backcast, var_bounds, start=None, horizon=1, method='analytic', simulations=1000, rng=None, random_state=None)

Forecast volatility from the model

Parameters

parameters : {ndarray, Series}

Parameters required to forecast the volatility model

resids : ndarray

Residuals to use in the recursion

backcast : float

Value to use when initializing the recursion

var_bounds : ndarray, 2-d

Array containing columns of lower and upper bounds

start : {None, int}

Index of the first observation to use as the starting point for the forecast. Default is len(resids).

horizon : int

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in [1, horizon].

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is ‘simulation’. Must take a single shape input and return random samples numbers with that shape.

random_state : RandomState, optional

NumPy RandomState instance to use when method is ‘bootstrap’

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
– If method is not supported
- **ValueError** –
– If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a ValueError.

arch.univariate.MIDASHyperbolic.parameter_names

MIDASHyperbolic.parameter_names()

Names of model parameters

Returns

names – Variables names

Return type

list (str)

arch.univariate.MIDASHyperbolic.simulate

MIDASHyperbolic.simulate(parameters, nobs, rng, burn=500, initial_value=None)

Simulate data from the model

Parameters

parameters : {ndarray, Series}

Parameters required to simulate the volatility model

nobs : int

Number of data points to simulate

rng : callable

Callable function that takes a single integer input and returns a vector of random numbers

burn : int, optional

Number of additional observations to generate when initializing the simulation

initial_value : {float, ndarray}, optional

Scalar or array of initial values to use when initializing the simulation

Return type

tuple[ndarray, ndarray]

Returns

- **resids** (ndarray) – The simulated residuals
- **variance** (ndarray) – The simulated variance

arch.univariate.MIDASHyperbolic.starting_values

MIDASHyperbolic.starting_values(resids)

Returns starting values for the ARCH model

Parameters

resids : ndarray

Array of (approximate) residuals to use when computing starting values

Returns

sv – Array of starting values

Return type

ndarray

arch.univariate.MIDASHyperbolic.update

MIDASHyperbolic.update(index, parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for a single observation

Parameters

index : int

The numerical index of the variance to compute

parameters : ndarray

The variance model parameters

resids

The residual array. Only uses resids[:index] when computing sigma2[index]

sigma2 : ndarray

The array containing the variances. Only uses sigma2[:index] when computing sigma2[index]. The computed value is stored in sigma2[index].

backcast : {float, ndarray}

Value to use when initializing the recursion

var_bounds : ndarray

Array containing columns of lower and upper bounds

Returns

The variance computed for location index

Return type

float

arch.univariate.MIDASHyperbolic.variance_bounds**MIDASHyperbolic.variance_bounds**(resids, power=**2.0**)

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters**resids** : ndarray

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns**var_bounds** – Array containing columns of lower and upper bounds with the same number of elements as resids**Return type**

ndarray

Properties

<i>name</i>	The name of the volatility process
<i>num_params</i>	The number of parameters in the model
<i>start</i>	Index to use to start variance subarray selection
<i>stop</i>	Index to use to stop variance subarray selection
<i>updateable</i>	Flag indicating that the volatility process supports update
<i>volatility_updater</i>	Get the volatility updater associated with the volatility process

arch.univariate.MIDASHyperbolic.name**property** MIDASHyperbolic.name : str

The name of the volatility process

Return type

str

arch.univariate.MIDASHyperbolic.num_params**property** MIDASHyperbolic.num_params : int

The number of parameters in the model

Return type

int

arch.univariate.MIDASHyperbolic.start**property** MIDASHyperbolic.start : int

Index to use to start variance subarray selection

Return type

int

arch.univariate.MIDASHyperbolic.stop**property** MIDASHyperbolic.stop : int

Index to use to stop variance subarray selection

Return type

int

arch.univariate.MIDASHyperbolic.updateable**property** MIDASHyperbolic.updateable : bool

Flag indicating that the volatility process supports update

Return type

bool

arch.univariate.MIDASHyperbolic.volatility_updater**property** MIDASHyperbolic.volatility_updater : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type*VolatilityUpdater***Raises****NotImplementedError** – If the process is not updateable

1.9.7 arch.univariate.ARCH

class arch.univariate.ARCH(p=*1*)

ARCH process

Parameters**p** : int

Order of the symmetric innovation

Examples

ARCH(1) process

```
>>> from arch.univariate import ARCH
```

ARCH(5) process

```
>>> arch = ARCH(p=5)
```

Notes

The variance dynamics of the model estimated

$$\sigma_t^2 = \omega + \sum_{i=1}^p \alpha_i \epsilon_{t-i}^2$$

Methods

<i>backcast</i> (resids)	Construct values for backcasting to start the recursion
<i>backcast_transform</i> (backcast)	Transformation to apply to user-provided backcast values
<i>bounds</i> (resids)	Returns bounds for parameters
<i>compute_variance</i> (parameters, resids, sigma2, ...)	Compute the variance for the ARCH model
<i>constraints</i> ()	Construct parameter constraints arrays for parameter estimation
<i>forecast</i> (parameters, resids, backcast, ...)	Forecast volatility from the model
<i>parameter_names</i> ()	Names of model parameters
<i>simulate</i> (parameters, nob, rng[, burn, ...])	Simulate data from the model
<i>starting_values</i> (resids)	Returns starting values for the ARCH model
<i>update</i> (index, parameters, resids, sigma2, ...)	Compute the variance for a single observation
<i>variance_bounds</i> (resids[, power])	Construct loose bounds for conditional variances.

arch.univariate.ARCH.backcast

ARCH.**backcast**(*resids*)

Construct values for backcasting to start the recursion

Parameters

resids : ndarray

Vector of (approximate) residuals

Returns

backcast – Value to use in backcasting in the volatility recursion

Return type

float

arch.univariate.ARCH.backcast_transform**ARCH.backcast_transform**(backcast)

Transformation to apply to user-provided backcast values

Parameters**backcast** : {float, ndarray}User-provided backcast that approximates $\sigma^2[0]$.**Returns****backcast** – Backcast transformed to the model-appropriate scale**Return type**

{float, ndarray}

arch.univariate.ARCH.bounds**ARCH.bounds**(resids)

Returns bounds for parameters

Parameters**resids** : ndarray

Vector of (approximate) residuals

Returns**bounds** – List of bounds where each element is (lower, upper).**Return type**

list[tuple[float, float]]

arch.univariate.ARCH.compute_variance**ARCH.compute_variance**(parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for the ARCH model

Parameters**parameters** : ndarray

Model parameters

resids : ndarray

Vector of mean zero residuals

sigma2 : ndarray

Array with same size as resids to store the conditional variance

backcast : {float, ndarray}

Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.

var_bounds : ndarray

Array containing columns of lower and upper bounds

Return type

ndarray

arch.univariate.ARCH.constraints

ARCH.constraints()

Construct parameter constraints arrays for parameter estimation

Return type

`tuple[ndarray, ndarray]`

Returns

- **A** (*ndarray*) – Parameters loadings in constraint. Shape is number of constraints by number of parameters
- **b** (*ndarray*) – Constraint values, one for each constraint

Notes

Values returned are used in constructing linear inequality constraints of the form $A \cdot \text{parameters} - b \geq 0$

arch.univariate.ARCH.forecast

ARCH.**forecast**(parameters, resids, backcast, var_bounds, start=*None*, horizon=*1*, method=*analytic*, simulations=*1000*, rng=*None*, random_state=*None*)

Forecast volatility from the model

Parameters

parameters : {*ndarray*, *Series*}

Parameters required to forecast the volatility model

resids : *ndarray*

Residuals to use in the recursion

backcast : *float*

Value to use when initializing the recursion

var_bounds : *ndarray*, 2-d

Array containing columns of lower and upper bounds

start : {*None*, *int*}

Index of the first observation to use as the starting point for the forecast. Default is `len(resids)`.

horizon : *int*

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in `[1, horizon]`.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic.

simulations : *int*

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is 'simulation'. Must take a single shape input and return random samples numbers with that shape.

random_state : *RandomState*, optional

NumPy *RandomState* instance to use when method is 'bootstrap'

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
 - If method is not supported
- **ValueError** –
 - If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a ValueError.

arch.univariate.ARCH.parameter_names

ARCH.**parameter_names**()

Names of model parameters

Returns

names – Variables names

Return type

list (str)

arch.univariate.ARCH.simulate

ARCH.**simulate**(parameters, nobs, rng, burn=500, initial_value=None)

Simulate data from the model

Parameters

parameters : {ndarray, Series}

Parameters required to simulate the volatility model

nobs : int

Number of data points to simulate

rng : callable

Callable function that takes a single integer input and returns a vector of random numbers

burn : int, optional

Number of additional observations to generate when initializing the simulation

initial_value : {float, ndarray}, optional

Scalar or array of initial values to use when initializing the simulation

Return type

tuple[ndarray, ndarray]

Returns

- **resids** (*ndarray*) – The simulated residuals
- **variance** (*ndarray*) – The simulated variance

arch.univariate.ARCH.starting_values

ARCH.starting_values(*resids*)

Returns starting values for the ARCH model

Parameters

resids : *ndarray*

Array of (approximate) residuals to use when computing starting values

Returns

sv – Array of starting values

Return type

ndarray

arch.univariate.ARCH.update

ARCH.update(*index*, *parameters*, *resids*, *sigma2*, *backcast*, *var_bounds*)

Compute the variance for a single observation

Parameters

index : *int*

The numerical index of the variance to compute

parameters : *ndarray*

The variance model parameters

resids

The residual array. Only uses *resids[:index]* when computing *sigma2[index]*

sigma2 : *ndarray*

The array containing the variances. Only uses *sigma2[:index]* when computing *sigma2[index]*. The computed value is stored in *sigma2[index]*.

backcast : {*float*, *ndarray*}

Value to use when initializing the recursion

var_bounds : *ndarray*

Array containing columns of lower and upper bounds

Returns

The variance computed for location *index*

Return type

float

arch.univariate.ARCH.variance_bounds

ARCH.**variance_bounds**(resids, power=**2.0**)

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters

resids : ndarray

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns

var_bounds – Array containing columns of lower and upper bounds with the same number of elements as resids

Return type

ndarray

Properties

<i>name</i>	The name of the volatility process
<i>num_params</i>	The number of parameters in the model
<i>start</i>	Index to use to start variance subarray selection
<i>stop</i>	Index to use to stop variance subarray selection
<i>updateable</i>	Flag indicating that the volatility process supports update
<i>volatility_updater</i>	Get the volatility updater associated with the volatility process

arch.univariate.ARCH.name

property ARCH.**name** : str

The name of the volatility process

Return type

str

arch.univariate.ARCH.num_params

property ARCH.**num_params** : int

The number of parameters in the model

Return type

int

arch.univariate.ARCH.start**property** ARCH.start : int

Index to use to start variance subarray selection

Return type

int

arch.univariate.ARCH.stop**property** ARCH.stop : int

Index to use to stop variance subarray selection

Return type

int

arch.univariate.ARCH.updateable**property** ARCH.updateable : bool

Flag indicating that the volatility process supports update

Return type

bool

arch.univariate.ARCH.volatility_updater**property** ARCH.volatility_updater : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type*VolatilityUpdater***Raises****NotImplementedError** – If the process is not updateable**1.9.8 arch.univariate.APARCH****class** arch.univariate.APARCH(p=1, o=1, q=1, delta=None, common_asym=False)

Asymmetric Power ARCH (APARCH) volatility process

Parameters**p** : intOrder of the symmetric innovation. Must satisfy $p \geq 0$.**o** : intOrder of the asymmetric innovation. Must satisfy $o \leq p$.**q** : int

Order of the lagged (transformed) conditional variance

delta : float, optional

Value to use for a fixed delta in the APARCH model. If not provided, the value of delta is jointly estimated with other model parameters. User provided delta is restricted to lie in (0.05, 4.0).

common_asym : bool, optional

Restrict all asymmetry terms to share the same asymmetry parameter. If False (default), then there are no restrictions on the o asymmetry parameters.

Examples

```
>>> from arch.univariate import APARCH
```

Symmetric Power ARCH(1,1)

```
>>> aparch = APARCH(p=1, q=1)
```

Standard APARCH process

```
>>> aparch = APARCH(p=1, o=1, q=1)
```

Fixed power parameters

```
>>> aparch = APARCH(p=1, o=1, q=1, delta=1.3)
```

Notes

In this class of processes, the variance dynamics are

$$\sigma_t^\delta = \omega + \sum_{i=1}^p \alpha_i (|\epsilon_{t-i}| - \gamma_i I_{[o \geq i]} \epsilon_{t-i})^\delta + \sum_{k=1}^q \beta_k \sigma_{t-k}^\delta$$

If `common_asym` is True, then all of γ_i are restricted to have a common value.

Methods

<code>backcast(resids)</code>	Construct values for backcasting to start the recursion
<code>backcast_transform(backcast)</code>	Transformation to apply to user-provided backcast values
<code>bounds(resids)</code>	Returns bounds for parameters
<code>compute_variance(parameters, resids, sigma2, ...)</code>	Compute the variance for the ARCH model
<code>constraints()</code>	Construct parameter constraints arrays for parameter estimation
<code>forecast(parameters, resids, backcast, ...)</code>	Forecast volatility from the model
<code>parameter_names()</code>	Names of model parameters
<code>simulate(parameters, nob, rng[, burn, ...])</code>	Simulate data from the model
<code>starting_values(resids)</code>	Returns starting values for the ARCH model
<code>update(index, parameters, resids, sigma2, ...)</code>	Compute the variance for a single observation
<code>variance_bounds(resids[, power])</code>	Construct loose bounds for conditional variances.

arch.univariate.APARCH.backcast**APARCH.backcast**(*resids*)

Construct values for backcasting to start the recursion

Parameters**resids** : ndarray
Vector of (approximate) residuals**Returns****backcast** – Value to use in backcasting in the volatility recursion**Return type**

float

arch.univariate.APARCH.backcast_transform**APARCH.backcast_transform**(*backcast*)

Transformation to apply to user-provided backcast values

Parameters**backcast** : {float, ndarray}
User-provided backcast that approximates $\sigma^2[0]$.**Returns****backcast** – Backcast transformed to the model-appropriate scale**Return type**

{float, ndarray}

arch.univariate.APARCH.bounds**APARCH.bounds**(*resids*)

Returns bounds for parameters

Parameters**resids** : ndarray
Vector of (approximate) residuals**Returns****bounds** – List of bounds where each element is (lower, upper).**Return type**

list[tuple[float, float]]

arch.univariate.APARCH.compute_variance

APARCH.**compute_variance**(parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for the ARCH model

Parameters

parameters : ndarray

Model parameters

resids : ndarray

Vector of mean zero residuals

sigma2 : ndarray

Array with same size as resids to store the conditional variance

backcast : {float, ndarray}

Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.

var_bounds : ndarray

Array containing columns of lower and upper bounds

Return type

ndarray

arch.univariate.APARCH.constraints

APARCH.**constraints**()

Construct parameter constraints arrays for parameter estimation

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Parameters loadings in constraint. Shape is number of constraints by number of parameters
- **b** (ndarray) – Constraint values, one for each constraint

Notes

Values returned are used in constructing linear inequality constraints of the form $A \cdot \text{parameters} - b \geq 0$

arch.univariate.APARCH.forecast

APARCH.**forecast**(parameters, resids, backcast, var_bounds, start=None, horizon=1, method='analytic', simulations=1000, rng=None, random_state=None)

Forecast volatility from the model

Parameters

parameters : {ndarray, Series}

Parameters required to forecast the volatility model

resids : ndarray

Residuals to use in the recursion

backcast : float

Value to use when initializing the recursion

var_bounds : ndarray, 2-d

Array containing columns of lower and upper bounds

start : {None, int}

Index of the first observation to use as the starting point for the forecast. Default is `len(resids)`.

horizon : int

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in `[1, horizon]`.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is 'simulation'. Must take a single shape input and return random samples numbers with that shape.

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
 - If method is not supported
- **ValueError** –
 - If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a `ValueError`.

arch.univariate.APARCH.parameter_names

APARCH.**parameter_names**()

Names of model parameters

Returns

names – Variables names

Return type

`list (str)`

arch.univariate.APARCH.simulate

APARCH.**simulate**(*parameters*, *nobs*, *rng*, *burn*=500, *initial_value*=None)

Simulate data from the model

Parameters

parameters : {ndarray, Series}

Parameters required to simulate the volatility model

nobs : int

Number of data points to simulate

rng : callable

Callable function that takes a single integer input and returns a vector of random numbers

burn : int, optional

Number of additional observations to generate when initializing the simulation

initial_value : {float, ndarray}, optional

Scalar or array of initial values to use when initializing the simulation

Return type

`tuple[ndarray, ndarray]`

Returns

- **resids** (ndarray) – The simulated residuals
- **variance** (ndarray) – The simulated variance

arch.univariate.APARCH.starting_values

APARCH.**starting_values**(*resids*)

Returns starting values for the ARCH model

Parameters

resids : ndarray

Array of (approximate) residuals to use when computing starting values

Returns

sv – Array of starting values

Return type

ndarray

arch.univariate.APARCH.update**APARCH.update**(index, parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for a single observation

Parameters**index : int**

The numerical index of the variance to compute

parameters : ndarray

The variance model parameters

residsThe residual array. Only uses `resids[:index]` when computing `sigma2[index]`**sigma2 : ndarray**The array containing the variances. Only uses `sigma2[:index]` when computing `sigma2[index]`. The computed value is stored in `sigma2[index]`.**backcast : {float, ndarray}**

Value to use when initializing the recursion

var_bounds : ndarray

Array containing columns of lower and upper bounds

ReturnsThe variance computed for location `index`**Return type**

float

arch.univariate.APARCH.variance_bounds**APARCH.variance_bounds**(resids, power=2.0)

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters**resids : ndarray**

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns**var_bounds** – Array containing columns of lower and upper bounds with the same number of elements as `resids`**Return type**

ndarray

Properties

<code>common_asym</code>	The value of delta in the model.
<code>delta</code>	The value of delta in the model.
<code>name</code>	The name of the volatility process
<code>num_params</code>	The number of parameters in the model
<code>start</code>	Index to use to start variance subarray selection
<code>stop</code>	Index to use to stop variance subarray selection
<code>updateable</code>	Flag indicating that the volatility process supports update
<code>volatility_updater</code>	Get the volatility updater associated with the volatility process

arch.univariate.APARCH.common_asym

property APARCH.common_asym : bool

The value of delta in the model. NaN is delta is estimated.

Return type

bool

arch.univariate.APARCH.delta

property APARCH.delta : float

The value of delta in the model. NaN is delta is estimated.

Return type

float

arch.univariate.APARCH.name

property APARCH.name : str

The name of the volatility process

Return type

str

arch.univariate.APARCH.num_params

property APARCH.num_params : int

The number of parameters in the model

Return type

int

arch.univariate.APARCH.start**property** APARCH.start : int

Index to use to start variance subarray selection

Return type

int

arch.univariate.APARCH.stop**property** APARCH.stop : int

Index to use to stop variance subarray selection

Return type

int

arch.univariate.APARCH.updateable**property** APARCH.updateable : bool

Flag indicating that the volatility process supports update

Return type

bool

arch.univariate.APARCH.volatility_updater**property** APARCH.volatility_updater : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type*VolatilityUpdater***Raises****NotImplementedError** – If the process is not updateable

1.9.9 Parameterless Variance Processes

Some volatility processes use fixed parameters and so have no parameters that are estimable.

<i>EWMAVariance</i> ([lam])	Exponentially Weighted Moving-Average (RiskMetrics) Variance process
<i>RiskMetrics2006</i> ([tau0, tau1, kmax, rho])	RiskMetrics 2006 Variance process

arch.univariate.EWMAVariance

class arch.univariate.EWMAVariance(lam=**0.94**)

Exponentially Weighted Moving-Average (RiskMetrics) Variance process

Parameters

lam : {float, None}, optional

Smoothing parameter. Default is 0.94. Set to None to estimate lam jointly with other model parameters

Examples

Daily RiskMetrics EWMA process

```
>>> from arch.univariate import EWMAVariance
>>> rm = EWMAVariance(0.94)
```

Notes

The variance dynamics of the model

$$\sigma_t^2 = \lambda \sigma_{t-1}^2 + (1 - \lambda) \epsilon_{t-1}^2$$

When lam is provided, this model has no parameters since the smoothing parameter is treated as fixed. Set lam to None to jointly estimate this parameter when fitting the model.

Methods

<i>backcast</i> (resids)	Construct values for backcasting to start the recursion
<i>backcast_transform</i> (backcast)	Transformation to apply to user-provided backcast values
<i>bounds</i> (resids)	Returns bounds for parameters
<i>compute_variance</i> (parameters, resids, sigma2, ...)	Compute the variance for the ARCH model
<i>constraints</i> ()	Construct parameter constraints arrays for parameter estimation
<i>forecast</i> (parameters, resids, backcast, ...)	Forecast volatility from the model
<i>parameter_names</i> ()	Names of model parameters
<i>simulate</i> (parameters, nobs, rng[, burn, ...])	Simulate data from the model
<i>starting_values</i> (resids)	Returns starting values for the ARCH model
<i>update</i> (index, parameters, resids, sigma2, ...)	Compute the variance for a single observation
<i>variance_bounds</i> (resids[, power])	Construct loose bounds for conditional variances.

arch.univariate.EWMAVariance.backcast**EWMAVariance.backcast**(*resids*)

Construct values for backcasting to start the recursion

Parameters**resids** : ndarray

Vector of (approximate) residuals

Returns**backcast** – Value to use in backcasting in the volatility recursion**Return type**

float

arch.univariate.EWMAVariance.backcast_transform**EWMAVariance.backcast_transform**(*backcast*)

Transformation to apply to user-provided backcast values

Parameters**backcast** : {float, ndarray}User-provided backcast that approximates σ^2_0 .**Returns****backcast** – Backcast transformed to the model-appropriate scale**Return type**

{float, ndarray}

arch.univariate.EWMAVariance.bounds**EWMAVariance.bounds**(*resids*)

Returns bounds for parameters

Parameters**resids** : ndarray

Vector of (approximate) residuals

Returns**bounds** – List of bounds where each element is (lower, upper).**Return type**

list[tuple[float, float]]

arch.univariate.EWMAVariance.compute_variance

`EWMAVariance.compute_variance(parameters, resids, sigma2, backcast, var_bounds)`

Compute the variance for the ARCH model

Parameters

parameters : ndarray

Model parameters

resids : ndarray

Vector of mean zero residuals

sigma2 : ndarray

Array with same size as resids to store the conditional variance

backcast : {float, ndarray}

Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.

var_bounds : ndarray

Array containing columns of lower and upper bounds

Return type

ndarray

arch.univariate.EWMAVariance.constraints

`EWMAVariance.constraints()`

Construct parameter constraints arrays for parameter estimation

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Parameters loadings in constraint. Shape is number of constraints by number of parameters
- **b** (ndarray) – Constraint values, one for each constraint

Notes

Values returned are used in constructing linear inequality constraints of the form $A \cdot \text{parameters} - b \geq 0$

arch.univariate.EWMAVariance.forecast

`EWMAVariance.forecast(parameters, resids, backcast, var_bounds, start=None, horizon=1, method='analytic', simulations=1000, rng=None, random_state=None)`

Forecast volatility from the model

Parameters

parameters : {ndarray, Series}

Parameters required to forecast the volatility model

resids : ndarray

Residuals to use in the recursion

backcast : float

Value to use when initializing the recursion

var_bounds : ndarray, 2-d

Array containing columns of lower and upper bounds

start : {None, int}

Index of the first observation to use as the starting point for the forecast. Default is `len(resids)`.

horizon : int

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in `[1, horizon]`.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is 'simulation'. Must take a single shape input and return random samples numbers with that shape.

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
– If method is not supported
- **ValueError** –
– If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a `ValueError`.

arch.univariate.EWMAVariance.parameter_names

EWMAVariance.parameter_names()

Names of model parameters

Returns

names – Variables names

Return type

list (str)

arch.univariate.EWMAVariance.simulate

EWMAVariance.simulate(parameters, nobs, rng, burn=500, initial_value=None)

Simulate data from the model

Parameters

parameters : {ndarray, Series}

Parameters required to simulate the volatility model

nobs : int

Number of data points to simulate

rng : callable

Callable function that takes a single integer input and returns a vector of random numbers

burn : int, optional

Number of additional observations to generate when initializing the simulation

initial_value : {float, ndarray}, optional

Scalar or array of initial values to use when initializing the simulation

Return type

tuple[ndarray, ndarray]

Returns

- **resids** (ndarray) – The simulated residuals
- **variance** (ndarray) – The simulated variance

arch.univariate.EWMAVariance.starting_values

EWMAVariance.starting_values(resids)

Returns starting values for the ARCH model

Parameters

resids : ndarray

Array of (approximate) residuals to use when computing starting values

Returns

sv – Array of starting values

Return type

ndarray

arch.univariate.EWMAVariance.update

`EWMAVariance.update(index, parameters, resids, sigma2, backcast, var_bounds)`

Compute the variance for a single observation

Parameters

index : int

The numerical index of the variance to compute

parameters : ndarray

The variance model parameters

resids

The residual array. Only uses `resids[:index]` when computing `sigma2[index]`

sigma2 : ndarray

The array containing the variances. Only uses `sigma2[:index]` when computing `sigma2[index]`. The computed value is stored in `sigma2[index]`.

backcast : {float, ndarray}

Value to use when initializing the recursion

var_bounds : ndarray

Array containing columns of lower and upper bounds

Returns

The variance computed for location `index`

Return type

float

arch.univariate.EWMAVariance.variance_bounds

`EWMAVariance.variance_bounds(resids, power=2.0)`

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters

resids : ndarray

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns

var_bounds – Array containing columns of lower and upper bounds with the same number of elements as `resids`

Return type

ndarray

Properties

<i>name</i>	The name of the volatility process
<i>num_params</i>	The number of parameters in the model
<i>start</i>	Index to use to start variance subarray selection
<i>stop</i>	Index to use to stop variance subarray selection
<i>updateable</i>	Flag indicating that the volatility process supports update
<i>volatility_updater</i>	Get the volatility updater associated with the volatility process

arch.univariate.EWMAVariance.name

property EWMAVariance.name : str

The name of the volatility process

Return type

str

arch.univariate.EWMAVariance.num_params

property EWMAVariance.num_params : int

The number of parameters in the model

Return type

int

arch.univariate.EWMAVariance.start

property EWMAVariance.start : int

Index to use to start variance subarray selection

Return type

int

arch.univariate.EWMAVariance.stop

property EWMAVariance.stop : int

Index to use to stop variance subarray selection

Return type

int

arch.univariate.EWMAVariance.updateable**property** EWMAVariance.updateable : bool

Flag indicating that the volatility process supports update

Return type

bool

arch.univariate.EWMAVariance.volatility_updater**property** EWMAVariance.volatility_updater : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type*VolatilityUpdater***Raises****NotImplementedError** – If the process is not updateable**arch.univariate.RiskMetrics2006****class** arch.univariate.RiskMetrics2006(tau0=1560, tau1=4, kmax=14, rho=1.4142135623730951)

RiskMetrics 2006 Variance process

Parameters**tau0** : {int, float}, optional

Length of long cycle. Default is 1560.

tau1 : {int, float}, optional

Length of short cycle. Default is 4.

kmax : int, optional

Number of components. Default is 14.

rho : float, optional

Relative scale of adjacent cycles. Default is sqrt(2)

Examples

Daily RiskMetrics 2006 process

```
>>> from arch.univariate import RiskMetrics2006
>>> rm = RiskMetrics2006()
```

Notes

The variance dynamics of the model are given as a weighted average of kmax EWMA variance processes where the smoothing parameters and weights are determined by tau0, tau1 and rho.

This model has no parameters since the smoothing parameter is fixed.

Methods

<i>backcast</i> (resids)	Construct values for backcasting to start the recursion
<i>backcast_transform</i> (backcast)	Transformation to apply to user-provided backcast values
<i>bounds</i> (resids)	Returns bounds for parameters
<i>compute_variance</i> (parameters, resids, sigma2, ...)	Compute the variance for the ARCH model
<i>constraints</i> ()	Construct parameter constraints arrays for parameter estimation
<i>forecast</i> (parameters, resids, backcast, ...)	Forecast volatility from the model
<i>parameter_names</i> ()	Names of model parameters
<i>simulate</i> (parameters, nobs, rng[, burn, ...])	Simulate data from the model
<i>starting_values</i> (resids)	Returns starting values for the ARCH model
<i>update</i> (index, parameters, resids, sigma2, ...)	Compute the variance for a single observation
<i>variance_bounds</i> (resids[, power])	Construct loose bounds for conditional variances.

arch.univariate.RiskMetrics2006.backcast

RiskMetrics2006.**backcast**(*resids*)

Construct values for backcasting to start the recursion

Parameters

resids : ndarray
Vector of (approximate) residuals

Returns

backcast – Backcast values for each EWMA component

Return type

ndarray

arch.univariate.RiskMetrics2006.backcast_transform

RiskMetrics2006.**backcast_transform**(*backcast*)

Transformation to apply to user-provided backcast values

Parameters

backcast : {float, ndarray}
User-provided backcast that approximates sigma2[0].

Returns

backcast – Backcast transformed to the model-appropriate scale

Return type

{float, ndarray}

arch.univariate.RiskMetrics2006.bounds**RiskMetrics2006.bounds**(resids)

Returns bounds for parameters

Parameters**resids** : ndarray

Vector of (approximate) residuals

Returns**bounds** – List of bounds where each element is (lower, upper).**Return type**

list[tuple[float,float]]

arch.univariate.RiskMetrics2006.compute_variance**RiskMetrics2006.compute_variance**(parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for the ARCH model

Parameters**parameters** : ndarray

Model parameters

resids : ndarray

Vector of mean zero residuals

sigma2 : ndarray

Array with same size as resids to store the conditional variance

backcast : {float, ndarray}

Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.

var_bounds : ndarray

Array containing columns of lower and upper bounds

Return type

ndarray

arch.univariate.RiskMetrics2006.constraints**RiskMetrics2006.constraints**()

Construct parameter constraints arrays for parameter estimation

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Parameters loadings in constraint. Shape is number of constraints by number of parameters
- **b** (ndarray) – Constraint values, one for each constraint

Notes

Values returned are used in constructing linear inequality constraints of the form $A \cdot \text{parameters} - b \geq 0$

arch.univariate.RiskMetrics2006.forecast

`RiskMetrics2006.forecast(parameters, resids, backcast, var_bounds, start=None, horizon=1, method='analytic', simulations=1000, rng=None, random_state=None)`

Forecast volatility from the model

Parameters

parameters : {ndarray, Series}

Parameters required to forecast the volatility model

resids : ndarray

Residuals to use in the recursion

backcast : float

Value to use when initializing the recursion

var_bounds : ndarray, 2-d

Array containing columns of lower and upper bounds

start : {None, int}

Index of the first observation to use as the starting point for the forecast. Default is `len(resids)`.

horizon : int

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in `[1, horizon]`.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is 'simulation'. Must take a single shape input and return random samples numbers with that shape.

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
 - If method is not supported
- **ValueError** –
 - If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a `ValueError`.

`arch.univariate.RiskMetrics2006.parameter_names`

`RiskMetrics2006.parameter_names()`

Names of model parameters

Returns

names – Variables names

Return type

`list (str)`

`arch.univariate.RiskMetrics2006.simulate`

`RiskMetrics2006.simulate(parameters, nobs, rng, burn=500, initial_value=None)`

Simulate data from the model

Parameters

parameters : `{ndarray, Series}`

Parameters required to simulate the volatility model

nobs : `int`

Number of data points to simulate

rng : `callable`

Callable function that takes a single integer input and returns a vector of random numbers

burn : `int, optional`

Number of additional observations to generate when initializing the simulation

initial_value : `{float, ndarray}, optional`

Scalar or array of initial values to use when initializing the simulation

Return type

`tuple[ndarray, ndarray]`

Returns

- **resids** (`ndarray`) – The simulated residuals
- **variance** (`ndarray`) – The simulated variance

`arch.univariate.RiskMetrics2006.starting_values`

`RiskMetrics2006.starting_values(resids)`

Returns starting values for the ARCH model

Parameters

resids : `ndarray`

Array of (approximate) residuals to use when computing starting values

Returns

sv – Array of starting values

Return type

ndarray

arch.univariate.RiskMetrics2006.update

RiskMetrics2006.update(**index**, **parameters**, **resids**, **sigma2**, **backcast**, **var_bounds**)

Compute the variance for a single observation

Parameters

index : int

The numerical index of the variance to compute

parameters : ndarray

The variance model parameters

resids

The residual array. Only uses `resids[:index]` when computing `sigma2[index]`

sigma2 : ndarray

The array containing the variances. Only uses `sigma2[:index]` when computing `sigma2[index]`. The computed value is stored in `sigma2[index]`.

backcast : {float, ndarray}

Value to use when initializing the recursion

var_bounds : ndarray

Array containing columns of lower and upper bounds

Returns

The variance computed for location `index`

Return type

float

arch.univariate.RiskMetrics2006.variance_bounds

RiskMetrics2006.variance_bounds(**resids**, **power=2.0**)

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters

resids : ndarray

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns

var_bounds – Array containing columns of lower and upper bounds with the same number of elements as `resids`

Return type
ndarray

Properties

<i>name</i>	The name of the volatility process
<i>num_params</i>	The number of parameters in the model
<i>start</i>	Index to use to start variance subarray selection
<i>stop</i>	Index to use to stop variance subarray selection
<i>updateable</i>	Flag indicating that the volatility process supports update
<i>volatility_updater</i>	Get the volatility updater associated with the volatility process

arch.univariate.RiskMetrics2006.name

property RiskMetrics2006.name : str
The name of the volatility process

Return type
str

arch.univariate.RiskMetrics2006.num_params

property RiskMetrics2006.num_params : int
The number of parameters in the model

Return type
int

arch.univariate.RiskMetrics2006.start

property RiskMetrics2006.start : int
Index to use to start variance subarray selection

Return type
int

arch.univariate.RiskMetrics2006.stop

property RiskMetrics2006.stop : int
Index to use to stop variance subarray selection

Return type
int

arch.univariate.RiskMetrics2006.updateable

property RiskMetrics2006.updateable : bool

Flag indicating that the volatility process supports update

Return type

bool

arch.univariate.RiskMetrics2006.volatility_updater

property RiskMetrics2006.volatility_updater : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type

VolatilityUpdater

Raises

NotImplementedError – If the process is not updateable

1.9.10 FixedVariance

The `FixedVariance` class is a special-purpose volatility process that allows the so-called zig-zag algorithm to be used. See the example for usage.

<i>FixedVariance</i> (variance[, unit_scale])	Fixed volatility process
---	--------------------------

arch.univariate.FixedVariance

class arch.univariate.FixedVariance(variance, unit_scale=False)

Fixed volatility process

Parameters

variance : {array, Series}

Array containing the variances to use. Should have the same shape as the data used in the model.

unit_scale : bool, optional

Flag whether to enforce a unit scale. If False, a scale parameter will be estimated so that the model variance will be proportional to variance. If True, the model variance is set of variance

Notes

Allows a fixed set of variances to be used when estimating a mean model, allowing GLS estimation.

Methods

<i>backcast</i> (resids)	Construct values for backcasting to start the recursion
<i>backcast_transform</i> (backcast)	Transformation to apply to user-provided backcast values
<i>bounds</i> (resids)	Returns bounds for parameters
<i>compute_variance</i> (parameters, resids, sigma2, ...)	Compute the variance for the ARCH model
<i>constraints</i> ()	Construct parameter constraints arrays for parameter estimation
<i>forecast</i> (parameters, resids, backcast, ...)	Forecast volatility from the model
<i>parameter_names</i> ()	Names of model parameters
<i>simulate</i> (parameters, nob, rng[, burn, ...])	Simulate data from the model
<i>starting_values</i> (resids)	Returns starting values for the ARCH model
<i>update</i> (index, parameters, resids, sigma2, ...)	Compute the variance for a single observation
<i>variance_bounds</i> (resids[, power])	Construct loose bounds for conditional variances.

arch.univariate.FixedVariance.backcast

FixedVariance.**backcast**(resids)

Construct values for backcasting to start the recursion

Parameters

resids : ndarray
Vector of (approximate) residuals

Returns

backcast – Value to use in backcasting in the volatility recursion

Return type

float

arch.univariate.FixedVariance.backcast_transform

FixedVariance.**backcast_transform**(backcast)

Transformation to apply to user-provided backcast values

Parameters

backcast : {float, ndarray}
User-provided backcast that approximates sigma2[0].

Returns

backcast – Backcast transformed to the model-appropriate scale

Return type

{float, ndarray}

arch.univariate.FixedVariance.bounds

FixedVariance.**bounds**(resids)

Returns bounds for parameters

Parameters

resids : ndarray

Vector of (approximate) residuals

Returns

bounds – List of bounds where each element is (lower, upper).

Return type

list[tuple[float, float]]

arch.univariate.FixedVariance.compute_variance

FixedVariance.**compute_variance**(parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for the ARCH model

Parameters

parameters : ndarray

Model parameters

resids : ndarray

Vector of mean zero residuals

sigma2 : ndarray

Array with same size as resids to store the conditional variance

backcast : {float, ndarray}

Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.

var_bounds : ndarray

Array containing columns of lower and upper bounds

Return type

ndarray

arch.univariate.FixedVariance.constraints

FixedVariance.**constraints**()

Construct parameter constraints arrays for parameter estimation

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Parameters loadings in constraint. Shape is number of constraints by number of parameters
- **b** (ndarray) – Constraint values, one for each constraint

Notes

Values returned are used in constructing linear inequality constraints of the form $A \cdot \text{parameters} - b \geq 0$

arch.univariate.FixedVariance.forecast

`FixedVariance.forecast(parameters, resids, backcast, var_bounds, start=None, horizon=1, method='analytic', simulations=1000, rng=None, random_state=None)`

Forecast volatility from the model

Parameters

parameters : {ndarray, Series}

Parameters required to forecast the volatility model

resids : ndarray

Residuals to use in the recursion

backcast : float

Value to use when initializing the recursion

var_bounds : ndarray, 2-d

Array containing columns of lower and upper bounds

start : {None, int}

Index of the first observation to use as the starting point for the forecast. Default is `len(resids)`.

horizon : int

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in `[1, horizon]`.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is 'simulation'. Must take a single shape input and return random samples numbers with that shape.

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
 - If method is not supported
- **ValueError** –
 - If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a `ValueError`.

`arch.univariate.FixedVariance.parameter_names`

`FixedVariance.parameter_names()`

Names of model parameters

Returns

names – Variables names

Return type

`list (str)`

`arch.univariate.FixedVariance.simulate`

`FixedVariance.simulate(parameters, nobs, rng, burn=500, initial_value=None)`

Simulate data from the model

Parameters

parameters : `{ndarray, Series}`

Parameters required to simulate the volatility model

nobs : `int`

Number of data points to simulate

rng : `callable`

Callable function that takes a single integer input and returns a vector of random numbers

burn : `int`, optional

Number of additional observations to generate when initializing the simulation

initial_value : `{float, ndarray}`, optional

Scalar or array of initial values to use when initializing the simulation

Return type

`tuple[ndarray, ndarray]`

Returns

- **resids** (`ndarray`) – The simulated residuals
- **variance** (`ndarray`) – The simulated variance

`arch.univariate.FixedVariance.starting_values`

`FixedVariance.starting_values(resids)`

Returns starting values for the ARCH model

Parameters

resids : `ndarray`

Array of (approximate) residuals to use when computing starting values

Returns

sv – Array of starting values

Return type

ndarray

arch.univariate.FixedVariance.update

FixedVariance.update(**index**, **parameters**, **resids**, **sigma2**, **backcast**, **var_bounds**)

Compute the variance for a single observation

Parameters

index : int

The numerical index of the variance to compute

parameters : ndarray

The variance model parameters

resids

The residual array. Only uses `resids[:index]` when computing `sigma2[index]`

sigma2 : ndarray

The array containing the variances. Only uses `sigma2[:index]` when computing `sigma2[index]`. The computed value is stored in `sigma2[index]`.

backcast : {float, ndarray}

Value to use when initializing the recursion

var_bounds : ndarray

Array containing columns of lower and upper bounds

Returns

The variance computed for location `index`

Return type

float

arch.univariate.FixedVariance.variance_bounds

FixedVariance.variance_bounds(**resids**, **power=2.0**)

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters

resids : ndarray

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns

var_bounds – Array containing columns of lower and upper bounds with the same number of elements as `resids`

Return type
ndarray

Properties

<i>name</i>	The name of the volatility process
<i>num_params</i>	The number of parameters in the model
<i>start</i>	Index to use to start variance subarray selection
<i>stop</i>	Index to use to stop variance subarray selection
<i>updateable</i>	Flag indicating that the volatility process supports update
<i>volatility_updater</i>	Get the volatility updater associated with the volatility process

arch.univariate.FixedVariance.name

property FixedVariance.name : str
The name of the volatility process

Return type
str

arch.univariate.FixedVariance.num_params

property FixedVariance.num_params : int
The number of parameters in the model

Return type
int

arch.univariate.FixedVariance.start

property FixedVariance.start : int
Index to use to start variance subarray selection

Return type
int

arch.univariate.FixedVariance.stop

property FixedVariance.stop : int
Index to use to stop variance subarray selection

Return type
int

arch.univariate.FixedVariance.updateable**property** FixedVariance.updateable : bool

Flag indicating that the volatility process supports update

Return type

bool

arch.univariate.FixedVariance.volatility_updater**property** FixedVariance.volatility_updater : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type*VolatilityUpdater***Raises****NotImplementedError** – If the process is not updateable

1.9.11 Writing New Volatility Processes

All volatility processes must inherit from *VolatilityProcess* and provide all public methods.*VolatilityProcess()*

Abstract base class for ARCH models.

arch.univariate.volatility.VolatilityProcess**class** arch.univariate.volatility.VolatilityProcess

Abstract base class for ARCH models. Allows the conditional mean model to be specified separately from the conditional variance, even though parameters are estimated jointly.

Methods

<i>backcast</i> (resids)	Construct values for backcasting to start the recursion
<i>backcast_transform</i> (backcast)	Transformation to apply to user-provided backcast values
<i>bounds</i> (resids)	Returns bounds for parameters
<i>compute_variance</i> (parameters, resids, sigma2, ...)	Compute the variance for the ARCH model
<i>constraints</i> ()	Construct parameter constraints arrays for parameter estimation
<i>forecast</i> (parameters, resids, backcast, ...)	Forecast volatility from the model
<i>parameter_names</i> ()	Names of model parameters
<i>simulate</i> (parameters, nob, rng[, burn, ...])	Simulate data from the model
<i>starting_values</i> (resids)	Returns starting values for the ARCH model
<i>update</i> (index, parameters, resids, sigma2, ...)	Compute the variance for a single observation
<i>variance_bounds</i> (resids[, power])	Construct loose bounds for conditional variances.

arch.univariate.volatility.VolatilityProcess.backcast**VolatilityProcess.backcast**(resids)

Construct values for backcasting to start the recursion

Parameters**resids** : ndarray

Vector of (approximate) residuals

Returns**backcast** – Value to use in backcasting in the volatility recursion**Return type**

float

arch.univariate.volatility.VolatilityProcess.backcast_transform**VolatilityProcess.backcast_transform**(backcast)

Transformation to apply to user-provided backcast values

Parameters**backcast** : {float, ndarray}User-provided backcast that approximates σ^2_0 .**Returns****backcast** – Backcast transformed to the model-appropriate scale**Return type**

{float, ndarray}

arch.univariate.volatility.VolatilityProcess.bounds**abstract VolatilityProcess.bounds**(resids)

Returns bounds for parameters

Parameters**resids** : ndarray

Vector of (approximate) residuals

Returns**bounds** – List of bounds where each element is (lower, upper).**Return type**

list[tuple[float, float]]

arch.univariate.volatility.VolatilityProcess.compute_variance

abstract VolatilityProcess.compute_variance(parameters, resids, sigma2, backcast, var_bounds)

Compute the variance for the ARCH model

Parameters

parameters : ndarray

Model parameters

resids : ndarray

Vector of mean zero residuals

sigma2 : ndarray

Array with same size as resids to store the conditional variance

backcast : {float, ndarray}

Value to use when initializing ARCH recursion. Can be an ndarray when the model contains multiple components.

var_bounds : ndarray

Array containing columns of lower and upper bounds

Return type

ndarray

arch.univariate.volatility.VolatilityProcess.constraints

abstract VolatilityProcess.constraints()

Construct parameter constraints arrays for parameter estimation

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Parameters loadings in constraint. Shape is number of constraints by number of parameters
- **b** (ndarray) – Constraint values, one for each constraint

Notes

Values returned are used in constructing linear inequality constraints of the form $A \cdot \text{parameters} - b \geq 0$

arch.univariate.volatility.VolatilityProcess.forecast

VolatilityProcess.forecast(parameters, resids, backcast, var_bounds, start=None, horizon=1, method='analytic', simulations=1000, rng=None, random_state=None)

Forecast volatility from the model

Parameters

parameters : {ndarray, Series}

Parameters required to forecast the volatility model

resids : ndarray

Residuals to use in the recursion

backcast : float

Value to use when initializing the recursion

var_bounds : ndarray, 2-d

Array containing columns of lower and upper bounds

start : {None, int}

Index of the first observation to use as the starting point for the forecast. Default is `len(resids)`.

horizon : int

Forecast horizon. Must be 1 or larger. Forecasts are produced for horizons in `[1, horizon]`.

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable

Callable random number generator required if method is 'simulation'. Must take a single shape input and return random samples numbers with that shape.

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

Returns

forecasts – Class containing the variance forecasts, and, if using simulation or bootstrap, the simulated paths.

Return type

VarianceForecast

Raises

- **NotImplementedError** –
 - If method is not supported
- **ValueError** –
 - If the method is not known

Notes

The analytic method is not supported for all models. Attempting to use this method when not available will raise a `ValueError`.

arch.univariate.volatility.VolatilityProcess.parameter_names**abstract** VolatilityProcess.**parameter_names**()

Names of model parameters

Returns**names** – Variables names**Return type**

list (str)

arch.univariate.volatility.VolatilityProcess.simulate**abstract** VolatilityProcess.**simulate**(parameters, nobs, rng, burn=500, initial_value=None)

Simulate data from the model

Parameters**parameters** : {ndarray, Series}

Parameters required to simulate the volatility model

nobs : int

Number of data points to simulate

rng : callable

Callable function that takes a single integer input and returns a vector of random numbers

burn : int, optional

Number of additional observations to generate when initializing the simulation

initial_value : {float, ndarray}, optional

Scalar or array of initial values to use when initializing the simulation

Return type

tuple[ndarray, ndarray]

Returns

- **resids** (ndarray) – The simulated residuals
- **variance** (ndarray) – The simulated variance

arch.univariate.volatility.VolatilityProcess.starting_values**abstract** VolatilityProcess.**starting_values**(resids)

Returns starting values for the ARCH model

Parameters**resids** : ndarray

Array of (approximate) residuals to use when computing starting values

Returns**sv** – Array of starting values**Return type**

ndarray

arch.univariate.volatility.VolatilityProcess.update

`VolatilityProcess.update(index, parameters, resids, sigma2, backcast, var_bounds)`

Compute the variance for a single observation

Parameters

index : int

The numerical index of the variance to compute

parameters : ndarray

The variance model parameters

resids

The residual array. Only uses `resids[:index]` when computing `sigma2[index]`

sigma2 : ndarray

The array containing the variances. Only uses `sigma2[:index]` when computing `sigma2[index]`. The computed value is stored in `sigma2[index]`.

backcast : {float, ndarray}

Value to use when initializing the recursion

var_bounds : ndarray

Array containing columns of lower and upper bounds

Returns

The variance computed for location `index`

Return type

float

arch.univariate.volatility.VolatilityProcess.variance_bounds

`VolatilityProcess.variance_bounds(resids, power=2.0)`

Construct loose bounds for conditional variances.

These bounds are used in parameter estimation to ensure that the log-likelihood does not produce NaN values.

Parameters

resids : ndarray

Approximate residuals to use to compute the lower and upper bounds on the conditional variance

power : float, optional

Power used in the model. 2.0, the default corresponds to standard ARCH models that evolve in squares.

Returns

var_bounds – Array containing columns of lower and upper bounds with the same number of elements as `resids`

Return type

ndarray

Properties

<i>name</i>	The name of the volatility process
<i>num_params</i>	The number of parameters in the model
<i>start</i>	Index to use to start variance subarray selection
<i>stop</i>	Index to use to stop variance subarray selection
<i>updateable</i>	Flag indicating that the volatility process supports update
<i>volatility_updater</i>	Get the volatility updater associated with the volatility process

arch.univariate.volatility.VolatilityProcess.name

property VolatilityProcess.**name** : str

The name of the volatility process

Return type

str

arch.univariate.volatility.VolatilityProcess.num_params

property VolatilityProcess.**num_params** : int

The number of parameters in the model

Return type

int

arch.univariate.volatility.VolatilityProcess.start

property VolatilityProcess.**start** : int

Index to use to start variance subarray selection

Return type

int

arch.univariate.volatility.VolatilityProcess.stop

property VolatilityProcess.**stop** : int

Index to use to stop variance subarray selection

Return type

int

arch.univariate.volatility.VolatilityProcess.updateable

property VolatilityProcess.updateable : bool

Flag indicating that the volatility process supports update

Return type

bool

arch.univariate.volatility.VolatilityProcess.volatility_updater

property VolatilityProcess.volatility_updater : *VolatilityUpdater*

Get the volatility updater associated with the volatility process

Returns

The updater class

Return type

VolatilityUpdater

Raises

NotImplementedError – If the process is not updateable

They may optionally expose a *VolatilityUpdater* class that can be used in *ARCHInMean* estimation.

VolatilityUpdater()

Base class that all volatility updaters must inherit from.

arch.univariate.recursions_python.VolatilityUpdater

class arch.univariate.recursions_python.VolatilityUpdater

Base class that all volatility updaters must inherit from.

Notes

See the implementation available for information on modifying `__init__` to capture model-specific parameters and how `initialize_update` is used to precompute values that change in each likelihood but not each iteration of the recursion.

When writing a volatility updater, it is recommended to follow the examples in `recursions.pyx` which use Cython to produce a C-callable update function that can then be used to improve performance. The subclasses of this abstract metaclass are all pure Python and model estimation performance is poor since loops are written in Python.

Methods

<i>initialize_update</i> (parameters, backcast, nobs)	Initialize the recursion prior to calling update
<i>update</i> (t, parameters, resids, sigma2, var_bounds)	Update the current variance at location t

arch.univariate.recursions_python.VolatilityUpdater.initialize_update**abstract** VolatilityUpdater.**initialize_update**(parameters, backcast, nobs)

Initialize the recursion prior to calling update

Parameters**parameters** : ndarray

The model parameters.

backcast : {float, ndarray}

The backcast value(s).

nobs : int

The number of observations in the sample.

Notes

This function is called once per likelihood evaluation and can be used to pre-compute expensive parameter transformations that do not change with each call to **update**.

Return type

None

arch.univariate.recursions_python.VolatilityUpdater.update**abstract** VolatilityUpdater.**update**(t, parameters, resids, sigma2, var_bounds)

Update the current variance at location t

Parameters**t** : int

The index of the value of sigma2 to update. Assumes but does not check that update has been called recursively for 0,1,...,t-1.

parameters : ndarray

Model parameters

resids : ndarray

Residuals to use in the recursion

sigma2 : ndarray

Conditional variances with same shape as resids

var_bounds : ndarray

nobs by 2-element array of upper and lower bounds for conditional variances for each time period

Notes

The update to `sigma2` occurs inplace.

Return type

None

1.10 Using the Fixed Variance process

The `FixedVariance` volatility process can be used to implement zig-zag model estimation where two steps are repeated until convergence. This can be used to estimate models which may not be easy to estimate as a single process due to numerical issues or a high-dimensional parameter space.

This setup code is required to run in an IPython notebook

```
[1]: %matplotlib inline
import matplotlib.pyplot as plt
import seaborn

seaborn.set_style("darkgrid")
plt.rc("figure", figsize=(16, 6))
plt.rc("savefig", dpi=90)
plt.rc("font", family="sans-serif")
plt.rc("font", size=14)
```

1.10.1 Setup

Imports used in this example.

```
[2]: import datetime as dt


import numpy as np
```

Data

The VIX index will be used to illustrate the use of the `FixedVariance` process. The data is from FRED and is provided by the `arch` package.

```
[3]: import arch.data.vix

vix_data = arch.data.vix.load()
vix = vix_data.vix.dropna()
vix.name = "VIX Index"
ax = vix.plot(title="VIX Index")
```

Initial Mean Model Estimation

The first step is to estimate the mean to filter the residuals using a constant variance.

```
[4]: from arch.univariate.mean import HARX, ZeroMean
from arch.univariate.volatility import GARCH, FixedVariance
```

```
mod = HARX(vix, lags=[1, 5, 22])
res = mod.fit()
print(res.summary())
```

HAR - Constant Variance Model Results

```
=====
Dep. Variable:          VIX Index    R-squared:                0.876
Mean Model:              HAR         Adj. R-squared:           0.876
Vol Model:       Constant Variance   Log-Likelihood:        -2267.95
Distribution:           Normal       AIC:                   4545.90
Method:       Maximum Likelihood     BIC:                   4571.50
                                           No. Observations:      1237
Date:           Wed, Apr 26 2023     Df Residuals:          1233
Time:           08:27:31              Df Model:               4
=====
```

Mean Model

```
=====
              coef    std err          t      P>|t|     95.0% Conf. Int.
-----
Const          0.6335      0.189      3.359  7.831e-04 [ 0.264, 1.003]
VIX Index[0:1]  0.9287  6.589e-02     14.095  4.056e-45 [ 0.800, 1.058]
VIX Index[0:5] -0.0318  6.449e-02     -0.492   0.622 [-0.158, 0.463e-02]
VIX Index[0:22] 0.0612  3.180e-02      1.926  5.409e-02 [-1.076e-03, 0.124]
=====
```

Volatility Model

```
=====
              coef    std err          t      P>|t|     95.0% Conf. Int.
-----
sigma2          2.2910      0.396      5.782  7.361e-09 [ 1.514, 3.068]
=====
```

(continues on next page)

(continued from previous page)

Covariance estimator: White's Heteroskedasticity Consistent Estimator

Initial Volatility Model Estimation

Using the previously estimated residuals, a volatility model can be estimated using a `ZeroMean`. In this example, a GJR-GARCH process is used for the variance.

```
[5]: vol_mod = ZeroMean(res.resid.dropna(), volatility=GARCH(p=1, o=1, q=1))
vol_res = vol_mod.fit(dis="off")
print(vol_res.summary())
```


```

Zero Mean - GJR-GARCH Model Results
=====
Dep. Variable:          resid    R-squared:          0.000
Mean Model:            Zero Mean  Adj. R-squared:       0.001
Vol Model:             GJR-GARCH  Log-Likelihood:    -1936.93
Distribution:          Normal     AIC:                3881.86
Method:               Maximum Likelihood  BIC:                3902.35
                                     No. Observations:      1237
Date:                 Wed, Apr 26 2023  Df Residuals:         1237
Time:                 08:27:31          Df Model:            0
                                     Volatility Model
=====
              coef    std err          t      P>|t|      95.0% Conf. Int.
-----
omega         0.2355   9.134e-02     2.578   9.932e-03   [5.647e-02,  0.415]
alpha[1]       0.7217    0.374      1.931   5.353e-02   [-1.098e-02,  1.454]
gamma[1]      -0.7217    0.252     -2.859   4.255e-03   [ -1.217, -0.227]
beta[1]        0.5789    0.184      3.140   1.692e-03   [ 0.218,  0.940]
=====

```

Covariance estimator: robust

```
[6]: ax = vol_res.plot("D")
```



Re-estimating the mean with a FixedVariance

The `FixedVariance` requires that the variance is provided when initializing the object. The variance provided should have the same shape as the original data. Since the variance estimated from the GJR-GARCH model is missing the first 22 observations due to the HAR lags, we simply fill these with 1. These values will not be used to estimate the model, and so the value is not important.

The summary shows that there is a single parameter, `scale`, which is close to 1. The mean parameters have changed which reflects the GLS-like weighting that this re-estimation imposes.

```
[7]: variance = np.empty_like(vix)
variance.fill(1.0)
variance[22:] = vol_res.conditional_volatility**2.0
fv = FixedVariance(variance)
mod = HARX(vix, lags=[1, 5, 22], volatility=fv)
res = mod.fit()
print(res.summary())
```

```
Iteration:      1,   Func. Count:      7,   Neg. LLF: 255807014484.3444
Iteration:      2,   Func. Count:     19,   Neg. LLF: 930335.8686979255
Iteration:      3,   Func. Count:     28,   Neg. LLF: 3486.6805091801452
Iteration:      4,   Func. Count:     36,   Neg. LLF: 2885.70179188155
Iteration:      5,   Func. Count:     44,   Neg. LLF: 65535957.91751347
Iteration:      6,   Func. Count:     53,   Neg. LLF: 1935.9527540914005
Iteration:      7,   Func. Count:     59,   Neg. LLF: 1935.947052106923
Iteration:      8,   Func. Count:     65,   Neg. LLF: 1935.9470514960803
```

Optimization terminated successfully (Exit mode 0)

Current function value: 1935.9470514960803

Iterations: 8

Function evaluations: 65

Gradient evaluations: 8

HAR - Fixed Variance Model Results

```
=====
Dep. Variable:          VIX Index   R-squared:                0.876
Mean Model:              HAR        Adj. R-squared:             0.876
Vol Model:              Fixed Variance  Log-Likelihood:         -1935.95
Distribution:            Normal      AIC:                    3881.89
Method:                Maximum Likelihood  BIC:                    3907.50
                                           No. Observations:       1237
Date:                  Wed, Apr 26 2023  Df Residuals:           1233
Time:                  08:27:32          Df Model:                4
=====
```

Mean Model

```
=====
              coef      std err          t      P>|t|      95.0% Conf. Int.
-----
Const          0.5584        0.153        3.661  2.507e-04      [ 0.260,  0.857]
VIX Index[0:1]  0.9376    3.625e-02       25.866  1.608e-147      [ 0.867,  1.009]
VIX Index[0:5] -0.0249    3.782e-02       -0.657    0.511 [-9.899e-02,4.926e-02]
VIX Index[0:22] 0.0493    2.102e-02        2.344  1.909e-02      [8.064e-03,9.044e-02]
=====
```

Volatility Model

```
=====
              coef      std err          t      P>|t|      95.0% Conf. Int.
-----
scale          0.9986    8.081e-02       12.358  4.420e-35 [ 0.840,  1.157]
=====
```

(continues on next page)

(continued from previous page)

```
=====
Covariance estimator: robust
```

Zig-Zag estimation

A small repetitions of the previous two steps can be used to implement a so-called zig-zag estimation strategy.

```
[8]: for i in range(5):
    print(i)
    vol_mod = ZeroMean(res.resid.dropna(), volatility=GARCH(p=1, o=1, q=1))
    vol_res = vol_mod.fit(dispatch="off")
    variance[22:] = vol_res.conditional_volatility**2.0
    fv = FixedVariance(variance, unit_scale=True)
    mod = HARX(vix, lags=[1, 5, 22], volatility=fv)
    res = mod.fit(dispatch="off")
print(res.summary())
```

```
0
1
2
3
4
```

```

HAR - Fixed Variance (Unit Scale) Model Results
=====
Dep. Variable:          VIX Index      R-squared:                0.876
Mean Model:              HAR           Adj. R-squared:           0.876
Vol Model:      Fixed Variance (Unit Scale)  Log-Likelihood:        -1935.74
Distribution:              Normal       AIC:                   3879.48
Method:          Maximum Likelihood     BIC:                   3899.96
                                           No. Observations:      1237
Date:              Wed, Apr 26 2023     Df Residuals:          1233
Time:              08:27:33             Df Model:               4
                                           Mean Model
=====

```

	coef	std err	t	P> t	95.0% Conf. Int.
Const	0.5602	0.152	3.681	2.323e-04	[0.262, 0.858]
VIX Index[0:1]	0.9381	3.616e-02	25.940	2.387e-148	[0.867, 1.009]
VIX Index[0:5]	-0.0262	3.774e-02	-0.693	0.488	[-0.100, 4.781e-02]
VIX Index[0:22]	0.0499	2.099e-02	2.380	1.733e-02	[8.810e-03, 9.109e-02]

```
=====
Covariance estimator: robust
```

Direct Estimation

This model can be directly estimated. The results are provided for comparison to the previous `FixedVariance` estimates of the mean parameters.

```
[9]: mod = HARX(vix, lags=[1, 5, 22], volatility=GARCH(1, 1, 1))
res = mod.fit(dispatch="off")
print(res.summary())
```

```

=====
HAR - GJR-GARCH Model Results
=====
Dep. Variable:          VIX Index    R-squared:              0.876
Mean Model:              HAR         Adj. R-squared:         0.875
Vol Model:              GJR-GARCH    Log-Likelihood:        -1932.61
Distribution:           Normal       AIC:                  3881.23
Method:                Maximum Likelihood BIC:                3922.19
                                     No. Observations:      1237
Date:                  Wed, Apr 26 2023 Df Residuals:          1233
Time:                  08:27:33      Df Model:              4
                                     Mean Model
=====
              coef      std err          t      P>|t|      95.0% Conf. Int.
-----
Const                0.7796        1.190        0.655      0.513      [-1.554, 3.113]
VIX Index[0:1]       0.9180         0.291        3.156    1.597e-03      [ 0.348, 1.488]
VIX Index[0:5]      -0.0393         0.296       -0.133      0.894      [-0.620, 0.541]
VIX Index[0:22]      0.0632     6.353e-02        0.994      0.320 [-6.136e-02, 0.188]
Volatility Model
=====
              coef      std err          t      P>|t|      95.0% Conf. Int.
-----
omega                0.2357         0.250        0.944      0.345      [-0.254, 0.725]
alpha[1]             0.7091         1.069        0.664      0.507      [-1.386, 2.804]
gamma[1]            -0.7091         0.519       -1.367      0.172      [-1.726, 0.308]
beta[1]              0.5579         0.855        0.653      0.514      [-1.117, 2.233]
=====
Covariance estimator: robust

```

1.11 Distributions

A distribution is the final component of an ARCH Model.

<code>Normal([random_state, seed])</code>	Standard normal distribution for use with ARCH models
<code>StudentsT([random_state, seed])</code>	Standardized Student's distribution for use with ARCH models
<code>SkewStudent([random_state, seed])</code>	Standardized Skewed Student's distribution for use with ARCH models
<code>GeneralizedError([random_state, seed])</code>	Generalized Error distribution for use with ARCH models

1.11.1 arch.univariate.Normal

class `arch.univariate.Normal`(`random_state=None`, *, `seed=None`)

Standard normal distribution for use with ARCH models

Parameters

random_state : `RandomState`, optional

Deprecated since version 5.0: `random_state` is deprecated. Use `seed` instead.

seed : {`int`, `Generator`, `RandomState`}, optional

Random number generator instance or int to use. Set to ensure reproducibility. If using an int, the argument is passed to `np.random.default_rng`. If not provided, `default_rng` is used with system-provided entropy.

Methods

<code>bounds</code> (resids)	Parameter bounds for use in optimization.
<code>cdf</code> (resids[, parameters])	Cumulative distribution function
<code>constraints</code> ()	Construct arrays to use in constrained optimization.
<code>loglikelihood</code> (parameters, resids, sigma2[, ...])	Computes the log-likelihood of assuming residuals are normally distributed, conditional on the variance
<code>moment</code> (n[, parameters])	Moment of order n
<code>parameter_names</code> ()	Names of distribution shape parameters
<code>partial_moment</code> (n[, z, parameters])	Order n lower partial moment from -inf to z
<code>ppf</code> (pits[, parameters])	Inverse cumulative density function (ICDF)
<code>simulate</code> (parameters)	Simulates i.i.d.
<code>starting_values</code> (std_resid)	Construct starting values for use in optimization.

arch.univariate.Normal.bounds

`Normal.bounds`(resids)

Parameter bounds for use in optimization.

Parameters

resids : `ndarray`

Residuals to use when computing the bounds

Returns

bounds – List containing a single tuple with (lower, upper) bounds

Return type

list

arch.univariate.Normal.cdf`Normal.cdf(resids, parameters=None)`

Cumulative distribution function

Parameters**resids : ndarray**

Values at which to evaluate the cdf

parameters : ndarray

Distribution parameters. Use None for parameterless distributions.

Returns**f** – CDF values**Return type**

ndarray

arch.univariate.Normal.constraints`Normal.constraints()`

Construct arrays to use in constrained optimization.

Return type`tuple[ndarray, ndarray]`**Returns**

- **A** (ndarray) – Constraint loadings
- **b** (ndarray) – Constraint values

NotesParameters satisfy the constraints $A \cdot \text{parameters} - b \geq 0$ **arch.univariate.Normal.loglikelihood**`Normal.loglikelihood(parameters, resids, sigma2, individual=False)`

Computes the log-likelihood of assuming residuals are normally distributed, conditional on the variance

Parameters**parameters : ndarray**

The normal likelihood has no shape parameters. Empty since the standard normal has no shape parameters.

resids : ndarray

The residuals to use in the log-likelihood calculation

sigma2 : ndarray

Conditional variances of resids

individual : bool, optional

Flag indicating whether to return the vector of individual log likelihoods (True) or the sum (False)

Returns

ll – The log-likelihood

Return type

float

Notes

The log-likelihood of a single data point x is

$$\ln f(x) = -\frac{1}{2} \left(\ln 2\pi + \ln \sigma^2 + \frac{x^2}{\sigma^2} \right)$$

arch.univariate.Normal.moment

`Normal.moment(n, parameters=None)`

Moment of order n

Parameters

n : int

Order of moment

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

Calculated moment

Return type

float

arch.univariate.Normal.parameter_names

`Normal.parameter_names()`

Names of distribution shape parameters

Returns

names – Parameter names

Return type

list (str)

arch.univariate.Normal.partial_moment

`Normal.partial_moment(n, z=0.0, parameters=None)`

Order n lower partial moment from $-\infty$ to z

Parameters

n : int

Order of partial moment

z : float, optional

Upper bound for partial moment integral

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

Partial moment

Return type

float

References

Notes

The order n lower partial moment to z is

$$\int_{-\infty}^z x^n f(x) dx$$

See¹ for more details.

arch.univariate.Normal.ppf

`Normal.ppf(pits, parameters=None)`

Inverse cumulative density function (ICDF)

Parameters

pits : {float, ndarray}

Probability-integral-transformed values in the interval (0, 1).

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

i – Inverse CDF values

Return type

{float, ndarray}

arch.univariate.Normal.simulate

`Normal.simulate(parameters)`

Simulates i.i.d. draws from the distribution

Parameters

parameters : ndarray

Distribution parameters

Returns

simulator – Callable that take a single output size argument and returns i.i.d. draws from the distribution

Return type

callable

¹ Winkler et al. (1972) “The Determination of Partial Moments” *Management Science* Vol. 19 No. 3

arch.univariate.Normal.starting_values

`Normal.starting_values(std_resid)`

Construct starting values for use in optimization.

Parameters

std_resid : ndarray

Estimated standardized residuals to use in computing starting values for the shape parameter

Returns

sv – The estimated shape parameters for the distribution

Return type

ndarray

Notes

Size of sv depends on the distribution

Properties

<i>generator</i>	The NumPy Generator or RandomState attached to the distribution
<i>name</i>	The name of the distribution
<i>random_state</i>	The NumPy RandomState attached to the distribution

arch.univariate.Normal.generator

property `Normal.generator` : `numpy.random.mtrand.RandomState` | `numpy.random._generator.Generator`

The NumPy Generator or RandomState attached to the distribution

Return type

`RandomState` | `Generator`

arch.univariate.Normal.name

property `Normal.name` : `str`

The name of the distribution

Return type

`str`

arch.univariate.Normal.random_state

property `Normal.random_state`: `numpy.random.mtrand.RandomState` | `numpy.random._generator.Generator`

The NumPy `RandomState` attached to the distribution

Deprecated since version 5.0: `random_state` is deprecated. Use `generator` instead.

Return type

`RandomState` | `Generator`

1.11.2 arch.univariate.StudentsT

class `arch.univariate.StudentsT`(`random_state=None`, *, `seed=None`)

Standardized Student's distribution for use with ARCH models

Parameters

`random_state` : `RandomState`, optional

Deprecated since version 5.0: `random_state` is deprecated. Use `seed` instead.

`seed` : {`int`, `Generator`, `RandomState`}, optional

Random number generator instance or `int` to use. Set to ensure reproducibility. If using an `int`, the argument is passed to `np.random.default_rng`. If not provided, `default_rng` is used with system-provided entropy.

Methods

<code>bounds</code> (resids)	Parameter bounds for use in optimization.
<code>cdf</code> (resids[, parameters])	Cumulative distribution function
<code>constraints</code> ()	Construct arrays to use in constrained optimization.
<code>loglikelihood</code> (parameters, resids, sigma2[, ...])	Computes the log-likelihood of assuming residuals are have a standardized (to have unit variance) Student's t distribution, conditional on the variance.
<code>moment</code> (n[, parameters])	Moment of order n
<code>parameter_names</code> ()	Names of distribution shape parameters
<code>partial_moment</code> (n[, z, parameters])	Order n lower partial moment from -inf to z
<code>ppf</code> (pits[, parameters])	Inverse cumulative density function (ICDF)
<code>simulate</code> (parameters)	Simulates i.i.d.
<code>starting_values</code> (std_resid)	Construct starting values for use in optimization.

arch.univariate.StudentsT.bounds

`StudentsT.bounds`(`resids`)

Parameter bounds for use in optimization.

Parameters

`resids` : `ndarray`

Residuals to use when computing the bounds

Returns

`bounds` – List containing a single tuple with (lower, upper) bounds

Return type

list

arch.univariate.StudentsT.cdf`StudentsT.cdf(resids, parameters=None)`

Cumulative distribution function

Parameters**resids : ndarray**

Values at which to evaluate the cdf

parameters : ndarray

Distribution parameters. Use None for parameterless distributions.

Returns**f** – CDF values**Return type**

ndarray

arch.univariate.StudentsT.constraints`StudentsT.constraints()`

Construct arrays to use in constrained optimization.

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Constraint loadings
- **b** (ndarray) – Constraint values

NotesParameters satisfy the constraints $A \cdot \text{parameters} - b \geq 0$ **arch.univariate.StudentsT.loglikelihood**`StudentsT.loglikelihood(parameters, resids, sigma2, individual=False)`

Computes the log-likelihood of assuming residuals are have a standardized (to have unit variance) Student's t distribution, conditional on the variance.

Parameters**parameters : ndarray**

Shape parameter of the t distribution

resids : ndarray

The residuals to use in the log-likelihood calculation

sigma2 : ndarray

Conditional variances of resids

individual : bool, optional

Flag indicating whether to return the vector of individual log likelihoods (True) or the sum (False)

Returns

ll – The log-likelihood

Return type

float

Notes

The log-likelihood of a single data point x is

$$\ln \Gamma\left(\frac{\nu+1}{2}\right) - \ln \Gamma\left(\frac{\nu}{2}\right) - \frac{1}{2} \ln(\pi(\nu-2)\sigma^2) - \frac{\nu+1}{2} \ln(1+x^2/(\sigma^2(\nu-2)))$$

where Γ is the gamma function.

arch.univariate.StudentsT.moment

StudentsT.**moment**(**n**, **parameters=None**)

Moment of order n

Parameters

n : int

Order of moment

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

Calculated moment

Return type

float

arch.univariate.StudentsT.parameter_names

StudentsT.**parameter_names**()

Names of distribution shape parameters

Returns

names – Parameter names

Return type

list (str)

arch.univariate.StudentsT.partial_moment

StudentsT.**partial_moment**(n, z=0.0, parameters=None)

Order n lower partial moment from -inf to z

Parameters

n : int

Order of partial moment

z : float, optional

Upper bound for partial moment integral

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

Partial moment

Return type

float

References**Notes**

The order n lower partial moment to z is

$$\int_{-\infty}^z x^n f(x) dx$$

See¹ for more details.

arch.univariate.StudentsT.ppf

StudentsT.**ppf**(pits, parameters=None)

Inverse cumulative density function (ICDF)

Parameters

pits : {float, ndarray}

Probability-integral-transformed values in the interval (0, 1).

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

i – Inverse CDF values

Return type

{float, ndarray}

¹ Winkler et al. (1972) “The Determination of Partial Moments” *Management Science* Vol. 19 No. 3

arch.univariate.StudentsT.simulate**StudentsT.simulate(parameters)**

Simulates i.i.d. draws from the distribution

Parameters**parameters : ndarray**
Distribution parameters**Returns****simulator** – Callable that take a single output size argument and returns i.i.d. draws from the distribution**Return type**

callable

arch.univariate.StudentsT.starting_values**StudentsT.starting_values(std_resid)**

Construct starting values for use in optimization.

Parameters**std_resid : ndarray**
Estimated standardized residuals to use in computing starting values for the shape parameter**Returns****sv** – Array containing starting valuer for shape parameter**Return type**

ndarray

Notes

Uses relationship between kurtosis and degree of freedom parameter to produce a moment-based estimator for the starting values.

Properties

<i>generator</i>	The NumPy Generator or RandomState attached to the distribution
<i>name</i>	The name of the distribution
<i>random_state</i>	The NumPy RandomState attached to the distribution

arch.univariate.StudentsT.generator

property StudentsT.**generator** : `numpy.random.mtrand.RandomState` | `numpy.random._generator.Generator`

The NumPy Generator or RandomState attached to the distribution

Return type

`RandomState` | `Generator`

arch.univariate.StudentsT.name

property StudentsT.**name** : `str`

The name of the distribution

Return type

`str`

arch.univariate.StudentsT.random_state

property StudentsT.**random_state** : `numpy.random.mtrand.RandomState` | `numpy.random._generator.Generator`

The NumPy RandomState attached to the distribution

Deprecated since version 5.0: `random_state` is deprecated. Use `generator` instead.

Return type

`RandomState` | `Generator`

1.11.3 arch.univariate.SkewStudent

class arch.univariate.**SkewStudent**(`random_state=None`, *, `seed=None`)

Standardized Skewed Student's distribution for use with ARCH models

Parameters

random_state : `RandomState`, optional

Deprecated since version 5.0: `random_state` is deprecated. Use `seed` instead.

seed : {`int`, `Generator`, `RandomState`}, optional

Random number generator instance or int to use. Set to ensure reproducibility. If using an int, the argument is passed to `np.random.default_rng`. If not provided, `default_rng` is used with system-provided entropy.

Notes

The Standardized Skewed Student's distribution ⁽¹⁾ takes two parameters, η and λ . η controls the tail shape and is similar to the shape parameter in a Standardized Student's t. λ controls the skewness. When $\lambda = 0$ the distribution is identical to a standardized Student's t.

¹ Hansen, B. E. (1994). Autoregressive conditional density estimation. *International Economic Review*, 35(3), 705–730. <https://www.ssc.wisc.edu/~bhansen/papers/ier_94.pdf>

References

Methods

<i>bounds</i> (resids)	Parameter bounds for use in optimization.
<i>cdf</i> (resids[, parameters])	Cumulative distribution function
<i>constraints</i> ()	Construct arrays to use in constrained optimization.
<i>loglikelihood</i> (parameters, resids, sigma2[, ...])	Computes the log-likelihood of assuming residuals are have a standardized (to have unit variance) Skew Student's t distribution, conditional on the variance.
<i>moment</i> (n[, parameters])	Moment of order n
<i>parameter_names</i> ()	Names of distribution shape parameters
<i>partial_moment</i> (n[, z, parameters])	Order n lower partial moment from -inf to z
<i>ppf</i> (pits[, parameters])	Inverse cumulative density function (ICDF)
<i>simulate</i> (parameters)	Simulates i.i.d.
<i>starting_values</i> (std_resid)	Construct starting values for use in optimization.

arch.univariate.SkewStudent.bounds

SkewStudent.**bounds**(resids)

Parameter bounds for use in optimization.

Parameters

resids : ndarray

Residuals to use when computing the bounds

Returns

bounds – List containing a single tuple with (lower, upper) bounds

Return type

list

arch.univariate.SkewStudent.cdf

SkewStudent.**cdf**(resids, parameters=**None**)

Cumulative distribution function

Parameters

resids : ndarray

Values at which to evaluate the cdf

parameters : ndarray

Distribution parameters. Use None for parameterless distributions.

Returns

f – CDF values

Return type

ndarray

arch.univariate.SkewStudent.constraints

SkewStudent.constraints()

Construct arrays to use in constrained optimization.

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Constraint loadings
- **b** (ndarray) – Constraint values

Notes

Parameters satisfy the constraints $A \cdot \text{parameters} - b \geq 0$

arch.univariate.SkewStudent.loglikelihood

SkewStudent.loglikelihood(parameters, resids, sigma2, individual=False)

Computes the log-likelihood of assuming residuals are have a standardized (to have unit variance) Skew Student's t distribution, conditional on the variance.

Parameters

parameters : ndarray

Shape parameter of the skew-t distribution

resids : ndarray

The residuals to use in the log-likelihood calculation

sigma2 : ndarray

Conditional variances of resids

individual : bool, optional

Flag indicating whether to return the vector of individual log likelihoods (True) or the sum (False)

Returns

ll – The log-likelihood

Return type

float

Notes

The log-likelihood of a single data point x is

$$\ln \left[\frac{bc}{\sigma} \left(1 + \frac{1}{\eta - 2} \left(\frac{a + bx/\sigma}{1 + \text{sgn}(x/\sigma + a/b)\lambda} \right)^2 \right)^{-(\eta+1)/2} \right],$$

where $2 < \eta < \infty$, and $-1 < \lambda < 1$. The constants a , b , and c are given by

$$a = 4\lambda c \frac{\eta - 2}{\eta - 1}, \quad b^2 = 1 + 3\lambda^2 - a^2, \quad c = \frac{\Gamma(\frac{\eta+1}{2})}{\sqrt{\pi(\eta-2)}\Gamma(\frac{\eta}{2})},$$

and Γ is the gamma function.

arch.univariate.SkewStudent.moment

`SkewStudent.moment(n, parameters=None)`

Moment of order n

Parameters

n : int

Order of moment

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

Calculated moment

Return type

float

arch.univariate.SkewStudent.parameter_names

`SkewStudent.parameter_names()`

Names of distribution shape parameters

Returns

names – Parameter names

Return type

list (str)

arch.univariate.SkewStudent.partial_moment

`SkewStudent.partial_moment(n, z=0.0, parameters=None)`

Order n lower partial moment from -inf to z

Parameters

n : int

Order of partial moment

z : float, optional

Upper bound for partial moment integral

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

Partial moment

Return type

float

References

Notes

The order n lower partial moment to z is

$$\int_{-\infty}^z x^n f(x) dx$$

See¹ for more details.

arch.univariate.SkewStudent.ppf

SkewStudent.ppf(pits, parameters=None)

Inverse cumulative density function (ICDF)

Parameters

pits : {float, ndarray}

Probability-integral-transformed values in the interval (0, 1).

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

i – Inverse CDF values

Return type

{float, ndarray}

arch.univariate.SkewStudent.simulate

SkewStudent.simulate(parameters)

Simulates i.i.d. draws from the distribution

Parameters

parameters : ndarray

Distribution parameters

Returns

simulator – Callable that take a single output size argument and returns i.i.d. draws from the distribution

Return type

callable

¹ Winkler et al. (1972) “The Determination of Partial Moments” *Management Science* Vol. 19 No. 3

arch.univariate.SkewStudent.starting_values**SkewStudent.starting_values**(std_resid)

Construct starting values for use in optimization.

Parameters**std_resid** : ndarray

Estimated standardized residuals to use in computing starting values for the shape parameter

Returns**sv** – Array containing starting valuer for shape parameter**Return type**

ndarray

Notes

Uses relationship between kurtosis and degree of freedom parameter to produce a moment-based estimator for the starting values.

Properties

<i>generator</i>	The NumPy Generator or RandomState attached to the distribution
<i>name</i>	The name of the distribution
<i>random_state</i>	The NumPy RandomState attached to the distribution

arch.univariate.SkewStudent.generator

property SkewStudent.generator : `numpy.random.mtrand.RandomState` | `numpy.random._generator.Generator`

The NumPy Generator or RandomState attached to the distribution

Return type`RandomState` | `Generator`**arch.univariate.SkewStudent.name**

property SkewStudent.name : `str`

The name of the distribution

Return type`str`

arch.univariate.SkewStudent.random_state

property `SkewStudent.random_state` : `numpy.random.mtrand.RandomState` | `numpy.random._generator.Generator`

The NumPy RandomState attached to the distribution

Deprecated since version 5.0: `random_state` is deprecated. Use `generator` instead.

Return type

`RandomState` | `Generator`

1.11.4 arch.univariate.GeneralizedError

class `arch.univariate.GeneralizedError`(`random_state=None`, *, `seed=None`)

Generalized Error distribution for use with ARCH models

Parameters

`random_state` : `RandomState`, optional

Deprecated since version 5.0: `random_state` is deprecated. Use `seed` instead.

`seed` : {`int`, `Generator`, `RandomState`}, optional

Random number generator instance or int to use. Set to ensure reproducibility. If using an int, the argument is passed to `np.random.default_rng`. If not provided, `default_rng` is used with system-provided entropy.

Methods

<code>bounds</code> (resids)	Parameter bounds for use in optimization.
<code>cdf</code> (resids[, parameters])	Cumulative distribution function
<code>constraints</code> ()	Construct arrays to use in constrained optimization.
<code>loglikelihood</code> (parameters, resids, sigma2[, ...])	Computes the log-likelihood of assuming residuals are have a Generalized Error Distribution, conditional on the variance.
<code>moment</code> (n[, parameters])	Moment of order n
<code>parameter_names</code> ()	Names of distribution shape parameters
<code>partial_moment</code> (n[, z, parameters])	Order n lower partial moment from -inf to z
<code>ppf</code> (pits[, parameters])	Inverse cumulative density function (ICDF)
<code>simulate</code> (parameters)	Simulates i.i.d.
<code>starting_values</code> (std_resid)	Construct starting values for use in optimization.

arch.univariate.GeneralizedError.bounds

`GeneralizedError.bounds`(resids)

Parameter bounds for use in optimization.

Parameters

`resids` : `ndarray`

Residuals to use when computing the bounds

Returns

`bounds` – List containing a single tuple with (lower, upper) bounds

Return type

list

arch.univariate.GeneralizedError.cdf`GeneralizedError.cdf(resids, parameters=None)`

Cumulative distribution function

Parameters**resids : ndarray**

Values at which to evaluate the cdf

parameters : ndarray

Distribution parameters. Use None for parameterless distributions.

Returns**f** – CDF values**Return type**

ndarray

arch.univariate.GeneralizedError.constraints`GeneralizedError.constraints()`

Construct arrays to use in constrained optimization.

Return type

tuple[ndarray, ndarray]

Returns

- **A** (ndarray) – Constraint loadings
- **b** (ndarray) – Constraint values

NotesParameters satisfy the constraints $A \cdot \text{parameters} - b \geq 0$ **arch.univariate.GeneralizedError.loglikelihood**`GeneralizedError.loglikelihood(parameters, resids, sigma2, individual=False)`

Computes the log-likelihood of assuming residuals are have a Generalized Error Distribution, conditional on the variance.

Parameters**parameters : ndarray**

Shape parameter of the GED distribution

resids : ndarray

The residuals to use in the log-likelihood calculation

sigma2 : ndarray

Conditional variances of resids

individual : **bool**, optional

Flag indicating whether to return the vector of individual log likelihoods (True) or the sum (False)

Returns

ll – The log-likelihood

Return type

float

Notes

The log-likelihood of a single data point x is

$$\ln \nu - \ln c - \ln \Gamma\left(\frac{1}{\nu}\right) - \left(1 + \frac{1}{\nu}\right) \ln 2 - \frac{1}{2} \ln \sigma^2 - \frac{1}{2} \left| \frac{x}{c\sigma} \right|^\nu$$

where Γ is the gamma function and $\ln c$ is

$$\ln c = \frac{1}{2} \left(\frac{-2}{\nu} \ln 2 + \ln \Gamma\left(\frac{1}{\nu}\right) - \ln \Gamma\left(\frac{3}{\nu}\right) \right).$$

arch.univariate.GeneralizedError.moment

GeneralizedError.**moment**(**n**, **parameters**=**None**)

Moment of order n

Parameters

n : **int**

Order of moment

parameters : **ndarray**, optional

Distribution parameters. Use None for parameterless distributions.

Returns

Calculated moment

Return type

float

arch.univariate.GeneralizedError.parameter_names

GeneralizedError.**parameter_names**()

Names of distribution shape parameters

Returns

names – Parameter names

Return type

list (str)

arch.univariate.GeneralizedError.partial_moment

`GeneralizedError.partial_moment(n, z=0.0, parameters=None)`

Order n lower partial moment from -inf to z

Parameters

n : int

Order of partial moment

z : float, optional

Upper bound for partial moment integral

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

Partial moment

Return type

float

References**Notes**

The order n lower partial moment to z is

$$\int_{-\infty}^z x^n f(x) dx$$

See¹ for more details.

arch.univariate.GeneralizedError.ppf

`GeneralizedError.ppf(pits, parameters=None)`

Inverse cumulative density function (ICDF)

Parameters

pits : {float, ndarray}

Probability-integral-transformed values in the interval (0, 1).

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

i – Inverse CDF values

Return type

{float, ndarray}

¹ Winkler et al. (1972) “The Determination of Partial Moments” *Management Science* Vol. 19 No. 3

arch.univariate.GeneralizedError.simulate**GeneralizedError.simulate(parameters)**

Simulates i.i.d. draws from the distribution

Parameters**parameters : ndarray**
Distribution parameters**Returns****simulator** – Callable that take a single output size argument and returns i.i.d. draws from the distribution**Return type**

callable

arch.univariate.GeneralizedError.starting_values**GeneralizedError.starting_values(std_resid)**

Construct starting values for use in optimization.

Parameters**std_resid : ndarray**
Estimated standardized residuals to use in computing starting values for the shape parameter**Returns****sv** – Array containing starting valuer for shape parameter**Return type**

ndarray

Notes

Defaults to 1.5 which implies heavier tails than a normal

Properties

<i>generator</i>	The NumPy Generator or RandomState attached to the distribution
<i>name</i>	The name of the distribution
<i>random_state</i>	The NumPy RandomState attached to the distribution

arch.univariate.GeneralizedError.generator

property GeneralizedError.generator : numpy.random.mtrand.RandomState |
numpy.random._generator.Generator

The NumPy Generator or RandomState attached to the distribution

Return type

RandomState | Generator

arch.univariate.GeneralizedError.name

property GeneralizedError.name : str

The name of the distribution

Return type

str

arch.univariate.GeneralizedError.random_state

property GeneralizedError.random_state : numpy.random.mtrand.RandomState |
numpy.random._generator.Generator

The NumPy RandomState attached to the distribution

Deprecated since version 5.0: random_state is deprecated. Use generator instead.

Return type

RandomState | Generator

1.11.5 Writing New Distributions

All distributions must inherit from :class:Distribution and provide all public methods.

Distribution([random_state, seed])

Template for subclassing only

arch.univariate.distribution.Distribution

class arch.univariate.distribution.Distribution(random_state=*None*, *, seed=*None*)

Template for subclassing only

Methods

<code>bounds(resids)</code>	Parameter bounds for use in optimization.
<code>cdf(resids[, parameters])</code>	Cumulative distribution function
<code>constraints()</code>	Construct arrays to use in constrained optimization.
<code>loglikelihood(parameters, resids, sigma2[, ...])</code>	Loglikelihood evaluation.
<code>moment(n[, parameters])</code>	Moment of order n
<code>parameter_names()</code>	Names of distribution shape parameters
<code>partial_moment(n[, z, parameters])</code>	Order n lower partial moment from -inf to z
<code>ppf(pits[, parameters])</code>	Inverse cumulative density function (ICDF)
<code>simulate(parameters)</code>	Simulates i.i.d.
<code>starting_values(std_resid)</code>	Construct starting values for use in optimization.

arch.univariate.distribution.Distribution.bounds

abstract `Distribution.bounds(resids)`

Parameter bounds for use in optimization.

Parameters

resids : ndarray

Residuals to use when computing the bounds

Returns

bounds – List containing a single tuple with (lower, upper) bounds

Return type

list

arch.univariate.distribution.Distribution.cdf

abstract `Distribution.cdf(resids, parameters=None)`

Cumulative distribution function

Parameters

resids : ndarray

Values at which to evaluate the cdf

parameters : ndarray

Distribution parameters. Use None for parameterless distributions.

Returns

f – CDF values

Return type

ndarray

arch.univariate.distribution.Distribution.constraints

abstract `Distribution.constraints()`

Construct arrays to use in constrained optimization.

Return type

`tuple[ndarray, ndarray]`

Returns

- **A** (`ndarray`) – Constraint loadings
- **b** (`ndarray`) – Constraint values

Notes

Parameters satisfy the constraints $A \cdot \text{parameters} - b \geq 0$

arch.univariate.distribution.Distribution.loglikelihood

abstract `Distribution.loglikelihood(parameters, resids, sigma2, individual=False)`

Loglikelihood evaluation.

Parameters

parameters : `ndarray`

Distribution shape parameters

resids : `ndarray`

nobs array of model residuals

sigma2 : `ndarray`

nobs array of conditional variances

individual : `bool`, optional

Flag indicating whether to return the vector of individual log likelihoods (True) or the sum (False)

Notes

Returns the loglikelihood where resids are the “data”, and parameters and sigma2 are inputs.

Return type

`float | ndarray`

arch.univariate.distribution.Distribution.moment

abstract `Distribution.moment(n, parameters=None)`

Moment of order n

Parameters

n : `int`

Order of moment

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

Calculated moment

Return type

float

arch.univariate.distribution.Distribution.parameter_names

abstract Distribution.**parameter_names**()

Names of distribution shape parameters

Returns

names – Parameter names

Return type

list (str)

arch.univariate.distribution.Distribution.partial_moment

abstract Distribution.**partial_moment**(n, z=0.0, parameters=None)

Order n lower partial moment from -inf to z

Parameters

n : int

Order of partial moment

z : float, optional

Upper bound for partial moment integral

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns

Partial moment

Return type

float

References

Notes

The order n lower partial moment to z is

$$\int_{-\infty}^z x^n f(x) dx$$

See¹ for more details.

¹ Winkler et al. (1972) “The Determination of Partial Moments” *Management Science* Vol. 19 No. 3

arch.univariate.distribution.Distribution.ppf**abstract** `Distribution.ppf(pits, parameters=None)`

Inverse cumulative density function (ICDF)

Parameters**pits** : {float, ndarray}

Probability-integral-transformed values in the interval (0, 1).

parameters : ndarray, optional

Distribution parameters. Use None for parameterless distributions.

Returns**i** – Inverse CDF values**Return type**

{float, ndarray}

arch.univariate.distribution.Distribution.simulate**abstract** `Distribution.simulate(parameters)`

Simulates i.i.d. draws from the distribution

Parameters**parameters** : ndarray

Distribution parameters

Returns**simulator** – Callable that take a single output size argument and returns i.i.d. draws from the distribution**Return type**

callable

arch.univariate.distribution.Distribution.starting_values**abstract** `Distribution.starting_values(std_resid)`

Construct starting values for use in optimization.

Parameters**std_resid** : ndarray

Estimated standardized residuals to use in computing starting values for the shape parameter

Returns**sv** – The estimated shape parameters for the distribution**Return type**

ndarray

Notes

Size of `sv` depends on the distribution

Properties

<code>generator</code>	The NumPy Generator or RandomState attached to the distribution
<code>name</code>	The name of the distribution
<code>random_state</code>	The NumPy RandomState attached to the distribution

`arch.univariate.distribution.Distribution.generator`

property `Distribution.generator`: `numpy.random.mtrand.RandomState` | `numpy.random._generator.Generator`

The NumPy Generator or RandomState attached to the distribution

Return type

`RandomState` | `Generator`

`arch.univariate.distribution.Distribution.name`

property `Distribution.name`: `str`

The name of the distribution

Return type

`str`

`arch.univariate.distribution.Distribution.random_state`

property `Distribution.random_state`: `numpy.random.mtrand.RandomState` | `numpy.random._generator.Generator`

The NumPy RandomState attached to the distribution

Deprecated since version 5.0: `random_state` is deprecated. Use `generator` instead.

Return type

`RandomState` | `Generator`

1.12 Model Results

All model return the same object, a results class (`ARCHModelResult`). When using the `fix` method, a (`ARCHModelFixedResult`) is produced that lacks some properties of a (`ARCHModelResult`) that are not relevant when parameters are not estimated.

<code>ARCHModelResult</code> (params, param_cov, r2, ...)	Results from estimation of an ARCHModel model
<code>ARCHModelFixedResult</code> (params, resid, ...)	Results for fixed parameters for an ARCHModel model

1.12.1 arch.univariate.base.ARCHModelResult

```
class arch.univariate.base.ARCHModelResult(params, param_cov, r2, resid, volatility, cov_type, dep_var,
                                           names, loglikelihood, is_pandas, optim_output, fit_start,
                                           fit_stop, model)
```

Results from estimation of an ARCHModel model

Parameters

params : ndarray
Estimated parameters

param_cov : {ndarray, None}
Estimated variance-covariance matrix of params. If none, calls method to compute variance from model when parameter covariance is first used from result

r2 : float
Model R-squared

resid : ndarray
Residuals from model. Residuals have same shape as original data and contain nan-values in locations not used in estimation

volatility : ndarray
Conditional volatility from model

cov_type : str
String describing the covariance estimator used

dep_var : Series
Dependent variable

names : list (str)
Model parameter names

loglikelihood : float
Loglikelihood at estimated parameters

is_pandas : bool
Whether the original input was pandas

optim_output : OptimizeResult
Result of log-likelihood optimization

fit_start : int
Integer index of the first observation used to fit the model

fit_stop : int
Integer index of the last observation used to fit the model using slice notation *fit_start:fit_stop*

model : ARCHModel
The model object used to estimate the parameters

Methods

<code>arch_lm_test([lags, standardized])</code>	ARCH LM test for conditional heteroskedasticity
<code>conf_int([alpha])</code>	Parameter confidence intervals
<code>forecast([params, horizon, start, align, ...])</code>	Construct forecasts from estimated model
<code>hedgehog_plot([params, horizon, step, ...])</code>	Plot forecasts from estimated model
<code>plot([annualize, scale])</code>	Plot standardized residuals and conditional volatility
<code>summary()</code>	Constructs a summary of the results from a fit model.

`arch.univariate.base.ARCHModelResult.arch_lm_test`

`ARCHModelResult.arch_lm_test(lags=None, standardized=False)`

ARCH LM test for conditional heteroskedasticity

Parameters

lags : **int**, optional

Number of lags to include in the model. If not specified,

standardized : **bool**, optional

Flag indicating to test the model residuals divided by their conditional standard deviations.
If False, directly tests the estimated residuals.

Returns

result – Result of ARCH-LM test

Return type

WaldTestStatistic

`arch.univariate.base.ARCHModelResult.conf_int`

`ARCHModelResult.conf_int(alpha=0.05)`

Parameter confidence intervals

Parameters

alpha : **float**, optional

Size (prob.) to use when constructing the confidence interval.

Returns

ci – Array where the *i*th row contains the confidence interval for the *i*th parameter

Return type

DataFrame

`arch.univariate.base.ARCHModelResult.forecast`

`ARCHModelResult.forecast(params=None, horizon=1, start=None, align='origin', method='analytic',
simulations=1000, rng=None, random_state=None, *, reindex=None,
x=None)`

Construct forecasts from estimated model

Parameters

params : ndarray, optional

Alternative parameters to use. If not provided, the parameters estimated when fitting the model are used. Must be identical in shape to the parameters computed by fitting the model.

horizon : int, optional

Number of steps to forecast

start : {int, datetime, Timestamp, str}, optional

An integer, datetime or str indicating the first observation to produce the forecast for. Date-times can only be used with pandas inputs that have a datetime index. Strings must be convertible to a date time, such as in '1945-01-01'.

align : str, optional

Either 'origin' or 'target'. When set of 'origin', the t-th row of forecasts contains the forecasts for t+1, t+2, ..., t+h. When set to 'target', the t-th row contains the 1-step ahead forecast from time t-1, the 2 step from time t-2, ..., and the h-step from time t-h. 'target' simplified computing forecast errors since the realization and h-step forecast are aligned.

method : {'analytic', 'simulation', 'bootstrap'}, optional

Method to use when producing the forecast. The default is analytic. The method only affects the variance forecast generation. Not all volatility models support all methods. In particular, volatility models that do not evolve in squares such as EGARCH or TARCH do not support the 'analytic' method for horizons > 1.

simulations : int, optional

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable, optional

Custom random number generator to use in simulation-based forecasts. Must produce random samples using the syntax *rng(size)* where size the 2-element tuple (simulations, horizon).

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

reindex : bool, optional

Whether to reindex the forecasts to have the same dimension as the series being forecast. Prior to 4.18 this was the default. As of 4.19 this is now optional. If not provided, a warning is raised about the future change in the default which will occur after September 2021.

New in version 4.19.

x : {dict[label, array_like], array_like}

Values to use for exogenous regressors if any are included in the model. Three formats are accepted:

- 2-d array-like: This format can be used when there is a single exogenous variable. The input must have shape (nforecast, horizon) or (nobs, horizon) where nforecast is the number of forecasting periods and nobs is the original shape of y. For example, if a single series of forecasts are made from the end of the sample with a horizon of 10, then the input can be (1, 10). Alternatively, if the original data had 1000 observations, then the input can be (1000, 10), and only the final row is used to produce forecasts.
- A dictionary of 2-d array-like: This format is identical to the previous except that the dictionary keys must match the names of the exog variables. Requires that the exog variables were pass as a pandas DataFrame.

- A 3-d NumPy array (or equivalent). In this format, each panel (0th axis) is a 2-d array that must have shape (nforecast, horizon) or (nobs, horizon). The array `x[j]` corresponds to the `j`-th column of the exogenous variables.

Due to the complexity required to accommodate all scenarios, please see the example notebook that demonstrates the valid formats for `x`.

New in version 4.19.

Returns

Container for forecasts. Key properties are `mean`, `variance` and `residual_variance`.

Return type

arch.univariate.base.ARCHModelForecast

Notes

The most basic 1-step ahead forecast will return a vector with the same length as the original data, where the `t`-th value will be the time-`t` forecast for time `t + 1`. When the horizon is `> 1`, and when using the default value for `align`, the forecast value in position `[t, h]` is the time-`t`, `h+1` step ahead forecast.

If model contains exogenous variables (*model.x is not None*), then only 1-step ahead forecasts are available. Using horizon `> 1` will produce a warning and all columns, except the first, will be nan-filled.

If `align` is 'origin', `forecast[t,h]` contains the forecast made using `y[:t]` (that is, up to but not including `t`) for horizon `h + 1`. For example, `y[100,2]` contains the 3-step ahead forecast using the first 100 data points, which will correspond to the realization `y[100 + 2]`. If `align` is 'target', then the same forecast is in location `[102, 2]`, so that it is aligned with the observation to use when evaluating, but still in the same column.

`arch.univariate.base.ARCHModelResult.hedgehog_plot`

```
ARCHModelResult.hedgehog_plot(params=None, horizon=10, step=10, start=None,
                               plot_type='volatility', method='analytic', simulations=1000)
```

Plot forecasts from estimated model

Parameters

params : {ndarray, Series}

Alternative parameters to use. If not provided, the parameters computed by fitting the model are used. Must be 1-d and identical in shape to the parameters computed by fitting the model.

horizon : int, optional

Number of steps to forecast

step : int, optional

Non-negative number of forecasts to skip between spines

start : int, datetime or str, optional

An integer, datetime or str indicating the first observation to produce the forecast for. Datetimes can only be used with pandas inputs that have a datetime index. Strings must be convertible to a date time, such as in '1945-01-01'. If not provided, the start is set to the earliest forecastable date.

plot_type : {'volatility', 'mean'}

Quantity to plot, the forecast volatility or the forecast mean

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic. The method only affects the variance forecast generation. Not all volatility models support all methods. In particular, volatility models that do not evolve in squares such as EGARCH or TARCH do not support the 'analytic' method for horizons > 1.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

Returns

fig – Handle to the figure

Return type

figure

Examples

```
>>> import pandas as pd
>>> from arch import arch_model
>>> am = arch_model(None, mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> sim_data = am.simulate([0.1, 0.4, 0.3, 0.2, 1.0], 250)
>>> sim_data.index = pd.date_range('2000-01-01', periods=250)
>>> am = arch_model(sim_data['data'], mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> res = am.fit()
>>> fig = res.hedgehog_plot(plot_type='mean')
```

arch.univariate.base.ARCHModelResult.plot

ARCHModelResult.plot(annualize=None, scale=None)

Plot standardized residuals and conditional volatility

Parameters

annualize : str, optional

String containing frequency of data that indicates plot should contain annualized volatility. Supported values are 'D' (daily), 'W' (weekly) and 'M' (monthly), which scale variance by 252, 52, and 12, respectively.

scale : float, optional

Value to use when scaling returns to annualize. If scale is provided, annualize is ignored and the value in scale is used.

Returns

fig – Handle to the figure

Return type

figure

Examples

```
>>> from arch import arch_model
>>> am = arch_model(None)
>>> sim_data = am.simulate([0.0, 0.01, 0.07, 0.92], 2520)
>>> am = arch_model(sim_data['data'])
>>> res = am.fit(update_freq=0, disp='off')
>>> fig = res.plot()
```

Produce a plot with annualized volatility

```
>>> fig = res.plot(annualize='D')
```

Override the usual scale of 252 to use 360 for an asset that trades most days of the year

```
>>> fig = res.plot(scale=360)
```

arch.univariate.base.ARCHModelResult.summary

ARCHModelResult.summary()

Constructs a summary of the results from a fit model.

Returns

summary – Object that contains tables and facilitated export to text, html or latex

Return type

Summary instance

Properties

<i>aic</i>	Akaike Information Criteria
<i>bic</i>	Schwarz/Bayesian Information Criteria
<i>conditional_volatility</i>	Estimated conditional volatility
<i>convergence_flag</i>	scipy.optimize.minimize result flag
<i>fit_start</i>	Start of sample used to estimate parameters
<i>fit_stop</i>	End of sample used to estimate parameters
<i>loglikelihood</i>	Model loglikelihood
<i>model</i>	Model instance used to produce the fit
<i>nobs</i>	Number of data points used to estimate model
<i>num_params</i>	Number of parameters in model
<i>optimization_result</i>	Information about the convergence of the loglikelihood optimization
<i>param_cov</i>	Parameter covariance
<i>params</i>	Model Parameters
<i>pvalues</i>	Array of p-values for the t-statistics
<i>resid</i>	Model residuals
<i>rsquared</i>	R-squared
<i>rsquared_adj</i>	Degree of freedom adjusted R-squared
<i>scale</i>	The scale applied to the original data before estimating the model.
<i>std_err</i>	Array of parameter standard errors
<i>std_resid</i>	Residuals standardized by conditional volatility
<i>tvalues</i>	Array of t-statistics testing the null that the coefficient are 0

arch.univariate.base.ARCHModelResult.aic

property ARCHModelResult.aic: float

Akaike Information Criteria

$-2 * \text{loglikelihood} + 2 * \text{num_params}$

arch.univariate.base.ARCHModelResult.bic

property ARCHModelResult.bic : float
Schwarz/Bayesian Information Criteria
 $-2 * \text{loglikelihood} + \log(\text{nobs}) * \text{num_params}$

arch.univariate.base.ARCHModelResult.conditional_volatility

property ARCHModelResult.conditional_volatility : pandas.core.series.Series | numpy.ndarray
Estimated conditional volatility

Returns

conditional_volatility – nobs element array containing the conditional volatility (square root of conditional variance). The values are aligned with the input data so that the value in the t-th position is the variance of t-th error, which is computed using time-(t-1) information.

Return type

{ndarray, Series}

arch.univariate.base.ARCHModelResult.convergence_flag

property ARCHModelResult.convergence_flag : int
scipy.optimize.minimize result flag

arch.univariate.base.ARCHModelResult.fit_start

property ARCHModelResult.fit_start : int
Start of sample used to estimate parameters

arch.univariate.base.ARCHModelResult.fit_stop

property ARCHModelResult.fit_stop : int
End of sample used to estimate parameters

arch.univariate.base.ARCHModelResult.loglikelihood

property ARCHModelResult.loglikelihood : float
Model loglikelihood

arch.univariate.base.ARCHModelResult.model

property ARCHModelResult.model : ARCHModel
Model instance used to produce the fit

arch.univariate.base.ARCHModelResult.nobs**property** ARCHModelResult.nobs : int

Number of data points used to estimate model

arch.univariate.base.ARCHModelResult.num_params**property** ARCHModelResult.num_params : int

Number of parameters in model

arch.univariate.base.ARCHModelResult.optimization_result**property** ARCHModelResult.optimization_result : OptimizeResult

Information about the convergence of the loglikelihood optimization

Returns**optim_result** – Result from numerical optimization of the log-likelihood.**Return type**

OptimizeResult

arch.univariate.base.ARCHModelResult.param_cov**property** ARCHModelResult.param_cov : DataFrame

Parameter covariance

arch.univariate.base.ARCHModelResult.params**property** ARCHModelResult.params : Series

Model Parameters

arch.univariate.base.ARCHModelResult.pvalues**property** ARCHModelResult.pvalues : Series

Array of p-values for the t-statistics

arch.univariate.base.ARCHModelResult.resid**property** ARCHModelResult.resid : numpy.ndarray | pandas.core.series.Series

Model residuals

arch.univariate.base.ARCHModelResult.rsquared

property ARCHModelResult.rsquared : float
R-squared

arch.univariate.base.ARCHModelResult.rsquared_adj

property ARCHModelResult.rsquared_adj : float
Degree of freedom adjusted R-squared

arch.univariate.base.ARCHModelResult.scale

property ARCHModelResult.scale : float
The scale applied to the original data before estimating the model.
If scale=1.0, the the data have not been rescaled. Otherwise, the model parameters have been estimated on scale * y.

arch.univariate.base.ARCHModelResult.std_err

property ARCHModelResult.std_err : Series
Array of parameter standard errors

arch.univariate.base.ARCHModelResult.std_resid

property ARCHModelResult.std_resid : numpy.ndarray | pandas.core.series.Series
Residuals standardized by conditional volatility

arch.univariate.base.ARCHModelResult.tvalues

property ARCHModelResult.tvalues : Series
Array of t-statistics testing the null that the coefficient are 0

1.12.2 arch.univariate.base.ARCHModelFixedResult

class arch.univariate.base.ARCHModelFixedResult(params, resid, volatility, dep_var, names, loglikelihood, is_pandas, model)

Results for fixed parameters for an ARCHModel model

Parameters

params : ndarray
Estimated parameters

resid : ndarray
Residuals from model. Residuals have same shape as original data and contain nan-values in locations not used in estimation

volatility : ndarray
Conditional volatility from model

dep_var : **Series**
Dependent variable

names : **list (str)**
Model parameter names

loglikelihood : **float**
Loglikelihood at specified parameters

is_pandas : **bool**
Whether the original input was pandas

model : *ARCHModel*
The model object used to estimate the parameters

Methods

<i>arch_lm_test</i> ([lags, standardized])	ARCH LM test for conditional heteroskedasticity
<i>forecast</i> ([params, horizon, start, align, ...])	Construct forecasts from estimated model
<i>hedgehog_plot</i> ([params, horizon, step, ...])	Plot forecasts from estimated model
<i>plot</i> ([annualize, scale])	Plot standardized residuals and conditional volatility
<i>summary</i> ()	Constructs a summary of the results from a fit model.

arch.univariate.base.ARCHModelFixedResult.arch_lm_test

ARCHModelFixedResult.**arch_lm_test**(lags=*None*, standardized=*False*)

ARCH LM test for conditional heteroskedasticity

Parameters

lags : **int, optional**
Number of lags to include in the model. If not specified,

standardized : **bool, optional**
Flag indicating to test the model residuals divided by their conditional standard deviations.
If False, directly tests the estimated residuals.

Returns

result – Result of ARCH-LM test

Return type

WaldTestStatistic

arch.univariate.base.ARCHModelFixedResult.forecast

ARCHModelFixedResult.**forecast**(params=*None*, horizon=**1**, start=*None*, align='origin',
method='analytic', simulations=**1000**, rng=*None*,
random_state=*None*, *, reindex=*None*, x=*None*)

Construct forecasts from estimated model

Parameters

params : **ndarray, optional**
Alternative parameters to use. If not provided, the parameters estimated when fitting the model are used. Must be identical in shape to the parameters computed by fitting the model.

horizon : int, optional

Number of steps to forecast

start : {int, datetime, Timestamp, str}, optional

An integer, datetime or str indicating the first observation to produce the forecast for. Date-times can only be used with pandas inputs that have a datetime index. Strings must be convertible to a date time, such as in '1945-01-01'.

align : str, optional

Either 'origin' or 'target'. When set of 'origin', the t-th row of forecasts contains the forecasts for t+1, t+2, ..., t+h. When set to 'target', the t-th row contains the 1-step ahead forecast from time t-1, the 2 step from time t-2, ..., and the h-step from time t-h. 'target' simplified computing forecast errors since the realization and h-step forecast are aligned.

method : {'analytic', 'simulation', 'bootstrap'}, optional

Method to use when producing the forecast. The default is analytic. The method only affects the variance forecast generation. Not all volatility models support all methods. In particular, volatility models that do not evolve in squares such as EGARCH or TARCH do not support the 'analytic' method for horizons > 1.

simulations : int, optional

Number of simulations to run when computing the forecast using either simulation or bootstrap.

rng : callable, optional

Custom random number generator to use in simulation-based forecasts. Must produce random samples using the syntax *rng(size)* where size the 2-element tuple (simulations, horizon).

random_state : RandomState, optional

NumPy RandomState instance to use when method is 'bootstrap'

reindex : bool, optional

Whether to reindex the forecasts to have the same dimension as the series being forecast. Prior to 4.18 this was the default. As of 4.19 this is now optional. If not provided, a warning is raised about the future change in the default which will occur after September 2021.

New in version 4.19.

x : {dict[label, array_like], array_like}

Values to use for exogenous regressors if any are included in the model. Three formats are accepted:

- 2-d array-like: This format can be used when there is a single exogenous variable. The input must have shape (nforecast, horizon) or (nobs, horizon) where nforecast is the number of forecasting periods and nobs is the original shape of y. For example, if a single series of forecasts are made from the end of the sample with a horizon of 10, then the input can be (1, 10). Alternatively, if the original data had 1000 observations, then the input can be (1000, 10), and only the final row is used to produce forecasts.
- A dictionary of 2-d array-like: This format is identical to the previous except that the dictionary keys must match the names of the exog variables. Requires that the exog variables were pass as a pandas DataFrame.
- A 3-d NumPy array (or equivalent). In this format, each panel (0th axis) is a 2-d array that must have shape (nforecast, horizon) or (nobs,horizon). The array x[j] corresponds to the j-th column of the exogenous variables.

Due to the complexity required to accommodate all scenarios, please see the example notebook that demonstrates the valid formats for `x`.

New in version 4.19.

Returns

Container for forecasts. Key properties are `mean`, `variance` and `residual_variance`.

Return type

arch.univariate.base.ARCHModelForecast

Notes

The most basic 1-step ahead forecast will return a vector with the same length as the original data, where the t -th value will be the time- t forecast for time $t + 1$. When the horizon is > 1 , and when using the default value for *align*, the forecast value in position $[t, h]$ is the time- t , $h+1$ step ahead forecast.

If model contains exogenous variables (*model.x* is not *None*), then only 1-step ahead forecasts are available. Using horizon > 1 will produce a warning and all columns, except the first, will be nan-filled.

If *align* is 'origin', `forecast[t,h]` contains the forecast made using `y[:t]` (that is, up to but not including t) for horizon $h + 1$. For example, `y[100,2]` contains the 3-step ahead forecast using the first 100 data points, which will correspond to the realization `y[100 + 2]`. If *align* is 'target', then the same forecast is in location `[102, 2]`, so that it is aligned with the observation to use when evaluating, but still in the same column.

arch.univariate.base.ARCHModelFixedResult.hedgehog_plot

```
ARCHModelFixedResult.hedgehog_plot(params=None, horizon=10, step=10, start=None,
                                     plot_type='volatility', method='analytic',
                                     simulations=1000)
```

Plot forecasts from estimated model

Parameters

params : {ndarray, Series}

Alternative parameters to use. If not provided, the parameters computed by fitting the model are used. Must be 1-d and identical in shape to the parameters computed by fitting the model.

horizon : int, optional

Number of steps to forecast

step : int, optional

Non-negative number of forecasts to skip between spines

start : int, datetime or str, optional

An integer, datetime or str indicating the first observation to produce the forecast for. Datetimes can only be used with pandas inputs that have a datetime index. Strings must be convertible to a date time, such as in '1945-01-01'. If not provided, the start is set to the earliest forecastable date.

plot_type : {'volatility', 'mean'}

Quantity to plot, the forecast volatility or the forecast mean

method : {'analytic', 'simulation', 'bootstrap'}

Method to use when producing the forecast. The default is analytic. The method only affects the variance forecast generation. Not all volatility models support all methods. In

particular, volatility models that do not evolve in squares such as EGARCH or TARCH do not support the ‘analytic’ method for horizons > 1.

simulations : int

Number of simulations to run when computing the forecast using either simulation or bootstrap.

Returns

fig – Handle to the figure

Return type

figure

Examples

```
>>> import pandas as pd
>>> from arch import arch_model
>>> am = arch_model(None, mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> sim_data = am.simulate([0.1, 0.4, 0.3, 0.2, 1.0], 250)
>>> sim_data.index = pd.date_range('2000-01-01', periods=250)
>>> am = arch_model(sim_data['data'], mean='HAR', lags=[1, 5, 22], vol='Constant')
>>> res = am.fit()
>>> fig = res.hedgehog_plot(plot_type='mean')
```

arch.univariate.base.ARCHModelFixedResult.plot

ARCHModelFixedResult.plot(annualize=None, scale=None)

Plot standardized residuals and conditional volatility

Parameters

annualize : str, optional

String containing frequency of data that indicates plot should contain annualized volatility. Supported values are ‘D’ (daily), ‘W’ (weekly) and ‘M’ (monthly), which scale variance by 252, 52, and 12, respectively.

scale : float, optional

Value to use when scaling returns to annualize. If scale is provided, annualize is ignored and the value in scale is used.

Returns

fig – Handle to the figure

Return type

figure

Examples

```
>>> from arch import arch_model
>>> am = arch_model(None)
>>> sim_data = am.simulate([0.0, 0.01, 0.07, 0.92], 2520)
>>> am = arch_model(sim_data['data'])
>>> res = am.fit(update_freq=0, disp='off')
>>> fig = res.plot()
```

Produce a plot with annualized volatility

```
>>> fig = res.plot(annualize='D')
```

Override the usual scale of 252 to use 360 for an asset that trades most days of the year

```
>>> fig = res.plot(scale=360)
```

arch.univariate.base.ARCHModelFixedResult.summary

`ARCHModelFixedResult.summary()`

Constructs a summary of the results from a fit model.

Returns

summary – Object that contains tables and facilitated export to text, html or latex

Return type

Summary instance

Properties

<i>aic</i>	Akaike Information Criteria
<i>bic</i>	Schwarz/Bayesian Information Criteria
<i>conditional_volatility</i>	Estimated conditional volatility
<i>loglikelihood</i>	Model loglikelihood
<i>model</i>	Model instance used to produce the fit
<i>nobs</i>	Number of data points used to estimate model
<i>num_params</i>	Number of parameters in model
<i>params</i>	Model Parameters
<i>resid</i>	Model residuals
<i>std_resid</i>	Residuals standardized by conditional volatility

arch.univariate.base.ARCHModelFixedResult.aic

property `ARCHModelFixedResult.aic`: float

Akaike Information Criteria

$-2 * \text{loglikelihood} + 2 * \text{num_params}$

arch.univariate.base.ARCHModelFixedResult.bic

property ARCHModelFixedResult.bic : float
Schwarz/Bayesian Information Criteria
 $-2 * \text{loglikelihood} + \log(\text{nobs}) * \text{num_params}$

arch.univariate.base.ARCHModelFixedResult.conditional_volatility

property ARCHModelFixedResult.conditional_volatility : pandas.core.series.Series |
numpy.ndarray
Estimated conditional volatility

Returns

conditional_volatility – nobs element array containing the conditional volatility (square root of conditional variance). The values are aligned with the input data so that the value in the t-th position is the variance of t-th error, which is computed using time-(t-1) information.

Return type

{ndarray, Series}

arch.univariate.base.ARCHModelFixedResult.loglikelihood

property ARCHModelFixedResult.loglikelihood : float
Model loglikelihood

arch.univariate.base.ARCHModelFixedResult.model

property ARCHModelFixedResult.model : ARCHModel
Model instance used to produce the fit

arch.univariate.base.ARCHModelFixedResult.nobs

property ARCHModelFixedResult.nobs : int
Number of data points used to estimate model

arch.univariate.base.ARCHModelFixedResult.num_params

property ARCHModelFixedResult.num_params : int
Number of parameters in model

arch.univariate.base.ARCHModelFixedResult.params

property ARCHModelFixedResult.params : Series
Model Parameters

arch.univariate.base.ARCHModelFixedResult.resid

property ARCHModelFixedResult.resid : numpy.ndarray | pandas.core.series.Series
Model residuals

arch.univariate.base.ARCHModelFixedResult.std_resid

property ARCHModelFixedResult.std_resid : numpy.ndarray | pandas.core.series.Series
Residuals standardized by conditional volatility

1.13 Utilities

Utilities that do not fit well on other pages.

1.13.1 Test Results

class arch.utility.testing.WaldTestStatistic(stat, df, null, alternative, name='')
Test statistic holder for Wald-type tests

Parameters

stat : float
The test statistic

df : int
Degree of freedom.

null : str
A statement of the test's null hypothesis

alternative : str
A statement of the test's alternative hypothesis

name : str, default '' (empty)
Name of test

property critical_values : dict[str, float]
Critical values test for common test sizes

property null : str
Null hypothesis

Return type
str

property pval : float
P-value of test statistic

property **stat** : float

Test statistic

Return type

float

1.14 Theoretical Background

To be completed

BOOTSTRAPPING

The bootstrap module provides both high- and low-level interfaces for bootstrapping data contained in NumPy arrays or pandas Series or DataFrames.

All bootstraps have the same interfaces and only differ in their name, setup parameters and the (internally generated) sampling scheme.

2.1 Bootstrap Examples

This setup code is required to run in an IPython notebook

```
[1]: %matplotlib inline
import matplotlib.pyplot as plt
import seaborn

seaborn.set_style("darkgrid")
plt.rc("figure", figsize=(16, 6))
plt.rc("savefig", dpi=90)
plt.rc("font", family="sans-serif")
plt.rc("font", size=14)
```

2.1.1 Sharpe Ratio

The Sharpe Ratio is an important measure of return per unit of risk. The example shows how to estimate the variance of the Sharpe Ratio and how to construct confidence intervals for the Sharpe Ratio using a long series of U.S. equity data.

```
[2]: import arch.data.frenchdata
import numpy as np
import pandas as pd

ff = arch.data.frenchdata.load()
```

The data set contains the Fama-French factors, including the excess market return.

```
[3]: excess_market = ff.iloc[:, 0]
print(ff.describe())
```

	Mkt-RF	SMB	HML	RF
count	1109.000000	1109.000000	1109.000000	1109.000000
mean	0.659946	0.206555	0.368864	0.274220
std	5.327524	3.191132	3.482352	0.253377
min	-29.130000	-16.870000	-13.280000	-0.060000
25%	-1.970000	-1.560000	-1.320000	0.030000
50%	1.020000	0.070000	0.140000	0.230000
75%	3.610000	1.730000	1.740000	0.430000
max	38.850000	36.700000	35.460000	1.350000

The next step is to construct a function that computes the Sharpe Ratio. This function also return the annualized mean and annualized standard deviation which will allow the covariance matrix of these parameters to be estimated using the bootstrap.

```
[4]: def sharpe_ratio(x):
      mu, sigma = 12 * x.mean(), np.sqrt(12 * x.var())
      values = np.array([mu, sigma, mu / sigma]).squeeze()
      index = ["mu", "sigma", "SR"]
      return pd.Series(values, index=index)
```

The function can be called directly on the data to show full sample estimates.

```
[5]: params = sharpe_ratio(excess_market)
      params
[5]: mu      7.919351
      sigma  18.455084
      SR     0.429115
      dtype: float64
```

2.1.2 Reproducibility

All bootstraps accept the keyword argument `seed` which can contain a NumPy `Generator` or `RandomState` or an `int`. When using an `int`, the argument is passed `np.random.default_rng` to create the core generator. This allows the same pseudo random values to be used across multiple runs.

Warning

The bootstrap chosen must be appropriate for the data. Squared returns are serially correlated, and so a time-series bootstrap is required.

Bootstraps are initialized with any bootstrap specific parameters and the data to be used in the bootstrap. Here the 12 is the average window length in the Stationary Bootstrap, and the next input is the data to be bootstrapped.

```
[6]: from arch.bootstrap import StationaryBootstrap


      # Initialize with entropy from random.org
      entropy = [877788388, 418255226, 989657335, 69307515]
      seed = np.random.default_rng(entropy)

      bs = StationaryBootstrap(12, excess_market, seed=seed)
      results = bs.apply(sharpe_ratio, 2500)
```

(continues on next page)

(continued from previous page)

```
SR = pd.DataFrame(results[:, -1:], columns=["SR"])
fig = SR.hist(bins=40)
```



```
[7]: cov = bs.cov(sharpe_ratio, 1000)
cov = pd.DataFrame(cov, index=params.index, columns=params.index)
print(cov)
se = pd.Series(np.sqrt(np.diag(cov)), index=params.index)
se.name = "Std Errors"
print("\n")
print(se)
```

	mu	sigma	SR
mu	3.837196	-0.638431	0.224722
sigma	-0.638431	3.019569	-0.105762
SR	0.224722	-0.105762	0.014915

```
mu      1.958876
sigma   1.737691
SR       0.122126
Name: Std Errors, dtype: float64
```

```
[8]: ci = bs.conf_int(sharpe_ratio, 1000, method="basic")
ci = pd.DataFrame(ci, index=["Lower", "Upper"], columns=params.index)
print(ci)
```

	mu	sigma	SR
Lower	4.367662	14.780547	0.166759
Upper	11.958503	21.735752	0.659350

Alternative confidence intervals can be computed using a variety of methods. Setting `reuse=True` allows the previous bootstrap results to be used when constructing confidence intervals using alternative methods.

```
[9]: ci = bs.conf_int(sharpe_ratio, 1000, method="percentile", reuse=True)
ci = pd.DataFrame(ci, index=["Lower", "Upper"], columns=params.index)
print(ci)
```

	mu	sigma	SR
Lower	3.880198	15.174416	0.198880
Upper	11.471040	22.129620	0.691471

Optimal Block Length Estimation

The function `optimal_block_length` can be used to estimate the optimal block lengths for the Stationary and Circular bootstraps. Here we use the squared market return since the Sharpe ratio depends on the mean and the variance, and the autocorrelation in the squares is stronger than in the returns.

```
[10]: from arch.bootstrap import optimal_block_length
```

```
opt = optimal_block_length(excess_market**2)
print(opt)
```

	stationary	circular
Mkt-RF	47.766787	54.679322

We can repeat the analysis above using the estimated optimal block length. Here we see that the extremes appear to be slightly more extreme.

```
[11]: # Reinitialize using the same entropy
```


```
rs = np.random.default_rng(entropy)
```

```
bs = StationaryBootstrap(opt.loc["Mkt-RF", "stationary"], excess_market, seed=seed)
```

```
results = bs.apply(sharpe_ratio, 2500)
```

```
SR = pd.DataFrame(results[:, -1:], columns=["SR"])
```

```
fig = SR.hist(bins=40)
```



2.1.3 Probit (statsmodels)

The second example makes use of a Probit model from statsmodels. The demo data is university admissions data which contains a binary variable for being admitted, GRE score, GPA score and quartile rank. This data is downloaded from the internet and imported using pandas.

```
[12]: import arch.data.binary
```

```
binary = arch.data.binary.load()
binary = binary.dropna()
print(binary.describe())
```

	admit	gre	gpa	rank
count	400.000000	400.000000	400.000000	400.000000
mean	0.317500	587.700000	3.389900	2.48500
std	0.466087	115.516536	0.380567	0.94446
min	0.000000	220.000000	2.260000	1.00000
25%	0.000000	520.000000	3.130000	2.00000
50%	0.000000	580.000000	3.395000	2.00000
75%	1.000000	660.000000	3.670000	3.00000
max	1.000000	800.000000	4.000000	4.00000

Fitting the model directly

The first steps are to build the regressor and the dependent variable arrays. Then, using these arrays, the model can be estimated by calling `fit`

```
[13]: import statsmodels.api as sm
```

```
endog = binary[["admit"]]
exog = binary[["gre", "gpa"]]
const = pd.Series(np.ones(exog.shape[0]), index=endog.index)
const.name = "Const"
exog = pd.DataFrame([const, exog.gre, exog.gpa]).T
```

```
# Estimate the model
mod = sm.Probit(endog, exog)
fit = mod.fit(dis=0)
params = fit.params
print(params)
```

```
Const    -3.003536
gre         0.001643
gpa         0.454575
dtype: float64
```

The wrapper function

Most models in statsmodels are implemented as classes, require an explicit call to `fit` and return a class containing parameter estimates and other quantities. These classes cannot be directly used with the bootstrap methods. However, a simple wrapper can be written that takes the data as the only inputs and returns parameters estimated using a Statsmodel model.

```
[14]: def probit_wrap(endog, exog):
      return sm.Probit(endog, exog).fit(displ=0).params
```

A call to this function should return the same parameter values.

```
[15]: probit_wrap(endog, exog)
```

```
[15]: Const    -3.003536
      gre       0.001643
      gpa       0.454575
      dtype: float64
```

The wrapper can be directly used to estimate the parameter covariance or to construct confidence intervals.

```
[16]: from arch.bootstrap import IIDBootstrap

bs = IIDBootstrap(endog=endog, exog=exog)
cov = bs.cov(probit_wrap, 1000)
cov = pd.DataFrame(cov, index=exog.columns, columns=exog.columns)
print(cov)
```

```
          Const          gre          gpa
Const  0.397473 -6.641971e-05 -0.102525
gre    -0.000066  4.467596e-07 -0.000058
gpa    -0.102525 -5.815162e-05  0.039859
```

```
[17]: se = pd.Series(np.sqrt(np.diag(cov)), index=exog.columns)
      print(se)
      print("T-stats")
      print(params / se)
```

```
Const    0.630455
gre       0.000668
gpa       0.199647
dtype: float64
T-stats
Const   -4.764077
gre       2.457413
gpa       2.276894
dtype: float64
```

```
[18]: ci = bs.conf_int(probit_wrap, 1000, method="basic")
      ci = pd.DataFrame(ci, index=["Lower", "Upper"], columns=exog.columns)
      print(ci)
```

```
          Const          gre          gpa
Lower -4.214157  0.000360  0.005706
Upper -1.622607  0.002906  0.871725
```


Speeding things up

Starting values can be provided to `fit` which can save time finding starting values. Since the bootstrap parameter estimates should be close to the original sample estimates, the full sample estimated parameters are reasonable starting values. These can be passed using the `extra_kwargs` dictionary to a modified wrapper that will accept a keyword argument containing starting values.

```
[19]: def probit_wrap_start_params(endog, exog, start_params=None):
      return sm.Probit(endog, exog).fit(start_params=start_params, disp=0).params
```

```
[20]: bs.reset() # Reset to original state for comparability
      cov = bs.cov(
          probit_wrap_start_params, 1000, extra_kwargs={"start_params": params.values}
      )
      cov = pd.DataFrame(cov, index=exog.columns, columns=exog.columns)
      print(cov)
```

	Const	gre	gpa
Const	0.397473	-6.641971e-05	-0.102525
gre	-0.000066	4.467596e-07	-0.000058
gpa	-0.102525	-5.815162e-05	0.039859

2.1.4 Bootstrapping Uneven Length Samples

Independent samples of uneven length are common in experiment settings, e.g., A/B testing of a website. The `IIDBootstrap` allows for arbitrary dependence within an observation index and so cannot be naturally applied to these data sets. The `IndependentSamplesBootstrap` allows datasets with variables of different lengths to be sampled by exploiting the independence of the values to separately bootstrap each component. Below is an example showing how a confidence interval can be constructed for the difference in means of two groups.

```
[21]: from arch.bootstrap import IndependentSamplesBootstrap

def mean_diff(x, y):
    return x.mean() - y.mean()

rs = np.random.RandomState(0)
treatment = 0.2 + rs.standard_normal(200)
control = rs.standard_normal(800)

bs = IndependentSamplesBootstrap(treatment, control, seed=seed)
print(bs.conf_int(mean_diff, method="studentized"))

[[0.19450863]
 [0.49723719]]
```

2.2 Confidence Intervals

The confidence interval function allows three types of confidence intervals to be constructed:

- Nonparametric, which only resamples the data
- Semi-parametric, which use resampled residuals
- Parametric, which simulate residuals

Confidence intervals can then be computed using one of 6 methods:

- Basic (`basic`)
- Percentile (`percentile`)
- Studentized (`studentized`)
- Asymptotic using parameter covariance (`norm`, `var` or `cov`)
- Bias-corrected (`bc`, `bias-corrected` or `debiased`)
- Bias-corrected and accelerated (`bca`)

- *Setup*
- *Confidence Interval Types*
 - *Nonparametric Confidence Intervals*
 - *Semi-parametric Confidence Intervals*
 - *Parametric Confidence Intervals*
- *Confidence Interval Methods*
 - *Basic (`basic`)*
 - *Percentile (`percentile`)*
 - *Asymptotic Normal Approximation (`norm`, `cov` or `var`)*
 - *Studentized (`studentized`)*
 - *Bias-corrected (`bc`, `bias-corrected` or `debiased`)*
 - *Bias-corrected and accelerated (`bca`)*

2.2.1 Setup

All examples will construct confidence intervals for the Sharpe ratio of the S&P 500, which is the ratio of the annualized mean to the annualized standard deviation. The parameters will be the annualized mean, the annualized standard deviation and the Sharpe ratio.

The setup makes use of return data downloaded from Yahoo!

```
import datetime as dt

import pandas as pd
import pandas_datareader.data as web
```

(continues on next page)

(continued from previous page)

```

start = dt.datetime(1951, 1, 1)
end = dt.datetime(2014, 1, 1)
sp500 = web.DataReader('^GSPC', 'yahoo', start=start, end=end)
low = sp500.index.min()
high = sp500.index.max()
monthly_dates = pd.date_range(low, high, freq='M')
monthly = sp500.reindex(monthly_dates, method='ffill')
returns = 100 * monthly['Adj Close'].pct_change().dropna()

```

The main function used will return a 3-element array containing the parameters.

```

def sharpe_ratio(x):
    mu, sigma = 12 * x.mean(), np.sqrt(12 * x.var())
    return np.array([mu, sigma, mu / sigma])

```

Note

Functions must return 1-d NumPy arrays or Pandas Series.

2.2.2 Confidence Interval Types

Three types of confidence intervals can be computed. The simplest are non-parametric; these only make use of parameter estimates from both the original data as well as the resampled data. Semi-parametric mix the original data with a limited form of resampling, usually for residuals. Finally, parametric bootstrap confidence intervals make use of a parametric distribution to construct “as-if” exact confidence intervals.

Nonparametric Confidence Intervals

Non-parametric sampling is the simplest method to construct confidence intervals.

This example makes use of the percentile bootstrap which is conceptually the simplest method - it constructs many bootstrap replications and returns order statistics from these empirical distributions.

```

from arch.bootstrap import IIDBootstrap

bs = IIDBootstrap(returns)
ci = bs.conf_int(sharpe_ratio, 1000, method='percentile')

```

Note

While returns have little serial correlation, squared returns are highly persistent. The IID bootstrap is not a good choice here. Instead a time-series bootstrap with an appropriately chosen block size should be used.

Semi-parametric Confidence Intervals

See *Semiparametric Bootstraps*

Parametric Confidence Intervals

See *Parametric Bootstraps*

2.2.3 Confidence Interval Methods

Note

`conf_int` can construct two-sided, upper or lower (one-sided) confidence intervals. All examples use two-sided, 95% confidence intervals (the default). This can be modified using the keyword inputs `type` ('upper', 'lower' or 'two-sided') and `size`.

Basic (basic)

Basic confidence intervals construct many bootstrap replications $\hat{\theta}_b^*$ and then constructs the confidence interval as

$$\left[\hat{\theta} + \left(\hat{\theta} - \hat{\theta}_u^* \right), \hat{\theta} + \left(\hat{\theta} - \hat{\theta}_l^* \right) \right]$$

where $\hat{\theta}_l^*$ and $\hat{\theta}_u^*$ are the $\alpha/2$ and $1 - \alpha/2$ empirical quantiles of the bootstrap distribution. When θ is a vector, the empirical quantiles are computed element-by-element.

```
from arch.bootstrap import IIDBootstrap

bs = IIDBootstrap(returns)
ci = bs.conf_int(sharpe_ratio, 1000, method='basic')
```

Percentile (percentile)

The percentile method directly constructs confidence intervals from the empirical CDF of the bootstrap parameter estimates, $\hat{\theta}_b^*$. The confidence interval is then defined.

$$\left[\hat{\theta}_l^*, \hat{\theta}_u^* \right]$$

where $\hat{\theta}_l^*$ and $\hat{\theta}_u^*$ are the $\alpha/2$ and $1 - \alpha/2$ empirical quantiles of the bootstrap distribution.

```
from arch.bootstrap import IIDBootstrap

bs = IIDBootstrap(returns)
ci = bs.conf_int(sharpe_ratio, 1000, method='percentile')
```

Asymptotic Normal Approximation (norm, cov or var)

The asymptotic normal approximation method estimates the covariance of the parameters and then combines this with the usual quantiles from a normal distribution. The confidence interval is then

$$\left[\hat{\theta} + \hat{\sigma} \Phi^{-1}(\alpha/2), \hat{\theta} - \hat{\sigma} \Phi^{-1}(\alpha/2), \right]$$

where $\hat{\sigma}$ is the bootstrap estimate of the parameter standard error.

```
from arch.bootstrap import IIDBootstrap

bs = IIDBootstrap(returns)
ci = bs.conf_int(sharpe_ratio, 1000, method='norm')
```

Studentized (studentized)

The studentized bootstrap may be more accurate than some of the other methods. The studentized bootstrap makes use of either a standard error function, when parameter standard errors can be analytically computed, or a nested bootstrap, to bootstrap studentized versions of the original statistic. This can produce higher-order refinements in some circumstances.

The confidence interval is then

$$\left[\hat{\theta} + \hat{\sigma} \hat{G}^{-1}(\alpha/2), \hat{\theta} + \hat{\sigma} \hat{G}^{-1}(1 - \alpha/2), \right]$$

where \hat{G} is the estimated quantile function for the studentized data and where $\hat{\sigma}$ is a bootstrap estimate of the parameter standard error.

The version that uses a nested bootstrap is simple to implement although it can be slow since it requires B inner bootstraps of each of the B outer bootstraps.

```
from arch.bootstrap import IIDBootstrap

bs = IIDBootstrap(returns)
ci = bs.conf_int(sharpe_ratio, 1000, method='studentized')
```

In order to use the standard error function, it is necessary to estimate the standard error of the parameters. In this example, this can be done using a method-of-moments argument and the delta-method. A detailed description of the mathematical formula is beyond the intent of this document.

```
def sharpe_ratio_se(params, x):
    mu, sigma, sr = params
    y = 12 * x
    e1 = y - mu
    e2 = y ** 2.0 - sigma ** 2.0
    errors = np.vstack((e1, e2)).T
    t = errors.shape[0]
    vcv = errors.T.dot(errors) / t
    D = np.array([[1, 0],
                  [0, 0.5 * 1 / sigma],
                  [1.0 / sigma, - mu / (2.0 * sigma**3)]
                  ])
    avar = D.dot(vcv / t).dot(D.T)
    return np.sqrt(np.diag(avar))
```

The studentized bootstrap can then be implemented using the standard error function.

```
from arch.bootstrap import IIDBootstrap
bs = IIDBootstrap(returns)
ci = bs.conf_int(sharpe_ratio, 1000, method='studentized',
                 std_err_func=sharpe_ratio_se)
```

Note

Standard error functions must return a 1-d array with the same number of element as params.

Note

Standard error functions must match the patters `std_err_func(params, *args, **kwargs)` where `params` is an array of estimated parameters constructed using `*args` and `**kwargs`.

Bias-corrected (bc, bias-corrected or debiased)

The bias corrected bootstrap makes use of a bootstrap estimate of the bias to improve confidence intervals.

```
from arch.bootstrap import IIDBootstrap
bs = IIDBootstrap(returns)
ci = bs.conf_int(sharpe_ratio, 1000, method='bc')
```

The bias-corrected confidence interval is identical to the bias-corrected and accelerated where $a = 0$.

Bias-corrected and accelerated (bca)

Bias-corrected and accelerated confidence intervals make use of both a bootstrap bias estimate and a jackknife acceleration term. BCa intervals may offer higher-order accuracy if some conditions are satisfied. Bias-corrected confidence intervals are a special case of BCa intervals where the acceleration parameter is set to 0.

```
from arch.bootstrap import IIDBootstrap

bs = IIDBootstrap(returns)
ci = bs.conf_int(sharpe_ratio, 1000, method='bca')
```

The confidence interval is based on the empirical distribution of the bootstrap parameter estimates, $\hat{\theta}_b^*$, where the percentiles used are

$$\Phi \left(\Phi^{-1}(\hat{b}) + \frac{\Phi^{-1}(\hat{b}) + z_\alpha}{1 - \hat{a}(\Phi^{-1}(\hat{b}) + z_\alpha)} \right)$$

where z_α is the usual quantile from the normal distribution and \hat{b} is the empirical bias estimate,

$$\hat{b} = \# \left\{ \hat{\theta}_b^* < \hat{\theta} \right\} / B$$

\hat{a} is a skewness-like estimator using a leave-one-out jackknife.

2.3 Covariance Estimation

The bootstrap can be used to estimate parameter covariances in applications where analytical computation is challenging, or simply as an alternative to traditional estimators.

This example estimates the covariance of the mean, standard deviation and Sharpe ratio of the S&P 500 using Yahoo! Finance data.

```
import datetime as dt
import pandas as pd
import pandas_datareader.data as web

start = dt.datetime(1951, 1, 1)
end = dt.datetime(2014, 1, 1)
sp500 = web.DataReader('^GSPC', 'yahoo', start=start, end=end)
low = sp500.index.min()
high = sp500.index.max()
monthly_dates = pd.date_range(low, high, freq='M')
monthly = sp500.reindex(monthly_dates, method='ffill')
returns = 100 * monthly['Adj Close'].pct_change().dropna()
```

The function that returns the parameters.

```
def sharpe_ratio(r):
    mu = 12 * r.mean(0)
    sigma = np.sqrt(12 * r.var(0))
    sr = mu / sigma
    return np.array([mu, sigma, sr])
```

Like all applications of the bootstrap, it is important to choose a bootstrap that captures the dependence in the data. This example uses the stationary bootstrap with an average block size of 12.

```
import pandas as pd
from arch.bootstrap import StationaryBootstrap

bs = StationaryBootstrap(12, returns)
param_cov = bs.cov(sharpe_ratio)
index = ['mu', 'sigma', 'SR']
params = sharpe_ratio(returns)
params = pd.Series(params, index=index)
param_cov = pd.DataFrame(param_cov, index=index, columns=index)
```

The output is

```
>>> params
mu      8.148534
sigma   14.508540
SR       0.561637
dtype: float64

>>> param_cov
      mu      sigma      SR
mu  3.729435 -0.442891  0.273945
```

(continues on next page)

(continued from previous page)

```
sigma -0.442891  0.495087 -0.049454
SR      0.273945 -0.049454  0.020830
```

Note

The covariance estimator is centered using the average of the bootstrapped estimators. The original sample estimator can be used to center using the keyword argument `recenter=False`.

2.4 Low-level Interfaces

2.4.1 Constructing Parameter Estimates

The bootstrap method `apply` can be used to directly compute parameter estimates from a function and the bootstrapped data.

This example makes use of monthly S&P 500 data.

```
import datetime as dt

import pandas as pd
import pandas_datareader.data as web


start = dt.datetime(1951, 1, 1)
end = dt.datetime(2014, 1, 1)
sp500 = web.DataReader('^GSPC', 'yahoo', start=start, end=end)
low = sp500.index.min()
high = sp500.index.max()
monthly_dates = pd.date_range(low, high, freq='M')
monthly = sp500.reindex(monthly_dates, method='ffill')
returns = 100 * monthly['Adj Close'].pct_change().dropna()
```

The function will compute the Sharpe ratio – the (annualized) mean divided by the (annualized) standard deviation.

```
import numpy as np
def sharpe_ratio(x):
    return np.array([12 * x.mean() / np.sqrt(12 * x.var())])
```

The bootstrapped Sharpe ratios can be directly computed using `apply`.

```
import seaborn
from arch.bootstrap import IIDBootstrap
bs = IIDBootstrap(returns)
sharpe_ratios = bs.apply(sr, 1000)
sharpe_ratios = pd.DataFrame(sharpe_ratios, columns=['Sharpe Ratio'])
sharpe_ratios.hist(bins=20)
```

2.4.2 The Bootstrap Iterator

The lowest-level method to use a bootstrap is the iterator. This is used internally in all higher-level methods that estimate a function using multiple bootstrap replications. The iterator returns a two-element tuple where the first element contains all positional arguments (in the order input) passed when constructing the bootstrap instance, and the second contains the all keyword arguments passed when constructing the instance.

This example makes uses of simulated data to demonstrate how to use the bootstrap iterator.

```
import pandas as pd
import numpy as np

from arch.bootstrap import IIDBootstrap

x = np.random.randn(1000, 2)
y = pd.DataFrame(np.random.randn(1000, 3))
z = np.random.rand(1000, 10)
bs = IIDBootstrap(x, y=y, z=z)

for pos, kw in bs.bootstrap(1000):
    xstar = pos[0] # pos is always a tuple, even when a singleton
    ystar = kw['y'] # A dictionary
    zstar = kw['z'] # A dictionary
```

2.5 Semiparametric Bootstraps

Functions for semi-parametric bootstraps differ from those used in nonparametric bootstraps. At a minimum they must accept the keyword argument `params` which will contain the parameters estimated on the original (non-bootstrap) data. This keyword argument must be optional so that the function can be called without the keyword argument to estimate parameters. In most applications other inputs will also be needed to perform the semi-parametric step - these can be input using the `extra_kwargs` keyword input.

For simplicity, consider a semiparametric bootstrap of an OLS regression. The bootstrap step will combine the original parameter estimates and original regressors with bootstrapped residuals to construct a bootstrapped regressand. The bootstrap regressand and regressors can then be used to produce a bootstrapped parameter estimate.

The user-provided function must:

- Estimate the parameters when `params` is not provided
- Estimate residuals from bootstrapped data when `params` is provided to construct bootstrapped residuals, simulate the regressand, and then estimate the bootstrapped parameters

```
import numpy as np
def ols(y, x, params=None, x_orig=None):
    if params is None:
        return np.linalg.pinv(x).dot(y).ravel()

    # When params is not None
    # Bootstrap residuals
    resids = y - x.dot(params)
    # Simulated data
    y_star = x_orig.dot(params) + resids
    # Parameter estimates
    return np.linalg.pinv(x_orig).dot(y_star).ravel()
```

Note

The function should return a 1-dimensional array. `ravel` is used above to ensure that the parameters estimated are 1d.

This function can then be used to perform a semiparametric bootstrap

```
from arch.bootstrap import IIDBootstrap
x = np.random.randn(100, 3)
e = np.random.randn(100, 1)
b = np.arange(1, 4)[: , None]
y = x.dot(b) + e
bs = IIDBootstrap(y, x)
ci = bs.conf_int(ols, 1000, method='percentile',
                 sampling='semi', extra_kwargs={'x_orig': x})
```

2.5.1 Using partial instead of extra_kwargs

`functools.partial` can be used instead to provide a wrapper function which can then be used in the bootstrap. This example fixed the value of `x_orig` so that it is not necessary to use `extra_kwargs`.

```
from functools import partial
ols_partial = partial(ols, x_orig=x)
ci = bs.conf_int(ols_partial, 1000, sampling='semi')
```

2.5.2 Semiparametric Bootstrap (Alternative Method)

Since semiparametric bootstraps are effectively bootstrapping residuals, an alternative method can be used to conduct a semiparametric bootstrap. This requires passing both the data and the estimated residuals when initializing the bootstrap.

First, the function used must be account for this structure.

```
def ols_semi_v2(y, x, resids=None, params=None, x_orig=None):
    if params is None:
        return np.linalg.pinv(x).dot(y).ravel()

    # Simulated data if params provided
    y_star = x_orig.dot(params) + resids
    # Parameter estimates
    return np.linalg.pinv(x_orig).dot(y_star).ravel()
```

This version can then be used to *directly* implement a semiparametric bootstrap, although ultimately it is not meaningfully simpler than the previous method.

```
resids = y - x.dot(ols_semi_v2(y,x))
bs = IIDBootstrap(y, x, resids=resids)
bs.conf_int(ols_semi_v2, 1000, sampling='semi', extra_kwargs={'x_orig': x})
```

Note

This alternative method is more useful when computing residuals is relatively expensive when compared to simulating data or estimating parameters. These circumstances are rarely encountered in actual problems.

2.6 Parametric Bootstraps

Parametric bootstraps are meaningfully different from their nonparametric or semiparametric cousins. Instead of sampling the data to simulate the data (or residuals, in the case of a semiparametric bootstrap), a parametric bootstrap makes use of a fully parametric model to simulate data using a pseudo-random number generator.

Warning

Parametric bootstraps are model-based methods to construct exact confidence intervals through integration. Since these confidence intervals should be exact, bootstrap methods which make use of asymptotic normality are required (and may not be desirable).

Implementing a parametric bootstrap, like implementing a semi-parametric bootstrap, requires specific keyword arguments. The first is `params`, which, when present, will contain the parameters estimated on the original data. The second is `rng` which will contain the `numpy.random.RandomState` instance that is used by the bootstrap. This is provided to facilitate simulation in a reproducible manner.

A parametric bootstrap function must:

- Estimate the parameters when `params` is not provided
- Simulate data when `params` is provided and then estimate the bootstrapped parameters on the simulated data

This example continues the OLS example from the semiparametric example, only assuming that residuals are normally distributed. The variance estimator is the MLE.

```
def ols_para(y, x, params=None, state=None, x_orig=None):
    if params is None:
        beta = np.linalg.pinv(x).dot(y)
        e = y - x.dot(beta)
        sigma2 = e.T.dot(e) / e.shape[0]
        return np.r_[beta.ravel(), sigma2.ravel()]

    beta = params[:-1]
    sigma2 = params[-1]
    e = state.standard_normal(x_orig.shape[0])
    ystar = x_orig.dot(beta) + np.sqrt(sigma2) * e

    # Use the plain function to compute parameters
    return ols_para(ystar, x_orig)
```

This function can then be used to form parametric bootstrap confidence intervals.

```
bs = IIDBootstrap(y,x)
ci = bs.conf_int(ols_para, 1000, method='percentile',
                sampling='parametric', extra_kwargs={'x_orig': x})
```

Note

The parameter vector in this example includes the variance since this is required when specifying a complete model.

2.7 Independent, Identical Distributed Data (i.i.d.)

IIDBootstrap is the standard bootstrap that is appropriate for data that is either i.i.d. or at least not serially dependant.

<i>IIDBootstrap</i> (*args[, random_state, seed])	Bootstrap using uniform resampling
---	------------------------------------

2.7.1 arch.bootstrap.IIDBootstrap

class arch.bootstrap.IIDBootstrap(*args, random_state=None, seed=None, **kwargs)

Bootstrap using uniform resampling

Parameters

***args**

Positional arguments to bootstrap

seed : {Generator, RandomState, int}, optional

Seed to use to ensure reproducible results. If an int, passes the value to `np.random.default_rng`. If None, a fresh Generator is constructed with system-provided entropy.

random_state : RandomState, optional

RandomState to use to ensure reproducible results. Cannot be used with seed

Deprecated since version 5.0: The random_state keyword argument has been deprecated. Use seed instead.

****kwargs**

Keyword arguments to bootstrap

data

Two-element tuple with the pos_data in the first position and kw_data in the second (pos_data, kw_data)

Type

tuple

pos_data

Tuple containing the positional arguments (in the order entered)

Type

tuple

kw_data

Dictionary containing the keyword arguments

Type

dict

Notes

Supports numpy arrays and pandas Series and DataFrames. Data returned has the same type as the input data.

Data entered using keyword arguments is directly accessible as an attribute.

To ensure a reproducible bootstrap, you must set the `seed` attribute after the bootstrap has been created. See the example below. Note that `seed` is a reserved keyword and any variable passed using this keyword must be an integer, a Generator or a RandomState.

Examples

Data can be accessed in a number of ways. Positional data is retained in the same order as it was entered when the bootstrap was initialized. Keyword data is available both as an attribute or using a dictionary syntax on `kw_data`.

```
>>> from arch.bootstrap import IIDBootstrap
>>> from numpy.random import standard_normal
>>> y = standard_normal((500, 1))
>>> x = standard_normal((500, 2))
>>> z = standard_normal(500)
>>> bs = IIDBootstrap(x, y=y, z=z)
>>> for data in bs.bootstrap(100):
...     bs_x = data[0][0]
...     bs_y = data[1]['y']
...     bs_z = bs.z
```

Set the seed if reproducibility is required

```
>>> from numpy.random import default_rng
>>> seed = default_rng(1234)
>>> bs = IIDBootstrap(x, y=y, z=z, seed=seed)
```

This is equivalent to

```
>>> bs = IIDBootstrap(x, y=y, z=z, seed=1234)
```

See also

[*arch.bootstrap.IndependentSamplesBootstrap*](#)

Methods

<i>apply</i> (func[, reps, extra_kwargs])	Applies a function to bootstrap replicated data
<i>bootstrap</i> (reps)	Iterator for use when bootstrapping
<i>clone</i> (*args[, seed])	Clones the bootstrap using different data with a fresh prng.
<i>conf_int</i> (func[, reps, method, size, tail, ...])	
<div style="text-align: right;"> type func Callable[... , ndarray] </div>	
<i>cov</i> (func[, reps, recenter, extra_kwargs])	Compute parameter covariance using bootstrap
<i>get_state</i> ()	Gets the state of the bootstrap's random number generator
<i>reset</i> ([use_seed])	Resets the bootstrap to either its initial state or the last seed.
<i>seed</i> (value)	Reseeds the bootstrap's random number generator
<i>set_state</i> (state)	Sets the state of the bootstrap's random number generator
<i>update_indices</i> ()	Update indices for the next iteration of the bootstrap.
<i>var</i> (func[, reps, recenter, extra_kwargs])	Compute parameter variance using bootstrap

arch.bootstrap.IIDBootstrap.apply

`IIDBootstrap.apply(func, reps=1000, extra_kwargs=None)`

Applies a function to bootstrap replicated data

Parameters

func : callable

Function the computes parameter values. See Notes for requirements

reps : int, default 1000

Number of bootstrap replications

extra_kwargs : dict, default None

Extra keyword arguments to use when calling func. Must not conflict with keyword arguments used to initialize bootstrap

Returns

reps by nparam array of computed function values where each row corresponds to a bootstrap iteration

Return type

ndarray

Notes

When there are no extra keyword arguments, the function is called

```
func(params, *args, **kwargs)
```

where args and kwargs are the bootstrap version of the data provided when setting up the bootstrap. When extra keyword arguments are used, these are appended to kwargs before calling func

Examples

```
>>> import numpy as np
>>> x = np.random.randn(1000,2)
>>> from arch.bootstrap import IIDBootstrap
>>> bs = IIDBootstrap(x)
>>> def func(y):
...     return y.mean(0)
>>> results = bs.apply(func, 100)
```

arch.bootstrap.IIDBootstrap.bootstrap

`IIDBootstrap.bootstrap(reps)`

Iterator for use when bootstrapping

Parameters

reps : int

Number of bootstrap replications

Returns

Generator to iterate over in bootstrap calculations

Return type
generator

Examples

The key steps are problem dependent and so this example shows the use as an iterator that does not produce any output

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> bs = IIDBootstrap(np.arange(100), x=np.random.randn(100))
>>> for posdata, kwdata in bs.bootstrap(1000):
...     # Do something with the positional data and/or keyword data
...     pass
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

Notes

The iterator returns a tuple containing the data entered in positional arguments as a tuple and the data entered using keywords as a dictionary

arch.bootstrap.IIDBootstrap.clone

`IIDBootstrap.clone(*args, seed=None, **kwargs)`

Clones the bootstrap using different data with a fresh prng.

Parameters

***args**
Positional arguments to bootstrap

seed=None
The seed value to pass to the closed generator

****kwargs**
Keyword arguments to bootstrap

Returns

Bootstrap instance

Return type

bs

arch.bootstrap.IIDBootstrap.conf_int

```
IIDBootstrap.conf_int(func, reps=1000, method='basic', size=0.95, tail='two', extra_kwargs=None,
                      reuse=False, sampling='nonparametric', std_err_func=None,
                      studentize_reps=1000)
```

Parameters**func : callable**

Function the computes parameter values. See Notes for requirements

reps : int, default 1000

Number of bootstrap replications

method : str, default "basic"

One of 'basic', 'percentile', 'studentized', 'norm' (identical to 'var', 'cov'), 'bc' (identical to 'debiased', 'bias-corrected'), or 'bca'

size : float, default 0.95

Coverage of confidence interval

tail : str, default "two"

One of 'two', 'upper' or 'lower'.

reuse : bool, default False

Flag indicating whether to reuse previously computed bootstrap results. This allows alternative methods to be compared without rerunning the bootstrap simulation. Reuse is ignored if reps is not the same across multiple runs, func changes across calls, or method is 'studentized'.

sampling : str, default "nonparametric"

Type of sampling to use: 'nonparametric', 'semi-parametric' (or 'semi') or 'parametric'. The default is 'nonparametric'. See notes about the changes to func required when using 'semi' or 'parametric'.

extra_kwargs : dict, default None

Extra keyword arguments to use when calling func and std_err_func, when appropriate

std_err_func : callable, default None

Function to use when standardizing estimated parameters when using the studentized bootstrap. Providing an analytical function eliminates the need for a nested bootstrap

studentize_reps : int, default 1000

Number of bootstraps to use in the inner bootstrap when using the studentized bootstrap. Ignored when std_err_func is provided

Returns

Computed confidence interval. Row 0 contains the lower bounds, and row 1 contains the upper bounds. Each column corresponds to a parameter. When tail is 'lower', all upper bounds are inf. Similarly, 'upper' sets all lower bounds to -inf.

Return type

ndarray

Examples

```
>>> import numpy as np
>>> def func(x):
...     return x.mean(0)
>>> y = np.random.randn(1000, 2)
>>> from arch.bootstrap import IIDBootstrap
>>> bs = IIDBootstrap(y)
>>> ci = bs.conf_int(func, 1000)
```

Notes

When there are no extra keyword arguments, the function is called

```
func(*args, **kwargs)
```

where args and kwargs are the bootstrap version of the data provided when setting up the bootstrap. When extra keyword arguments are used, these are appended to kwargs before calling func.

The standard error function, if provided, must return a vector of parameter standard errors and is called

```
std_err_func(params, *args, **kwargs)
```

where params is the vector of estimated parameters using the same bootstrap data as in args and kwargs.

The bootstraps are:

- ‘basic’ - Basic confidence using the estimated parameter and difference between the estimated parameter and the bootstrap parameters
- ‘percentile’ - Direct use of bootstrap percentiles
- ‘norm’ - Makes use of normal approximation and bootstrap covariance estimator
- ‘studentized’ - Uses either a standard error function or a nested bootstrap to estimate percentiles and the bootstrap covariance for scale
- ‘bc’ - Bias corrected using estimate bootstrap bias correction
- ‘bca’ - Bias corrected and accelerated, adding acceleration parameter to ‘bc’ method

arch.bootstrap.IIDBootstrap.cov

```
IIDBootstrap.cov(func, reps=1000, recenter=True, extra_kwargs=None)
```

Compute parameter covariance using bootstrap

Parameters

func : callable

Callable function that returns the statistic of interest as a 1-d array

reps : int, default 1000

Number of bootstrap replications

recenter : bool, default True

Whether to center the bootstrap variance estimator on the average of the bootstrap samples (True) or to center on the original sample estimate (False). Default is True.

extra_kwargs : **dict**, default None

Dictionary of extra keyword arguments to pass to func

Returns

Bootstrap covariance estimator

Return type

ndarray

Notes

func must have the signature

```
func(params, *args, **kwargs)
```

where params are a 1-dimensional array, and **args* and ***kwargs* are data used in the the bootstrap. The first argument, params, will be none when called using the original data, and will contain the estimate computed using the original data in bootstrap replications. This parameter is passed to allow parametric bootstrap simulation.

Examples

Bootstrap covariance of the mean

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> def func(x):
...     return x.mean(axis=0)
>>> y = np.random.randn(1000, 3)
>>> bs = IIDBootstrap(y)
>>> cov = bs.cov(func, 1000)
```

Bootstrap covariance using a function that takes additional input

```
>>> def func(x, stat='mean'):
...     if stat=='mean':
...         return x.mean(axis=0)
...     elif stat=='var':
...         return x.var(axis=0)
>>> cov = bs.cov(func, 1000, extra_kwargs={'stat':'var'})
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

arch.bootstrap.IIDBootstrap.get_state**IIDBootstrap.get_state()**

Gets the state of the bootstrap's random number generator

Returns

Dictionary containing the state.

Return type`dict`**arch.bootstrap.IIDBootstrap.reset****IIDBootstrap.reset**(`use_seed=True`)

Resets the bootstrap to either its initial state or the last seed.

Parameters**use_seed** : `bool`, default `True`Flag indicating whether to use the last seed if provided. If `False` or if no seed has been set, the bootstrap will be reset to the initial state. Default is `True`**Return type**`None`**arch.bootstrap.IIDBootstrap.seed****IIDBootstrap.seed**(`value`)

Reseeds the bootstrap's random number generator

Parameters**value** : `{int, List[int], ndarray}`

Value to use as the seed.

Return type`None`**arch.bootstrap.IIDBootstrap.set_state****IIDBootstrap.set_state**(`state`)

Sets the state of the bootstrap's random number generator

Parameters**state** : `dict`

Dictionary or tuple containing the state.

Return type`None`

arch.bootstrap.IIDBootstrap.update_indices

`IIDBootstrap.update_indices()`

Update indices for the next iteration of the bootstrap. This must be overridden when creating new bootstraps.

Return type

`Union[ndarray, Tuple[ndarray, ...], Tuple[List[ndarray], Dict[str, ndarray]]]`

arch.bootstrap.IIDBootstrap.var

`IIDBootstrap.var(func, reps=1000, recenter=True, extra_kwargs=None)`

Compute parameter variance using bootstrap

Parameters

func : callable

Callable function that returns the statistic of interest as a 1-d array

reps : int, default 1000

Number of bootstrap replications

recenter : bool, default True

Whether to center the bootstrap variance estimator on the average of the bootstrap samples (True) or to center on the original sample estimate (False). Default is True.

extra_kwargs : dict, default None

Dictionary of extra keyword arguments to pass to func

Returns

Bootstrap variance estimator

Return type

ndarray

Notes

func must have the signature

```
func(params, *args, **kwargs)
```

where params are a 1-dimensional array, and **args* and ***kwargs* are data used in the the bootstrap. The first argument, params, will be none when called using the original data, and will contain the estimate computed using the original data in bootstrap replications. This parameter is passed to allow parametric bootstrap simulation.

Examples

Bootstrap covariance of the mean

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> def func(x):
...     return x.mean(axis=0)
>>> y = np.random.randn(1000, 3)
>>> bs = IIDBootstrap(y)
>>> variances = bs.var(func, 1000)
```

Bootstrap covariance using a function that takes additional input

```
>>> def func(x, stat='mean'):
...     if stat=='mean':
...         return x.mean(axis=0)
...     elif stat=='var':
...         return x.var(axis=0)
>>> variances = bs.var(func, 1000, extra_kwargs={'stat': 'var'})
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

Properties

<code>generator</code>	Set or get the instance PRNG
<code>index</code>	The current index of the bootstrap
<code>random_state</code>	Set or get the instance random state
<code>state</code>	Set or get the generator's state

arch.bootstrap.IIDBootstrap.generator

property IIDBootstrap.generator : `numpy.random._generator.Generator` | `numpy.random.mtrand.RandomState`

Set or get the instance PRNG

Parameters

seed : {Generator, RandomState}, optional

Generator or RandomState used to produce the pseudo-random values used in the bootstrap

Returns

The instance of the Generator or RandomState instance used by bootstrap

Return type

{Generator, RandomState}

arch.bootstrap.IIDBootstrap.index

property IIDBootstrap.index : `ndarray` | `tuple[ndarray, ...]` | `tuple[list[ndarray], dict[str, ndarray]]`

The current index of the bootstrap

Return type

`Union[ndarray, Tuple[ndarray, ...], Tuple[List[ndarray], Dict[str, ndarray]]]`

arch.bootstrap.IIDBootstrap.random_state

property IIDBootstrap.**random_state**: `numpy.random._generator.Generator` | `numpy.random.mtrand.RandomState`

Set or get the instance random state

Parameters

random_state : `RandomState`
RandomState instance used by bootstrap

Returns

RandomState instance used by bootstrap

Return type

RandomState

arch.bootstrap.IIDBootstrap.state

property IIDBootstrap.**state**: `tuple[str, ndarray, int, int, float]` | `Mapping[str, Any]`

Set or get the generator's state

Returns

A tuple or dictionary containing the generator's state. If using a RandomState, the value returned is a tuple. Otherwise it is a dictionary.

Return type

{tuple, dict}

2.8 Independent Samples

IndependentSamplesBootstrap is a bootstrap that is appropriate for data is totally independent, and where each variable may have a different sample size. This type of data arises naturally in experimental settings, e.g., website A/B testing.

<i>IndependentSamplesBootstrap</i> (*args[, ...])	Bootstrap where each input is independently resampled
---	---

2.8.1 arch.bootstrap.IndependentSamplesBootstrap

class arch.bootstrap.**IndependentSamplesBootstrap**(*args, random_state=`None`, seed=`None`, **kwargs)

Bootstrap where each input is independently resampled

Parameters

***args**
Positional arguments to bootstrap

****kwargs**
Keyword arguments to bootstrap

data

Two-element tuple with the pos_data in the first position and kw_data in the second (pos_data, kw_data)

Type

`tuple`

pos_data

Tuple containing the positional arguments (in the order entered)

Type

tuple

kw_data

Dictionary containing the keyword arguments

Type

dict

Notes

This bootstrap independently resamples each input and so is only appropriate when the inputs are independent. This structure allows bootstrapping statistics that depend on samples with unequal length, as is common in some experiments. If data have cross-sectional dependence, so that observation *i* is related across all inputs, this bootstrap is inappropriate.

Supports numpy arrays and pandas Series and DataFrames. Data returned has the same type as the input data.

Data entered using keyword arguments is directly accessible as an attribute.

To ensure a reproducible bootstrap, you must set the `random_state` attribute after the bootstrap has been created. See the example below. Note that `random_state` is a reserved keyword and any variable passed using this keyword must be an instance of `RandomState`.

Examples

Data can be accessed in a number of ways. Positional data is retained in the same order as it was entered when the bootstrap was initialized. Keyword data is available both as an attribute or using a dictionary syntax on `kw_data`.

```
>>> from arch.bootstrap import IndependentSamplesBootstrap
>>> from numpy.random import standard_normal
>>> y = standard_normal(500)
>>> x = standard_normal(200)
>>> z = standard_normal(2000)
>>> bs = IndependentSamplesBootstrap(x, y=y, z=z)
>>> for data in bs.bootstrap(100):
...     bs_x = data[0][0]
...     bs_y = data[1]['y']
...     bs_z = bs.z
```

Set the `random_state` if reproducibility is required

```
>>> from numpy.random import RandomState
>>> rs = RandomState(1234)
>>> bs = IndependentSamplesBootstrap(x, y=y, z=z, random_state=rs)
```

See also

[*arch.bootstrap.IIDBootstrap*](#)

Methods

<code>apply(func[, reps, extra_kwargs])</code>	Applies a function to bootstrap replicated data
<code>bootstrap(reps)</code>	Iterator for use when bootstrapping
<code>clone(*args[, seed])</code>	Clones the bootstrap using different data with a fresh prng.
<code>conf_int(func[, reps, method, size, tail, ...])</code>	
<div style="text-align: right;"> type func <code>Callable[... , ndarray]</code> </div>	
<code>cov(func[, reps, recenter, extra_kwargs])</code>	Compute parameter covariance using bootstrap
<code>get_state()</code>	Gets the state of the bootstrap's random number generator
<code>reset([use_seed])</code>	Resets the bootstrap to either its initial state or the last seed.
<code>seed(value)</code>	Reseeds the bootstrap's random number generator
<code>set_state(state)</code>	Sets the state of the bootstrap's random number generator
<code>update_indices()</code>	Update indices for the next iteration of the bootstrap.
<code>var(func[, reps, recenter, extra_kwargs])</code>	Compute parameter variance using bootstrap

arch.bootstrap.IndependentSamplesBootstrap.apply

IndependentSamplesBootstrap.**apply**(func, reps=**1000**, extra_kwargs=**None**)

Applies a function to bootstrap replicated data

Parameters

func : callable

Function the computes parameter values. See Notes for requirements

reps : int, default 1000

Number of bootstrap replications

extra_kwargs : dict, default None

Extra keyword arguments to use when calling func. Must not conflict with keyword arguments used to initialize bootstrap

Returns

reps by nparam array of computed function values where each row corresponds to a bootstrap iteration

Return type

ndarray

Notes

When there are no extra keyword arguments, the function is called

```
func(params, *args, **kwargs)
```

where args and kwargs are the bootstrap version of the data provided when setting up the bootstrap. When extra keyword arguments are used, these are appended to kwargs before calling func

Examples

```
>>> import numpy as np
>>> x = np.random.randn(1000,2)
>>> from arch.bootstrap import IIDBootstrap
>>> bs = IIDBootstrap(x)
>>> def func(y):
...     return y.mean(0)
>>> results = bs.apply(func, 100)
```

arch.bootstrap.IndependentSamplesBootstrap.bootstrap

IndependentSamplesBootstrap.bootstrap(*reps*)

Iterator for use when bootstrapping

Parameters

reps : int

Number of bootstrap replications

Returns

Generator to iterate over in bootstrap calculations

Return type

generator

Examples

The key steps are problem dependent and so this example shows the use as an iterator that does not produce any output

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> bs = IIDBootstrap(np.arange(100), x=np.random.randn(100))
>>> for posdata, kwdata in bs.bootstrap(1000):
...     # Do something with the positional data and/or keyword data
...     pass
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

Notes

The iterator returns a tuple containing the data entered in positional arguments as a tuple and the data entered using keywords as a dictionary

arch.bootstrap.IndependentSamplesBootstrap.clone

`IndependentSamplesBootstrap.clone(*args, seed=None, **kwargs)`

Clones the bootstrap using different data with a fresh prng.

Parameters

***args**

Positional arguments to bootstrap

seed=None

The seed value to pass to the closed generator

****kwargs**

Keyword arguments to bootstrap

Returns

Bootstrap instance

Return type

bs

arch.bootstrap.IndependentSamplesBootstrap.conf_int

`IndependentSamplesBootstrap.conf_int(func, reps=1000, method='basic', size=0.95, tail='two', extra_kwargs=None, reuse=False, sampling='nonparametric', std_err_func=None, studentize_reps=1000)`

Parameters

func : callable

Function the computes parameter values. See Notes for requirements

reps : int, default 1000

Number of bootstrap replications

method : str, default "basic"

One of 'basic', 'percentile', 'studentized', 'norm' (identical to 'var', 'cov'), 'bc' (identical to 'debiased', 'bias-corrected'), or 'bca'

size : float, default 0.95

Coverage of confidence interval

tail : str, default "two"

One of 'two', 'upper' or 'lower'.

reuse : bool, default False

Flag indicating whether to reuse previously computed bootstrap results. This allows alternative methods to be compared without rerunning the bootstrap simulation. Reuse is ignored if reps is not the same across multiple runs, func changes across calls, or method is 'studentized'.

sampling : **str**, default "nonparametric"

Type of sampling to use: 'nonparametric', 'semi-parametric' (or 'semi') or 'parametric'. The default is 'nonparametric'. See notes about the changes to func required when using 'semi' or 'parametric'.

extra_kwargs : **dict**, default None

Extra keyword arguments to use when calling func and std_err_func, when appropriate

std_err_func : **callable**, default None

Function to use when standardizing estimated parameters when using the studentized bootstrap. Providing an analytical function eliminates the need for a nested bootstrap

studentize_reps : **int**, default 1000

Number of bootstraps to use in the inner bootstrap when using the studentized bootstrap. Ignored when std_err_func is provided

Returns

Computed confidence interval. Row 0 contains the lower bounds, and row 1 contains the upper bounds. Each column corresponds to a parameter. When tail is 'lower', all upper bounds are inf. Similarly, 'upper' sets all lower bounds to -inf.

Return type

ndarray

Examples

```
>>> import numpy as np
>>> def func(x):
...     return x.mean(0)
>>> y = np.random.randn(1000, 2)
>>> from arch.bootstrap import IIDBootstrap
>>> bs = IIDBootstrap(y)
>>> ci = bs.conf_int(func, 1000)
```

Notes

When there are no extra keyword arguments, the function is called

```
func(*args, **kwargs)
```

where args and kwargs are the bootstrap version of the data provided when setting up the bootstrap. When extra keyword arguments are used, these are appended to kwargs before calling func.

The standard error function, if provided, must return a vector of parameter standard errors and is called

```
std_err_func(params, *args, **kwargs)
```

where params is the vector of estimated parameters using the same bootstrap data as in args and kwargs.

The bootstraps are:

- 'basic' - Basic confidence using the estimated parameter and difference between the estimated parameter and the bootstrap parameters
- 'percentile' - Direct use of bootstrap percentiles
- 'norm' - Makes use of normal approximation and bootstrap covariance estimator

- ‘studentized’ - Uses either a standard error function or a nested bootstrap to estimate percentiles and the bootstrap covariance for scale
- ‘bc’ - Bias corrected using estimate bootstrap bias correction
- ‘bca’ - Bias corrected and accelerated, adding acceleration parameter to ‘bc’ method

arch.bootstrap.IndependentSamplesBootstrap.cov

IndependentSamplesBootstrap.cov(func, reps=1000, recenter=True, extra_kwargs=None)

Compute parameter covariance using bootstrap

Parameters

func : callable

Callable function that returns the statistic of interest as a 1-d array

reps : int, default 1000

Number of bootstrap replications

recenter : bool, default True

Whether to center the bootstrap variance estimator on the average of the bootstrap samples (True) or to center on the original sample estimate (False). Default is True.

extra_kwargs : dict, default None

Dictionary of extra keyword arguments to pass to func

Returns

Bootstrap covariance estimator

Return type

ndarray

Notes

func must have the signature

```
func(params, *args, **kwargs)
```

where params are a 1-dimensional array, and *args and **kwargs are data used in the the bootstrap. The first argument, params, will be none when called using the original data, and will contain the estimate computed using the original data in bootstrap replications. This parameter is passed to allow parametric bootstrap simulation.

Examples

Bootstrap covariance of the mean

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> def func(x):
...     return x.mean(axis=0)
>>> y = np.random.randn(1000, 3)
>>> bs = IIDBootstrap(y)
>>> cov = bs.cov(func, 1000)
```

Bootstrap covariance using a function that takes additional input

```
>>> def func(x, stat='mean'):
...     if stat=='mean':
...         return x.mean(axis=0)
...     elif stat=='var':
...         return x.var(axis=0)
>>> cov = bs.cov(func, 1000, extra_kwargs={'stat':'var'})
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

arch.bootstrap.IndependentSamplesBootstrap.get_state

IndependentSamplesBootstrap.get_state()

Gets the state of the bootstrap's random number generator

Returns

Dictionary containing the state.

Return type

dict

arch.bootstrap.IndependentSamplesBootstrap.reset

IndependentSamplesBootstrap.reset(use_seed=True)

Resets the bootstrap to either its initial state or the last seed.

Parameters

use_seed : bool, default True

Flag indicating whether to use the last seed if provided. If False or if no seed has been set, the bootstrap will be reset to the initial state. Default is True

Return type

None

arch.bootstrap.IndependentSamplesBootstrap.seed

IndependentSamplesBootstrap.seed(value)

Reseeds the bootstrap's random number generator

Parameters

value : {int, List[int], ndarray}

Value to use as the seed.

Return type

None

arch.bootstrap.IndependentSamplesBootstrap.set_state

IndependentSamplesBootstrap.set_state(state)

Sets the state of the bootstrap's random number generator

Parameters

state : dict

Dictionary or tuple containing the state.

Return type

None

arch.bootstrap.IndependentSamplesBootstrap.update_indices

IndependentSamplesBootstrap.update_indices()

Update indices for the next iteration of the bootstrap. This must be overridden when creating new bootstraps.

Return type

tuple[list[ndarray], dict[str, ndarray]]

arch.bootstrap.IndependentSamplesBootstrap.var

IndependentSamplesBootstrap.var(func, reps=1000, recenter=True, extra_kwargs=None)

Compute parameter variance using bootstrap

Parameters

func : callable

Callable function that returns the statistic of interest as a 1-d array

reps : int, default 1000

Number of bootstrap replications

recenter : bool, default True

Whether to center the bootstrap variance estimator on the average of the bootstrap samples (True) or to center on the original sample estimate (False). Default is True.

extra_kwargs : dict, default None

Dictionary of extra keyword arguments to pass to func

Returns

Bootstrap variance estimator

Return type

ndarray

Notes

func must have the signature

```
func(params, *args, **kwargs)
```

where params are a 1-dimensional array, and **args* and ***kwargs* are data used in the the bootstrap. The first argument, params, will be none when called using the original data, and will contain the estimate computed using the original data in bootstrap replications. This parameter is passed to allow parametric bootstrap simulation.

Examples

Bootstrap covariance of the mean

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> def func(x):
...     return x.mean(axis=0)
>>> y = np.random.randn(1000, 3)
>>> bs = IIDBootstrap(y)
>>> variances = bs.var(func, 1000)
```

Bootstrap covariance using a function that takes additional input

```
>>> def func(x, stat='mean'):
...     if stat=='mean':
...         return x.mean(axis=0)
...     elif stat=='var':
...         return x.var(axis=0)
>>> variances = bs.var(func, 1000, extra_kwargs={'stat': 'var'})
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

Properties

<i>generator</i>	Set or get the instance PRNG
<i>index</i>	Returns the current index of the bootstrap
<i>random_state</i>	Set or get the instance random state
<i>state</i>	Set or get the generator's state

arch.bootstrap.IndependentSamplesBootstrap.generator

property IndependentSamplesBootstrap.generator : `numpy.random._generator.Generator` | `numpy.random.mtrand.RandomState`

Set or get the instance PRNG

Parameters

seed : {Generator, RandomState}, optional

Generator or RandomState used to produce the pseudo-random values used in the bootstrap

Returns

The instance of the Generator or RandomState instance used by bootstrap

Return type

{Generator, RandomState}

arch.bootstrap.IndependentSamplesBootstrap.index

property IndependentSamplesBootstrap.index : `ndarray` | `tuple[ndarray, ...]` | `tuple[list[ndarray], dict[str, ndarray]]`

Returns the current index of the bootstrap

Returns

2-element tuple containing a list and a dictionary. The list contains indices for each of the positional arguments. The dictionary contains the indices of keyword arguments.

Return type

`tuple[list[ndarray], dict[str, ndarray]]`

arch.bootstrap.IndependentSamplesBootstrap.random_state

property IndependentSamplesBootstrap.random_state : `numpy.random._generator.Generator` | `numpy.random.mtrand.RandomState`

Set or get the instance random state

Parameters

random_state : RandomState

RandomState instance used by bootstrap

Returns

RandomState instance used by bootstrap

Return type

RandomState

arch.bootstrap.IndependentSamplesBootstrap.state

property `IndependentSamplesBootstrap.state` : `tuple[str, ndarray, int, int, float] | Mapping[str, Any]`

Set or get the generator's state

Returns

A tuple or dictionary containing the generator's state. If using a `RandomState`, the value returned is a tuple. Otherwise it is a dictionary.

Return type

{tuple, dict}

2.9 Time-series Bootstraps

Bootstraps for time-series data come in a variety of forms. The three contained in this package are the stationary bootstrap (*StationaryBootstrap*), which uses blocks with an exponentially distributed lengths, the circular block bootstrap (*CircularBlockBootstrap*), which uses fixed length blocks, and the moving block bootstrap which also uses fixed length blocks (*MovingBlockBootstrap*). The moving block bootstrap does *not* wrap around and so observations near the start or end of the series will be systematically under-sampled. It is not recommended for this reason.

<i>StationaryBootstrap</i> (block_size, *args[, ...])	Politis and Romano (1994) bootstrap with expon distributed block sizes
<i>CircularBlockBootstrap</i> (block_size, *args[, ...])	Bootstrap using blocks of the same length with end-to-start wrap around
<i>MovingBlockBootstrap</i> (block_size, *args[, ...])	Bootstrap using blocks of the same length without wrap around
<i>optimal_block_length</i> (x)	Estimate optimal window length for time-series bootstraps

2.9.1 arch.bootstrap.StationaryBootstrap

class `arch.bootstrap.StationaryBootstrap`(block_size, *args, random_state=*None*, seed=*None*, **kwargs)

Politis and Romano (1994) bootstrap with expon distributed block sizes

Parameters

block_size : **int**

Average size of block to use

***args**

Positional arguments to bootstrap

seed : {{**Generator**, **RandomState**, **int**}}, optional

Seed to use to ensure reproducible results. If an int, passes the value to `np.random.default_rng`. If *None*, a fresh `Generator` is constructed with system-provided entropy.

random_state : **RandomState**, optional

`RandomState` to use to ensure reproducible results. Cannot be used with `seed`

Deprecated since version 5.0: The `random_state` keyword argument has been deprecated. Use `seed` instead.

****kwargs**

Keyword arguments to bootstrap

data

Two-element tuple with the pos_data in the first position and kw_data in the second (pos_data, kw_data)

Type

tuple

pos_data

Tuple containing the positional arguments (in the order entered)

Type

tuple

kw_data

Dictionary containing the keyword arguments

Type

dict

Notes

Supports numpy arrays and pandas Series and DataFrames. Data returned has the same type as the input data.

Data entered using keyword arguments is directly accessible as an attribute.

To ensure a reproducible bootstrap, you must set the `random_state` attribute after the bootstrap has been created. See the example below. Note that `random_state` is a reserved keyword and any variable passed using this keyword must be an instance of `RandomState`.

See also

[*arch.bootstrap.optimal_block_length*](#)

Optimal block length estimation

[*arch.bootstrap.CircularBlockBootstrap*](#)

Circular (wrap-around) bootstrap

Examples

Data can be accessed in a number of ways. Positional data is retained in the same order as it was entered when the bootstrap was initialized. Keyword data is available both as an attribute or using a dictionary syntax on `kw_data`.

```
>>> from arch.bootstrap import StationaryBootstrap
>>> from numpy.random import standard_normal
>>> y = standard_normal((500, 1))
>>> x = standard_normal((500, 2))
>>> z = standard_normal(500)
>>> bs = StationaryBootstrap(12, x, y=y, z=z)
>>> for data in bs.bootstrap(100):
...     bs_x = data[0][0]
...     bs_y = data[1]['y']
...     bs_z = bs.z
```

Set the `random_state` if reproducibility is required

```
>>> from numpy.random import RandomState
>>> rs = RandomState(1234)
>>> bs = StationaryBootstrap(12, x, y=y, z=z, random_state=rs)
```

Methods

<code>apply(func[, reps, extra_kwargs])</code>	Applies a function to bootstrap replicated data
<code>bootstrap(reps)</code>	Iterator for use when bootstrapping
<code>clone(*args[, seed])</code>	Clones the bootstrap using different data with a fresh prng.
<code>conf_int(func[, reps, method, size, tail, ...])</code>	<p>type func Callable[... , ndarray]</p>
<code>cov(func[, reps, recenter, extra_kwargs])</code>	Compute parameter covariance using bootstrap
<code>get_state()</code>	Gets the state of the bootstrap's random number generator
<code>reset([use_seed])</code>	Resets the bootstrap to either its initial state or the last seed.
<code>seed(value)</code>	Reseeds the bootstrap's random number generator
<code>set_state(state)</code>	Sets the state of the bootstrap's random number generator
<code>update_indices()</code>	Update indices for the next iteration of the bootstrap.
<code>var(func[, reps, recenter, extra_kwargs])</code>	Compute parameter variance using bootstrap

arch.bootstrap.StationaryBootstrap.apply

StationaryBootstrap.apply(func, reps=1000, extra_kwargs=None)

Applies a function to bootstrap replicated data

Parameters

func : callable

Function the computes parameter values. See Notes for requirements

reps : int, default 1000

Number of bootstrap replications

extra_kwargs : dict, default None

Extra keyword arguments to use when calling func. Must not conflict with keyword arguments used to initialize bootstrap

Returns

reps by nparam array of computed function values where each row corresponds to a bootstrap iteration

Return type

ndarray

Notes

When there are no extra keyword arguments, the function is called

```
func(params, *args, **kwargs)
```

where args and kwargs are the bootstrap version of the data provided when setting up the bootstrap. When extra keyword arguments are used, these are appended to kwargs before calling func

Examples

```
>>> import numpy as np
>>> x = np.random.randn(1000,2)
>>> from arch.bootstrap import IIDBootstrap
>>> bs = IIDBootstrap(x)
>>> def func(y):
...     return y.mean(0)
>>> results = bs.apply(func, 100)
```

arch.bootstrap.StationaryBootstrap.bootstrap

StationaryBootstrap.bootstrap(*reps*)

Iterator for use when bootstrapping

Parameters

reps : int
Number of bootstrap replications

Returns

Generator to iterate over in bootstrap calculations

Return type

generator

Examples

The key steps are problem dependent and so this example shows the use as an iterator that does not produce any output

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> bs = IIDBootstrap(np.arange(100), x=np.random.randn(100))
>>> for posdata, kwdata in bs.bootstrap(1000):
...     # Do something with the positional data and/or keyword data
...     pass
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

Notes

The iterator returns a tuple containing the data entered in positional arguments as a tuple and the data entered using keywords as a dictionary

`arch.bootstrap.StationaryBootstrap.clone`

`StationaryBootstrap.clone(*args, seed=None, **kwargs)`

Clones the bootstrap using different data with a fresh prng.

Parameters

***args**

Positional arguments to bootstrap

seed=None

The seed value to pass to the closed generator

****kwargs**

Keyword arguments to bootstrap

Returns

Bootstrap instance

Return type

bs

`arch.bootstrap.StationaryBootstrap.conf_int`

`StationaryBootstrap.conf_int(func, reps=1000, method='basic', size=0.95, tail='two',
extra_kwargs=None, reuse=False, sampling='nonparametric',
std_err_func=None, studentize_reps=1000)`

Parameters

func : callable

Function the computes parameter values. See Notes for requirements

reps : int, default 1000

Number of bootstrap replications

method : str, default "basic"

One of 'basic', 'percentile', 'studentized', 'norm' (identical to 'var', 'cov'), 'bc' (identical to 'debiased', 'bias-corrected'), or 'bca'

size : float, default 0.95

Coverage of confidence interval

tail : str, default "two"

One of 'two', 'upper' or 'lower'.

reuse : bool, default False

Flag indicating whether to reuse previously computed bootstrap results. This allows alternative methods to be compared without rerunning the bootstrap simulation. Reuse is ignored if reps is not the same across multiple runs, func changes across calls, or method is 'studentized'.

sampling : **str**, default "nonparametric"

Type of sampling to use: 'nonparametric', 'semi-parametric' (or 'semi') or 'parametric'. The default is 'nonparametric'. See notes about the changes to func required when using 'semi' or 'parametric'.

extra_kwargs : **dict**, default None

Extra keyword arguments to use when calling func and std_err_func, when appropriate

std_err_func : **callable**, default None

Function to use when standardizing estimated parameters when using the studentized bootstrap. Providing an analytical function eliminates the need for a nested bootstrap

studentize_reps : **int**, default 1000

Number of bootstraps to use in the inner bootstrap when using the studentized bootstrap. Ignored when std_err_func is provided

Returns

Computed confidence interval. Row 0 contains the lower bounds, and row 1 contains the upper bounds. Each column corresponds to a parameter. When tail is 'lower', all upper bounds are inf. Similarly, 'upper' sets all lower bounds to -inf.

Return type

ndarray

Examples

```
>>> import numpy as np
>>> def func(x):
...     return x.mean(0)
>>> y = np.random.randn(1000, 2)
>>> from arch.bootstrap import IIDBootstrap
>>> bs = IIDBootstrap(y)
>>> ci = bs.conf_int(func, 1000)
```

Notes

When there are no extra keyword arguments, the function is called

```
func(*args, **kwargs)
```

where args and kwargs are the bootstrap version of the data provided when setting up the bootstrap. When extra keyword arguments are used, these are appended to kwargs before calling func.

The standard error function, if provided, must return a vector of parameter standard errors and is called

```
std_err_func(params, *args, **kwargs)
```

where params is the vector of estimated parameters using the same bootstrap data as in args and kwargs.

The bootstraps are:

- 'basic' - Basic confidence using the estimated parameter and difference between the estimated parameter and the bootstrap parameters
- 'percentile' - Direct use of bootstrap percentiles
- 'norm' - Makes use of normal approximation and bootstrap covariance estimator

- ‘studentized’ - Uses either a standard error function or a nested bootstrap to estimate percentiles and the bootstrap covariance for scale
- ‘bc’ - Bias corrected using estimate bootstrap bias correction
- ‘bca’ - Bias corrected and accelerated, adding acceleration parameter to ‘bc’ method

arch.bootstrap.StationaryBootstrap.cov

StationaryBootstrap.cov(func, reps=1000, recenter=True, extra_kwargs=None)

Compute parameter covariance using bootstrap

Parameters

func : callable

Callable function that returns the statistic of interest as a 1-d array

reps : int, default 1000

Number of bootstrap replications

recenter : bool, default True

Whether to center the bootstrap variance estimator on the average of the bootstrap samples (True) or to center on the original sample estimate (False). Default is True.

extra_kwargs : dict, default None

Dictionary of extra keyword arguments to pass to func

Returns

Bootstrap covariance estimator

Return type

ndarray

Notes

func must have the signature

```
func(params, *args, **kwargs)
```

where params are a 1-dimensional array, and **args* and ***kwargs* are data used in the the bootstrap. The first argument, params, will be none when called using the original data, and will contain the estimate computed using the original data in bootstrap replications. This parameter is passed to allow parametric bootstrap simulation.

Examples

Bootstrap covariance of the mean

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> def func(x):
...     return x.mean(axis=0)
>>> y = np.random.randn(1000, 3)
>>> bs = IIDBootstrap(y)
>>> cov = bs.cov(func, 1000)
```

Bootstrap covariance using a function that takes additional input


```
>>> def func(x, stat='mean'):
...     if stat=='mean':
...         return x.mean(axis=0)
...     elif stat=='var':
...         return x.var(axis=0)
>>> cov = bs.cov(func, 1000, extra_kwargs={'stat':'var'})
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

arch.bootstrap.StationaryBootstrap.get_state

StationaryBootstrap.get_state()

Gets the state of the bootstrap's random number generator

Returns

Dictionary containing the state.

Return type

dict

arch.bootstrap.StationaryBootstrap.reset

StationaryBootstrap.reset(use_seed=True)

Resets the bootstrap to either its initial state or the last seed.

Parameters

use_seed : bool, default True

Flag indicating whether to use the last seed if provided. If False or if no seed has been set, the bootstrap will be reset to the initial state. Default is True

Return type

None

arch.bootstrap.StationaryBootstrap.seed

StationaryBootstrap.seed(value)

Reseeds the bootstrap's random number generator

Parameters

value : {int, List[int], ndarray}

Value to use as the seed.

Return type

None

arch.bootstrap.StationaryBootstrap.set_state

StationaryBootstrap.set_state(state)

Sets the state of the bootstrap's random number generator

Parameters

state : dict

Dictionary or tuple containing the state.

Return type

None

arch.bootstrap.StationaryBootstrap.update_indices

StationaryBootstrap.update_indices()

Update indices for the next iteration of the bootstrap. This must be overridden when creating new bootstraps.

Return type

ndarray

arch.bootstrap.StationaryBootstrap.var

StationaryBootstrap.var(func, reps=1000, recenter=True, extra_kwargs=None)

Compute parameter variance using bootstrap

Parameters

func : callable

Callable function that returns the statistic of interest as a 1-d array

reps : int, default 1000

Number of bootstrap replications

recenter : bool, default True

Whether to center the bootstrap variance estimator on the average of the bootstrap samples (True) or to center on the original sample estimate (False). Default is True.

extra_kwargs : dict, default None

Dictionary of extra keyword arguments to pass to func

Returns

Bootstrap variance estimator

Return type

ndarray

Notes

func must have the signature

```
func(params, *args, **kwargs)
```

where params are a 1-dimensional array, and **args* and ***kwargs* are data used in the the bootstrap. The first argument, params, will be none when called using the original data, and will contain the estimate computed using the original data in bootstrap replications. This parameter is passed to allow parametric bootstrap simulation.

Examples

Bootstrap covariance of the mean

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> def func(x):
...     return x.mean(axis=0)
>>> y = np.random.randn(1000, 3)
>>> bs = IIDBootstrap(y)
>>> variances = bs.var(func, 1000)
```

Bootstrap covariance using a function that takes additional input

```
>>> def func(x, stat='mean'):
...     if stat=='mean':
...         return x.mean(axis=0)
...     elif stat=='var':
...         return x.var(axis=0)
>>> variances = bs.var(func, 1000, extra_kwargs={'stat': 'var'})
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

Properties

<i>generator</i>	Set or get the instance PRNG
<i>index</i>	The current index of the bootstrap
<i>random_state</i>	Set or get the instance random state
<i>state</i>	Set or get the generator's state

arch.bootstrap.StationaryBootstrap.generator

property StationaryBootstrap.**generator** : `numpy.random._generator.Generator` | `numpy.random.mtrand.RandomState`

Set or get the instance PRNG

Parameters

seed : {**Generator**, **RandomState**}, optional

Generator or RandomState used to produce the pseudo-random values used in the bootstrap

Returns

The instance of the Generator or RandomState instance used by bootstrap

Return type

{Generator, RandomState}

arch.bootstrap.StationaryBootstrap.index

property StationaryBootstrap.**index** : `ndarray` | `tuple[ndarray, ...]` | `tuple[list[ndarray], dict[str, ndarray]]`

The current index of the bootstrap

Return type

`Union[ndarray, Tuple[ndarray, ...], Tuple[List[ndarray], Dict[str, ndarray]]]`

arch.bootstrap.StationaryBootstrap.random_state

property StationaryBootstrap.**random_state** : `numpy.random._generator.Generator` | `numpy.random.mtrand.RandomState`

Set or get the instance random state

Parameters

random_state : **RandomState**

RandomState instance used by bootstrap

Returns

RandomState instance used by bootstrap

Return type

RandomState

arch.bootstrap.StationaryBootstrap.state

property StationaryBootstrap.**state** : `tuple[str, ndarray, int, int, float]` | `Mapping[str, Any]`

Set or get the generator's state

Returns

A tuple or dictionary containing the generator's state. If using a RandomState, the value returned is a tuple. Otherwise it is a dictionary.

Return type

{tuple, dict}

2.9.2 arch.bootstrap.CircularBlockBootstrap

```
class arch.bootstrap.CircularBlockBootstrap(block_size, *args, random_state=None, seed=None,
                                           **kwargs)
```

Bootstrap using blocks of the same length with end-to-start wrap around

Parameters

block_size : int

Size of block to use

***args**

Positional arguments to bootstrap

seed : {Generator, RandomState, int}, optional

Seed to use to ensure reproducible results. If an int, passes the value to `np.random.default_rng`. If None, a fresh Generator is constructed with system-provided entropy.

random_state : RandomState, optional

RandomState to use to ensure reproducible results. Cannot be used with seed

Deprecated since version 5.0: The random_state keyword argument has been deprecated. Use seed instead.

****kwargs**

Keyword arguments to bootstrap

data

Two-element tuple with the pos_data in the first position and kw_data in the second (pos_data, kw_data)

Type

tuple

pos_data

Tuple containing the positional arguments (in the order entered)

Type

tuple

kw_data

Dictionary containing the keyword arguments

Type

dict

Notes

Supports numpy arrays and pandas Series and DataFrames. Data returned has the same type as the input data.

Data entered using keyword arguments is directly accessible as an attribute.

To ensure a reproducible bootstrap, you must set the `random_state` attribute after the bootstrap has been created. See the example below. Note that `random_state` is a reserved keyword and any variable passed using this keyword must be an instance of `RandomState`.

See also

[`arch.bootstrap.optimal_block_length`](#)

Optimal block length estimation

arch.bootstrap.StationaryBootstrap

Politis and Romano's bootstrap with exp. distributed block lengths

Examples

Data can be accessed in a number of ways. Positional data is retained in the same order as it was entered when the bootstrap was initialized. Keyword data is available both as an attribute or using a dictionary syntax on `kw_data`.

```
>>> from arch.bootstrap import CircularBlockBootstrap
>>> from numpy.random import standard_normal
>>> y = standard_normal((500, 1))
>>> x = standard_normal((500, 2))
>>> z = standard_normal(500)
>>> bs = CircularBlockBootstrap(17, x, y=y, z=z)
>>> for data in bs.bootstrap(100):
...     bs_x = data[0][0]
...     bs_y = data[1]['y']
...     bs_z = bs.z
```

Set the `random_state` if reproducibility is required

```
>>> from numpy.random import RandomState
>>> rs = RandomState(1234)
>>> bs = CircularBlockBootstrap(17, x, y=y, z=z, random_state=rs)
```

Methods

<i>apply</i> (func[, reps, extra_kwargs])	Applies a function to bootstrap replicated data
<i>bootstrap</i> (reps)	Iterator for use when bootstrapping
<i>clone</i> (*args[, seed])	Clones the bootstrap using different data with a fresh prng.
<i>conf_int</i> (func[, reps, method, size, tail, ...])	
<div style="text-align: right;"> type func Callable[..., ndarray] </div>	
<i>cov</i> (func[, reps, recenter, extra_kwargs])	Compute parameter covariance using bootstrap
<i>get_state</i> ()	Gets the state of the bootstrap's random number generator
<i>reset</i> ([use_seed])	Resets the bootstrap to either its initial state or the last seed.
<i>seed</i> (value)	Reseeds the bootstrap's random number generator
<i>set_state</i> (state)	Sets the state of the bootstrap's random number generator
<i>update_indices</i> ()	Update indices for the next iteration of the bootstrap.
<i>var</i> (func[, reps, recenter, extra_kwargs])	Compute parameter variance using bootstrap

arch.bootstrap.CircularBlockBootstrap.apply

CircularBlockBootstrap.**apply**(func, reps=**1000**, extra_kwargs=**None**)

Applies a function to bootstrap replicated data

Parameters

func : callable

Function the computes parameter values. See Notes for requirements

reps : int, default 1000

Number of bootstrap replications

extra_kwargs : dict, default None

Extra keyword arguments to use when calling func. Must not conflict with keyword arguments used to initialize bootstrap

Returns

reps by nparam array of computed function values where each row corresponds to a bootstrap iteration

Return type

ndarray

Notes

When there are no extra keyword arguments, the function is called

```
func(params, *args, **kwargs)
```

where args and kwargs are the bootstrap version of the data provided when setting up the bootstrap. When extra keyword arguments are used, these are appended to kwargs before calling func

Examples

```
>>> import numpy as np
>>> x = np.random.randn(1000,2)
>>> from arch.bootstrap import IIDBootstrap
>>> bs = IIDBootstrap(x)
>>> def func(y):
...     return y.mean(0)
>>> results = bs.apply(func, 100)
```

arch.bootstrap.CircularBlockBootstrap.bootstrap

CircularBlockBootstrap.**bootstrap**(reps)

Iterator for use when bootstrapping

Parameters

reps : int

Number of bootstrap replications

Returns

Generator to iterate over in bootstrap calculations

Return type
generator

Examples

The key steps are problem dependent and so this example shows the use as an iterator that does not produce any output

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> bs = IIDBootstrap(np.arange(100), x=np.random.randn(100))
>>> for posdata, kwdata in bs.bootstrap(1000):
...     # Do something with the positional data and/or keyword data
...     pass
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

Notes

The iterator returns a tuple containing the data entered in positional arguments as a tuple and the data entered using keywords as a dictionary

arch.bootstrap.CircularBlockBootstrap.clone

`CircularBlockBootstrap.clone(*args, seed=None, **kwargs)`

Clones the bootstrap using different data with a fresh prng.

Parameters

***args**
Positional arguments to bootstrap

seed=None
The seed value to pass to the closed generator

****kwargs**
Keyword arguments to bootstrap

Returns

Bootstrap instance

Return type

bs

arch.bootstrap.CircularBlockBootstrap.conf_int

```
CircularBlockBootstrap.conf_int(func, reps=1000, method='basic', size=0.95, tail='two',
                                extra_kwargs=None, reuse=False, sampling='nonparametric',
                                std_err_func=None, studentize_reps=1000)
```

Parameters**func : callable**

Function the computes parameter values. See Notes for requirements

reps : int, default 1000

Number of bootstrap replications

method : str, default "basic"

One of 'basic', 'percentile', 'studentized', 'norm' (identical to 'var', 'cov'), 'bc' (identical to 'debiased', 'bias-corrected'), or 'bca'

size : float, default 0.95

Coverage of confidence interval

tail : str, default "two"

One of 'two', 'upper' or 'lower'.

reuse : bool, default False

Flag indicating whether to reuse previously computed bootstrap results. This allows alternative methods to be compared without rerunning the bootstrap simulation. Reuse is ignored if reps is not the same across multiple runs, func changes across calls, or method is 'studentized'.

sampling : str, default "nonparametric"

Type of sampling to use: 'nonparametric', 'semi-parametric' (or 'semi') or 'parametric'. The default is 'nonparametric'. See notes about the changes to func required when using 'semi' or 'parametric'.

extra_kwargs : dict, default None

Extra keyword arguments to use when calling func and std_err_func, when appropriate

std_err_func : callable, default None

Function to use when standardizing estimated parameters when using the studentized bootstrap. Providing an analytical function eliminates the need for a nested bootstrap

studentize_reps : int, default 1000

Number of bootstraps to use in the inner bootstrap when using the studentized bootstrap. Ignored when std_err_func is provided

Returns

Computed confidence interval. Row 0 contains the lower bounds, and row 1 contains the upper bounds. Each column corresponds to a parameter. When tail is 'lower', all upper bounds are inf. Similarly, 'upper' sets all lower bounds to -inf.

Return type

ndarray

Examples

```
>>> import numpy as np
>>> def func(x):
...     return x.mean(0)
>>> y = np.random.randn(1000, 2)
>>> from arch.bootstrap import IIDBootstrap
>>> bs = IIDBootstrap(y)
>>> ci = bs.conf_int(func, 1000)
```

Notes

When there are no extra keyword arguments, the function is called

```
func(*args, **kwargs)
```

where args and kwargs are the bootstrap version of the data provided when setting up the bootstrap. When extra keyword arguments are used, these are appended to kwargs before calling func.

The standard error function, if provided, must return a vector of parameter standard errors and is called

```
std_err_func(params, *args, **kwargs)
```

where params is the vector of estimated parameters using the same bootstrap data as in args and kwargs.

The bootstraps are:

- ‘basic’ - Basic confidence using the estimated parameter and difference between the estimated parameter and the bootstrap parameters
- ‘percentile’ - Direct use of bootstrap percentiles
- ‘norm’ - Makes use of normal approximation and bootstrap covariance estimator
- ‘studentized’ - Uses either a standard error function or a nested bootstrap to estimate percentiles and the bootstrap covariance for scale
- ‘bc’ - Bias corrected using estimate bootstrap bias correction
- ‘bca’ - Bias corrected and accelerated, adding acceleration parameter to ‘bc’ method

arch.bootstrap.CircularBlockBootstrap.cov

CircularBlockBootstrap.cov(func, reps=1000, recenter=True, extra_kwargs=None)

Compute parameter covariance using bootstrap

Parameters

func : callable

Callable function that returns the statistic of interest as a 1-d array

reps : int, default 1000

Number of bootstrap replications

recenter : bool, default True

Whether to center the bootstrap variance estimator on the average of the bootstrap samples (True) or to center on the original sample estimate (False). Default is True.

extra_kwargs : **dict**, default **None**

Dictionary of extra keyword arguments to pass to func

Returns

Bootstrap covariance estimator

Return type

ndarray

Notes

func must have the signature

```
func(params, *args, **kwargs)
```

where params are a 1-dimensional array, and **args* and ***kwargs* are data used in the the bootstrap. The first argument, params, will be none when called using the original data, and will contain the estimate computed using the original data in bootstrap replications. This parameter is passed to allow parametric bootstrap simulation.

Examples

Bootstrap covariance of the mean

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> def func(x):
...     return x.mean(axis=0)
>>> y = np.random.randn(1000, 3)
>>> bs = IIDBootstrap(y)
>>> cov = bs.cov(func, 1000)
```

Bootstrap covariance using a function that takes additional input

```
>>> def func(x, stat='mean'):
...     if stat=='mean':
...         return x.mean(axis=0)
...     elif stat=='var':
...         return x.var(axis=0)
>>> cov = bs.cov(func, 1000, extra_kwargs={'stat':'var'})
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

arch.bootstrap.CircularBlockBootstrap.get_state

`CircularBlockBootstrap.get_state()`

Gets the state of the bootstrap's random number generator

Returns

Dictionary containing the state.

Return type

`dict`

arch.bootstrap.CircularBlockBootstrap.reset

`CircularBlockBootstrap.reset(use_seed=True)`

Resets the bootstrap to either its initial state or the last seed.

Parameters

use_seed : `bool`, default `True`

Flag indicating whether to use the last seed if provided. If `False` or if no seed has been set, the bootstrap will be reset to the initial state. Default is `True`

Return type

`None`

arch.bootstrap.CircularBlockBootstrap.seed

`CircularBlockBootstrap.seed(value)`

Reseeds the bootstrap's random number generator

Parameters

value : `{int, List[int], ndarray}`

Value to use as the seed.

Return type

`None`

arch.bootstrap.CircularBlockBootstrap.set_state

`CircularBlockBootstrap.set_state(state)`

Sets the state of the bootstrap's random number generator

Parameters

state : `dict`

Dictionary or tuple containing the state.

Return type

`None`

arch.bootstrap.CircularBlockBootstrap.update_indices**CircularBlockBootstrap.update_indices()**

Update indices for the next iteration of the bootstrap. This must be overridden when creating new bootstraps.

Return type

ndarray

arch.bootstrap.CircularBlockBootstrap.var**CircularBlockBootstrap.var**(func, reps=**1000**, recenter=**True**, extra_kwargs=**None**)

Compute parameter variance using bootstrap

Parameters**func** : callable

Callable function that returns the statistic of interest as a 1-d array

reps : int, default 1000

Number of bootstrap replications

recenter : bool, default True

Whether to center the bootstrap variance estimator on the average of the bootstrap samples (True) or to center on the original sample estimate (False). Default is True.

extra_kwargs : dict, default None

Dictionary of extra keyword arguments to pass to func

Returns

Bootstrap variance estimator

Return type

ndarray

Notes

func must have the signature

```
func(params, *args, **kwargs)
```

where params are a 1-dimensional array, and **args* and ***kwargs* are data used in the the bootstrap. The first argument, params, will be none when called using the original data, and will contain the estimate computed using the original data in bootstrap replications. This parameter is passed to allow parametric bootstrap simulation.

Examples

Bootstrap covariance of the mean

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> def func(x):
...     return x.mean(axis=0)
>>> y = np.random.randn(1000, 3)
>>> bs = IIDBootstrap(y)
>>> variances = bs.var(func, 1000)
```

Bootstrap covariance using a function that takes additional input

```
>>> def func(x, stat='mean'):
...     if stat=='mean':
...         return x.mean(axis=0)
...     elif stat=='var':
...         return x.var(axis=0)
>>> variances = bs.var(func, 1000, extra_kwargs={'stat': 'var'})
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

Properties

<i>generator</i>	Set or get the instance PRNG
<i>index</i>	The current index of the bootstrap
<i>random_state</i>	Set or get the instance random state
<i>state</i>	Set or get the generator's state

arch.bootstrap.CircularBlockBootstrap.generator

property CircularBlockBootstrap.generator : `numpy.random._generator.Generator` | `numpy.random.mtrand.RandomState`

Set or get the instance PRNG

Parameters

seed : {Generator, RandomState}, optional

Generator or RandomState used to produce the pseudo-random values used in the bootstrap

Returns

The instance of the Generator or RandomState instance used by bootstrap

Return type

{Generator, RandomState}

arch.bootstrap.CircularBlockBootstrap.index

property CircularBlockBootstrap.index : `ndarray` | `tuple[ndarray, ...]` | `tuple[list[ndarray], dict[str, ndarray]]`

The current index of the bootstrap

Return type

`Union[ndarray, Tuple[ndarray, ...], Tuple[List[ndarray], Dict[str, ndarray]]]`

arch.bootstrap.CircularBlockBootstrap.random_state

property CircularBlockBootstrap.random_state : `numpy.random._generator.Generator` | `numpy.random.mtrand.RandomState`

Set or get the instance random state

Parameters

random_state : `RandomState`
RandomState instance used by bootstrap

Returns

RandomState instance used by bootstrap

Return type

RandomState

arch.bootstrap.CircularBlockBootstrap.state

property CircularBlockBootstrap.state : `tuple[str, ndarray, int, int, float]` | `Mapping[str, Any]`

Set or get the generator's state

Returns

A tuple or dictionary containing the generator's state. If using a RandomState, the value returned is a tuple. Otherwise it is a dictionary.

Return type

{tuple, dict}

2.9.3 arch.bootstrap.MovingBlockBootstrap

class arch.bootstrap.MovingBlockBootstrap(block_size, *args, random_state=None, seed=None, **kwargs)

Bootstrap using blocks of the same length without wrap around

Parameters

block_size : `int`
Size of block to use

***args**
Positional arguments to bootstrap

seed : `{{Generator, RandomState, int}}`, optional
Seed to use to ensure reproducible results. If an int, passes the value to `np.random.default_rng`. If None, a fresh Generator is constructed with system-provided entropy.

random_state : `RandomState`, optional
RandomState to use to ensure reproducible results. Cannot be used with seed
Deprecated since version 5.0: The random_state keyword argument has been deprecated. Use seed instead.

****kwargs**
Keyword arguments to bootstrap

data

Two-element tuple with the pos_data in the first position and kw_data in the second (pos_data, kw_data)

Type

tuple

pos_data

Tuple containing the positional arguments (in the order entered)

Type

tuple

kw_data

Dictionary containing the keyword arguments

Type

dict

Notes

Supports numpy arrays and pandas Series and DataFrames. Data returned has the same type as the input data.

Data entered using keyword arguments is directly accessible as an attribute.

To ensure a reproducible bootstrap, you must set the random_state attribute after the bootstrap has been created. See the example below. Note that random_state is a reserved keyword and any variable passed using this keyword must be an instance of RandomState.

See also

[*arch.bootstrap.optimal_block_length*](#)

Optimal block length estimation

[*arch.bootstrap.StationaryBootstrap*](#)

Politis and Romano's bootstrap with exp. distributed block lengths

[*arch.bootstrap.CircularBlockBootstrap*](#)

Circular (wrap-around) bootstrap

Examples

Data can be accessed in a number of ways. Positional data is retained in the same order as it was entered when the bootstrap was initialized. Keyword data is available both as an attribute or using a dictionary syntax on kw_data.

```
>>> from arch.bootstrap import MovingBlockBootstrap
>>> from numpy.random import standard_normal
>>> y = standard_normal((500, 1))
>>> x = standard_normal((500, 2))
>>> z = standard_normal(500)
>>> bs = MovingBlockBootstrap(7, x, y=y, z=z)
>>> for data in bs.bootstrap(100):
...     bs_x = data[0][0]
...     bs_y = data[1]['y']
...     bs_z = bs.z
```

Set the random_state if reproducibility is required


```
>>> from numpy.random import RandomState
>>> rs = RandomState(1234)
>>> bs = MovingBlockBootstrap(7, x, y=y, z=z, random_state=rs)
```

Methods

<code>apply(func[, reps, extra_kwargs])</code>	Applies a function to bootstrap replicated data
<code>bootstrap(reps)</code>	Iterator for use when bootstrapping
<code>clone(*args[, seed])</code>	Clones the bootstrap using different data with a fresh prng.
<code>conf_int(func[, reps, method, size, tail, ...])</code>	<p>type func Callable[..., ndarray]</p>
<code>cov(func[, reps, recenter, extra_kwargs])</code>	Compute parameter covariance using bootstrap
<code>get_state()</code>	Gets the state of the bootstrap's random number generator
<code>reset([use_seed])</code>	Resets the bootstrap to either its initial state or the last seed.
<code>seed(value)</code>	Reseeds the bootstrap's random number generator
<code>set_state(state)</code>	Sets the state of the bootstrap's random number generator
<code>update_indices()</code>	Update indices for the next iteration of the bootstrap.
<code>var(func[, reps, recenter, extra_kwargs])</code>	Compute parameter variance using bootstrap

arch.bootstrap.MovingBlockBootstrap.apply

MovingBlockBootstrap.**apply**(func, reps=1000, extra_kwargs=None)

Applies a function to bootstrap replicated data

Parameters

func : callable

Function the computes parameter values. See Notes for requirements

reps : int, default 1000

Number of bootstrap replications

extra_kwargs : dict, default None

Extra keyword arguments to use when calling func. Must not conflict with keyword arguments used to initialize bootstrap

Returns

reps by nparam array of computed function values where each row corresponds to a bootstrap iteration

Return type

ndarray

Notes

When there are no extra keyword arguments, the function is called

```
func(params, *args, **kwargs)
```

where args and kwargs are the bootstrap version of the data provided when setting up the bootstrap. When extra keyword arguments are used, these are appended to kwargs before calling func

Examples

```
>>> import numpy as np
>>> x = np.random.randn(1000,2)
>>> from arch.bootstrap import IIDBootstrap
>>> bs = IIDBootstrap(x)
>>> def func(y):
...     return y.mean(0)
>>> results = bs.apply(func, 100)
```

arch.bootstrap.MovingBlockBootstrap.bootstrap

MovingBlockBootstrap.bootstrap(*reps*)

Iterator for use when bootstrapping

Parameters

reps : int

Number of bootstrap replications

Returns

Generator to iterate over in bootstrap calculations

Return type

generator

Examples

The key steps are problem dependent and so this example shows the use as an iterator that does not produce any output

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> bs = IIDBootstrap(np.arange(100), x=np.random.randn(100))
>>> for posdata, kwdata in bs.bootstrap(1000):
...     # Do something with the positional data and/or keyword data
...     pass
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

Notes

The iterator returns a tuple containing the data entered in positional arguments as a tuple and the data entered using keywords as a dictionary

arch.bootstrap.MovingBlockBootstrap.clone

`MovingBlockBootstrap.clone(*args, seed=None, **kwargs)`

Clones the bootstrap using different data with a fresh prng.

Parameters

***args**

Positional arguments to bootstrap

seed=None

The seed value to pass to the closed generator

****kwargs**

Keyword arguments to bootstrap

Returns

Bootstrap instance

Return type

bs

arch.bootstrap.MovingBlockBootstrap.conf_int

`MovingBlockBootstrap.conf_int(func, reps=1000, method='basic', size=0.95, tail='two', extra_kwargs=None, reuse=False, sampling='nonparametric', std_err_func=None, studentize_reps=1000)`

Parameters

func : callable

Function the computes parameter values. See Notes for requirements

reps : int, default 1000

Number of bootstrap replications

method : str, default "basic"

One of 'basic', 'percentile', 'studentized', 'norm' (identical to 'var', 'cov'), 'bc' (identical to 'debiased', 'bias-corrected'), or 'bca'

size : float, default 0.95

Coverage of confidence interval

tail : str, default "two"

One of 'two', 'upper' or 'lower'.

reuse : bool, default False

Flag indicating whether to reuse previously computed bootstrap results. This allows alternative methods to be compared without rerunning the bootstrap simulation. Reuse is ignored if reps is not the same across multiple runs, func changes across calls, or method is 'studentized'.

sampling : **str**, default "nonparametric"

Type of sampling to use: 'nonparametric', 'semi-parametric' (or 'semi') or 'parametric'. The default is 'nonparametric'. See notes about the changes to func required when using 'semi' or 'parametric'.

extra_kwargs : **dict**, default None

Extra keyword arguments to use when calling func and std_err_func, when appropriate

std_err_func : **callable**, default None

Function to use when standardizing estimated parameters when using the studentized bootstrap. Providing an analytical function eliminates the need for a nested bootstrap

studentize_reps : **int**, default 1000

Number of bootstraps to use in the inner bootstrap when using the studentized bootstrap. Ignored when std_err_func is provided

Returns

Computed confidence interval. Row 0 contains the lower bounds, and row 1 contains the upper bounds. Each column corresponds to a parameter. When tail is 'lower', all upper bounds are inf. Similarly, 'upper' sets all lower bounds to -inf.

Return type

ndarray

Examples

```
>>> import numpy as np
>>> def func(x):
...     return x.mean(0)
>>> y = np.random.randn(1000, 2)
>>> from arch.bootstrap import IIDBootstrap
>>> bs = IIDBootstrap(y)
>>> ci = bs.conf_int(func, 1000)
```

Notes

When there are no extra keyword arguments, the function is called

```
func(*args, **kwargs)
```

where args and kwargs are the bootstrap version of the data provided when setting up the bootstrap. When extra keyword arguments are used, these are appended to kwargs before calling func.

The standard error function, if provided, must return a vector of parameter standard errors and is called

```
std_err_func(params, *args, **kwargs)
```

where params is the vector of estimated parameters using the same bootstrap data as in args and kwargs.

The bootstraps are:

- 'basic' - Basic confidence using the estimated parameter and difference between the estimated parameter and the bootstrap parameters
- 'percentile' - Direct use of bootstrap percentiles
- 'norm' - Makes use of normal approximation and bootstrap covariance estimator

- ‘studentized’ - Uses either a standard error function or a nested bootstrap to estimate percentiles and the bootstrap covariance for scale
- ‘bc’ - Bias corrected using estimate bootstrap bias correction
- ‘bca’ - Bias corrected and accelerated, adding acceleration parameter to ‘bc’ method

arch.bootstrap.MovingBlockBootstrap.cov

MovingBlockBootstrap.cov(func, reps=1000, recenter=True, extra_kwargs=None)

Compute parameter covariance using bootstrap

Parameters

func : callable

Callable function that returns the statistic of interest as a 1-d array

reps : int, default 1000

Number of bootstrap replications

recenter : bool, default True

Whether to center the bootstrap variance estimator on the average of the bootstrap samples (True) or to center on the original sample estimate (False). Default is True.

extra_kwargs : dict, default None

Dictionary of extra keyword arguments to pass to func

Returns

Bootstrap covariance estimator

Return type

ndarray

Notes

func must have the signature

```
func(params, *args, **kwargs)
```

where params are a 1-dimensional array, and **args* and ***kwargs* are data used in the the bootstrap. The first argument, params, will be none when called using the original data, and will contain the estimate computed using the original data in bootstrap replications. This parameter is passed to allow parametric bootstrap simulation.

Examples

Bootstrap covariance of the mean

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> def func(x):
...     return x.mean(axis=0)
>>> y = np.random.randn(1000, 3)
>>> bs = IIDBootstrap(y)
>>> cov = bs.cov(func, 1000)
```

Bootstrap covariance using a function that takes additional input

```
>>> def func(x, stat='mean'):
...     if stat=='mean':
...         return x.mean(axis=0)
...     elif stat=='var':
...         return x.var(axis=0)
>>> cov = bs.cov(func, 1000, extra_kwargs={'stat':'var'})
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

arch.bootstrap.MovingBlockBootstrap.get_state

MovingBlockBootstrap.get_state()

Gets the state of the bootstrap's random number generator

Returns

Dictionary containing the state.

Return type

`dict`

arch.bootstrap.MovingBlockBootstrap.reset

MovingBlockBootstrap.reset(*use_seed=True*)

Resets the bootstrap to either its initial state or the last seed.

Parameters

use_seed : `bool`, default `True`

Flag indicating whether to use the last seed if provided. If `False` or if no seed has been set, the bootstrap will be reset to the initial state. Default is `True`

Return type

`None`

arch.bootstrap.MovingBlockBootstrap.seed

MovingBlockBootstrap.seed(*value*)

Reseeds the bootstrap's random number generator

Parameters

value : `{int, List[int], ndarray}`

Value to use as the seed.

Return type

`None`

arch.bootstrap.MovingBlockBootstrap.set_state**MovingBlockBootstrap.set_state**(state)

Sets the state of the bootstrap's random number generator

Parameters**state** : dict

Dictionary or tuple containing the state.

Return type

None

arch.bootstrap.MovingBlockBootstrap.update_indices**MovingBlockBootstrap.update_indices**()

Update indices for the next iteration of the bootstrap. This must be overridden when creating new bootstraps.

Return type

ndarray

arch.bootstrap.MovingBlockBootstrap.var**MovingBlockBootstrap.var**(func, reps=1000, recenter=True, extra_kwargs=None)

Compute parameter variance using bootstrap

Parameters**func** : callable

Callable function that returns the statistic of interest as a 1-d array

reps : int, default 1000

Number of bootstrap replications

recenter : bool, default True

Whether to center the bootstrap variance estimator on the average of the bootstrap samples (True) or to center on the original sample estimate (False). Default is True.

extra_kwargs : dict, default None

Dictionary of extra keyword arguments to pass to func

Returns

Bootstrap variance estimator

Return type

ndarray

Notes

func must have the signature

```
func(params, *args, **kwargs)
```

where params are a 1-dimensional array, and **args* and ***kwargs* are data used in the the bootstrap. The first argument, params, will be none when called using the original data, and will contain the estimate computed using the original data in bootstrap replications. This parameter is passed to allow parametric bootstrap simulation.

Examples

Bootstrap covariance of the mean

```
>>> from arch.bootstrap import IIDBootstrap
>>> import numpy as np
>>> def func(x):
...     return x.mean(axis=0)
>>> y = np.random.randn(1000, 3)
>>> bs = IIDBootstrap(y)
>>> variances = bs.var(func, 1000)
```

Bootstrap covariance using a function that takes additional input

```
>>> def func(x, stat='mean'):
...     if stat=='mean':
...         return x.mean(axis=0)
...     elif stat=='var':
...         return x.var(axis=0)
>>> variances = bs.var(func, 1000, extra_kwargs={'stat': 'var'})
```

Note

Note this is a generic example and so the class used should be the name of the required bootstrap

Properties

<i>generator</i>	Set or get the instance PRNG
<i>index</i>	The current index of the bootstrap
<i>random_state</i>	Set or get the instance random state
<i>state</i>	Set or get the generator's state

arch.bootstrap.MovingBlockBootstrap.generator

property MovingBlockBootstrap.**generator** : `numpy.random._generator.Generator` | `numpy.random.mtrand.RandomState`

Set or get the instance PRNG

Parameters

seed : {**Generator**, **RandomState**}, optional

Generator or RandomState used to produce the pseudo-random values used in the bootstrap

Returns

The instance of the Generator or RandomState instance used by bootstrap

Return type

{Generator, RandomState}

arch.bootstrap.MovingBlockBootstrap.index

property MovingBlockBootstrap.**index** : `ndarray` | `tuple[ndarray, ...]` | `tuple[list[ndarray], dict[str, ndarray]]`

The current index of the bootstrap

Return type

`Union[ndarray, Tuple[ndarray, ...], Tuple[List[ndarray], Dict[str, ndarray]]]`

arch.bootstrap.MovingBlockBootstrap.random_state

property MovingBlockBootstrap.**random_state** : `numpy.random._generator.Generator` | `numpy.random.mtrand.RandomState`

Set or get the instance random state

Parameters

random_state : **RandomState**

RandomState instance used by bootstrap

Returns

RandomState instance used by bootstrap

Return type

RandomState

arch.bootstrap.MovingBlockBootstrap.state

property MovingBlockBootstrap.**state** : `tuple[str, ndarray, int, int, float]` | `Mapping[str, Any]`

Set or get the generator's state

Returns

A tuple or dictionary containing the generator's state. If using a RandomState, the value returned is a tuple. Otherwise it is a dictionary.

Return type

{tuple, dict}

2.9.4 arch.bootstrap.optimal_block_length

`arch.bootstrap.optimal_block_length(x)`

Estimate optimal window length for time-series bootstraps

Parameters

x : array_like

A one-dimensional or two-dimensional array-like. Operates columns by column if 2-dimensional.

Returns

A DataFrame with two columns `b_sb`, the estimated optimal block size for the Stationary Bootstrap and `b_cb`, the estimated optimal block size for the circular bootstrap.

Return type

DataFrame

See also

[`arch.bootstrap.StationaryBootstrap`](#)

Politis and Romano's bootstrap with exp. distributed block lengths

[`arch.bootstrap.CircularBlockBootstrap`](#)

Circular (wrap-around) bootstrap

Notes

Algorithm described in ⁽¹⁾ its correction ⁽²⁾ depends on a tuning parameter m , which is chosen as the first value where k_n consecutive autocorrelations of x are all inside a conservative band of $\pm 2\sqrt{\log_{10}(n)/n}$ where n is the sample size. The maximum value of m is set to $\lceil \sqrt{n} + k_n \rceil$ where $k_n = \max(5, \log_{10}(n))$. The block length is then computed as

$$b_i^{OPT} = \left(\frac{2g^2}{d_i} n \right)^{\frac{1}{3}}$$

where

$$\begin{aligned} g &= \sum_{k=-m}^m h\left(\frac{k}{m}\right) |k| \hat{\gamma}_k \\ h(x) &= \min(1, 2(1 - |x|)) \\ d_i &= c_i (\hat{\sigma}^2)^2 \\ \hat{\sigma}^2 &= \sum_{k=-m}^m h\left(\frac{k}{m}\right) \hat{\gamma}_k \\ \hat{\gamma}_i &= n^{-1} \sum_{k=i+1}^n (x_k - \bar{x})(x_{k-i} - \bar{x}) \end{aligned}$$

and the two remaining constants c_i are 2 for the Stationary bootstrap and 4/3 for the Circular bootstrap.

¹ Dimitris N. Politis & Halbert White (2004) Automatic Block-Length Selection for the Dependent Bootstrap, *Econometric Reviews*, 23:1, 53-70, DOI: 10.1081/ETC-120028836.

² Andrew Patton, Dimitris N. Politis & Halbert White (2009) Correction to "Automatic Block-Length Selection for the Dependent Bootstrap" by D. Politis and H. White, *Econometric Reviews*, 28:4, 372-375, DOI: 10.1080/07474930802459016.

Some of the tuning parameters are taken from Andrew Patton's MATLAB program that computes the optimal block length. The block lengths do not match this implementation since the autocovariances and autocorrelations are all computed using the maximum sample length rather than a common sampling length.

References

2.10 References

The bootstrap is a large area with a number of high-quality books. Leading references include

References

Articles used in the creation of this module include

MULTIPLE COMPARISON PROCEDURES

This module contains a set of bootstrap-based multiple comparison procedures. These are designed to allow multiple models to be compared while controlling a the [Familywise Error Rate](#), which is similar to the size of a test.

3.1 Multiple Comparisons

This setup code is required to run in an IPython notebook

```
[1]: %matplotlib inline
import matplotlib.pyplot as plt
import seaborn

seaborn.set_style("darkgrid")
plt.rc("figure", figsize=(16, 6))
plt.rc("savefig", dpi=90)
plt.rc("font", family="sans-serif")
plt.rc("font", size=14)
```

```
[2]: # Reproducibility
import numpy as np

gen = np.random.default_rng(23456)
# Common seed used throughout
seed = gen.integers(0, 2**31 - 1)
```

The multiple comparison procedures all allow for examining aspects of superior predictive ability. There are three available:

- SPA - The test of Superior Predictive Ability, also known as the Reality Check (and accessible as `RealityCheck`) or the bootstrap data snooper, examines whether any model in a set of models can outperform a benchmark.
- StepM - The stepwise multiple testing procedure uses sequential testing to determine which models are superior to a benchmark.
- MCS - The model confidence set which computes the set of models which with performance indistinguishable from others in the set.

All procedures take **losses** as inputs. That is, smaller values are preferred to larger values. This is common when evaluating forecasting models where the loss function is usually defined as a positive function of the forecast error that is increasing in the absolute error. Leading examples are Mean Square Error (MSE) and Mean Absolute Deviation (MAD).

3.1.1 The test of Superior Predictive Ability (SPA)

This procedure requires a t -element array of benchmark losses and a t by k -element array of model losses. The null hypothesis is that no model is better than the benchmark, or

$$H_0 : \max_i E[L_i] \geq E[L_{bm}]$$

where L_i is the loss from model i and L_{bm} is the loss from the benchmark model.

This procedure is normally used when there are many competing forecasting models such as in the study of technical trading rules. The example below will make use of a set of models which are all equivalently good to a benchmark model and will serve as a *size study*.

Study Design

The study will make use of a measurement error in predictors to produce a large set of correlated variables that all have equal expected MSE. The benchmark will have identical measurement error and so all models have the same expected loss, although will have different forecasts.

The first block computed the series to be forecast.

```
[3]: import statsmodels.api as sm
      from numpy.random import randn

      t = 1000
      factors = randn(t, 3)
      beta = np.array([1, 0.5, 0.1])
      e = randn(t)
      y = factors.dot(beta)
```

The next block computes the benchmark factors and the model factors by contaminating the original factors with noise. The models are estimated on the first 500 observations and predictions are made for the second 500. Finally, losses are constructed from these predictions.

```
[4]: # Measurement noise
      bm_factors = factors + randn(t, 3)
      # Fit using first half, predict second half
      bm_beta = sm.OLS(y[:500], bm_factors[:500]).fit().params
      # MSE loss
      bm_losses = (y[500:] - bm_factors[500:].dot(bm_beta)) ** 2.0
      # Number of models
      k = 500
      model_factors = np.zeros((k, t, 3))
      model_losses = np.zeros((500, k))
      for i in range(k):
          # Add measurement noise
          model_factors[i] = factors + randn(1000, 3)
          # Compute regression parameters
          model_beta = sm.OLS(y[:500], model_factors[i, :500]).fit().params
          # Prediction and losses
          model_losses[:, i] = (y[500:] - model_factors[i, 500:].dot(model_beta)) ** 2.0
```

Finally the SPA can be used. The SPA requires the **losses** from the benchmark and the models as inputs. Other inputs allow the bootstrap seed to be changed or for various options regarding studentization of the losses. `compute` does the real work, and then `pvalues` contains the probability that the null is true given the realizations.

In this case, one would not reject. The three p-values correspond to different re-centerings of the losses. In general, the consistent p-value should be used. It should always be the case that

$$lower \leq consistent \leq upper.$$

See the original papers for more details.

```
[5]: from arch.bootstrap import SPA

spa = SPA(bm_losses, model_losses, seed=seed)
spa.compute()
spa.pvalues
```

```
[5]: lower          0.005
consistent        0.005
upper            0.005
dtype: float64
```

The same blocks can be repeated to perform a simulation study. Here I only use 100 replications since this should complete in a reasonable amount of time. Also I set `reps=250` to limit the number of bootstrap replications in each application of the SPA (the default is a more reasonable 1000).

```
[6]: # Save the pvalues
pvalues = []
b = 100
seeds = gen.integers(0, 2**31 - 1, b)
# Repeat 100 times
for j in range(b):
    if j % 10 == 0:
        print(j)
    factors = randn(t, 3)
    beta = np.array([1, 0.5, 0.1])
    e = randn(t)
    y = factors.dot(beta)


    # Measurement noise
    bm_factors = factors + randn(t, 3)
    # Fit using first half, predict second half
    bm_beta = sm.OLS(y[:500], bm_factors[:500]).fit().params
    # MSE loss
    bm_losses = (y[500:] - bm_factors[500:].dot(bm_beta)) ** 2.0
    # Number of models
    k = 500
    model_factors = np.zeros((k, t, 3))
    model_losses = np.zeros((500, k))
    for i in range(k):
        model_factors[i] = factors + randn(1000, 3)
        model_beta = sm.OLS(y[:500], model_factors[i, :500]).fit().params
        # MSE loss
        model_losses[:, i] = (y[500:] - model_factors[i, 500:].dot(model_beta)) ** 2.0
    # Lower the bootstrap replications to 250
    spa = SPA(bm_losses, model_losses, reps=250, seed=seeds[j])
    spa.compute()
    pvalues.append(spa.pvalues)
```

```
0
10
20
30
40
50
60
70
80
90
```

Finally the pvalues can be plotted. Ideally they should form a 45° line indicating the size is correct. Both the consistent and upper perform well. The lower has too many small p-values.

```
[7]: import pandas as pd

pvalues = pd.DataFrame(pvalues)
for col in pvalues:
    values = pvalues[col].values
    values.sort()
    pvalues[col] = values
# Change the index so that the x-values are between 0 and 1
pvalues.index = np.linspace(0.005, 0.995, 100)
fig = pvalues.plot()
```



Power

The SPA also has power to reject then the null is violated. The simulation will be modified so that the amount of measurement error differs across models, and so that some models are actually better than the benchmark. The p-values should be small indicating rejection of the null.

```
[8]: # Number of models
k = 500
model_factors = np.zeros((k, t, 3))
model_losses = np.zeros((500, k))
for i in range(k):
```

(continues on next page)

(continued from previous page)

```

scale = (2500.0 - i) / 2500.0
model_factors[i] = factors + scale * randn(1000, 3)
model_beta = sm.OLS(y[:500], model_factors[i, :500]).fit().params
# MSE loss
model_losses[:, i] = (y[500:] - model_factors[i, 500:].dot(model_beta)) ** 2.0

spa = SPA(bm_losses, model_losses, seed=seed)
spa.compute()
spa.pvalues

```

```

[8]: lower      0.039
      consistent 0.049
      upper      0.050
      dtype: float64

```

Here the average losses are plotted. The higher index models are clearly better than the lower index models – and the benchmark model (which is identical to model.0).

```

[9]: model_losses = pd.DataFrame(model_losses, columns=["model." + str(i) for i in range(k)])
      avg_model_losses = pd.DataFrame(model_losses.mean(0), columns=["Average loss"])
      fig = avg_model_losses.plot(style=["o"])

```



3.1.2 Stepwise Multiple Testing (StepM)

Stepwise Multiple Testing is similar to the SPA and has the same null. The primary difference is that it identifies the set of models which are better than the benchmark, rather than just asking the basic question if any model is better.

```


[10]: from arch.bootstrap import StepM

stepm = StepM(bm_losses, model_losses)
stepm.compute()
print("Model indices:")
print([model.split(".")[1] for model in stepm.superior_models])

Model indices:
['379', '466', '475']

```

```
[11]: better_models = pd.concat([model_losses.mean(0), model_losses.mean(0)], 1)
better_models.columns = ["Same or worse", "Better"]
better = better_models.index.isin(stepm.superior_models)
worse = np.logical_not(better)
better_models.loc[better, "Same or worse"] = np.nan
better_models.loc[worse, "Better"] = np.nan
fig = better_models.plot(style=["o", "s"], rot=270)
```



3.1.3 The Model Confidence Set

The model confidence set takes a set of **losses** as its input and finds the set which are not statistically different from each other while controlling the familywise error rate. The primary output is a set of p-values, where models with a pvalue above the size are in the MCS. Small p-values indicate that the model is easily rejected from the set that includes the best.

```
[12]: from arch.bootstrap import MCS

# Limit the size of the set
losses = model_losses.iloc[:, ::20]
mcs = MCS(losses, size=0.10)
mcs.compute()
print("MCS P-values")
print(mcs.pvalues)
print("Included")
included = mcs.included
print([model.split(".")[1] for model in included])
print("Excluded")
excluded = mcs.excluded
print([model.split(".")[1] for model in excluded])
```

```
MCS P-values
      Pvalue
Model name
model.20    0.001
```

(continues on next page)

(continued from previous page)

```


model.0      0.003
model.120    0.005
model.100    0.005
model.140    0.011
model.60     0.074
model.40     0.101
model.160    0.118
model.380    0.216
model.300    0.287
model.80     0.443
model.180    0.443
model.220    0.443
model.460    0.506
model.340    0.536
model.200    0.619
model.240    0.740
model.360    0.840
model.400    0.840
model.320    0.840
model.260    0.840
model.420    0.840
model.280    0.840
model.440    0.840
model.480    1.000
Included
['160', '180', '200', '220', '240', '260', '280', '300', '320', '340', '360', '380', '40
→', '400', '420', '440', '460', '480', '80']
Excluded
['0', '100', '120', '140', '20', '60']

```

```

[13]: status = pd.DataFrame(
        [losses.mean(0), losses.mean(0)], index=["Excluded", "Included"]
    ).T
    status.loc[status.index.isin(included), "Excluded"] = np.nan
    status.loc[status.index.isin(excluded), "Included"] = np.nan
    fig = status.plot(style=["o", "s"])

```



3.2 Module Reference

3.2.1 Test of Superior Predictive Ability (SPA), Reality Check

The test of Superior Predictive Ability (Hansen 2005), or SPA, is an improved version of the Reality Check (White 2000). It tests whether the best forecasting performance from a set of models is better than that of the forecasts from a benchmark model. A model is “better” if its losses are smaller than those from the benchmark. Formally, it tests the null

$$H_0 : \max_i E[L_i] \geq E[L_{bm}]$$

where L_i is the loss from model i and L_{bm} is the loss from the benchmark model. The alternative is

$$H_1 : \min_i E[L_i] < E[L_{bm}]$$

This procedure accounts for dependence between the losses and the fact that there are potentially alternative models being considered.

Note: Also callable using `RealityCheck`

<code>SPA(benchmark, models[, block_size, reps, ...])</code>	Test of Superior Predictive Ability (SPA) of White and Hansen.
--	--

arch.bootstrap.SPA

```
class arch.bootstrap.SPA(benchmark, models, block_size=None, reps=1000, bootstrap='stationary',
                        studentize=True, nested=False, *, seed=None)
```

Test of Superior Predictive Ability (SPA) of White and Hansen.

The SPA is also known as the Reality Check or Bootstrap Data Snooper.

Parameters

benchmark : {ndarray, Series}

T element array of benchmark model *losses*

models : {ndarray, DataFrame}

T by k element array of alternative model *losses*

block_size : int, optional

Length of window to use in the bootstrap. If not provided, \sqrt{T} is used. In general, this should be provided and chosen to be appropriate for the data.

reps : int, optional

Number of bootstrap replications to uses. Default is 1000.

bootstrap : str, optional

Bootstrap to use. Options are ‘stationary’ or ‘sb’: Stationary bootstrap (Default) ‘circular’ or ‘cbb’: Circular block bootstrap ‘moving block’ or ‘mbb’: Moving block bootstrap

studentize : bool

Flag indicating to studentize loss differentials. Default is True

nested : bool

Flag indicating to use a nested bootstrap to compute variances for studentization. Default is False. Note that this can be slow since the procedure requires k extra bootstraps.

seed : {int, Generator, RandomState}, optional

Seed value to use when creating the bootstrap used in the comparison. If an integer or None, the NumPy default_rng is used with the seed value. If a Generator or a RandomState, the argument is used.

Notes

The three p-value correspond to different re-centering decisions.

- Upper : Never recenter to all models are relevant to distribution
- Consistent : Only recenter if closer than a $\log(\log(t))$ bound
- Lower : Never recenter a model if worse than benchmark

See¹ and² for details.

See also

StepM

References**Methods**

<i>better_models</i> ([pvalue, pvalue_type])	Returns set of models rejected as being equal-or-worse than the benchmark
<i>compute</i> ()	Compute the bootstrap pvalue.
<i>critical_values</i> ([pvalue])	Returns data-dependent critical values
<i>reset</i> ()	Reset the bootstrap to its initial state.
<i>seed</i> (value)	Seed the bootstrap's random number generator
<i>subset</i> (selector)	Sets a list of active models to run the SPA on.

arch.bootstrap.SPA.better_models

SPA.better_models(pvalue=0.05, pvalue_type='consistent')

Returns set of models rejected as being equal-or-worse than the benchmark

Parameters

pvalue : float, optional

P-value in (0,1) to use when computing superior models

pvalue_type : str, optional

String in 'lower', 'consistent', or 'upper' indicating which critical value to use.

Returns

indices – List of column names or indices of the superior models. Column names are returned if models is a DataFrame.

¹ Hansen, P. R. (2005). A test for superior predictive ability. Journal of Business & Economic Statistics, 23(4), 365-380.

² White, H. (2000). A reality check for data snooping. Econometrica, 68(5), 1097-1126.

Return type

list

Notes

List of superior models returned is always with respect to the initial set of models, even when using `subset()`.

arch.bootstrap.SPA.compute**SPA.compute()**

Compute the bootstrap pvalue.

Notes

Must be called before accessing the pvalue.

Return type

None

arch.bootstrap.SPA.critical_values**SPA.critical_values(pvalue=0.05)**

Returns data-dependent critical values

Parameters

pvalue : float, optional

P-value in (0,1) to use when computing the critical values.

Returns

crit_vals – Series containing critical values for the lower, consistent and upper methodologies

Return type

Series

arch.bootstrap.SPA.reset**SPA.reset()**

Reset the bootstrap to its initial state.

Return type

None

arch.bootstrap.SPA.seed**SPA.seed**(value)

Seed the bootstrap's random number generator

Parameters**value** : {int, List[int], ndarray[int]}
Integer to use as the seed**Return type**

None

arch.bootstrap.SPA.subset**SPA.subset**(selector)

Sets a list of active models to run the SPA on. Primarily for internal use.

Parameters**selector** : ndarray
Boolean array indicating which columns to use when computing the p-values. This is primarily for use by StepM.**Return type**

None

Properties

<i>pvalues</i>	P-values corresponding to the lower, consistent and upper p-values.
----------------	---

arch.bootstrap.SPA.pvalues**property** SPA.pvalues : Series

P-values corresponding to the lower, consistent and upper p-values.

Returns**pvals** – Three p-values corresponding to the lower bound, the consistent estimator, and the upper bound.**Return type**

Series

3.2.2 Stepwise Multiple Testing (StepM)

The Stepwise Multiple Testing procedure (Romano & Wolf (2005)) is closely related to the SPA, except that it returns a set of models that are superior to the benchmark model, rather than the p-value from the null. They are so closely related that `StepM` is essentially a wrapper around `SPA` with some small modifications to allow multiple calls.

<code>StepM(benchmark, models[, size, block_size, ...])</code>	StepM multiple comparison procedure of Romano and Wolf.
--	---

`arch.bootstrap.StepM`

```
class arch.bootstrap.StepM(benchmark, models, size=0.05, block_size=None, reps=1000,
                           bootstrap='stationary', studentize=True, nested=False, *, seed=None)
```

StepM multiple comparison procedure of Romano and Wolf.

Parameters

benchmark : {ndarray, Series}

T element array of benchmark model *losses*

models : {ndarray, DataFrame}

T by k element array of alternative model *losses*

size : float, optional

Value in (0,1) to use as the test size when implementing the comparison. Default value is 0.05.

block_size : int, optional

Length of window to use in the bootstrap. If not provided, \sqrt{T} is used. In general, this should be provided and chosen to be appropriate for the data.

reps : int, optional

Number of bootstrap replications to uses. Default is 1000.

bootstrap : str, optional

Bootstrap to use. Options are 'stationary' or 'sb': Stationary bootstrap (Default) 'circular' or 'cbb': Circular block bootstrap 'moving block' or 'mbb': Moving block bootstrap

studentize : bool, optional

Flag indicating to studentize loss differentials. Default is True

nested : bool, optional

Flag indicating to use a nested bootstrap to compute variances for studentization. Default is False. Note that this can be slow since the procedure requires k extra bootstraps.

seed : {int, Generator, RandomState}, optional

Seed value to use when creating the bootstrap used in the comparison. If an integer or None, the NumPy default_rng is used with the seed value. If a Generator or a RandomState, the argument is used.

Notes

The size controls the Family Wise Error Rate (FWER) since this is a multiple comparison procedure. Uses SPA and the consistent selection procedure.

See¹ for detail.

See also

[SPA](#)

References

Methods

<code>compute()</code>	Compute the set of superior models.
<code>reset()</code>	Reset the bootstrap to it's initial state.
<code>seed(value)</code>	Seed the bootstrap's random number generator

arch.bootstrap.StepM.compute

StepM.`compute()`

Compute the set of superior models.

Return type

`None`

arch.bootstrap.StepM.reset

StepM.`reset()`

Reset the bootstrap to it's initial state.

Return type

`None`

arch.bootstrap.StepM.seed

StepM.`seed(value)`

Seed the bootstrap's random number generator

Parameters

value : {int, List[int], ndarray[int]}

Integer to use as the seed

Return type

`None`

¹ Romano, J. P., & Wolf, M. (2005). Stepwise multiple testing as formalized data snooping. *Econometrica*, 73(4), 1237-1282.

Properties

<i>superior_models</i>	List of the indices or column names of the superior models
------------------------	--

arch.bootstrap.StepM.superior_models

property StepM.superior_models : list[collections.abc.Hashable]

List of the indices or column names of the superior models

Returns

List of superior models. Contains column indices if models is an array or contains column names if models is a DataFrame.

Return type

list

3.2.3 Model Confidence Set (MCS)

The Model Confidence Set (Hansen, Lunde & Nason (2011)) differs from other multiple comparison procedures in that there is no benchmark. The MCS attempts to identify the set of models which produce the same expected loss, while controlling the probability that a model that is worse than the best model is in the model confidence set. Like the other MCPs, it controls the Familywise Error Rate rather than the usual test size.

<i>MCS</i> (losses, size[, reps, block_size, ...])	Model Confidence Set (MCS) of Hansen, Lunde and Nason.
--	--

arch.bootstrap.MCS

class arch.bootstrap.MCS(losses, size, reps=**1000**, block_size=**None**, method=**'R'**, bootstrap=**'stationary'**, *, seed=**None**)

Model Confidence Set (MCS) of Hansen, Lunde and Nason.

Parameters

losses : {ndarray, DataFrame}

T by k array containing losses from a set of models

size : float, optional

Value in (0,1) to use as the test size when implementing the mcs. Default value is 0.05.

block_size : int, optional

Length of window to use in the bootstrap. If not provided, sqrt(T) is used. In general, this should be provided and chosen to be appropriate for the data.

method : {'max', 'R'}, optional

MCS test and elimination implementation method, either 'max' or 'R'. Default is 'R'.

reps : int, optional

Number of bootstrap replications to uses. Default is 1000.

bootstrap : str, optional

Bootstrap to use. Options are 'stationary' or 'sb': Stationary bootstrap (Default) 'circular' or 'cbb': Circular block bootstrap 'moving block' or 'mbb': Moving block bootstrap

seed : {int, Generator, RandomState}, optional

Seed value to use when creating the bootstrap used in the comparison. If an integer or None, the NumPy default_rng is used with the seed value. If a Generator or a RandomState, the argument is used.

Notes

See¹ for details.

References**Methods**

<i>compute()</i>	Compute the set of models in the confidence set.
<i>reset()</i>	Reset the bootstrap to it's initial state.
<i>seed(value)</i>	Seed the bootstrap's random number generator

arch.bootstrap.MCS.compute**MCS.compute()**

Compute the set of models in the confidence set.

Return type

None

arch.bootstrap.MCS.reset**MCS.reset()**

Reset the bootstrap to it's initial state.

Return type

None

arch.bootstrap.MCS.seed**MCS.seed(value)**

Seed the bootstrap's random number generator

Parameters

value : {int, List[int], ndarray[int]}

Integer to use as the seed

Return type

None

¹ Hansen, P. R., Lunde, A., & Nason, J. M. (2011). The model confidence set. *Econometrica*, 79(2), 453-497.

Properties

<i>excluded</i>	List of model indices that are excluded from the MCS
<i>included</i>	List of model indices that are included in the MCS
<i>pvalues</i>	Model p-values for inclusion in the MCS

arch.bootstrap.MCS.excluded

property `MCS.excluded` : `list[collections.abc.Hashable]`

List of model indices that are excluded from the MCS

Returns

excluded – List of column indices or names of the excluded models

Return type

`list`

arch.bootstrap.MCS.included

property `MCS.included` : `list[collections.abc.Hashable]`

List of model indices that are included in the MCS

Returns

included – List of column indices or names of the included models

Return type

`list`

arch.bootstrap.MCS.pvalues

property `MCS.pvalues` : `DataFrame`

Model p-values for inclusion in the MCS

Returns

pvalues – `DataFrame` where the index is the model index (column or name) containing the smallest size where the model is in the MCS.

Return type

`DataFrame`

3.3 References

Articles used in the creation of this module include

UNIT ROOT TESTING

Many time series are highly persistent, and determining whether the data appear to be stationary or contains a unit root is the first step in many analyses. This module contains a number of routines:

- Augmented Dickey-Fuller (*ADF*)
- Dickey-Fuller GLS (*DFGLS*)
- Phillips-Perron (*PhillipsPerron*)
- KPSS (*KPSS*)
- Zivot-Andrews (*ZivotAndrews*)
- Variance Ratio (*VarianceRatio*)
- Automatic Bandwidth Selection (*auto_bandwidth()*)

The first four all start with the null of a unit root and have an alternative of a stationary process. The final test, KPSS, has a null of a stationary process with an alternative of a unit root.

4.1 Introduction

All tests expect a 1-d series as the first input. The input can be any array that can *squeeze* into a 1-d array, a pandas *Series* or a pandas *DataFrame* that contains a single variable.

All tests share a common structure. The key elements are:

- *stat* - Returns the test statistic
- *pvalue* - Returns the p-value of the test statistic
- *lags* - Sets or gets the number of lags used in the model. In most test, can be *None* to trigger automatic selection.
- *trend* - Sets or gets the trend used in the model. Supported trends vary by model, but include:
 - ‘*nc*’: No constant
 - ‘*c*’: Constant
 - ‘*ct*’: Constant and time trend
 - ‘*ctt*’: Constant, time trend and quadratic time trend
- *summary()* - Returns a summary object that can be printed to get a formatted table

4.1.1 Basic Example

This basic example show the use of the Augmented-Dickey fuller to test whether the default premium, defined as the difference between the yields of large portfolios of BAA and AAA bonds. This example uses a constant and time trend.

```
import datetime as dt

import pandas_datareader.data as web
from arch.unitroot import ADF

start = dt.datetime(1919, 1, 1)
end = dt.datetime(2014, 1, 1)

df = web.DataReader(["AAA", "BAA"], "fred", start, end)
df['diff'] = df['BAA'] - df['AAA']
adf = ADF(df['diff'])
adf.trend = 'ct'

print(adf.summary())
```

which yields

```
Augmented Dickey-Fuller Results
=====
Test Statistic          -3.448
P-value                  0.045
Lags                     21
-----

Trend: Constant and Linear Time Trend
Critical Values: -3.97 (1%), -3.41 (5%), -3.13 (10%)
Null Hypothesis: The process contains a unit root.
Alternative Hypothesis: The process is weakly stationary.
```

4.2 Unit Root Testing

This setup code is required to run in an IPython notebook

```
[1]: import warnings

warnings.simplefilter("ignore")

%matplotlib inline
import matplotlib.pyplot as plt
import seaborn


seaborn.set_style("darkgrid")
plt.rc("figure", figsize=(16, 6))
plt.rc("savefig", dpi=90)
plt.rc("font", family="sans-serif")
plt.rc("font", size=14)
```

4.2.1 Setup

Most examples will make use of the Default premium, which is the difference between the yields of BAA and AAA rated corporate bonds. The data is downloaded from FRED using pandas.


```
[2]: import arch.data.default
import pandas as pd
import statsmodels.api as sm

default_data = arch.data.default.load()
default = default_data.BAA.copy()
default.name = "default"
default = default - default_data.AAA.values
fig = default.plot()
```



The Default premium is clearly highly persistent. A simple check of the autocorrelations confirms this.

```
[3]: acf = pd.DataFrame(sm.tsa.stattools.acf(default), columns=["ACF"])
fig = acf[1:].plot(kind="bar", title="Autocorrelations")
```



4.2.2 Augmented Dickey-Fuller Testing

The Augmented Dickey-Fuller test is the most common unit root test used. It is a regression of the first difference of the variable on its lagged level as well as additional lags of the first difference. The null is that the series contains a unit root, and the (one-sided) alternative is that the series is stationary.

By default, the number of lags is selected by minimizing the AIC across a range of lag lengths (which can be set using `max_lag` when initializing the model). Additionally, the basic test includes a constant in the ADF regression.

These results indicate that the Default premium is stationary.

```
[4]: from arch.unitroot import ADF
```

```
adf = ADF(default)
print(adf.summary().as_text())
```

```

Augmented Dickey-Fuller Results
=====
Test Statistic          -3.356
P-value                  0.013
Lags                     21
-----

Trend: Constant
Critical Values: -3.44 (1%), -2.86 (5%), -2.57 (10%)
Null Hypothesis: The process contains a unit root.
Alternative Hypothesis: The process is weakly stationary.
```

The number of lags can be directly set using `lags`. Changing the number of lags makes no difference to the conclusion.

Note: The ADF assumes residuals are white noise, and that the number of lags is sufficient to pick up any dependence in the data.

Setting the number of lags

```
[5]: adf = ADF(default, lags=5)
print(adf.summary().as_text())
```

```

Augmented Dickey-Fuller Results
=====
Test Statistic          -3.582
P-value                  0.006
Lags                     5
-----

Trend: Constant
Critical Values: -3.44 (1%), -2.86 (5%), -2.57 (10%)
Null Hypothesis: The process contains a unit root.
Alternative Hypothesis: The process is weakly stationary.
```


Deterministic terms

The deterministic terms can be altered using `trend`. The options are:

- 'nc' : No deterministic terms
- 'c' : Constant only
- 'ct' : Constant and time trend
- 'ctt' : Constant, time trend and time-trend squared

Changing the type of constant also makes no difference for this data.

```
[6]: adf = ADF(default, trend="ct", lags=5)
      print(adf.summary().as_text())
```

```
Augmented Dickey-Fuller Results
=====
Test Statistic          -3.786
P-value                 0.017
Lags                    5
-----

Trend: Constant and Linear Time Trend
Critical Values: -3.97 (1%), -3.41 (5%), -3.13 (10%)
Null Hypothesis: The process contains a unit root.
Alternative Hypothesis: The process is weakly stationary.
```

Regression output

The ADF uses a standard regression when computing results. These can be accessed using `regression`.

```
[7]: reg_res = adf.regression
      print(reg_res.summary().as_text())
```

```
OLS Regression Results
=====
Dep. Variable:          y      R-squared:          0.095
Model:                  OLS    Adj. R-squared:       0.090
Method:                 Least Squares    F-statistic:       17.83
Date:                  Tue, 18 May 2021    Prob (F-statistic): 1.30e-22
Time:                  13:22:02    Log-Likelihood:    630.15
No. Observations:      1194    AIC:              -1244.
Df Residuals:          1186    BIC:              -1204.
Df Model:              7
Covariance Type:       nonrobust
=====
               coef      std err          t      P>|t|      [0.025      0.975]
-----
Level.L1      -0.0248      0.007      -3.786      0.000      -0.038      -0.012
Diff.L1        0.2229      0.029       7.669      0.000       0.166       0.280
Diff.L2       -0.0525      0.030      -1.769      0.077      -0.111       0.006
Diff.L3       -0.1363      0.029      -4.642      0.000      -0.194      -0.079
Diff.L4       -0.0510      0.030      -1.727      0.084      -0.109       0.007
Diff.L5        0.0440      0.029       1.516      0.130      -0.013       0.101
```

(continues on next page)

(continued from previous page)

const	0.0383	0.013	2.858	0.004	0.012	0.065
trend	-1.586e-05	1.29e-05	-1.230	0.219	-4.11e-05	9.43e-06
=====						
Omnibus:	665.553	Durbin-Watson:	2.000			
Prob(Omnibus):	0.000	Jarque-Bera (JB):	146083.295			
Skew:	-1.425	Prob(JB):	0.00			
Kurtosis:	57.113	Cond. No.	5.70e+03			
=====						


Notes:

[1] Standard Errors assume that the covariance matrix of the errors is correctly specified.

[2] The condition number is large, 5.7e+03. This might indicate that there are strong multicollinearity or other numerical problems.


```
[8]: import matplotlib.pyplot as plt
import pandas as pd

resids = pd.DataFrame(reg_res.resid)
resids.index = default.index[6:]
resids.columns = ["resids"]
fig = resids.plot()
```



Since the number lags was directly set, it is good to check whether the residuals appear to be white noise.

```
[9]: acf = pd.DataFrame(sm.tsa.stattools.acf(reg_res.resid), columns=["ACF"])
fig = acf[1:].plot(kind="bar", title="Residual Autocorrelations")
```



4.2.3 Dickey-Fuller GLS Testing

The Dickey-Fuller GLS test is an improved version of the ADF which uses a GLS-detrending regression before running an ADF regression with no additional deterministic terms. This test is only available with a constant or constant and time trend (`trend='c'` or `trend='ct'`).

The results of this test agree with the ADF results.

```
[10]: from arch.unitroot import DFGLS
```

```
dfgls = DFGLS(default)
print(dfgls.summary().as_text())
```

```

Dickey-Fuller GLS Results
=====
Test Statistic      -2.322
P-value             0.020
Lags                 21
-----

Trend: Constant
Critical Values: -2.59 (1%), -1.96 (5%), -1.64 (10%)
Null Hypothesis: The process contains a unit root.
Alternative Hypothesis: The process is weakly stationary.
```

The trend can be altered using `trend`. The conclusion is the same.

```
[11]: dfgls = DFGLS(default, trend="ct")
print(dfgls.summary().as_text())
```

```

Dickey-Fuller GLS Results
=====
Test Statistic      -3.464
P-value             0.009
Lags                 21
-----
```

(continues on next page)

(continued from previous page)

```
Trend: Constant and Linear Time Trend
Critical Values: -3.43 (1%), -2.86 (5%), -2.58 (10%)
Null Hypothesis: The process contains a unit root.
Alternative Hypothesis: The process is weakly stationary.
```

4.2.4 Phillips-Perron Testing

The Phillips-Perron test is similar to the ADF except that the regression run does not include lagged values of the first differences. Instead, the PP test fixed the t-statistic using a long run variance estimation, implemented using a Newey-West covariance estimator.

By default, the number of lags is automatically set, although this can be overridden using `lags`.

```
[12]: from arch.unitroot import PhillipsPerron
```

```
pp = PhillipsPerron(default)
print(pp.summary().as_text())
```

```
Phillips-Perron Test (Z-tau)
=====
Test Statistic      -3.898
P-value              0.002
Lags                 23
-----
```

```
Trend: Constant
Critical Values: -3.44 (1%), -2.86 (5%), -2.57 (10%)
Null Hypothesis: The process contains a unit root.
Alternative Hypothesis: The process is weakly stationary.
```

It is important that the number of lags is sufficient to pick up any dependence in the data.

```
[13]: pp = PhillipsPerron(default, lags=12)
print(pp.summary().as_text())
```

```
Phillips-Perron Test (Z-tau)
=====
Test Statistic      -4.024
P-value              0.001
Lags                 12
-----
```

```
Trend: Constant
Critical Values: -3.44 (1%), -2.86 (5%), -2.57 (10%)
Null Hypothesis: The process contains a unit root.
Alternative Hypothesis: The process is weakly stationary.
```

The trend can be changed as well.

```
[14]: pp = PhillipsPerron(default, trend="ct", lags=12)
print(pp.summary().as_text())
```

```

Phillips-Perron Test (Z-tau)
=====
Test Statistic          -4.262
P-value                  0.004
Lags                     12
-----

Trend: Constant and Linear Time Trend
Critical Values: -3.97 (1%), -3.41 (5%), -3.13 (10%)
Null Hypothesis: The process contains a unit root.
Alternative Hypothesis: The process is weakly stationary.

```

Finally, the PP testing framework includes two types of tests. One which uses an ADF-type regression of the first difference on the level, the other which regresses the level on the level. The default is the tau test, which is similar to an ADF regression, although this can be changed using `test_type='rho'`.

```
[15]: pp = PhillipsPerron(default, test_type="rho", trend="ct", lags=12)
      print(pp.summary().as_text())
```

```

Phillips-Perron Test (Z-rho)
=====
Test Statistic          -36.114
P-value                  0.002
Lags                     12
-----

Trend: Constant and Linear Time Trend
Critical Values: -29.16 (1%), -21.60 (5%), -18.17 (10%)
Null Hypothesis: The process contains a unit root.
Alternative Hypothesis: The process is weakly stationary.

```

4.2.5 KPSS Testing

The KPSS test differs from the three previous in that the null is a stationary process and the alternative is a unit root.

Note that here the null is rejected which indicates that the series might be a unit root.

```
[16]: from arch.unitroot import KPSS
```

```

kpss = KPSS(default)
print(kpss.summary().as_text())

```

```

KPSS Stationarity Test Results
=====
Test Statistic          1.088
P-value                  0.002
Lags                     20
-----

Trend: Constant
Critical Values: 0.74 (1%), 0.46 (5%), 0.35 (10%)
Null Hypothesis: The process is weakly stationary.
Alternative Hypothesis: The process contains a unit root.

```

Changing the trend does not alter the conclusion.

```
[17]: kpss = KPSS(default, trend="ct")
print(kpss.summary().as_text())
```

```
      KPSS Stationarity Test Results
=====
Test Statistic           0.393
P-value                  0.000
Lags                     20
-----

Trend: Constant and Linear Time Trend
Critical Values: 0.22 (1%), 0.15 (5%), 0.12 (10%)
Null Hypothesis: The process is weakly stationary.
Alternative Hypothesis: The process contains a unit root.
```

4.2.6 Zivot-Andrews Test

The Zivot-Andrews test allows the possibility of a single structural break in the series. Here we test the default using the test.

```
[18]: from arch.unitroot import ZivotAndrews

za = ZivotAndrews(default)
print(za.summary().as_text())
```

```
      Zivot-Andrews Results
=====
Test Statistic          -4.900
P-value                 0.040
Lags                    21
-----

Trend: Constant
Critical Values: -5.28 (1%), -4.81 (5%), -4.57 (10%)
Null Hypothesis: The process contains a unit root with a single structural break.
Alternative Hypothesis: The process is trend and break stationary.
```

4.2.7 Variance Ratio Testing

Variance ratio tests are not usually used as unit root tests, and are instead used for testing whether a financial return series is a pure random walk versus having some predictability. This example uses the excess return on the market from Ken French's data.

```
[19]: import arch.data.frenchdata
import numpy as np
import pandas as pd

ff = arch.data.frenchdata.load()
excess_market = ff.iloc[:, 0] # Excess Market
print(ff.describe())
```

	Mkt-RF	SMB	HML	RF
count	1109.000000	1109.000000	1109.000000	1109.000000
mean	0.659946	0.206555	0.368864	0.274220
std	5.327524	3.191132	3.482352	0.253377
min	-29.130000	-16.870000	-13.280000	-0.060000
25%	-1.970000	-1.560000	-1.320000	0.030000
50%	1.020000	0.070000	0.140000	0.230000
75%	3.610000	1.730000	1.740000	0.430000
max	38.850000	36.700000	35.460000	1.350000

The variance ratio compares the variance of a 1-period return to that of a multi-period return. The comparison length has to be set when initializing the test.

This example compares 1-month to 12-month returns, and the null that the series is a pure random walk is rejected. Negative values indicate some positive autocorrelation in the returns (momentum).

```
[20]: from arch.unitroot import VarianceRatio
```

```
vr = VarianceRatio(excess_market, 12)
print(vr.summary().as_text())
```

```

Variance-Ratio Test Results
=====
Test Statistic          -5.029
P-value                  0.000
Lags                     12
-----

```

Computed with overlapping blocks (de-biased)

By default the VR test uses all overlapping blocks to estimate the variance of the long period's return. This can be changed by setting `overlap=False`. This lowers the power but does not change the conclusion.

```
[21]: warnings.simplefilter("always") # Restore warnings
```

```
vr = VarianceRatio(excess_market, 12, overlap=False)
print(vr.summary().as_text())
```

```

Variance-Ratio Test Results
=====
Test Statistic          -6.206
P-value                  0.000
Lags                     12
-----

```

Computed with non-overlapping blocks

```
c:\git\arch\arch\unitroot\unitroot.py:1679: InvalidLengthWarning:
The length of y is not an exact multiple of 12, and so the final
4 observations have been dropped.
```

```
warnings.warn(
```

Note: The warning is intentional. It appears here since when it is not possible to use all data since the data length is not an integer multiple of the long period when using non-overlapping blocks. There is little reason to use `overlap=False`.

4.3 The Unit Root Tests

<code>ADF(y[, lags, trend, max_lags, method, ...])</code>	Augmented Dickey-Fuller unit root test
<code>DFGLS(y[, lags, trend, max_lags, method, ...])</code>	Elliott, Rothenberg and Stock's (11) GLS detrended Dickey-Fuller
<code>PhillipsPerron(y[, lags, trend, test_type])</code>	Phillips-Perron unit root test
<code>ZivotAndrews(y[, lags, trend, trim, ...])</code>	Zivot-Andrews structural-break unit-root test
<code>VarianceRatio(y[, lags, trend, debiased, ...])</code>	Variance Ratio test of a random walk.
<code>KPSS(y[, lags, trend])</code>	Kwiatkowski, Phillips, Schmidt and Shin (KPSS) stationarity test

4.3.1 arch.unitroot.ADF

class arch.unitroot.ADF(y, lags=None, trend='c', max_lags=None, method='aic', low_memory=None)

Augmented Dickey-Fuller unit root test

Parameters

y : {ndarray, Series}

The data to test for a unit root

lags : int, optional

The number of lags to use in the ADF regression. If omitted or None, *method* is used to automatically select the lag length with no more than *max_lags* are included.

trend : {'n', 'c', 'ct', 'ctt'}, optional

The trend component to include in the test

- "n" - No trend components
- "c" - Include a constant (Default)
- "ct" - Include a constant and linear time trend
- "ctt" - Include a constant and linear and quadratic time trends

max_lags : int, optional

The maximum number of lags to use when selecting lag length

method : {"AIC", "BIC", "t-stat"}, optional

The method to use when selecting the lag length

- "AIC" - Select the minimum of the Akaike IC
- "BIC" - Select the minimum of the Schwarz/Bayesian IC
- "t-stat" - Select the minimum of the Schwarz/Bayesian IC

low_memory : bool

Flag indicating whether to use a low memory implementation of the lag selection algorithm. The low memory algorithm is slower than the standard algorithm but will use 2-4% of the memory required for the standard algorithm. This options allows automatic lag selection to be used in very long time series. If None, use automatic selection of algorithm.

Notes

The null hypothesis of the Augmented Dickey-Fuller is that there is a unit root, with the alternative that there is no unit root. If the pvalue is above a critical size, then the null cannot be rejected that there and the series appears to be a unit root.

The p-values are obtained through regression surface approximation from MacKinnon (1994) using the updated 2010 tables. If the p-value is close to significant, then the critical values should be used to judge whether to reject the null.

The autolag option and maxlag for it are described in Greene.

Examples

```
>>> from arch.unitroot import ADF
>>> import numpy as np
>>> import statsmodels.api as sm
>>> data = sm.datasets.macrodta.load().data
>>> inflation = np.diff(np.log(data["cpi"]))
>>> adf = ADF(inflation)
>>> print("{0:0.4f}".format(adf.stat))
-3.0931
>>> print("{0:0.4f}".format(adf.pvalue))
0.0271
>>> adf.lags
2
>>> adf.trend="ct"
>>> print("{0:0.4f}".format(adf.stat))
-3.2111
>>> print("{0:0.4f}".format(adf.pvalue))
0.0822
```

References

Methods

<code>summary()</code>	Summary of test, containing statistic, p-value and critical values
------------------------	--

arch.unitroot.ADF.summary

`ADF.summary()`

Summary of test, containing statistic, p-value and critical values

Return type

Summary

Properties

<i>alternative_hypothesis</i>	The alternative hypothesis
<i>critical_values</i>	Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.
<i>lags</i>	Sets or gets the number of lags used in the model.
<i>max_lags</i>	Sets or gets the maximum lags used when automatically selecting lag length
<i>nobs</i>	The number of observations used when computing the test statistic.
<i>null_hypothesis</i>	The null hypothesis
<i>pvalue</i>	Returns the p-value for the test statistic
<i>regression</i>	Returns the OLS regression results from the ADF model estimated
<i>stat</i>	The test statistic for a unit root
<i>trend</i>	Sets or gets the deterministic trend term used in the test.
<i>valid_trends</i>	List of valid trend terms.
<i>y</i>	Returns the data used in the test statistic

arch.unitroot.ADF.alternative_hypothesis

property ADF.alternative_hypothesis : str

The alternative hypothesis

Return type

str

arch.unitroot.ADF.critical_values

property ADF.critical_values : dict[str, float]

Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.

Return type

dict[str, float]

arch.unitroot.ADF.lags

property ADF.lags : int

Sets or gets the number of lags used in the model. When bootstrap use DF-type regressions, lags is the number of lags in the regression model. When bootstrap use long-run variance estimators, lags is the number of lags used in the long-run variance estimator.

Return type

int

arch.unitroot.ADF.max_lags

property ADF.max_lags : int | None

Sets or gets the maximum lags used when automatically selecting lag length

Return type

Optional[int]

arch.unitroot.ADF.nobs

property ADF.nobs : int

The number of observations used when computing the test statistic. Accounts for loss of data due to lags for regression-based bootstrap.

Return type

int

arch.unitroot.ADF.null_hypothesis

property ADF.null_hypothesis : str

The null hypothesis

Return type

str

arch.unitroot.ADF.pvalue

property ADF.pvalue : float

Returns the p-value for the test statistic

Return type

float

arch.unitroot.ADF.regression

property ADF.regression : RegressionResults

Returns the OLS regression results from the ADF model estimated

Return type

RegressionResults

arch.unitroot.ADF.stat

property ADF.stat : float

The test statistic for a unit root

Return type

float

arch.unitroot.ADF.trend**property** ADF.trend : str

Sets or gets the deterministic trend term used in the test. See valid_trends for a list of supported trends

Return type

str

arch.unitroot.ADF.valid_trends**property** ADF.valid_trends : list[str]

List of valid trend terms.

Return type

list[str]

arch.unitroot.ADF.y**property** ADF.y : ndarray | DataFrame | Series

Returns the data used in the test statistic

Return type

Union[ndarray, DataFrame, Series]

4.3.2 arch.unitroot.DFGLS

class arch.unitroot.DFGLS(y, lags=None, trend='c', max_lags=None, method='aic', low_memory=None)

Elliott, Rothenberg and Stock's ⁽¹⁾ GLS detrended Dickey-Fuller

Parameters**y : {ndarray, Series}**

The data to test for a unit root

lags : int, optional

The number of lags to use in the ADF regression. If omitted or None, *method* is used to automatically select the lag length with no more than *max_lags* are included.

trend : {"c", "ct"}, optional

The trend component to include in the test

- "c" - Include a constant (Default)
- "ct" - Include a constant and linear time trend

max_lags : int, optional

The maximum number of lags to use when selecting lag length. When using automatic lag length selection, the lag is selected using OLS detrending rather than GLS detrending ⁽²⁾.

method : {"AIC", "BIC", "t-stat"}, optional

The method to use when selecting the lag length

¹ Elliott, G. R., T. J. Rothenberg, and J. H. Stock. 1996. Efficient bootstrap for an autoregressive unit root. *Econometrica* 64: 813-836

² Perron, P., & Qu, Z. (2007). A simple modification to improve the finite sample properties of Ng and Perron's unit root tests. *Economics letters*, 94(1), 12-19.

- "AIC" - Select the minimum of the Akaike IC
- "BIC" - Select the minimum of the Schwarz/Bayesian IC
- "t-stat" - Select the minimum of the Schwarz/Bayesian IC

Notes

The null hypothesis of the Dickey-Fuller GLS is that there is a unit root, with the alternative that there is no unit root. If the pvalue is above a critical size, then the null cannot be rejected and the series appears to be a unit root.

DFGLS differs from the ADF test in that an initial GLS detrending step is used before a trend-less ADF regression is run.

Critical values and p-values when trend is "c" are identical to the ADF. When trend is set to "ct", they are from ...

Examples

```
>>> from arch.unitroot import DFGLS
>>> import numpy as np
>>> import statsmodels.api as sm
>>> data = sm.datasets.macrodatab.load().data
>>> inflation = np.diff(np.log(data["cpi"]))
>>> dfpls = DFGLS(inflation)
>>> print("{0:0.4f}".format(dfpls.stat))
-2.7611
>>> print("{0:0.4f}".format(dfpls.pvalue))
0.0059
>>> dfpls.lags
2
>>> dfpls.trend = "ct"
>>> print("{0:0.4f}".format(dfpls.stat))
-2.9036
>>> print("{0:0.4f}".format(dfpls.pvalue))
0.0447
```

References

Methods

<code>summary()</code>	Summary of test, containing statistic, p-value and critical values
------------------------	--

arch.unitroot.DFGLS.summary**DFGLS.summary()**

Summary of test, containing statistic, p-value and critical values

Return type

Summary

Properties

<i>alternative_hypothesis</i>	The alternative hypothesis
<i>critical_values</i>	Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.
<i>lags</i>	Sets or gets the number of lags used in the model.
<i>max_lags</i>	Sets or gets the maximum lags used when automatically selecting lag length
<i>nobs</i>	The number of observations used when computing the test statistic.
<i>null_hypothesis</i>	The null hypothesis
<i>pvalue</i>	Returns the p-value for the test statistic
<i>regression</i>	Returns the OLS regression results from the ADF model estimated
<i>stat</i>	The test statistic for a unit root
<i>trend</i>	Sets or gets the deterministic trend term used in the test.
<i>valid_trends</i>	List of valid trend terms.
<i>y</i>	Returns the data used in the test statistic

arch.unitroot.DFGLS.alternative_hypothesis**property** DFGLS.alternative_hypothesis : str

The alternative hypothesis

Return type

str

arch.unitroot.DFGLS.critical_values**property** DFGLS.critical_values : dict[str, float]

Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.

Return type

dict[str, float]

arch.unitroot.DFGLS.lags**property** DFGLS.lags : int

Sets or gets the number of lags used in the model. When bootstrap use DF-type regressions, lags is the number of lags in the regression model. When bootstrap use long-run variance estimators, lags is the number of lags used in the long-run variance estimator.

Return type

int

arch.unitroot.DFGLS.max_lags**property** DFGLS.max_lags : int | None

Sets or gets the maximum lags used when automatically selecting lag length

Return type

Optional[int]

arch.unitroot.DFGLS.nobs**property** DFGLS.nobs : int

The number of observations used when computing the test statistic. Accounts for loss of data due to lags for regression-based bootstrap.

Return type

int

arch.unitroot.DFGLS.null_hypothesis**property** DFGLS.null_hypothesis : str

The null hypothesis

Return type

str

arch.unitroot.DFGLS.pvalue**property** DFGLS.pvalue : float

Returns the p-value for the test statistic

Return type

float

arch.unitroot.DFGLS.regression

property DFGLS.regression : RegressionResults

Returns the OLS regression results from the ADF model estimated

Return type

RegressionResults

arch.unitroot.DFGLS.stat

property DFGLS.stat : float

The test statistic for a unit root

Return type

float

arch.unitroot.DFGLS.trend

property DFGLS.trend

Sets or gets the deterministic trend term used in the test. See valid_trends for a list of supported trends

arch.unitroot.DFGLS.valid_trends

property DFGLS.valid_trends : list[str]

List of valid trend terms.

Return type

list[str]

arch.unitroot.DFGLS.y

property DFGLS.y : ndarray | DataFrame | Series

Returns the data used in the test statistic

Return type

Union[ndarray, DataFrame, Series]

4.3.3 arch.unitroot.PhillipsPerron

class arch.unitroot.PhillipsPerron(y, lags=None, trend='c', test_type='tau')

Phillips-Perron unit root test

Parameters

y : {ndarray, Series}

The data to test for a unit root

lags : int, optional

The number of lags to use in the Newey-West estimator of the long-run covariance. If omitted or None, the lag length is set automatically to $12 * (\text{nobs}/100)^{1/4}$

trend : {"n", "c", "ct"}, optional

The trend component to include in the test

- "n" - No trend components
- "c" - Include a constant (Default)
- "ct" - Include a constant and linear time trend

test_type : {"tau", "rho"}

The test to use when computing the test statistic. "tau" is based on the t-stat and "rho" uses a test based on nobs times the re-centered regression coefficient

Notes

The null hypothesis of the Phillips-Perron (PP) test is that there is a unit root, with the alternative that there is no unit root. If the pvalue is above a critical size, then the null cannot be rejected that there and the series appears to be a unit root.

Unlike the ADF test, the regression estimated includes only one lag of the dependant variable, in addition to trend terms. Any serial correlation in the regression errors is accounted for using a long-run variance estimator (currently Newey-West).

The p-values are obtained through regression surface approximation from MacKinnon (1994) using the updated 2010 tables. If the p-value is close to significant, then the critical values should be used to judge whether to reject the null.

Examples

```
>>> from arch.unitroot import PhillipsPerron
>>> import numpy as np
>>> import statsmodels.api as sm
>>> data = sm.datasets.macrodta.load().data
>>> inflation = np.diff(np.log(data["cpi"]))
>>> pp = PhillipsPerron(inflation)
>>> print("{0:0.4f}".format(pp.stat))
-8.1356
>>> print("{0:0.4f}".format(pp.pvalue))
0.0000
>>> pp.lags
15
>>> pp.trend = "ct"
>>> print("{0:0.4f}".format(pp.stat))
-8.2022
>>> print("{0:0.4f}".format(pp.pvalue))
0.0000
>>> pp.test_type = "rho"
>>> print("{0:0.4f}".format(pp.stat))
-120.3271
>>> print("{0:0.4f}".format(pp.pvalue))
0.0000
```

References

Methods

<i>summary()</i>	Summary of test, containing statistic, p-value and critical values
------------------	--

arch.unitroot.PhillipsPerron.summary

PhillipsPerron.**summary()**

Summary of test, containing statistic, p-value and critical values

Return type

Summary

Properties

<i>alternative_hypothesis</i>	The alternative hypothesis
<i>critical_values</i>	Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.
<i>lags</i>	Sets or gets the number of lags used in the model.
<i>nobs</i>	The number of observations used when computing the test statistic.
<i>null_hypothesis</i>	The null hypothesis
<i>pvalue</i>	Returns the p-value for the test statistic
<i>regression</i>	Returns OLS regression results for the specification used in the test
<i>stat</i>	The test statistic for a unit root
<i>test_type</i>	Gets or sets the test type returned by stat.
<i>trend</i>	Sets or gets the deterministic trend term used in the test.
<i>valid_trends</i>	List of valid trend terms.
<i>y</i>	Returns the data used in the test statistic

arch.unitroot.PhillipsPerron.alternative_hypothesis

property PhillipsPerron.**alternative_hypothesis**: str

The alternative hypothesis

Return type

str

arch.unitroot.PhillipsPerron.critical_values

property `PhillipsPerron.critical_values` : `dict[str, float]`

Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.

Return type

`dict[str, float]`

arch.unitroot.PhillipsPerron.lags

property `PhillipsPerron.lags` : `int`

Sets or gets the number of lags used in the model. When bootstrap use DF-type regressions, lags is the number of lags in the regression model. When bootstrap use long-run variance estimators, lags is the number of lags used in the long-run variance estimator.

Return type

`int`

arch.unitroot.PhillipsPerron.nobs

property `PhillipsPerron.nobs` : `int`

The number of observations used when computing the test statistic. Accounts for loss of data due to lags for regression-based bootstrap.

Return type

`int`

arch.unitroot.PhillipsPerron.null_hypothesis

property `PhillipsPerron.null_hypothesis` : `str`

The null hypothesis

Return type

`str`

arch.unitroot.PhillipsPerron.pvalue

property `PhillipsPerron.pvalue` : `float`

Returns the p-value for the test statistic

Return type

`float`

arch.unitroot.PhillipsPerron.regression

property `PhillipsPerron.regression` : `RegressionResults`

Returns OLS regression results for the specification used in the test

The results returned use a Newey-West covariance matrix with the same number of lags as are used in the test statistic.

Return type

`RegressionResults`

arch.unitroot.PhillipsPerron.stat

property `PhillipsPerron.stat` : `float`

The test statistic for a unit root

Return type

`float`

arch.unitroot.PhillipsPerron.test_type

property `PhillipsPerron.test_type` : `str`

Gets or sets the test type returned by stat. Valid values are “tau” or “rho”

Return type

`str`

arch.unitroot.PhillipsPerron.trend

property `PhillipsPerron.trend` : `str`

Sets or gets the deterministic trend term used in the test. See `valid_trends` for a list of supported trends

Return type

`str`

arch.unitroot.PhillipsPerron.valid_trends

property `PhillipsPerron.valid_trends` : `list[str]`

List of valid trend terms.

Return type

`list[str]`

arch.unitroot.PhillipsPerron.y**property** PhillipsPerron.y : ndarray | DataFrame | Series

Returns the data used in the test statistic

Return type

Union[ndarray, DataFrame, Series]

4.3.4 arch.unitroot.ZivotAndrews**class** arch.unitroot.ZivotAndrews(y, lags=None, trend='c', trim=0.15, max_lags=None, method='aic')

Zivot-Andrews structural-break unit-root test

The Zivot-Andrews test can be used to test for a unit root in a univariate process in the presence of serial correlation and a single structural break.

Parameters**y : array_like**

data series

lags : int, optional

The number of lags to use in the ADF regression. If omitted or None, *method* is used to automatically select the lag length with no more than *max_lags* are included.

trend : {"c", "t", "ct"}, optional

The trend component to include in the test

- "c" - Include a constant (Default)
- "t" - Include a linear time trend
- "ct" - Include a constant and linear time trend

trim : float

percentage of series at begin/end to exclude from break-period calculation in range [0, 0.333] (default=0.15)

max_lags : int, optional

The maximum number of lags to use when selecting lag length

method : {"AIC", "BIC", "t-stat"}, optional

The method to use when selecting the lag length

- "AIC" - Select the minimum of the Akaike IC
- "BIC" - Select the minimum of the Schwarz/Bayesian IC
- "t-stat" - Select the minimum of the Schwarz/Bayesian IC

Notes

H_0 = unit root with a single structural break

Algorithm follows Baum (2004/2015) approximation to original Zivot-Andrews method. Rather than performing an autolag regression at each candidate break period (as per the original paper), a single autolag regression is run up-front on the base model (constant + trend with no dummies) to determine the best lag length. This lag length is then used for all subsequent break-period regressions. This results in significant run time reduction but also slightly more pessimistic test statistics than the original Zivot-Andrews method,

No attempt has been made to characterize the size/power trade-off.

References

Methods

<code>summary()</code>	Summary of test, containing statistic, p-value and critical values
------------------------	--

`arch.unitroot.ZivotAndrews.summary`

`ZivotAndrews.summary()`

Summary of test, containing statistic, p-value and critical values

Return type

Summary

Properties

<code>alternative_hypothesis</code>	The alternative hypothesis
<code>critical_values</code>	Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.
<code>lags</code>	Sets or gets the number of lags used in the model.
<code>nobs</code>	The number of observations used when computing the test statistic.
<code>null_hypothesis</code>	The null hypothesis
<code>pvalue</code>	Returns the p-value for the test statistic
<code>stat</code>	The test statistic for a unit root
<code>trend</code>	Sets or gets the deterministic trend term used in the test.
<code>valid_trends</code>	List of valid trend terms.
<code>y</code>	Returns the data used in the test statistic

arch.unitroot.ZivotAndrews.alternative_hypothesis

property ZivotAndrews.alternative_hypothesis : str

The alternative hypothesis

Return type

str

arch.unitroot.ZivotAndrews.critical_values

property ZivotAndrews.critical_values : dict[str, float]

Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.

Return type

dict[str, float]

arch.unitroot.ZivotAndrews.lags

property ZivotAndrews.lags : int

Sets or gets the number of lags used in the model. When bootstrap use DF-type regressions, lags is the number of lags in the regression model. When bootstrap use long-run variance estimators, lags is the number of lags used in the long-run variance estimator.

Return type

int

arch.unitroot.ZivotAndrews.nobs

property ZivotAndrews.nobs : int

The number of observations used when computing the test statistic. Accounts for loss of data due to lags for regression-based bootstrap.

Return type

int

arch.unitroot.ZivotAndrews.null_hypothesis

property ZivotAndrews.null_hypothesis : str

The null hypothesis

Return type

str

arch.unitroot.ZivotAndrews.pvalue

property ZivotAndrews.pvalue : float
Returns the p-value for the test statistic

Return type
float

arch.unitroot.ZivotAndrews.stat

property ZivotAndrews.stat : float
The test statistic for a unit root

Return type
float

arch.unitroot.ZivotAndrews.trend

property ZivotAndrews.trend : str
Sets or gets the deterministic trend term used in the test. See valid_trends for a list of supported trends

Return type
str

arch.unitroot.ZivotAndrews.valid_trends

property ZivotAndrews.valid_trends : list[str]
List of valid trend terms.

Return type
list[str]

arch.unitroot.ZivotAndrews.y

property ZivotAndrews.y : ndarray | DataFrame | Series
Returns the data used in the test statistic

Return type
Union[ndarray, DataFrame, Series]

4.3.5 arch.unitroot.VarianceRatio

class arch.unitroot.VarianceRatio(y, lags=2, trend='c', debiased=True, robust=True, overlap=True)
Variance Ratio test of a random walk.

Parameters

y : {ndarray, Series}
The data to test for a random walk

lags : int
The number of periods to used in the multi-period variance, which is the numerator of the test statistic. Must be at least 2

trend : {"n", "c"}, optional

“c” allows for a non-zero drift in the random walk, while “n” requires that the increments to y are mean 0

overlap : bool, optional

Indicates whether to use all overlapping blocks. Default is True. If False, the number of observations in y minus 1 must be an exact multiple of lags. If this condition is not satisfied, some values at the end of y will be discarded.

robust : bool, optional

Indicates whether to use heteroskedasticity robust inference. Default is True.

debiased : bool, optional

Indicates whether to use a debiased version of the test. Default is True. Only applicable if overlap is True.

Notes

The null hypothesis of a VR is that the process is a random walk, possibly plus drift. Rejection of the null with a positive test statistic indicates the presence of positive serial correlation in the time series.

Examples

```
>>> from arch.unitroot import VarianceRatio
>>> import pandas_datareader as pdr
>>> data = pdr.get_data_fred("DJIA", start="2010-1-1", end="2020-12-31")
>>> data = np.log(data.resample("M").last()) # End of month
>>> vr = VarianceRatio(data, lags=12)
>>> print("{0:0.4f}".format(vr.pvalue))
0.1370
```

References**Methods**

<code>summary()</code>	Summary of test, containing statistic, p-value and critical values
------------------------	--

arch.unitroot.VarianceRatio.summary**VarianceRatio.summary()**

Summary of test, containing statistic, p-value and critical values

Return type

Summary

Properties

<i>alternative_hypothesis</i>	The alternative hypothesis
<i>critical_values</i>	Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.
<i>debiased</i>	Sets or gets the indicator to use debiased variances in the ratio
<i>lags</i>	Sets or gets the number of lags used in the model.
<i>nobs</i>	The number of observations used when computing the test statistic.
<i>null_hypothesis</i>	The null hypothesis
<i>overlap</i>	Sets or gets the indicator to use overlapping returns in the long-period variance estimator
<i>pvalue</i>	Returns the p-value for the test statistic
<i>robust</i>	Sets or gets the indicator to use a heteroskedasticity robust variance estimator
<i>stat</i>	The test statistic for a unit root
<i>trend</i>	Sets or gets the deterministic trend term used in the test.
<i>valid_trends</i>	List of valid trend terms.
<i>vr</i>	The ratio of the long block lags-period variance to the 1-period variance
<i>y</i>	Returns the data used in the test statistic

arch.unitroot.VarianceRatio.alternative_hypothesis

property VarianceRatio.alternative_hypothesis : str

The alternative hypothesis

Return type

str

arch.unitroot.VarianceRatio.critical_values

property VarianceRatio.critical_values : dict[str, float]

Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.

Return type

dict[str, float]

arch.unitroot.VarianceRatio.debiased

property `VarianceRatio.debiased` : `bool`

Sets or gets the indicator to use debiased variances in the ratio

Return type
`bool`

arch.unitroot.VarianceRatio.lags

property `VarianceRatio.lags` : `int`

Sets or gets the number of lags used in the model. When bootstrap use DF-type regressions, lags is the number of lags in the regression model. When bootstrap use long-run variance estimators, lags is the number of lags used in the long-run variance estimator.

Return type
`int`

arch.unitroot.VarianceRatio.nobs

property `VarianceRatio.nobs` : `int`

The number of observations used when computing the test statistic. Accounts for loss of data due to lags for regression-based bootstrap.

Return type
`int`

arch.unitroot.VarianceRatio.null_hypothesis

property `VarianceRatio.null_hypothesis` : `str`

The null hypothesis

Return type
`str`

arch.unitroot.VarianceRatio.overlap

property `VarianceRatio.overlap` : `bool`

Sets or gets the indicator to use overlapping returns in the long-period variance estimator

Return type
`bool`

arch.unitroot.VarianceRatio.pvalue

property `VarianceRatio.pvalue` : `float`

Returns the p-value for the test statistic

Return type
`float`

arch.unitroot.VarianceRatio.robust

property `VarianceRatio.robust` : `bool`

Sets or gets the indicator to use a heteroskedasticity robust variance estimator

Return type
`bool`

arch.unitroot.VarianceRatio.stat

property `VarianceRatio.stat` : `float`

The test statistic for a unit root

Return type
`float`

arch.unitroot.VarianceRatio.trend

property `VarianceRatio.trend` : `str`

Sets or gets the deterministic trend term used in the test. See `valid_trends` for a list of supported trends

Return type
`str`

arch.unitroot.VarianceRatio.valid_trends

property `VarianceRatio.valid_trends` : `list[str]`

List of valid trend terms.

Return type
`list[str]`

arch.unitroot.VarianceRatio.vr

property `VarianceRatio.vr` : `float`

The ratio of the long block lags-period variance to the 1-period variance

Return type
`float`

arch.unitroot.VarianceRatio.y**property** VarianceRatio.y : ndarray | DataFrame | Series

Returns the data used in the test statistic

Return type

Union[ndarray, DataFrame, Series]

4.3.6 arch.unitroot.KPSS**class** arch.unitroot.KPSS(y, lags=None, trend='c')

Kwiatkowski, Phillips, Schmidt and Shin (KPSS) stationarity test

Parameters**y** : {ndarray, Series}

The data to test for stationarity

lags : int, optional

The number of lags to use in the Newey-West estimator of the long-run covariance. If omitted or None, the number of lags is calculated with the data-dependent method of Hobijn et al. (1998). See also Andrews (1991), Newey & West (1994), and Schwert (1989). Set lags=-1 to use the old method that only depends on the sample size, $12 * (\text{nobs}/100) ** (1/4)$.

trend : {'c', 'ct'}, optional**The trend component to include in the ADF test**

"c" - Include a constant (Default) "ct" - Include a constant and linear time trend

Notes

The null hypothesis of the KPSS test is that the series is weakly stationary and the alternative is that it is non-stationary. If the p-value is above a critical size, then the null cannot be rejected that there and the series appears stationary.

The p-values and critical values were computed using an extensive simulation based on 100,000,000 replications using series with 2,000 observations.

Examples

```
>>> from arch.unitroot import KPSS
>>> import numpy as np
>>> import statsmodels.api as sm
>>> data = sm.datasets.macrodta.load().data
>>> inflation = np.diff(np.log(data["cpi"]))
>>> kpss = KPSS(inflation)
>>> print("{0:0.4f}".format(kpss.stat))
0.2870
>>> print("{0:0.4f}".format(kpss.pvalue))
0.1473
>>> kpss.trend = "ct"
>>> print("{0:0.4f}".format(kpss.stat))
0.2075
```

(continues on next page)

(continued from previous page)

```
>>> print("{0:0.4f}".format(kpss.pvalue))
0.0128
```

References

Methods

<code>summary()</code>	Summary of test, containing statistic, p-value and critical values
------------------------	--

arch.unitroot.KPSS.summary

KPSS.**summary()**

Summary of test, containing statistic, p-value and critical values

Return type

Summary

Properties

<code>alternative_hypothesis</code>	The alternative hypothesis
<code>critical_values</code>	Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.
<code>lags</code>	Sets or gets the number of lags used in the model.
<code>nobs</code>	The number of observations used when computing the test statistic.
<code>null_hypothesis</code>	The null hypothesis
<code>pvalue</code>	Returns the p-value for the test statistic
<code>stat</code>	The test statistic for a unit root
<code>trend</code>	Sets or gets the deterministic trend term used in the test.
<code>valid_trends</code>	List of valid trend terms.
<code>y</code>	Returns the data used in the test statistic

arch.unitroot.KPSS.alternative_hypothesis

property KPSS.**alternative_hypothesis**: str

The alternative hypothesis

Return type

str

arch.unitroot.KPSS.critical_values

property KPSS.critical_values : dict[str, float]

Dictionary containing critical values specific to the test, number of observations and included deterministic trend terms.

Return type

dict[str, float]

arch.unitroot.KPSS.lags

property KPSS.lags : int

Sets or gets the number of lags used in the model. When bootstrap use DF-type regressions, lags is the number of lags in the regression model. When bootstrap use long-run variance estimators, lags is the number of lags used in the long-run variance estimator.

Return type

int

arch.unitroot.KPSS.nobs

property KPSS.nobs : int

The number of observations used when computing the test statistic. Accounts for loss of data due to lags for regression-based bootstrap.

Return type

int

arch.unitroot.KPSS.null_hypothesis

property KPSS.null_hypothesis : str

The null hypothesis

Return type

str

arch.unitroot.KPSS.pvalue

property KPSS.pvalue : float

Returns the p-value for the test statistic

Return type

float

arch.unitroot.KPSS.stat

property KPSS.stat : float

The test statistic for a unit root

Return type
float

arch.unitroot.KPSS.trend

property KPSS.trend : str

Sets or gets the deterministic trend term used in the test. See valid_trends for a list of supported trends

Return type
str

arch.unitroot.KPSS.valid_trends

property KPSS.valid_trends : list[str]

List of valid trend terms.

Return type
list[str]

arch.unitroot.KPSS.y

property KPSS.y : ndarray | DataFrame | Series

Returns the data used in the test statistic

Return type
Union[ndarray, DataFrame, Series]

4.3.7 Automatic Bandwidth Selection

auto_bandwidth(y[, kernel])

Automatic bandwidth selection of Andrews (1991) and Newey & West (1994).

arch.unitroot.auto_bandwidth

arch.unitroot.auto_bandwidth(y, kernel='ba')

Automatic bandwidth selection of Andrews (1991) and Newey & West (1994).

Parameters

y : {ndarray, Series}
Data on which to apply the bandwidth selection

kernel : str
The kernel function to use for selecting the bandwidth

- "ba", "bartlett", "nw": Bartlett kernel (default)

- "pa", "parzen", "gallant": Parzen kernel
- "qs", "andrews": Quadratic Spectral kernel

Returns

The estimated optimal bandwidth.

Return type

float

COINTEGRATION ANALYSIS

The module extended the single-series unit root testing to multiple series and cointegration testing and cointegrating vector estimation.

- Cointegrating Testing
 - Engle-Granger Test (*engle_granger*)
 - Phillips-Ouliaris Tests (*phillips_ouliaris*)
- Cointegrating Vector Estimation
 - Dynamic OLS (*DynamicOLS*)
 - Fully Modified OLS (*FullyModifiedOLS*)
 - Canonical Cointegrating Regression (*CanonicalCointegratingReg*)

5.1 Cointegration Testing

This setup code is required to run in an IPython notebook

```
[1]: %matplotlib inline
import matplotlib.pyplot as plt
import seaborn

seaborn.set_style("darkgrid")
plt.rc("figure", figsize=(16, 6))
plt.rc("savefig", dpi=90)
plt.rc("font", family="sans-serif")
plt.rc("font", size=14)
```

We will look at the spot prices of crude oil measured in Cushing, OK for West Texas Intermediate Crude, and Brent Crude. The underlying data in this data set come from the [U.S. Energy Information Administration](#).

```
[2]: import numpy as np
from arch.data import crude

data = crude.load()
log_price = np.log(data)

ax = log_price.plot()
xl = ax.set_xlim(log_price.index.min(), log_price.index.max())
```



We can verify these both of these series appear to contains unit roots using Augmented Dickey-Fuller tests. The p-values are large indicating that the null cannot be rejected.

```
[3]: from arch.unitroot import ADF
```

```
ADF(log_price.WTI, trend="c")
```

```
[3]: <class 'arch.unitroot.unitroot.ADF'>
      """
```

Augmented Dickey-Fuller Results

```
=====
Test Statistic      -1.780
P-value             0.391
Lags                 1
-----
```

Trend: Constant

Critical Values: -3.45 (1%), -2.87 (5%), -2.57 (10%)

Null Hypothesis: The process contains a unit root.

Alternative Hypothesis: The process is weakly stationary.

```
"""
```

```
[4]: ADF(log_price.Brent, trend="c")
```

```
[4]: <class 'arch.unitroot.unitroot.ADF'>
      """
```

Augmented Dickey-Fuller Results

```
=====
Test Statistic      -1.655
P-value             0.454
Lags                 1
-----
```

Trend: Constant

Critical Values: -3.45 (1%), -2.87 (5%), -2.57 (10%)

Null Hypothesis: The process contains a unit root.

Alternative Hypothesis: The process is weakly stationary.

(continues on next page)

(continued from previous page)

"""

The Engle-Granger test is a 2-step test that first estimates a cross-sectional regression, and then tests the residuals from this regression using an Augmented Dickey-Fuller distribution with modified critical values. The cross-sectional regression is

$$Y_t = X_t\beta + D_t\gamma + \epsilon_t$$

where Y_t and X_t combine to contain the set of variables being tested for cointegration and D_t are a set of deterministic regressors that might include a constant, a time trend, or a quadratic time trend. The trend is specified using `trend` as

- "n": No trend
- "c": Constant
- "ct": Constant and time trend
- "ctt": Constant, time and quadratic trends

Here we assume that that cointegrating relationship is exact so that no deterministics are needed.


```
[5]: from arch.unitroot import engle_granger

eg_test = engle_granger(log_price.WTI, log_price.Brent, trend="n")
eg_test
```

```
[5]: Engle-Granger Cointegration Test
Statistic: -3.4676471998477267
P-value: 0.006860702109284017
Null: No Cointegration, Alternative: Cointegration
ADF Lag length: 0
Trend: c
Estimated Root (+1): 0.9386946007157646
Distribution Order: 1
ID: 0x2352eeb6e50
```

The `plot` method can be used to plot the model residual. We see that while this appears to be mean 0, it might have a trend in it.

```
[6]: fig = eg_test.plot()
```



The estimated cointegrating vector is exposed through the `cointegrating_vector` property. Here we see it is very close to $[1, -1]$, indicating a simple no-arbitrage relationship.

```
[7]: eg_test.cointegrating_vector
```

```
[7]: WTI      1.000000
      Brent  -1.000621
      dtype: float64
```

We can rerun the test with both a constant and a time trend to see how this affects the conclusion. We firmly reject the null of no cointegration even with this alternative assumption.

```
[8]: eg_test = engle_granger(log_price.WTI, log_price.Brent, trend="ct")
      eg_test
```


```
[8]: Engle-Granger Cointegration Test
      Statistic: -5.83664970914174
      P-value: 2.3286206215070878e-05
      Null: No Cointegration, Alternative: Cointegration
      ADF Lag length: 0
      Trend: c
      Estimated Root (+1): 0.8400729995315473
      Distribution Order: 1
      ID: 0x235285d7340
```

```
[9]: eg_test.cointegrating_vector
```

```
[9]: WTI      1.000000
      Brent  -0.931769
      const  -0.296939
      trend   0.000185
      dtype: float64
```

The residuals are clearly mean zero but show evidence of a structural break around the financial crisis of 2008.

```
[10]: fig = eg_test.plot()
```




To investigate the changes in the 2008 financial crisis, we can re-run the test on only the pre-crisis period.

```
[11]: eg_test = engle_granger(log_price[:"2008"].WTI, log_price[:"2008"].Brent, trend="n")
      eg_test
```

```
[11]: Engle-Granger Cointegration Test
Statistic: -4.962489476284803
P-value: 2.054007070920808e-05
Null: No Cointegration, Alternative: Cointegration
ADF Lag length: 0
Trend: c
Estimated Root (+1): 0.8246009342909095
Distribution Order: 1
ID: 0x2352f312f70
```

These residuals look quite a bit better although it is possible the break in the cointegrating vector happened around 2005 when oil prices first surged.

```
[12]: fig = eg_test.plot()
ax = fig.get_axes()[0]
title = ax.set_title("Pre-2009 Cointegration Residual")
```



5.1.1 Phillips-Ouliaris

The Phillips-Ouliaris tests consists four distinct tests. Two are similar to the Engle-Granger test, only using a Phillips & Perron-like approach replaces the lags in the ADF test with a long-run variance estimator. The other two use variance-ratio like approaches to test. In both cases the test stabilizes when there is no cointegration and diverges due to singularity of the covariance matrix of the $I(1)$ time series when there is cointegration.

- Z_t - Like PP using the t-stat of the AR(1) coefficient in an AR(1) of the residual from the cross-sectional regression.
- Z_α - Like PP using $T(\alpha - 1)$ and a bias term from the same AR(1)
- P_u - A univariate variance ratio test.
- P_z - A multivariate variance ratio test.

The four test statistics all agree on the crude oil data.

The Z_t and Z_α test statistics are both based on the quantity $\gamma = \rho - 1$ from the regression $y_t = d_t\Delta + \rho y_{t-1} + \epsilon_t$. The null is rejected in favor of the alternative when $\gamma < 0$ so that the test statistic is *below* its critical value.

```
[13]: from arch.unitroot.cointegration import phillips_ouliaris
```

(continues on next page)

(continued from previous page)

```
po_zt_test = phillips_ouliaris(
    log_price.WTI, log_price.Brent, trend="c", test_type="Zt"
)
po_zt_test.summary()
```

```
[13]: <class 'statsmodels.iolib.summary.Summary'>
      """
      Phillips-Ouliaris Zt Cointegration Test
      =====
      Test Statistic          -5.357
      P-value                  0.000
      Kernel                   Bartlett
      Bandwidth                10.185
      -----

      Trend: Constant
      Critical Values: -3.06 (10%), -3.36 (5%), -3.93 (1%)
      Null Hypothesis: No Cointegration
      Alternative Hypothesis: Cointegration
      Distribution Order: 3
      """
```

```
[14]: po_za_test = phillips_ouliaris(
    log_price.WTI, log_price.Brent, trend="c", test_type="Za"
)
po_za_test.summary()
```

```
[14]: <class 'statsmodels.iolib.summary.Summary'>
      """
      Phillips-Ouliaris Za Cointegration Test
      =====
      Test Statistic          -53.531
      P-value                  0.000
      Kernel                   Bartlett
      Bandwidth                10.185
      -----

      Trend: Constant
      Critical Values: -16.95 (10%), -20.34 (5%), -27.76 (1%)
      Null Hypothesis: No Cointegration
      Alternative Hypothesis: Cointegration
      Distribution Order: 3
      """
```

The P_u and P_z statistics are variance ratios where under the null the numerator and denominator are balanced and so converge at the same rate. Under the alternative the denominator converges to zero and the statistic diverges, so that rejection of the null occurs when the test statistic is *above* a critical value.

```
[15]: po_pu_test = phillips_ouliaris(
    log_price.WTI, log_price.Brent, trend="c", test_type="Pu"
)
po_pu_test.summary()
```



```
[15]: <class 'statsmodels.iolib.summary.Summary'>
      """
      Phillips-Ouliaris Pu Cointegration Test
      =====
      Test Statistic          102.868
      P-value                  0.000
      Kernel                   Bartlett
      Bandwidth                14.648
      -----

      Trend: Constant
      Critical Values: 27.01 (10%), 32.93 (5%), 46.01 (1%)
      Null Hypothesis: No Cointegration
      Alternative Hypothesis: Cointegration
      Distribution Order: 2
      """
```


```
[16]: po_pz_test = phillips_ouliaris(
      log_price.WTI, log_price.Brent, trend="c", test_type="Pz"
      )
      po_pz_test.summary()
```

```
[16]: <class 'statsmodels.iolib.summary.Summary'>
      """
      Phillips-Ouliaris Pz Cointegration Test
      =====
      Test Statistic          114.601
      P-value                  0.000
      Kernel                   Bartlett
      Bandwidth                14.648
      -----

      Trend: Constant
      Critical Values: 45.39 (10%), 52.41 (5%), 67.39 (1%)
      Null Hypothesis: No Cointegration
      Alternative Hypothesis: Cointegration
      Distribution Order: 2
      """
```

The cointegrating residual is identical to the EG test since the first step is identical.

```
[17]: fig = po_zt_test.plot()
```



5.2 Cointegration Tests

<code>engle_granger(y, x[, trend, lags, max_lags, ...])</code>	Test for cointegration within a set of time series.
<code>phillips_ouliaris(y, x[, trend, test_type, ...])</code>	Test for cointegration within a set of time series.

5.2.1 `arch.unitroot.cointegration.engle_granger`

`arch.unitroot.cointegration.engle_granger(y, x, trend='c', *, lags=None, max_lags=None, method='bic')`

Test for cointegration within a set of time series.

Parameters

y : array_like

The left-hand-side variable in the cointegrating regression.

x : array_like

The right-hand-side variables in the cointegrating regression.

trend : {"n", "c", "ct", "ctt"}, default "c"

Trend to include in the cointegrating regression. Trends are:

- "n": No deterministic terms
- "c": Constant
- "ct": Constant and linear trend
- "ctt": Constant, linear and quadratic trends

lags : int, default None

The number of lagged differences to include in the Augmented Dickey-Fuller test used on the residuals of the

max_lags : int, default None

The maximum number of lags to consider when using automatic lag-length in the Augmented Dickey-Fuller regression.

method : {"aic", "bic", "tstat"}, default "bic"

The method used to select the number of lags included in the Augmented Dickey-Fuller regression.

Returns

Results of the Engle-Granger test.

Return type

EngleGrangerTestResults

See also

[*arch.unitroot.ADF*](#)

Augmented Dickey-Fuller testing.

[*arch.unitroot.PhillipsPerron*](#)

Phillips & Perron's unit root test.

[*arch.unitroot.cointegration.phillips_ouliaris*](#)

Phillips-Ouliaris tests of cointegration.

Notes

The model estimated is

$$Y_t = X_t\beta + D_t\gamma + \epsilon_t$$

where $Z_t = [Y_t, X_t]$ is being tested for cointegration. D_t is a set of deterministic terms that may include a constant, a time trend or a quadratic time trend.

The null hypothesis is that the series are not cointegrated.

The test is implemented as an ADF of the estimated residuals from the cross-sectional regression using a set of critical values that is determined by the number of assumed stochastic trends when the null hypothesis is true.

5.2.2 *arch.unitroot.cointegration.phillips_ouliaris*

```
arch.unitroot.cointegration.phillips_ouliaris(y, x, trend='c', *, test_type='Zt', kernel=bartlett,
                                              bandwidth=None, force_int=False)
```

Test for cointegration within a set of time series.

Parameters

y : *array_like*

The left-hand-side variable in the cointegrating regression.

x : *array_like*

The right-hand-side variables in the cointegrating regression.

trend : {"n", "c", "ct", "ctt"}, default "c"

Trend to include in the cointegrating regression. Trends are:

- "n": No deterministic terms
- "c": Constant
- "ct": Constant and linear trend

- "ctt": Constant, linear and quadratic trends

test_type : {"Za", "Zt", "Pu", "Pz"}, default "Zt"

The test statistic to compute. Supported options are:

- "Za": The Z test based on the the debiased AR(1) coefficient.
- "Zt": The Zt test based on the t-statistic from an AR(1).
- "Pu": The P variance-ratio test.
- "Pz": The Pz test of the trace of the product of an estimate of the long-run residual variance and the inner-product of the data.

See the notes for details on the test.

kernel : **str**, default "bartlett"

The string name of any of any known kernel-based long-run covariance estimators. Common choices are "bartlett" for the Bartlett kernel (Newey-West), "parzen" for the Parzen kernel and "quadratic-spectral" for the Quadratic Spectral kernel.

bandwidth : **int**, default None

The bandwidth to use. If not provided, the optimal bandwidth is estimated from the data. Setting the bandwidth to 0 and using "unadjusted" produces the classic OLS covariance estimator. Setting the bandwidth to 0 and using "robust" produces White's covariance estimator.

force_int : **bool**, default False

Whether the force the estimated optimal bandwidth to be an integer.

Returns

Results of the Phillips-Ouliaris test.

Return type

PhillipsOuliarisTestResults

See also

[*arch.unitroot.ADF*](#)

Augmented Dickey-Fuller testing.

[*arch.unitroot.PhillipsPerron*](#)

Phillips & Perron's unit root test.

[*arch.unitroot.cointegration.engle_granger*](#)

Engle & Granger's cointegration test.

Notes

Warning

The critical value simulation is on-going and so the critical values may change slightly as more simulations are completed. These are still based on far more simulations (minimum 2,000,000) than were possible in 1990 (5000) that are reported in¹.

Supports 4 distinct tests.

¹ Phillips, P. C., & Ouliaris, S. (1990). Asymptotic properties of residual based tests for cointegration. *Econometrica: Journal of the Econometric Society*, 165-193.

Define the cross-sectional regression

$$y_t = x_t\beta + d_t\gamma + u_t$$

where d_t are any included deterministic terms. Let $\hat{u}_t = y_t - x_t\hat{\beta} + d_t\hat{\gamma}$.

The Z and Z_t statistics are defined as

$$\begin{aligned}\hat{Z}_\alpha &= T \times z \\ \hat{Z}_t &= \frac{\hat{\sigma}_u}{\hat{\omega}^2} \times \sqrt{T}z \\ z &= (\hat{\alpha} - 1) - \hat{\omega}_1^2 / \hat{\sigma}_u^2\end{aligned}$$

where $\hat{\sigma}_u^2 = T^{-1} \sum_{t=2}^T \hat{u}_t^2$, $\hat{\omega}_1^2$ is an estimate of the one-sided strict autocovariance, and $\hat{\omega}^2$ is an estimate of the long-run variance of the process.

The \hat{P}_u variance-ratio statistic is defined as

$$\hat{P}_u = \frac{\hat{\omega}_{11.2}}{\tilde{\sigma}_u^2}$$

where $\tilde{\sigma}_u^2 = T^{-1} \sum_{t=1}^T \hat{u}_t^2$ and

$$\hat{\omega}_{11.2} = \hat{\omega}_{11} - \hat{\omega}_{21}' \hat{\Omega}_{22}^{-1} \hat{\omega}_{21}$$

and

$$\hat{\Omega} = \begin{bmatrix} \hat{\omega}_{11} & \hat{\omega}_{21}' \\ \hat{\omega}_{21} & \hat{\Omega}_{22} \end{bmatrix}$$

is an estimate of the long-run covariance of ξ_t , the residuals from an VAR(1) on $z_t = [y_t, z_t]$ that includes and trends included in the test.

$$z_t = \Phi z_{t-1} + \xi_\tau$$

The final test statistic is defined

$$\hat{P}_z = T \times \text{tr}(\hat{\Omega} M_{zz}^{-1})$$

where $M_{zz} = \sum_{t=1}^T \tilde{z}_t' \tilde{z}_t$, \tilde{z}_t is the vector of data $z_t = [y_t, x_t]$ detrended using any trend terms included in the test, $\tilde{z}_t = z_t - d_t \hat{\kappa}$ and $\hat{\Omega}$ is defined above.

The specification of the \hat{P}_z test statistic when trend is “n” differs from the expression in [Page 392, 1](#). We recenter z_t by subtracting the first observation, so that $\tilde{z}_t = z_t - z_1$. This is needed to ensure that the initial value does not affect the distribution under the null. When the trend is anything other than “n”, this set is not needed and the test statistics is identical whether the first observation is subtracted or not.

References

5.3 Cointegrating Vector Estimation

<i>DynamicOLS</i>(y, x[, trend, lags, leads, ...])	Dynamic OLS (DOLS) cointegrating vector estimation
<i>FullyModifiedOLS</i>(y, x[, trend, x_trend])	Fully Modified OLS cointegrating vector estimation.
<i>CanonicalCointegratingReg</i>(y, x[, trend, x_trend])	Canonical Cointegrating Regression cointegrating vector estimation.

5.3.1 arch.unitroot.cointegration.DynamicOLS

```
class arch.unitroot.cointegration.DynamicOLS(y, x, trend='c', lags=None, leads=None, common=False,
                                             max_lag=None, max_lead=None, method='bic')
```

Dynamic OLS (DOLS) cointegrating vector estimation

Parameters

y : array_like

The left-hand-side variable in the cointegrating regression.

x : array_like

The right-hand-side variables in the cointegrating regression.

trend : {"n", "c", "ct", "ctt"}, default "c"

Trend to include in the cointegrating regression. Trends are:

- "n": No deterministic terms
- "c": Constant
- "ct": Constant and linear trend
- "ctt": Constant, linear and quadratic trends

lags : int, default None

The number of lags to include in the model. If None, the optimal number of lags is chosen using method.

leads : int, default None

The number of leads to include in the model. If None, the optimal number of leads is chosen using method.

common : bool, default False

Flag indicating that lags and leads should be restricted to the same value. When common is None, lags must equal leads and max_lag must equal max_lead.

max_lag : int, default None

The maximum lag to consider. See Notes for value used when None.

max_lead : int, default None

The maximum lead to consider. See Notes for value used when None.

method : {"aic", "bic", "hqic"}, default "bic"

The method used to select lag length when lags or leads is None.

- "aic" - Akaike Information Criterion
- "hqic" - Hannan-Quinn Information Criterion
- "bic" - Schwartz/Bayesian Information Criterion

Notes

The cointegrating vector is estimated from the regression

$$Y_t = D_t\delta + X_t\beta + \Delta X_t\gamma + \sum_{i=1}^p \Delta X_{t-i}\kappa_i + \sum_{j=1}^q \Delta X_{t+j}\lambda_j + \epsilon_t$$

where p is the lag length and q is the lead length. D_t is a vector containing the deterministic terms, if any. All specifications include the contemporaneous difference ΔX_t .

When lag lengths are not provided, the optimal lag length is chosen to minimize an Information Criterion of the form

$$\ln(\hat{\sigma}^2) + k \frac{c}{T}$$

where c is 2 for Akaike, $2 \ln \ln T$ for Hannan-Quinn and $\ln T$ for Schwartz/Bayesian.

See¹ and² for further details.

References

Methods

<code>fit(cov_type, kernel, bandwidth, ...)</code>	Estimate the Dynamic OLS regression
--	-------------------------------------

arch.unitroot.cointegration.DynamicOLS.fit

DynamicOLS.**fit**(cov_type='unadjusted', kernel='bartlett', bandwidth=None, force_int=False, df_adjust=False)

Estimate the Dynamic OLS regression

Parameters

cov_type : str, default "unadjusted"

Either “unadjusted” (or is equivalent “homoskedastic”) or “robust” (or its equivalent “kernel”).

kernel : str, default "bartlett"

The string name of any of any known kernel-based long-run covariance estimators. Common choices are “bartlett” for the Bartlett kernel (Newey-West), “parzen” for the Parzen kernel and “quadratic-spectral” for the Quadratic Spectral kernel.

bandwidth : int, default None

The bandwidth to use. If not provided, the optimal bandwidth is estimated from the data. Setting the bandwidth to 0 and using “unadjusted” produces the classic OLS covariance estimator. Setting the bandwidth to 0 and using “robust” produces White’s covariance estimator.

force_int : bool, default False

Whether the force the estimated optimal bandwidth to be an integer.

¹ Saikkonen, P. (1992). Estimation and testing of cointegrated systems by an autoregressive approximation. *Econometric theory*, 8(1), 1-27.

² Stock, J. H., & Watson, M. W. (1993). A simple estimator of cointegrating vectors in higher order integrated systems. *Econometrica: Journal of the Econometric Society*, 783-820.

df_adjust : **bool**, default **False**

Whether to adjust the parameter covariance to account for the number of parameters estimated in the regression. If true, the parameter covariance estimator is multiplied by $T/(T-k)$ where k is the number of regressors in the model.

Returns

The estimation results.

Return type

DynamicOLSResults

See also

[*arch.unitroot.cointegration.EngleGranger*](#)

Cointegration testing using the Engle-Granger methodology

[*statsmodels.regression.linear_model.OLS*](#)

Ordinary Least Squares regression.

Notes

When using the unadjusted covariance, the parameter covariance is estimated as

$$T^{-1} \hat{\sigma}_{HAC}^2 \hat{\Sigma}_{ZZ}^{-1}$$

where $\hat{\sigma}_{HAC}^2$ is an estimator of the long-run variance of the regression error and $\hat{\Sigma}_{ZZ} = T^{-1} Z'Z$. Z_t is a vector that includes all terms in the regression (i.e., deterministics, cross-sectional, leads and lags) When using the robust covariance, the parameter covariance is estimated as

$$T^{-1} \hat{\Sigma}_{ZZ}^{-1} \hat{S}_{HAC} \hat{\Sigma}_{ZZ}^{-1}$$

where \hat{S}_{HAC} is a Heteroskedasticity-Autocorrelation Consistent estimator of the covariance of the regression scores $Z_t \epsilon_t$.

5.3.2 [*arch.unitroot.cointegration.FullyModifiedOLS*](#)

class [*arch.unitroot.cointegration.FullyModifiedOLS*](#)(*y*, *x*, *trend*='c', *x_trend*=**None**)

Fully Modified OLS cointegrating vector estimation.

Parameters

y : **array_like**

The left-hand-side variable in the cointegrating regression.

x : **array_like**

The right-hand-side variables in the cointegrating regression.

trend : **{{"n"}, "c", "ct", "ctt"}}**, default **"c"**

Trend to include in the cointegrating regression. Trends are:

- "n": No deterministic terms
- "c": Constant
- "ct": Constant and linear trend

- "ctt": Constant, linear and quadratic trends

x_trend : {None, "c", "ct", "ctt"}, default None

Trends that affects affect the x-data but do not appear in the cointegrating regression. x_trend must be at least as large as trend, so that if trend is "ct", x_trend must be either "ct" or "ctt".

Notes

The cointegrating vector is estimated from the regressions

$$\begin{aligned} Y_t &= D_{1t}\delta + X_t\beta + \eta_{1t} \\ X_t &= D_{1t}\Gamma_1 + D_{2t}\Gamma_2 + \epsilon_{2t} \\ \eta_{2t} &= \Delta\epsilon_{2t} \end{aligned}$$

or if estimated in differences, the last two lines are

$$\Delta X_t = \Delta D_{1t}\Gamma_1 + \Delta D_{2t}\Gamma_2 + \eta_{2t}$$

Define the vector of residuals as $\eta = (\eta_{1t}, \eta_{2t}')'$, and the long-run covariance

$$\Omega = \sum_{h=-\infty}^{\infty} E[\eta_t \eta_{t-h}']$$

and the one-sided long-run covariance matrix

$$\Lambda_0 = \sum_{h=0}^{\infty} E[\eta_t \eta_{t-h}']$$

The covariance matrices are partitioned into a block form

$$\Omega = \begin{bmatrix} \omega_{11} & \omega_{12} \\ \omega_{12}' & \Omega_{22} \end{bmatrix}$$

The cointegrating vector is then estimated using modified data

$$Y_t^* = Y_t - \hat{\omega}_{12}\hat{\Omega}_{22}^{-1}\hat{\eta}_{2t}$$

as

$$\hat{\theta} = \begin{bmatrix} \hat{\gamma}_1 \\ \hat{\beta} \end{bmatrix} = \left(\sum_{t=2}^T Z_t Z_t' \right)^{-1} \left(\sum_{t=2}^T Z_t Y_t^* - T \begin{bmatrix} 0 \\ \lambda_{12}^* \end{bmatrix} \right)$$

where the bias term is defined

$$\lambda_{12}^* = \hat{\lambda}_{12} - \hat{\omega}_{12}\hat{\Omega}_{22}^{-1}\hat{\omega}_{21}$$

See¹ for further details.

References

Methods

fit([kernel, bandwidth, force_int, diff, ...])

Estimate the cointegrating vector.

¹ Hansen, B. E., & Phillips, P. C. (1990). Estimation and inference in models of cointegration: A simulation study. *Advances in Econometrics*, 8(1989), 225-248.

arch.unitroot.cointegration.FullyModifiedOLS.fit

```
FullyModifiedOLS.fit(kernel='bartlett', bandwidth=None, force_int=True, diff=False,
                     df_adjust=False)
```

Estimate the cointegrating vector.

Parameters

diff : **bool**, default **False**

Use differenced data to estimate the residuals.

kernel : **str**, default **"bartlett"**

The string name of any of any known kernel-based long-run covariance estimators. Common choices are “bartlett” for the Bartlett kernel (Newey-West), “parzen” for the Parzen kernel and “quadratic-spectral” for the Quadratic Spectral kernel.

bandwidth : **int**, default **None**

The bandwidth to use. If not provided, the optimal bandwidth is estimated from the data. Setting the bandwidth to 0 and using “unadjusted” produces the classic OLS covariance estimator. Setting the bandwidth to 0 and using “robust” produces White’s covariance estimator.

force_int : **bool**, default **False**

Whether the force the estimated optimal bandwidth to be an integer.

df_adjust : **bool**, default **False**

Whether the adjust the parameter covariance to account for the number of parameters estimated in the regression. If true, the parameter covariance estimator is multiplied by $T/(T-k)$ where k is the number of regressors in the model.

Returns

The estimation results instance.

Return type

CointegrationAnalysisResults

5.3.3 arch.unitroot.cointegration.CanonicalCointegratingReg

```
class arch.unitroot.cointegration.CanonicalCointegratingReg(y, x, trend='c', x_trend=None)
```

Canonical Cointegrating Regression cointegrating vector estimation.

Parameters

y : **array_like**

The left-hand-side variable in the cointegrating regression.

x : **array_like**

The right-hand-side variables in the cointegrating regression.

trend : **{{"n", "c", "ct", "ctt"}}**, default **"c"**

Trend to include in the cointegrating regression. Trends are:

- “n”: No deterministic terms
- “c”: Constant
- “ct”: Constant and linear trend
- “ctt”: Constant, linear and quadratic trends

x_trend : {None, "c", "ct", "ctt"}, default None

Trends that affects affect the x-data but do not appear in the cointegrating regression. x_trend must be at least as large as trend, so that if trend is “ct”, x_trend must be either “ct” or “ctt”.

Notes

The cointegrating vector is estimated from the regressions

$$\begin{aligned} Y_t &= D_{1t}\delta + X_t\beta + \eta_{1t} \\ X_t &= D_{1t}\Gamma_1 + D_{2t}\Gamma_2 + \epsilon_{2t} \\ \eta_{2t} &= \Delta\epsilon_{2t} \end{aligned}$$

or if estimated in differences, the last two lines are

$$\Delta X_t = \Delta D_{1t}\Gamma_1 + \Delta D_{2t}\Gamma_2 + \eta_{2t}$$

Define the vector of residuals as $\eta = (\eta_{1t}, \eta_{2t}')'$, and the long-run covariance

$$\Omega = \sum_{h=-\infty}^{\infty} E[\eta_t \eta_{t-h}']$$

and the one-sided long-run covariance matrix

$$\Lambda_0 = \sum_{h=0}^{\infty} E[\eta_t \eta_{t-h}']$$

The covariance matrices are partitioned into a block form

$$\Omega = \begin{bmatrix} \omega_{11} & \omega_{12} \\ \omega_{12}' & \Omega_{22} \end{bmatrix}$$

The cointegrating vector is then estimated using modified data

$$\begin{aligned} X_t^* &= X_t - \hat{\Lambda}_2' \hat{\Sigma}^{-1} \hat{\eta}_t \\ Y_t^* &= Y_t - (\hat{\Sigma}^{-1} \hat{\Lambda}_2 \hat{\beta} + \hat{\kappa})' \hat{\eta}_t \end{aligned}$$

where $\hat{\kappa} = (0, \hat{\Omega}_{22}^{-1} \hat{\Omega}_{12}')$ and the regression

$$Y_t^* = D_{1t}\delta + X_t^*\beta + \eta_{1t}^*$$

See¹ for further details.

References

Methods

<code>fit(kernel, bandwidth, force_int, diff, ...)</code>	Estimate the cointegrating vector.
---	------------------------------------

¹ Park, J. Y. (1992). Canonical cointegrating regressions. *Econometrica: Journal of the Econometric Society*, 119-143.

arch.unitroot.cointegration.CanonicalCointegratingReg.fit

```
CanonicalCointegratingReg.fit(kernel='bartlett', bandwidth=None, force_int=True, diff=False,
                              df_adjust=False)
```

Estimate the cointegrating vector.

Parameters

diff : **bool**, default **False**

Use differenced data to estimate the residuals.

kernel : **str**, default **"bartlett"**

The string name of any of any known kernel-based long-run covariance estimators. Common choices are “bartlett” for the Bartlett kernel (Newey-West), “parzen” for the Parzen kernel and “quadratic-spectral” for the Quadratic Spectral kernel.

bandwidth : **int**, default **None**

The bandwidth to use. If not provided, the optimal bandwidth is estimated from the data. Setting the bandwidth to 0 and using “unadjusted” produces the classic OLS covariance estimator. Setting the bandwidth to 0 and using “robust” produces White’s covariance estimator.

force_int : **bool**, default **False**

Whether the force the estimated optimal bandwidth to be an integer.

df_adjust : **bool**, default **False**

Whether the adjust the parameter covariance to account for the number of parameters estimated in the regression. If true, the parameter covariance estimator is multiplied by $T/(T-k)$ where k is the number of regressors in the model.

Returns

The estimation results instance.

Return type

CointegrationAnalysisResults

5.3.4 Results Classes

CointegrationAnalysisResults(params, cov, ...)

<i>DynamicOLSResults</i> (params, cov, resid, lags, ...)	Estimation results for Dynamic OLS models
--	---

<i>EngleGrangerTestResults</i> (stat, pvalue, crit_vals)	Results class for Engle-Granger cointegration tests.
--	--

<i>PhillipsOuliarisTestResults</i> (stat, pvalue, ...)	
--	--

arch.unitroot.cointegration.CointegrationAnalysisResults

```
class arch.unitroot.cointegration.CointegrationAnalysisResults(params, cov, resid, omega_112,
                                                                kernel_est, num_x, trend,
                                                                df_adjust, rsquared, rsquared_adj,
                                                                estimator_type)
```

Methods

<code>summary()</code>	Summary of the model, containing estimated parameters and std.
------------------------	--

`arch.unitroot.cointegration.CointegrationAnalysisResults.summary`

`CointegrationAnalysisResults.summary()`

Summary of the model, containing estimated parameters and std. errors

Returns

A summary instance with method that support export to text, csv or latex.

Return type

Summary

Properties

<code>bandwidth</code>	The bandwidth used in the parameter covariance estimation
<code>cov</code>	The estimated parameter covariance of the cointegrating vector
<code>kernel</code>	The kernel used to estimate the covariance
<code>long_run_variance</code>	Long-run variance estimate used in the parameter covariance estimator
<code>params</code>	The estimated parameters of the cointegrating vector
<code>pvalues</code>	P-value of the parameters in the cointegrating vector
<code>resid</code>	The model residuals
<code>residual_variance</code>	The variance of the regression residual.
<code>rsquared</code>	The model R^2
<code>rsquared_adj</code>	The degree-of-freedom adjusted R^2
<code>std_errors</code>	Standard errors of the parameters in the cointegrating vector
<code>tvalues</code>	T-statistics of the parameters in the cointegrating vector

`arch.unitroot.cointegration.CointegrationAnalysisResults.bandwidth`

property `CointegrationAnalysisResults.bandwidth`: float

The bandwidth used in the parameter covariance estimation

Return type

float

arch.unitroot.cointegration.CointegrationAnalysisResults.cov

property CointegrationAnalysisResults.cov : DataFrame

The estimated parameter covariance of the cointegrating vector

Return type

DataFrame

arch.unitroot.cointegration.CointegrationAnalysisResults.kernel

property CointegrationAnalysisResults.kernel : str

The kernel used to estimate the covariance

Return type

str

arch.unitroot.cointegration.CointegrationAnalysisResults.long_run_variance

property CointegrationAnalysisResults.long_run_variance : float

Long-run variance estimate used in the parameter covariance estimator

Return type

float

arch.unitroot.cointegration.CointegrationAnalysisResults.params

property CointegrationAnalysisResults.params : Series

The estimated parameters of the cointegrating vector

Return type

Series

arch.unitroot.cointegration.CointegrationAnalysisResults.pvalues

property CointegrationAnalysisResults.pvalues : Series

P-value of the parameters in the cointegrating vector

arch.unitroot.cointegration.CointegrationAnalysisResults.resid

property CointegrationAnalysisResults.resid : Series

The model residuals

Return type

Series

arch.unitroot.cointegration.CointegrationAnalysisResults.residual_variance**property** CointegrationAnalysisResults.residual_variance : float

The variance of the regression residual.

Returns

The estimated residual variance.

Return type

float

Notes

The residual variance only accounts for the short-run variance of the residual and does not account for any autocorrelation. It is defined as

$$\hat{\sigma}^2 = T^{-1} \sum_{t=p}^{T-q} \hat{\epsilon}_t^2$$

If *df_adjust* is True, then the estimator is rescaled by $T/(T-m)$ where *m* is the number of regressors in the model.

arch.unitroot.cointegration.CointegrationAnalysisResults.rsquared**property** CointegrationAnalysisResults.rsquared : floatThe model R^2 **Return type**

float

arch.unitroot.cointegration.CointegrationAnalysisResults.rsquared_adj**property** CointegrationAnalysisResults.rsquared_adj : floatThe degree-of-freedom adjusted R^2 **Return type**

float

arch.unitroot.cointegration.CointegrationAnalysisResults.std_errors**property** CointegrationAnalysisResults.std_errors : Series

Standard errors of the parameters in the cointegrating vector

arch.unitroot.cointegration.CointegrationAnalysisResults.tvalues

property CointegrationAnalysisResults.tvalues : Series

T-statistics of the parameters in the cointegrating vector

arch.unitroot.cointegration.DynamicOLSResults

class arch.unitroot.cointegration.DynamicOLSResults(params, cov, resid, lags, leads, cov_type, kernel_est, num_x, trend, reg_results, df_adjust)

Estimation results for Dynamic OLS models

Parameters

params : Series

The estimated model parameters.

cov : DataFrame

The estimated parameter covariance.

resid : Series

The model residuals.

lags : int

The number of lags included in the model.

leads : int

The number of leads included in the model.

cov_type : str

The type of the parameter covariance estimator used.

kernel_est : CovarianceEstimator

The covariance estimator instance used to estimate the parameter covariance.

reg_results : RegressionResults

Regression results from fitting statsmodels OLS.

df_adjust : bool

Whether to degree of freedom adjust the estimator.

Methods

summary([full])

Summary of the model, containing estimated parameters and std.

arch.unitroot.cointegration.DynamicOLSResults.summary

DynamicOLSResults.summary(full=False)

Summary of the model, containing estimated parameters and std. errors

Parameters

full : bool, default False

Flag indicating whether to include all estimated parameters (True) or only the parameters of the cointegrating vector

Returns

A summary instance with method that support export to text, csv or latex.

Return type

Summary

Properties

<i>bandwidth</i>	The bandwidth used in the parameter covariance estimation
<i>cov</i>	The estimated parameter covariance of the cointegrating vector
<i>cov_type</i>	The type of parameter covariance estimator used
<i>full_cov</i>	Parameter covariance of the all model parameters, incl.
<i>full_params</i>	The complete set of parameters, including leads and lags
<i>kernel</i>	The kernel used to estimate the covariance
<i>lags</i>	The number of lags included in the model
<i>leads</i>	The number of leads included in the model
<i>long_run_variance</i>	The long-run variance of the regression residual.
<i>params</i>	The estimated parameters of the cointegrating vector
<i>pvalues</i>	P-value of the parameters in the cointegrating vector
<i>resid</i>	The model residuals
<i>residual_variance</i>	The variance of the regression residual.
<i>rsquared</i>	The model R^2
<i>rsquared_adj</i>	The degree-of-freedom adjusted R^2
<i>std_errors</i>	Standard errors of the parameters in the cointegrating vector
<i>tvalues</i>	T-statistics of the parameters in the cointegrating vector

arch.unitroot.cointegration.DynamicOLSResults.bandwidth

property `DynamicOLSResults.bandwidth`: float

The bandwidth used in the parameter covariance estimation

Return type

float

arch.unitroot.cointegration.DynamicOLSResults.cov

property `DynamicOLSResults.cov`: DataFrame

The estimated parameter covariance of the cointegrating vector

Return type

DataFrame

arch.unitroot.cointegration.DynamicOLSResults.cov_type

property `DynamicOLSResults.cov_type` : `str`

The type of parameter covariance estimator used

Return type

`str`

arch.unitroot.cointegration.DynamicOLSResults.full_cov

property `DynamicOLSResults.full_cov` : `DataFrame`

Parameter covariance of the all model parameters, incl. leads and lags

Return type

`DataFrame`

arch.unitroot.cointegration.DynamicOLSResults.full_params

property `DynamicOLSResults.full_params` : `Series`

The complete set of parameters, including leads and lags

Return type

`Series`

arch.unitroot.cointegration.DynamicOLSResults.kernel

property `DynamicOLSResults.kernel` : `str`

The kernel used to estimate the covariance

Return type

`str`

arch.unitroot.cointegration.DynamicOLSResults.lags

property `DynamicOLSResults.lags` : `int`

The number of lags included in the model

Return type

`int`

arch.unitroot.cointegration.DynamicOLSResults.leads

property `DynamicOLSResults.leads` : `int`

The number of leads included in the model

Return type

`int`

arch.unitroot.cointegration.DynamicOLSResults.long_run_variance**property** `DynamicOLSResults.long_run_variance` : `float`

The long-run variance of the regression residual.

Returns

The estimated long-run variance of the residual.

Return type`float`**Notes**

The long-run variance is estimated from the model residuals using the same kernel used to estimate the parameter covariance.

If *df_adjst* is True, then the estimator is rescaled by $T/(T-m)$ where *m* is the number of regressors in the model.

arch.unitroot.cointegration.DynamicOLSResults.params**property** `DynamicOLSResults.params` : `Series`

The estimated parameters of the cointegrating vector

Return type`Series`**arch.unitroot.cointegration.DynamicOLSResults.pvalues****property** `DynamicOLSResults.pvalues` : `Series`

P-value of the parameters in the cointegrating vector

arch.unitroot.cointegration.DynamicOLSResults.resid**property** `DynamicOLSResults.resid` : `Series`

The model residuals

Return type`Series`**arch.unitroot.cointegration.DynamicOLSResults.residual_variance****property** `DynamicOLSResults.residual_variance` : `float`

The variance of the regression residual.

Returns

The estimated residual variance.

Return type`float`

Notes

The residual variance only accounts for the short-run variance of the residual and does not account for any autocorrelation. It is defined as

$$\hat{\sigma}^2 = T^{-1} \sum_{t=p}^{T-q} \hat{\epsilon}_t^2$$

If `df_adjust` is True, then the estimator is rescaled by $T/(T-m)$ where m is the number of regressors in the model.

`arch.unitroot.cointegration.DynamicOLSResults.rsquared`

property `DynamicOLSResults.rsquared` : float

The model R^2

Return type
float

`arch.unitroot.cointegration.DynamicOLSResults.rsquared_adj`

property `DynamicOLSResults.rsquared_adj` : float

The degree-of-freedom adjusted R^2

Return type
float

`arch.unitroot.cointegration.DynamicOLSResults.std_errors`

property `DynamicOLSResults.std_errors` : Series

Standard errors of the parameters in the cointegrating vector

`arch.unitroot.cointegration.DynamicOLSResults.tvalues`

property `DynamicOLSResults.tvalues` : Series

T-statistics of the parameters in the cointegrating vector

`arch.unitroot.cointegration.EngleGrangerTestResults`

```
class arch.unitroot.cointegration.EngleGrangerTestResults(stat, pvalue, crit_vals,
                                                         null='No Cointegration',
                                                         alternative='Cointegration', trend='c',
                                                         order=2, adf=None, xsection=None)
```

Results class for Engle-Granger cointegration tests.

Parameters

stat : float
The Engle-Granger test statistic.

pvalue : float

The pvalue of the Engle-Granger test statistic.

crit_vals : Series

The critical values of the Engle-Granger specific to the sample size and model dimension.

null : str

The null hypothesis.

alternative : str

The alternative hypothesis.

trend : str

The model's trend description.

order : int

The number of stochastic trends in the null distribution.

adf : ADF

The ADF instance used to perform the test and lag selection.

xsection : RegressionResults

The OLS results used in the cross-sectional regression.

Methods

<code>plot([axes, title])</code>	Plot the cointegration residuals.
<code>summary()</code>	Summary of test, containing statistic, p-value and critical values

arch.unitroot.cointegration.EngleGrangerTestResults.plot

`EngleGrangerTestResults.plot(axes=None, title=None)`

Plot the cointegration residuals.

Parameters

axes : Axes, default None

matplotlib axes instance to hold the figure.

title : str, default None

Title for the figure.

Returns

The matplotlib Figure instance.

Return type

Figure

arch.unitroot.cointegration.EngleGrangerTestResults.summary**EngleGrangerTestResults.summary()**

Summary of test, containing statistic, p-value and critical values

Return type

Summary

Properties

<i>alternative_hypothesis</i>	The alternative hypothesis
<i>cointegrating_vector</i>	The estimated cointegrating vector.
<i>critical_values</i>	Critical Values
<i>distribution_order</i>	The number of stochastic trends under the null hypothesis.
<i>lags</i>	The number of lags used in the Augmented Dickey-Fuller regression.
<i>max_lags</i>	The maximum number of lags used in the lag-length selection.
<i>name</i>	Sets or gets the name of the cointegration test
<i>null_hypothesis</i>	The null hypothesis
<i>pvalue</i>	The p-value of the test statistic.
<i>resid</i>	The residual from the cointegrating regression.
<i>rho</i>	The estimated coefficient in the Dickey-Fuller Test
<i>stat</i>	The test statistic.
<i>trend</i>	The trend used in the cointegrating regression

arch.unitroot.cointegration.EngleGrangerTestResults.alternative_hypothesis**property** EngleGrangerTestResults.alternative_hypothesis : str

The alternative hypothesis

Return type

str

arch.unitroot.cointegration.EngleGrangerTestResults.cointegrating_vector**property** EngleGrangerTestResults.cointegrating_vector : Series

The estimated cointegrating vector.

Return type

Series

arch.unitroot.cointegration.EngleGrangerTestResults.critical_values**property** EngleGrangerTestResults.critical_values : Series

Critical Values

Returns

Series with three keys, 1, 5 and 10 containing the critical values of the test statistic.

Return type

Series

arch.unitroot.cointegration.EngleGrangerTestResults.distribution_order**property** EngleGrangerTestResults.distribution_order : int

The number of stochastic trends under the null hypothesis.

Return type

int

arch.unitroot.cointegration.EngleGrangerTestResults.lags**property** EngleGrangerTestResults.lags : int

The number of lags used in the Augmented Dickey-Fuller regression.

Return type

int

arch.unitroot.cointegration.EngleGrangerTestResults.max_lags**property** EngleGrangerTestResults.max_lags : int | None

The maximum number of lags used in the lag-length selection.

Return type

Optional[int]

arch.unitroot.cointegration.EngleGrangerTestResults.name**property** EngleGrangerTestResults.name : str

Sets or gets the name of the cointegration test

Return type

str

arch.unitroot.cointegration.EngleGrangerTestResults.null_hypothesis

property EngleGrangerTestResults.null_hypothesis : str

The null hypothesis

Return type

str

arch.unitroot.cointegration.EngleGrangerTestResults.pvalue

property EngleGrangerTestResults.pvalue : float

The p-value of the test statistic.

Return type

float

arch.unitroot.cointegration.EngleGrangerTestResults.resid

property EngleGrangerTestResults.resid : Series

The residual from the cointegrating regression.

Return type

Series

arch.unitroot.cointegration.EngleGrangerTestResults.rho

property EngleGrangerTestResults.rho : float

The estimated coefficient in the Dickey-Fuller Test

Returns

The coefficient.

Return type

float

Notes

The value returned is $\hat{\rho} = \hat{\gamma} + 1$ from the ADF regression

$$\Delta y_t = \gamma y_{t-1} + \sum_{i=1}^p \delta_i \Delta y_{t-i} + \epsilon_t$$

arch.unitroot.cointegration.EngleGrangerTestResults.stat**property** EngleGrangerTestResults.stat : float

The test statistic.

Return type

float

arch.unitroot.cointegration.EngleGrangerTestResults.trend**property** EngleGrangerTestResults.trend : str

The trend used in the cointegrating regression

Return type

str

arch.unitroot.cointegration.PhillipsOuliarisTestResults

```
class arch.unitroot.cointegration.PhillipsOuliarisTestResults(stat, pvalue, crit_vals,
                                                             null=No Cointegration',
                                                             alternative=Cointegration',
                                                             trend='c', order=2, xsection=None,
                                                             test_type='Za', kernel_est=None,
                                                             rho=0.0)
```

Methods

<code>plot([axes, title])</code>	Plot the cointegration residuals.
<code>summary()</code>	Summary of test, containing statistic, p-value and critical values

arch.unitroot.cointegration.PhillipsOuliarisTestResults.plot

PhillipsOuliarisTestResults.plot(axes=None, title=None)

Plot the cointegration residuals.

Parameters**axes** : Axes, default None

matplotlib axes instance to hold the figure.

title : str, default None

Title for the figure.

Returns

The matplotlib Figure instance.

Return type

Figure

arch.unitroot.cointegration.PhillipsOuliarisTestResults.summary**PhillipsOuliarisTestResults.summary()**

Summary of test, containing statistic, p-value and critical values

Return type

Summary

Properties

<i>alternative_hypothesis</i>	The alternative hypothesis
<i>bandwidth</i>	Bandwidth used by the long-run covariance estimator
<i>cointegrating_vector</i>	The estimated cointegrating vector.
<i>critical_values</i>	Critical Values
<i>distribution_order</i>	The number of stochastic trends under the null hypothesis.
<i>kernel</i>	Name of the long-run covariance estimator
<i>name</i>	Sets or gets the name of the cointegration test
<i>null_hypothesis</i>	The null hypothesis
<i>pvalue</i>	The p-value of the test statistic.
<i>resid</i>	The residual from the cointegrating regression.
<i>stat</i>	The test statistic.
<i>trend</i>	The trend used in the cointegrating regression

arch.unitroot.cointegration.PhillipsOuliarisTestResults.alternative_hypothesis**property** PhillipsOuliarisTestResults.alternative_hypothesis : str

The alternative hypothesis

Return type

str

arch.unitroot.cointegration.PhillipsOuliarisTestResults.bandwidth**property** PhillipsOuliarisTestResults.bandwidth : float

Bandwidth used by the long-run covariance estimator

Return type

float

arch.unitroot.cointegration.PhillipsOuliarisTestResults.cointegrating_vector**property** PhillipsOuliarisTestResults.cointegrating_vector : Series

The estimated cointegrating vector.

Return type

Series

arch.unitroot.cointegration.PhillipsOuliarisTestResults.critical_values

property PhillipsOuliarisTestResults.critical_values : Series

Critical Values

Returns

Series with three keys, 1, 5 and 10 containing the critical values of the test statistic.

Return type

Series

arch.unitroot.cointegration.PhillipsOuliarisTestResults.distribution_order

property PhillipsOuliarisTestResults.distribution_order : int

The number of stochastic trends under the null hypothesis.

Return type

int

arch.unitroot.cointegration.PhillipsOuliarisTestResults.kernel

property PhillipsOuliarisTestResults.kernel : str

Name of the long-run covariance estimator

Return type

str

arch.unitroot.cointegration.PhillipsOuliarisTestResults.name

property PhillipsOuliarisTestResults.name : str

Sets or gets the name of the cointegration test

Return type

str

arch.unitroot.cointegration.PhillipsOuliarisTestResults.null_hypothesis

property PhillipsOuliarisTestResults.null_hypothesis : str

The null hypothesis

Return type

str

arch.unitroot.cointegration.PhillipsOuliarisTestResults.pvalue

property PhillipsOuliarisTestResults.**pvalue** : float

The p-value of the test statistic.

Return type

float

arch.unitroot.cointegration.PhillipsOuliarisTestResults.resid

property PhillipsOuliarisTestResults.**resid** : Series

The residual from the cointegrating regression.

Return type

Series

arch.unitroot.cointegration.PhillipsOuliarisTestResults.stat

property PhillipsOuliarisTestResults.**stat** : float

The test statistic.

Return type

float

arch.unitroot.cointegration.PhillipsOuliarisTestResults.trend

property PhillipsOuliarisTestResults.**trend** : str

The trend used in the cointegrating regression

Return type

str

LONG-RUN COVARIANCE ESTIMATION

6.1 Long-run Covariance Estimators

<i>Andrews</i> (x[, bandwidth, df_adjust, center, ...])	Alternative name of the QuadraticSpectral covariance estimator.
<i>Bartlett</i> (x[, bandwidth, df_adjust, center, ...])	Bartlett's (Newey-West) kernel covariance estimation.
<i>Gallant</i> (x[, bandwidth, df_adjust, center, ...])	Alternative name for Parzen covariance estimator.
<i>NeweyWest</i> (x[, bandwidth, df_adjust, center, ...])	Alternative name for Bartlett covariance estimator.
<i>Parzen</i> (x[, bandwidth, df_adjust, center, ...])	Parzen's kernel covariance estimation.
<i>ParzenCauchy</i> (x[, bandwidth, df_adjust, ...])	Parzen's Cauchy kernel covariance estimation.
<i>ParzenGeometric</i> (x[, bandwidth, df_adjust, ...])	Parzen's Geometric kernel covariance estimation.
<i>ParzenRiesz</i> (x[, bandwidth, df_adjust, ...])	Parzen-Reisz kernel covariance estimation.
<i>QuadraticSpectral</i> (x[, bandwidth, df_adjust, ...])	Quadratic-Spectral (Andrews') kernel covariance estimation.
<i>TukeyHamming</i> (x[, bandwidth, df_adjust, ...])	Tukey-Hamming kernel covariance estimation.
<i>TukeyHanning</i> (x[, bandwidth, df_adjust, ...])	Tukey-Hanning kernel covariance estimation.
<i>TukeyParzen</i> (x[, bandwidth, df_adjust, ...])	Tukey-Parzen kernel covariance estimation.

6.1.1 arch.covariance.kernel.Andrews

class arch.covariance.kernel.**Andrews**(x, bandwidth=**None**, df_adjust=**0**, center=**True**, weights=**None**, force_int=**False**)

Alternative name of the QuadraticSpectral covariance estimator.

See also

QuadraticSpectral

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (de-meanned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.Andrews.bandwidth

property Andrews.bandwidth : float

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type

float

arch.covariance.kernel.Andrews.bandwidth_scale

property Andrews.bandwidth_scale

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.Andrews.centered

property Andrews.centered : bool

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type

bool

arch.covariance.kernel.Andrews.cov**property** Andrews.cov : *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- long_run
- short_run
- one_sided
- one_sided_strict

Return type*CovarianceEstimate*

See also*CovarianceEstimate*

arch.covariance.kernel.Andrews.force_int**property** Andrews.force_int : bool

Flag indicating whether the bandwidth is restricted to be an integer.

Return type

bool

arch.covariance.kernel.Andrews.kernel_const**property** Andrews.kernel_const

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.Andrews.kernel_weights**property** Andrews.kernel_weights : ndarray

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

ndarray

arch.covariance.kernel.Andrews.name

property Andrews.name : str

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

str

arch.covariance.kernel.Andrews.opt_bandwidth

property Andrews.opt_bandwidth : float

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

float

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

arch.covariance.kernel.Andrews.rate

property Andrews.rate

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.1.2 arch.covariance.kernel.Bartlett

class arch.covariance.kernel.Bartlett(x, bandwidth=None, df_adjust=0, center=True, weights=None, force_int=False)

Bartlett's (Newey-West) kernel covariance estimation.

Parameters

x : array_like

The data to use in covariance estimation.

bandwidth : **float**, default **None**

The kernel's bandwidth. If **None**, optimal bandwidth is estimated.

df_adjust : **int**, default **0**

Degrees of freedom to remove when adjusting the covariance. Uses the number of observations in **x** minus **df_adjust** when dividing inner-products.

center : **bool**, default **True**

A flag indicating whether **x** should be demeaned before estimating the covariance.

weights : **array_like**, default **None**

An array of weights used to combine when estimating optimal bandwidth. If not provided, a vector of 1s is used. Must have **nvar** elements.

force_int : **bool**, default **False**

Force bandwidth to be an integer.

Notes

The kernel weights are computed using

$$w = \begin{cases} 1 - |z| & z \leq 1 \\ 0 & z > 1 \end{cases}$$

where $z = \frac{h}{H}$, $h = 0, 1, \dots, H$ where **H** is the bandwidth.

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (demeaned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.Bartlett.bandwidth

property Bartlett.**bandwidth**: float

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type

float

arch.covariance.kernel.Bartlett.bandwidth_scale

property Bartlett.**bandwidth_scale**

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.Bartlett.centered

property Bartlett.**centered**: bool

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type

bool

arch.covariance.kernel.Bartlett.cov

property Bartlett.**cov**: *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- long_run
- short_run
- one_sided
- one_sided_strict

Return type

CovarianceEstimate

See also

CovarianceEstimate

arch.covariance.kernel.Bartlett.force_int

property Bartlett.**force_int** : bool

Flag indicating whether the bandwidth is restricted to be an integer.

Return type

bool

arch.covariance.kernel.Bartlett.kernel_const

property Bartlett.**kernel_const**

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.Bartlett.kernel_weights

property Bartlett.**kernel_weights** : ndarray

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

ndarray

arch.covariance.kernel.Bartlett.name

property Bartlett.**name** : str

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

str

arch.covariance.kernel.Bartlett.opt_bandwidth

property Bartlett.**opt_bandwidth** : float

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

float

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

arch.covariance.kernel.Bartlett.rate

property Bartlett.rate

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.1.3 arch.covariance.kernel.Gallant

```
class arch.covariance.kernel.Gallant(x, bandwidth=None, df_adjust=0, center=True, weights=None,
                                     force_int=False)
```

Alternative name for Parzen covariance estimator.

See also

[*Parzen*](#)

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (de-meanned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.Gallant.bandwidth**property** `Gallant.bandwidth` : `float`

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type`float`**arch.covariance.kernel.Gallant.bandwidth_scale****property** `Gallant.bandwidth_scale`

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type`float`**arch.covariance.kernel.Gallant.centered****property** `Gallant.centered` : `bool`

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type`bool`**arch.covariance.kernel.Gallant.cov****property** `Gallant.cov` : *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- `long_run`
- `short_run`
- `one_sided`
- `one_sided_strict`

Return type*CovarianceEstimate*

See also*CovarianceEstimate*

arch.covariance.kernel.Gallant.force_int

property `Gallant.force_int` : `bool`

Flag indicating whether the bandwidth is restricted to be an integer.

Return type

`bool`

arch.covariance.kernel.Gallant.kernel_const

property `Gallant.kernel_const`

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type

`float`

arch.covariance.kernel.Gallant.kernel_weights

property `Gallant.kernel_weights` : `ndarray`

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

`ndarray`

arch.covariance.kernel.Gallant.name

property `Gallant.name` : `str`

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

`str`

arch.covariance.kernel.Gallant.opt_bandwidth

property `Gallant.opt_bandwidth` : `float`

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

`float`

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

arch.covariance.kernel.Gallant.rate

property Gallant.rate

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.1.4 arch.covariance.kernel.NeweyWest

class arch.covariance.kernel.NeweyWest(*x*, *bandwidth*=None, *df_adjust*=0, *center*=True, *weights*=None, *force_int*=False)

Alternative name for Bartlett covariance estimator.

See also

[Bartlett](#)

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (de-meanned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.NeweyWest.bandwidth

property NeweyWest.bandwidth: float

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type

float

arch.covariance.kernel.NeweyWest.bandwidth_scale

property NeweyWest.bandwidth_scale

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.NeweyWest.centered

property NeweyWest.centered: bool

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type

bool

arch.covariance.kernel.NeweyWest.cov

property NeweyWest.cov: *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- long_run
- short_run
- one_sided
- one_sided_strict

Return type

CovarianceEstimate

See also

CovarianceEstimate

arch.covariance.kernel.NeweyWest.force_int

property NeweyWest.**force_int** : bool

Flag indicating whether the bandwidth is restricted to be an integer.

Return type

bool

arch.covariance.kernel.NeweyWest.kernel_const

property NeweyWest.**kernel_const**

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.NeweyWest.kernel_weights

property NeweyWest.**kernel_weights** : ndarray

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

ndarray

arch.covariance.kernel.NeweyWest.name

property NeweyWest.**name** : str

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

str

arch.covariance.kernel.NeweyWest.opt_bandwidth

property NeweyWest.**opt_bandwidth** : float

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

float

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

arch.covariance.kernel.NeweyWest.rate

property NeweyWest.rate

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.1.5 arch.covariance.kernel.Parzen

```
class arch.covariance.kernel.Parzen(x, bandwidth=None, df_adjust=0, center=True, weights=None,
                                   force_int=False)
```

Parzen's kernel covariance estimation.

Parameters

x : array_like

The data to use in covariance estimation.

bandwidth : float, default None

The kernel's bandwidth. If None, optimal bandwidth is estimated.

df_adjust : int, default 0

Degrees of freedom to remove when adjusting the covariance. Uses the number of observations in x minus df_adjust when dividing inner-products.

center : bool, default True

A flag indicating whether x should be demeaned before estimating the covariance.

weights : array_like, default None

An array of weights used to combine when estimating optimal bandwidth. If not provided, a vector of 1s is used. Must have $nvar$ elements.

force_int : bool, default False

Force bandwidth to be an integer.

Notes

The kernel weights are computed using

$$w = \begin{cases} 1 - 6z^2(1 - z) & z \leq \frac{1}{2} \\ 2(1 - z)^3 & \frac{1}{2} < z \leq 1 \\ 0 & z > 1 \end{cases}$$

where $z = \frac{h}{H}$, $h = 0, 1, \dots, H$ where H is the bandwidth.

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (de-meanned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.Parzen.bandwidth

property `Parzen.bandwidth` : float

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type

float

arch.covariance.kernel.Parzen.bandwidth_scale

property `Parzen.bandwidth_scale`

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.Parzen.centered

property Parzen.**centered** : `bool`

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type

`bool`

arch.covariance.kernel.Parzen.cov

property Parzen.**cov** : *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- `long_run`
- `short_run`
- `one_sided`
- `one_sided_strict`

Return type

CovarianceEstimate

See also

CovarianceEstimate

arch.covariance.kernel.Parzen.force_int

property Parzen.**force_int** : `bool`

Flag indicating whether the bandwidth is restricted to be an integer.

Return type

`bool`

arch.covariance.kernel.Parzen.kernel_const

property Parzen.**kernel_const**

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type

`float`

arch.covariance.kernel.Parzen.kernel_weights**property** Parzen.kernel_weights : ndarray

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

ndarray

arch.covariance.kernel.Parzen.name**property** Parzen.name : str

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

str

arch.covariance.kernel.Parzen.opt_bandwidth**property** Parzen.opt_bandwidth : float

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

float

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

arch.covariance.kernel.Parzen.rate**property** Parzen.rate

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.1.6 arch.covariance.kernel.ParzenCauchy

```
class arch.covariance.kernel.ParzenCauchy(x, bandwidth=None, df_adjust=0, center=True,
                                         weights=None, force_int=False)
```

Parzen's Cauchy kernel covariance estimation.

Parameters

x : array_like

The data to use in covariance estimation.

bandwidth : float, default None

The kernel's bandwidth. If None, optimal bandwidth is estimated.

df_adjust : int, default 0

Degrees of freedom to remove when adjusting the covariance. Uses the number of observations in x minus df_adjust when dividing inner-products.

center : bool, default True

A flag indicating whether x should be demeaned before estimating the covariance.

weights : array_like, default None

An array of weights used to combine when estimating optimal bandwidth. If not provided, a vector of 1s is used. Must have nvar elements.

force_int : bool, default False

Force bandwidth to be an integer.

Notes

The kernel weights are computed using

$$w = \begin{cases} \frac{1}{1+z^2} & z \leq 1 \\ 0 & z > 1 \end{cases}$$

where $z = \frac{h}{H}$, $h = 0, 1, \dots, H$ where H is the bandwidth.

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (demeaned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.ParzenCauchy.bandwidth**property** ParzenCauchy.bandwidth : float

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type

float

arch.covariance.kernel.ParzenCauchy.bandwidth_scale**property** ParzenCauchy.bandwidth_scale

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.ParzenCauchy.centered**property** ParzenCauchy.centered : bool

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type

bool

arch.covariance.kernel.ParzenCauchy.cov**property** ParzenCauchy.cov : *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- long_run
- short_run
- one_sided
- one_sided_strict

Return type*CovarianceEstimate*

See also*CovarianceEstimate*

arch.covariance.kernel.ParzenCauchy.force_int

property ParzenCauchy.**force_int** : bool

Flag indicating whether the bandwidth is restricted to be an integer.

Return type

bool

arch.covariance.kernel.ParzenCauchy.kernel_const

property ParzenCauchy.**kernel_const**

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.ParzenCauchy.kernel_weights

property ParzenCauchy.**kernel_weights** : ndarray

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

ndarray

arch.covariance.kernel.ParzenCauchy.name

property ParzenCauchy.**name** : str

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

str

arch.covariance.kernel.ParzenCauchy.opt_bandwidth

property ParzenCauchy.**opt_bandwidth** : float

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

float

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

arch.covariance.kernel.ParzenCauchy.rate

property ParzenCauchy.rate

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.1.7 arch.covariance.kernel.ParzenGeometric

```
class arch.covariance.kernel.ParzenGeometric(x, bandwidth=None, df_adjust=0, center=True,
                                             weights=None, force_int=False)
```

Parzen's Geometric kernel covariance estimation.

Parameters

x : array_like

The data to use in covariance estimation.

bandwidth : float, default None

The kernel's bandwidth. If None, optimal bandwidth is estimated.

df_adjust : int, default 0

Degrees of freedom to remove when adjusting the covariance. Uses the number of observations in x minus df_adjust when dividing inner-products.

center : bool, default True

A flag indicating whether x should be demeaned before estimating the covariance.

weights : array_like, default None

An array of weights used to combine when estimating optimal bandwidth. If not provided, a vector of 1s is used. Must have $nvar$ elements.

force_int : bool, default False

Force bandwidth to be an integer.

Notes

The kernel weights are computed using

$$w = \begin{cases} \frac{1}{1+z} & z \leq 1 \\ 0 & z > 1 \end{cases}$$

where $z = \frac{h}{H}$, $h = 0, 1, \dots, H$ where H is the bandwidth.

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (de-meanned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.ParzenGeometric.bandwidth

property ParzenGeometric.bandwidth : float

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type

float

arch.covariance.kernel.ParzenGeometric.bandwidth_scale

property ParzenGeometric.bandwidth_scale

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.ParzenGeometric.centered

property ParzenGeometric.centered : bool

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type

bool

arch.covariance.kernel.ParzenGeometric.cov

property ParzenGeometric.cov : *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- long_run
- short_run
- one_sided
- one_sided_strict

Return type

CovarianceEstimate

See also

CovarianceEstimate

arch.covariance.kernel.ParzenGeometric.force_int

property ParzenGeometric.force_int : bool

Flag indicating whether the bandwidth is restricted to be an integer.

Return type

bool

arch.covariance.kernel.ParzenGeometric.kernel_const

property ParzenGeometric.kernel_const

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.ParzenGeometric.kernel_weights

property ParzenGeometric.**kernel_weights** : ndarray

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

ndarray

arch.covariance.kernel.ParzenGeometric.name

property ParzenGeometric.**name** : str

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

str

arch.covariance.kernel.ParzenGeometric.opt_bandwidth

property ParzenGeometric.**opt_bandwidth** : float

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

float

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

arch.covariance.kernel.ParzenGeometric.rate

property ParzenGeometric.**rate**

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.1.8 arch.covariance.kernel.ParzenRiesz

```
class arch.covariance.kernel.ParzenRiesz(x, bandwidth=None, df_adjust=0, center=True,
                                         weights=None, force_int=False)
```

Parzen-Reisz kernel covariance estimation.

Parameters

x : array_like

The data to use in covariance estimation.

bandwidth : float, default None

The kernel's bandwidth. If None, optimal bandwidth is estimated.

df_adjust : int, default 0

Degrees of freedom to remove when adjusting the covariance. Uses the number of observations in x minus df_adjust when dividing inner-products.

center : bool, default True

A flag indicating whether x should be demeaned before estimating the covariance.

weights : array_like, default None

An array of weights used to combine when estimating optimal bandwidth. If not provided, a vector of 1s is used. Must have nvar elements.

force_int : bool, default False

Force bandwidth to be an integer.

Notes

The kernel weights are computed using

$$w = \begin{cases} 1 - z^2 & z \leq 1 \\ 0 & z > 1 \end{cases}$$

where $z = \frac{h}{H}$, $h = 0, 1, \dots, H$ where H is the bandwidth.

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (demeaned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.ParzenRiesz.bandwidth

property ParzenRiesz.bandwidth : float

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type

float

arch.covariance.kernel.ParzenRiesz.bandwidth_scale

property ParzenRiesz.bandwidth_scale

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.ParzenRiesz.centered

property ParzenRiesz.centered : bool

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type

bool

arch.covariance.kernel.ParzenRiesz.cov

property ParzenRiesz.cov : *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- long_run
- short_run
- one_sided
- one_sided_strict

Return type

CovarianceEstimate

See also

CovarianceEstimate

arch.covariance.kernel.ParzenRiesz.force_int**property** ParzenRiesz.**force_int** : bool

Flag indicating whether the bandwidth is restricted to be an integer.

Return type

bool

arch.covariance.kernel.ParzenRiesz.kernel_const**property** ParzenRiesz.**kernel_const**

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.ParzenRiesz.kernel_weights**property** ParzenRiesz.**kernel_weights** : ndarray

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

ndarray

arch.covariance.kernel.ParzenRiesz.name**property** ParzenRiesz.**name** : str

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

str

arch.covariance.kernel.ParzenRiesz.opt_bandwidth**property** ParzenRiesz.**opt_bandwidth** : float

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

float

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

arch.covariance.kernel.ParzenRiesz.rate

property ParzenRiesz.rate

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.1.9 arch.covariance.kernel.QuadraticSpectral

```
class arch.covariance.kernel.QuadraticSpectral(x, bandwidth=None, df_adjust=0, center=True,
                                              weights=None, force_int=False)
```

Quadratic-Spectral (Andrews') kernel covariance estimation.

Parameters

x : array_like

The data to use in covariance estimation.

bandwidth : float, default None

The kernel's bandwidth. If None, optimal bandwidth is estimated.

df_adjust : int, default 0

Degrees of freedom to remove when adjusting the covariance. Uses the number of observations in x minus df_adjust when dividing inner-products.

center : bool, default True

A flag indicating whether x should be demeaned before estimating the covariance.

weights : array_like, default None

An array of weights used to combine when estimating optimal bandwidth. If not provided, a vector of 1s is used. Must have $nvar$ elements.

force_int : bool, default False

Force bandwidth to be an integer.

Notes

The kernel weights are computed using

$$w = \begin{cases} 1 & z = 0 \\ \frac{3}{x^2} \left(\frac{\sin x}{x} - \cos x \right), x = \frac{6\pi z}{5} & z > 0 \end{cases}$$

where $z = \frac{h}{H}$, $h = 0, 1, \dots, H$ where H is the bandwidth.

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (de-meanned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.QuadraticSpectral.bandwidth

property QuadraticSpectral.**bandwidth**: float

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type

float

arch.covariance.kernel.QuadraticSpectral.bandwidth_scale

property QuadraticSpectral.**bandwidth_scale**

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.QuadraticSpectral.centered

property QuadraticSpectral.**centered** : `bool`

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type

`bool`

arch.covariance.kernel.QuadraticSpectral.cov

property QuadraticSpectral.**cov** : *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- `long_run`
- `short_run`
- `one_sided`
- `one_sided_strict`

Return type

CovarianceEstimate

See also

CovarianceEstimate

arch.covariance.kernel.QuadraticSpectral.force_int

property QuadraticSpectral.**force_int** : `bool`

Flag indicating whether the bandwidth is restricted to be an integer.

Return type

`bool`

arch.covariance.kernel.QuadraticSpectral.kernel_const

property QuadraticSpectral.**kernel_const**

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type

`float`

arch.covariance.kernel.QuadraticSpectral.kernel_weights**property** QuadraticSpectral.**kernel_weights** : ndarray

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

ndarray

arch.covariance.kernel.QuadraticSpectral.name**property** QuadraticSpectral.**name** : str

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

str

arch.covariance.kernel.QuadraticSpectral.opt_bandwidth**property** QuadraticSpectral.**opt_bandwidth** : float

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

float

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

arch.covariance.kernel.QuadraticSpectral.rate**property** QuadraticSpectral.**rate**

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.1.10 arch.covariance.kernel.TukeyHamming

```
class arch.covariance.kernel.TukeyHamming(x, bandwidth=None, df_adjust=0, center=True,
                                         weights=None, force_int=False)
```

Tukey-Hamming kernel covariance estimation.

Parameters

x : array_like

The data to use in covariance estimation.

bandwidth : float, default None

The kernel's bandwidth. If None, optimal bandwidth is estimated.

df_adjust : int, default 0

Degrees of freedom to remove when adjusting the covariance. Uses the number of observations in x minus df_adjust when dividing inner-products.

center : bool, default True

A flag indicating whether x should be demeaned before estimating the covariance.

weights : array_like, default None

An array of weights used to combine when estimating optimal bandwidth. If not provided, a vector of 1s is used. Must have nvar elements.

force_int : bool, default False

Force bandwidth to be an integer.

Notes

The kernel weights are computed using

$$w = \begin{cases} 0.54 + 0.46 \cos \pi z & z \leq 1 \\ 0 & z > 1 \end{cases}$$

where $z = \frac{h}{H}$, $h = 0, 1, \dots, H$ where H is the bandwidth.

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (demeaned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.TukeyHamming.bandwidth**property** `TukeyHamming.bandwidth` : float

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type

float

arch.covariance.kernel.TukeyHamming.bandwidth_scale**property** `TukeyHamming.bandwidth_scale`

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.TukeyHamming.centered**property** `TukeyHamming.centered` : bool

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type

bool

arch.covariance.kernel.TukeyHamming.cov**property** `TukeyHamming.cov` : *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- long_run
- short_run
- one_sided
- one_sided_strict

Return type*CovarianceEstimate*

See also*CovarianceEstimate*

arch.covariance.kernel.TukeyHamming.force_int

property `TukeyHamming.force_int` : `bool`

Flag indicating whether the bandwidth is restricted to be an integer.

Return type

`bool`

arch.covariance.kernel.TukeyHamming.kernel_const

property `TukeyHamming.kernel_const`

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type

`float`

arch.covariance.kernel.TukeyHamming.kernel_weights

property `TukeyHamming.kernel_weights` : `ndarray`

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

`ndarray`

arch.covariance.kernel.TukeyHamming.name

property `TukeyHamming.name` : `str`

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

`str`

arch.covariance.kernel.TukeyHamming.opt_bandwidth

property `TukeyHamming.opt_bandwidth` : `float`

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

`float`

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

arch.covariance.kernel.TukeyHamming.rate

property TukeyHamming.rate

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.1.11 arch.covariance.kernel.TukeyHanning

```
class arch.covariance.kernel.TukeyHanning(x, bandwidth=None, df_adjust=0, center=True,
                                         weights=None, force_int=False)
```

Tukey-Hanning kernel covariance estimation.

Parameters

x : array_like

The data to use in covariance estimation.

bandwidth : float, default None

The kernel's bandwidth. If None, optimal bandwidth is estimated.

df_adjust : int, default 0

Degrees of freedom to remove when adjusting the covariance. Uses the number of observations in x minus df_adjust when dividing inner-products.

center : bool, default True

A flag indicating whether x should be demeaned before estimating the covariance.

weights : array_like, default None

An array of weights used to combine when estimating optimal bandwidth. If not provided, a vector of 1s is used. Must have $nvar$ elements.

force_int : bool, default False

Force bandwidth to be an integer.

Notes

The kernel weights are computed using

$$w = \begin{cases} \frac{1}{2} + \frac{1}{2} \cos \pi z & z \leq 1 \\ 0 & z > 1 \end{cases}$$

where $z = \frac{h}{H}$, $h = 0, 1, \dots, H$ where H is the bandwidth.

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (de-meanned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.TukeyHanning.bandwidth

property `TukeyHanning.bandwidth` : float

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type

float

arch.covariance.kernel.TukeyHanning.bandwidth_scale

property `TukeyHanning.bandwidth_scale`

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.TukeyHanning.centered**property** `TukeyHanning.centered` : `bool`

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type`bool`**arch.covariance.kernel.TukeyHanning.cov****property** `TukeyHanning.cov` : *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- `long_run`
- `short_run`
- `one_sided`
- `one_sided_strict`

Return type*CovarianceEstimate*

See also*CovarianceEstimate*

arch.covariance.kernel.TukeyHanning.force_int**property** `TukeyHanning.force_int` : `bool`

Flag indicating whether the bandwidth is restricted to be an integer.

Return type`bool`**arch.covariance.kernel.TukeyHanning.kernel_const****property** `TukeyHanning.kernel_const`

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type`float`

arch.covariance.kernel.TukeyHanning.kernel_weights

property TukeyHanning.**kernel_weights** : ndarray

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

ndarray

arch.covariance.kernel.TukeyHanning.name

property TukeyHanning.**name** : str

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

str

arch.covariance.kernel.TukeyHanning.opt_bandwidth

property TukeyHanning.**opt_bandwidth** : float

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

float

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

arch.covariance.kernel.TukeyHanning.rate

property TukeyHanning.**rate**

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.1.12 arch.covariance.kernel.TukeyParzen

```
class arch.covariance.kernel.TukeyParzen(x, bandwidth=None, df_adjust=0, center=True,
                                         weights=None, force_int=False)
```

Tukey-Parzen kernel covariance estimation.

Parameters

x : array_like

The data to use in covariance estimation.

bandwidth : float, default None

The kernel's bandwidth. If None, optimal bandwidth is estimated.

df_adjust : int, default 0

Degrees of freedom to remove when adjusting the covariance. Uses the number of observations in x minus df_adjust when dividing inner-products.

center : bool, default True

A flag indicating whether x should be demeaned before estimating the covariance.

weights : array_like, default None

An array of weights used to combine when estimating optimal bandwidth. If not provided, a vector of 1s is used. Must have nvar elements.

force_int : bool, default False

Force bandwidth to be an integer.

Notes

The kernel weights are computed using

$$w = \begin{cases} 0.436 + 0.564 \cos \pi z & z \leq 1 \\ 0 & z > 1 \end{cases}$$

where $z = \frac{h}{H}$, $h = 0, 1, \dots, H$ where H is the bandwidth.

Methods

Properties

<i>bandwidth</i>	The bandwidth used by the covariance estimator.
<i>bandwidth_scale</i>	The power used in optimal bandwidth calculation.
<i>centered</i>	Flag indicating whether the data are centered (demeaned).
<i>cov</i>	The estimated covariances.
<i>force_int</i>	Flag indicating whether the bandwidth is restricted to be an integer.
<i>kernel_const</i>	The constant used in optimal bandwidth calculation.
<i>kernel_weights</i>	Weights used in covariance calculation.
<i>name</i>	The covariance estimator's name.
<i>opt_bandwidth</i>	Estimate optimal bandwidth.
<i>rate</i>	The optimal rate used in bandwidth selection.

arch.covariance.kernel.TukeyParzen.bandwidth

property TukeyParzen.bandwidth : float

The bandwidth used by the covariance estimator.

Returns

The user-provided or estimated optimal bandwidth.

Return type

float

arch.covariance.kernel.TukeyParzen.bandwidth_scale

property TukeyParzen.bandwidth_scale

The power used in optimal bandwidth calculation.

Returns

The power value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.TukeyParzen.centered

property TukeyParzen.centered : bool

Flag indicating whether the data are centered (demeaned).

Returns

A flag indicating whether the estimator is centered.

Return type

bool

arch.covariance.kernel.TukeyParzen.cov

property TukeyParzen.cov : *CovarianceEstimate*

The estimated covariances.

Returns

Covariance estimate instance containing 4 estimates:

- long_run
- short_run
- one_sided
- one_sided_strict

Return type

CovarianceEstimate

See also

CovarianceEstimate

arch.covariance.kernel.TukeyParzen.force_int

property TukeyParzen.**force_int** : bool

Flag indicating whether the bandwidth is restricted to be an integer.

Return type

bool

arch.covariance.kernel.TukeyParzen.kernel_const

property TukeyParzen.**kernel_const**

The constant used in optimal bandwidth calculation.

Returns

The constant value used in the optimal bandwidth calculation.

Return type

float

arch.covariance.kernel.TukeyParzen.kernel_weights

property TukeyParzen.**kernel_weights** : ndarray

Weights used in covariance calculation.

Returns

The weight vector including 1 in position 0.

Return type

ndarray

arch.covariance.kernel.TukeyParzen.name

property TukeyParzen.**name** : str

The covariance estimator's name.

Returns

The covariance estimator's name.

Return type

str

arch.covariance.kernel.TukeyParzen.opt_bandwidth

property TukeyParzen.**opt_bandwidth** : float

Estimate optimal bandwidth.

Returns

The estimated optimal bandwidth.

Return type

float

Notes

Computed as

$$\hat{b}_T = c_k [\hat{\alpha}(q) T]^{\frac{1}{2q+1}}$$

where c_k is a kernel-dependent constant, T is the sample size, q determines the optimal bandwidth rate for the kernel.

`arch.covariance.kernel.TukeyParzen.rate`

property `TukeyParzen.rate`

The optimal rate used in bandwidth selection.

Controls the number of lags used in the variance estimate that determines the estimate of the optimal bandwidth.

Returns

The rate used in bandwidth selection.

Return type

float

6.2 Results

<code>CovarianceEstimate</code> (short_run, one_sided_strict)	Covariance estimate using a long-run covariance estimator
---	---

6.2.1 `arch.covariance.kernel.CovarianceEstimate`

```
class arch.covariance.kernel.CovarianceEstimate(short_run, one_sided_strict, columns=None,  
                                                long_run=None, one_sided=None)
```

Covariance estimate using a long-run covariance estimator

Parameters

short_run : ndarray

The short-run covariance estimate.

one_sided_strict : ndarray, default None

The one-sided strict covariance estimate.

columns : {None, list[str]}

Column labels to use if covariance estimates are returned as DataFrames.

long_run : ndarray, default None

The long-run covariance estimate. If not provided, computed from short_run and one_sided_strict.

one_sided_strict

The one-sided-strict covariance estimate. If not provided, computed from short_run and one_sided_strict.

Notes

If Γ_0 is the short-run covariance and Λ_1 is the one-sided strict covariance, then the long-run covariance is defined

$$\Omega = \Gamma_0 + \Lambda_1 + \Lambda_1'$$

and the one-sided covariance is

$$\Lambda_0 = \Gamma_0 + \Lambda_1.$$

Methods

Properties

<code>long_run</code>	The long-run covariance estimate.
<code>one_sided</code>	The one-sided covariance estimate.
<code>one_sided_strict</code>	The one-sided strict covariance estimate.
<code>short_run</code>	The short-run covariance estimate.

`arch.covariance.kernel.CovarianceEstimate.long_run`

property `CovarianceEstimate.long_run`: `numpy.ndarray` | `pandas.core.frame.DataFrame`
The long-run covariance estimate.

`arch.covariance.kernel.CovarianceEstimate.one_sided`

property `CovarianceEstimate.one_sided`: `numpy.ndarray` | `pandas.core.frame.DataFrame`
The one-sided covariance estimate.

`arch.covariance.kernel.CovarianceEstimate.one_sided_strict`

property `CovarianceEstimate.one_sided_strict`: `numpy.ndarray` | `pandas.core.frame.DataFrame`
The one-sided strict covariance estimate.

`arch.covariance.kernel.CovarianceEstimate.short_run`

property `CovarianceEstimate.short_run`: `numpy.ndarray` | `pandas.core.frame.DataFrame`
The short-run covariance estimate.

API REFERENCE

This page lists contains a list of the essential end-user API functions and classes.

7.1 Volatility Modeling

7.1.1 High-level

<i>arch_model</i>(y[, x, mean, lags, vol, p, o, q, ...])	Initialization of common ARCH model specifications
--	--

7.1.2 Mean Specification

<i>ConstantMean</i>([y, hold_back, volatility, ...])	Constant mean model estimation and simulation.
<i>ZeroMean</i>([y, hold_back, volatility, ...])	Model with zero conditional mean estimation and simulation
<i>HARX</i>([y, x, lags, constant, use_rotated, ...])	Heterogeneous Autoregression (HAR), with optional exogenous regressors, model estimation and simulation
<i>ARX</i>([y, x, lags, constant, hold_back, ...])	Autoregressive model with optional exogenous regressors estimation and simulation
<i>LS</i>([y, x, constant, hold_back, volatility, ...])	Least squares model estimation and simulation

7.1.3 Volatility Process Specification

<i>GARCH</i>([p, o, q, power])	GARCH and related model estimation
<i>EGARCH</i>([p, o, q])	EGARCH model estimation
<i>HARCH</i>([lags])	Heterogeneous ARCH process
<i>FIGARCH</i>([p, q, power, truncation])	FIGARCH model
<i>MIDASHyperbolic</i>([m, asym])	MIDAS Hyperbolic ARCH process
<i>EWMAVariance</i>([lam])	Exponentially Weighted Moving-Average (RiskMetrics) Variance process
<i>RiskMetrics2006</i>([tau0, tau1, kmax, rho])	RiskMetrics 2006 Variance process
<i>ConstantVariance</i>()	Constant volatility process
<i>FixedVariance</i>(variance[, unit_scale])	Fixed volatility process

7.1.4 Shock Distributions

<i>Normal</i> ([random_state, seed])	Standard normal distribution for use with ARCH models
<i>StudentsT</i> ([random_state, seed])	Standardized Student's distribution for use with ARCH models
<i>SkewStudent</i> ([random_state, seed])	Standardized Skewed Student's distribution for use with ARCH models
<i>GeneralizedError</i> ([random_state, seed])	Generalized Error distribution for use with ARCH models

7.2 Unit Root Testing

<i>ADF</i> (y[, lags, trend, max_lags, method, ...])	Augmented Dickey-Fuller unit root test
<i>DFGLS</i> (y[, lags, trend, max_lags, method, ...])	Elliott, Rothenberg and Stock's (1988) GLS detrended Dickey-Fuller
<i>PhillipsPerron</i> (y[, lags, trend, test_type])	Phillips-Perron unit root test
<i>ZivotAndrews</i> (y[, lags, trend, trim, ...])	Zivot-Andrews structural-break unit-root test
<i>VarianceRatio</i> (y[, lags, trend, debiased, ...])	Variance Ratio test of a random walk.
<i>KPSS</i> (y[, lags, trend])	Kwiatkowski, Phillips, Schmidt and Shin (KPSS) stationarity test

7.3 Cointegration Testing

<i>engle_granger</i> (y, x[, trend, lags, max_lags, ...])	Test for cointegration within a set of time series.
<i>phillips_perron</i> (y, x[, trend, test_type, ...])	Test for cointegration within a set of time series.

7.4 Cointegrating Relationship Estimation

<i>CanonicalCointegratingReg</i> (y, x[, trend, x_trend])	Canonical Cointegrating Regression cointegrating vector estimation.
<i>DynamicOLS</i> (y, x[, trend, lags, leads, ...])	Dynamic OLS (DOLS) cointegrating vector estimation
<i>FullyModifiedOLS</i> (y, x[, trend, x_trend])	Fully Modified OLS cointegrating vector estimation.

7.5 Bootstraps

<i>IIDBootstrap</i> (*args[, random_state, seed])	Bootstrap using uniform resampling
<i>IndependentSamplesBootstrap</i> (*args[, ...])	Bootstrap where each input is independently resampled
<i>StationaryBootstrap</i> (block_size, *args[, ...])	Politis and Romano (1994) bootstrap with exponentially distributed block sizes
<i>CircularBlockBootstrap</i> (block_size, *args[, ...])	Bootstrap using blocks of the same length with end-to-start wrap around
<i>MovingBlockBootstrap</i> (block_size, *args[, ...])	Bootstrap using blocks of the same length without wrap around

7.5.1 Block-length Selection

<i>optimal_block_length</i> (x)	Estimate optimal window length for time-series bootstraps
---------------------------------	---

7.6 Testing with Multiple-Comparison

<i>SPA</i> (benchmark, models[, block_size, reps, ...])	Test of Superior Predictive Ability (SPA) of White and Hansen.
<i>MCS</i> (losses, size[, reps, block_size, ...])	Model Confidence Set (MCS) of Hansen, Lunde and Naason.
<i>StepM</i> (benchmark, models[, size, block_size, ...])	StepM multiple comparison procedure of Romano and Wolf.

7.7 Long-run Covariance (HAC) Estimation

<i>Bartlett</i> (x[, bandwidth, df_adjust, center, ...])	Bartlett's (Newey-West) kernel covariance estimation.
<i>Parzen</i> (x[, bandwidth, df_adjust, center, ...])	Parzen's kernel covariance estimation.
<i>ParzenCauchy</i> (x[, bandwidth, df_adjust, ...])	Parzen's Cauchy kernel covariance estimation.
<i>ParzenGeometric</i> (x[, bandwidth, df_adjust, ...])	Parzen's Geometric kernel covariance estimation.
<i>ParzenRiesz</i> (x[, bandwidth, df_adjust, ...])	Parzen-Reisz kernel covariance estimation.
<i>QuadraticSpectral</i> (x[, bandwidth, df_adjust, ...])	Quadratic-Spectral (Andrews') kernel covariance estimation.
<i>TukeyHamming</i> (x[, bandwidth, df_adjust, ...])	Tukey-Hamming kernel covariance estimation.
<i>TukeyHanning</i> (x[, bandwidth, df_adjust, ...])	Tukey-Hanning kernel covariance estimation.
<i>TukeyParzen</i> (x[, bandwidth, df_adjust, ...])	Tukey-Parzen kernel covariance estimation.

CHANGE LOGS

8.1 Version 5

8.1.1 Release 5.5

- NumPy 1.25 fixes
- Initial pandas copy-on-write support
- Switched doc theme to sphinx-immaterial
- Small fixes for typing issues

8.1.2 Release 5.4

- Compatability release with pandas 2.0
- Add testing and wheel support for Python 3.11

8.1.3 Release 5.3

- Fixed a bug in `arch_model()` where `power` was not passed to the *FIGARCH* constructor ([GH572](#)).
- Fixed a bug that affected downstream projects due to an overly specific assert ([GH569](#)).

8.1.4 Release 5.2

- Fixed a bug in `std_resid()` that would raise an exception when the data used to construct the model with a NumPy array ([GH565](#)).
- Fixed a bug in *forecast()* and related `forecast` methods when producing multi-step forecasts using simulation with exogenous variables ([GH551](#)).

8.1.5 Release 5.1

Unit Root

- Improved automatic lag length selection in *DFGLS* by using OLS rather than GLS detrended data when selecting the lag length. This problem was studied by Perron, P., & Qu, Z. (2007).

8.1.6 Release 5.0

Unit Root

- All unit root tests are now immutable, and so properties such as `trend` cannot be set after the test is created.

Bootstrap

- Added `seed` keyword argument to all bootstraps (e.g., *IIDBootstrap* and *StationaryBootstrap*) that allows a NumPy `numpy.random.Generator` to be used. The `seed` keyword argument also accepts legacy `numpy.random.RandomState` instances and integers. If an integer is passed, the random number generator is constructed by calling `numpy.random.default_rng()`. The `seed` keyword argument replaces the `random_state` keyword argument.
- The `random_state()` property has also been deprecated in favor of `generator()`.
- The `get_state()` and `set_state()` methods have been replaced by the `state()` property.

Volatility Modeling

- Added `seed` keyword argument to all distributions (e.g., *Normal* and *StudentsT*) that allows a NumPy `numpy.random.Generator` to be used. The `seed` keyword argument also accepts legacy `numpy.random.RandomState` instances and integers. If an integer is passed, the random number generator is constructed by calling `numpy.random.default_rng()`. The `seed` keyword argument replaces the `random_state` keyword argument.
- The `random_state()` property has also been deprecated in favor of `generator()`.
- Added *ARCHInMean* mean process supporting (G)ARCH-in-mean models.
- Extended *VolatilityProcess* with `volatility_updater()` that contains a *VolatilityUpdater* to allow *ARCHInMean* to be created from different volatility processes.

Setup

- Added support for using an environmental variable to disable C-extension compilation.
 - Linux and OSX: `export ARCH_NO_BINARY=1`
 - PowerShell: `$env:ARCH_NO_BINARY=1`
 - cmd: `set ARCH_NO_BINARY=1`

8.2 Version 4

8.2.1 Release 4.19

- Added the keyword argument `reindex` to `forecast()` that allows the returned forecasts to have minimal size when `reindex=False`. The default is `reindex=True` which preserved the current behavior. This will change in a future release. Using `reindex=True` often requires substantially more memory than when `reindex=False`. This is especially true when using simulation or bootstrap-based forecasting.
- The default value `reindex` can be changed by importing

```
from arch.__future__ import reindexing
```

- Fixed handling of exogenous regressors in `forecast()`. It is now possible to pass values for $E_t[X_{t+h}]$ using the `x` argument.

8.2.2 Release 4.18

- Improved `fit()` performance of ARCH models.
- Fixed a bug where ``typing_extensions`` was subtly introduced as a run-time dependency.

8.2.3 Release 4.17

- Fixed a bug that produced incorrect conditional volatility from EWMA models ([GH458](#)).

8.2.4 Release 4.16

- Added `APARCH` volatility process ([GH443](#)).
- Added support for Python 3.9 in `pyproject.toml` ([GH438](#)).
- Fixed a bug in model degree-of-freedom calculation ([GH437](#)).
- Improved HARX initialization ([GH417](#)).

8.2.5 Release 4.15

- This is a minor release with doc fixes and other small updates. The only notable feature is `regression()` which returns regression results from the model estimated as part of the test ([GH395](#)).

8.2.6 Release 4.14

- Added Kernel-based long-run variance estimation in `arch.covariance.kernel`. Examples include the `Bartlett` and the `Parzen` kernels. All estimators suppose automatic bandwidth selection.
- Improved exceptions in `ADF`, `KPSS`, `PhillipsPerron`, `VarianceRatio`, and `ZivotAndrews` when test specification is infeasible to the time series being too short or the required regression model having reduced rank ([GH364](#)).
- Fixed a bug when using “bca” confidence intervals with `extra_kwargs` ([GH366](#)).
- Added Phillips-Ouliaris (`phillips_ouliaris()`) cointegration tests ([GH360](#)).

- Added three methods to estimate cointegrating vectors: `CanonicalCointegratingReg`, `DynamicOLS`, and `FullyModifiedOLS` (GH356, GH359).
- Added the Engle-Granger (`engle_granger()`) cointegration test (GH354).
- Issue warnings when unit root tests are mutated. Will raise after 5.0 is released.
- Fixed a bug in `arch.univariate.SkewStudent` which did not use the user-provided `RandomState` when one was provided. This prevented reproducing simulated values (GH353).

8.2.7 Release 4.13

- Restored the vendored copy of `property_cached` for conda package building.

8.2.8 Release 4.12

- Added typing support to all classes, functions and methods (GH338, GH341, GH342, GH343, GH345, GH346).
- Fixed an issue that caused tests to fail on SciPy 1.4+ (GH339).
- Dropped support for Python 3.5 inline with NEP 29 (GH334).
- Added methods to compute moment and lower partial moments for standardized residuals. See, for example, `moment()` and `partial_moment()` (GH329).
- Fixed a bug that produced an `OverflowError` when a time series has no variance (GH331).

8.2.9 Release 4.11

- Added `std_resid()` (GH326).
- Error if inputs are not `ndarrays`, `DataFrames` or `Series` (GH315).
- Added a check that the covariance is non-zero when using “studentized” confidence intervals. If the function bootstrapped produces statistics with 0 variance, it is not possible to studentized (GH322).

8.2.10 Release 4.10

- Fixed a bug in `arch_lm_test` that assumed that the model data is contained in a pandas `Series`. (GH313).
- Fixed a bug that can affect use in certain environments that reload modules (GH317).

8.2.11 Release 4.9

- Removed support for Python 2.7.
- Added `auto_bandwidth()` to compute optimized bandwidth for a number of common kernel covariance estimators (GH303). This code was written by Michael Rabba.
- Added a parameter `rescale` to `arch_model()` that allows the estimator to rescale data if it may help parameter estimation. If `rescale=True`, then the data will be rescaled by a power of 10 (e.g., 10, 100, or 1000) to produce a series with a residual variance between 1 and 1000. The model is then estimated on the rescaled data. The scale is reported `scale()`. If `rescale=None`, a warning is produced if the data appear to be poorly scaled, but no change of scale is applied. If `rescale=False`, no scale change is applied and no warning is issued.

- Fixed a bug when using the BCA bootstrap method where the leave-one-out jackknife used the wrong centering variable (GH288).
- Added `optimization_result()` to simplify checking for convergence of the numerical optimizer (GH292).
- Added `random_state` argument to `forecast()` to allow a `RandomState` object to be passed in when forecasting when `method='bootstrap'`. This allows the repeatable forecast to be produced (GH290).
- Fixed a bug in `VarianceRatio` that used the wrong variance in nonrobust inference with overlapping samples (GH286).

8.2.12 Release 4.8.1

- Fixed a bug which prevented extension modules from being correctly imported.

8.2.13 Release 4.8

- Added Zivot-Andrews unit root test `ZivotAndrews`. This code was originally written by Jim Varanelli.
- Added data dependent lag length selection to the KPSS test, `KPSS`. This code was originally written by Jim Varanelli.
- Added `IndependentSamplesBootstrap` to perform bootstrap inference on statistics from independent samples that may have uneven length (GH260).
- Added `arch_lm_test()` to perform ARCH-LM tests on model residuals or standardized residuals (GH261).
- Fixed a bug in `ADF` when applying to very short time series (GH262).
- Added ability to set the `random_state` when initializing a bootstrap (GH259).

8.2.14 Release 4.7

- Added support for Fractionally Integrated GARCH (FIGARCH) in `FIGARCH`.
- Enable user to specify a specific value of the `backcast` in place of the automatically generated value.
- Fixed a bug where parameter-less models were incorrectly reported as having constant variance (GH248).

8.2.15 Release 4.6

- Added support for MIDAS volatility processes using Hyperbolic weighting in `MidasHyperbolic` (GH233).

8.2.16 Release 4.5

- Added a parameter to `forecast` that allows a user-provided callable random generator to be used in place of the model random generator (GH225).
- Added a low memory automatic lag selection method that can be used with very large time-series.
- Improved performance of automatic lag selection in ADF and related tests.

8.2.17 Release 4.4

- Added named parameters to Dickey-Fuller regressions.
- Removed use of the module-level NumPy RandomState. All random number generators use separate RandomState instances.
- Fixed a bug that prevented 1-step forecasts with exogenous regressors.
- Added the Generalized Error Distribution for univariate ARCH models.
- Fixed a bug in MCS when using the max method that prevented all included models from being listed.

8.2.18 Release 4.3

- Added *FixedVariance* volatility process which allows pre-specified variances to be used with a mean model. This has been added to allow so-called zig-zag estimation where a mean model is estimated with a fixed variance, and then a variance model is estimated on the residuals using a *ZeroMean* variance process.

8.2.19 Release 4.2

- Fixed a bug that prevented `fix` from being used with a new model ([GH156](#)).
- Added `first_obs` and `last_obs` parameters to `fix` to mimic `fit`.
- Added ability to jointly estimate smoothing parameter in EWMA variance when fitting the model.
- Added ability to pass optimization options to ARCH model estimation ([GH195](#)).

8.3 Version 3

- Added forecast code for mean forecasting
- Added volatility hedgehog plot
- Added `fix` to arch models which allows for user specified parameters instead of estimated parameters.
- Added Hansen's Skew T distribution to distribution (Stanislav Khrapov)
- Updated IPython notebooks to latest IPython version
- Bug and typo fixes to IPython notebooks
- Changed MCS to give a pvalue of 1.0 to best model. Previously was NaN
- Removed `hold_back` and `last_obs` from model initialization and to `fit` method to simplify estimating a model over alternative samples (e.g., rolling window estimation)
- Redefined `hold_back` to only accept integers so that is simply defined the number of observations held back. This number is now held out of the sample irrespective of the value of `first_obs`.

8.4 Version 2

8.4.1 Version 2.2

- Added multiple comparison procedures
- Typographical and other small changes

8.4.2 Version 2.1

- Add unit root tests: * Augmented Dickey-Fuller * Dickey-Fuller GLS * Phillips-Perron * KPSS * Variance Ratio
- Removed deprecated locations for ARCH modeling functions

8.5 Version 1

8.5.1 Version 1.1

- Refactored to move the univariate routines to *arch.univariate* and added deprecation warnings in the old locations
- Enable *numba* jit compilation in the python recursions
- Added a bootstrap framework, which will be used in future versions. The bootstrap framework is general purpose and can be used via high-level functions such as *conf_int* or *cov*, or as a low level iterator using *bootstrap*

CITATION

This package should be cited using Zenodo. For example, for the 4.13 release,

INDEX

- genindex
- modindex

BIBLIOGRAPHY

- [Chernick] Chernick, M. R. (2011). *Bootstrap methods: A guide for practitioners and researchers* (Vol. 619). John Wiley & Sons.
- [Davidson] Davison, A. C. (1997). *Bootstrap methods and their application* (Vol. 1). Cambridge university press.
- [EfronTibshirani] Efron, B., & Tibshirani, R. J. (1994). *An introduction to the bootstrap* (Vol. 57). CRC press.
- [PolitisRomanoWolf] Politis, D. N., & Romano, J. P. M. Wolf, 1999. *Subsampling*.
- [CarpenterBithell] Carpenter, J., & Bithell, J. (2000). "Bootstrap confidence intervals: when, which, what? A practical guide for medical statisticians." *Statistics in medicine*, 19(9), 1141-1164.
- [DavidsonMacKinnon] Davidson, R., & MacKinnon, J. G. (2006). "Bootstrap methods in econometrics." *Palgrave Handbook of Econometrics*, 1, 812-38.
- [DiCiccioEfron] DiCiccio, T. J., & Efron, B. (1996). "Bootstrap confidence intervals." *Statistical Science*, 189-212.
- [Efron] Efron, B. (1987). "Better bootstrap confidence intervals." *Journal of the American statistical Association*, 82(397), 171-185.
- [Hansen] Hansen, P. R. (2005). A test for superior predictive ability. *Journal of Business & Economic Statistics*, 23(4).
- [HansenLundeNason] Hansen, P. R., Lunde, A., & Nason, J. M. (2011). The model confidence set. *Econometrica*, 79(2), 453-497.
- [RomanoWolf] Romano, J. P., & Wolf, M. (2005). Stepwise multiple testing as formalized data snooping. *Econometrica*, 73(4), 1237-1282.
- [White] White, H. (2000). A reality check for data snooping. *Econometrica*, 68(5), 1097-1126.

PYTHON MODULE INDEX

a

- `arch.bootstrap`, [255](#)
- `arch.bootstrap.multiple_comparison`, [336](#)
- `arch.covariance.kernel`, [417](#)
- `arch.unitroot`, [356](#)
- `arch.unitroot.cointegration`, [390](#)
- `arch.utility.testing`, [253](#)

A

- ADF (*class in arch.unitroot*), 356
- aic (*arch.univariate.base.ARCHModelFixedResult* property), 251
- aic (*arch.univariate.base.ARCHModelResult* property), 243
- alternative_hypothesis (*arch.unitroot.ADF* property), 358
- alternative_hypothesis (*arch.unitroot.cointegration.EngleGrangerTestResults* property), 410
- alternative_hypothesis (*arch.unitroot.cointegration.PhillipsOuliarisTestResults* property), 414
- alternative_hypothesis (*arch.unitroot.DFGLS* property), 362
- alternative_hypothesis (*arch.unitroot.KPSS* property), 378
- alternative_hypothesis (*arch.unitroot.PhillipsPerron* property), 366
- alternative_hypothesis (*arch.unitroot.VarianceRatio* property), 374
- alternative_hypothesis (*arch.unitroot.ZivotAndrews* property), 371
- Andrews (*class in arch.covariance.kernel*), 417
- APARCH (*class in arch.univariate*), 165
- apply() (*arch.bootstrap.CircularBlockBootstrap* method), 307
- apply() (*arch.bootstrap.IIDBootstrap* method), 275
- apply() (*arch.bootstrap.IndependentSamplesBootstrap* method), 285
- apply() (*arch.bootstrap.MovingBlockBootstrap* method), 317
- apply() (*arch.bootstrap.StationaryBootstrap* method), 296
- ARCH (*class in arch.univariate*), 158
- arch.bootstrap
 - module, 255
- arch.bootstrap.multiple_comparison
 - module, 336
- arch.covariance.kernel
 - module, 417
- arch.unitroot
 - module, 356
- arch.unitroot.cointegration
 - module, 390
- arch.utility.testing
 - module, 253
- arch_lm_test() (*arch.univariate.base.ARCHModelFixedResult* method), 247
- arch_lm_test() (*arch.univariate.base.ARCHModelResult* method), 238
- arch_model() (*in module arch.univariate*), 5
- ARCHInMean (*class in arch.univariate*), 96
- ARCHModel (*class in arch.univariate.base*), 106
- ARCHModelFixedResult (*class in arch.univariate.base*), 246
- ARCHModelForecast (*class in arch.univariate.base*), 23
- ARCHModelForecastSimulation (*class in arch.univariate.base*), 25
- ARCHModelResult (*class in arch.univariate.base*), 237
- ARX (*class in arch.univariate*), 69
- auto_bandwidth() (*in module arch.unitroot*), 380

B

- backcast() (*arch.univariate.APARCH* method), 167
- backcast() (*arch.univariate.ARCH* method), 159
- backcast() (*arch.univariate.ConstantVariance* method), 114
- backcast() (*arch.univariate.EGARCH* method), 137
- backcast() (*arch.univariate.EWMAVariance* method), 175
- backcast() (*arch.univariate.FIGARCH* method), 130
- backcast() (*arch.univariate.FixedVariance* method), 189
- backcast() (*arch.univariate.GARCH* method), 122
- backcast() (*arch.univariate.HARCH* method), 145
- backcast() (*arch.univariate.MIDASHyperbolic* method), 152
- backcast() (*arch.univariate.RiskMetrics2006* method), 182
- backcast() (*arch.univariate.volatility.VolatilityProcess* method), 196

- `backcast_transform()` (*arch.univariate.APARCH method*), 167
- `backcast_transform()` (*arch.univariate.ARCH method*), 160
- `backcast_transform()` (*arch.univariate.ConstantVariance method*), 115
- `backcast_transform()` (*arch.univariate.EGARCH method*), 138
- `backcast_transform()` (*arch.univariate.EWMAVariance method*), 175
- `backcast_transform()` (*arch.univariate.FIGARCH method*), 130
- `backcast_transform()` (*arch.univariate.FixedVariance method*), 189
- `backcast_transform()` (*arch.univariate.GARCH method*), 122
- `backcast_transform()` (*arch.univariate.HARCH method*), 145
- `backcast_transform()` (*arch.univariate.MIDASHyperbolic method*), 153
- `backcast_transform()` (*arch.univariate.RiskMetrics2006 method*), 182
- `backcast_transform()` (*arch.univariate.volatility.VolatilityProcess method*), 196
- `bandwidth` (*arch.covariance.kernel.Andrews property*), 418
- `bandwidth` (*arch.covariance.kernel.Bartlett property*), 422
- `bandwidth` (*arch.covariance.kernel.Gallant property*), 425
- `bandwidth` (*arch.covariance.kernel.NeweyWest property*), 428
- `bandwidth` (*arch.covariance.kernel.Parzen property*), 431
- `bandwidth` (*arch.covariance.kernel.ParzenCauchy property*), 435
- `bandwidth` (*arch.covariance.kernel.ParzenGeometric property*), 438
- `bandwidth` (*arch.covariance.kernel.ParzenRiesz property*), 442
- `bandwidth` (*arch.covariance.kernel.QuadraticSpectral property*), 445
- `bandwidth` (*arch.covariance.kernel.TukeyHamming property*), 449
- `bandwidth` (*arch.covariance.kernel.TukeyHanning property*), 452
- `bandwidth` (*arch.covariance.kernel.TukeyParzen property*), 456
- `bandwidth` (*arch.unitroot.cointegration.CointegrationAnalysisResults property*), 401
- `bandwidth` (*arch.unitroot.cointegration.DynamicOLSResults property*), 405
- `bandwidth` (*arch.unitroot.cointegration.PhillipsOuliarisTestResults property*), 414
- `bandwidth_scale` (*arch.covariance.kernel.Andrews property*), 418
- `bandwidth_scale` (*arch.covariance.kernel.Bartlett property*), 422
- `bandwidth_scale` (*arch.covariance.kernel.Gallant property*), 425
- `bandwidth_scale` (*arch.covariance.kernel.NeweyWest property*), 428
- `bandwidth_scale` (*arch.covariance.kernel.Parzen property*), 431
- `bandwidth_scale` (*arch.covariance.kernel.ParzenCauchy property*), 435
- `bandwidth_scale` (*arch.covariance.kernel.ParzenGeometric property*), 438
- `bandwidth_scale` (*arch.covariance.kernel.ParzenRiesz property*), 442
- `bandwidth_scale` (*arch.covariance.kernel.QuadraticSpectral property*), 445
- `bandwidth_scale` (*arch.covariance.kernel.TukeyHamming property*), 449
- `bandwidth_scale` (*arch.covariance.kernel.TukeyHanning property*), 452
- `bandwidth_scale` (*arch.covariance.kernel.TukeyParzen property*), 456
- `Bartlett` (*class in arch.covariance.kernel*), 420
- `better_models()` (*arch.bootstrap.SPA method*), 337
- `bic` (*arch.univariate.base.ARCHModelFixedResult property*), 252
- `bic` (*arch.univariate.base.ARCHModelResult property*), 244
- `bootstrap()` (*arch.bootstrap.CircularBlockBootstrap method*), 307
- `bootstrap()` (*arch.bootstrap.IIDBootstrap method*), 275
- `bootstrap()` (*arch.bootstrap.IndependentSamplesBootstrap method*), 286
- `bootstrap()` (*arch.bootstrap.MovingBlockBootstrap method*), 318
- `bootstrap()` (*arch.bootstrap.StationaryBootstrap method*), 297
- `bounds()` (*arch.univariate.APARCH method*), 167
- `bounds()` (*arch.univariate.ARCH method*), 160
- `bounds()` (*arch.univariate.ARCHInMean method*), 98
- `bounds()` (*arch.univariate.ARX method*), 71
- `bounds()` (*arch.univariate.base.ARCHModel method*), 107
- `bounds()` (*arch.univariate.ConstantMean method*), 62
- `bounds()` (*arch.univariate.ConstantVariance method*),

- 115
- `bounds()` (*arch.univariate.distribution.Distribution* method), 232
- `bounds()` (*arch.univariate.EGARCH* method), 138
- `bounds()` (*arch.univariate.EWMAVariance* method), 175
- `bounds()` (*arch.univariate.FIGARCH* method), 130
- `bounds()` (*arch.univariate.FixedVariance* method), 190
- `bounds()` (*arch.univariate.GARCH* method), 123
- `bounds()` (*arch.univariate.GeneralizedError* method), 226
- `bounds()` (*arch.univariate.HARCH* method), 145
- `bounds()` (*arch.univariate.HARX* method), 80
- `bounds()` (*arch.univariate.LS* method), 89
- `bounds()` (*arch.univariate.MIDASHyperbolic* method), 153
- `bounds()` (*arch.univariate.Normal* method), 210
- `bounds()` (*arch.univariate.RiskMetrics2006* method), 183
- `bounds()` (*arch.univariate.SkewStudent* method), 221
- `bounds()` (*arch.univariate.StudentsT* method), 215
- `bounds()` (*arch.univariate.volatility.VolatilityProcess* method), 196
- `bounds()` (*arch.univariate.ZeroMean* method), 54
- ## C
- `CanonicalCointegratingReg` (class in *arch.unitroot.cointegration*), 398
- `cdf()` (*arch.univariate.distribution.Distribution* method), 232
- `cdf()` (*arch.univariate.GeneralizedError* method), 227
- `cdf()` (*arch.univariate.Normal* method), 211
- `cdf()` (*arch.univariate.SkewStudent* method), 221
- `cdf()` (*arch.univariate.StudentsT* method), 216
- `centered` (*arch.covariance.kernel.Andrews* property), 418
- `centered` (*arch.covariance.kernel.Bartlett* property), 422
- `centered` (*arch.covariance.kernel.Gallant* property), 425
- `centered` (*arch.covariance.kernel.NeweyWest* property), 428
- `centered` (*arch.covariance.kernel.Parzen* property), 432
- `centered` (*arch.covariance.kernel.ParzenCauchy* property), 435
- `centered` (*arch.covariance.kernel.ParzenGeometric* property), 439
- `centered` (*arch.covariance.kernel.ParzenRiesz* property), 442
- `centered` (*arch.covariance.kernel.QuadraticSpectral* property), 446
- `centered` (*arch.covariance.kernel.TukeyHamming* property), 449
- `centered` (*arch.covariance.kernel.TukeyHanning* property), 453
- `centered` (*arch.covariance.kernel.TukeyParzen* property), 456
- `CircularBlockBootstrap` (class in *arch.bootstrap*), 305
- `clone()` (*arch.bootstrap.CircularBlockBootstrap* method), 308
- `clone()` (*arch.bootstrap.IIDBootstrap* method), 276
- `clone()` (*arch.bootstrap.IndependentSamplesBootstrap* method), 287
- `clone()` (*arch.bootstrap.MovingBlockBootstrap* method), 319
- `clone()` (*arch.bootstrap.StationaryBootstrap* method), 298
- `cointegrating_vector` (*arch.unitroot.cointegration.EngleGrangerTestResults* property), 410
- `cointegrating_vector` (*arch.unitroot.cointegration.PhillipsOuliarisTestResults* property), 414
- `CointegrationAnalysisResults` (class in *arch.unitroot.cointegration*), 400
- `common_asym` (*arch.univariate.APARCH* property), 172
- `compute()` (*arch.bootstrap.MCS* method), 343
- `compute()` (*arch.bootstrap.SPA* method), 338
- `compute()` (*arch.bootstrap.StepM* method), 341
- `compute_param_cov()` (*arch.univariate.ARCHInMean* method), 98
- `compute_param_cov()` (*arch.univariate.ARX* method), 71
- `compute_param_cov()` (*arch.univariate.base.ARCHModel* method), 107
- `compute_param_cov()` (*arch.univariate.ConstantMean* method), 63
- `compute_param_cov()` (*arch.univariate.HARX* method), 81
- `compute_param_cov()` (*arch.univariate.LS* method), 89
- `compute_param_cov()` (*arch.univariate.ZeroMean* method), 54
- `compute_variance()` (*arch.univariate.APARCH* method), 168
- `compute_variance()` (*arch.univariate.ARCH* method), 160
- `compute_variance()` (*arch.univariate.ConstantVariance* method), 115
- `compute_variance()` (*arch.univariate.EGARCH* method), 138
- `compute_variance()` (*arch.univariate.EWMAVariance* method), 176
- `compute_variance()` (*arch.univariate.FIGARCH* method), 131
- `compute_variance()` (*arch.univariate.FixedVariance* method), 190
- `compute_variance()` (*arch.univariate.GARCH*

- method*), 123
- `compute_variance()` (*arch.univariate.HARCH method*), 146
- `compute_variance()` (*arch.univariate.MIDASHyperbolic method*), 153
- `compute_variance()` (*arch.univariate.RiskMetrics2006 method*), 183
- `compute_variance()` (*arch.univariate.volatility.VolatilityProcess method*), 197
- `conditional_volatility` (*arch.univariate.base.ARCHModelFixedResult property*), 252
- `conditional_volatility` (*arch.univariate.base.ARCHModelResult property*), 244
- `conf_int()` (*arch.bootstrap.CircularBlockBootstrap method*), 309
- `conf_int()` (*arch.bootstrap.IIDBootstrap method*), 277
- `conf_int()` (*arch.bootstrap.IndependentSamplesBootstrap method*), 287
- `conf_int()` (*arch.bootstrap.MovingBlockBootstrap method*), 319
- `conf_int()` (*arch.bootstrap.StationaryBootstrap method*), 298
- `conf_int()` (*arch.univariate.base.ARCHModelResult method*), 238
- `ConstantMean` (*class in arch.univariate*), 61
- `ConstantVariance` (*class in arch.univariate*), 114
- `constraints()` (*arch.univariate.APARCH method*), 168
- `constraints()` (*arch.univariate.ARCH method*), 161
- `constraints()` (*arch.univariate.ARCHInMean method*), 99
- `constraints()` (*arch.univariate.ARX method*), 72
- `constraints()` (*arch.univariate.base.ARCHModel method*), 108
- `constraints()` (*arch.univariate.ConstantMean method*), 63
- `constraints()` (*arch.univariate.ConstantVariance method*), 116
- `constraints()` (*arch.univariate.distribution.Distribution method*), 233
- `constraints()` (*arch.univariate.EGARCH method*), 139
- `constraints()` (*arch.univariate.EWMAVariance method*), 176
- `constraints()` (*arch.univariate.FIGARCH method*), 131
- `constraints()` (*arch.univariate.FixedVariance method*), 190
- `constraints()` (*arch.univariate.GARCH method*), 123
- `constraints()` (*arch.univariate.GeneralizedError method*), 227
- `constraints()` (*arch.univariate.HARCH method*), 146
- `constraints()` (*arch.univariate.HARX method*), 81
- `constraints()` (*arch.univariate.LS method*), 90
- `constraints()` (*arch.univariate.MIDASHyperbolic method*), 154
- `constraints()` (*arch.univariate.Normal method*), 211
- `constraints()` (*arch.univariate.RiskMetrics2006 method*), 183
- `constraints()` (*arch.univariate.SkewStudent method*), 222
- `constraints()` (*arch.univariate.StudentsT method*), 216
- `constraints()` (*arch.univariate.volatility.VolatilityProcess method*), 197
- `constraints()` (*arch.univariate.ZeroMean method*), 55
- `convergence_flag` (*arch.univariate.base.ARCHModelResult property*), 244
- `cov` (*arch.covariance.kernel.Andrews property*), 419
- `cov` (*arch.covariance.kernel.Bartlett property*), 422
- `cov` (*arch.covariance.kernel.Gallant property*), 425
- `cov` (*arch.covariance.kernel.NeweyWest property*), 428
- `cov` (*arch.covariance.kernel.Parzen property*), 432
- `cov` (*arch.covariance.kernel.ParzenCauchy property*), 435
- `cov` (*arch.covariance.kernel.ParzenGeometric property*), 439
- `cov` (*arch.covariance.kernel.ParzenRiesz property*), 442
- `cov` (*arch.covariance.kernel.QuadraticSpectral property*), 446
- `cov` (*arch.covariance.kernel.TukeyHamming property*), 449
- `cov` (*arch.covariance.kernel.TukeyHanning property*), 453
- `cov` (*arch.covariance.kernel.TukeyParzen property*), 456
- `cov` (*arch.unitroot.cointegration.CointegrationAnalysisResults property*), 402
- `cov` (*arch.unitroot.cointegration.DynamicOLSResults property*), 405
- `cov()` (*arch.bootstrap.CircularBlockBootstrap method*), 310
- `cov()` (*arch.bootstrap.IIDBootstrap method*), 278
- `cov()` (*arch.bootstrap.IndependentSamplesBootstrap method*), 289
- `cov()` (*arch.bootstrap.MovingBlockBootstrap method*), 321
- `cov()` (*arch.bootstrap.StationaryBootstrap method*), 300
- `cov_type` (*arch.unitroot.cointegration.DynamicOLSResults property*), 406
- `CovarianceEstimate` (*class in arch.covariance.kernel*), 458
- `critical_values` (*arch.unitroot.ADF property*), 358
- `critical_values` (*arch.unitroot.cointegration.EngleGrangerTestResults property*), 411
- `critical_values` (*arch.unitroot.cointegration.PhillipsOuliarisTestResults property*), 415
- `critical_values` (*arch.unitroot.DFGLS property*), 362
- `critical_values` (*arch.unitroot.KPSS property*), 379

- `critical_values` (`arch.unitroot.PhillipsPerron` property), 367
- `critical_values` (`arch.unitroot.VarianceRatio` property), 374
- `critical_values` (`arch.unitroot.ZivotAndrews` property), 371
- `critical_values` (`arch.utility.testing.WaldTestStatistic` property), 253
- `critical_values()` (`arch.bootstrap.SPA` method), 338
- ## D
- `data` (`arch.bootstrap.CircularBlockBootstrap` attribute), 305
- `data` (`arch.bootstrap.IIDBootstrap` attribute), 273
- `data` (`arch.bootstrap.IndependentSamplesBootstrap` attribute), 283
- `data` (`arch.bootstrap.MovingBlockBootstrap` attribute), 315
- `data` (`arch.bootstrap.StationaryBootstrap` attribute), 295
- `debiased` (`arch.unitroot.VarianceRatio` property), 375
- `delta` (`arch.univariate.APARCH` property), 172
- `DFGLS` (class in `arch.unitroot`), 360
- `distribution` (`arch.univariate.ARCHInMean` property), 105
- `distribution` (`arch.univariate.ARX` property), 77
- `distribution` (`arch.univariate.base.ARCHModel` property), 113
- `distribution` (`arch.univariate.ConstantMean` property), 68
- `distribution` (`arch.univariate.HARX` property), 87
- `distribution` (`arch.univariate.LS` property), 95
- `distribution` (`arch.univariate.ZeroMean` property), 60
- `Distribution` (class in `arch.univariate.distribution`), 231
- `distribution_order` (`arch.unitroot.cointegration.EngleGrangerTestResults` property), 411
- `distribution_order` (`arch.unitroot.cointegration.PhillipsOuliarisTestResults` property), 415
- `DynamicOLS` (class in `arch.unitroot.cointegration`), 394
- `DynamicOLSResults` (class in `arch.unitroot.cointegration`), 404
- ## E
- `EGARCH` (class in `arch.univariate`), 136
- `engle_granger()` (in module `arch.unitroot.cointegration`), 390
- `EngleGrangerTestResults` (class in `arch.unitroot.cointegration`), 408
- `EWMAVariance` (class in `arch.univariate`), 174
- `excluded` (`arch.bootstrap.MCS` property), 344
- ## F
- `FIGARCH` (class in `arch.univariate`), 128
- `fit()` (`arch.unitroot.cointegration.CanonicalCointegratingReg` method), 400
- `fit()` (`arch.unitroot.cointegration.DynamicOLS` method), 395
- `fit()` (`arch.unitroot.cointegration.FullyModifiedOLS` method), 398
- `fit()` (`arch.univariate.ARCHInMean` method), 99
- `fit()` (`arch.univariate.ARX` method), 72
- `fit()` (`arch.univariate.base.ARCHModel` method), 108
- `fit()` (`arch.univariate.ConstantMean` method), 63
- `fit()` (`arch.univariate.HARX` method), 81
- `fit()` (`arch.univariate.LS` method), 90
- `fit()` (`arch.univariate.ZeroMean` method), 55
- `fit_start` (`arch.univariate.base.ARCHModelResult` property), 244
- `fit_stop` (`arch.univariate.base.ARCHModelResult` property), 244
- `fix()` (`arch.univariate.ARCHInMean` method), 100
- `fix()` (`arch.univariate.ARX` method), 73
- `fix()` (`arch.univariate.base.ARCHModel` method), 109
- `fix()` (`arch.univariate.ConstantMean` method), 64
- `fix()` (`arch.univariate.HARX` method), 82
- `fix()` (`arch.univariate.LS` method), 91
- `fix()` (`arch.univariate.ZeroMean` method), 56
- `FixedVariance` (class in `arch.univariate`), 188
- `force_int` (`arch.covariance.kernel.Andrews` property), 419
- `force_int` (`arch.covariance.kernel.Bartlett` property), 423
- `force_int` (`arch.covariance.kernel.Gallant` property), 426
- `force_int` (`arch.covariance.kernel.NeweyWest` property), 429
- `force_int` (`arch.covariance.kernel.Parzen` property), 432
- `force_int` (`arch.covariance.kernel.ParzenCauchy` property), 436
- `force_int` (`arch.covariance.kernel.ParzenGeometric` property), 439
- `force_int` (`arch.covariance.kernel.ParzenRiesz` property), 443
- `force_int` (`arch.covariance.kernel.QuadraticSpectral` property), 446
- `force_int` (`arch.covariance.kernel.TukeyHamming` property), 450
- `force_int` (`arch.covariance.kernel.TukeyHanning` property), 453
- `force_int` (`arch.covariance.kernel.TukeyParzen` property), 457
- `forecast()` (`arch.univariate.APARCH` method), 168
- `forecast()` (`arch.univariate.ARCH` method), 161
- `forecast()` (`arch.univariate.ARCHInMean` method), 100
- `forecast()` (`arch.univariate.ARX` method), 73

- `forecast()` (*arch.univariate.base.ARCHModel* method), 109
- `forecast()` (*arch.univariate.base.ARCHModelFixedResult* method), 247
- `forecast()` (*arch.univariate.base.ARCHModelResult* method), 238
- `forecast()` (*arch.univariate.ConstantMean* method), 65
- `forecast()` (*arch.univariate.ConstantVariance* method), 116
- `forecast()` (*arch.univariate.EGARCH* method), 139
- `forecast()` (*arch.univariate.EWMAVariance* method), 176
- `forecast()` (*arch.univariate.FIGARCH* method), 131
- `forecast()` (*arch.univariate.FixedVariance* method), 191
- `forecast()` (*arch.univariate.GARCH* method), 124
- `forecast()` (*arch.univariate.HARCH* method), 146
- `forecast()` (*arch.univariate.HARX* method), 83
- `forecast()` (*arch.univariate.LS* method), 91
- `forecast()` (*arch.univariate.MIDASHyperbolic* method), 154
- `forecast()` (*arch.univariate.RiskMetrics2006* method), 184
- `forecast()` (*arch.univariate.volatility.VolatilityProcess* method), 197
- `forecast()` (*arch.univariate.ZeroMean* method), 56
- `form` (*arch.univariate.ARCHInMean* property), 105
- `full_cov` (*arch.unitroot.cointegration.DynamicOLSResults* property), 406
- `full_params` (*arch.unitroot.cointegration.DynamicOLSResults* property), 406
- `FullyModifiedOLS` (class in *arch.unitroot.cointegration*), 396
- ## G
- `Gallant` (class in *arch.covariance.kernel*), 424
- `GARCH` (class in *arch.univariate*), 120
- `GeneralizedError` (class in *arch.univariate*), 226
- `generator` (*arch.bootstrap.CircularBlockBootstrap* property), 314
- `generator` (*arch.bootstrap.IIDBootstrap* property), 282
- `generator` (*arch.bootstrap.IndependentSamplesBootstrap* property), 293
- `generator` (*arch.bootstrap.MovingBlockBootstrap* property), 325
- `generator` (*arch.bootstrap.StationaryBootstrap* property), 304
- `generator` (*arch.univariate.distribution.Distribution* property), 236
- `generator` (*arch.univariate.GeneralizedError* property), 231
- `generator` (*arch.univariate.Normal* property), 214
- `generator` (*arch.univariate.SkewStudent* property), 225
- `generator` (*arch.univariate.StudentsT* property), 220
- `get_state()` (*arch.bootstrap.CircularBlockBootstrap* method), 312
- `get_state()` (*arch.bootstrap.IIDBootstrap* method), 280
- `get_state()` (*arch.bootstrap.IndependentSamplesBootstrap* method), 290
- `get_state()` (*arch.bootstrap.MovingBlockBootstrap* method), 322
- `get_state()` (*arch.bootstrap.StationaryBootstrap* method), 301
- ## H
- `HARCH` (class in *arch.univariate*), 144
- `HARX` (class in *arch.univariate*), 78
- `hedgehog_plot()` (*arch.univariate.base.ARCHModelFixedResult* method), 249
- `hedgehog_plot()` (*arch.univariate.base.ARCHModelResult* method), 240
- ## I
- `IIDBootstrap` (class in *arch.bootstrap*), 273
- `included` (*arch.bootstrap.MCS* property), 344
- `IndependentSamplesBootstrap` (class in *arch.bootstrap*), 283
- `index` (*arch.bootstrap.CircularBlockBootstrap* property), 314
- `index` (*arch.bootstrap.IIDBootstrap* property), 282
- `index` (*arch.bootstrap.IndependentSamplesBootstrap* property), 293
- `index` (*arch.bootstrap.MovingBlockBootstrap* property), 325
- `index` (*arch.bootstrap.StationaryBootstrap* property), 304
- `index` (*arch.univariate.base.ARCHModelForecastSimulation* property), 26
- `initialize_update()` (*arch.univariate.recursions_python.VolatilityUpdater* method), 203
- ## K
- `kernel` (*arch.unitroot.cointegration.CointegrationAnalysisResults* property), 402
- `kernel` (*arch.unitroot.cointegration.DynamicOLSResults* property), 406
- `kernel` (*arch.unitroot.cointegration.PhillipsOuliarisTestResults* property), 415
- `kernel_const` (*arch.covariance.kernel.Andrews* property), 419
- `kernel_const` (*arch.covariance.kernel.Bartlett* property), 423
- `kernel_const` (*arch.covariance.kernel.Gallant* property), 426
- `kernel_const` (*arch.covariance.kernel.NeweyWest* property), 429

- [kernel_const \(arch.covariance.kernel.Parzen property\), 432](#)
[kernel_const \(arch.covariance.kernel.ParzenCauchy property\), 436](#)
[kernel_const \(arch.covariance.kernel.ParzenGeometric property\), 439](#)
[kernel_const \(arch.covariance.kernel.ParzenRiesz property\), 443](#)
[kernel_const \(arch.covariance.kernel.QuadraticSpectral property\), 446](#)
[kernel_const \(arch.covariance.kernel.TukeyHamming property\), 450](#)
[kernel_const \(arch.covariance.kernel.TukeyHanning property\), 453](#)
[kernel_const \(arch.covariance.kernel.TukeyParzen property\), 457](#)
[kernel_weights \(arch.covariance.kernel.Andrews property\), 419](#)
[kernel_weights \(arch.covariance.kernel.Bartlett property\), 423](#)
[kernel_weights \(arch.covariance.kernel.Gallant property\), 426](#)
[kernel_weights \(arch.covariance.kernel.NeweyWest property\), 429](#)
[kernel_weights \(arch.covariance.kernel.Parzen property\), 433](#)
[kernel_weights \(arch.covariance.kernel.ParzenCauchy property\), 436](#)
[kernel_weights \(arch.covariance.kernel.ParzenGeometric property\), 440](#)
[kernel_weights \(arch.covariance.kernel.ParzenRiesz property\), 443](#)
[kernel_weights \(arch.covariance.kernel.QuadraticSpectral property\), 447](#)
[kernel_weights \(arch.covariance.kernel.TukeyHamming property\), 450](#)
[kernel_weights \(arch.covariance.kernel.TukeyHanning property\), 454](#)
[kernel_weights \(arch.covariance.kernel.TukeyParzen property\), 457](#)
[KPSS \(class in arch.unitroot\), 377](#)
[kw_data \(arch.bootstrap.CircularBlockBootstrap attribute\), 305](#)
[kw_data \(arch.bootstrap.IIDBootstrap attribute\), 273](#)
[kw_data \(arch.bootstrap.IndependentSamplesBootstrap attribute\), 284](#)
[kw_data \(arch.bootstrap.MovingBlockBootstrap attribute\), 316](#)
[kw_data \(arch.bootstrap.StationaryBootstrap attribute\), 295](#)
- L**
- [lags \(arch.unitroot.ADF property\), 358](#)
[lags \(arch.unitroot.cointegration.DynamicOLSResults property\), 406](#)
[lags \(arch.unitroot.cointegration.EngleGrangerTestResults property\), 411](#)
[lags \(arch.unitroot.DFGLS property\), 363](#)
[lags \(arch.unitroot.KPSS property\), 379](#)
[lags \(arch.unitroot.PhillipsPerron property\), 367](#)
[lags \(arch.unitroot.VarianceRatio property\), 375](#)
[lags \(arch.unitroot.ZivotAndrews property\), 371](#)
[leads \(arch.unitroot.cointegration.DynamicOLSResults property\), 406](#)
[loglikelihood \(arch.univariate.base.ARCHModelFixedResult property\), 252](#)
[loglikelihood \(arch.univariate.base.ARCHModelResult property\), 244](#)
[loglikelihood\(\) \(arch.univariate.distribution.Distribution method\), 233](#)
[loglikelihood\(\) \(arch.univariate.GeneralizedError method\), 227](#)
[loglikelihood\(\) \(arch.univariate.Normal method\), 211](#)
[loglikelihood\(\) \(arch.univariate.SkewStudent method\), 222](#)
[loglikelihood\(\) \(arch.univariate.StudentsT method\), 216](#)
[long_run \(arch.covariance.kernel.CovarianceEstimate property\), 459](#)
[long_run_variance \(arch.unitroot.cointegration.CointegrationAnalysisResults property\), 402](#)
[long_run_variance \(arch.unitroot.cointegration.DynamicOLSResults property\), 407](#)
[LS \(class in arch.univariate\), 88](#)
- M**
- [max_lags \(arch.unitroot.ADF property\), 359](#)
[max_lags \(arch.unitroot.cointegration.EngleGrangerTestResults property\), 411](#)
[max_lags \(arch.unitroot.DFGLS property\), 363](#)
[MCS \(class in arch.bootstrap\), 342](#)
[mean \(arch.univariate.base.ARCHModelForecast property\), 24](#)
[MIDASHyperbolic \(class in arch.univariate\), 151](#)
[model \(arch.univariate.base.ARCHModelFixedResult property\), 252](#)
[model \(arch.univariate.base.ARCHModelResult property\), 244](#)
[module](#)
 - [arch.bootstrap, 255](#)
 - [arch.bootstrap.multiple_comparison, 336](#)
 - [arch.covariance.kernel, 417](#)
 - [arch.unitroot, 356](#)
 - [arch.unitroot.cointegration, 390](#)
 - [arch.utility.testing, 253](#)

`moment()` (*arch.univariate.distribution.Distribution* method), 233
`moment()` (*arch.univariate.GeneralizedError* method), 228
`moment()` (*arch.univariate.Normal* method), 212
`moment()` (*arch.univariate.SkewStudent* method), 223
`moment()` (*arch.univariate.StudentsT* method), 217
`MovingBlockBootstrap` (class in *arch.bootstrap*), 315

N

`name` (*arch.covariance.kernel.Andrews* property), 420
`name` (*arch.covariance.kernel.Bartlett* property), 423
`name` (*arch.covariance.kernel.Gallant* property), 426
`name` (*arch.covariance.kernel.NeweyWest* property), 429
`name` (*arch.covariance.kernel.Parzen* property), 433
`name` (*arch.covariance.kernel.ParzenCauchy* property), 436
`name` (*arch.covariance.kernel.ParzenGeometric* property), 440
`name` (*arch.covariance.kernel.ParzenRiesz* property), 443
`name` (*arch.covariance.kernel.QuadraticSpectral* property), 447
`name` (*arch.covariance.kernel.TukeyHamming* property), 450
`name` (*arch.covariance.kernel.TukeyHanning* property), 454
`name` (*arch.covariance.kernel.TukeyParzen* property), 457
`name` (*arch.unitroot.cointegration.EngleGrangerTestResults* property), 411
`name` (*arch.unitroot.cointegration.PhillipsOuliarisTestResults* property), 415
`name` (*arch.univariate.APARCH* property), 172
`name` (*arch.univariate.ARCH* property), 164
`name` (*arch.univariate.ARCHInMean* property), 105
`name` (*arch.univariate.ARX* property), 77
`name` (*arch.univariate.base.ARCHModel* property), 113
`name` (*arch.univariate.ConstantMean* property), 69
`name` (*arch.univariate.ConstantVariance* property), 119
`name` (*arch.univariate.distribution.Distribution* property), 236
`name` (*arch.univariate.EGARCH* property), 142
`name` (*arch.univariate.EWMAVariance* property), 180
`name` (*arch.univariate.FIGARCH* property), 135
`name` (*arch.univariate.FixedVariance* property), 194
`name` (*arch.univariate.GARCH* property), 127
`name` (*arch.univariate.GeneralizedError* property), 231
`name` (*arch.univariate.HARCH* property), 150
`name` (*arch.univariate.HARX* property), 87
`name` (*arch.univariate.LS* property), 95
`name` (*arch.univariate.MIDASHyperbolic* property), 157
`name` (*arch.univariate.Normal* property), 214
`name` (*arch.univariate.RiskMetrics2006* property), 187
`name` (*arch.univariate.SkewStudent* property), 225
`name` (*arch.univariate.StudentsT* property), 220
`name` (*arch.univariate.volatility.VolatilityProcess* property), 201
`name` (*arch.univariate.ZeroMean* property), 60
`NeweyWest` (class in *arch.covariance.kernel*), 427
`nobs` (*arch.unitroot.ADF* property), 359
`nobs` (*arch.unitroot.DFGLS* property), 363
`nobs` (*arch.unitroot.KPSS* property), 379
`nobs` (*arch.unitroot.PhillipsPerron* property), 367
`nobs` (*arch.unitroot.VarianceRatio* property), 375
`nobs` (*arch.unitroot.ZivotAndrews* property), 371
`nobs` (*arch.univariate.base.ARCHModelFixedResult* property), 252
`nobs` (*arch.univariate.base.ARCHModelResult* property), 245
`Normal` (class in *arch.univariate*), 210
`null` (*arch.utility.testing.WaldTestStatistic* property), 253
`null_hypothesis` (*arch.unitroot.ADF* property), 359
`null_hypothesis` (*arch.unitroot.cointegration.EngleGrangerTestResults* property), 412
`null_hypothesis` (*arch.unitroot.cointegration.PhillipsOuliarisTestResults* property), 415
`null_hypothesis` (*arch.unitroot.DFGLS* property), 363
`null_hypothesis` (*arch.unitroot.KPSS* property), 379
`null_hypothesis` (*arch.unitroot.PhillipsPerron* property), 367
`null_hypothesis` (*arch.unitroot.VarianceRatio* property), 375
`null_hypothesis` (*arch.unitroot.ZivotAndrews* property), 371
`num_params` (*arch.univariate.APARCH* property), 172
`num_params` (*arch.univariate.ARCH* property), 164
`num_params` (*arch.univariate.ARCHInMean* property), 105
`num_params` (*arch.univariate.ARX* property), 78
`num_params` (*arch.univariate.base.ARCHModel* property), 113
`num_params` (*arch.univariate.base.ARCHModelFixedResult* property), 252
`num_params` (*arch.univariate.base.ARCHModelResult* property), 245
`num_params` (*arch.univariate.ConstantMean* property), 69
`num_params` (*arch.univariate.ConstantVariance* property), 119
`num_params` (*arch.univariate.EGARCH* property), 143
`num_params` (*arch.univariate.EWMAVariance* property), 180
`num_params` (*arch.univariate.FIGARCH* property), 135
`num_params` (*arch.univariate.FixedVariance* property), 194
`num_params` (*arch.univariate.GARCH* property), 127
`num_params` (*arch.univariate.HARCH* property), 150
`num_params` (*arch.univariate.HARX* property), 87
`num_params` (*arch.univariate.LS* property), 96

- num_params (*arch.univariate.MIDASHyperbolic* property), 157
- num_params (*arch.univariate.RiskMetrics2006* property), 187
- num_params (*arch.univariate.volatility.VolatilityProcess* property), 201
- num_params (*arch.univariate.ZeroMean* property), 60
- ## O
- one_sided (*arch.covariance.kernel.CovarianceEstimate* property), 459
- one_sided_strict (*arch.covariance.kernel.CovarianceEstimate* property), 459
- opt_bandwidth (*arch.covariance.kernel.Andrews* property), 420
- opt_bandwidth (*arch.covariance.kernel.Bartlett* property), 423
- opt_bandwidth (*arch.covariance.kernel.Gallant* property), 426
- opt_bandwidth (*arch.covariance.kernel.NeweyWest* property), 429
- opt_bandwidth (*arch.covariance.kernel.Parzen* property), 433
- opt_bandwidth (*arch.covariance.kernel.ParzenCauchy* property), 436
- opt_bandwidth (*arch.covariance.kernel.ParzenGeometric* property), 440
- opt_bandwidth (*arch.covariance.kernel.ParzenRiesz* property), 443
- opt_bandwidth (*arch.covariance.kernel.QuadraticSpectral* property), 447
- opt_bandwidth (*arch.covariance.kernel.TukeyHamming* property), 450
- opt_bandwidth (*arch.covariance.kernel.TukeyHanning* property), 454
- opt_bandwidth (*arch.covariance.kernel.TukeyParzen* property), 457
- optimal_block_length() (in module *arch.bootstrap*), 326
- optimization_result (*arch.univariate.base.ARCHModelResult* property), 245
- overlap (*arch.unitroot.VarianceRatio* property), 375
- ## P
- param_cov (*arch.univariate.base.ARCHModelResult* property), 245
- parameter_names() (*arch.univariate.APARCH* method), 170
- parameter_names() (*arch.univariate.ARCH* method), 162
- parameter_names() (*arch.univariate.ARCHInMean* method), 102
- parameter_names() (*arch.univariate.ARX* method), 75
- parameter_names() (*arch.univariate.base.ARCHModel* method), 111
- parameter_names() (*arch.univariate.ConstantMean* method), 67
- parameter_names() (*arch.univariate.ConstantVariance* method), 117
- parameter_names() (*arch.univariate.distribution.Distribution* method), 234
- parameter_names() (*arch.univariate.EGARCH* method), 140
- parameter_names() (*arch.univariate.EWMAVariance* method), 178
- parameter_names() (*arch.univariate.FIGARCH* method), 133
- parameter_names() (*arch.univariate.FixedVariance* method), 192
- parameter_names() (*arch.univariate.GARCH* method), 125
- parameter_names() (*arch.univariate.GeneralizedError* method), 228
- parameter_names() (*arch.univariate.HARCH* method), 148
- parameter_names() (*arch.univariate.HARX* method), 85
- parameter_names() (*arch.univariate.LS* method), 93
- parameter_names() (*arch.univariate.MIDASHyperbolic* method), 155
- parameter_names() (*arch.univariate.Normal* method), 212
- parameter_names() (*arch.univariate.RiskMetrics2006* method), 185
- parameter_names() (*arch.univariate.SkewStudent* method), 223
- parameter_names() (*arch.univariate.StudentsT* method), 217
- parameter_names() (*arch.univariate.volatility.VolatilityProcess* method), 199
- parameter_names() (*arch.univariate.ZeroMean* method), 58
- params (*arch.unitroot.cointegration.CointegrationAnalysisResults* property), 402
- params (*arch.unitroot.cointegration.DynamicOLSResults* property), 407
- params (*arch.univariate.base.ARCHModelFixedResult* property), 253
- params (*arch.univariate.base.ARCHModelResult* property), 245
- partial_moment() (*arch.univariate.distribution.Distribution* method), 234
- partial_moment() (*arch.univariate.GeneralizedError* method), 229
- partial_moment() (*arch.univariate.Normal* method), 212
- partial_moment() (*arch.univariate.SkewStudent* method), 223

method), 223

partial_moment() (arch.univariate.StudentsT method), 218

Parzen (class in arch.covariance.kernel), 430

ParzenCauchy (class in arch.covariance.kernel), 434

ParzenGeometric (class in arch.covariance.kernel), 437

ParzenRiesz (class in arch.covariance.kernel), 441

phillips_ouliaris() (in module arch.unitroot.cointegration), 391

PhillipsOuliarisTestResults (class in arch.unitroot.cointegration), 413

PhillipsPerron (class in arch.unitroot), 364

plot() (arch.unitroot.cointegration.EngleGrangerTestResults method), 409

plot() (arch.unitroot.cointegration.PhillipsOuliarisTestResults method), 413

plot() (arch.univariate.base.ARCHModelFixedResult method), 250

plot() (arch.univariate.base.ARCHModelResult method), 241

pos_data (arch.bootstrap.CircularBlockBootstrap attribute), 305

pos_data (arch.bootstrap.IIDBootstrap attribute), 273

pos_data (arch.bootstrap.IndependentSamplesBootstrap attribute), 284

pos_data (arch.bootstrap.MovingBlockBootstrap attribute), 316

pos_data (arch.bootstrap.StationaryBootstrap attribute), 295

ppf() (arch.univariate.distribution.Distribution method), 235

ppf() (arch.univariate.GeneralizedError method), 229

ppf() (arch.univariate.Normal method), 213

ppf() (arch.univariate.SkewStudent method), 224

ppf() (arch.univariate.StudentsT method), 218

pval (arch.utility.testing.WaldTestStatistic property), 253

pvalue (arch.unitroot.ADF property), 359

pvalue (arch.unitroot.cointegration.EngleGrangerTestResults property), 412

pvalue (arch.unitroot.cointegration.PhillipsOuliarisTestResults property), 416

pvalue (arch.unitroot.DFGLS property), 363

pvalue (arch.unitroot.KPSS property), 379

pvalue (arch.unitroot.PhillipsPerron property), 367

pvalue (arch.unitroot.VarianceRatio property), 376

pvalue (arch.unitroot.ZivotAndrews property), 372

pvalues (arch.bootstrap.MCS property), 344

pvalues (arch.bootstrap.SPA property), 339

pvalues (arch.unitroot.cointegration.CointegrationAnalysisResults property), 402

pvalues (arch.unitroot.cointegration.DynamicOLSResults property), 407

pvalues (arch.univariate.base.ARCHModelResult property), 245

Q

QuadraticSpectral (class in arch.covariance.kernel), 444

R

random_state (arch.bootstrap.CircularBlockBootstrap property), 315

random_state (arch.bootstrap.IIDBootstrap property), 283

random_state (arch.bootstrap.IndependentSamplesBootstrap property), 293

random_state (arch.bootstrap.MovingBlockBootstrap property), 325

random_state (arch.bootstrap.StationaryBootstrap property), 304

random_state (arch.univariate.distribution.Distribution property), 236

random_state (arch.univariate.GeneralizedError property), 231

random_state (arch.univariate.Normal property), 215

random_state (arch.univariate.SkewStudent property), 226

random_state (arch.univariate.StudentsT property), 220

rate (arch.covariance.kernel.Andrews property), 420

rate (arch.covariance.kernel.Bartlett property), 424

rate (arch.covariance.kernel.Gallant property), 427

rate (arch.covariance.kernel.NeweyWest property), 430

rate (arch.covariance.kernel.Parzen property), 433

rate (arch.covariance.kernel.ParzenCauchy property), 437

rate (arch.covariance.kernel.ParzenGeometric property), 440

rate (arch.covariance.kernel.ParzenRiesz property), 444

rate (arch.covariance.kernel.QuadraticSpectral property), 447

rate (arch.covariance.kernel.TukeyHamming property), 451

rate (arch.covariance.kernel.TukeyHanning property), 454

rate (arch.covariance.kernel.TukeyParzen property), 458

regression (arch.unitroot.ADF property), 359

regression (arch.unitroot.DFGLS property), 364

regression (arch.unitroot.PhillipsPerron property), 368

reset() (arch.bootstrap.CircularBlockBootstrap method), 312

reset() (arch.bootstrap.IIDBootstrap method), 280

reset() (arch.bootstrap.IndependentSamplesBootstrap method), 290

reset() (arch.bootstrap.MCS method), 343

reset() (arch.bootstrap.MovingBlockBootstrap method), 322

reset() (arch.bootstrap.SPA method), 338

reset() (arch.bootstrap.StationaryBootstrap method), 301

[reset\(\)](#) ([arch.bootstrap.StepM](#) method), 341
[resid\(\)](#) ([arch.unitroot.cointegration.CointegrationAnalysisResults](#) property), 402
[resid\(\)](#) ([arch.unitroot.cointegration.DynamicOLSResults](#) property), 407
[resid\(\)](#) ([arch.unitroot.cointegration.EngleGrangerTestResults](#) property), 412
[resid\(\)](#) ([arch.unitroot.cointegration.PhillipsOuliarisTestResults](#) property), 416
[resid\(\)](#) ([arch.univariate.base.ARCHModelFixedResult](#) property), 253
[resid\(\)](#) ([arch.univariate.base.ARCHModelResult](#) property), 245
[resids\(\)](#) ([arch.univariate.ARCHInMean](#) method), 103
[resids\(\)](#) ([arch.univariate.ARX](#) method), 75
[resids\(\)](#) ([arch.univariate.base.ARCHModel](#) method), 112
[resids\(\)](#) ([arch.univariate.ConstantMean](#) method), 67
[resids\(\)](#) ([arch.univariate.HARX](#) method), 85
[resids\(\)](#) ([arch.univariate.LS](#) method), 93
[resids\(\)](#) ([arch.univariate.ZeroMean](#) method), 58
[residual_variance\(\)](#) ([arch.unitroot.cointegration.CointegrationAnalysisResults](#) property), 403
[residual_variance\(\)](#) ([arch.unitroot.cointegration.DynamicOLSResults](#) property), 407
[residual_variance\(\)](#) ([arch.univariate.base.ARCHModelForecastSimulation](#) property), 24
[residual_variances\(\)](#) ([arch.univariate.base.ARCHModelForecastSimulation](#) property), 26
[residuals\(\)](#) ([arch.univariate.base.ARCHModelForecastSimulation](#) property), 26
[rho\(\)](#) ([arch.unitroot.cointegration.EngleGrangerTestResults](#) property), 412
[RiskMetrics2006](#) (class in [arch.univariate](#)), 181
[robust\(\)](#) ([arch.unitroot.VarianceRatio](#) property), 376
[rsquared\(\)](#) ([arch.unitroot.cointegration.CointegrationAnalysisResults](#) property), 403
[rsquared\(\)](#) ([arch.unitroot.cointegration.DynamicOLSResults](#) property), 408
[rsquared\(\)](#) ([arch.univariate.base.ARCHModelResult](#) property), 246
[rsquared_adj\(\)](#) ([arch.unitroot.cointegration.CointegrationAnalysisResults](#) property), 403
[rsquared_adj\(\)](#) ([arch.unitroot.cointegration.DynamicOLSResults](#) property), 408
[rsquared_adj\(\)](#) ([arch.univariate.base.ARCHModelResult](#) property), 246

S
[scale\(\)](#) ([arch.univariate.base.ARCHModelResult](#) property), 246
[seed\(\)](#) ([arch.bootstrap.CircularBlockBootstrap](#) method), 312
[seed\(\)](#) ([arch.bootstrap.IIDBootstrap](#) method), 280
[seed\(\)](#) ([arch.bootstrap.IndependentSamplesBootstrap](#) method), 290
[seed\(\)](#) ([arch.bootstrap.MCS](#) method), 343
[seed\(\)](#) ([arch.bootstrap.MovingBlockBootstrap](#) method), 322
[seed\(\)](#) ([arch.bootstrap.SPA](#) method), 339
[seed\(\)](#) ([arch.bootstrap.StationaryBootstrap](#) method), 301
[seed\(\)](#) ([arch.bootstrap.StepM](#) method), 341
[set_state\(\)](#) ([arch.bootstrap.CircularBlockBootstrap](#) method), 312
[set_state\(\)](#) ([arch.bootstrap.IIDBootstrap](#) method), 280
[set_state\(\)](#) ([arch.bootstrap.IndependentSamplesBootstrap](#) method), 291
[set_state\(\)](#) ([arch.bootstrap.MovingBlockBootstrap](#) method), 323
[set_state\(\)](#) ([arch.bootstrap.StationaryBootstrap](#) method), 302
[short_run\(\)](#) ([arch.covariance.kernel.CovarianceEstimate](#) property), 459
[simulate\(\)](#) ([arch.univariate.APARCH](#) method), 170
[simulate\(\)](#) ([arch.univariate.ARCH](#) method), 162
[simulate\(\)](#) ([arch.univariate.ARCHInMean](#) method), 103
[simulate\(\)](#) ([arch.univariate.ARX](#) method), 76
[simulate\(\)](#) ([arch.univariate.base.ARCHModel](#) method), 112
[simulate\(\)](#) ([arch.univariate.ConstantMean](#) method), 67
[simulate\(\)](#) ([arch.univariate.ConstantVariance](#) method), 117
[simulate\(\)](#) ([arch.univariate.distribution.Distribution](#) method), 235
[simulate\(\)](#) ([arch.univariate.EGARCH](#) method), 140
[simulate\(\)](#) ([arch.univariate.EWMAVariance](#) method), 178
[simulate\(\)](#) ([arch.univariate.FIGARCH](#) method), 133
[simulate\(\)](#) ([arch.univariate.FixedVariance](#) method), 192
[simulate\(\)](#) ([arch.univariate.GARCH](#) method), 125
[simulate\(\)](#) ([arch.univariate.GeneralizedError](#) method), 216
[simulate\(\)](#) ([arch.univariate.HARCH](#) method), 148
[simulate\(\)](#) ([arch.univariate.HARX](#) method), 85
[simulate\(\)](#) ([arch.univariate.LS](#) method), 94
[simulate\(\)](#) ([arch.univariate.MIDASHyperbolic](#) method), 155
[simulate\(\)](#) ([arch.univariate.Normal](#) method), 213
[simulate\(\)](#) ([arch.univariate.RiskMetrics2006](#) method), 185
[simulate\(\)](#) ([arch.univariate.SkewStudent](#) method), 224
[simulate\(\)](#) ([arch.univariate.StudentsT](#) method), 219
[simulate\(\)](#) ([arch.univariate.volatility.VolatilityProcess](#) method), 199

- `simulate()` (*arch.univariate.ZeroMean* method), 59
- `simulations` (*arch.univariate.base.ARCHModelForecast* property), 25
- `SkewStudent` (class in *arch.univariate*), 220
- `SPA` (class in *arch.bootstrap*), 336
- `start` (*arch.univariate.APARCH* property), 173
- `start` (*arch.univariate.ARCH* property), 165
- `start` (*arch.univariate.ConstantVariance* property), 120
- `start` (*arch.univariate.EGARCH* property), 143
- `start` (*arch.univariate.EWMAVariance* property), 180
- `start` (*arch.univariate.FIGARCH* property), 135
- `start` (*arch.univariate.FixedVariance* property), 194
- `start` (*arch.univariate.GARCH* property), 127
- `start` (*arch.univariate.HARCH* property), 150
- `start` (*arch.univariate.MIDASHyperbolic* property), 158
- `start` (*arch.univariate.RiskMetrics2006* property), 187
- `start` (*arch.univariate.volatility.VolatilityProcess* property), 201
- `starting_values()` (*arch.univariate.APARCH* method), 170
- `starting_values()` (*arch.univariate.ARCH* method), 163
- `starting_values()` (*arch.univariate.ARCHInMean* method), 104
- `starting_values()` (*arch.univariate.ARX* method), 77
- `starting_values()` (*arch.univariate.base.ARCHModel* method), 112
- `starting_values()` (*arch.univariate.ConstantMean* method), 68
- `starting_values()` (*arch.univariate.ConstantVariance* method), 118
- `starting_values()` (*arch.univariate.distribution.Distribution* method), 235
- `starting_values()` (*arch.univariate.EGARCH* method), 141
- `starting_values()` (*arch.univariate.EWMAVariance* method), 178
- `starting_values()` (*arch.univariate.FIGARCH* method), 133
- `starting_values()` (*arch.univariate.FixedVariance* method), 192
- `starting_values()` (*arch.univariate.GARCH* method), 125
- `starting_values()` (*arch.univariate.GeneralizedError* method), 230
- `starting_values()` (*arch.univariate.HARCH* method), 148
- `starting_values()` (*arch.univariate.HARX* method), 86
- `starting_values()` (*arch.univariate.LS* method), 95
- `starting_values()` (*arch.univariate.MIDASHyperbolic* method), 156
- `starting_values()` (*arch.univariate.Normal* method), 214
- `starting_values()` (*arch.univariate.RiskMetrics2006* method), 185
- `starting_values()` (*arch.univariate.SkewStudent* method), 225
- `starting_values()` (*arch.univariate.StudentsT* method), 219
- `starting_values()` (*arch.univariate.volatility.VolatilityProcess* method), 199
- `starting_values()` (*arch.univariate.ZeroMean* method), 60
- `stat` (*arch.unitroot.ADF* property), 359
- `stat` (*arch.unitroot.cointegration.EngleGrangerTestResults* property), 413
- `stat` (*arch.unitroot.cointegration.PhillipsOuliarisTestResults* property), 416
- `stat` (*arch.unitroot.DFGLS* property), 364
- `stat` (*arch.unitroot.KPSS* property), 380
- `stat` (*arch.unitroot.PhillipsPerron* property), 368
- `stat` (*arch.unitroot.VarianceRatio* property), 376
- `stat` (*arch.unitroot.ZivotAndrews* property), 372
- `stat` (*arch.utility.testing.WaldTestStatistic* property), 253
- `state` (*arch.bootstrap.CircularBlockBootstrap* property), 315
- `state` (*arch.bootstrap.IIDBootstrap* property), 283
- `state` (*arch.bootstrap.IndependentSamplesBootstrap* property), 294
- `state` (*arch.bootstrap.MovingBlockBootstrap* property), 325
- `state` (*arch.bootstrap.StationaryBootstrap* property), 304
- `StationaryBootstrap` (class in *arch.bootstrap*), 294
- `std_err` (*arch.univariate.base.ARCHModelResult* property), 246
- `std_errors` (*arch.unitroot.cointegration.CointegrationAnalysisResults* property), 403
- `std_errors` (*arch.unitroot.cointegration.DynamicOLSResults* property), 408
- `std_resid` (*arch.univariate.base.ARCHModelFixedResult* property), 253
- `std_resid` (*arch.univariate.base.ARCHModelResult* property), 246
- `StepM` (class in *arch.bootstrap*), 340
- `stop` (*arch.univariate.APARCH* property), 173
- `stop` (*arch.univariate.ARCH* property), 165
- `stop` (*arch.univariate.ConstantVariance* property), 120
- `stop` (*arch.univariate.EGARCH* property), 143
- `stop` (*arch.univariate.EWMAVariance* property), 180
- `stop` (*arch.univariate.FIGARCH* property), 135
- `stop` (*arch.univariate.FixedVariance* property), 194
- `stop` (*arch.univariate.GARCH* property), 127
- `stop` (*arch.univariate.HARCH* property), 150
- `stop` (*arch.univariate.MIDASHyperbolic* property), 158
- `stop` (*arch.univariate.RiskMetrics2006* property), 187

- stop (*arch.univariate.volatility.VolatilityProcess* property), 201
- StudentsT (*class in arch.univariate*), 215
- subset() (*arch.bootstrap.SPA* method), 339
- summary() (*arch.unitroot.ADF* method), 357
- summary() (*arch.unitroot.cointegration.CointegrationAnalysisResults* method), 401
- summary() (*arch.unitroot.cointegration.DynamicOLSResults* method), 404
- summary() (*arch.unitroot.cointegration.EngleGrangerTestResults* method), 410
- summary() (*arch.unitroot.cointegration.PhillipsOuliarisTestResults* method), 414
- summary() (*arch.unitroot.DFGLS* method), 362
- summary() (*arch.unitroot.KPSS* method), 378
- summary() (*arch.unitroot.PhillipsPerron* method), 366
- summary() (*arch.unitroot.VarianceRatio* method), 373
- summary() (*arch.unitroot.ZivotAndrews* method), 370
- summary() (*arch.univariate.base.ARCHModelFixedResult* method), 251
- summary() (*arch.univariate.base.ARCHModelResult* method), 242
- superior_models (*arch.bootstrap.StepM* property), 342
- ## T
- test_type (*arch.unitroot.PhillipsPerron* property), 368
- trend (*arch.unitroot.ADF* property), 360
- trend (*arch.unitroot.cointegration.EngleGrangerTestResults* property), 413
- trend (*arch.unitroot.cointegration.PhillipsOuliarisTestResults* property), 416
- trend (*arch.unitroot.DFGLS* property), 364
- trend (*arch.unitroot.KPSS* property), 380
- trend (*arch.unitroot.PhillipsPerron* property), 368
- trend (*arch.unitroot.VarianceRatio* property), 376
- trend (*arch.unitroot.ZivotAndrews* property), 372
- truncation (*arch.univariate.FIGARCH* property), 136
- TukeyHamming (*class in arch.covariance.kernel*), 448
- TukeyHanning (*class in arch.covariance.kernel*), 451
- TukeyParzen (*class in arch.covariance.kernel*), 455
- tvalues (*arch.unitroot.cointegration.CointegrationAnalysisResults* property), 404
- tvalues (*arch.unitroot.cointegration.DynamicOLSResults* property), 408
- tvalues (*arch.univariate.base.ARCHModelResult* property), 246
- ## U
- update() (*arch.univariate.APARCH* method), 171
- update() (*arch.univariate.ARCH* method), 163
- update() (*arch.univariate.ConstantVariance* method), 118
- update() (*arch.univariate.EGARCH* method), 141
- update() (*arch.univariate.EWMAVariance* method), 179
- update() (*arch.univariate.FIGARCH* method), 134
- update() (*arch.univariate.FixedVariance* method), 193
- update() (*arch.univariate.GARCH* method), 126
- update() (*arch.univariate.HARCH* method), 149
- update() (*arch.univariate.MIDASHyperbolic* method), 158
- update() (*arch.univariate.recursions_python.VolatilityUpdater* method), 203
- update() (*arch.univariate.RiskMetrics2006* method), 186
- update() (*arch.univariate.volatility.VolatilityProcess* method), 200
- update_indices() (*arch.bootstrap.CircularBlockBootstrap* method), 313
- update_indices() (*arch.bootstrap.IIDBootstrap* method), 281
- update_indices() (*arch.bootstrap.IndependentSamplesBootstrap* method), 291
- update_indices() (*arch.bootstrap.MovingBlockBootstrap* method), 323
- update_indices() (*arch.bootstrap.StationaryBootstrap* method), 302
- updateable (*arch.univariate.APARCH* property), 173
- updateable (*arch.univariate.ARCH* property), 165
- updateable (*arch.univariate.ConstantVariance* property), 120
- updateable (*arch.univariate.EGARCH* property), 143
- updateable (*arch.univariate.EWMAVariance* property), 181
- updateable (*arch.univariate.FIGARCH* property), 136
- updateable (*arch.univariate.FixedVariance* property), 195
- updateable (*arch.univariate.GARCH* property), 128
- updateable (*arch.univariate.HARCH* property), 151
- updateable (*arch.univariate.MIDASHyperbolic* property), 158
- updateable (*arch.univariate.RiskMetrics2006* property), 188
- updateable (*arch.univariate.volatility.VolatilityProcess* property), 202
- ## V
- valid_trends (*arch.unitroot.ADF* property), 360
- valid_trends (*arch.unitroot.DFGLS* property), 364
- valid_trends (*arch.unitroot.KPSS* property), 380
- valid_trends (*arch.unitroot.PhillipsPerron* property), 368
- valid_trends (*arch.unitroot.VarianceRatio* property), 376
- valid_trends (*arch.unitroot.ZivotAndrews* property), 372
- values (*arch.univariate.base.ARCHModelForecastSimulation* property), 26

- `var()` (*arch.bootstrap.CircularBlockBootstrap* method), 313
 - `var()` (*arch.bootstrap.IIDBootstrap* method), 281
 - `var()` (*arch.bootstrap.IndependentSamplesBootstrap* method), 291
 - `var()` (*arch.bootstrap.MovingBlockBootstrap* method), 323
 - `var()` (*arch.bootstrap.StationaryBootstrap* method), 302
 - `variance` (*arch.univariate.base.ARCHModelForecast* property), 25
 - `variance_bounds()` (*arch.univariate.APARCH* method), 171
 - `variance_bounds()` (*arch.univariate.ARCH* method), 164
 - `variance_bounds()` (*arch.univariate.ConstantVariance* method), 119
 - `variance_bounds()` (*arch.univariate.EGARCH* method), 142
 - `variance_bounds()` (*arch.univariate.EWMAVariance* method), 179
 - `variance_bounds()` (*arch.univariate.FIGARCH* method), 134
 - `variance_bounds()` (*arch.univariate.FixedVariance* method), 193
 - `variance_bounds()` (*arch.univariate.GARCH* method), 126
 - `variance_bounds()` (*arch.univariate.HARCH* method), 149
 - `variance_bounds()` (*arch.univariate.MIDASHyperbolic* method), 157
 - `variance_bounds()` (*arch.univariate.RiskMetrics2006* method), 186
 - `variance_bounds()` (*arch.univariate.volatility.VolatilityProcess* method), 200
 - `VarianceRatio` (class in *arch.unitroot*), 372
 - `variances` (*arch.univariate.base.ARCHModelForecastSimulation* property), 26
 - `volatility` (*arch.univariate.ARCHInMean* property), 105
 - `volatility` (*arch.univariate.ARX* property), 78
 - `volatility` (*arch.univariate.base.ARCHModel* property), 113
 - `volatility` (*arch.univariate.ConstantMean* property), 69
 - `volatility` (*arch.univariate.HARX* property), 87
 - `volatility` (*arch.univariate.LS* property), 96
 - `volatility` (*arch.univariate.ZeroMean* property), 61
 - `volatility_updater` (*arch.univariate.APARCH* property), 173
 - `volatility_updater` (*arch.univariate.ARCH* property), 165
 - `volatility_updater` (*arch.univariate.ConstantVariance* property), 120
 - `volatility_updater` (*arch.univariate.EGARCH* property), 143
 - `volatility_updater` (*arch.univariate.EWMAVariance* property), 181
 - `volatility_updater` (*arch.univariate.FIGARCH* property), 136
 - `volatility_updater` (*arch.univariate.FixedVariance* property), 195
 - `volatility_updater` (*arch.univariate.GARCH* property), 128
 - `volatility_updater` (*arch.univariate.HARCH* property), 151
 - `volatility_updater` (*arch.univariate.MIDASHyperbolic* property), 158
 - `volatility_updater` (*arch.univariate.RiskMetrics2006* property), 188
 - `volatility_updater` (*arch.univariate.volatility.VolatilityProcess* property), 202
 - `VolatilityProcess` (class in *arch.univariate.volatility*), 195
 - `VolatilityUpdater` (class in *arch.univariate.recursions_python*), 202
 - `vr` (*arch.unitroot.VarianceRatio* property), 376
- ## W
- `WaldTestStatistic` (class in *arch.utility.testing*), 253
- ## X
- `x` (*arch.univariate.ARCHInMean* property), 105
 - `x` (*arch.univariate.ARX* property), 78
 - `x` (*arch.univariate.ConstantMean* property), 69
 - `x` (*arch.univariate.HARX* property), 87
 - `x` (*arch.univariate.LS* property), 96
 - `x` (*arch.univariate.ZeroMean* property), 61
- ## Y
- `y` (*arch.unitroot.ADF* property), 360
 - `y` (*arch.unitroot.DFGLS* property), 364
 - `y` (*arch.unitroot.KPSS* property), 380
 - `y` (*arch.unitroot.PhillipsPerron* property), 369
 - `y` (*arch.unitroot.VarianceRatio* property), 377
 - `y` (*arch.unitroot.ZivotAndrews* property), 372
 - `y` (*arch.univariate.ARCHInMean* property), 106
 - `y` (*arch.univariate.ARX* property), 78
 - `y` (*arch.univariate.base.ARCHModel* property), 113
 - `y` (*arch.univariate.ConstantMean* property), 69
 - `y` (*arch.univariate.HARX* property), 87
 - `y` (*arch.univariate.LS* property), 96
 - `y` (*arch.univariate.ZeroMean* property), 61
- ## Z
- `ZeroMean` (class in *arch.univariate*), 53
 - `ZivotAndrews` (class in *arch.unitroot*), 369