USB PD CTS ENGINEERING CHANGE NOTICE

NOTICE: Any Company or Companies submitting a USB Power Delivery ECR proposal must be one of the following: a Promoter or Contributor of the USB 3.0 and 2.0 Specifications who have completed the USB Power Delivery addendum. If a group of Companies is submitting an ECR proposal, each company must be either a Promoter or Contributor of the USB 3.0 and 2.0 Specifications who have completed the USB Power Delivery addendum.

SPECIFICATION REVISIONS AND ADDENDA: At any point in time, there shall only be one current version of the USB PD CTS, termed the production version. At the same time, there may also be proposed revisions to the specification's design which are not yet approved and shall be held confidential as deemed necessary by the USB 3.0 and USB 2.0 Promoters and within the Group of Working Committee(s).

PROCEDURES FOR SUBMITTING PROPOSALS: Both members of the USB Implementers Forum as a whole and members of the USB 3.0 and USB 2.0 Promoters may submit requests to revise the USB PD CTS Specification. Such a request may be rejected or may result in a USB PD Engineering Change Notice (ECN), which is the official way USB specifications may be changed.

FORMAT OF PROPOSAL: The originator of a request to alter the USB PD CTS Specification may do so by posting this to the USB Power Delivery Compliance working group for review. Once the proposal has been reviewed by the working group it will be passed to the USB 3.0 and 2.0 Promoters for approval to publish.

RESUBMISSION AND APPEAL: The originator of a request that was not approved can redraft the original request. Rewritten proposal will be treated as a new proposal and will be evaluated using the procedures described above. The originator of a request that was not approved can also submit an appeal to the USB 3.0 and 2.0 Promoters. The appeal must be made in writing and addressed to the Secretary of the USB Implementers Forum.

ABOUT THE ENGINEERING CHANGE REQUEST FORM:
The Purpose of this Engineering Change Request Form is to expedite the review process of the proposal by providing explanations, background information, and examples of the proposed changes at a high level. This form serves as an executive summary to the actual proposal.

STEPS ON HOW TO SUBMIT A USB PD ENGINEERING CHANGE REQUEST:

1) Please fill out the Engineering Change Request Form on the following pages completely:
   a) Detail the names and contact details for each of the ECR contributors
   b) Update the ECR Title
   c) Give a minimum of 2-3 sentences for each description on the form outlining the background to the ECR
2) For each section/table/figure to be updated:
   a) Detail the section number, starting page and figure/table number to be updated as appropriate.
   b) Detail existing text under "From Text"
   c) Detail changed text under "To Text"
3) Save the file as "USB PD CTS 1.0 R 1" followed by the ECR Title as per step 1)b)
4) Post the ECR in the USB PD CTS Documents section under "ECR | New ECRs".
   a) This ECR will then be reviewed by the Power Delivery Compliance Working Group.
   b) Revisions to the ECR originating from the review should be submitted as document revision of the original ECR using "Add new document".

USB PD CTS ENGINEERING CHANGE NOTICE

Name: Shubha T R Email: s-tr@ti.com

Company: Texas Instruments Mailstop:

Address:

City: State/Province:

Country: Zip/Postal Code:

Phone: FAX:

Name: Aakash Lawana Email: a-lawana@ti.com

Company: Texas Instruments Mailstop:

Address:

City: State/Province:

Country: Zip/Postal Code:

Phone: FAX:

Name: Biju Erayamkot Panayamthatta Email: bijuep@ti.com

Company: Texas Instruments Mailstop:

Address:

City: State/Province:

Country: Zip/Postal Code:

Phone: FAX:

Name: Email:

Company: Mailstop:

Address:

City: State/Province:

Country: Zip/Postal Code:

Phone: FAX:

USB PD CTS ENGINEERING CHANGE NOTICE

Title: *Get_Status Timing Changes*
Applied to: USB PD CTS Specification Version Q4 2026

Brief description of the functional changes proposed:
This ECR aligns CTS as per the base spec related to Get_Status timing after Alert is received.

Benefits as a result of the proposed changes:
Aligns CTS with the base spec.

An assessment of the impact to the existing revision and systems that currently conform to the USB specification:
None. Ensure that existing systems conform to USB PD Spec.

An analysis of the hardware implications:
No modification

An analysis of the software implications:
No modification

An analysis of the compliance testing implications:
Compliance testers will have to be updated to cover the new test condition.

An analysis of the Vendor Info File (VIF) implications:
NA

USB PD CTS ENGINEERING CHANGE NOTICE

Actual Change Requested

From Text:

TEST.PD.PROT.SNK3.2 Alert Response Source Input Change

Test Procedures:

1. There are 2 possible bring-up procedures:
    a. The UUT has VIF field PD_Port_Type set to Provider/Consumer, the Tester runs bring-up procedure with the UUT as a Sink COMMON.PROC.BU.8
    b. The UUT has VIF field PD_Port_Type set to anything else, the Tester runs bring-up procedure with the UUT as a Sink COMMON.PROC.BU.2
2. The Tester sends an *Alert* Message to the UUT with Type of *Alert* field = OTP event (Bit 3).
3. The Tester presents *SinkTxOK*.
4. The test passes if one of the following conditions happens [TEST.PD.PROT.SNK3.2#1]
    a. A *Not_Supported* Message is received as a response to the last *Alert* Message and the UUT as a Sink has no sink PPS APDO in VIF.
    b. A *Get_ Status* Message is received within *tSenderResponse* min as a response to the last *Alert* Message.
    c. No message is received for *tSenderResponse* min

   Otherwise, the test fails and stops here.

To Text:

TEST.PD.PROT.SNK3.2 Alert Response Source Input Change

Test Procedures:

1. There are 2 possible bring-up procedures:
    a. The UUT has VIF field PD_Port_Type set to Provider/Consumer, the Tester runs bring-up procedure with the UUT as a Sink COMMON.PROC.BU.8
    b. The UUT has VIF field PD_Port_Type set to anything else, the Tester runs bring-up procedure with the UUT as a Sink COMMON.PROC.BU.2
2. The Tester sends an *Alert* Message to the UUT with Type of *Alert* field = OTP event (Bit 3).
3. The Tester presents *SinkTxOK*.
4. The test passes if the first bit of the Preamble of any of the following response messages is received within *tReceiverResponse* max: [TEST.PD.PROT.SNK3.2#1]
    a. A *Not_Supported* Message as a response to the last *Alert* Message and the UUT as a Sink has no sink PPS APDO in VIF.
    b. A *Get_ Status* Message as a response to the last *Alert* Message.
    c. No message has started.

   Otherwise, the test fails and stops here.

USB PD CTS ENGINEERING CHANGE NOTICE

From Text:

TEST.PD.PROT.SNK3.3 Alert Response Battery Status Change

Test Procedures:

3. The Tester presents *SinkTxOK*.
4. The test passes if one of the following conditions happens [TEST.PD.PROT.SNK3.3#1]:
    a. A *Not_Supported* Message is received as a response to the last *Alert* Message and the UUT as a Sink does not have sink PPS APDO in VIF.
    b. A *Get_Battery_Status* Message is received within *tSenderResponse* min after the Alert Message was sent.
    c. No message is received for *tSenderResponse* min.

   Otherwise, the test fails and stops here.

To Text:

TEST.PD.PROT.SNK3.3 Alert Response Battery Status Change

Test Procedures:

3. The Tester presents *SinkTxOK*.
4. The test passes if the first bit of the Preamble of any of the following response messages is received within *tReceiverResponse* max: [TEST.PD.PROT.SNK3.3#1]:
    i. A *Not_Supported* Message as a response to the last *Alert* Message and the UUT as a Sink does not have sink PPS APDO in VIF.
    ii. A *Get_Battery_Status* Message after the Alert Message is sent.
    iii. No message has started.

   Otherwise, the test fails and stops here.