

Bachelor Project



**Czech
Technical
University
in Prague**

F3

**Faculty of Electrical Engineering
Department of Radioelectronics**

Design of a platform for 2D LiDaR

Illia Novosad

Supervisor: Ing. Pavel Puričér, Ph.D.

Field of study: Electronics and Communications

November 2025

Acknowledgements

Děkuji ČVUT, že mi je tak dobrou *alma mater*.

Declaration

Prohlašuji, že jsem předloženou práci vypracoval samostatně, a že jsem uvedl veškerou použitou literaturu.

V Praze, 13. November 2025

Abstract

There are currently many advanced LiDAR sensors available for 3D spatial scanning [*insert citation]. However, most of these sensors are too expensive for the average user. The most affordable commercial option is the Unitree L1, which costs \$ 250 [*insert citation]. The aim of this miniproject is to design a platform for a 360° LiDAR sensor, which will be utilized in a subsequent bachelor's thesis to visualize a 3D image of the scanned environment.

Keywords: LiDAR, 3D reconstruction, point cloud, signal processing, mapping

Supervisor: Ing. Pavel Puričer, Ph.D.

Abstrakt

V současnosti existuje spousta pokročilých lidar-senzorů určených pro 3D snímání prostoru [*insert citation*]. Většina z nich je však cenově nedostupná pro běžného uživatele. Nejvíce dostupným komerčním řešením je Unitree L1, který stojí \$ 250 [*insert citation*]. Cílem toho miniprojektu je navrhnout pro 360° lidar-senzor platformu a použít ji v navazující bakalářské práci pro vizualizaci 3D-obrazu naskenovaného prostoru.

Klíčová slova: LiDAR, 3D rekonstrukce, point cloud, zpracování signálů, mapování

Překlad názvu: Návrh platformy pro 2D LiDaR

Contents

Acronyms	3
1 Introduction	5
2 Design of a Platform	7
2.1 Existing DIY Solutions for Environmental Mapping	7
2.1.1 Using a Single-Point Light Detection and Ranging (LiDAR) module	7
2.1.2 Using a Single-Point LiDAR and a Mirror	8
2.1.3 Using a 2D LiDAR Mounted on a Tilting Platform	8
2.2 Proposed Design of a 360° LiDAR Platform	9
3 Conclusion	11

Figures

Tables

.....



Acronyms

LiDAR Light Detection and Ranging

DSP Digital Signal Processing

SLAM Simultaneous Localization and Mapping



Chapter 1

Introduction

Nowadays, LiDAR sensors are widely used in various applications, including autonomous vehicles, robotics, and environmental mapping [insert citation for robotics BAP and Pinliang book]. While the former two applications often require high-end and expensive LiDAR systems, environmental mapping can be effectively performed using more affordable sensors. However, even the most affordable commercial LiDAR sensors which was found during the research for this miniproject cost approximately \$250[insert Unitree citation]. The primary motivation behind this miniproject (and the subsequent bachelor thesis) is to develop a cost-effective platform for a 360° LiDAR sensor that can be utilized for 3D spatial scanning and visualization of the surrounding environment. A subsequent bachelor thesis will then focus on the Digital Signal Processing (DSP) techniques for effective processing of the acquired point cloud data and proper utilization of open-source visualization tools (such as Python's Open3D library[insert citation of a site or a thesis for that library]) to recreate a 3D scene.

Chapter 2

Design of a Platform

This chapter will firstly go over the existing DIY solutions for 360° LiDAR platforms which the author has stumbled upon during the research[too informal?], analyzing their pros and cons.

2.1 Existing DIY Solutions for Environmental Mapping

2.1.1 Using a Single-Point LiDAR module

One of the most straightforward approaches to achieve 360° environmental mapping is to utilize a single-point LiDAR module mounted on a rotating platform, as was done in this project[add citation and picture].

Pros:

- Single-point LiDARs are the most cost-effective among all existing types
- Simple design

Cons:

- Slow data acquisition relative to methods leveraging 2D LiDAR's speed
- Movement of lidar may introduce inaccuracies in distance measurements, which need to be compensated for in code if we want to assume that all points are measured from a single position in space

■ 2.1.2 Using a Single-Point LiDAR and a Mirror

The following approach was used in this project[add citation and picture]. A single-point LiDAR is placed below a rotating mirror, which reflects the laser beam horizontally. As the mirror rotates, the laser beam scans the environment in 360°. Moreover, by tilting the mirror at an angle, vertical scanning can also be achieved, allowing for the acquisition of the whole scene.

Pros:

- Cost-effectiveness as in previous implementation
- Simple design
- Much easier to correct the distance measurement, since the LiDAR is stationary and the distance from it to the mirror is known.

Cons:

- Slow data acquisition relative to methods leveraging 2D LiDAR's speed
- Mirror's quality may affect the accuracy of distance measurements
- Mechanical structure holding the mirror may introduce vibrations, thus affecting measurement accuracy

■ 2.1.3 Using a 2D LiDAR Mounted on a Tilting Platform

This approach utilizes a 2D LiDAR sensor mounted on a platform that can tilt the sensor side-to-side, as demonstrated in this project[add citation and picture]. The 2D LiDAR scans the environment in a horizontal plane, while the tilting mechanism allows for vertical scanning. Pros:

10

However, this issue can be mitigated by carefully selecting the tilt angle based on the specific application in which the system will be used. (more on that in the next chapter) [system? :/]



Chapter 3

Conclusion