

Bachelor Project



**Czech
Technical
University
in Prague**

F3

**Faculty of Electrical Engineering
Department of Radioelectronics**

Design of a platform for 2D LiDaR

Illia Novosad

Supervisor: Ing. Pavel Puričer, Ph.D.

Field of study: Electronics and Communications

November 2025

Acknowledgements

Děkuji ČVUT, že mi je tak dobrou *alma mater*.

Declaration

Prohlašuji, že jsem předloženou práci vypracoval samostatně, a že jsem uvedl veškerou použitou literaturu.

V Praze, 13. November 2025

Abstract

There are currently many advanced LiDAR sensors available for 3D spatial scanning [*insert citation]. However, most of these sensors are too expensive for the average user. The most affordable commercial option is the Unitree L1, which costs \$ 250 [*insert citation]. The aim of this miniproject is to design a platform for a 360° LiDAR sensor, which will be utilized in a subsequent bachelor's thesis to visualize a 3D image of the scanned environment.

Keywords: LiDAR, 3D reconstruction, point cloud, signal processing, mapping

Supervisor: Ing. Pavel Puričer, Ph.D.

Abstrakt

V současnosti existuje spousta pokročilých lidar-senzorů určených pro 3D snímání prostoru [*insert citation*]. Většina z nich je však cenově nedostupná pro běžného uživatele. Nejvíce dostupným komerčním řešením je Unitree L1, který stojí \$ 250 [*insert citation*]. Cílem toho miniprojektu je navrhnout pro 360° lidar-senzor platformu a použít ji v navazující bakalářské práci pro vizualizaci 3D-obrazu naskenovaného prostoru.

Klíčová slova: LiDAR, 3D rekonstrukce, point cloud, zpracování signálů, mapování

Překlad názvu: Návrh platformy pro 2D LiDaR

Contents

Acronyms	3
1 Introduction	5
2 Design of a Platform	7
2.1 Existing DIY Solutions for Environmental Mapping	7
2.1.1 Using a Single-Point Light Detection and Ranging (LiDAR) module	7
2.1.2 Using a Single-Point LiDAR and a Mirror	8
2.1.3 Using a 2D LiDAR Mounted on a Tilting Platform	8
2.2 Proposed Design of a 360° LiDAR Platform	9
2.2.1 Controlling the Platform	10
2.2.2 Choosing the Tilt Angle	10
3 Conclusion	11

Figures

Tables

.....



Acronyms

LiDAR Light Detection and Ranging

DSP Digital Signal Processing

SLAM Simultaneous Localization and Mapping



Chapter 1

Introduction

Nowadays, LiDAR sensors are widely used in various applications, including autonomous vehicles, robotics, and environmental mapping [insert citation for robotics BAP and Pinliang book]. While the former two applications often require high-end and expensive LiDAR systems, environmental mapping can be effectively performed using more affordable sensors. However, even the cheapest commercial LiDAR sensors, which were found during the research for this miniproject, cost approximately \$250[insert Unitree citation]. The primary motivation behind this mini-project (and the subsequent bachelor's thesis) is to develop a cost-effective platform for a 360° LiDAR sensor that can be utilised for 3D spatial scanning and visualisation of the surrounding environment. A subsequent bachelor's thesis will then focus on the Digital Signal Processing (DSP) techniques for the effective processing of the acquired point cloud data and proper utilisation of open-source visualisation tools (such as Python's Open3D library[insert citation of a site or a thesis for that library]) to recreate a 3D scene.

Chapter 2

Design of a Platform

This chapter will firstly go over the existing DIY solutions for 360° LiDAR platforms which the author has stumbled upon during the research[too informal?], analyzing their pros and cons. After that, the proposed design will be presented, along with the chosen design decisions and their justifications.

2.1 Existing DIY Solutions for Environmental Mapping

2.1.1 Using a Single-Point LiDAR module

One of the most straightforward approaches to achieve 360° environmental mapping is to utilize a single-point LiDAR module mounted on a platform which is able to rotate and tilt, as was done in this project[add citation and picture].

Pros:

- Single-point LiDARs are the most cost-effective among all existing types
- Simple design

Cons:

- Slow data acquisition relative to methods leveraging 2D LiDAR's speed
- Movement of lidar may introduce inaccuracies in distance measurements, which need to be compensated for in code if we want to assume that all points are measured from a single position in space

■ 2.1.2 Using a Single-Point LiDAR and a Mirror

The following approach was used in this project[add citation and picture]. A single-point LiDAR is placed below a rotating mirror, which reflects the laser beam horizontally. As the mirror rotates, the laser beam scans the environment in 360°. Moreover, by tilting the mirror at an angle, vertical scanning can also be achieved, allowing for the acquisition of the whole scene.

Pros:

- Cost-effectiveness as in previous implementation
- Simple design
- Much easier to correct the distance measurement, since the LiDAR is stationary and the distance from it to the mirror is known.

Cons:

- Slow data acquisition relative to methods leveraging 2D LiDAR's speed
- Mirror's quality may affect the accuracy of distance measurements
- Mechanical structure holding the mirror may introduce vibrations, thus affecting measurement accuracy

■ 2.1.3 Using a 2D LiDAR Mounted on a Tilting Platform

This approach utilizes a 2D LiDAR sensor mounted on a platform that can tilt the sensor side-to-side, as demonstrated in this project[add citation and

picture]. The 2D LiDAR scans the environment in a horizontal plane, while the tilting mechanism allows for vertical scanning. Pros:

- Faster data acquisition compared to solutions with single-point LiDAR measurements
- Higher resolution given by the use of a 2D LiDAR sensor
- This design could be potentially used for Simultaneous Localization and Mapping (SLAM) applications, given the higher speed

Cons:

- More expensive than single-point LiDAR solutions
- Point distribution is non-uniform due to the tilting mechanism which produces denser point clouds on the axis of tilting (see MATLAB simulation below) [should this note be here?]
- Mechanical design is both more complex and more prone to vibrations produced by the LiDAR itself affecting measurement accuracy

2.2 Proposed Design of a 360° LiDAR Platform

Based on the analysis of existing DIY solutions for 360° LiDAR platforms, the proposed design for this miniproject involves using a 2D LiDAR sensor mounted on a tilted platform that is able to rotate 360°[insert photo]. This design leverages the advantages of 2D LiDAR sensors, such as fast data acquisition and high resolution, while also eliminating some of the drawbacks of previous designs, namely:

- The platform will be quite rigid, minimizing vibrations
- Mechanical design is very simple, making it easy to build and troubleshoot
- The point cloud will be more uniformly distributed compared to the tilting platform design, as the rotation will ensure that a LiDAR won't have a preferred direction around which it collects denser data unless the slope is very steep (see MATLAB simulation below)[could this be phrased better?]

The main drawback of this design is the existence of "blind spots" in the point cloud, which are areas that the LiDAR cannot scan due to the tilt angle. However, this issue can be mitigated by carefully selecting the tilt angle based on the specific application in which the system will be used. (more on that in the next chapter) [system? :/]

■ 2.2.1 Controlling the Platform

Since we want our platform to be precisely controlled, we need to choose an appropriate motor. Stepper motors are commonly used in applications requiring precise positioning, as they can be controlled to move in small, discrete steps. For this design, a NEMA 17 stepper motor is used to rotate the LiDAR platform[Add a photo and crucial parameters of the motor]. Granted that the motor is not under heavy load, we can assume that each step of the motor corresponds to a precise angular movement of the platform, allowing for accurate control of the platform's position without the need for additional feedback mechanisms[reformulate it better, provide a link to a bachelor thesis with the description of stepper motor errors].

■ 2.2.2 Choosing the Tilt Angle

The tilt angle of the LiDAR platform is a crucial parameter that affects the size of the aforementioned blind spots in the point cloud. A larger tilt angle will result in smaller blind spots, but the trade-off is a more spread-out point cloud in the horizontal direction if we rotate our platform in discrete steps [see point cloud simulations below]. Without any further solutions, we would have to choose a compromise tilt angle that balances the size of blind spots and point cloud density.

Thankfully, there is a way to achieve a more complete coverage of the environment without sacrificing point cloud density.



Chapter 3

Conclusion