Darren Lee
CSE13S

Assignment 6: Huffman Coding
Design Document

Purpose

The purpose of this assignment is to create a Huffman coding module with an encoder and a decoder using node, priority queue, code, and stack abstract data types. Huffman coding creates static encodings of information and allows for data compression. The optimal static encoding assigns the least number of bits to the most common symbol and the greatest number of bits to the least common symbol according to the entropy equation

$$H(X) = \sum_{i=1}^{n} \Pr[x_i] I(x_i) = -\sum_{i=1}^{n} \Pr[x_i] \log_2 \Pr[x_i].$$

for the set X with I(x) as the measure of the amount of information in the set.

Layout/Structure

- Encode.c-contains the implementation for the Huffman encoder
- Decode.c-contains the implementation for the Huffman decoder
- Entropy.c-provided by the resources repository and contains the code for measuring the entropy of a file
- defines.h - contains macro definitions for the assignment
- Header.h - contains the struct definition for a file header
- Node.h-provided by resource repository, contains the node ADT interface
- Node.c-contains the implementation for the node ADT
- pq.h -provided by resources repository, contains the priority queue ADT interface
- pq.c -contains the implementation of the priority queue ADT, priority queue struct is defined in this file
- Code.h- contains the code ADT interface
- Code.c-this file will contain your implementation of the code ADT
- Io.h- provided by resources repository. This file contains the I/O module interface.
- Io.c - contains the implementation for the I/O module
- stack.h - contains the stack ADT interface
- Stack.c -contains the implementation of the stack ADT, the stack struct is defined in this file
- Huffman.h-provided by the resources repository, contains the Huffman coding module interface
- Huffman.c-contains the implementation of the Huffman coding module interface
- Makefile-allows user to compile the programs

Node ADT

- The Huffman trees are made up of nodes.

- Each node has a pointer to its left child, a pointer to its right child, a symbol and a frequency of that symbol. The node's frequency is used by the decoder.
- A symbol is a uint8_t and the input is read as raw bytes. The definition of a node is made transparent.

Priority Queue ADT

- High priority elements are dequeued before low priority elements.
- Enqueue adds elements to a position based on priority.
- The priority queue will be implemented using an insertion sort to enqueue nodes.
- When nodes have matching frequencies, the node with a smaller ASCII symbol will be dequeued first.
- A lower frequency node has a higher priority.

Code ADT

- Represents a stack of bits
- The struct definition of a code is transparent so we can pass a struct by value
- The MAX_CODE_SIZE macro is defined in defines.h

I/O

- Uses low level syscalls like read(), write(), open(), and close()

Stacks

- The stack will be used to store nodes.

Functionality

Encoder

- The Huffman encoder reads from an input file, gets the Huffman encoding of the contents, and compresses the file using the encoding. It supports the command line options [-h] [-i infile] [-o outfile] [-v].
    - -h option prints out a help message the explains the purpose of the program and the command line options the encoder accepts then exits the program
    - -i infile option specifies the input file to encode with Huffman coding. The default input is stdin
    - -o outfile option specifies the output file to write the compressed input to. The default output is stdout
    - -v option specifies to print the compression statistics to stderr. The statistics are the uncompressed file size, the compressed file size and the space saving (100 * (1-(compressed size/uncompressed size))
- The encoder function process::
    - Counts the number of occurrences of each unique symbol in the file and computers a histogram
    - The counts for symbols 0 and 255 are both incremented once. Their priorities are increased in the priority queue to account for the artificially increased count.
    - Constructs a Huffman tree using the histogram with a priority queue
    - Creates a code table. The indices in the table represent symbols and the value at each index represents the symbol's code. This step uses a stack of bits to perform a traversal of the Huffman tree.

    - Puts an encoding of the Huffman tree called a tree dump in the file using a post-order traversal of the Huffman tree
    - Go through each symbol in the input file and emit each symbol's code to the output file

Decoder

- The Huffman decoder reads a compressed input file and decompresses it back to its original, uncompressed size. It supports the command line options [-h] [-i infile] [-o outfile] [-v].
    - -h option tells the program to print out a help message describing the purpose of the decoder and the available command-line options then exits the program
    - -i infile specifies the input file to decode using Huffman coding. The default input is stdin
    - -o outfile specifies the output file to write the decompressed input to. The default output is stdout
    - -v prints decompression statistics to stderr. The statistics are compressed file size, the decompressed file size, and space saving (100 * (1 - (compressed size/decompressed size))
- Process for decode/decompress:
    - Reads the tree dump from the input file, using a stack of nodes to reconstruct the Huffman tree
    - Reads in the rest of the file bit-by-bit, traversing down the Huffman tree. A read of 0 leads to walking down the left link while a read of 1 leads to walking down the right link. When a leaf node is reached, its symbol is emitted and the program traverses again from the root.

Error handling

- If the infile fails to open for the encoder or decoder, the program will print an error message and exit.
- If the outfile fails to open for the encoder or decoder, the program will print an error message and exit.
- If the magic number for the header does not match MAGIC defined in defines.h, the decoder will print an error message and exit.
- If the tree size in the header is greater than the MAX_TREE_SIZE of 3*ALPHABET - 1 defined in defines.h, the decoder will print an error message and exit.

Pseudocode

node.c

```
Node *node_create(int symbol, int frequency):
    Node *n=(Node *)malloc(sizeof(Node))
    If (n):
        n->symbol=symbol
        n->frequency=frequency
        n->left=null
        n->right =null
```

```
            Return n
        Else:
            free(n)
            Return null

Void node_delete(Node **n):
        free(*n)
        *n=null

Node *node_join(Node *left, Node *right):
        Node *n=node_create('$',left->frequency+right->frequency)
        n->left=left
        n->right=right
        Return n

Void node_print(Node *n):
        printf(symbol:<n->symbol>)
        Print new line
        Printf(frequency:<n->frequency>)
        Print new line
```

pq.c

```
Struct PriorityQueue {
        Head
        Tail
        Slot
        Size
        Capacity
        Node **elements
}

U32 get_left(PriorityQueue *q, u32 i):
        Return (i-1+q->capacity)%q->capacity

U32 get_right(PriorityQueue *q,u32 i):
        Return (i+1)%q->capacity

PriorityQueue *pq_create(int capacity)
        PriorityQueue *q=(PriorityQueue *)malloc(sizeof(PriorityQueue))
        If (q):
            q->capacity=capacity
            q->head=0
            q->tail=0
            q->slot=0
```

```
            q->size=0
            q->elements=(Node **)calloc(capacity,sizeof(Node *))
            if(!q->elements):
                free(q)
                q=null
        Return q

Void pq_delete(PriorityQueue **q):
        free((*q)->elements)
        free(*q)
        *q=null

Bool pq_empty(PriorityQueue *q):
        Return !q->size

Bool pq_full(PriorityQueue *q):
        Return q->size==q->capacity

Int pq_size(PriorityQueue *q):
        Return q->size

Bool enqueue(PriorityQueue *q, Node *n):
        If pq_full(q):
            Return false
        If (n->symbol==0 or n->symbol==255):
            n->frequency--
        q->slot=q->tail
        while(q->slot!=q->head and q->elements[get_left(q,q->slot))]->frequency >
n->frequency):
            q->elements[q->slot]=q->elements[get_left(q,q->slot))]
            q->slot=get_left(q,q->slot)
        While (q->slot!=q->head and q->elements[get_left(q,q->slot)]->frequency==n->frequency
and q->elements[get_left(q,q->slot)]->symbol > n->symbol]:
            q->elements[q->slot]=q->elements[get_left(q,q->slot))]
            q->slot=get_left(q,q->slot)
        If (n->symbol==0 or n->symbol==255):
            n->frequency++
        q->elements[q->slot]=n
        q->elements[q->tail]=get_right(q,q->tail)
        q->size++
        Return true

Bool dequeue(PriorityQueue *q, Node **n):
        If pq_empty(q):
```

```
            Return false
        *n=q->elements[q->head]
        q->head=get_right(q,q->head)
        q->size--
        Return true

Void pq_print(PriorityQueue *q):
        If (!pq_full(q)):
            For i in range q->head to q->tail:
                node_print(q->elements[i])
        Else:
            For i in range q->head to get_left(q,q->tail):
                node_print(q->elements[i])
```

Code.c

```
Define BYTE_SIZE 8

Code code_init(void):
        Code *c
        c->top=0
        For i in range MAX_CODE_SIZE:
            c->bits[i]=0
        Return c

Int code_size(Code *c):
        Return c->top

Bool code_empty(Code *c):
        Return !c->top

Bool code_full(Code *c):
        Return c->top==ALPHABET

Bool code_push_bit(Code *c, int bit):
        If code_full(c):
            Return false
        c->bits[c->top/BYTE_SIZE] |= (bit <<(c->top % BYTE_SIZE)
        c->top++
        Return true

Bool code_pop_bit(Code *c,int *bit):
        If code_empty(c):
            Return false
        c->top--
```

```
        *bit=(c->bits[c->top/BYTE_SIZE] & (1 << (c->top % BYTE_SIZE)))>>(c->top %
BYTE_SIZE)
        Return true

Void code_print(Code *c):
        For i in range c->top:
                Print <c->bits[i/BYTE_SIZE] & (1<<(i % BYTE_SIZE)))>>(i%BYTE_SIZE)]>
        Print new line
```

io.c

```
Define BYTE_SIZE 8

Static u8 buffer[BLOCK]= { 0 }
Static u32 bufindex

U8 code_get_bit(Code *c, u32 i ):
        Return (c->bits[i/BYTE_SIZE]&((u64) 1<<(i%BYTE_SIZE)))>>(i%BYTE_SIZE)

U8 buf_get_bit(u8 *buf, u32 i):
        Return (buf[i/BYTE_SIZE] & ((u64) 1<<(i%BYTE_SIZE)))>>(i%BYTE_SIZE)

Void buf_set_bit(u8 *buf, u32 i):
        buf[i/BYTE_SIZE] |= ((u64) 1<<(i%BYTE_SIZE)

Void buf_clr_bit(u8 *buf,u32 i):
        buf[i/BYTE_SIZE] |= ((u64) 1 << (i%BYTE_SIZE))

Int read_bytes(int infile, int *buf, int nbytes):
        Int bytes=0
        Int total=0
        While (total!=nbytes):
                bytes=read(infile,bu,nbytes-total)
                If (!bytes):
                        Break
                total+=bytes
        bytes_read+=total
        Return total

Int write_bytes(int outfile, int *buf, int nbytes):
        Int bytes=0
        Int total=0
        while(total!=nbytes):
                bytes=write(outfile,buf,nbytes-total)
                if(!bytes):
```

```
                Break
            total+=bytes
        bytes_written+=total
        Return total
```

Influenced by Eugene's lab section on 5/11

```
Bool read_bit(int infile, int *bit):
        U32 last_bit=0
        U32 read=0
        If (!bufindex)::
            read=read_bytes(infile,buffer,BLOCK)
            if(read<BLOCK):
                last_bit=read*BYTE_SIZE+1
        *bit=buf_get_bit(buffer,bufindex)
        bufindex++
        If (bufindex==BLOCK*BYTE_SIZE):
            bufindex=0
        If (bufindex==last_bit):
            Return false
        else:
            Return true
```

Inspired by Eugene's lab section on 5/11

```
Void write_code(int outfile, Code *c)
        For i in range code_size(c):
            If (code_get_bit(c,i)):
                buf_set_bit(buffer, bufindex)
            Else:
                buf_clr_bit((buffer, bufindex)
        Bufindex++
        If bufindex==BLOCK*BYTE_SIZE:
            write_bytes(outfile,buffer,BLOCK)
            bufindex=0

Void flush_codes(int outfile):
        If bufindex>0:
            write_bytes(outfile,buffer, bufindex/BYTE_SIZE+(bufindex%BYTE_SIZE then 1
else 0)
```

stack.c

Struct code provided by Professor Long in assignment pdf

```
Struct Stack {
        Int top
        Int capacity
```

```
        Node **items
}

Stack *stack_create(int capacity):
        Stack *s=(Stack *s) malloc(sizeof(Stack))
        If (s):
                s->top=0
                s->capacity=capacity
                s->items=(Node **)calloc(capacity,sizeof(Node *))
                If (!s->items):
                        free(s)
                        s=null
        Return s

Void stack_delete(Stack **s):
        if(*s and (*s)->items):
                free((*s)->items)
                free(*s)
                *s=null

Bool Stack_empty(Stack *s):
        Return !s->top

Bool stack_full(Stack *s):
        Return s->top==s->capacity

Int stack_size(Stack *s):
        Return s->top

Bool stack_push(Stack *s, Node *n):
        if(stack_full(s)):
                Return false
        s->items[s->top]=n
        s->top++
        Return true

stack_pop(Stack *s, Node **n):
        if(stack_empty(s)):
                Return false
        s->top--
        *n=s->items[s->top]
        Return true

stack_print(Stack *s):
```

```
        For i in range s->top:
                node_print(s->items[i])
```

huffman.c

Code inspired by Eugene's 5/11 lab section

```
postorder(Node *n, Code table[static ALPHABET], Code c):
        U8 bit
        If (n):
                If n is a leaf:
                        table[n->symbol]=c
                code_push_bit(&c,0)
                postorder(n->left)
                code_pop_bit(&c, &bit)
                code_push_bit(&c,1)
                postorder(n->right)
                code_pop_bit(&c,&bit)

Node *build_tree(int hist[static ALPHABET]):
        PriorityQueue *q=pq_create(ALPHABET)
        Node *left
        Node *right
        Node *root
        For i in range ALPHABET:
                if (hist[i] > 0):
                        enqueue(q, node_create(i,hist[i))
        While (pq_size>1):
                dequeue to get left child
                Dequeue to get right child
                Enqueue node_join(left child, right child)
        Dequeue last node into root
        Delete q
        Return root

Void build_codes(Node *root, Code table[static ALPHABET]):
        Code c=code_init()
        postorder(root,table,c)

Node *rebuild_tree(int bytes, int tree_dump[static nbytes]):
        Stack *s=stack_create(ALPHABET)
        Node *left
        Node *right
        Node *root
        For i in range nbytes:
```

```
        If (tree_dump[i]=='L'):
            Push node_create(tree_dump[i+1],0) onto the stack
            I++
        Else if (tree_dump[i]=='I'):
            Pop to get the right child
            Pop to get the left child
            Push node_join(left,right) onto the stack
    Pop the last node of the stack into root
    Delete s
    Return root

Void delete_tree(Node **root):
    If (*root):
        delete_tree(root->left)
        delete_tree(root->right)
        node_delete(root)
```

Draft Work

priority queue (5 elements)

slot

[2 , 3 , 4 , 5 , 6]

head tail

5, 3, 2, 4, 6

pq[slot-1] > 6

pq[slot] = pq[slot-1]

right(k, n)

(k+1)% n

input aaaabbc

symbol	freq
a	4
b	2
c	1

head

head c b a tail

1 2 4



symbol	code
a	1
b	01
c	00

a	4
b	2
c	1
d	1

symbol	code
a	0
b	11
c	100
d	101

input: a a a a b b c d

a a a a b b c d

0 0 0 0 11 11 100 101

if both children are NULL, then it's a leaf

postorder traversal

```
def postorder(Node *n):
    if n is not null{
        post order(n->left)
        postorder(n->right)
        node_print(n)
    }
```

9, 10, 5, 7, 8, 6, 3

Tree Dump



LaLcLd I LbII