EECS 487: Introduction to Natural Language Processing

Instructor: Prof. Lu Wang

Computer Science and Engineering

University of Michigan

https://web.eecs.umich.edu/~wangluxy/

The grammar

S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0


fish
1
people
2
fish
3
tanks
4
0
1
2
3
4
score[0][1]
score[0][2]
score[0][3]
score[0][4]
score[1][2]
score[1][3]
score[1][4]
score[2][3]
score[2][4]
score[3][4]

S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0
N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0



S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0
N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0



S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0
N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0



S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0

	fish	1	people	2	fish	3	tanks	4
0	N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006		NP → NP NP 0.0049 VP → V NP 0.105 S → NP VP 0.00126					
1			N → people 0.5 V → people 0.1 NP → N 0.35 VP → V 0.01 S → VP 0.001		NP → NP NP 0.0049 VP → V NP 0.007 S → NP VP 0.0189			
2					N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006		NP → NP NP 0.00196 VP → V NP 0.042 S → NP VP 0.00378	
3							N → tanks 0.2 V → tanks 0.3 NP → N 0.14 VP → V 0.03 S → VP 0.003	
4								

S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0

	fish	1	people	2	fish	3	tanks	4
0	N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006		NP → NP NP 0.0049 VP → V NP 0.105 S → VP 0.0105					
1			N → people 0.5 V → people 0.1 NP → N 0.35 VP → V 0.01 S → VP 0.001		NP → NP NP 0.0049 VP → V NP 0.007 S → NP VP 0.0189			
2					N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006		NP → NP NP 0.00196 VP → V NP 0.042 S → VP 0.0042	
3							N → tanks 0.2 V → tanks 0.3 NP → N 0.14 VP → V 0.03 S → VP 0.003	
4								

S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0

	fish	1	people	2	fish	3	tanks	4
0	N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006		NP → NP NP 0.0049 VP → V NP 0.105 S → VP 0.0105		NP → NP NP 0.0000686 VP → V NP 0.00147 S → NP VP 0.000882			
1			N → people 0.5 V → people 0.1 NP → N 0.35 VP → V 0.01 S → VP 0.001		NP → NP NP 0.0049 VP → V NP 0.007 S → NP VP 0.0189			
2					N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006		NP → NP NP 0.00196 VP → V NP 0.042 S → VP 0.0042	
3							N → tanks 0.2 V → tanks 0.3 NP → N 0.14 VP → V 0.03 S → VP 0.003	
4								

S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0

	fish 1	people 2	fish 3	tanks 4
0	N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006	NP → NP NP 0.0049 VP → V NP 0.105 S → VP 0.0105	NP → NP NP 0.0000686 VP → V NP 0.00147 S → NP VP 0.000882	
1		N → people 0.5 V → people 0.1 NP → N 0.35 VP → V 0.01 S → VP 0.001	NP → NP NP 0.0049 VP → V NP 0.007 S → NP VP 0.0189	NP → NP NP 0.0000686 VP → V NP 0.000098 S → NP VP 0.01323
2			N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006	NP → NP NP 0.00196 VP → V NP 0.042 S → VP 0.0042
3				N → tanks 0.2 V → tanks 0.3 NP → N 0.14 VP → V 0.03 S → VP 0.003
4				

S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0

	fish	people	fish	tanks
	1	2	3	4
0	N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006	NP → NP NP 0.0049 VP → V NP 0.105 S → VP 0.0105	NP → NP NP 0.0000686 VP → V NP 0.00147 S → NP VP 0.000882	NP → NP NP 0.0000009604 VP → V NP 0.00002058 S → NP VP 0.00018522
1		N → people 0.5 V → people 0.1 NP → N 0.35 VP → V 0.01 S → VP 0.001	NP → NP NP 0.0049 VP → V NP 0.007 S → NP VP 0.0189	NP → NP NP 0.0000686 VP → V NP 0.000098 S → NP VP 0.01323
2			N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006	NP → NP NP 0.00196 VP → V NP 0.042 S → VP 0.0042
3				N → tanks 0.2 V → tanks 0.3 NP → N 0.14 VP → V 0.03 S → VP 0.003
4				

S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0
N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0




```
for i=0; i<#(words); i++
   for A in nonterms
     if A -> words[i] in grammar
       score[i][i+1][A] = P(A -> words[i]);
```

S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0




```
// handle unaries
boolean added = true
    while added
      added = false
      for A, B in nonterms
        if score[i][i+1][B] > 0 && A->B in grammar
          prob = P(A->B)*score[i][i+1][B]
          if(prob > score[i][i+1][A])
            score[i][i+1][A] = prob
            back[i][i+1][A] = B
            added = true
```

S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0
N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0



S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0



S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0



S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0

	fish	1	people	2	fish	3	tanks	4
0	N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006		NP → NP NP 0.0049 VP → V NP 0.105 S → VP 0.0105		NP → NP NP 0.0000686 VP → V NP 0.00147 S → NP VP 0.000882			
1			N → people 0.5 V → people 0.1 NP → N 0.35 VP → V 0.01 S → VP 0.001		NP → NP NP 0.0049 VP → V NP 0.007 S → NP VP 0.0189			
2					N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006		NP → NP NP 0.00196 VP → V NP 0.042 S → VP 0.0042	
3							N → tanks 0.2 V → tanks 0.3 NP → N 0.14 VP → V 0.03 S → VP 0.003	
4								

```
for split = begin+1 to end-1
  for A,B,C in nonterms
    prob=score[begin][split][B]*score[split][end][C]*P(A->BC)
    if prob > score[begin][end][A]
      score[begin]end][A] = prob
      back[begin][end][A] = new Triple(split,B,C)
```

S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0

	fish	people	fish	tanks
	0	1	2	3	4
0	N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006	NP → NP NP 0.0049 VP → V NP 0.105 S → VP 0.0105	NP → NP NP 0.0000686 VP → V NP 0.00147 S → NP VP 0.000882	
1		N → people 0.5 V → people 0.1 NP → N 0.35 VP → V 0.01 S → VP 0.001	NP → NP NP 0.0049 VP → V NP 0.007 S → NP VP 0.0189	NP → NP NP 0.0000686 VP → V NP 0.000098 S → NP VP 0.01323
2			N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006	NP → NP NP 0.00196 VP → V NP 0.042 S → VP 0.0042
3				N → tanks 0.2 V → tanks 0.3 NP → N 0.14 VP → V 0.03 S → VP 0.003
4				

```
for split = begin+1 to end-1
  for A,B,C in nonterms
    prob=score[begin][split][B]*score[split][end][C]*P(A->BC)
    if prob > score[begin][end][A]
      score[begin]end][A] = prob
      back[begin][end][A] = new Triple(split,B,C)
```

S → NP VP	0.9
S → VP	0.1
VP → V NP	0.5
VP → V	0.1
VP → V @VP_V	0.3
VP → V PP	0.1
@VP_V → NP PP	1.0
NP → NP NP	0.1
NP → NP PP	0.2
NP → N	0.7
PP → P NP	1.0

N → *people*	0.5
N → *fish*	0.2
N → *tanks*	0.2
N → *rods*	0.1
V → *people*	0.1
V → *fish*	0.6
V → *tanks*	0.3
P → *with*	1.0

	fish	people	fish	tanks
	0	1	2	3	4
0	N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006	NP → NP NP 0.0049 VP → V NP 0.105 S → VP 0.0105	NP → NP NP 0.0000686 VP → V NP 0.00147 S → NP VP 0.000882	NP → NP NP 0.0000009604 VP → V NP 0.00002058 S → NP VP 0.00018522
1		N → people 0.5 V → people 0.1 NP → N 0.35 VP → V 0.01 S → VP 0.001	NP → NP NP 0.0049 VP → V NP 0.007 S → NP VP 0.0189	NP → NP NP 0.0000686 VP → V NP 0.000098 S → NP VP 0.01323
2			N → fish 0.2 V → fish 0.6 NP → N 0.14 VP → V 0.06 S → VP 0.006	NP → NP NP 0.00196 VP → V NP 0.042 S → VP 0.0042
3				N → tanks 0.2 V → tanks 0.3 NP → N 0.14 VP → V 0.03 S → VP 0.003
4				

Call buildTree(score, back) to get the best parse

Some Comments on CKY parsing

- CKY parsing is usually done **after binarization**
- Unaries can be incorporated into the algorithm
  - Messy, but doesn't increase algorithmic complexity
- Empties can be incorporated
  - Doesn't increase complexity; essentially like unaries
- Binarization is *vital*
  - Without binarization, you don't get parsing cubic in the length of the sentence and in the number of nonterminals in the grammar

Where to learn the probabilities: Treebanks

- English Penn Treebank: Standard corpus for testing syntactic parsing consists of 1.2 M words of text from the Wall Street Journal (WSJ).
- Typical to train on about 40,000 parsed sentences and test on an additional standard disjoint test set of 2,416 sentences.
- Chinese Penn Treebank: 100K words from the Xinhua news service.
- Other corpora existing in many languages, see the Wikipedia article "Treebank"

Computing Evaluation Metrics



Constituents: 12

Constituents: 12

Correct Constituents: 10

Recall = 10/12= 83.3% Precision = 10/12=83.3% F_1 = 83.3%

Evaluating constituency parsing

Gold standard brackets: **S-(0:11)**, **NP-(0:2)**, VP-(2:9), VP-(3:9), **NP-(4:6)**, PP-(6-9), NP-(7,9), NP-(9:10)



Candidate brackets: **S-(0:11)**, **NP-(0:2)**, VP-(2:10), VP-(3:10), **NP-(4:6)**, PP-(6-10), NP-(7,10)



Evaluating constituency parsing

Gold standard brackets:

S-(0:11), NP-(0:2), VP-(2:9), VP-(3:9), **NP-(4:6)**, PP-(6-9), NP-(7,9), NP-(9:10)

Candidate brackets:

S-(0:11), **NP-(0:2)**, VP-(2:10), VP-(3:10), **NP-(4:6)**, PP-(6-10), NP-(7,10)

Labeled Precision	3/7 = 42.9%
Labeled Recall	3/8 = 37.5%
LP/LR F1	40.0%
POS Tagging Accuracy	11/11 = 100.0%

But we still can’t produce two different trees like…



(Head) Lexicalization of PCFGs

[Magerman 1995, Collins 1997; Charniak 1997]

- The head word of a phrase gives a good representation of the phrase's structure and meaning (*head words are decided by rules, the **most important word** in a constituent*)
- Puts the properties of words back into a PCFG



Head Words

- Syntactic phrases usually have a word in them that is most “central” to the phrase.
- Linguists have defined the concept of a lexical **head** of a phrase.
- Simple rules can identify the head of any phrase by percolating head words up the parse tree.
  - Head of a VP is the main verb
  - Head of an NP is the main noun
  - Head of a PP is the preposition
  - Head of a sentence is the head of its VP

(Head) Lexicalization of PCFGs

[Magerman 1995, Collins 1997; Charniak 1997]

- The head word of a phrase gives a good representation of the phrase's structure and meaning
- Puts the properties of words back into a PCFG



(Head) Lexicalization of PCFGs

[Magerman 1995, Collins 1997; Charniak 1997]

- The head word of a phrase gives a good representation of the phrase's structure and meaning
- Puts the properties of words back into a PCFG



(Head) Lexicalization of PCFGs

[Magerman 1995, Collins 1997; Charniak 1997]

- Word-to-word affinities are useful for certain ambiguities
  - PP attachment is now (partly) captured in a local PCFG rule.





Lexicalized parsing was seen as *the* parsing breakthrough of the late 1990s

- Eugene Charniak, 2000 JHU workshop: "To do better, it is necessary to condition probabilities on the actual words of the sentence. This makes the probabilities much tighter:
  - $p(\text{VP} \rightarrow \text{V NP NP})$ = 0.00151
  - $p(\text{VP} \rightarrow \text{V NP NP} \mid \text{said})$ = 0.00001
  - $p(\text{VP} \rightarrow \text{V NP NP} \mid \text{gave})$ = 0.01980 " *p(rule|head word)*
- Michael Collins, 2003 COLT tutorial: "**Lexicalized Probabilistic Context-Free Grammars** … perform vastly better than PCFGs (88% vs. 73% accuracy)"

Lexicalization models argument selection by sharpening rule expansion probabilities

- The probability of different verbal complement frames (i.e., "subcategorizations") depends on the verb:

Local Tree	*come*	*take*	*think*	*want*
VP → V	9.5%	2.6%	4.6%	5.7%
VP → V NP	1.1%	**32.1%**	0.2%	13.9%
VP → V PP	**34.5%**	3.1%	7.1%	0.3%
VP → V SBAR	6.6%	0.3%	**73.0%**	0.2%
VP → V S	2.2%	1.3%	4.8%	**70.8%**
VP → V NP S	0.1%	5.7%	0.0%	0.3%
VP → V PRT NP	0.3%	5.8%	0.0%	0.0%
VP → V PRT PP	6.1%	1.5%	0.2%	0.0%

Dependency Grammar and Dependency Structure

Dependency syntax postulates that syntactic structure consists of lexical items linked by binary asymmetric relations ("arrows") called dependencies

The arrows are commonly typed with the name of grammatical relations (subject, prepositional object, apposition, etc.)



Bills on ports and immigration were submitted by Senator Brownback, Republican of Kansas.

Dependency Grammar and Dependency Structure

Dependency syntax postulates that syntactic structure consists of lexical items linked by binary asymmetric relations ("arrows") called dependencies

The arrow connects a head (governor, superior, regent) with a dependent (modifier, inferior, subordinate)

Usually, dependencies form a tree (connected, acyclic, single-head)



Relation between phrase structure and dependency structure

- A dependency grammar has a notion of a head. Officially, CFGs don't.
- But modern linguistic theory and all modern statistical parsers (Charniak, Collins, Stanford, …) do, via hand-written phrasal "head rules":
  - The head of a Noun Phrase is a noun/number/adj/…
  - The head of a Verb Phrase is a verb/modal/….
- The head rules can be used to extract a dependency parse from a CFG parse

Dependency Graph from Parse Tree

- Can convert a phrase structure parse to a dependency tree by making the head of each non-head child of a node depend on the head of the head child.





Like a depth first search