

SI 506 Programming I

[Syllabus](#) [Meetings](#) [Schedule](#) [Resources](#) [Team](#) [Contact](#)

Unix shell commands primer

[Home](#) / [Resources](#) / [Unix shell commands](#)

Below is a select list of Unix shell commands that you can use from the command line to navigate your local file system as well as create, delete, copy, and move directories and files. Additional commands are included that list the location of the current working directory or the path to an executable, view the contents of a text file, and clear the terminal screen of content.

1.0 Location uncertain

If your terminal prompt provides no hint and you are unsure in which directory you currently reside, use the built-in **pwd** command to print the current working directory.

1.1 macOS

```
pwd
```

```
/Users/arwhyte
```

1.2 Windows

```
pwd
```

```
/c/Users/arwhyte
```

2.0 List files in the current working directory

If you require basic info about subdirectories and files that reside in the current directory, use the `ls` command along with command options to print out the details.

! the output below represents a subset of subdirectories and files found in a macOS home directory; certain items have been excluded for display purposes only.

2.1 macOS

```
ls
```

| | | |
|--------------|-------------|----------|
| Applications | Development | Music |
| Downloads | Documents | Pictures |
| Dropbox | Library | Postman |
| Desktop | Movies | Public |

2.2 Windows

```
ls
```

```
'3D Objects'/  
AppData/  
'Application Data'@
```

```
Contacts/  
Cookies@  
Desktop/  
Documents/  
Downloads/  
Favorites/  
Links/  
'Local Settings'@  
MicrosoftEdgeBackups/  
Music/  
'My Documents'@  
OneDrive/  
Pictures/  
PrinHood@  
Recent@  
Searches/  
SendTo@  
'Start Menu'@  
Templates@  
Videos/
```

2.3 ls command options (select list)

| Option | Description |
|-------------------|--|
| -a, --all | List all files including hidden . files. |
| -d, --directory | List only directory information (not files). |
| -l, --format=long | Long format listing (permissions, owner, size, modification time, etc.). |
| -R, --recursive | Recursively list subdirectories as well as current directory |

! the output below represents a subset of subdirectories and files found in a macOS home directory; certain items have been excluded for display purposes

only.

```
ls -al
```

```
total 2848520
```

```
drwx-----+ 76 arwhyte staff 2432 Sep 3 07:56 .
drwxr-xr-x 11 root admin 352 Dec 5 2019 ..
-rw-r--r--@ 1 arwhyte staff 10244 Sep 3 07:28 .DS_Store
drwx----- 2 arwhyte staff 64 Sep 3 07:29 .Trash
-rw----- 1 arwhyte staff 33742 Mar 16 14:58 .bash_history
-rw-r--r--@ 1 arwhyte staff 1870 Apr 19 23:15 .bash_profile
drwx----- 4 arwhyte staff 128 Jan 14 2019 .config
drwx----- 3 arwhyte staff 96 Feb 13 2019 .cups
drwx----- 15 arwhyte staff 480 Oct 16 2019 .dropbox
-rw-r--r-- 1 arwhyte staff 767 Aug 20 15:01 .gitconfig
drwxr-xr-x 3 arwhyte staff 96 Oct 19 2019 .idlerc
drwxr-xr-x 3 arwhyte staff 96 Mar 27 13:03 .local
drwxr-xr-x 19 arwhyte staff 608 Aug 31 20:59 .oh-my-zsh
drwxr-xr-x 304 arwhyte staff 9728 Sep 1 13:54 .pylint.d
-rw----- 1 arwhyte staff 8730 Sep 1 17:02 .python_history
drwx----- 8 arwhyte staff 256 Jan 11 2019 .ssh
drwxr-xr-x 4 arwhyte staff 128 Dec 3 2019 .vscode
drwxr-xr-x 2 arwhyte staff 64 Aug 6 2019 .zoomus
-rw----- 1 arwhyte staff 660463 Sep 3 07:56 .zsh_history
-rw-r--r-- 1 arwhyte staff 281 Jul 2 17:04 .zshenv
-rw-r--r-- 1 arwhyte staff 4188 Aug 14 18:15 .zshrc
drwx-----@ 4 arwhyte staff 128 Jun 16 14:20 Applications
drwx-----@ 35 arwhyte staff 1120 Sep 2 14:47 Desktop
drwxr-xr-x 10 arwhyte staff 320 Aug 23 19:55 Development
drwx-----@ 5 arwhyte staff 160 Sep 3 07:28 Documents
drwx-----@ 275 arwhyte staff 8800 Sep 2 18:13 Downloads
drwx-----@ 12 arwhyte staff 384 Aug 22 08:27 Dropbox
drwx-----@ 83 arwhyte staff 2656 Jun 11 20:22 Library
drwx-----+ 8 arwhyte staff 256 Jul 20 21:38 Movies
```

```
drwx-----+  7 arwhyte  staff      224 Dec 20 2019 Music
drwx-----+ 87 arwhyte  staff    2784 Aug  5 17:58 Pictures
drwxr-xr-x   3 arwhyte  staff      96 Jul 15 12:36 Postman
drwxr-xr-x   4 arwhyte  staff     128 Nov 28 2018 Public
```

3.0 Change directory

If you need to change your current location, use the **cd** command to change your to a different working directory in your file system.

! Note that directory names and file names are case sensitive.

3.1 Change to a child directory

You can change to child directory using a *relative* path (i.e., relative to the current working directory).

```
pwd
```

```
/Users/arwhyte
```

```
cd Documents
```

```
pwd
```

```
/Users/arwhyte/Documents
```

💡 the current working directory is denoted by a single dot (.).

```
pwd
```

```
/Users/arwhyte
```

```
cd ../Documents
```

```
pwd
```

```
/Users/arwhyte/Documents
```

💡 If you need to traverse n-levels deep you can do so by extending the relative path with additional directory names separated by a slash (/).

```
pwd
```

```
/Users/arwhyte
```

```
cd Documents/umsi
```

```
pwd
```

```
/Users/arwhyte/Documents/umsi
```

3.2 Change to a parent directory

Two dots (..) represent the parent directory or the directory one level up.

```
pwd
```

```
/Users/arwhyte/Documents
```

```
cd ..
```

```
pwd
```

```
/Users/arwhyte
```

💡 You can concatenate the two dot parent directory notation using a slash as a separator (e.g., `../..`) *n-times* in order to traverse the directory tree *n-levels* up.

```
pwd
```

```
/Users/arwhyte/Documents
```

```
cd ../../
```

```
pwd
```

```
/Users
```

3.3 Change to an adjacent or sibling directory

You can switch to an adjacent or sibling directory by using the two dot notation (`..`) together with the directory name separated by a slash (`/`). In the following example the **Documents** directory contains two child directories: **umsi** and **umpy**.

```
pwd
```

```
/Users/arwhyte/Documents/umsi
```

```
cd ../umpy
```

```
pwd
```

```
/Users/arwhyte/Documents/umpy
```

3.4 Change directory using an absolute path

You can also change directories using an *absolute* path.

```
pwd
```

```
/Users/arwhyte
```

```
cd /Users/arwhyte/Documents
```

```
pwd
```

```
/Users/arwhyte/Documents
```

3.5 Change to user's home directory

You can change to your home directory by using the tilde (~) character.

```
pwd
```

```
/Users/arwhyte/Documents/umsi
```

```
cd ~
```

```
pwd
```

```
/Users/arwhyte
```

3.6 Directory names with spaces

If you need to change to a directory that includes spaces in its name you *must* either surround the name with a pair of single or double quotation marks or escape the spaces with the backslash (\) character.

💡 I recommend avoiding the use of spaces when naming directories or files in order to avoid having to add quotation marks or escape characters to your

paths. Instead consider using underscores (_) if you want to separate characters in a directory or filename (e.g., `si_506` not `si 506`).

While on the subject of filenames, the Python community's naming convention for filenames or [modules](#) as they are called is as follows:

Modules should have short, all-lowercase names. Underscores can be used in the module name if it improves readability.

```
pwd
/Users/arwhyte/Documents/umsi
→ umsi ls

si 506

cd 'si 506'
pwd

/Users/arwhyte/Documents/umsi/si 506

cd ..
cd "si 506"
pwd

/Users/arwhyte/Documents/umsi/si 506

cd ..
cd si\ 506
pwd

/Users/arwhyte/Documents/umsi/si 506
```

4.0 Create a directory

To create a new director use the `mkdir` command passing the name of the new directory as an argument.

```
pwd
```

```
/Users/arwhyte/Documents
```

```
mkdir umich
```

```
ls
```

```
umich  umpy  umsi
```

💡 You can create multiple directories at the same time by passing multiple names each separated by a space.

```
pwd
```

```
/Users/arwhyte/Documents
```

```
mkdir msu osu
```

```
ls
```

```
msu  osu  umich  umpy  umsi
```

5.0 Delete a directory

5.1 Delete an empty directory

To delete an *empty* directory use the **rmdir** command passing the name of the directory you wish to delete as an argument.

```
pwd
```

```
/Users/arwhyte/Documents
```

```
rmdir osu
```

```
ls
```

```
msu    umich  umpy   umsi
```

5.2 Delete a directory with content

To delete a directory that contains content (i.e., subdirectories and/or files) use the **rm** command together with the **-r** recursive command option and either the **-f** force option or **-i** interactive command option.

5.2.1 rm command options (select list)

| Option | Description |
|--------------------------|--|
| -f, --force | Remove write protected files without prompting. |
| -i, --interactive | Prompt for y (yes) or n (no) before removing a file. Overrides -f . |
| -r, --recursive | Remove all subdirectories and content recursively. |

```
rmdir msu
```

```
rmdir: msu: Directory not empty
```

```
cd msu
```

```
ls

spartans.txt

cd ..
rm -rf msu
ls

umich  umpy  umsi
```

6.0 Create a file

You can use the **touch** command to create an empty file by passing the new filename as an argument.

```
pwd

/Users/arwhyte/Documents/umich

touch wolverines.txt
ls

wolverines.txt
```

7.0 View the contents of a text file

To view the contents of a text file use the **cat** command.

```
cat wolverines.txt
```

Go Blue!

8.0 Delete a file

You can use the `rm` command to delete a file.

```
rm delete_me.txt
```

9.0 Move a directory or file to another location

You can use the `mv` command to move a directory or file from one location to another. Specify the *source* directory or file (i.e., the directory or file you wish to move) and the *target* location as arguments.

⚠ if you move a file to a directory that contains a file with the same name you will overwrite the existing file.

```
pwd
```

```
/Users/arwhyte/Documents
```

```
mv umpy umich/
```

```
mv umsi umich/
```

```
cd umich
```

```
ls
```

```
umpy    umsi    wolverines.txt
```

To move directories or files up one level employ the two dot notation with a trailing slash to construct a relative path. You can also employ an absolute path

(e.g., `/Users/arwhyte/Documents/`) for the *target* location.

```
pwd
```

```
/Users/arwhyte/Documents/umsi/
```

```
ls
```

```
umpy    umsi    wolverines.txt
```

```
mv umpy ../
```

```
mv umsi ../
```

```
ls
```

```
wolverines.txt
```

```
cd ../
```

```
ls
```

```
umich    umpy    umsi
```

When you move a directory or file you can also change the name by specifying a new name in the *target* path.

```
pwd
```

```
/Users/arwhyte/Documents/
```

```
cd umich
```

```
ls
```

```
wolverines.txt
```

```
mv wolverines.txt ../go_blue.txt
cd ../

ls

go_blue.txt    umich    umpy    umsi
```

💡 If you possess the requisite permissions and construct the correct *target* path you can move directories and files to any target location in your file system.

10.0 Copy a directory or file to another location

You can use the **cp** command to copy a directory or file to another location. Specify the *source* directory or file (i.e., the directory or file you wish to copy) and the *target* location as arguments.

💡 You can change the name of the directory or file you copy by specifying the new directory name or filename as part of the *target* path.

10.1 cp command options (select list)

| Option | Description |
|-------------------|---|
| -f, --force | Remove existing files in target directory. |
| -i, --interactive | Prompt for y (yes) or n (no) before overwriting an existing file. |
| -R, --recursive | Copy directories recursively. |

10.2 Copy a directory to another location

When you use the **cp** command to copy a directory to another location you *must* also specify the command option **-R** in order to create a copy of the

directory recursively. Otherwise, the copy operation will fail.

```
pwd

/Users/arwhyte/Documents/

mkdir program_01 program_02
cp -R program_01 umsi/msi
cp -R program_02 umsi/mhi
cd umsi
ls

mhi    msi
```

10.3 Copy a file to another location

Copying a file does not require use of the `-R` command option. Specify the *source* directory or file (i.e., the directory or file you wish to copy) and the *target* location as arguments.

```
pwd

/Users/arwhyte/Documents/

cp go_blue.txt umich/victors.txt

cd umich
ls

victors.txt
```


💡 you can copy multiple files to the same target path by passing the names as arguments before specifying the target path.

```
cp go_blue.txt go_green.txt cheers/
```

Alternatively, you can employ a pattern matching wildcard (*).

```
cp *.txt cheers/
```

11.0 Clear the terminal screen

There are times when clearing the terminal screen of output makes sense. Use the `clear` command to do so.

```
clear
```

12.0 which

The `which` command comes in handy when you need to identify the location of an executable that is associated with a given command. For example, to return the executable path for Python 3.x pass the command alias as the argument (Windows users pass `python`).

```
which python3
```

```
/usr/local/bin/python3
```

13.0 Start the Python interactive console

You can run the Python interactive console (a.k.a the Python shell) from the terminal. Once the console is started the prompt will change. The new prompt comprises three greater than symbols (>>>).

13.1 macOS

```
python3
```

```
Python 3.9.6 (default, Jun 29 2021, 05:25:02)
[Clang 12.0.5 (clang-1205.0.22.9)] on darwin
Type "help", "copyright", "credits" or "license" for more information.
>>>
```

13.2 Windows Git Bash

When using Git Bash you *must* include the `-i` interactive command option or the Python interactive console. If you fail to specify the `-i` option Git Bash will hang (terminate the application and restart it).

```
python -i
```

```
Python 3.9.6 (default, Jun 29 2021, 05:25:02)
[Clang 12.0.5 (clang-1205.0.22.9)] on darwin
Type "help", "copyright", "credits" or "license" for more information.
>>>
```

You can also start the Python interactive console from Git Bash by first invoking **winpty**, a Windows software package that provides an interface for running Windows console programs.

```
winpty python
```

```
Python 3.9.6 (default, Jun 29 2021, 05:25:02)
[Clang 12.0.5 (clang-1205.0.22.9)] on darwin
Type "help", "copyright", "credits" or "license" for more information.
>>>
```

13.3 Windows Command Prompt

You can also start the Python Interactive console using the the Command Prompt (cmd). The `-i` command option is not required.

```
python
```

```
Python 3.9.6 (default, Jun 29 2021, 05:25:02)
[Clang 12.0.5 (clang-1205.0.22.9)] on darwin
Type "help", "copyright", "credits" or "license" for more information.
>>>
```

13.4 Quitting the console session

To exit the Python interactive console type `quit()` and then press enter.

```
>>> quit()
```

Sources

A. Robbins, [Unix in a Nutshell](https://www.oreilly.com/catalog/linutshell/), 4th edition (O'Reilly Media, Inc., 2005).

