

Assignment -6  
Using Special Operators in Conditions.

- 1) Write two different queries that would produce all orders taken on October 3<sup>rd</sup> or 4<sup>th</sup>, 1990.

```
mysql> SELECT *
-> FROM orders
-> WHERE Odate='1990-10-03' OR Odate='1990-10-04';
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002

```
7 rows in set (0.00 sec)
```

```
mysql> SELECT *
-> FROM orders
-> WHERE Odate BETWEEN '1990-10-03' AND '1990-10-04';
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002

```
7 rows in set (0.00 sec)
```

- 2) Write a query that selects all of the customers serviced by Peel or Motika.  
(Hint: the snum field relates the two tables to one another).

```
mysql> SELECT *
-> FROM customers
-> WHERE Snum = 1001 OR Snum = 1004;
+-----+-----+-----+-----+-----+
| Cnum | Cname | City | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100 | 1001 |
| 2006 | Clemens | London | 100 | 1001 |
| 2007 | Pereira | Rome | 100 | 1004 |
+-----+-----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql> SELECT *
-> FROM customers
-> WHERE Snum IN(SELECT Snum FROM salespeople WHERE Sname = 'Peel' OR Sname='Motika');
+-----+-----+-----+-----+-----+
| Cnum | Cname | City | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2001 | Hoffman | London | 100 | 1001 |
| 2006 | Clemens | London | 100 | 1001 |
| 2007 | Pereira | Rome | 100 | 1004 |
+-----+-----+-----+-----+-----+
3 rows in set (0.01 sec)
```

- 3) Write a query that will produce all the customers whose names begin with a letter from 'A' to 'G'.

```
mysql> SELECT *
-> FROM customers
-> WHERE Cname >'A' AND Cname<'H';
+-----+-----+-----+-----+-----+
| Cnum | Cname | City | Rating | Snum |
+-----+-----+-----+-----+-----+
| 2002 | Giovanni | Rome | 200 | 1003 |
| 2004 | Grass | Berlin | 300 | 1002 |
| 2006 | Clemens | London | 100 | 1001 |
| 2008 | Cisneros | San Jose | 300 | 1007 |
+-----+-----+-----+-----+-----+
4 rows in set (0.00 sec)
```

- 4) Write a query that selects all customers whose names begin with the letter 'C'.

```
mysql> SELECT *
-> FROM customers
-> WHERE Cname LIKE 'C%';
```

Cnum	Cname	City	Rating	Snum
2006	Clemens	London	100	1001
2008	Cisneros	San Jose	300	1007

```
2 rows in set (0.00 sec)
```

- 5) Write a query that selects all orders except those with zeroes or NULLs in the amt field.

```
mysql> SELECT *
-> FROM orders
-> WHERE amt>0 AND amt IS NOT NULL;
```

Onum	Amt	Odate	Cnum	Snum
3001	18.69	1990-10-03	2008	1007
3003	767.19	1990-10-03	2001	1001
3002	1900.10	1990-10-03	2007	1004
3005	5160.45	1990-10-03	2003	1002
3006	1098.16	1990-10-03	2008	1007
3009	1713.23	1990-10-04	2002	1003
3007	75.75	1990-10-04	2004	1002
3008	4723.00	1990-10-05	2006	1001
3010	1309.95	1990-10-06	2004	1002
3011	9891.88	1990-10-06	2006	1001

```
10 rows in set (0.00 sec)
```