DBMS LAB – 10 REPORT

Name: Darshan Kushalkar
Roll No: 24BCS035
Semester: IV

Aim

To learn the TRIGGERS.

---

1)

```
DELIMITER $$
CREATE TRIGGER MIN_SAL
BEFORE INSERT ON Employee
FOR EACH ROW
BEGIN
    IF NEW.salary < 20000 THEN
        SIGNAL SQLSTATE '45000'
        SET MESSAGE_TEXT = 'At least 20k salary must be there';
    END IF;
END$$
DELIMITER ;
```

Output:

```
INSERT INTO Employee VALUES("BYE",'K',"MY",131,"2020-04-07","hubli",'M',15000,333445555,4);
```

---

2)

create a table :

```
Create table Del_employee( Fname varchar(15) , Minit char(1), Lname Varchar(15), Ssn char(9) , Bdate date, Address varchar(50),Sex char(1), Sal
```

```
DELIMITER $$
Create Trigger Del_employee
After delete on Employee
For each row
begin
Insert into  Del_employee values(old.Fname,old.Minit,old.Lname,old.Ssn,old.Bdate,old.Address,old.Sex,old.Salary,old.Super_ssn,old.Dno);

end$$
DELIMITER ;
```

Deleting the row :

```
1249
1250 •    DELETE FROM EMPLOYEE WHERE Ssn=43212;
1251
```

29 18:01:12 DELETE FROM EMPLOYEE WHERE Ssn=43212

The data coming and getting stored in the new table :

```
1252 •    SELECT * FROM Del_employee;
1253
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

	Fname	Minit	Lname	Ssn	Bdate	Address	Sex	Salary	Super_ssn	Dno
▶	HI	K	MY	43212	2020-04-07	hubli	M	15000.00	333445555	4