

NULL Pointer

In C++, a null pointer is a special pointer value that indicates that the pointer is not pointing to any valid memory location. It is typically represented by the constant value `nullptr` or `NULL` and is used to signify that the pointer is not intended to point to any valid entity.

Here are some key points about null pointers in C++:

1. **nullptr:** In C++, the keyword `nullptr` or `NULL` is used to represent a null pointer.

2. **Pointer Initialization:** You can initialize a pointer to be a null pointer by assigning it the value `nullptr`. For example:

```
int *ptr = nullptr; // ptr is now a null pointer
```

3. **Checking for Null Pointers:** Before dereferencing a pointer, it's important to check if it's a null pointer to avoid runtime errors (such as segmentation faults). This can be done using an `if` statement or by directly checking the pointer value.

```
int *ptr = nullptr;
if (ptr != nullptr) {
    // Pointer is not null, safe to dereference
    *ptr = 10;
}
```

4. **Pointer Arithmetic:** Null pointers can participate in pointer arithmetic, but attempting to dereference a null pointer results in undefined behavior. It's crucial to ensure that a pointer is not null before attempting to dereference it.

```
int *ptr = nullptr;
ptr++; // Valid, but ptr is still a null pointer
```

5. **Default Initialization:** If a pointer is declared without initialization, it will have an indeterminate value, which is not guaranteed to be a null pointer. It's good