Network Toll Solution Pvt. Ltd.

MSWIM Bending Plate- NTS-NV-00M7

GENERAL INFORMATION

1	Type	BENDING PLATE based WIM
2	Weighing Capacity	30 / 40 / 50 ton / individual Axle
3	Each Load cell capacity	20 Ton
4	Ambient temperature	50 Degree celsius
5	Humidity	95%
6	Normal Lane	3.2 meter
7	Wide Lane	4.2 meter

SPECIFICATION OF THE WEIGH BRIDGE

1	Type of the weigh bridge	MSWIM - Bending plate based
2	Weighing Capacity	30 / 40 / 50 ton / individual Axle
3	Load cell	Strain gauge
4	Type of weighing	Individual axle based
5	Weighing speed	20 kmph
6	Axle load	40 Ton (Maximum) / axle
7	Calibration	Automatic
8	Increment	50 kg
9	Accuracy	(+/-) 0.1% FSR @ STATIC
10		(=/-) 5% UP TO 30 km
11	Power Supply	230 v +/- 10% Single phase 50 hz

WEIGH IN MOTION FEATURES

1	Simple transportation and fast set up time
2	Weigh all Vehicles from simple van to articulated trucks
3	Light weight Low Profile
4	Multiple Power sources
5	Reduced weight Transfer
6	Advanced Data Management (optional)
7	Bright bold Graphical display
8	Laptop and modem communication port (Optional)
9	Telemetry output module for Data download via mobile telephone work (optional)
10	Classification of over 100 unique vehicle type
11	Vehicle by vehicle data storage
12	RS232 Communication Port (Default)
13	TCP/IP Communication port (Optional)
14	In corporate tested high speed micro controller & very high speed monolithic AD Converter
15	Highly efficient and Highly immune RF & Infra-red Sensor for vehicle classification

Network Toll Solution

WEIGH IN MOTION STRUCTURE SPECIFICATION

1	WIM Structure Dimension	1500mm x 510 mm x 25 mm
2	Bending plate material	P 20 / EN 19 Alloy steel Material
3	Capacity	40 Ton
4	Accuracy in static	(+/-) 0.1 % verified Gross weight
5	In motion Accuracy	(+/-) 7% upto 50 kmph
6	Rated axle load	(</=) 40 Ton
7	Safe Overload	150%
8	Ultimate Over load	300%
9	Maximum Passing speed	50kmph
10	Static Accuracy	OIML CLASS 5
11	Dynamic Accuracy	(+/-) 7 %
12	Operating speed	1 to 50 kmph
13	Operating Temperature	(- 29 degree to 165 degree F)
14	Power Source	240V AC and 12V AC
15	Relative Moisture	95% MH
16	Controlling device protection class	IP 65
17	Weighing load cell protection class	IP 67

Network Toll Solution