Network Toll Solution

# UHF Reader for Toll ETC – Impinj E710 Module Model: NTS IR-05



**Key Features:**

- Impinj IndyE510/E710 (Optional) chipset offer high performance
- Aluminum casting / waterproof housing apply to all weather industrial scenarios
- Various communication / software Interfaces helps faster application system
- Different developing languages SDK meet different developer needs
- Excellent communication protocol architecture support faster data processing algorithm
- Integrated design supports better deploy /installation / engineering / wiring
- Special application projects customized interfaces / data transferring prolongable
- Seamlessly compatible with RFID middleware for rapid implementation of large projects
- Widely used in E-parking, garbage truck, feeding vehicle, access control and so on

| **Technical Specification of Sensor** | |
|---|---|
| **HARDWARE, OS AND FIRMWARE MANAGEMENT** | |
| Firmware Upgrade | Demo software / Telnet |
| API Support | Windows - .NET, C++ and Java SDK<br>Android - Java<br>Linux platform - C and Java SDK |
| **PHYSICAL CHARACTERISTICS** | |
| Weigh | Main body 1.4Kgs t |
| Dimensions | 276mm×276mm×40mm |
| Housing Material | Aluminum plate / ABS cover |
| **RFID CHARACTERISTICS** | |
| Air Protocols | ISO/IEC18000-6B,6C / EPC C1Gen2 |
| Frequency | USA: 902 MHz-928MHz (FCC part 15)<br>EU: 865-868MHz (ETSI EN 302208)<br>CN: 920-925MHz (CMIIT) |
| Chipset - | Impinj E510 (E710- Optional) |

**Network Toll Solution Pvt. Ltd.**
Corporate Office: Unit No. 1008, Tower 3, Aastha Green, Sector 4, Greater Noida West, 201306
**Website:** www.networktoll.com **Email:** sales@networktoll.com **Contact:** +919958097339

Network Toll Solution

| | |
|---|---|
| Programing Functions | Automatic reading/ White list<br>Breakpoint Resume / Match reading / Data filter Data format customizable (PLC / Modbus compatible) RF Micron / EM Temperature sensor custom Services. |
| Supportable /Optional | Russian / Japan / Korea / Malaysia / Thailand / other customizable |
| Built-in antenna | Circular 9dBi, VSWR ≤ 1.2:1 |
| Output Power | 0dBm-30dBm (±1dBm) adjustable |
| Channel bandwidth | >200KHz |
| Reading Distance | 0-15m (According to Tag & Environment) |
| Anti-collision | RSSI / multi-tag / intensive inventory supportable |
| Work Mode | Fixed/hop frequency optional |
| **CONNECTIVITY** | |
| Communications | RJ45, RS-232, RS-485, Wiegand |
| General Purpose I/O | 1 optcoupler input, 1 pair 5V output or Wiegand output (Wiegand output is shared with 5V output) |
| Power supply | DC 24V/2.5A (DC 9V ~ 30V,30W) |
| **ENVIRONMENTAL** | |
| Operating Temp. - | -30 - +70°C |
| Storage Temp. - | -40 - +85°C |
| Humidity - | 5-90% non-condensing (+25℃) |
| Sealing - | Ip66 |