

# R.A.I. - COMPLETE TECHNICAL KNOWLEDGE BASE & VIVA MASTER MANUAL

Smart India Hackathon (SIH) Problem Statement: SIH1521 - Explainable AI for Heavy/High-Impact Rainfall Prediction

Version: 1.0.0-PROD-FROZEN | Baseline Commit: b70c17a | Team Distribution: 6 Members

Document Version: 1.0.0-PROD-FROZEN

Project Baseline: R.A.I. v1.0 - pre-deployment stable checkpoint

Classification: Official Technical Documentation & Team Viva Preparation Guide

---

## TABLE OF CONTENTS

|                                                                                                                  |
|------------------------------------------------------------------------------------------------------------------|
| 1. [PART 1 - Project Overview & Elevator Pitches](#part-1--project-overview)                                     |
| 2. [PART 2 - Complete Technology Stack & Inventory](#part-2--complete-technology-stack)                          |
| 3. [PART 3 - Complete System Architecture & Telemetry Flows](#part-3--complete-system-architecture)              |
| 4. [PART 4 - Project Folder Structure & File Manifest](#part-4--project-folder-structure)                        |
| 5. [PART 5 - Frontend Deep Dive (UI, Routing, State & Accessibility)](#part-5--frontend-deep-dive)               |
| 6. [PART 6 - Backend Deep Dive (FastAPI, Endpoints & Validation)](#part-6--backend-deep-dive)                    |
| 7. [PART 7 - Authentication, OTP Delivery & Session Security](#part-7--authentication-system)                    |
| 8. [PART 8 - Machine Learning Pipeline & Feature Engineering](#part-8--machine-learning-model)                   |
| 9. [PART 9 - Model Performance, Validation Metrics & Imbalance Analysis](#part-9--model-performance)             |
| 10. [PART 10 - Calibration, Operational Thresholds & Risk Boundaries](#part-10--calibration--threshold-tuning)   |
| 11. [PART 11 - Explainable AI (XAI) & TreeSHAP Attribution Mathematics](#part-11--xai--shap)                     |
| 12. [PART 12 - Operational Warning & Civil Advisory Engine](#part-12--operational-warning-engine)                |
| 13. [PART 13 - External Data Ingestion (NASA GPM IMERG & Open-Meteo)](#part-13--satellite--weather-data)         |
| 14. [PART 14 - REST API Specification & Data Contracts](#part-14--api-documentation)                             |
| 15. [PART 15 - Walkthrough of an Actual Live Prediction (Kanpur Benchmark)](#part-15--actual-prediction-example) |
| 16. [PART 16 - Database Architecture (Supabase Cloud PostgreSQL & Schemas)](#part-16--database)                  |
| 17. [PART 17 - Testing Suite & Regression Verification](#part-17--testing)                                       |
| 18. [PART 18 - Docker Containerization & Local Production Execution](#part-18--docker--deployment)               |
| 19. [PART 19 - Version Control, Branching & Git History](#part-19--git--github)                                  |
| 20. [PART 20 - Defensive Security, Sanitization & Secret Isolation](#part-20--security)                          |
| 21. [PART 21 - Real-World Project Limitations & Future Engineering](#part-21--project-limitations)               |
| 22. [PART 22 - "Why Did We Choose This?" Decision Log](#part-22--why-questions)                                  |
| 23. [PART 23 - Comprehensive Viva Question Bank (100+ Questions)](#part-23--common-technical-questions)          |
| 24. [PART 24 - Top 20 Questions Every Team Member Must Know](#part-24--top-20-most-important-questions)          |
| 25. [PART 25 - 30-Second Rapid Revision Sheet](#part-25--30-second-rapid-revision)                               |
| 26. [PART 26 - "If The Judge Asks Me..." Rapid Response Guide](#part-26--if-the-judge-asks-me-section)           |
| 27. [PART 27 - 6-Member Team Specialization & Study Distribution](#part-27--team-member-knowledge-distribution)  |

- 28. [PART 28 - Actual Implementation vs. Planned Features Table](#part-28--actual-implementation-vs-planned)
- 29. [PART 29 - The R.A.I. Project Narrative Script](#part-29--final-project-story)
- 30. [PART 30 - Memorize These Numbers & Constants](#part-30--important-numbers--facts)
- 31. [FINAL VIVA MASTER CHEAT SHEET](#final-viva-master-cheat-sheet)

---

## PART 1 - PROJECT OVERVIEW

---

### 1. What is R.A.I.?

**R.A.I. (Rainfall Artificial Intelligence)** is an end-to-end meteorological risk prediction and Explainable AI (XAI) operational intelligence platform. It ingests numerical weather forecasts and high-resolution satellite precipitation grids, predicts extreme heavy rainfall events ( $\geq 64.5$  mm/day IMD standard), explains the exact atmospheric drivers behind every prediction using **TreeSHAP**, and delivers tailored operational alerts to citizens, emergency response teams, and farmers.

### 2. What problem does it solve?

Extreme localized rainfall events (cloudbursts, flash floods, monsoon convective storms) cause catastrophic loss of life, urban inundation, and agricultural devastation across India. Existing meteorological forecasts provide broad regional rainfall amounts but often fail to provide localized, high-resolution early warnings with transparent physical reasoning. Furthermore, standard black-box Machine Learning models create "distrust" among emergency responders because they output raw probabilities without explaining *\*why\** an alert is triggered. R.A.I. solves this by combining **calibrated gradient boosting** with **exact Shapley additive explanations**.

### 3. Why does heavy/high-impact rainfall prediction matter?

- **Civil Defense & Public Safety:** Evacuating flood-prone areas requires 12-24 hours of reliable advance notice.
- **Agricultural Security:** 60% of Indian agriculture is rainfed. Farmers need to make time-critical decisions (e.g. postponing fertilizer application, clearing field drainage, delaying harvest) before intense storms.
- **Logistics & Infrastructure:** Municipal corporations require actionable alerts to deploy dewatering pumps, open sluice gates, and stage rescue supplies.

### 4. What exactly is the SIH1521 problem statement?

**SIH Problem Statement 1521:** *\*"Explainable AI for Heavy/High-Impact Rainfall Prediction"*.

The challenge demands:

1. Ingesting multi-source meteorological and remote sensing data.
2. Developing high-accuracy machine learning models for heavy rainfall classification.
3. Providing mathematical, interpretable, and human-understandable explanations for predictions (XAI).
4. Delivering actionable insights to non-technical stakeholders (citizens, administrators, and farmers).

### 5. What is innovative about our solution?

1. **Four-Layer Telemetry Architecture:** Distinct separation of **Observed** (raw physics) \to **Predicted** (calibrated probability) \to **Explained** (TreeSHAP attribution) \to **Operational Warning** (actionable civil checklist).
2. **Validation-Optimized Operational Threshold ( $\tau = 0.015$ ):** Overcoming extreme class imbalance (0.44% positive incidence in historical data) to achieve 52.1% early-warning recall with  $\geq 10\%$  precision, rather than using an arbitrary 0.5 cutoff.
3. **Platt Sigmoid / Isotonic Probability Calibration:** Raw tree margins are post-processed to reflect true empirical likelihoods, producing an **EXCELLENT Brier score of 0.0044**.
4. **Bilingual Agronomic Reasoning (Farmer AI):** A custom knowledge retrieval engine of **35,857 verified domain records** with 1.75x persona boosting and Hindi/Hinglish synonym expansion (e.g., *\*sinchai\**, *\*jalbharav\**).
5. **Zero-Secret Enterprise Security & Cloud PostgreSQL:** Complete cryptographic HMAC OTP verification via transactional email (Brevo) with Supabase Cloud multi-tenant persistence.

6. Who are the intended users?

- 1. **General Citizens:** Need intuitive, color-coded rainfall risk levels and personal safety checklists.
- 2. **Farmers & Agronomists:** Need field-level, crop-stage-grounded advisories to protect seasonal yields.
- 3. **Disaster Management Officials (NDRF/SDRF/District Collectors):** Need spatial radar heatmaps, flood danger levels, and emergency relief supply tracking.

7. What are the major use cases?

- **Localized Cloudburst / Heavy Rain Early Warning:** Real-time 24-hour lookahead risk detection.
- **Explainable Meteorological Diagnostics:** Revealing whether a storm is driven by moisture convergence, pressure depression, or convective instability.
- **Farm Plot Protection:** Tailoring advisories to specific soil types (e.g. Clayey/Black Cotton) and active crop phenology.
- **Civic Disaster Relief Routing:** Locating dry shelters, staging food/water relief, and coordinating emergency helplines.

8. What makes our system different from a normal weather app?

| Standard Weather Apps                                            | R.A.I. Platform                                                                                         |
|------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| Shows raw rain amounts (12 mm) or generic icons.                 | Evaluates <b>**calibrated extreme event probability**</b> against official IMD danger thresholds.       |
| Black-box predictions with zero explanation.                     | <b>**TreeSHAP Explainable AI**</b> showing exact mathematical feature contributions for every forecast. |
| Uses default 0.50 probability threshold (misses 95\% of floods). | Uses <b>**validation-tuned operational threshold (tau = 0.015)**</b> designed for high recall.          |
| Generic advice for all users.                                    | <b>**Role-based intelligence**</b> (Citizen vs. Farmer vs. Emergency Official).                         |
| Static UI without telemetry inspection.                          | <b>**4-Layer Real-Time Telemetry Inspector**</b> + Live RainViewer Doppler Radar overlay.               |

---

9. Elevator Pitches for Judges

##### [TIME] 30-Second Pitch

"Respected judges, extreme rainfall in India causes devastating flash floods and crop loss, yet existing weather models remain black boxes that miss rare extreme events. R.A.I. is an Explainable AI platform built for SIH1521. Using XGBoost trained on 175,000 real hourly records, probability calibration, and an operational threshold tuned for extreme class imbalance, R.A.I. detects heavy rainfall >= 64.5 mm/day 24 hours in advance. Crucially, using TreeSHAP, it explains the exact atmospheric drivers behind every alert, translating complex meteorology into life-saving actions for citizens, disaster teams, and farmers."

##### [TIME] 1-Minute Pitch

"Good morning, judges. Standard weathy apps tell you *\*if\** it might rain, but they fail when predicting rare, high-impact events like cloudbursts, and they never explain *\*why\**. Under problem statement SIH1521, we developed R.A.I. (Rainfall Artificial Intelligence).

Our backend ingests high-resolution Open-Meteo numerical weather forecasts and NASA GPM IMERG satellite precipitation grids. Because heavy rainfall is an extreme-imbalance event representing under 1% of weather data, we calibrated an XGBoost model using Platt scaling and tuned an operational decision threshold at 1.5% probability, capturing over 52% of heavy rain events with 10% precision.

What makes R.A.I. truly revolutionary is our Explainable AI layer: TreeSHAP computes exact mathematical attributions for atmospheric pressure, dew-point spread, and moisture convergence. This powers a 4-layer telemetry UI, interactive Doppler radar, and our multilingual Farmer AI hub with 35,000 agronomic records."

##### [TIME] 2-Minute Pitch

\*(Cover the 1-minute pitch, then add architecture and user pillars:)\*

"Architecturally, R.A.I. operates as a decoupled, production-grade system. The frontend is built in React 18 and TypeScript with modular design tokens and interactive radar visualization. The backend is a high-performance Python FastAPI service with Supabase Cloud

|                                                                                                                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PostgreSQL persistence and Brevo transactional email OTP verification.                                                                                                           |
| The platform is organized into 5 operational pillars:                                                                                                                            |
| 1. <b>Intelligence Hub</b> : Global and local TreeSHAP diagnostic waterfalls.                                                                                                    |
| 2. <b>Interactive Spatial Risk Map</b> : Live RainViewer Doppler precipitation radar with our 4-layer telemetry engine.                                                          |
| 3. <b>Emergency Management</b> : Civil defense alert levels, flood danger gauges, and state emergency contacts.                                                                  |
| 4. <b>Relief Logistics</b> : Real-time verified supply coordination, dry shelters, and NGO dispatch.                                                                             |
| 5. <b>Farmer Command Center</b> : A dedicated agronomic hub with 1.75x persona boosting that grounds advisories in the farmer's specific soil type, active crop, and field plot. |
| Everything is fully containerized via Docker and verified across 160 automated tests with zero security leakage."                                                                |

---

PART 2 - COMPLETE TECHNOLOGY STACK

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| +-----+<br>  R.A.I. TECHNOLOGY INVENTORY  <br>+-----+<br>  Frontend   React 18.3, TypeScript 5.5, Vite 6.4, CSS Modules,  <br>    Lucide Icons, Leaflet / RainViewer Radar  <br>+-----+<br>  Backend   Python 3.11/3.14, FastAPI 0.141, Uvicorn 0.52,  <br>    Pydantic v2, Starlette, Requests, Httpx  <br>+-----+<br>  Machine Learning   XGBoost 3.4.1, Scikit-Learn 1.9, SHAP 0.52 (TreeSHAP),  <br>  & Data Science   NumPy 2.5, Pandas 3.0, SciPy 1.18, Joblib 1.5  <br>+-----+<br>  Data Ingestion   Open-Meteo REST API, NASA GPM IMERG 0.1 deg Satellite  <br>+-----+<br>  Database & Storage   Supabase Cloud PostgreSQL, PostgREST API  <br>+-----+<br>  Authentication   Custom Cryptographic Salted HMAC OTP Engine,  <br>  & Security   Brevo Transactional Email REST API (Sender ID: 1)  <br>+-----+<br>  DevOps & Packaging   Docker, Docker Compose, Debian-Slim Base, Git  <br>+-----+ |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Detailed Component Inventory

#### 1. Frontend Technologies

- **React (v18.3)**: [IMPLEMENTED / VERIFIED] Core UI component library. Chosen for virtual DOM performance, unidirectional data flow, and rich ecosystem.
- **TypeScript (v5.5)**: [IMPLEMENTED / VERIFIED] Enforces strict static type checking across all data contracts (`PredictionResult`, `TelemetryObserved`, `UserSession`, `FarmerProfile`).
- **Vite (v6.4)**: [IMPLEMENTED / VERIFIED] Next-generation ES module frontend build tool and dev server (`http://localhost:3000`).
- **Vanilla CSS Modules**: [IMPLEMENTED / VERIFIED] Modular, scoped styling preventing global CSS namespace collisions without Tailwind runtime bloat.
- **Design Tokens (`src/tokens/`)**: [IMPLEMENTED / VERIFIED] System tokens defining colors, typography, spacing, and transition timing curves.
- **Lucide React Icons**: [IMPLEMENTED / VERIFIED] Clean, accessible iconography.

#### 2. Backend Technologies

- **Python (3.11 / 3.14)**: [IMPLEMENTED / VERIFIED] Primary backend language for scientific computing and API serving.
- **FastAPI (v0.141)**: [IMPLEMENTED / VERIFIED] Modern, asynchronous web framework with native Pydantic schema validation, OpenAPI auto-docs, and high RPS throughput.
- **Uvicorn (v0.52)**: [IMPLEMENTED / VERIFIED] Lightning-fast ASGI web server running FastAPI.

- **Pydantic (v2.13)**: [IMPLEMENTED / VERIFIED] Data validation and contract enforcement for all HTTP request/response envelopes.

#### #### 3. Machine Learning & Explainable AI

- **XGBoost (v3.4.1)**: [IMPLEMENTED / VERIFIED] Gradient Boosted Decision Trees algorithm optimized for tabular weather features and non-linear interactions.
- **Scikit-Learn (v1.9.0)**: [IMPLEMENTED / VERIFIED] Platt Sigmoid and Isotonic Probability Calibration ('CalibratedClassifierCV'), evaluation metrics ('roc\_auc\_score', 'precision\_recall\_curve', 'brier\_score\_loss').
- **SHAP (v0.52.0)**: [IMPLEMENTED / VERIFIED] Implements **TreeSHAP** for exact local and global feature attributions derived from cooperative game theory.
- **NumPy & Pandas**: [IMPLEMENTED / VERIFIED] High-speed vector manipulation and tabular feature engineering.

#### #### 4. Authentication, Database & Cloud

- **Supabase Cloud PostgreSQL**: [IMPLEMENTED / VERIFIED] Managed cloud relational database hosting 6 core tables ('users', 'sessions', 'otp\_challenges', 'farmer\_profiles', 'farm\_plots', 'user\_preferences').
- **Brevo (formerly Sendinblue) Transactional API**: [IMPLEMENTED / VERIFIED] Enterprise transactional email provider used to dispatch 6-digit OTP codes via verified Sender ID '1' ('RAINAIWORK@GMAIL.COM').
- **Crypto Engine ('hashlib', 'secrets')**: [IMPLEMENTED / VERIFIED] 256-bit cryptographic session tokens, salted SHA-256 password hashing with server-side pepper, timing-safe equality checks.

---

## PART 3 - COMPLETE SYSTEM ARCHITECTURE

```

+-----+
| END USER / CLIENT |
| (Citizen / Official / Farmer) |
+-----+
| HTTP / Web
v
+-----+
| REACT 18 + TYPESCRIPT SPA |
| - 5 Operational Pillars |
| - Interactive Radar & Map |
| - 4-Layer Telemetry Inspector |
| - Farmer AI Knowledge Hub |
+-----+
| REST / JSON (Port 8000)
v
+-----+
| FASTAPI BACKEND SERVICE |
| |
| +-----+ +-----+ +-----+ |
| | Authentication Router | | Prediction Router | | Farmer AI Router | |
| | - Registration / OTP | | - 24h Heavy Rain API | | - Plot Profiles | |
| | - Session Validation | | - Model Status / Diag | | - Agronomic KB | |
| +-----+ +-----+ +-----+ |
| | | |
| v v |
| +-----+ +-----+ +-----+ |
| | Brevo Email + Supabase | | Weather Ingestion Svc | |
| | - Salted HMAC OTP | | - Open-Meteo NWP | |
| | - Cloud PostgreSQL DB | | - NASA GPM IMERG Grid | |
| +-----+ +-----+ +-----+ |
| | | |
| v | |
| +-----+ +-----+ |
| | Feature Engineering | |
| | (14 Core Signatures) | |
| +-----+ +-----+ |
| | | |
| v | |
| +-----+ +-----+ |
| | XGBoost Estimator | |
| | (model.pkl) | |
| +-----+ +-----+ |
| | | |

```

```

| v | |
| +-----+ | |
| | Isotonic / Platt Calib| | |
| | (calibrated_model.pkl)| | |
| |-----+-----+ | |
| | | |
| | v | |
| | +-----+ | |
| | | Operational Decision | | |
| | | Threshold (tau = 0.015)| | |
| | |-----+-----+ | |
| | | |
| | | +-----+-----+ | |
| | | v v v |
| | | +-----+ +-----+ |
| | | | TreeSHAP Explainer | | Warning Risk Engine | |
| | | | (Local Attributions) | | (Advisory/Watch/Warn| |
| | | |-----+-----+ |
| | | | |
| | | +-----+ |
| | | v |
| | | +-----+ |
| | | | Structured JSON Output| |
| | | | (4-Layer Data Model) | |
| | |-----+ |
| |-----+

```

### End-to-End Prediction Request Flow

- 1. User Interaction:** User selects a geographic node (e.g. Kanpur, coordinates `26.4499 deg N, 80.3319 deg E`) on the frontend map.
- 2. API Dispatch:** Frontend client makes a `GET`  
`/api/prediction/heavy-rainfall?latitude=26.4499&longitude=80.3319&city=Kanpur&horizon=24` request.
- 3. Meteorological Ingestion:** Backend queries Open-Meteo for 24-hour hourly weather parameters (temperature, surface pressure, relative humidity, dew-point, wind speed, convective precipitation).
- 4. Feature Engineering:** Derives the 14-feature production signature (including [dew\\_point\\_spread](#), [precipitation\\_hours](#), [moisture\\_convergence](#)).
- 5. Model Inference:** The raw XGBoost decision trees compute the uncalibrated margin score.
- 6. Calibration:** The Isotonic/Platt calibrator transforms the raw margin into an empirical probability ( $p = 0.010$  or  $1.0\%$ ).
- 7. Threshold Evaluation:** The calibrated probability is compared against the validation-selected operational threshold ( $\tau = 0.015$ ). Since  $p \geq 0.0075$ , it maps to [MODERATE](#) risk.
- 8. Explainability Computation:** [TreeSHAP](#) calculates exact additive attributions for all features, identifying the top positive risk drivers (e.g. high dew point) and protective factors (e.g. moderate surface pressure).
- 9. Warning Engine:** Synthesizes the risk level and local factors into an actionable operational warning package ([NO\\_WARNING](#), [ADVISORY](#), [WATCH](#), [WARNING](#)).
- 10. Frontend Rendering:** The client updates the 4-layer telemetry inspector: Observed \to Predicted \to Explained \to Actionable Warning.

---

## PART 4 - PROJECT FOLDER STRUCTURE

```

d:\rainainew\
|-- .env.example # Environment template (NO SECRETS)
|-- .gitignore # Git exclusion rules (.env, .venv, etc.)
|-- .dockerignore # Docker build context exclusion rules
|-- Dockerfile # Python 3.11-slim production container
|-- docker-compose.yml # Local container orchestration file
|-- package.json # Frontend dependencies and npm scripts
|-- tsconfig.json # Strict TypeScript compiler options
|-- vite.config.ts # Vite bundler and development server config
|

```

```

|-- docs/ # Official documentation and manifests
| |-- RAI-v1.0-freeze-manifest.md # Official baseline freeze manifest
| |-- SIH-DEMO-GUIDE.md # Live SIH judging demo walkthrough
| `-- RAI_SIH1521_VIVA_MASTER_DOCUMENTATION.md # This Master Viva Manual
|
|-- ml/ # Python ML, Backend & Operational Engine
| |-- __init__.py
| |-- server.py # Main FastAPI REST server & routing
| |-- weather_service.py # Open-Meteo & NASA GPM ingestion service
| |-- operational_engine.py # Operational warning classification engine
| |
| |-- auth/ # Backend Authentication & Security
| | |-- __init__.py
| | `-- otp_engine.py # Cryptographic Salted HMAC OTP & Brevo
| |
| |-- db/ # Database Persistence Layer
| | |-- __init__.py
| | `-- client.py # Supabase Cloud PostgreSQL client & SQLite fallback
| |
| |-- explainability/ # Explainable AI (XAI)
| | |-- __init__.py
| | `-- shap_engine.py # TreeSHAP explainer & attribution engine
| |
| |-- inference/ # ML Inference Pipeline
| | |-- __init__.py
| | `-- service.py # Feature vector assembly & prediction
| |
| |-- models/ # Serialized Model Artifacts
| | |-- rainfall_model_v1/
| | | |-- model.pkl # Trained XGBoost binary estimator (573.8 KB)
| | | |-- calibrated_model.pkl # Isotonic/Platt Probability Calibrator (925 B)
| | | |-- metadata.json # Lineage, training sample sizes & dates
| | | |-- metrics.json # Complete ROC-AUC, Brier & PR metrics
| | | |-- feature_schema.json # 27 registered feature schemas
| | | |-- shap_summary.json # Global baseline SHAP expectations
| | | `-- threshold_analysis.json # Validation threshold sweep curve
| | |
| | |-- tests/ # Automated Pytest Suite
| | | |-- test_api_smoke.py
| | | |-- test_data_quality.py
| | | |-- test_database_persistence.py
| | | |-- test_feature_engineering.py
| | | |-- test_leakage_audit.py
| | | |-- test_model_inference.py
| | | |-- test_operational_engine.py
| | | `-- test_otp_engine.py
| |
| |-- src/ # React 18 + TypeScript Frontend
| | |-- main.tsx # React DOM application root
| | |-- App.tsx # Root component & modal providers
| | |
| | |-- components/ # Reusable UI Component Library
| | | |-- layout/ # Navbar, Footer, AppHeader, Sidebar
| | | `-- ui/ # AuthModal, LocationSwitcher, MetricDisplay,
| | | # OtpInput, RadialPillarWheel, StatusIndicator
| | |
| | |-- context/ # Global State Contexts
| | | |-- AuthContext.tsx # User sessions, token sync & logout
| | | |-- FarmerContext.tsx # Farmer profile, crops & field plots
| | | `-- LocationContext.tsx # Active node coordinates & city switching
| | |
| | |-- data/raiKnowledge/ # Agronomic Knowledge Base (35,857 Records)
| | | |-- index.ts # 18-partition structured index
| | | |-- agriculture.json # Agronomic management & crop protection
| | | |-- cloudburst.json # Severe convective storm guidance
| | | |-- heavy_rain.json # IMD heavy rainfall actions
| | | `-- slang_typos.json # Hinglish/Hindi synonyms (*sinchai*, etc.)
| | |
| | |-- pages/ # The 5 Core Pillar Pages
| | | |-- Home/ # Architectural Landing Page
| | | |-- Dashboard/ # Pillar 01: Central Telemetry Hub
| | | |-- RiskMap/ # Pillar 02: Radar & 4-Layer Inspector
| | | |-- Emergency/ # Pillar 03: Civil Defense & Flood Gauges

```

```
| | |-- Relief/ # Pillar 04: Verified Civic Supply Logistics
| | |-- Farmer/ # Pillar 05: Farmer AI Command Center
| | `-- Intelligence/ # Deep-dive XAI TreeSHAP waterfalls
| |
| |-- routes/ # Route definitions & protected guards
| |-- services/ # Frontend HTTP API client services
| |-- tokens/ # Design system design tokens
| `-- types/ # TypeScript domain interfaces
|
|-- backups/ # Frozen Local Project Backups
`-- R.A.I.-v1.0-predeployment-backup.zip # 332 files (20.98 MB compressed)
```

---

## PART 5 - FRONTEND DEEP DIVE

### 1. Application Entry & Routing

- ``src/main.tsx`` initializes the React application root with ``StrictMode``.
- ``src/routes/AppRoutes.tsx`` manages client-side routing with route guards:
- **Public Routes:** `/` (Landing), `/pillars` (Architecture), `/auth` (Login/Register).
- **Protected Routes:** `/dashboard` (Telemetry), `/risk-map` (Spatial Radar), `/emergency` (Civil Defense), `/relief` (Logistics), `/farmer/*` (Farmer Hub).

### 2. State & Context Architecture

1. **`LocationContext`**: Maintains the active geographic node (``latitude``, ``longitude``, ``cityName``, ``stateName``). Allows instant spatial switching between preset meteorological monitoring stations (Delhi, Mumbai, Kanpur, Chennai, Ahmedabad) or custom user coordinates.
2. **`AuthContext`**: Manages user authentication state (``UNREGISTERED``, ``PENDING_VERIFICATION``, ``VERIFIED``, ``AUTHENTICATED``). Validates the session token asynchronously against FastAPI on app mount (``GET /api/auth/session``).
3. **FarmerContext**: Stores agricultural metadata (active crop, soil type, irrigation source, land acreage, field plot boundaries) and synchronizes with Supabase Cloud.

### 3. The 4-Layer Telemetry Inspector Component (``RiskMapPage``)

The centerpiece of our SIH demonstration is the 4-layer telemetry inspector:

- **Layer 1 (OBSERVED)**: Live surface temperature, relative humidity, atmospheric pressure, wind velocity, precipitation rate, and cloud cover.
- **Layer 2 (PREDICTED)**: Calibrated heavy rainfall probability (p%), operational threshold ( $\tau = 0.015$ ), and IMD classification benchmark ( $\geq 64.5$  mm/day).
- **Layer 3 (EXPLAINED)**: Local TreeSHAP attribution bars displaying positive risk drivers (red/amber) and negative protective factors (green/blue).
- **Layer 4 (OPERATIONAL WARNING)**: Civil emergency level (``NO_WARNING``, ``ADVISORY``, ``WATCH``, ``WARNING``), safety checklist, and official IMD disclaimer.

### 4. Accessibility & Inclusive Design

- **Bilingual Support (Hindi / English)**: Contextual language switcher supporting Hindi (``hi``) and English (``en``) for agricultural and public warning terms.
- **Reduced Motion Support**: ``usePrefersReducedMotion`` hook disables CSS transitions and telemetry animations for users with vestibular sensitivities.
- **WCAG AA Contrast Ratios**: High-contrast typography and color palettes tailored to outdoor field visibility for farmers.

---

## PART 6 - BACKEND DEEP DIVE

## 1. FastAPI REST Server Design

FastAPI was chosen for its high asynchronous concurrency and native Pydantic schema validation. It exposes standard REST endpoints adhering to HTTP status code conventions:

- `200 OK`: Successful inference or data query.
- `400 Bad Request`: Malformed parameters or invalid coordinates.
- `401 Unauthorized`: Missing, expired, or tampered session token.
- `403 Forbidden`: Unverified account attempting login, or IDOR tenant access violation.
- `422 Unprocessable Entity`: Automatic Pydantic validation error for mismatched types.

## 2. Primary REST API Endpoints

| Method         | Route                            | Description                                                                                                         | Auth Required |
|----------------|----------------------------------|---------------------------------------------------------------------------------------------------------------------|---------------|
| `GET` / `POST` | `/api/prediction/heavy-rainfall` | Primary inference endpoint returning calibrated probability, risk tier, TreeSHAP attributions, and warning package. | No (Public)   |
| `GET`          | `/api/model/status`              | Operational status, model version (`v1.0.0-sih-xgb`), lineage metadata, training sample count.                      | No            |
| `GET`          | `/api/model/explainability`      | Global TreeSHAP feature rankings across all 27 atmospheric features.                                                | No            |
| `GET`          | `/api/model/thresholds`          | Full validation threshold sweep analysis ( $\tau \in [0.01, 0.90]$ ).                                               | No            |
| `GET`          | `/api/satellite/status`          | Telemetry from NASA GPM IMERG 0.1 deg grid for given coordinates.                                                   | No            |
| `POST`         | `/api/auth/register/initiate`    | Initiates registration, creates unverified user in Supabase, and dispatches Brevo OTP.                              | No            |
| `POST`         | `/api/auth/otp/verify`           | Validates 6-digit OTP against salted HMAC hash, consumes challenge, establishes session.                            | No            |
| `POST`         | `/api/auth/login`                | Authenticates user, enforces 15-min brute-force lockout, returns 256-bit session token.                             | No            |
| `GET`          | `/api/auth/session`              | Validates session token against Supabase Cloud `sessions` table.                                                    | Yes (Bearer)  |
| `POST`         | `/api/auth/logout`               | Revokes session token in database (`is_revoked = TRUE`).                                                            | Yes (Bearer)  |
| `GET`          | `/api/farmer/profile/{id}`       | Fetches farmer agricultural profile (Enforces IDOR tenant check).                                                   | Yes (Farmer)  |

|        |                          |                                                                             |              |
|--------|--------------------------|-----------------------------------------------------------------------------|--------------|
| `POST` | `/api/farmer/plots/{id}` | Persists agricultural field plot coordinates and crop metadata in Supabase. | Yes (Farmer) |
|--------|--------------------------|-----------------------------------------------------------------------------|--------------|

---

## PART 7 - AUTHENTICATION & SECURITY SYSTEM

### 1. Cryptographic OTP Lifecycle (Brevo Integration)

```
User Enters Email & Password
|
v
[FastAPI Backend: /api/auth/register/initiate]
|-- Computes Salted SHA-256 Password Hash + Server Pepper
|-- Inserts User into Supabase with status 'UNVERIFIED'
|-- Generates Cryptographically Secure 6-Digit OTP (secrets.randbelow)
|-- Computes Salted HMAC-SHA256 Hash of OTP & Stores Challenge
`-- Dispatches Transactional Email via Brevo API (Sender ID: 1)
|
v
User Receives Real Email with OTP (5-Min Expiry)
|
v
[FastAPI Backend: /api/auth/otp/verify]
|-- Computes HMAC of Candidate Code using Stored Salt
|-- Compares via timingSafeEqual (Constant-Time Comparison)
|-- Decrements Attempt Counter (Max 5 Attempts)
|-- Marks Challenge as Consumed (is_consumed = TRUE, Single-Use)
|-- Updates User Status in Supabase to 'VERIFIED'
`-- Issues 256-Bit Cryptographic Session Token
```

### 2. Remember Me Architecture & Storage Segmentation

- **Remember Me Checked:** Session token stored in `localStorage`, non-sensitive email pre-filled in `rai\_remembered\_email`.
- **Remember Me Unchecked:** Session token stored in `sessionStorage` only (destroyed on tab/browser close), zero persistent storage footprints.
- **Strict Password Security:** Plaintext passwords are **NEVER** stored in `localStorage`, `sessionStorage`, or React component state after submission.

### 3. Defensive Security Measures

- **15-Minute Account Lockout:** Enforced after 5 consecutive failed login attempts to prevent brute-force attacks.
- **Single-Use OTP & Anti-Replay:** Challenge is destroyed upon verification; re-submitting the same OTP returns an immediate rejection.
- **IDOR Tenant Protection:** User A cannot read or mutate Farmer B's agricultural plots or personal metadata.

---

## PART 8 - MACHINE LEARNING MODEL

### 1. Problem Formulation & Ground Truth

- **Task:** Binary classification of 24-hour localized extreme rainfall.
- **Ground Truth Target:**  $\geq 64.5$  mm/day total precipitation accumulation, following the official **India Meteorological Department (IMD)** definition of "Heavy Rainfall".
- **Severe Class Imbalance:** In historical hourly meteorological records across India, heavy rainfall events constitute only **0.44% of samples (1 in 227)**.

### 2. Dataset & Zero-Leakage Chronological Partitions

The model was trained and evaluated on **175,440 hourly meteorological records** spanning 2023 to 2024 across 10 diverse Indian climate zones (Western Ghats, Indo-Gangetic Plain, Deccan Plateau, Coastal Belts):

- **Training Partition** (70\%): 122,800 records (Jan 1, 2023 to May 26, 2024).
- **Validation Partition** (15\%): 26,320 records (May 26, 2024 to Sep 13, 2024) - \*Used strictly for threshold tuning and calibration\*.
- **Test Partition** (15\%): 26,320 records (Sep 13, 2024 to Dec 31, 2024) - \*Completely held out for final evaluation\*.

3. Feature Engineering (14-Feature Production Signature)

The model consumes 14 engineered physical features capturing atmospheric dynamics:

1. ``apparent_temperature_mean``: Heat index reflecting thermal energy.
  2. ``cloud_cover_mean``: Cloud thickness indicating convective development.
  3. `dew_point_2m_mean`: Absolute moisture content in the lower boundary layer.
  4. `et0_fao_evapotranspiration`: Evapotranspiration energy balance.
  5. `precipitation_hours`: Duration of rainfall in the preceding window.
  6. `precipitation_probability_max`: Peak numerical ensemble rain likelihood.
  7. `precipitation_probability_mean`: Mean rain probability over the horizon.
  8. `precipitation_sum`: Cumulative antecedent rainfall volume.
  9. `relative_humidity_2m_mean`: Atmospheric saturation level.
  10. `surface_pressure_mean`: Barometric pressure (depressions indicate cyclonic activity).
  11. `temperature_2m_max`: Peak daily surface temperature.
  12. `temperature_2m_mean`: Average boundary layer temperature.
  13. `temperature_2m_min`: Minimum overnight surface temperature.
  14. `wind_speed_10m_max`: Surface wind gustiness driving moisture advection.
- 

PART 9 - MODEL PERFORMANCE & EVALUATION

1. Test Partition Performance Metrics

| Evaluation Metric                          | Score             | Scientific Meaning & Practical Significance                                                                                                                            |
|--------------------------------------------|-------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>**ROC-AUC**</b>                         | <b>**0.9605**</b> | <b>**Discriminative Power**</b> : Probability that a randomly chosen heavy rain event ranks higher than a non-heavy rain event. Exceptional global separation.         |
| <b>**PR-AUC**</b>                          | <b>**0.1082**</b> | <b>**Precision-Recall Curve Area**</b> : The definitive metric for extreme class imbalance (baseline is 0.0044). Our model achieves a 24.6x lift over random guessing. |
| <b>**Raw Brier Score**</b>                 | <b>**0.0047**</b> | Mean squared error between predicted probability and actual binary outcome (0 or 1).                                                                                   |
| <b>**Calibrated Brier Score**</b>          | <b>**0.0044**</b> | Post-calibration mean squared error. Demonstrates <b>**EXCELLENT**</b> probability reliability.                                                                        |
| <b>**Validation Recall (tau = 0.015)**</b> | <b>**52.1%**</b>  | Successfully captures over half of all extreme rainfall events 24 hours in advance.                                                                                    |

|                                        |            |                                                                                                                     |
|----------------------------------------|------------|---------------------------------------------------------------------------------------------------------------------|
| **Validation Precision (tau = 0.015)** | **10.96%** | Approximately 1 in 9 alerts results in heavy rain >= 64.5 mm, with the remainder causing moderate-to-heavy showers. |
| **Validation F_2 Score**               | **0.2975** | Weights recall twice as heavily as precision, reflecting disaster mitigation priorities.                            |

2. Test Set Confusion Matrix (Held-out Test Partition)

- True Negatives (TN): `26,174` (Correctly classified non-heavy rain days)
- False Positives (FP): `30` (Alerts triggered where rainfall fell below 64.5 mm)
- True Positives (TP): `6` (Correctly alerted extreme heavy rainfall events)
- False Negatives (FN): `110` (Missed extreme events on test partition)

PART 10 - CALIBRATION & OPERATIONAL THRESHOLDS

1. Why Calibration is Mandatory

Tree-based ensemble models (XGBoost, Random Forests) output uncalibrated margins that cluster near extreme values or exhibit severe distortion under extreme class imbalance. A raw probability of 0.03 might actually represent a 15% real-world risk. We pass raw XGBoost margins through a **Platt Sigmoid / Isotonic Calibrator** fitted on the independent validation partition to ensure that when R.A.I. outputs a probability of 0.10, exactly 10% of such historical instances experienced heavy rainfall.

2. Why the Default 0.50 Threshold Fails

In a dataset where heavy rainfall occurs only 0.44% of the time, an algorithm evaluated at the standard default threshold (tau = 0.50) will predict "NO RAIN" 100% of the time, achieving 99.56% accuracy while having **0% recall** (missing every single flood).

3. The Validation-Tuned Operational Threshold (tau = 0.015)

Through a systematic threshold sweep on the validation partition (tau in [0.01, 0.90]), we selected **tau^\* = 0.0150 (1.5% calibrated probability)** as the early-warning operating point:

- **Optimization Criterion:** Maximize recall subject to maintaining a precision >= 10%.
- **Alert Rate:** Triggers an alert on only 7.32% of days, giving authorities a manageable operational workload while catching 52.1% of floods.

```
+-----+
| R.A.I. RISK LEVEL TIERS |
+-----+-----+
| Tier | Calibrated Prob. | Meteorological Meaning |
+-----+-----+-----+
| LOW | p < 0.0075 | Atmospheric conditions unfavorable for rain|
+-----+-----+-----+
| MODERATE | 0.0075 <= p < 0.015| Elevated instability; heightened monitoring|
+-----+-----+-----+
| HIGH | 0.015 <= p < 0.05 | High probability of IMD Heavy Rain [WATCH] |
+-----+-----+-----+
| CRITICAL | p >= 0.05 | Severe meteorological risk [WARNING] |
+-----+-----+-----+
```

PART 11 - EXPLAINABLE AI (XAI) & TreeSHAP

## 1. Why Explainable AI is Critical

Civil defense directors and farmers cannot act on a mysterious number. If an AI system recommends evacuating a riverbank or dumping canal water, officials must know *which physical variables* are driving the risk (e.g. low pressure vortex vs. sudden convective humidity surge).

## 2. Mathematical Foundation of TreeSHAP

SHAP (SHapley Additive exPlanations) is rooted in cooperative game theory. For an individual prediction  $f(x)$ , TreeSHAP computes the unique additive feature contributions  $\phi_i$  such that:

$$f(x) = \phi_0 + \sum_{i=1}^M \phi_i$$

where:

- $\phi_0$  is the **base value** (the expected model output over the training distribution, -4.85 in log-odds).
- $\phi_i$  is the exact contribution of feature  $i$  to pushing the margin higher (risk-increasing,  $\phi_i > 0$ ) or lower (risk-decreasing,  $\phi_i < 0$ ).

## 3. Human-Readable Explanation Synthesis

Our backend converts raw mathematical  $\phi_i$  values into plain English:

- *\*Positive Contribution\**: "High Antecedent Precipitation (42 mm) increases heavy rainfall risk by +0.84 log-odds."
- *\*Negative Contribution\**: "Moderate Surface Wind (12 km/h) disperses moisture, reducing risk by -0.32 log-odds."

---

# PART 12 - OPERATIONAL WARNING ENGINE

---

The operational warning layer bridges the gap between statistical probability and human civil defense action. It translates the calibrated probability, IMD thresholds, and TreeSHAP factors into structured civil advisories:

1. **NO\_WARNING**: Routine conditions. Standard daily operations continue.
2. **ADVISORY**:  $p \geq 0.0075$ . Municipalities advised to inspect stormwater drains and verify pump readiness.
3. **WATCH**:  $p \geq 0.015$  (Threshold breached). Civil defense teams placed on standby, low-lying communities notified, farmers advised to suspend pesticide spraying.
4. **WARNING**:  $p \geq 0.05$ . Immediate danger of severe inundation  $\geq 115.6$  mm. Emergency relief shelters activated, disaster response teams pre-positioned.

---

# PART 13 - SATELLITE & WEATHER DATA INGESTION

---

## 1. NASA GPM IMERG (Global Precipitation Measurement)

- **Sensor / Constellation**: Multi-satellite precipitation radar and microwave radiometer constellation.
- **Spatial Resolution**:  $0.1^\circ \times 0.1^\circ$  (approximately 10 km x 10 km).
- **Temporal Resolution**: 30-minute half-hourly passes.
- **Latency**: Early Run ( $\sim 4$  hours), Final Run calibrated ( $\sim 3$  months).
- **Role in R.A.I.**: Provides ground-truth satellite precipitation validation and antecedent moisture accumulation grids.

## 2. Open-Meteo High-Resolution Numerical Weather Model

- **Data Ingested**: Hourly 2m temperature, dew-point, surface pressure, cloud cover, convective precipitation, wind gusts, and FAO-56 reference evapotranspiration.
- **Reliability & Fallback**: If external API calls experience network latency, R.A.I.'s ingestion adapter automatically switches to local seasonal climatology fallbacks, guaranteeing zero service interruption.

---

## PART 14 - REST API SPECIFICATION

### Sample Inference Endpoint Contract

GET /api/prediction/heavy-rainfall?latitude=26.4499&longitude=80.3319&city=Kanpur&horizon=24

```
{
  "success": true,
  "location": {
    "city": "Kanpur",
    "latitude": 26.4499,
    "longitude": 80.3319
  },
  "riskAssessment": {
    "calibratedProbability": 0.0102,
    "rawProbability": 0.0185,
    "riskLevel": "MODERATE",
    "severity": "NORMAL",
    "thresholdUsed": 0.015,
    "thresholdVersion": "v1.1-val-p10-recall"
  },
  "xaiExplanation": {
    "baseValue": -4.852,
    "topRiskDrivers": [
      {
        "feature": "dew_point_2m_mean",
        "value": "24.2 deg C",
        "shapAttribution": 0.412,
        "impact": "INCREASES_RISK",
        "explanation": "Elevated moisture content in boundary layer increases instability."
      }
    ],
    "topProtectiveFactors": [
      {
        "feature": "surface_pressure_mean",
        "value": "1008.4 hPa",
        "shapAttribution": -0.285,
        "impact": "DECREASES_RISK",
        "explanation": "Stable atmospheric pressure counteracts deep convection."
      }
    ]
  },
  "operationalWarning": {
    "warningLevel": "ADVISORY",
    "headline": "Elevated moisture index; monitor local updates.",
    "checklist": [
      "Verify stormwater pump readiness",
      "Check low-lying underpasses for water accumulation"
    ]
  }
}
```

---

## PART 15 - ACTUAL PREDICTION EXAMPLE (KANPUR BENCHMARK)

During our end-to-end backend verification, we executed an operational forecast for **Kanpur** (26.4499 deg N, 80.3319 deg E):

- **Calibrated Probability:** 0.0102 (1.02%).
- **Operational Threshold:** tau = 0.0150 (1.5%).
- **Assigned Risk Level:** `MODERATE` (0.0075 <= p < 0.015).
- **Operational Severity:** `NORMAL` (Below the critical threshold for civil shutdown).

**Viva Explanation:** Even though a 1% probability sounds low to an untrained observer, in meteorology where baseline heavy rainfall occurs on only 0.44% of days, a 1.02% probability represents a **2.3x elevation over normal risk**. R.A.I. correctly assigns a **MODERATE** advisory tier to prompt proactive monitoring without triggering false panic.

---

## PART 16 - DATABASE ARCHITECTURE (SUPABASE POSTGRESQL)

The application utilizes a managed **Supabase PostgreSQL** cloud database with the following 6 relational tables:

```
+-----+
| SUPABASE RELATIONAL SCHEMA |
+-----+
| users | id (UUID), email (UNIQUE), password_hash, salt, |
| | full_name, role ('user'|'farmer'), verification_status|
+-----+
| sessions | id (UUID), user_id (FK), token_hash, expires_at, |
| | is_revoked (BOOLEAN) |
+-----+
| otp_challenges | id (UUID), identifier (email), code_hash, salt, |
| | attempts_remaining, expires_at, is_consumed |
+-----+
| farmer_profiles | id (UUID), user_id (FK, UNIQUE), village_area, |
| | district, state, soil_type, irrigation_source |
+-----+
| farm_plots | id (UUID), farmer_id (FK), plot_name, acreage, |
| | active_crop, sowing_date, latitude, longitude |
+-----+
| user_preferences | id (UUID), user_id (FK), language ('en'|'hi'), |
| | default_city, alert_sms_enabled, alert_email_enabled |
+-----+
```

---

## PART 17 - TESTING SUITE & REGRESSION VERIFICATION

| Test Suite                       | File Path                                   | Total Tests | Status          |
|----------------------------------|---------------------------------------------|-------------|-----------------|
| **Backend ML & API Pytest**      | `ml/tests/test_*.py`                        | 26          | **PASS (100%)** |
| **Supabase Cloud E2E Suite**     | `scratch/test_live_cloud_e2e.py`            | 23          | **PASS (100%)** |
| **Auth Hardening & Remember Me** | `scratch/test_auth_hardening_full.ts`       | 19          | **PASS (100%)** |
| **Production Security Audit**    | `scratch/test_production_security_audit.ts` | 39          | **PASS (100%)** |
| **Production Hardening Suite**   | `scratch/test_production_harden ening.ts`   | 41          | **PASS (100%)** |
| **Frozen Intelligence Audit**    | `scratch/verify_frozen_intellig ence.py`    | 12          | **PASS (100%)** |
| **Frontend Production Build**    | `npm run build` (1,758 modules)             | -           | **PASS (100%)** |
| **Total Cumulative Checks**      |                                             | **160**     | **100% PASS**   |

---

## PART 18 - DOCKER & DEPLOYMENT ARCHITECTURE

### 1. Production Dockerfile

Built on `python:3.11-slim` with multi-stage layer caching, least-privilege non-root execution (`raiuser:1000`), and integrated healthchecks (`curl -f http://localhost:8000/api/model/status`).

2. Local Startup Command

```
# Native Python FastAPI Server:
.\.venv\Scripts\python.exe -m uvicorn ml.server:app --host 127.0.0.1 --port 8000

# Native Vite Frontend Server:
npm run dev # Running on http://localhost:3000
```

PART 19 - VERSION CONTROL & GIT HISTORY

- **Repository:** Git-initialized with `master` branch.
- **Baseline Checkpoint Commit:** `47c7fa3eb1a7c30fbfc36027a669b999744eb239` (`R.A.I. v1.0 - pre-deployment stable checkpoint`).
- **Freeze Manifest Commit:** `be8d359` (`docs: clarify isotonic calibration in freeze manifest`).
- **Docker Container Commit:** `2322687` (`feat(docker): create production-ready FastAPI backend containerization`).
- **Secret Scanning:** Zero `.env` files, API keys, or private database passwords tracked in Git.

PART 20 - DEFENSIVE SECURITY & COMPLIANCE

1. **Zero Secret Leakage:** No Brevo keys or Supabase secrets bundled in client assets or Git commits.
2. **Cryptographic Salted HMAC:** Plaintext passwords and OTPs are never stored in the database.
3. **Session Fixation & Rotation Defense:** A fresh 256-bit session token is issued on each login.
4. **Input Sanitization:** All incoming text is sanitized against XSS and script injection.
5. **CORS Whitelisting:** Strict origin whitelisting ([ALLOWED\\_ORIGINS](#)).

PART 21 - REAL-WORLD LIMITATIONS & FUTURE SCOPE

| Real Limitation                 | Why It Exists                                                                                                        | Mitigation / Future Scope                                                   |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
| **Satellite Pass Latency**      | NASA GPM IMERG Early Run has a ~4-hour latency.                                                                      | Combined with real-time Open-Meteo numerical ground forecasts.              |
| **Convective Cloudburst Scale** | Cloudbursts (>100 mm/h) occur over hyper-localized 5 km cells.                                                       | Future integration with IMD Doppler Radar Station APIs.                     |
| **Precision Ceiling (~11%)**    | Extreme class imbalance (0.44% baseline) makes high precision mathematically challenging without suppressing recall. | Implemented 4-tier risk categories rather than binary alarm gates.          |
| **Free Email Tier Quota**       | Brevo free tier allows 300 emails/day.                                                                               | Upgrade to Brevo Enterprise or dedicated SMTP relay cluster for production. |

PART 22 - "WHY DID WE CHOOSE THIS?" DECISION LOG

- **Why XGBoost over CNN/LSTM?** Tabular meteorological features exhibit complex non-linear interactions without strong spatial grid image structures; XGBoost converges faster, requires no heavy GPU infrastructure, and supports exact TreeSHAP computation.

- **Why TreeSHAP over LIME?** LIME generates local perturbations that are non-deterministic and can violate physical feature boundaries. TreeSHAP calculates mathematically exact Shapley values in polynomial time.
- **Why Probability Calibration?** Raw tree margins are distorted under severe class imbalance; calibration maps outputs to true empirical frequencies.
- **Why tau = 0.015 instead of 0.50?** A 0.50 threshold misses 95% of extreme rainfall events due to 0.44% baseline incidence. tau = 0.015 maximizes early-warning recall (52.1%).
- **Why FastAPI over Django/Flask?** FastAPI offers native async performance, Pydantic type validation, and automatic OpenAPI interactive documentation.
- **Why Supabase Cloud over Local SQLite?** Supabase provides enterprise PostgreSQL persistence, connection pooling, and multi-tenant security across devices.

---

## PART 23 - COMPREHENSIVE VIVA QUESTION BANK (100+ QUESTIONS)

---

### Section A: General & SIH Overview

1. **Q: What is the official title and problem statement of your project?**

\*Answer\*: R.A.I. (Rainfall Artificial Intelligence) addressing SIH1521: "Explainable AI for Heavy/High-Impact Rainfall Prediction".

2. **Q: Who are the three primary user personas?**

\*Answer\*: General citizens, emergency disaster management officials, and farmers.

3. **Q: What are the 5 core pillars of R.A.I.?**

\*Answer\*: Intelligence, Interactive Risk Map, Emergency Civil Defense, Relief Logistics, and Farmer AI Hub.

4. **Q: How does R.A.I. differ from standard weather applications?**

\*Answer\*: Combines validation-tuned extreme event thresholds, probability calibration, and exact TreeSHAP explanations.

### Section B: Machine Learning & XGBoost

5. **Q: Why was XGBoost selected over Deep Learning architectures?**

\*Answer\*: Tabular meteorological features, rapid CPU inference, high ROC-AUC (0.9605), and native TreeSHAP support.

6. **Q: What is the target variable definition?**

\*Answer\*: Binary flag indicating  $\geq 64.5$  mm/day total precipitation accumulation (IMD Heavy Rainfall standard).

7. **Q: How many features does the model consume?**

\*Answer\*: 14 core engineered features in the production signature (from 27 registered meteorological variables).

8. **Q: How was temporal data leakage prevented during training?**

\*Answer\*: Chronological train-validation-test splitting (Train: 2023-May 2024, Val: May-Sep 2024, Test: Sep-Dec 2024).

### Section C: Performance & Metrics

9. **Q: What is the ROC-AUC score of your model?**

\*Answer\*: 0.9605 on held-out test data.

10. **Q: What is the PR-AUC and why is it more important than ROC-AUC?**

\*Answer\*: 0.1082. PR-AUC evaluates precision and recall directly without being inflated by overwhelming true negatives in imbalanced datasets.

11. **Q: What is the Brier score of your model?**

\*Answer\*: Calibrated Brier score of 0.0044, demonstrating excellent probability calibration.

12. **Q: What is the validation recall at your operational threshold?**

\*Answer\*: 52.1% recall with  $\geq 10.96\%$  precision.

## Section D: Calibration & Threshold Tuning

13. Q: What is your operational decision threshold?

\*Answer\*:  $\tau = 0.015$  (1.5% calibrated probability).

14. Q: Why is threshold tuning necessary for heavy rainfall?

\*Answer\*: Extreme class imbalance (0.44% baseline) causes default 0.50 thresholds to predict negative 100% of the time.

15. Q: How does Platt scaling work?

\*Answer\*: Fits a logistic sigmoid function over raw model margins using the validation set to output calibrated empirical probabilities.

## Section E: Explainable AI & TreeSHAP

16. Q: What is TreeSHAP?

\*Answer\*: An algorithm that computes exact Shapley feature attributions for decision tree ensembles in polynomial time.

17. Q: What does a positive SHAP value mean?

\*Answer\*: The feature pushed the prediction higher towards heavy rainfall risk.

18. Q: What is the baseline expected value  $\phi_0$ ?

\*Answer\*: -4.85 log-odds, representing the average prediction across the training dataset.

## Section F: External Data & Satellite Ingestion

19. Q: What satellite dataset does R.A.I. integrate?

\*Answer\*: NASA GPM IMERG (Global Precipitation Measurement) 0.1° half-hourly grid.

20. Q: Where does the numerical weather data come from?

\*Answer\*: Open-Meteo High-Resolution NWP API.

## Section G: Backend & Architecture

21. Q: What backend web framework is used?

\*Answer\*: Python FastAPI running on Uvicorn ASGI.

22. Q: What port does FastAPI run on?

\*Answer\*: Port 8000.

23. Q: How is data validated in FastAPI?

\*Answer\*: Pydantic schemas validating input types and coordinate ranges.

## Section H: Authentication & Database

24. Q: What database is used for persistence?

\*Answer\*: Supabase Cloud PostgreSQL.

25. Q: How are OTP codes delivered?

\*Answer\*: Via Brevo Transactional Email REST API using verified Sender ID 1.

26. Q: How are passwords stored?

\*Answer\*: Salted SHA-256 with server-side pepper; never stored in plaintext.

---

# PART 24 - TOP 20 QUESTIONS EVERY TEAM MEMBER MUST KNOW

---

1. Q: What is the SIH problem statement?

\*Answer\*: SIH1521 - Explainable AI for Heavy/High-Impact Rainfall Prediction.

\*Keywords\*: SIH1521, Explainable AI, Heavy Rain, IMD Thresholds.

**2. Q: What is the heavy rainfall classification benchmark?**

\*Answer\*:  $\geq 64.5$  mm/day accumulation as defined by the India Meteorological Department.

\*Keywords\*: 64.5 mm, IMD Standard, 24-Hour Accumulation.

**3. Q: What algorithm is used for prediction?**

\*Answer\*: XGBoost (Gradient Boosted Decision Trees) calibrated with Platt Sigmoid / Isotonic scaling.

\*Keywords\*: XGBoost, CalibratedClassifierCV, Platt Scaling.

**4. Q: What is your operational decision threshold?**

\*Answer\*:  $\tau = 0.0150$  (1.5%), selected on validation data to maximize recall (52.1%) under class imbalance.

\*Keywords\*:  $\tau = 0.015$ , 1.5%, Validation Sweep, 52.1% Recall.

**5. Q: What is the ROC-AUC and PR-AUC?**

\*Answer\*: ROC-AUC is 0.9605; PR-AUC is 0.1082 (24.6x lift over baseline).

\*Keywords\*: ROC-AUC 0.9605, PR-AUC 0.1082, Imbalance Lift.

**6. Q: How does Explainable AI work in R.A.I.?**

\*Answer\*: TreeSHAP calculates exact additive Shapley feature attributions ( $\phi_i$ ), showing positive risk drivers and protective factors.

\*Keywords\*: TreeSHAP, Shapley Values, Additive Attribution, Positive/Negative Drivers.

**7. Q: What are the 4 layers in the telemetry inspector?**

\*Answer\*: Layer 1: Observed \to Layer 2: Predicted \to Layer 3: Explained \to Layer 4: Operational Warning.

\*Keywords\*: Observed, Predicted, Explained, Operational Warning.

**8. Q: What weather data sources are used?**

\*Answer\*: Open-Meteo NWP forecasts and NASA GPM IMERG 0.1° satellite precipitation grids.

\*Keywords\*: Open-Meteo, NASA GPM IMERG, 0.1 Degree Grid.

**9. Q: How is class imbalance handled?**

\*Answer\*: Validation-tuned decision threshold ( $\tau = 0.015$ ), Platt probability calibration, and  $F_2$  evaluation.

\*Keywords\*: 0.44% Baseline, Threshold Tuning, Calibration,  $F_2$  Metric.

**10. Q: What backend stack is used?**

\*Answer\*: Python FastAPI running on Uvicorn, structured with Pydantic contracts.

\*Keywords\*: FastAPI, Uvicorn, Pydantic, Python 3.11/3.14.

**11. Q: What frontend stack is used?**

\*Answer\*: React 18 with TypeScript, Vite bundler, and Vanilla CSS Modules.

\*Keywords\*: React 18, TypeScript, Vite, CSS Modules.

**12. Q: What database is used?**

\*Answer\*: Supabase Cloud PostgreSQL with 6 relational tables and strict IDOR isolation.

\*Keywords\*: Supabase Cloud, PostgreSQL, IDOR Defense.

**13. Q: How does OTP verification work?**

\*Answer\*: 6-digit cryptographic random code, salted HMAC hash, single-use destruction, dispatched via Brevo email.

\*Keywords\*: Brevo, Sender ID 1, Salted HMAC, Single-Use.

**14. Q: What is Farmer AI?**

\*Answer\*: An agronomic decision hub with 35,857 knowledge records, 1.75x persona boosting, and Hindi/Hinglish synonym expansion.

\*Keywords\*: 35,857 Records, 1.75x Boost, Hinglish Synonyms, Soil/Crop Grounding.

15. Q: How are passwords secured?

\*Answer\*: Salted SHA-256 with server-side pepper; never stored in plaintext or client storage.

\*Keywords\*: Salted SHA-256, Server Pepper, Zero Client Storage.

16. Q: How was temporal leakage prevented?

\*Answer\*: Strict chronological data splits (Train 2023-May 2024, Val May-Sep 2024, Test Sep-Dec 2024).

\*Keywords\*: Chronological Splitting, No Future Leakage, 175,440 Records.

17. Q: What is the Brier score?

\*Answer\*: Calibrated Brier score of 0.0044 (Rated EXCELLENT reliability).

\*Keywords\*: Brier Score 0.0044, Probability Calibration.

18. Q: How is the app containerized?

\*Answer\*: Dockerfile using `python:3.11-slim` running non-root user `raiuser:1000` on port 8000.

\*Keywords\*: Docker, python:3.11-slim, Non-root User, Port 8000.

19. Q: What automated tests were performed?

\*Answer\*: 160 cumulative automated tests spanning pytest, Supabase E2E, auth hardening, security audit, and build.

\*Keywords\*: 160 Tests, 100% Pass, Pytest, E2E, Security Audit.

20. Q: What is the single biggest advantage of R.A.I.?

\*Answer\*: Transforming opaque probabilities into transparent, physics-grounded civil actions that users can trust.

\*Keywords\*: Trust, Transparency, Actionable Warnings, Physics-Grounded.

---

PART 25 - 30-SECOND RAPID REVISION SHEET

```
+-----+
| R.A.I. 30-SECOND VIVA CHEAT SHEET |
+-----+
| Problem Statement | SIH1521 - Explainable AI for Heavy Rainfall |
| Target Definition | IMD Heavy Rainfall (>= 64.5 mm / 24 hours) |
| ML Model | XGBoost + Platt/Isotonic Calibrator (CalibratedCV) |
| Operational tau | tau = 0.0150 (1.5% calibrated probability) |
| Evaluation | ROC-AUC: 0.9605 | PR-AUC: 0.1082 | Brier Score: 0.0044 |
| XAI Technology | TreeSHAP (Exact Additive Feature Attributions) |
| Ingestion Feeds | Open-Meteo NWP + NASA GPM IMERG 0.1 deg Satellite Grid |
| Frontend Stack | React 18, TypeScript, Vite 6.4, CSS Modules |
| Backend Stack | Python FastAPI, Uvicorn (Port 8000), Pydantic v2 |
| Cloud Database | Supabase Managed PostgreSQL (6 Relational Tables) |
| Authentication | Brevo Transactional Email OTP (Sender ID 1), Salted HMAC |
| Farmer AI Hub | 35,857 Records, 1.75x Persona Boost, Hinglish Synonyms |
| Containerization | Docker (python:3.11-slim, Non-Root raiuser:1000) |
| Test Coverage | 160 Automated Tests (100% Verified Pass Rate) |
+-----+
```

---

PART 26 - "IF THE JUDGE ASKS ME..." RAPID RESPONSE GUIDE

- "Why is your probability so low (e.g. 1.5%)?"

↳ "Because heavy rainfall is an extreme-imbalance event (0.44% baseline frequency). In this domain, a 1.5% calibrated probability represents a 3.4x risk elevation over normal conditions."

- "How do you prove your model isn't overfitting?"

↳ "We used strict chronological train/validation/test splitting across 175,440 hourly records spanning 10 distinct climate zones with zero temporal data leakage."

- "Why should disaster officials trust your AI?"

\to **"Because R.A.I. provides mathematical TreeSHAP attributions showing the exact physical atmospheric drivers (pressure drop, humidity, wind) behind every alert."**

- **"What happens if Open-Meteo goes down during a storm?"**

\to **"Our weather ingestion adapter includes automatic fallback heuristics grounded in local seasonal climatology, ensuring zero service crash."**

- **"Why didn't you use deep learning (LSTMs/Transformers)?"**

\to **"Tabular meteorological features are best modeled by gradient boosted trees, which achieve higher ROC-AUC (0.9605), require no heavy GPU, and allow exact polynomial-time TreeSHAP computation."**

---

PART 27 - 6-MEMBER TEAM KNOWLEDGE DISTRIBUTION

|                                                                                                                                         |                          |                                    |
|-----------------------------------------------------------------------------------------------------------------------------------------|--------------------------|------------------------------------|
| +-----+<br>  TEAM MEMBER SPECIALIZATION MATRIX  <br> --+-----+<br>  Team Member   Primary Domain   Key Responsibilities  <br> --+-----+ |                          |                                    |
| Member 1                                                                                                                                | Project Lead & Overview  | SIH1521 Mission, 5 Pillars, Demo   |
| Member 2                                                                                                                                | Machine Learning & Stats | XGBoost, Calibration, Metrics      |
| Member 3                                                                                                                                | Explainable AI (XAI)     | TreeSHAP Mathematics, Features     |
| Member 4                                                                                                                                | Frontend & Visualization | React 18, 4-Layer Telemetry, Radar |
| Member 5                                                                                                                                | Backend & APIs           | FastAPI, Pydantic, Ingestion       |
| Member 6                                                                                                                                | Security & Cloud DB      | Supabase, Brevo OTP, Docker        |
| +-----+                                                                                                                                 |                          |                                    |

---

PART 28 - ACTUAL IMPLEMENTATION VS. PLANNED FEATURES

| Feature / Module                                   | Status                               | Evidence / File Location                           |
|----------------------------------------------------|--------------------------------------|----------------------------------------------------|
| <b>**XGBoost 24h Heavy Rain Model**</b>            | <b>**IMPLEMENTED / VERIFIED**</b>    | `ml/models/rainfall_model_v1/model.pkl`            |
| <b>**Isotonic / Platt Calibration**</b>            | <b>**IMPLEMENTED / VERIFIED**</b>    | `ml/models/rainfall_model_v1/calibrated_model.pkl` |
| <b>**Validation Threshold Tuning (tau=0.015)**</b> | <b>**IMPLEMENTED / VERIFIED**</b>    | `ml/models/rainfall_model_v1/metadata.json`        |
| <b>**TreeSHAP Explainability Engine**</b>          | <b>**IMPLEMENTED / VERIFIED**</b>    | `ml/explainability/shap_engine.py`                 |
| <b>**4-Layer Telemetry Inspector**</b>             | <b>**IMPLEMENTED / VERIFIED**</b>    | `src/pages/RiskMap/RiskMapPage.tsx`                |
| <b>**Live RainViewer Radar Overlay**</b>           | <b>**IMPLEMENTED / VERIFIED**</b>    | `src/pages/RiskMap/RiskMapPage.tsx`                |
| <b>**Supabase Cloud PostgreSQL DB**</b>            | <b>**IMPLEMENTED / VERIFIED**</b>    | `ml/db/client.py`                                  |
| <b>**Brevo Real Email OTP Delivery**</b>           | <b>**IMPLEMENTED / VERIFIED**</b>    | `ml/auth/otp_engine.py` (Sender ID: 1)             |
| <b>**Remember Me Storage Segmentation**</b>        | <b>**IMPLEMENTED / VERIFIED**</b>    | `src/services/auth.service.ts`                     |
| <b>**Farmer AI (35,857 Records)**</b>              | <b>**IMPLEMENTED / VERIFIED**</b>    | `src/data/raiKnowledge/index.ts`                   |
| <b>**Docker Production Container**</b>             | <b>**IMPLEMENTED / VERIFIED**</b>    | `Dockerfile`, `docker-compose.yml`                 |
| <b>**Multi-Worker Gunicorn Cluster**</b>           | <b>**PLANNED / NOT IMPLEMENTED**</b> | Scheduled for future Kubernetes deployment         |
| <b>**Direct IMD Doppler Radar API**</b>            | <b>**PLANNED / NOT IMPLEMENTED**</b> | Proprietary radar access in future phase           |

---

PART 29 - THE R.A.I. PROJECT NARRATIVE SCRIPT

*\*"Extreme rainfall events in India are sudden, violent, and devastating. When a cloudburst hits, communities have minutes, not days, to react. Yet, traditional meteorological systems either issue broad, non-specific warnings or rely on opaque AI black boxes that emergency responders cannot trust."\**

*\*We built R.A.I. to solve this crisis through three core pillars: Precision, Transparency, and Action.\**

*\*First, **\*\*Precision\*\***: We trained an XGBoost model on 175,000 real meteorological records across India, calibrated its probabilities to match empirical reality, and tuned an operational decision threshold at 1.5% to overcome extreme class imbalance, catching over 52% of heavy rain events.\**

*\*Second, **\*\*Transparency\*\***: We integrated TreeSHAP to calculate the exact physical contribution of every atmospheric variable - showing officials whether an alert is driven by moisture saturation, falling barometric pressure, or convective wind convergence.\**

*\*Third, **\*\*Action\*\***: We developed a 4-layer telemetry system and dedicated farmer intelligence hub with 35,000 agronomic records, translating raw meteorological physics into life-saving checklists for citizens, disaster relief teams, and farmers.\**

*\*"R.A.I. is not just another weather app - it is an Explainable Artificial Intelligence early-warning platform designed to save lives and protect livelihoods."\**

---

PART 30 - MEMORIZE THESE NUMBERS & CONSTANTS

- **SIH Problem Code:** `SIH1521`
- **Heavy Rainfall Threshold:**  $\geq 64.5$  mm/day (IMD Standard)
- **Historical Positive Class Frequency:** 0.44% (1 in 227 samples)
- **Total Training Records:** 175,440 hourly records (10 Indian Climate Stations)
- **Model Version:** `v1.0.0-sih-xgb`
- **Operational Decision Threshold:**  $\tau = 0.0150$  (1.5% calibrated probability)
- **Test ROC-AUC:** 0.9605
- **Test PR-AUC:** 0.1082 (24.6x lift over baseline)
- **Calibrated Brier Score:** 0.0044 (Rated `EXCELLENT`)
- **Validation Early-Warning Recall:** 52.1%
- **Validation Precision:** 10.96%
- **TreeSHAP Base Value ( $\phi_0$ ):** -4.852 log-odds
- **Core Production Signature Features:** 14 features
- **Total Registered Feature Schemas:** 27 features
- **NASA GPM IMERG Grid Resolution:**  $0.1^\circ \times 0.1^\circ$  ( $\sim 10$  km)
- **Master Knowledge Base Records:** 35,857 records across 18 JSON partitions
- **Farmer Persona Category Boost:** 1.75x
- **Brevo Sender ID:** `1` (`RAINAIWORK@GMAIL.COM`)
- **Backend API Port:** `8000`
- **Frontend Dev Port:** `3000`
- **Non-Root Docker User:** `raiuser` (`UID: 1000`)
- **Automated Tests Passed:** 160 / 160 (100%)

---

FINAL VIVA MASTER CHEAT SHEET

```
+-----+
| FINAL VIVA MASTER SUMMARY |
+-----+
| 1. SYSTEM IDENTITY: R.A.I. (Rainfall Artificial Intelligence) for SIH1521. |
| 2. CORE PROBLEM: Explainable 24h early warning for extreme rain (>=64.5mm). |
| 3. ML ALGORITHM: XGBoost + Platt Sigmoid / Isotonic Probability Calibrator. |
| 4. CRITICAL METRIC: PR-AUC 0.1082 & ROC-AUC 0.9605 on 175k real records. |
| 5. OPERATIONAL THRESHOLD: tau = 0.015 (1.5% prob.) giving 52.1% flood recall. |
| 6. XAI ENGINE: TreeSHAP computing exact additive Shapley log-odds factors. |
| 7. 4-LAYER TELEMETRY: Observed -> Predicted -> Explained -> Actionable Warning. |
| 8. DATA FEEDS: Open-Meteo High-Resolution NWP + NASA GPM IMERG 0.1 deg Grid. |
| 9. FULL STACK: React 18 + TS (Port 3000) ■ FastAPI + Python (Port 8000). |
| 10. CLOUD DATABASE: Supabase Managed PostgreSQL with IDOR tenant defense. |
| 11. SECURITY & OTP: Brevo Sender ID 1, 256-bit sessions, zero secret leaks. |
| 12. FARMER AI HUB: 35,857 records, 1.75x persona boost, Hinglish synonyms. |
| 13. CONTAINERIZATION: Docker (python:3.11-slim, non-root user raiuser:1000). |
| 14. VERIFICATION: 160 / 160 Automated Tests Passed (100% Verified). |
+-----+
```