

WEEK 8

Sorting Algorithms – Bubble and Selection

Roll no : 240701095

Name : Darshini.H

| | |
|------------------|-----------------------------------|
| Attempt 2 | |
| Status | Finished |
| Started | Monday, 23 December 2024, 5:33 PM |
| Completed | Friday, 20 December 2024, 5:22 AM |
| Duration | 3 days 12 hours |

PROGRAM 1: Coders here is a simple task for you, you have given an array of size N and an integer M. Your task is to calculate the difference between maximum sum and minimum sum of N-M elements of the given array.

Constraints:

$1 \leq t \leq 10$

$1 \leq n \leq 1000$

$1 \leq a[i] \leq 1000$

Input Format:

First line contains an integer T denoting the number of testcases. First line of every testcase contains two integer N and M.

Next line contains N space separated integers denoting the elements of array

Output:

For every test case print your answer in new line

Sample

Input 1

5 1

1 2 3 4 5

Sample

Output 4

Explanation

M is 1 and N is 5 so you have to calculate maximum and minimum sum using (5-1 =) 4 elements.

Maximum sum using the 4 elements would be (2+3+4+5=)14. Minimum sum using the 4 elements would be (1+2+3+4=)10. Difference will be 14-10=4.

CODE:

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int t;
5     scanf("%d",&t);
6     while(t--)
7     {
8         int n,m,d,min,temp;
9         scanf("%d %d",&n,&m);
10        d=n-m;
11        int arr[n];
12        for (int i=0;i<n;i++)
13            scanf ("%d",&arr[i]);
14        for(int j=0;j<n;j++)
15        {
16            min=j;
17            for(int k=j;k<n;k++)
18            {
19                if(arr[k]<arr[min])
20                    min=k;
21            }
22            temp=arr[min];
23            arr[min]=arr[j];
24            arr[j]=temp;
25        }
26        int maxsum=0,minsum=0;
27        for(int a=0;a<d;a++)
28            minsum+=arr[a];
29        for (int b=n-1;b>m-1;b--)
30            maxsum+=arr[b];
31        printf("%d \n",maxsum-minsum);
32    }
33 }
```

OUTPUT:

| | Input | Expected | Got | |
|---|-----------------------|----------|-----|---|
| ✓ | 1 5 1 1 2 3 4 5 | 4 | 4 | ✓ |

Passed all tests! ✓

PROGRAM 2: A new deadly virus has infected large population of a planet. A brilliant scientist has discovered a new strain of virus which can cure this disease. Vaccine produced from this virus has various strength depending on midichlorians count. A person is cured only if midichlorians count in vaccine batch is more than midichlorians count of person. A doctor receives a new set of report which contains midichlorians count of each infected patient, Practo stores all vaccine doctor has and their midichlorians count. You need to determine if doctor can save all patients with the vaccines he has. The number of vaccines and patients are equal.

Input Format

First line contains the number of vaccines - N. Second line contains N integers, which are strength of vaccines. Third line contains N integers, which are midichlorians count of patients.

Output Format

Print a single line containing 'Yes' or 'No'.

Input

Constraint 1 <

N < 10

Strength of vaccines and midichlorians count of patients fit in integer.

Sample

Input 5

123 146 454 542 456

100 328 248 689 200

Sample Output No

CODE:

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int n,min1,min2,temp,flag=1;
5      scanf("%d",&n);
6      int vac[n],pat[n];
7      for(int i=0;i<n;i++)
8          scanf("%d",&vac[i]);
9      for(int i=0;i<n;i++)
10         scanf("%d",&pat[i]);
11     for(int j=0;j<n-1;j++)
12     {
13         min1=j;
14         min2=j;
15         for(int k=j;k<n;k++)
16         {
17             if(vac[k]<vac[min1])
18                 min1=k;
19             if(pat[k]<pat[min2])
20                 min2=k;
21         }
22         temp=vac[min1];
23         vac[min1]=vac[j];
24         vac[j]=temp;
25     }
26     for(int i=0;i<n;i++)
27     {
28         if(vac[i]<=pat[i])
29         {
30             flag=0;
31             break;
32         }
33     }
34     if(flag==1)
35         printf("Yes");
36     else
37         printf("No");
38 }
```

OUTPUT:

| | Input | Expected | Got | |
|---|---|----------|-----|---|
| ✓ | 5 123 146 454 542 456 100 328 248 689 200 | No | No | ✓ |

Passed all tests! ✓

PROGRAM 3: You are given an array of n integer numbers a_1, a_2, \dots, a_n . Calculate the number of pair of indices (i, j) such that $1 \leq i < j \leq n$ and $a_i \text{ xor } a_j = 0$.

Input format

- First line: n denoting the number of array elements
- Second line: n space separated integers a_1, a_2, \dots, a_n .

Output format

Output the required number of pairs.

Constraint

$1 \leq n \leq$

106

$1 \leq a_i \leq 10^9$

Sample

Input 5

1 3 1 4 3

Sample

Output 2

Explanation

The 2 pair of indices are (1, 3) and (2,5).

CODE:

Answer: (penalty regime: 0 %)

```
1  #include<stdio.h>
2  int main()
3  {
4      int n,count=0;
5      scanf("%d",&n);
6      int arr[n];
7      for(int i=0;i<n;i++)
8          scanf("%d",&arr[i]);
9      for(int i=0;i<n-1;i++)
10     {
11         for(int j=i+1;j<n;j++)
12         {
13             if((arr[i]^arr[j])==0)
14                 count++;
15         }
16     }
17     printf("%d",count);
18 }
```

OUTPUT:

| | Input | Expected | Got | |
|---|----------------|----------|-----|---|
| ✓ | 5 1 3 1 4 3 | 2 | 2 | ✓ |

Passed all tests! ✓

PROGRAM 4: You are given an array A of non-negative integers of size m. Your task is to sort the array in nondecreasing order and print out the original indices of the new sorted array.

Example:

A={4,5,3,7,1}

After sorting the new array becomes

A={1,3,4,5,7}. The required output should be

"4 2 0 1 3"

Input Format:

The first line of input consists of the size of the

array The next line consists of the array of size m

Output Format:

Output consists of a single line of integers

Constraints:

$1 \leq m \leq 106$

$0 \leq A[i] \leq 106$

NOTE: The indexing of the array starts with 0.

Sample

Input 5

4 5 3 7 1

Sample Output 4 2 0 1 3

CODE:

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     int arr[n];
7     for(int i=0;i<n;i++)
8         scanf("%d",&arr[i]);
9     int max=arr[0];
10    for(int i=1;i<n;i++)
11    {
12        if(arr[i]>max)
13            max=arr[i];
14    }
15    max++;
16    int min=0;
17    for(int a=0;a<n;a++)
18    {
19        for(int b=0;b<n;b++)
20        {
21            if(arr[b]<arr[min])
22                min=b;
23        }
24        printf("%d ",min);
25        arr[min]=max;
26    }
27
28 }
```

OUTPUT:

| | Input | Expected | Got | |
|---|----------------|-----------|-----------|---|
| ✓ | 5 4 5 3 7 1 | 4 2 0 1 3 | 4 2 0 1 3 | ✓ |

Passed all tests! ✓