Computer Vision · Weeks 2 & 3

Beginner study guide: plain-language notes + notebooks with outputs

Part 1: notes (00 deep-learning basics → 07 Vision Transformers)
Part 2: notebooks · Part 3: the 7 course labs, worked through
01 Neural-network building blocks · 02 LeNet, AlexNet, VGG · 03 ResNet, EfficientNet
04 Object detection · 05 Segmentation & Mask R-CNN · 06 RNN, LSTM, video · 07 Vision Transformers

Plus: answers to the 60-question course question bank and the cheat sheet.
Runnable notebooks are in the **notebooks/** folder next to this PDF.

00 · Deep learning from zero (read this first)

Week 1 was about **hand-made** image tools. You picked the kernel (`[[0,-1,0],[-1,5,-1],[0,-1,0]]` to sharpen), you picked the threshold (127), you picked the rules. Weeks 2–3 are about letting the computer **learn those numbers by itself** from examples. That is all "deep learning" means.

Notebook for this chapter: `notebooks/01_neural_network_building_blocks.ipynb`

---


1. The big idea in one paragraph

> Show the computer thousands of labelled pictures ("this is a 3", "this is a 7"). It starts with **random** kernels, makes a guess, sees how wrong it was, and **nudges every number a tiny bit** in the direction that would have made the guess less wrong. After thousands of nudges, the random numbers have turned into useful edge detectors, stroke detectors and digit detectors.

The model never gets told "look for a loop at the top". It discovers that by itself, because it helps reduce the mistakes.

---

2. A neuron is a tiny calculator



A **neuron** does three things:

1. Multiplies each input by a **weight** (how important that input is).
2. Adds them all up, plus a **bias** (a constant nudge).
3. Passes the total through an **activation function** (e.g. ReLU: negative → 0).

```
output = ReLU( w1·x1 + w2·x2 + w3·x3 + b )
```

That should look familiar: **a 3×3 convolution kernel is a neuron with 9 weights**, applied at every position of the image. The only difference from Week 1 is that the 9 numbers are

learned rather than typed in.


Layers are rows of neurons. A **network** is layers stacked one after another. "**Deep**" just means "many layers".

Word	Plain meaning
Weights / parameters	the numbers the network learns (kernel values, connection strengths)
Layer	one stage of processing (a conv layer, a pooling layer, a dense layer)
Feature map	the output image of a conv layer (one per kernel)
Architecture	the *recipe*: which layers, in what order, how big (LeNet, VGG, ResNet are architectures)
Model	an architecture **plus** its learned weights

---

3. How it learns: the training loop

Training = guess, measure the mistake, nudge every weight, repeat




Step	What happens	PyTorch line
1. **Forward pass**	push a batch of images through the network → predictions	`out = model(x)`
2. **Loss**	one number that says *how wrong* the predictions are	`loss = loss_fn(out, y)`
3. **Backward pass**	work out, for **every** weight, "if I nudge you up, does the loss go up or down?" That answer is the **gradient**	`loss.backward()`
4. **Update**	move each weight a small step against its gradient	`optimizer.step()`

Then repeat thousands of times. One full pass over the training images is an **epoch**.

Analogy: walking downhill in fog. The loss is your height on a hillside, and you want to reach the valley. You can't see far, but you can feel which way the ground slopes under your feet (the gradient). Take a small step downhill, feel again, step again. The **learning rate** is the size of your step: too big and you overshoot, too small and you take forever.

```
for epoch in range(10):
    for x, y in train_loader:          # x = batch of images, y = correct labels
        out  = model(x)                # 1. guess
        loss = loss_fn(out, y)         # 2. how wrong?
        optimizer.zero_grad()          #    clear old gradients
        loss.backward()                # 3. who is to blame?
        optimizer.step()               # 4. nudge the weights
```



From notebook 01: the loss goes down as training proceeds, and the 3×3 kernels go from random noise to structured patterns.

---

4. Training data vs test data

- **Training set:** the pictures the network learns from.
- **Test set:** pictures it has **never seen**, used only to check how good it really is.

The real goal is to do well on **new** pictures. Doing well on the training pictures is easy: the network could simply memorise them.

> **Overfitting** = great on training data, noticeably worse on test data. The network memorised instead of understanding. This is like a student who memorised last year's answers and fails when the questions change.

Fixes you will meet: **dropout** (chapter 01), more data, **data augmentation** (Week 1 Day 2: flips, rotations, crops), smaller models.

---

5. Just enough PyTorch

The notebooks use **PyTorch** (`import torch`). You need very little of it:

```
import torch, torch.nn as nn

x = torch.randn(8, 1, 28, 28)   # a batch: 8 images, 1 channel (grey), 28×28 pixels
#               N  C   H   W      ← PyTorch order: batch, channels, height, width
```

> ⚠️ OpenCV images are `(H, W, C)`. PyTorch wants `(N, C, H, W)`. Converting: `torch.from_numpy(img).permute(2, 0, 1).unsqueeze(0)`.

```
model = nn.Sequential(
    nn.Conv2d(1, 6, kernel_size=5),   # 1 input channel → 6 learned 5×5 kernels
    nn.ReLU(),
    nn.MaxPool2d(2),                  # halve height and width
    nn.Flatten(),                     # grid → long list
    nn.Linear(6 * 12 * 12, 10),       # fully connected → 10 scores (digits 0–9)
)
print(model(x).shape)                 # torch.Size([8, 10])
print(sum(p.numel() for p in model.parameters()))   # how many weights to learn
```

Layer	What it is
`nn.Conv2d(in, out, k)`	`out` learned kernels of size k×k (Week 1 convolution, learned)
`nn.ReLU()`	negatives → 0
`nn.MaxPool2d(2)`	keep the max of every 2×2 block
`nn.Dropout(p)`	randomly zero a fraction p (training only)
`nn.Flatten()`	`(N, C, H, W)` → `(N, C·H·W)`
`nn.Linear(in, out)`	fully connected layer

`model.train()` turns dropout on, and `model.eval()` turns it off for testing. `with torch.no_grad():` means "just predict, don't track gradients".

---

6. The output: scores → probabilities → answer

The last layer gives one **score** per class (called **logits**), e.g. `[1.2, -0.3, 4.1, ...]`. **Softmax** turns them into probabilities that add up to 1. The predicted class is the biggest one: `out.argmax(1)`.

The usual loss for classification is **cross-entropy**. It is small when the network puts a high probability on the correct class and large when it is confidently wrong.

---

7. Why this beats Week 1 methods

Week 1 (hand-crafted)	Weeks 2–3 (learned)
you design the kernel / threshold / features (HOG, SIFT)	the network learns them from examples
works well when *you* understand the problem	works when the pattern is too complex to describe by hand (faces, tumours, cats)
needs little data, little compute	needs lots of labelled data and compute (GPUs)
transparent: you know what each step does	harder to interpret (we visualise kernels and feature maps to peek inside)

Week 1 is not obsolete: preprocessing (resize, normalise, augment) and post-processing (thresholding a mask, finding contours on it) still use exactly those tools.

Check yourself

1. What are "weights" and who chooses them?
2. Name the four steps of the training loop.
3. What is an epoch?
4. What is overfitting and how do you detect it?
5. What shape does PyTorch expect for a batch of 16 colour 224×224 images?

Answers

1. The numbers inside the layers (kernel values, connection strengths). The network learns them during training. You only choose the architecture.
2. Forward pass → loss → backward pass (gradients) → optimiser step (update).
3. One full pass through all the training data.
4. High training accuracy but clearly lower test accuracy. Compare the two.
5. `(16, 3, 224, 224)`.

01 · The building blocks: conv vs dense layers, ReLU, dropout, pooling

Key Concepts covers: Fully connected (dense) layers · Convolutional layers · ReLU · Dropout · (and in the question bank) vanishing gradient, pooling

Notebook: `notebooks/01_neural_network_building_blocks.ipynb`

---

1. Fully connected (dense) layers


> **Every neuron connects to every value in the previous layer.**

- **Input:** a **flattened** vector. A 28×28 image becomes a list of 784 numbers, and the network no longer knows which pixels were neighbours.
- **Purpose:** combine **everything** into a final decision ("these features together mean *cat*").
- **Strength:** captures complex relationships between all features.
- **Weaknesses:**
- **huge number of parameters** (every input × every output);
- **ignores spatial locality** (a pixel's neighbours mean nothing special to it).

How huge? A 224×224 colour image has 150,528 values. One dense layer with 1,000 neurons needs **150,528 × 1,000 ≈ 150 million weights**. That is just one layer.

2. Convolutional layers


> **Each neuron looks only at a small local window (its *receptive field*), and the same kernel is slid across the whole image.**



This is exactly Week 1's `cv2.filter2D`, except the kernel values are **learned**.

- **Input:** keeps the spatial layout: height × width × channels.
- **Purpose:** extract **local features** such as edges, textures and shapes.

- **Advantages:**
- **Few parameters.** A 3×3 conv from 3 channels to 64 channels has 3·3·3·64 + 64 = **1,792** weights, *whatever the image size*. The same kernel is reused at every position (**weight sharing**).
- **Spatial hierarchy.** Layer 1 finds edges, layer 2 combines edges into corners and textures, and deeper layers find parts (eyes, wheels) and then whole objects.
- **Translation invariance.** A feature is detected **wherever** it appears, because the same kernel scans everywhere.
- **Limitation:** on its own a conv layer only sees locally. That's why CNNs usually **end with pooling and dense layers** to make the final decision.



Notebook 01: the same square moved to another corner. The conv response just moves with it, with the same strength (max 9 both times).


> **In practice:** conv layers for **feature extraction** (early and middle), dense layers for **decision making** (end).

	Fully connected	Convolutional
Connects to	**all** inputs	a **small local window**
Input	flat vector (layout lost)	grid (layout kept)
Parameters	very many	few (shared kernel)
Learns	global relationships	local features, building up a hierarchy
Position of a pattern	matters (has to be re-learned at each spot)	doesn't matter (translation invariant)
Typical place	the end (classifier)	the start and middle (feature extractor)

---

3. ReLU (Rectified Linear Unit)

> **If the input is positive, keep it. If it is negative, output zero.** `ReLU(x) = max(0, x)`



Why we need *any* activation: without one, stacking layers is pointless. Two linear layers in a row equal one linear layer. The activation adds **non-linearity**, which lets the network learn curved, complicated decision boundaries.


Why ReLU instead of sigmoid / tanh (the older choices):

1. **Faster.** It is just `max(0, x)`, with no exponentials. AlexNet trained about **6× faster** with ReLU.
2. **Less vanishing gradient.** Look at the right-hand plot above:
3. the slope of **sigmoid** is at most **0.25**, and nearly 0 for big or small inputs ("saturated");
4. the slope of **ReLU** is exactly **1** for every positive input.

The vanishing gradient problem (exam favourite)

During the backward pass, the gradient for an early layer is a **product of one factor per layer** it passes through. Multiply many numbers smaller than 1 and the result shrinks towards zero:

```
sigmoid, 20 layers:  0.25 × 0.25 × ... (20 times) ≈ 0.000000000001
ReLU,    20 layers:  1 × 1 × ... × 1              = 1
```



With a gradient of nearly 0 the early layers **stop learning**, because their weights barely change. ReLU reduces this problem, and ResNet (chapter 03) fixes it properly for very deep networks.


Analogy: ReLU is like a filter (or a one-way valve) that only lets positive signals through.


> ReLU's one weakness is "**dying ReLU**". A neuron whose input is always negative outputs 0 forever and has gradient 0, so it never recovers. Variants such as Leaky ReLU fix this, but they are not in the syllabus.

---

4. Dropout

> **During training, randomly switch off (set to zero) a fraction *p* of the neurons on every step.**





- **Purpose: regularisation**, i.e. preventing **overfitting**.
- **Key Concepts example:** a layer with **10 neurons** and dropout rate **0.3** drops **about 3 neurons** each training pass, a *different* random 3 each time.
- **Why it helps:**
- no neuron can rely on one specific partner always being there, so knowledge is **spread across many neurons**;
- the network learns **robust** features instead of memorising;
- it **generalises** better to unseen data.
- **Only during training.** At test time all neurons are used: `model.eval()` turns dropout off. During training the surviving values are scaled up by 1/(1−p), so the average signal stays the same.

Analogy (from the course): a team exercise where some members randomly sit out, so everyone has to learn to contribute and the team never over-relies on one star player.

Honest result from notebook 01: on our small digits dataset, dropout raised test accuracy from **86.7% to 87.8%** (averaged over 5 runs). It helps, but it is not magic. The effect is biggest on large networks that have room to memorise, like AlexNet's huge dense layers.

```
nn.Dropout(p=0.3)     # put it between dense layers
model.train()         # dropout ON
```

```
model.eval()          # dropout OFF for testing
```

---

5. Pooling

> **Max pooling 2×2** keeps the **largest** value in each 2×2 block (see the right half of the picture above).

- **Halves the height and width**, so there is less to compute in later layers.
- **Has no weights to learn.**
- Gives a little **tolerance to small shifts**: if the pattern moves by one pixel, the max of the block is often unchanged.
- Each later kernel now covers a **bigger part of the original image** (a bigger receptive field).

Average pooling takes the mean instead. **Global average pooling** averages a whole feature map down to one number. ResNet and EfficientNet use this instead of giant dense layers.

---

6. Putting it together: a typical small CNN

```
image → [conv → ReLU → pool] → [conv → ReLU → pool] → flatten → dense → ReLU → dropout → dense → class scores
        └──────── feature extraction ──────────────┘              └──────── decision ──────────────────┘
```

That is LeNet (next chapter) with ReLU and dropout added, which is almost exactly what AlexNet did at a bigger scale.

Check yourself

1. Why does a dense layer on a 224×224×3 image need so many weights, and why doesn't a conv layer?
2. What does "translation invariance" mean, and which layer type gives it?
3. What does ReLU do to −3, 0 and 5?
4. Give two reasons ReLU replaced sigmoid.
5. A layer has 20 neurons and dropout 0.25. How many are dropped per training step? At test time?
6. A 64×64×16 feature map goes through 2×2 max pooling. What is the new shape? How many weights does the pooling layer have?

Answers

1. Every one of the 150,528 inputs connects to every neuron. A conv layer reuses one small kernel everywhere, so its weight count depends only on the kernel size and channel counts.
2. A pattern is recognised wherever it is in the image. Conv layers give it, because the same kernel is applied at every position (pooling adds a little more).

3. 0, 0 and 5.
4. It is cheaper and faster to compute, and its slope is 1 for positive inputs, so gradients don't vanish (sigmoid's slope is at most 0.25).
5. About 5 per step (a different 5 each time). At test time, none.
6. 32×32×16. Zero weights.


02 · Classic CNNs: LeNet (1998), AlexNet (2012), VGG (2014)

Key Concepts covers: CNN architectures intro · LeNet · AlexNet · VGG · Key takeaways · ReLU and dropout in AlexNet

Notebook: `notebooks/02_classic_cnns_lenet_alexnet_vgg.ipynb`

Why study old architectures?

Each landmark model fixed a weakness of the one before it. If you know **what problem each one solved**, you can answer almost any "why" question in the eval.




> **One-line summary: LeNet** = proof of concept · **AlexNet** = the breakthrough in scale and performance · **VGG** = depth and simplicity as design principles.

---


1. LeNet-5 (1998): the proof of concept

Inventor	**Yann LeCun** (and colleagues at AT&T Bell Labs)
Purpose	**handwritten digit recognition**, reading postcodes and **bank cheques**
Dataset	**MNIST**: 70,000 images of handwritten digits 0–9, 28×28 grey
Architecture	**conv → pool → conv → pool → fully connected → fully connected → output**
Size	about **60,000** parameters (tiny by today's standards)



Key contribution: the first convincing proof that a network that **learns its own features** can beat **traditional machine learning** (hand-designed features + a classifier such as an SVM) on images. It was actually deployed: in the late 1990s it read a large share of the cheques written in the USA.

How did it beat traditional methods? Traditional pipelines needed a human to design the features (Week 1 style: edges, HOG, …). LeNet learned the features **and** the classifier **together**, end to end, using convolution's built-in advantages: weight sharing, local patterns and tolerance to shifts.



Notebook 02: top row = LeNet's six learned 5×5 kernels; bottom row = what each one "sees" in a digit (the feature maps). Some act as stroke or edge detectors.

Honest note from the notebook: on the tiny scikit-learn digits (1,257 training images, originally 8×8 pixels), a well-tuned SVM actually scored **98.9%** vs LeNet's **95.9%**. When the test digits are **shifted a few pixels**, both collapse (SVM 69.3%, LeNet 67.2%). Trained with shifted copies (**augmentation**), both recover (SVM 95.6%, LeNet 93.3% on shifted digits). In 1998, on the full MNIST, LeNet matched the best SVMs of its time while being much faster and smaller. Small, clean datasets don't show CNNs at their best. Their advantage grows with **bigger, messier images and more data**. That is exactly what AlexNet proved 14 years later.

---

2. AlexNet (2012): the breakthrough

Authors	Alex Krizhevsky, Ilya Sutskever, Geoffrey Hinton (University of Toronto)
Event	won the **ImageNet** competition (ILSVRC 2012) **by a huge margin**
Dataset	ImageNet: about 1.2 million training images, **1,000 classes**
Architecture	**5 convolutional layers + 3 fully connected layers**
Size	about **61 million** parameters (about 58.6 M of them in the 3 dense layers)
Key contribution	**sparked the deep-learning revolution** in vision

The numbers (remember these)

- **Top-5 error:** the best traditional method had about **26%**. AlexNet got **15.3%**, a huge jump in one year.
- **Key Concepts phrasing:** accuracy before AlexNet **~70%**, after **~85%+**.
- (*Top-5* = counted correct if the right answer is anywhere in the model's 5 best guesses.)


Three innovations (exam: "name two")

Innovation	What it did
ReLU activation	trained about 6× faster than tanh and reduced vanishing gradients
Dropout (p = 0.5 in the dense layers)	reduced overfitting in the 58 M-parameter dense layers
GPU training	split across **two GTX 580 GPUs**. Training took about 5–6 days instead of weeks or months on CPUs

Also used: data augmentation (random crops and flips), overlapping max pooling and local response normalisation.

Why were GPUs critical?

Training means billions of multiply-adds per image (convolution is the same simple maths at millions of positions). A **GPU** has thousands of small cores that do these in **parallel**. Without GPUs, a network that size on 1.2 M images would have taken an impractically long time, so it simply wouldn't have been tried. **Big data (ImageNet) + GPUs + ReLU/dropout** arrived together, and that is why 2012 was the turning point.




*Notebook 02: the same LeNet trained three ways. Sigmoid learns much more slowly (81% vs 96–97%). In this small network tanh slightly edged out ReLU; ReLU's big advantage shows up in **deep** networks, where vanishing gradients bite.*

---

3. VGG (2014): depth and simplicity

Name	**V**isual **G**eometry **G**roup, University of **Oxford**
Depth	**16–19 layers** (VGG-16 and VGG-19)
Design choice	**only small 3×3 filters**, stacked, everywhere
Size	about **138 M** (VGG-16) and **144 M** (VGG-19) parameters
Key contribution	showed that **depth improves accuracy**, and its simple, uniform design became a **standard baseline** in research

Why stack 3×3 filters instead of using one big one? (very common question)



- **Same view.** Two 3×3 layers in a row see a **5×5** area of the input, and three see **7×7**. That is the same "receptive field" as one 5×5 or 7×7 filter.
- **Fewer weights.** For C channels in and out:
- three 3×3 layers: $3 \times (3 \cdot 3 \cdot C^2) =$ **$27\ C^2$**;
- one 7×7 layer: $7 \cdot 7 \cdot C^2 =$ **$49\ C^2$**.

That is about **45% fewer** weights. - **More non-linearity.** Three layers means **three ReLUs** instead of one, so the network can learn more complex functions.

VGG's weakness: about 138 M parameters (most in the dense layers), slow and memory-hungry. Making it even deeper didn't help, because of the problem ResNet solved next.

---

4. Key takeaways (straight from Key Concepts)

Model	Year	Remember it as
LeNet	1998	**proof of concept**: CNNs work (digits, cheques)
AlexNet	2012	**breakthrough**: scale + ReLU + dropout + GPUs → won ImageNet
VGG	2014	**depth + simplicity**: 16–19 layers of 3×3 filters → a standard baseline

Together they form the timeline of CNN evolution, which continues in chapter 03 (ResNet, EfficientNet).

Check yourself

1. Who invented LeNet, and what was it used for? On which dataset?
2. AlexNet: how many conv and FC layers? Name three innovations.
3. What happened to ImageNet error in 2012?
4. Why were GPUs essential for AlexNet?
5. VGG uses only one filter size. Which, and why is that clever?
6. How many weights do three stacked 3×3 layers use (C channels) compared with one 7×7?

Answers

1. Yann LeCun (1998). Handwritten digit recognition for postcodes and bank cheques. MNIST.
2. 5 conv + 3 FC. ReLU, dropout and GPU training (also data augmentation).
3. Top-5 error dropped from about 26% to 15.3%: a huge margin that started the deep-learning era.
4. Training needs billions of parallel multiply-adds. GPUs do these in parallel, cutting training from impractical to about 6 days.
5. 3×3. Stacking gives the same receptive field as a big filter with fewer weights and more non-linearity (more ReLUs).
6. $27C^2$ vs $49C^2$.

03 · Modern CNNs: ResNet (2015) and EfficientNet (2019)

Key Concepts covers: Why study modern CNNs · ResNet · EfficientNet · Key takeaways · Real-world applications

Notebook: `notebooks/03_modern_cnns_resnet_efficientnet.ipynb`

Why "modern" CNNs?

VGG showed that **deeper is better**, but only up to a point. Two problems appeared:

1. **Depth problem:** past about 20 layers, plain networks got *worse*, even on their **training** data. Gradients vanished and weights stopped updating.
2. **Efficiency problem:** making networks bigger (deeper, wider, bigger images) was done by guesswork, wasted computation and was too heavy for phones.


ResNet solved problem 1. **EfficientNet** solved problem 2.

---

1. ResNet (2015): learn the change, not the whole thing

Authors	Kaiming He et al., Microsoft Research
Problem solved	**vanishing gradients / degradation**: very deep networks stopped learning
Innovation	**residual (skip) connections**
Impact	trainable networks of **50, 101, even 152 layers** · won ImageNet 2015 (about 3.6% top-5 error, around human level)
Key idea	**learn residuals instead of direct mappings**

The skip connection



A plain block must learn the whole output: `out = F(x)`. A **residual block** adds its input back on: **`out = F(x) + x`**.

So the layers inside only have to learn **F(x) = out − x**, the **residual**: *what needs to change*.

Direct mapping vs residual, an analogy: you are editing an essay. A *direct mapping* means rewriting the whole essay from scratch every time. A *residual* means "keep the essay and write down only the corrections". If the essay is already fine, the corrections are simply "none" (F(x) = 0), which is very easy to learn. So extra layers can at worst do nothing, and they never make things worse.

Why it fixes the vanishing gradient

The backward pass through `out = F(x) + x` gives a gradient of **F′(x) + 1**. That **"+1"** is a highway: even if F′(x) is tiny, the gradient flows straight back through the shortcut to the early layers without shrinking.

The notebook proves it

Notebook 03 trains plain and residual networks of the same depth on the same data:

Depth	Plain network	Residual network
6 layers	78%	88%
22 layers	**10%** (= random guessing)	76%
52 layers	**10%**	66%

At 52 plain layers the gradient reaching the first layer was **exactly 0**: those layers never learned anything. The residual version still trains.

ResNet sizes

Model	Layers	Parameters
ResNet-18	18	11.7 M
ResNet-50	50	25.6 M
ResNet-152	152	60.2 M

Even ResNet-152 is **smaller than VGG-16 (138 M)**. ResNet uses **global average pooling** instead of giant dense layers, and "**bottleneck**" blocks (1×1 conv to shrink the channels → 3×3 → 1×1 to expand them again).

Real-world use (Key Concepts): medical imaging. ResNet is a common backbone for X-ray, CT and MRI analysis and for detection and segmentation models (Faster/Mask R-CNN usually sit on a ResNet).


---

2. EfficientNet (2019): grow in a balanced way

Authors	Mingxing Tan & Quoc Le, Google

Problem solved	scaling (deeper, wider or higher resolution) was **inefficient and unbalanced**
Innovation	**compound scaling**: scale **depth, width and resolution together** with one formula
Impact	higher accuracy with **far fewer parameters** · EfficientNet-B0 (**5.3 M**) beats ResNet-50 (25.6 M)
Key idea	**balanced scaling across dimensions**

Three ways to make a CNN bigger



Dimension	Means	Gives on its own	Problem when it is the only one scaled
Depth	more layers	more complex features	gains flatten, harder to train
Width	more channels per layer	more fine-grained features	misses high-level features
Resolution	bigger input image	more fine detail	needs more depth and width to use it

Scaling **only one** gives diminishing returns. They depend on each other: a bigger image needs **more layers** (for a bigger receptive field) and **more channels** (to capture the extra detail).

The compound scaling formula

```
depth      d = α^φ        α = 1.2
width      w = β^φ        β = 1.1
resolution r = γ^φ        γ = 1.15
constraint: α · β² · γ² ≈ 2
```

- **φ (phi)** is the single dial you turn: φ = 0 → B0, φ = 1 → B1, … up to B7.
- α, β and γ were found **once** by a small search on the baseline network.
- Why **α · β² · γ² ≈ 2**? Computation grows with depth × width² × resolution², because doubling the channels or the image side roughly quadruples the work. So each step of φ roughly **doubles the compute**.

Analogy: making a bigger cake. You don't just add more flour (depth only). You scale **all** the ingredients in the right proportions.

Real-world use (Key Concepts): mobile vision apps. These run on phones and edge devices with little memory and battery (EfficientNet-Lite, on-device photo classification).

Bonus: MobileNet and depthwise-separable convolution

Mobile models also use **depthwise-separable convolutions**. A normal convolution is split into: 1. a K×K filter on **each channel separately** (depthwise), then 2. a **1×1** convolution that mixes the channels (pointwise).

Notebook 03 counts the weights: about **8.4× fewer** than a normal 3×3 conv with the same input and output channels. EfficientNet's building block (MBConv) uses this.

---

3. Key takeaways

- **ResNet:** made **very deep** networks trainable (skip connections, residual learning).
- **EfficientNet:** made **scaling efficient** and practical (compound scaling).
- Together they represent the **modern era** of CNNs: solving **depth** and **efficiency**.
- Their ideas carry over to **Vision Transformers**: every transformer layer uses **residual connections**, and ViTs are scaled up systematically too (chapter 07).

The full evolution in one table (Hard Q10)

Step	Lesson passed on
LeNet → AlexNet	learned features + **scale, data, GPUs, ReLU, dropout**
AlexNet → VGG	**depth** with small, uniform blocks
VGG → ResNet	depth needs **skip connections** to train
ResNet → EfficientNet	**scale in a balanced way**, care about efficiency
→ **Vision Transformers**	keep residuals, layer norm, big data and scaling laws, but swap convolution for **attention**

Check yourself

1. What problem made networks deeper than about 20 layers perform worse?
2. Write the formula for a residual block. What is the "residual"?
3. Why does the skip connection help the gradient?
4. Which network trained successfully with 152 layers?
5. What three things does EfficientNet scale, and what does φ control?
6. Give one real-world application each for ResNet and EfficientNet.

Answers

1. Vanishing gradients / degradation: the gradient shrinks layer by layer, so early layers stop updating.
2. out = F(x) + x. The residual F(x) = out − x is the change the block adds on top of its input.
3. Its derivative contributes a +1, so the gradient passes back unchanged through the shortcut even when F′ is tiny.

4. ResNet (ResNet-152).
5. Depth, width and resolution, together. φ is the single scaling dial (B0 → B7), and each step roughly doubles the computation.
6. ResNet: medical imaging (X-ray/CT/MRI analysis, a backbone for detectors). EfficientNet: mobile and on-device vision apps.

04 · Object detection: R-CNN, YOLO, SSD

Key Concepts covers: Object detection intro · R-CNN (2014) · YOLO (2016) · SSD (2016) · Key takeaways · Medical imaging vs autonomous driving

Notebook: `notebooks/04_object_detection_rcnn_yolo_ssd.ipynb`


---

1. What is object detection?

Task	Answers	Output
Classification (chapters 02–03)	*what* is in the image?	one label: "dog"
Object detection	*what* is in the image **and where**?	for **every** object: a class + a **bounding box** + a confidence score
Segmentation (chapter 05)	which **pixels** belong to what?	a label per pixel

A **bounding box** is a rectangle `(x1, y1, x2, y2)`, exactly like `cv2.rectangle` in Week 1.

Detection is harder than classification because the number of objects varies, they come in every size, and they can overlap. Different architectures balance **accuracy versus speed** differently.




---

2. Two tools every detector needs

IoU: Intersection over Union (how good is a box?)


```
IoU = area of overlap / area of union        (0 = no overlap, 1 = perfect match)
```



A predicted box usually counts as **correct if IoU ≥ 0.5** with the true box.

NMS: Non-Maximum Suppression (remove duplicates)

Detectors usually fire **several overlapping boxes** on the same object. NMS cleans this up: 1. Take the box with the **highest score** and keep it. 2. Delete every other box that overlaps it with IoU > threshold (e.g. 0.5). 3. Repeat with the next highest remaining box.




```
from torchvision.ops import box_iou, nms
keep = nms(boxes, scores, iou_threshold=0.5)
```

---

3. R-CNN (2014): accurate but slow

Full name: **R**egion-based **C**onvolutional **N**eural **N**etwork (Ross Girshick et al.)

Process: 1. **Generate region proposals:** about **2,000** candidate boxes that *might* contain an object ("selective search" groups similar-coloured and similar-textured pixels, a Week 1-style method). 2. **Run a CNN on each region:** warp each crop to 227×227 and pass it through a CNN (AlexNet) → a feature vector. 3. **Classify and refine:** an SVM per class says what it is, and a regressor nudges the box to fit better.

Example (Key Concepts): an image of a dog → about 2,000 proposals, some on the dog, some on grass → each is classified → the "dog" boxes win, and NMS keeps the best one.

Strengths	Weaknesses
high accuracy (careful look at each region)	**very slow**: the CNN runs about **2,000 times per image** (around 47 s per image in the original paper)
first major CNN-based detector, **proved deep learning works for detection**	multi-stage pipeline, complicated to train

The faster successors (good to know)

- **Fast R-CNN (2015):** run the CNN **once** on the whole image, then cut each region out of the **feature map** ("RoI pooling").
- **Faster R-CNN (2015):** replace selective search with a small learned **Region Proposal Network (RPN)**. Everything becomes one network, close to real time.
- **Mask R-CNN (2017):** Faster R-CNN plus a **mask** per object (chapter 05).

---

4. YOLO (2016): You Only Look Once

Full name: You **O**nly **L**ook **O**nce (Joseph Redmon et al.)


Process: - Treats detection as **one regression problem**: predict the numbers (box coordinates + class probabilities) directly. - Divides the image into an **S × S grid** (7×7 in YOLOv1). Each cell predicts a few boxes (x, y, w, h, confidence) and class probabilities **for objects whose centre falls in that cell**. - **All in one forward pass** of a single CNN, followed by NMS.

Why it is fast: the whole image goes through the network **once**, with no thousands of crops. YOLOv1 ran at about **45 frames per second**.

Example (Key Concepts): a street scene → one pass → cars, people and traffic lights all boxed at once.


Strengths	Weaknesses
real-time speed	**less accurate for small objects**
sees the whole image, so fewer false alarms on background	each cell predicts only a few objects, so **crowded groups** of small objects get missed
made detection practical (**self-driving cars**, video)	coarse grid → less precise box edges

Notebook 04 race: tiny R-CNN vs tiny YOLO on a synthetic shapes dataset



	R-CNN-style (sliding windows)	YOLO-style (grid)
Regions per image	2,299	1 pass
Precision / recall	72.2% / 91.9%	99.5% / 99.0%
Speed	slow	**over 100× faster** (laptop CPU)

(Our toy R-CNN uses crude sliding-window proposals, which is why its precision is low. The *real* R-CNN is more accurate than YOLOv1. The speed gap is the point here.)



YOLO's weakness made visible: several small objects inside one grid cell, and the cell can only report one of them.

How to adapt YOLO for very small objects (Hard Q6)


1. **Higher input resolution** (e.g. 640 → 1280), so small objects cover more pixels.
2. **Finer grid / more output scales:** add a high-resolution detection head (feature pyramid, FPN).
3. **Small anchor boxes** matched to the object sizes in your data.
4. **Tiling:** cut a big image into overlapping tiles and detect on each.
5. **Augmentation:** copy-paste small objects, use mosaic images, oversample them.

---

5. SSD (2016): Single Shot MultiBox Detector

Full name: Single **S**hot Multi**B**ox **D**etector (Wei Liu et al.)

Process: - One pass like YOLO (**single shot**), **but** it makes predictions from **several feature maps of different sizes**. - **Early, big maps** (38×38, fine detail) → detect **small** objects. - **Late, small maps** (3×3, 1×1, large receptive field) → detect **large** objects. - Each map position has several **default boxes** (anchors) of different shapes. SSD300 checks **8,732** default boxes in total.



Example (Key Concepts): a **small cat and a large cat** in the same image: the fine map catches the small one, the coarse map the large one.

Strengths	Weaknesses
faster than R-CNN, competitive accuracy	slightly less accurate than R-CNN-family models on very complex scenes
handles **small and large objects at the same time**	very small objects are still hard (early maps carry little meaning)
widely used in **mobile vision** (e.g. MobileNet-SSD)	

---

6. Key takeaways and the "which one would you use?" question

	R-CNN	YOLO	SSD
Passes	about 2,000 CNN runs	**1**	**1**
Speed	slow	**fastest**	fast
Accuracy	**highest**	lower (small objects)	good, across scales
Remember as	research breakthrough	real-time practical	balanced

Medical imaging → R-CNN family (Faster R-CNN)

- Tumours and lesions demand **high accuracy and careful localisation**.
- **False negatives (missing a tumour) are unacceptable.**
- Analysis is **offline**: a few seconds per scan is fine.

- *Example:* detecting small tumours in MRI scans.

Autonomous driving → YOLO (or SSD)

- Must detect pedestrians, vehicles and signs in **real time** (many frames per second).
- One pass = high speed. SSD adds good multi-scale detection (near and far objects).
- *Example:* a pedestrian stepping into the road. A slightly less precise box **now** beats a perfect box **too late**.

  Key insight: medical imaging: accuracy > speed → R-CNN. Driving: speed > accuracy → YOLO/SSD. The choice depends on the application's **tolerance for errors** versus its **need for real-time speed**.

Try a real detector

The project folder (`../project/project2_...ipynb`) runs a real pretrained **YOLOv8** on a street photo with `ultralytics`:

```
from ultralytics import YOLO
results = YOLO("yolov8n.pt")("bus.jpg")
results[0].show()
```

Check yourself

1. What does detection output that classification doesn't?
2. Box A and box B each have area 100 and overlap by 50. What is the IoU?
3. Why is R-CNN slow?
4. Why is YOLO fast? What is its main weakness?
5. How does SSD handle different object sizes?
6. Which detector for a tumour-detection system? For a self-driving car? Why?

Answers

1. Where each object is (a bounding box), for every object, with a confidence score.
2. 50 / (100 + 100 − 50) = 50/150 ≈ 0.33.
3. It runs the CNN separately on about 2,000 region proposals per image.
4. One forward pass over the whole image treats detection as a single regression. Its weakness is small and crowded objects (few predictions per grid cell, coarse grid).
5. It predicts from several feature maps: big early maps for small objects, small late maps for large objects, each with default boxes.
6. Tumour: R-CNN family (accuracy matters most, missing one is unacceptable, offline). Car: YOLO/SSD (real-time speed matters most).

05 · Segmentation: FCN, U-Net, Mask R-CNN

Key Concepts covers: Semantic segmentation · FCN · U-Net · Skip connections · Encoder & decoder · Mask R-CNN · Why masks beat boxes in medicine


Notebook: `notebooks/05_segmentation_fcn_unet_mask_rcnn.ipynb`

---


1. What is segmentation?

> **Semantic segmentation = assigning a class label to *every pixel* in an image.**

The output is an image the same size as the input, where each pixel says "cat", "road" or "background". It is like Week 1 thresholding, but **learned**, and with many classes instead of just black and white.



Type	Question	Two touching coins become…
Semantic segmentation	what class is each pixel?	**one** "coin" region
Instance segmentation	which **object** does each pixel belong to?	coin #1 and coin #2, **separately**



Applications: medical imaging (tumours, organs, cells), autonomous driving (road, lanes, pedestrians), satellite imagery (buildings, roads, crops, flooding).

The core challenge: context and precision

- **Context (what):** to know a region is a *tumour* you need to see a wide area, so the image has to be shrunk down (deep layers, large receptive field).
- **Precision (where):** to draw its exact border you need **full resolution**, but shrinking threw that away.

Classification only needs the "what". Segmentation needs both at once. Every architecture below is a way to solve this tension.

---

2. FCN (2015): Fully Convolutional Network

Problem solved: classic CNNs end with **fully connected layers**, which **flatten** the feature maps. All spatial information is lost and the output is a single label for the whole image.

Innovation: replace the fully connected layers with convolutional layers (1×1 convolutions). The network is now **convolutional all the way through**, so the output is still a grid, with a class score at every location. Upsample that grid back to the image size → a **dense, pixel-wise prediction map**.

- **Key idea:** end-to-end segmentation using **only convolutional layers**.
- **Bonus:** with no fixed-size dense layer it accepts **any input size**.
- **Example (Key Concepts):** an image of a cat → a mask labelling each pixel "cat" or "background".


Strengths	Weaknesses
simple, effective, **first major CNN for segmentation**	**coarse predictions**, struggles with **fine boundaries**

Why are FCN predictions coarse?

The encoder downsamples by **32×** (five 2× poolings). A 224×224 image becomes a 7×7 grid of predictions. Blowing 7×7 back up to 224×224 is like enlarging a thumbnail: the **edges come out blobby**, and thin or small things vanish. FCN-16s and FCN-8s added some skips from earlier layers to help a bit.

---

3. U-Net (2015): encoder + decoder + skip connections



Originally designed for **biomedical** images (Ronneberger et al.), it is named after its **U shape**.

Encoder (the downsampling path, left side)

- Repeated **conv + max pooling**, so the image gets smaller and the channels increase.
- Captures **context and high-level meaning**: "this region looks like a tumour".
- **Analogy:** compressing a photo into a summary. You lose fine detail but keep the big picture.

Decoder (the upsampling path, right side)

- **Transposed convolutions** (learned upsampling) gradually restore the original resolution.
- Rebuilds a **pixel-level prediction**.
- **Analogy:** expanding the summary back to full resolution, now with a label on every pixel.

Skip connections (the horizontal bridges)


- At each level, the encoder's feature map is **copied and concatenated** onto the decoder's feature map of the same size.
- **Why they help (Key Concepts):**
- **Preserve fine detail.** Downsampling lost the exact edges, and the skip brings them back from the early layers.
- **Combine low-level and high-level features.** Early layers know *edges and textures* (where), deep layers know *what the object is*. The decoder gets both.
- **Improve gradient flow.** Gradients have a short path back to early layers.

  In short: the encoder compresses for **context** (*what*), the decoder reconstructs for **precision** (*where*), and skip connections bridge the two so no important detail is

lost.

Example: segmenting a tumour in an MRI. The encoder recognises "tissue that looks like a tumour" but loses the exact boundary. The skips bring back the original edges, and the decoder combines both → **sharp, accurate tumour borders**.

Notebook 05: FCN vs U-Net on the same data



	FCN-style	U-Net
mean IoU	0.824	**0.941**
accuracy on **boundary pixels**	77.2%	**99.2%**

Look at the triangles' sharp corners: FCN rounds them off, U-Net keeps them.

Why U-Net is the standard in medical imaging

1. **Precise boundaries:** tumour and organ outlines are needed for measurement and treatment planning.
2. **Small structures:** cells, vessels and small lesions survive thanks to the skips.

3. **Small datasets:** works well with a few hundred labelled scans (plus heavy augmentation), and medical labels are expensive.
4. **Every pixel matters:** the output is a full mask, not a box.

Skip connections in ResNet vs U-Net (Hard Q7)

	ResNet	U-Net
Operation	**add**: F(x) + x	**concatenate** encoder map onto decoder map
Connects	input and output of a **block** (short, same level)	encoder ↔ decoder at the **same resolution** (long, across the U)
Main purpose	**gradient flow → train very deep nets**	**carry spatial detail → sharp boundaries**

Both are "shortcuts that let information skip layers", used for different reasons.

Satellite imagery (Hard Q9)

Choose a **U-Net** (often with a ResNet/EfficientNet encoder). Satellite tiles are large and full of thin, small structures (roads, field edges, buildings) that need precise boundaries. Labelled data is limited, and the image is split into tiles. Use **Mask R-CNN** if you need individual instances (counting buildings).

---

4. Mask R-CNN (2017): detection + a mask for every object

The limitation it addresses: detectors output only **boxes + labels**, and many applications need the **exact shape** of each individual object. That is **instance segmentation**.

Architecture: built on **Faster R-CNN**, plus a **mask branch** for each Region of Interest (RoI).

How it works (4 steps)

1. **Region Proposal Network (RPN):** a small network sliding over the backbone's feature map that **suggests candidate object regions** ("something is probably here"), with no slow selective search.
2. **RoI Align:** cuts out an **exactly aligned** fixed-size feature patch (e.g. 7×7 or 14×14) for each proposal.
3. **Classification + bounding-box regression:** what is it, plus a refined box.
4. **Mask branch:** a small FCN that predicts a **binary mask** (e.g. 28×28) for each object, i.e. *which pixels inside the box belong to it*.

Outputs for each object (three things): a **bounding box** (where) · a **class label** (what) · a **pixel-level mask** (exact shape).

RoI Pooling vs RoI Align (why RoI Align was introduced)

- A proposal box rarely lines up with the feature-map grid. For example, it might start at x = 3.7 cells.
- **RoI Pooling** (Fast/Faster R-CNN) **rounds** these positions to whole numbers (**quantisation**). Each feature-map cell covers about 16–32 pixels, so rounding shifts the

box by many pixels. That doesn't matter much for a class label, but it **ruins a pixel-accurate mask**.
- **RoI Align does not round**. It samples the feature map at the exact (fractional) positions using **bilinear interpolation** (Week 1 Day 2!). The features stay aligned with the object, which gives much better masks.

Handling overlapping objects (crowds)

Each person gets their **own RoI and their own mask**, predicted separately. Overlapping people are therefore **separated**, which semantic segmentation (one "person" blob) cannot do.

Applications

- **Medical:** tumour segmentation, organ boundaries.
- **Autonomous driving:** pedestrians, vehicles and lane markings with exact shapes.
- **Crowd analysis:** separating overlapping people.
- Also: robotics (grasping an object by its exact outline), photo editing (cut out a person), agriculture (individual fruit and leaves), retail shelf counting.

Key contributions: extended detection to **instance segmentation**, introduced **RoI Align**, and became a **benchmark** model.

---

5. Why pixel masks beat bounding boxes in medical imaging

1. **Precise localisation:** tumours and organs are irregular, and a rectangle includes healthy tissue.
2. **Quantitative analysis:** masks give the true **area and volume** (e.g. tumour volume for **chemotherapy dosage**). Boxes overestimate because they include background.
3. **Clinical decisions:** surgery and radiotherapy planning, and monitoring growth, need exact borders and spread.
4. **Overlaps:** structures inside structures (a tumour within an organ) can't be separated by boxes.

   Boxes say "there's a tumour **here**". Masks say exactly **which pixels**, **how big** and **how it spreads**.

Check yourself

1. Semantic vs instance segmentation: what's the difference?
2. Why does segmentation need both context and precision?
3. What did FCN replace, and with what? Why are its outputs coarse?
4. Roles of the encoder, decoder and skip connections in U-Net?
5. How does ResNet's skip differ from U-Net's?
6. Mask R-CNN: what are the three outputs per object? What does the RPN do? Why RoI Align?

Answers

1. Semantic gives each pixel a class (touching objects merge). Instance separates individual objects.
2. Context to know what an object is (needs a wide view and downsampling). Precision to know exactly which pixels (needs full resolution).
3. It replaced the fully connected layers with convolutional layers. Coarse because it predicts at 1/32 resolution and upsamples, so edges are blurry.
4. Encoder: downsample → context (what). Decoder: upsample → precision (where). Skips: copy fine detail from the encoder to the decoder and improve gradient flow.
5. ResNet adds (short, for gradient flow and depth). U-Net concatenates (long, across the U, for spatial detail).
6. Box, class and mask. The RPN proposes candidate regions. RoI Align avoids RoI Pooling's rounding by using bilinear interpolation, so features align with pixels and masks are accurate.

06 · Video & sequence models: RNN, LSTM, CNN + LSTM

Key Concepts covers: Sequence modelling for video · CNNs for spatial features · RNNs/LSTMs for temporal dependencies · CNN + LSTM pipeline · RNN vs LSTM · What CNNs and LSTMs capture · Features captured by RNNs

Notebook: `notebooks/06_video_sequence_models_rnn_lstm.ipynb`

---


1. What is sequence modelling?

> **Sequence modelling** = building models that understand and predict data that comes **in order** (steps over time).

Unlike a single photo, in a sequence **the current element depends on what came before** (*temporal dependencies*). Examples: - **Text:** a word's meaning depends on the earlier words. - **Speech, music, sensor readings, stock prices.** - **Video:** a sequence of frames (images over time).

Why video is hard: two kinds of information

	Spatial	Temporal
Question	**what** is in each frame?	**how** does it change across frames?
Examples	a hand, a ball, a car, edges, textures	motion, order, speed, rhythm
Tool	**CNN**	**RNN / LSTM**




*Notebook 06's toy videos: a square moving left vs moving right. Any **single frame** looks the same for both classes, so only the **order** tells them apart.*


Why can't a CNN alone do it?

A CNN looks at **one frame at a time** and has no memory of the previous frame. It can recognise a *hand shape* in one frame but not the *waving gesture* across frames. Even averaging all the frames throws the order away: "left then right" and "right then left" average to the same thing.

---

2. RNN: Recurrent Neural Network






How it works: - Processes the sequence **step by step** (frame 1, then frame 2, ...). - Keeps a **hidden state h**, a small memory vector carried forward. - At every step it combines **the new input** with **the previous memory**:

```
h_t = tanh( W · x_t + U · h_(t−1) + b )
```

- The **same weights** (W, U) are used at every step, just as a conv kernel is reused at every position.

What RNNs capture (Key Concepts): 1. **Sequential patterns:** order ("the cat" comes before "sat on the mat"). 2. **Temporal dependencies:** how a hand moves frame to frame. 3. **Context:** the hidden state carries the meaning of earlier inputs ("bank" means a riverbank if "river" came earlier). 4. **Short-term memory:** good at **recent** steps (the next note in a melody from the last few notes).

Limitations: - **Vanishing gradient over long sequences.** Information from early steps gets squashed by `tanh` and multiplied by U **again at every step**, so it fades away (chapter 01's vanishing-gradient problem, but through **time**). - **Slow training:** steps must be processed in order, one after another (not parallel).



Notebook 06: the trace of one event inside a plain RNN's memory shrinks by about 10× every few steps. After 25 steps it is essentially gone.

---

3. LSTM: Long Short-Term Memory

A special RNN designed to **remember over long sequences**.

Innovation: besides h, an LSTM keeps a separate **cell state c**, a "conveyor belt" of memory that runs straight through time. Information on the belt is changed only by **gentle additions and gated erasing**, not squashed every step. Three **gates** (each a value from 0 = block to 1 = let through, computed with a sigmoid) control it:

Gate	Decides	Everyday analogy
Forget gate f	what **old** information to **discard** from c	wiping an old note off the whiteboard
Input gate i	what **new** information to **store** in c	writing a new note on the whiteboard
Output gate o	what information to **pass on** as the output h	deciding which notes to read out right now

```
c_t = f ⊙ c_(t−1)  +  i ⊙ c̃_t        ← keep some old, add some new
h_t = o ⊙ tanh(c_t)                   ← reveal part of it
```

Why this solves vanishing gradients: when the forget gate is near 1, `c_t ≈ c_(t−1) + …`, so memory (and the gradient) flows back through time **almost unchanged**. That is the same trick as ResNet's "+x" highway, applied across time.

Strengths: - remembers information **over long sequences**; - handles **variable-length input** (short and long videos).

Notebook 06: a memory test

Each sequence is T = 50 steps of random noise, except that the **first** step secretly encodes a class (0–3). The model must report that class at the end, so it has to carry information from step 1 all the way through.

Model	Accuracy
plain RNN	24.6% (= guessing among 4 classes: it forgot)
LSTM	**99.8%**


RNN vs LSTM (table from Key Concepts)

Aspect	RNN	LSTM
Memory	**short-term**	**long-term** (long dependencies)
Problem	vanishing gradients	**solves** vanishing gradients (gates + cell state)
Best for	simple, short sequences	complex, long sequences
Example	next word in a short sentence	context across a long paragraph or a video

When is a plain RNN still enough? Short sequences where only the last few steps matter: next character prediction, smoothing the last few sensor readings, short gesture snippets. It is also smaller and faster than an LSTM. (A **GRU** is a lighter LSTM with 2 gates, a good middle ground.)

---

4. The CNN + LSTM pipeline




1. **CNN** extracts **spatial features** from **each frame** (the same CNN, shared weights). Each frame becomes a feature vector.
2. **LSTM** processes the **sequence of feature vectors** across frames.
3. **Output layer** predicts the action or gesture class from the LSTM's last hidden state.


Result: an **end-to-end** system that understands **what** is in each frame and **how** it changes.


What does each part capture? (Key Concepts)

	CNN, "the photographer"	LSTM, "the storyteller"
Captures	**objects** (hand, ball, car), **shapes and edges**, **textures**	**motion** (left → right), **order** (first → last), **dynamics** (speed, rhythm)
Gesture example	the hand shape in each frame	the sequence of movements → "wave"
Action example	a person and a ball	the sequence → "throwing a ball"

Notebook 06: three models on the left/right/up/down motion videos







Model	Sees	Accuracy
SingleFrame (CNN on one frame)	no time	58%
FrameAverage (CNN on every frame, averaged)	all frames but **no order**	30%
CNN + LSTM	frames **in order**	**100%**

That is the whole point in one table: **order matters, and only the LSTM uses it.**

```
class CNNLSTM(nn.Module):
    def __init__(self):
        super().__init__()
        self.cnn  = nn.Sequential(nn.Conv2d(1, 8, 3, padding=1), nn.ReLU(),
nn.MaxPool2d(2),
                                  nn.Flatten(), nn.Linear(8 * 16 * 16, 32))
        self.lstm = nn.LSTM(32, 64, batch_first=True)
        self.head = nn.Linear(64, 4)
    def forward(self, video):                    # video: (N, T, 1, 32, 32)
        N, T = video.shape[:2]
        feats = self.cnn(video.flatten(0, 1))    # every frame through the SAME CNN
        out, (h, c) = self.lstm(feats.view(N, T, -1))
        return self.head(h[-1])                  # classify from the final memory
```

Applications

- **Action recognition:** sports analysis, surveillance.
- **Gesture recognition:** sign language, human–computer interaction.
- **Video captioning:** describe a clip in words.
- **Autonomous driving:** predicting how pedestrians and cars will move.

In short: CNNs capture the **what** (spatial), RNNs/LSTMs capture the **when / how** (temporal). Together they make video understanding possible.

Check yourself

1. What is a temporal dependency? Give a video example.
2. Why can't a CNN alone recognise a waving gesture?
3. What does an RNN's hidden state do? What is its main limitation?
4. Name the three LSTM gates and what each one does.
5. Why does the LSTM remember longer than an RNN?
6. In a CNN + LSTM, what does each part contribute?

Answers

1. The current element depends on earlier ones. For example, whether a hand is "waving" depends on where it was in the previous frames.
2. It sees one frame at a time with no memory of order or motion. One frame shows a hand, not a wave.
3. It carries a summary of past inputs forward to the next step. Over long sequences that information fades (vanishing gradient), so it is only short-term memory.
4. Forget: what to discard from memory. Input: what new information to store. Output: what to pass on as the output.
5. The cell state is updated by addition and gated forgetting, not squashed every step, so information and gradients flow through time almost unchanged when the forget gate is about 1.
6. CNN: spatial features of each frame (objects, shapes, textures). LSTM: temporal pattern across frames (motion, order, speed), leading to the action class.

07 · Attention & Vision Transformers (ViT)

Key Concepts covers: Attention mechanism (Q, K, V) · Vision Transformer steps · Benefits of ViT · Applications · Why patches help capture global context


Notebook: `notebooks/07_vision_transformers_attention.ipynb` · course originals: `course-files/CV-Week3-vit1.ipynb`, `CV-Week3-vit2.ipynb`

---

1. Why something beyond CNNs?

CNNs are excellent at **local** features, but each layer only sees a small window (3×3). To connect the **top-left corner with the bottom-right corner**, information has to travel through many layers. CNNs **struggle with long-range dependencies**.

Transformers were invented for language (2017, "Attention Is All You Need"). Their **attention mechanism** lets **every element look at every other element directly**, in one step. The **Vision Transformer (ViT, 2020)** applies the same idea to images.



*Notebook 07: in layer 1, a CNN output sees only a 3×3 window, while a ViT patch can attend to **every** patch in the image.*

---


2. Attention: a soft lookup


> **Attention computes how relevant every element is to every other element, then mixes their information accordingly.**

Every element (word or image patch) produces three vectors:

	Name	Plain meaning	Library analogy
Q	**Query**	what I am **looking for**	your search request
K	**Key**	what I **contain / offer** (a label)	the titles on the book spines
V	**Value**	the actual **information** I hand over	the contents of the books

Process: 1. **Compare** the query with every key (dot product) → **similarity scores**. 2. **Softmax** the scores → **weights** that add up to 1. 3. Output = **weighted sum of the values**.






```
Attention(Q, K, V) = softmax( Q·Kᵀ / √d ) · V
```

(The **÷ √d**, where d is the vector length, keeps the scores from getting huge, which would make softmax too spiky.)

The "bank" example (Key Concepts): in "*the river bank flooded*", the word *bank* attends most strongly to *river*, so its output representation leans towards "riverbank". In "*the bank approved my loan*" it would attend to *loan* / *approved* → "money bank". **Same word, different meaning, decided by context.** Notebook 07 computes this with real numbers.


Benefits: - captures **long-range dependencies** (pixels far apart but related); - **flexible:** it **learns** which parts matter, separately for each input (a CNN's kernel is fixed after training).

Self-attention = Q, K and V all come from the **same** sequence (every patch attends to every patch). **Multi-head attention** runs several attentions in parallel, so different heads can focus on different relationships.

```
attn = nn.MultiheadAttention(embed_dim=64, num_heads=4, batch_first=True)
out, weights = attn(x, x, x)      # self-attention: Q = K = V = x
```

---

3. The Vision Transformer, step by step



224×224 image, 16×16 patches → 14×14 = 196 tokens. Every token can attend to every other token from layer 1 → global context.

Step 1: split the image into patches

- e.g. **16×16-pixel patches**. A 224×224 image → 14 × 14 = **196 patches**.
- Each patch is **flattened** (16·16·3 = 768 numbers) and passed through a **linear layer** (the "**patch embedding**") → a vector called a **token**, like a word in a sentence.


image with 16×16 patch grid



first 16 patches in reading order → a SEQUENCE




patch 8×8 → 256 tokens



patch 16×16 → 64 tokens



patch 32×32 → 16 tokens



Smaller patches → more tokens → finer detail but much more computation (attention compares every pair, so cost grows with tokens²).

```
 # patch embedding in one line: a conv whose kernel size = stride = patch size
patch_embed = nn.Conv2d(3, 768, kernel_size=16, stride=16)    # (1,3,224,224) → (1,768,14,14)
tokens = patch_embed(img).flatten(2).transpose(1, 2)           # → (1, 196, 768)
```

Step 1½: position embeddings


Attention by itself has **no idea of order**: shuffle the patches and it gives the same result. So a learned **position embedding** is **added** to each token, telling the model *where* each patch came from.

Step 2: transformer encoder

A stack of identical layers, each containing: - **multi-head self-attention:** every patch looks at every patch (**global context**); - an **MLP** (two dense layers) applied to each token; - **residual connections** (from ResNet!) and layer normalisation around both.

Step 3: the classification token [CLS]

- An extra learnable token is placed at the **front** of the sequence.
- It owns no patch of its own. Through attention it **gathers a summary of the whole image**.
- Its final output goes to a small classifier → "cat" / "dog".



Notebook 07: where the [CLS] token "looks" in our tiny ViT's last block. For some digits it focuses on one or two stroke patches; for others it is spread out, because earlier layers have already mixed information between patches. Attention maps are a useful hint, not a full explanation. The key point: the model chooses where to look by itself.

> **Key idea:** apply the transformer architecture **directly to images**, bypassing convolutions.

---

4. Why split the image into patches? (Key Concepts question)

1. **Treats the image like a sequence.** Patches become tokens, like words, so the transformer's attention can be applied across them.
2. **Captures long-range dependencies.** Any patch can directly compare itself to any other patch, from the very first layer. *Zebra example:* stripes on the head and on the legs are related, and attention links them directly.
3. **Reduces complexity.** Attention compares **every pair**. Using individual pixels (224 × 224 = 50,176 tokens) would mean about 2.5 **billion** pairs, while 196 patches give only about 38,000. Patches make it **affordable**.
4. **Balances local and global. Inside** each patch: local detail (edges, texture). **Across** patches: attention builds the global picture (shape, scene).

   In short: patches turn an image into a sequence, so transformers can connect distant regions and capture global context efficiently.

---

5. CNN vs ViT

	CNN	Vision Transformer
Basic operation	convolution (local window)	self-attention (all patches)
View in layer 1	**local** (3×3)	**global** (every patch)
Built-in assumptions	"nearby pixels are related", "patterns can be anywhere"	very few, so it has to learn them
Data needed	works with **less data**	needs **large datasets** (or pretraining) to shine
Scaling	improves, then saturates	**keeps improving** with more data and size
Weakness	long-range relationships	data-hungry, cost grows with tokens²

Honest result from notebook 07: on our small digits dataset, a tiny ViT got **96.9%** and a tiny CNN **98.1%**. With little data the CNN's built-in assumptions ("look locally") are a free head start. The original ViT paper beat CNNs only after pretraining on **hundreds of millions of images**. This is exactly why **hybrid models** (CNN layers first, transformer on top) are popular.

Benefits of ViT (Key Concepts)

- captures **global context** better than CNNs;
- **scales well** with large datasets;
- **flexible:** classification, detection (DETR), segmentation (SegFormer);
- inspired many **hybrid** models (CNN + Transformer).

Applications

- image classification (ImageNet benchmarks);
- **medical imaging** (global patterns across a whole scan);
- **video understanding** (add **temporal attention** across frames, replacing the LSTM of chapter 06);

- **multimodal** vision + language (image captioning, CLIP, visual question answering).

  Impact: shifted computer vision from **CNN-centric** to **transformer-centric** approaches.

---

6. How the course's own ViT notebooks fit in

`course-files/CV-Week3-vit1.ipynb` and `vit2.ipynb` load an image, cut it into patches and display them as a grid. That is Step 1 above. They expect a `cat.jpg` that was not in the zip, so our notebook 07 runs the same exercises on `../../week-1/code/sample.jpg`. Any photo works.

Check yourself

1. What do Query, Key and Value mean, in plain words?
2. Write the attention formula. Why divide by √d?
3. A 224×224 image with 16×16 patches gives how many tokens? With 32×32 patches?
4. Why does ViT need position embeddings?
5. What is the [CLS] token for?
6. Give four reasons for splitting the image into patches.
7. When would you still pick a CNN over a ViT?

Answers

1. Query: what I'm looking for. Key: what each element offers (used for matching). Value: the information actually passed on.
2. softmax($QK^T/\sqrt{d}$)·V. Dividing keeps the dot products from growing with the vector length, so softmax doesn't become extremely peaked.
3. 14 × 14 = 196 with 16×16 patches; 7 × 7 = 49 with 32×32 patches.
4. Attention ignores order. Without position embeddings, shuffled patches would look the same.
5. A learnable summary token that gathers information from all patches through attention. Its output is used for classification.
6. Image becomes a sequence of tokens · direct long-range comparisons · far fewer tokens than pixels, so it is affordable · local detail inside patches, global context across them.
7. Small datasets, limited compute, or edge and mobile devices, where the CNN's built-in locality makes it data-efficient and cheap.

01 · Neural-network building blocks

From Week 1's hand-made kernels to *learned* kernels

Covers (Week 3 Key Concepts): fully connected vs convolutional layers · ReLU · Dropout · pooling · how a network learns. **Questions answered here:** Easy 5–7 · Hard 1–2 · Week-1 Q "role of kernels in CNNs".

Everything later this week (LeNet, ResNet, YOLO, U-Net, LSTMs, ViT) is built from the few pieces in this notebook. Run each cell with **Shift + Enter** and read the text around it.

> **The one-sentence version:** a CNN is a stack of Week-1 convolutions, but instead of a human choosing the kernel numbers (like Sobel), **the computer learns them from examples**.

0 · Setup

Install once, from a terminal: `pip install torch torchvision scikit-learn matplotlib opencv-python`. On Google Colab everything is already installed.

```
%matplotlib inline
import numpy as np
import matplotlib.pyplot as plt
import torch
import torch.nn as nn
import torch.nn.functional as F
import cv2

torch.manual_seed(0)
np.random.seed(0)
print("torch", torch.__version__, "| GPU available:", torch.cuda.is_available())
```

```
torch 2.14.1+cu130 | GPU available: False
```

1 · A convolution layer *is* Week-1 convolution

PyTorch's `nn.Conv2d` slides kernels over an image exactly like `cv2.filter2D`. To prove it, we create a conv layer, **paste the Sobel-X kernel into its weights by hand**, and compare it with OpenCV.

- `nn.Conv2d(in_channels=1, out_channels=1, kernel_size=3, padding=1, bias=False)` means 1 input channel (grayscale) and 1 kernel of size 3×3. `padding=1` keeps the output the same size, like OpenCV's border handling.
- PyTorch images are shaped **(batch, channels, height, width)**, unlike OpenCV's (height, width, channels).

```
# A small test image: dark left half, bright right half -> one vertical edge
img = np.zeros((8, 8), np.float32)
img[:, 4:] = 200
```

```
sobel_x = np.array([[-1, 0, 1],
                    [-2, 0, 2],
                    [-1, 0, 1]], np.float32)

conv = nn.Conv2d(1, 1, kernel_size=3, padding=1, bias=False)
with torch.no_grad():
    conv.weight[:] = torch.from_numpy(sobel_x)          # paste Sobel into the layer

x = torch.from_numpy(img)[None, None]                   # (8,8) -> (1,1,8,8) = (batch, channel,
H, W)
torch_out = conv(x)[0, 0].detach().numpy()
cv_out = cv2.filter2D(img, -1, sobel_x, borderType=cv2.BORDER_CONSTANT)

print("PyTorch conv layer output (row 0):", torch_out[0])
print("OpenCV filter2D output    (row 0):", cv_out[0])
print("Same result?", np.allclose(torch_out, cv_out))
```

```
PyTorch conv layer output (row 0): [   0.    0.    0.  600.  600.    0.    0. -600.]
OpenCV filter2D output    (row 0): [   0.    0.    0.  600.  600.    0.    0. -600.]
Same result? True
```

Same numbers. The only difference in a real CNN is that the 9 kernel numbers start **random** and are adjusted during training until they become useful detectors. A CNN layer also has **many** kernels (e.g. 64), each producing its own **feature map**.

2 · Fully connected (dense) layer vs convolutional layer

	Fully connected (`nn.Linear`)	Convolutional (`nn.Conv2d`)
Connects to	**every** input value	a small **local** patch (receptive field)
Input	a **flat vector** (spatial layout lost)	an **image** (H × W × C kept)
Weights	different for every position	the **same kernel reused everywhere** (weight sharing)
Good at	combining everything for the final decision	finding local patterns: edges, textures, shapes
Parameters	**huge**	**few**

Let's **count the parameters** (the learnable numbers) for a small 32×32 colour image:

```
def n_params(layer):
    return sum(p.numel() for p in layer.parameters())

fc = nn.Linear(32 * 32 * 3, 100)                    # 3072 inputs -> 100 neurons
cv = nn.Conv2d(3, 100, kernel_size=3, padding=1)    # 100 kernels of size 3x3x3

print(f"Fully connected: {n_params(fc):>9,} parameters  (each neuron sees all 3,072 pixel
values)")
print(f"Convolutional  : {n_params(cv):>9,} parameters  (each kernel is just 3x3x3 = 27 weights +
1 bias)")
print(f"-> the FC layer needs {n_params(fc) / n_params(cv):.0f}x more parameters")

big_fc = 224 * 224 * 3 * 1000
print(f"\nFor a 224x224 photo, an FC layer of 1000 neurons would need {big_fc / 1e6:.0f} million
weights!")
```

```
Fully connected:   307,300 parameters  (each neuron sees all 3,072 pixel values)
Convolutional  :     2,800 parameters  (each kernel is just 3x3x3 = 27 weights + 1 bias)
-> the FC layer needs 110x more parameters

For a 224x224 photo, an FC layer of 1000 neurons would need 151 million weights!
```


Translation invariance: "find the pattern wherever it is"

Because the **same** kernel slides over every position, a pattern produces the **same response wherever it appears**: move the pattern and the response moves with it. A fully connected layer has separate weights per pixel, so a moved pattern looks like a completely different input.

```
pattern = np.zeros((12, 12), np.float32); pattern[3:6, 2:5] = 1          # a small square, top-left
moved = np.zeros((12, 12), np.float32);   moved[7:10, 7:10] = 1          # same square, bottom-right

with torch.no_grad():
    k = nn.Conv2d(1, 1, 3, padding=1, bias=False)
    k.weight[:] = 1.0                                                     # a simple "blob detector"
    r1 = k(torch.from_numpy(pattern)[None, None])[0, 0].numpy()
    r2 = k(torch.from_numpy(moved)[None, None])[0, 0].numpy()

fig, ax = plt.subplots(1, 4, figsize=(12, 3))
for a, im, t in zip(ax, [pattern, r1, moved, r2],
                    ["square at top-left", f"conv response (max {r1.max():.0f})",
                     "same square moved", f"conv response (max {r2.max():.0f})"]):
    a.imshow(im, cmap="viridis"); a.set_title(t); a.axis("off")
plt.tight_layout(); plt.show()
print("Strongest response is identical:", r1.max() == r2.max(), "- it just moved along with the square.")
```




```
Strongest response is identical: True - it just moved along with the square.
```

In practice CNNs use **convolutional layers for feature extraction** and **fully connected layers at the end for the decision** ("this is a 7"). You'll see that shape in LeNet, AlexNet and VGG in notebook 02.

3 · Activation functions: why ReLU won

Without an activation function, stacking layers is pointless: a linear layer followed by another linear layer is still just one linear layer. **Activations add non-linearity**, so networks can learn curved, complex patterns.

Function	Formula	Output range
Sigmoid	$1 / (1 + e^{-x})$	0 to 1


Function	Formula	Output range
Tanh	$(e^x - e^{-x})/(e^x + e^{-x})$	−1 to 1
ReLU	**max(0, x)**	0 to ∞

ReLU: "if the input is positive, keep it; if negative, output zero." It's like a filter that only lets positive signals through.

```
x = torch.linspace(-6, 6, 400, requires_grad=True)
funcs = {"sigmoid": torch.sigmoid, "tanh": torch.tanh, "ReLU": torch.relu}

fig, ax = plt.subplots(1, 2, figsize=(11, 3.6))
for name, f in funcs.items():
    y = f(x)
    grad, = torch.autograd.grad(y.sum(), x)          # the slope (derivative) at every x
    ax[0].plot(x.detach(), y.detach(), label=name, lw=2)
    ax[1].plot(x.detach(), grad, label=name, lw=2)
ax[0].set_title("Activation output"); ax[1].set_title("Its slope (gradient) - what training
uses")
for a in ax:
    a.axhline(0, color="gray", lw=0.5); a.legend(); a.grid(alpha=0.3)
plt.tight_layout(); plt.show()

print("ReLU on [-3, -1, 0, 2, 5] ->", torch.relu(torch.tensor([-3., -1., 0., 2., 5.])).tolist())
```




```
ReLU on [-3, -1, 0, 2, 5] -> [0.0, 0.0, 0.0, 2.0, 5.0]
```

Look at the **right plot**:

- **Sigmoid's slope is never more than 0.25**, and it's almost 0 for big or small inputs ("saturation"). Tanh's slope also dies at the ends.
- **ReLU's slope is exactly 1 for every positive input.**

Why that matters: the vanishing gradient problem

Training works by **backpropagation**. The error signal travels backwards through the layers and gets **multiplied by each layer's slope** on the way. Multiply by ≤ 0.25 again and again and the signal **shrinks to almost nothing**, so the early layers stop learning. With ReLU, positive paths multiply by 1, so the signal survives.


```
layers = np.arange(1, 21)
print("Best-case gradient left after N layers (sigmoid slope <= 0.25, ReLU slope = 1):\n")
for n in [1, 2, 5, 10, 20]:
    print(f"  {n:>2} layers: sigmoid {0.25 ** n:.2e}   ReLU {1.0 ** n:.0f}")

plt.figure(figsize=(6, 3.2))
```

```
plt.semilogy(layers, 0.25 ** layers, "o-", label="sigmoid (best case 0.25 per layer)")
plt.semilogy(layers, np.ones_like(layers, dtype=float), "s-", label="ReLU (1 per active layer)")
plt.xlabel("number of layers the signal passes through"); plt.ylabel("gradient size (log scale)")
plt.title("Vanishing gradient"); plt.legend(); plt.grid(alpha=0.3); plt.show()
```

```
Best-case gradient left after N layers (sigmoid slope <= 0.25, ReLU slope = 1):

   1 layers: sigmoid 2.50e-01   ReLU 1
   2 layers: sigmoid 6.25e-02   ReLU 1
   5 layers: sigmoid 9.77e-04   ReLU 1
  10 layers: sigmoid 9.54e-07   ReLU 1
  20 layers: sigmoid 9.09e-13   ReLU 1
```



After only 10 sigmoid layers the gradient is a **millionth** of its size. This is one of the reasons **AlexNet (2012)** switched to ReLU: it trained about **6× faster** than tanh in the original paper, and deeper networks became practical.

> Exam phrasing: *ReLU introduces non-linearity, is cheap to compute (just max(0, x)), and its gradient is 1 for positive inputs, so it reduces the vanishing-gradient problem.* One caveat: neurons stuck at negative inputs output 0 forever (the "dying ReLU" problem). Variants such as Leaky ReLU fix this.

4 · Dropout: randomly benching neurons during training

Definition: a **regularization** technique (a way to prevent **overfitting**, i.e. memorising the training data instead of learning general rules). **How:** during each **training** step, each neuron is switched off (set to 0) with probability *p*. A different random set is dropped each time. **Analogy:** a team where random members sit out each practice, so everyone has to learn to contribute and nobody becomes a single point of failure.

The Key Concepts example: *a layer has 10 neurons and dropout rate 0.3, so about 3 are ignored in each training pass.*

```
drop = nn.Dropout(p=0.3)
activations = torch.ones(10)                    # 10 neurons, all outputting 1.0

drop.train()                                    # TRAINING mode: dropout is active
```

```
for step in range(3):
    out = drop(activations)
    print(f"training pass {step + 1}: {np.round(out.numpy(), 2)}  -> {int((out == 0).sum())}
dropped")

drop.eval()                                          # EVALUATION / test mode: dropout switched
OFF
print("\ntest time      :", drop(activations).numpy())
```

```
training pass 1: [1.43 1.43 0.   1.43 1.43 1.43 1.43 1.43 1.43 1.43]  -> 1 dropped
training pass 2: [1.43 1.43 0.   1.43 1.43 1.43 1.43 1.43 0.   0.  ]  -> 3 dropped
training pass 3: [1.43 1.43 1.43 0.   0.   1.43 0.   1.43 1.43 1.43]  -> 3 dropped

test time      : [1. 1. 1. 1. 1. 1. 1. 1. 1. 1.]
```

Two details worth knowing:

1. The surviving neurons are **scaled up by 1/(1 − p)** (here 1/0.7 ≈ 1.43). This keeps the *average* signal the same as at test time.
2. Dropout is **only active during training**. `model.train()` turns it on and `model.eval()` turns it off. Forgetting `model.eval()` before testing is a classic bug.

Why it generalises better (Hard Q1): the network can't rely on one specific neuron ("the neuron that detects *this exact* cat photo's ear"), because that neuron may be missing. It has to spread knowledge across many neurons and learn **robust features** that work even with parts missing. That's exactly what's needed on new, unseen images. Below we test it on a deliberately overfitting-prone setup.

```
from sklearn.datasets import load_digits
from sklearn.model_selection import train_test_split

digits = load_digits()                                       # 1,797 handwritten digits, 8x8
pixels, ships with sklearn
X = torch.tensor(digits.data, dtype=torch.float32) / 16.0    # pixel values 0..16 -> 0..1
y = torch.tensor(digits.target)

def train_and_test(p_drop, seed, n_train=60, epochs=500):
    # a BIG network + only 60 training images = a recipe for overfitting
    Xtr, Xte, ytr, yte = train_test_split(X, y, train_size=n_train, random_state=seed,
stratify=y)
    torch.manual_seed(seed)
    model = nn.Sequential(nn.Linear(64, 1024), nn.ReLU(), nn.Dropout(p_drop),
                          nn.Linear(1024, 1024), nn.ReLU(), nn.Dropout(p_drop),
                          nn.Linear(1024, 10))
    opt = torch.optim.Adam(model.parameters(), lr=1e-3)
    for _ in range(epochs):
        model.train()                                        # dropout ON
        loss = F.cross_entropy(model(Xtr), ytr)
        opt.zero_grad(); loss.backward(); opt.step()
    model.eval()                                             # dropout OFF for testing
    with torch.no_grad():
        train_acc = (model(Xtr).argmax(1) == ytr).float().mean().item()
        test_acc = (model(Xte).argmax(1) == yte).float().mean().item()
    return train_acc, test_acc

# Results vary from run to run, so average 5 runs (different data splits and starting weights)
for p in [0.0, 0.5]:
    runs = [train_and_test(p, seed) for seed in range(5)]
    tr = np.mean([r[0] for r in runs]); te = np.mean([r[1] for r in runs])
    print(f"dropout p={p}: train accuracy {tr:.1%}   test accuracy (unseen) {te:.1%}")
```

```
dropout p=0.0: train accuracy 100.0%   test accuracy (unseen) 86.7%
dropout p=0.5: train accuracy 100.0%   test accuracy (unseen) 87.8%
```

Both versions score **100% on the 60 training images**: they have memorised them. On the ~1,700 **unseen** images, the dropout version does slightly but consistently better. The gap between training and test accuracy *is* overfitting, and dropout narrows it.

The gain here is small (about 1 percentage point) because this problem is tiny. Dropout matters most in **huge** layers. AlexNet's fully connected layers held about 58 million weights, and the paper reports that without dropout the network overfitted badly.

5 · Pooling: shrinking feature maps

CNNs (LeNet, AlexNet, VGG) alternate **conv → ReLU → pool**. **Max pooling 2×2** keeps the biggest value in each 2×2 block:

- it halves the height and width, which means less computation for the next layer,
- it keeps "was the pattern present somewhere around here?", and
- it adds a little tolerance to small shifts.

It has no learnable parameters.

```
fm = torch.tensor([[1., 3, 2, 0],
                   [4, 6, 1, 1],
                   [0, 2, 9, 5],
                   [1, 1, 3, 7]])
print("feature map (4x4):\n", fm.int().numpy())
print("\nafter 2x2 max pooling (2x2):\n", F.max_pool2d(fm[None, None], 2)[0, 0].int().numpy())
print("\nafter 2x2 average pooling:\n", F.avg_pool2d(fm[None, None], 2)[0, 0].numpy())
```

```
feature map (4x4):
 [[1 3 2 0]
 [4 6 1 1]
 [0 2 9 5]
 [1 1 3 7]]

after 2x2 max pooling (2x2):
 [[6 2]
 [2 9]]

after 2x2 average pooling:
 [[3.5 1. ]
 [1.  6. ]]
```

6 · How a network learns: the training loop

Every model in this course is trained with the same 4-step loop, repeated thousands of times:

1. **Forward pass:** push images through the network to get predictions.
2. **Loss:** one number for "how wrong were we?" (cross-entropy for classification).
3. **Backward pass:** `loss.backward()` computes the **gradient**, i.e. which way to nudge every weight to reduce the loss. This is backpropagation.
4. **Step:** the optimizer (SGD or Adam) nudges all the weights a little.

Below is a tiny CNN learning the 8×8 digits. Watch the loss fall, and compare the first layer's kernels before and after training: every number has been adjusted by the loop.

```
Xtr_img, Xte_img, ytr_d, yte_d = train_test_split(X.reshape(-1, 1, 8, 8), y, test_size=0.3,
random_state=0, stratify=y)


torch.manual_seed(0)
tiny_cnn = nn.Sequential(
    nn.Conv2d(1, 8, kernel_size=3, padding=1), nn.ReLU(), nn.MaxPool2d(2),   # 8 learned 3x3
kernels -> 8 maps of 4x4
    nn.Flatten(), nn.Linear(8 * 4 * 4, 10))                                  # FC layer makes the
decision
first_kernels_before = tiny_cnn[0].weight.detach().clone()

opt = torch.optim.Adam(tiny_cnn.parameters(), lr=0.01)
losses = []
for epoch in range(60):
    logits = tiny_cnn(Xtr_img)                # 1. forward
    loss = F.cross_entropy(logits, ytr_d)     # 2. loss
    opt.zero_grad(); loss.backward()          # 3. backward (gradients)
    opt.step()                                # 4. update weights
    losses.append(loss.item())

with torch.no_grad():
    acc = (tiny_cnn(Xte_img).argmax(1) == yte_d).float().mean().item()
print(f"test accuracy after 60 steps: {acc:.1%}  (random guessing = 10%)")

fig = plt.figure(figsize=(12, 3.4))
ax = fig.add_subplot(1, 3, 1); ax.plot(losses); ax.set_title("loss goes down");
ax.set_xlabel("step")
for row, (w, title) in enumerate([(first_kernels_before, "kernels BEFORE training (random)"),
                                  (tiny_cnn[0].weight.detach(), "kernels AFTER training
(learned)")]):
    sub = fig.add_subplot(1, 3, row + 2); sub.set_title(title); sub.axis("off")
    tiles = np.full((7, 15), np.nan)
    for i in range(8):
        r, c = divmod(i, 4)
        tiles[r * 4:r * 4 + 3, c * 4:c * 4 + 3] = w[i, 0].numpy()
    sub.imshow(tiles, cmap="coolwarm")
plt.tight_layout(); plt.show()
```

```
test accuracy after 60 steps: 96.1%  (random guessing = 10%)
```



The learned kernels changed, but on 8×8 images with only 3×3 kernels they're hard to interpret by eye. Notebook 02 trains LeNet on bigger images, where the learned filters and their feature maps are much easier to read.

That is the whole idea of deep learning in vision: **the same convolution as Week 1, with kernels learned by the 4-step loop.**

✅ Check yourself

1. What does ReLU do to negative inputs? *(sets them to 0; positives pass through unchanged)*

2. Give two reasons ReLU replaced sigmoid/tanh in AlexNet. *(faster and simpler to compute; gradient = 1 for positive inputs, so less vanishing gradient)*
3. What is dropout, and is it used at test time? *(randomly zeroing neurons during training to prevent overfitting; no, it's switched off with* `model.eval()` *)*
4. A layer has 20 neurons and dropout 0.25. How many are dropped per pass, on average? *(5)*
5. Why do conv layers need far fewer parameters than fully connected layers? *(local connections + the same kernel reused across the whole image)*
6. Where are conv layers and FC layers used in a typical CNN? *(conv for feature extraction early; FC at the end for the decision)*

02 · Classic CNN architectures: LeNet → AlexNet → VGG

Covers (Week 3 Key Concepts, "CNN Architectures"): LeNet (1998), AlexNet (2012), VGG (2014). **Questions answered here:** Easy 1–9 · Medium 1–4 · Hard 2, 10.

Year	Model	One-line contribution
1998	**LeNet-5** (Yann LeCun)	**Proof of concept**: CNNs can read handwriting (cheques, zip codes)
2012	**AlexNet** (Krizhevsky, Sutskever, Hinton)	**The breakthrough**: won ImageNet by a huge margin using ReLU, dropout and GPUs
2014	**VGG** (Visual Geometry Group, Oxford)	**Depth + simplicity**: 16–19 layers, only small 3×3 filters
2015	ResNet	made *very* deep networks trainable (notebook 03)
2019	EfficientNet	balanced, efficient scaling (notebook 03)
2020	Vision Transformer	attention instead of convolution (notebook 07)

We'll **build and train LeNet** ourselves (it runs in seconds on a laptop CPU), then **inspect** AlexNet and VGG. Those are too big to train here, but we can build them and look inside.

```
%matplotlib inline
import time
import numpy as np
import matplotlib.pyplot as plt
import torch
import torch.nn as nn
import torch.nn.functional as F
from sklearn.datasets import load_digits
from sklearn.model_selection import train_test_split

torch.manual_seed(0)
print("torch", torch.__version__)
```

```
torch 2.14.1+cu130
```

1 · Data: handwritten digits


LeNet was trained on **MNIST**: 70,000 handwritten digits, 28×28 pixels, padded to 32×32. MNIST needs a download, so we use scikit-learn's built-in **digits** dataset instead. It has the same idea (handwritten 0–9) but is smaller: 1,797 images of 8×8. We **resize them to 32×32**, LeNet's input size.

```
digits = load_digits()
X = torch.tensor(digits.images, dtype=torch.float32)[:, None] / 16.0      # (1797, 1, 8, 8), values 0..1
X = F.interpolate(X, size=(32, 32), mode="bilinear", align_corners=False)  # -> (1797, 1, 32, 32)
y = torch.tensor(digits.target)
Xtr, Xte, ytr, yte = train_test_split(X, y, test_size=0.3, random_state=0, stratify=y)
print("train:", tuple(Xtr.shape), " test:", tuple(Xte.shape))

fig, ax = plt.subplots(1, 10, figsize=(12, 1.6))
```

```
for i in range(10):
    ax[i].imshow(Xtr[i, 0], cmap="gray"); ax[i].set_title(int(ytr[i])); ax[i].axis("off")
plt.show()
```

```
train: (1257, 1, 32, 32)  test: (540, 1, 32, 32)
```



2 · LeNet-5 (1998)

Inventor: Yann LeCun (Bell Labs). **Purpose:** digit recognition. It was used to read **bank cheques and postal codes**. **Architecture: Convolution → Pooling → Convolution → Pooling → Fully Connected → Fully Connected → Output.**

```
input 32×32 — conv 5×5 (6 maps) — pool — conv 5×5 (16 maps) — pool — FC 120 — FC 84 — 10
classes
              "find strokes"            "combine strokes"            "decide which
digit"
```

The original used tanh/sigmoid and average pooling. We use ReLU and max-pooling, the modern defaults, and compare activations later.

```
class LeNet5(nn.Module):
    def __init__(self, act=nn.ReLU):
        super().__init__()
        self.features = nn.Sequential(                # feature extraction (convolutions)
            nn.Conv2d(1, 6, kernel_size=5), act(), nn.MaxPool2d(2),
            nn.Conv2d(6, 16, kernel_size=5), act(), nn.MaxPool2d(2))
        self.classifier = nn.Sequential(              # decision making (fully connected)
            nn.Flatten(),
            nn.Linear(16 * 5 * 5, 120), act(),
            nn.Linear(120, 84), act(),
            nn.Linear(84, 10))

    def forward(self, x):
        return self.classifier(self.features(x))

model = LeNet5()

# Trace one image through the network and print the shape after every layer
x = Xtr[:1]
print(f"{'layer':<34} output shape")
print(f"{'input':<34} {tuple(x.shape)}")
for layer in list(model.features) + list(model.classifier):
    x = layer(x)
    print(f"{str(layer):<34} {tuple(x.shape)}")
print(f"\nTotal parameters: {sum(p.numel() for p in model.parameters()):,}")
```

```
layer                                output shape
input                                (1, 1, 32, 32)
Conv2d(1, 6, kernel_size=(5, 5), stride=(1, 1)) (1, 6, 28, 28)
ReLU()                               (1, 6, 28, 28)
MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False) (1, 6, 14, 14)
Conv2d(6, 16, kernel_size=(5, 5), stride=(1, 1)) (1, 16, 10, 10)
ReLU()                               (1, 16, 10, 10)
MaxPool2d(kernel_size=2, stride=2, padding=0, dilation=1, ceil_mode=False) (1, 16, 5, 5)
Flatten(start_dim=1, end_dim=-1)     (1, 400)
Linear(in_features=400, out_features=120, bias=True) (1, 120)
ReLU()                               (1, 120)
Linear(in_features=120, out_features=84, bias=True) (1, 84)
ReLU()                               (1, 84)
Linear(in_features=84, out_features=10, bias=True) (1, 10)

Total parameters: 61,706
```

Read the shapes:

- **32×32 → 28×28** after a 5×5 convolution with no padding (32 − 5 + 1 = 28, the Week-1 formula).
- **28 → 14** after 2×2 pooling, **14 → 10** after the second 5×5 conv, **10 → 5** after pooling.
- 16 maps × 5 × 5 = **400 numbers** are flattened and sent to the fully connected layers.

The whole of LeNet has only about **62 thousand** parameters. AlexNet has about 61 *million* (see below).

Train it

```python
def train(model, epochs=15, lr=1e-3, batch=64, augment=None, verbose=True):
    opt = torch.optim.Adam(model.parameters(), lr=lr)
    history = []
    for epoch in range(epochs):
        model.train()
        perm = torch.randperm(len(Xtr))
        for i in range(0, len(Xtr), batch):
            idx = perm[i:i + batch]
            xb = Xtr[idx] if augment is None else augment(Xtr[idx], seed=epoch * 10_000 + i)
            loss = F.cross_entropy(model(xb), ytr[idx])
            opt.zero_grad(); loss.backward(); opt.step()
        history.append(accuracy(model, Xte))
        if verbose and (epoch % 5 == 4 or epoch == 0):
            print(f"epoch {epoch + 1:>2}: test accuracy {history[-1]:.1%}")
    return history

def accuracy(model, X_, y_=None):
    y_ = yte if y_ is None else y_
    model.eval()
    with torch.no_grad():
        return (model(X_).argmax(1) == y_).float().mean().item()

torch.manual_seed(0)
lenet = LeNet5()
t = time.time()
hist_relu = train(lenet)
print(f"\nLeNet-5 final test accuracy: {hist_relu[-1]:.1%}  (trained in {time.time() - t:.1f} s
on CPU)")
```

```
epoch  1: test accuracy 57.2%
epoch  5: test accuracy 91.7%
epoch 10: test accuracy 95.4%
epoch 15: test accuracy 95.9%


LeNet-5 final test accuracy: 95.9%  (trained in 2.9 s on CPU)
```

What did LeNet learn? Look at its filters and feature maps

The first layer has **6 learned 5×5 kernels**. Applying them to a digit gives 6 **feature maps**. Each one lights up where its pattern (a stroke direction, an edge or a blob) appears.

```
sample = Xte[3:4]
with torch.no_grad():
    maps = F.relu(lenet.features[0](sample))[0]           # output of first conv + ReLU

fig, ax = plt.subplots(2, 7, figsize=(13, 4))
ax[0, 0].imshow(sample[0, 0], cmap="gray"); ax[0, 0].set_title(f"input: {int(yte[3])}")
ax[1, 0].axis("off"); ax[0, 0].axis("off")
for i in range(6):
    ax[0, i + 1].imshow(lenet.features[0].weight[i, 0].detach(), cmap="coolwarm")
    ax[0, i + 1].set_title(f"kernel {i}"); ax[0, i + 1].axis("off")
    ax[1, i + 1].imshow(maps[i], cmap="magma"); ax[1, i + 1].set_title(f"feature map {i}"); ax[1,
i + 1].axis("off")
plt.suptitle("Top: LeNet's learned 5x5 kernels.  Bottom: what each one 'sees' in the digit")
plt.tight_layout(); plt.show()
```



Different kernels respond to different parts of the stroke: some to its edges on one side, some to the whole body of the stroke. A completely black map means that kernel's pattern isn't in this digit at all (ReLU turned every negative response into 0). It may fire on other digits. **Nobody programmed these.** They're Week-1-style edge and stroke detectors that LeNet discovered by itself from the data.

LeNet vs "traditional machine learning" (Medium Q1)

The course's exam answer: *LeNet was the **first proof** that CNNs beat traditional ML methods (like SVMs, support vector machines) on images, which inspired their use in handwriting recognition and banking.*

Let's test it honestly on our small dataset. We'll also test **shifted** digits (moved up to 4 pixels), because CNNs are supposed to be good at "find the pattern wherever it is".

```
from sklearn.svm import SVC

def shift(images, max_shift=4, seed=0):
    # move every image by a random amount (up to max_shift pixels in x and y)
    g = torch.Generator().manual_seed(seed)
    out = torch.empty_like(images)
    for i in range(len(images)):
        dx, dy = torch.randint(-max_shift, max_shift + 1, (2,), generator=g).tolist()
        out[i] = torch.roll(images[i], shifts=(dy, dx), dims=(1, 2))
    return out
```

```
Xte_shifted = shift(Xte)

svm = SVC(gamma="scale").fit(Xtr.reshape(len(Xtr), -1), ytr)      # SVM sees the raw 1,024 pixel
values
svm_clean = svm.score(Xte.reshape(len(Xte), -1), yte)
svm_shift = svm.score(Xte_shifted.reshape(len(Xte), -1), yte)

# Fair comparison: give BOTH models training data with shifted copies (augmentation)
torch.manual_seed(0)
lenet_aug = LeNet5()
train(lenet_aug, epochs=25, augment=shift, verbose=False)          # sees new random shifts every
epoch
X_aug = torch.cat([Xtr] + [shift(Xtr, seed=s) for s in range(1, 4)])   # SVM: original + 3
shifted copies
svm_aug = SVC(gamma="scale").fit(X_aug.reshape(len(X_aug), -1), ytr.repeat(4))

def svm_scores(m):
    return m.score(Xte.reshape(len(Xte), -1), yte), m.score(Xte_shifted.reshape(len(Xte), -1),
yte)

rows = [("SVM (raw pixels)", (svm_clean, svm_shift)),
        ("LeNet-5", (accuracy(lenet, Xte), accuracy(lenet, Xte_shifted))),
        ("SVM + shifted training copies", svm_scores(svm_aug)),
        ("LeNet-5 + shifted training copies", (accuracy(lenet_aug, Xte), accuracy(lenet_aug,
Xte_shifted)))]
print(f"{'model':<36}{'normal test':>12}{'shifted test':>14}")
for name, (a, b) in rows:
    print(f"{name:<36}{a:>12.1%}{b:>14.1%}")
```

```
model                                normal test  shifted test
SVM (raw pixels)                           98.9%         69.3%
LeNet-5                                    95.9%         67.2%
SVM + shifted training copies              99.4%         95.6%
LeNet-5 + shifted training copies          98.3%         93.3%
```

Honest result: on this *tiny* dataset (1,257 training images, originally 8×8 pixels) a modern SVM is **just as good or slightly better** than LeNet. Both collapse on shifted digits (about 70%) until they're trained on shifted examples (augmentation, from Week 1 Day 2), and then both recover to over 90%.

So why do we credit LeNet?

- **In 1998, on MNIST** (60,000 training images), LeNet-5 reached about **0.95% error**. That was on par with the best SVMs of the time, while being **much faster and smaller to run**, which mattered for reading millions of cheques. Boosted LeNet variants did best of all.
- **CNNs learn their own features.** The SVM only works this well because the digits are tiny, centred and clean. As images get bigger and messier (real photos, many classes), hand-made features plus SVMs fall far behind. AlexNet proved that dramatically in 2012.

> **Exam answer (Medium Q1):** LeNet showed that a CNN trained end-to-end on raw pixels could match or beat the best traditional methods (SVMs with hand-crafted features) on handwriting recognition, while learning its own features. That led to real deployments in banking (cheque reading) and postal services.

3 · AlexNet (2012): the breakthrough

Event: won the **ImageNet** competition (ILSVRC 2012: 1.2 million photos, 1,000 classes) by a huge margin.

	Top-5 error	Top-5 accuracy
Best entry *before* deep learning (2011, hand-crafted features)	≈ 26%	≈ 74%
AlexNet (2012)	**≈ 15.3%**	**≈ 85%**

The second-best entry in 2012 scored about 26%, so AlexNet's lead was more than 10 points. The course notes summarise this as "~70% → ~85%+". **Top-5 accuracy** means "the right answer is somewhere in the model's 5 best guesses".

Architecture: 5 convolutional layers + 3 fully connected layers.

```
from torchvision.models import alexnet
anet = alexnet(weights=None)          # build the architecture with random weights (no download)
print(anet)

convs = [m for m in anet.modules() if isinstance(m, nn.Conv2d)]
fcs = [m for m in anet.modules() if isinstance(m, nn.Linear)]
n_conv = sum(p.numel() for m in convs for p in m.parameters())
n_fc = sum(p.numel() for m in fcs for p in m.parameters())
print(f"\n{len(convs)} conv layers + {len(fcs)} fully connected layers")
print(f"parameters: conv {n_conv / 1e6:.1f} M   +   FC {n_fc / 1e6:.1f} M   =   {(n_conv + n_fc)
/ 1e6:.1f} M total")
```

```
AlexNet(
  (features): Sequential(
    (0): Conv2d(3, 64, kernel_size=(11, 11), stride=(4, 4), padding=(2, 2))
    (1): ReLU(inplace=True)
    (2): MaxPool2d(kernel_size=3, stride=2, padding=0, dilation=1, ceil_mode=False)
    (3): Conv2d(64, 192, kernel_size=(5, 5), stride=(1, 1), padding=(2, 2))
    (4): ReLU(inplace=True)
    (5): MaxPool2d(kernel_size=3, stride=2, padding=0, dilation=1, ceil_mode=False)
    (6): Conv2d(192, 384, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
    (7): ReLU(inplace=True)
    (8): Conv2d(384, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
    (9): ReLU(inplace=True)
    (10): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1))
    (11): ReLU(inplace=True)
    (12): MaxPool2d(kernel_size=3, stride=2, padding=0, dilation=1, ceil_mode=False)
  )
  (avgpool): AdaptiveAvgPool2d(output_size=(6, 6))
  (classifier): Sequential(
    (0): Dropout(p=0.5, inplace=False)
    (1): Linear(in_features=9216, out_features=4096, bias=True)
    (2): ReLU(inplace=True)
    (3): Dropout(p=0.5, inplace=False)
    (4): Linear(in_features=4096, out_features=4096, bias=True)
    (5): ReLU(inplace=True)
    (6): Linear(in_features=4096, out_features=1000, bias=True)
  )
)

5 conv layers + 3 fully connected layers
parameters: conv 2.5 M   +   FC 58.6 M   =   61.1 M total
```

Notice: **about 95% of AlexNet's parameters are in the 3 fully connected layers.** That's exactly why it needed **dropout** (you can see `Dropout(p=0.5)` in the classifier above). Those huge layers would otherwise memorise the training set.

AlexNet's three innovations

Innovation	What it did
ReLU activation	much faster training than sigmoid/tanh; less vanishing gradient
Dropout	reduced overfitting in the giant FC layers
GPU training	split across 2 NVIDIA GTX 580 GPUs, it trained in about a week instead of months


Plus heavy **data augmentation** (random crops and flips, from Day 2) and **overlapping max-pooling**.

ReLU vs sigmoid, measured (Easy Q5, Hard Q2)

Let's train LeNet three times, changing only the activation:

```
results = {"ReLU": hist_relu}
for name, act in [("tanh", nn.Tanh), ("sigmoid", nn.Sigmoid)]:
    torch.manual_seed(0)
    results[name] = train(LeNet5(act=act), verbose=False)

plt.figure(figsize=(7, 3.6))
for name, h in results.items():
    plt.plot(range(1, len(h) + 1), h, "o-", label=f"{name} (final {h[-1]:.0%})")
plt.xlabel("epoch"); plt.ylabel("test accuracy"); plt.ylim(0, 1)
plt.title("Same LeNet, different activation"); plt.legend(); plt.grid(alpha=0.3); plt.show()
```



Sigmoid learns much more slowly. It's stuck near 10% (random guessing) for the first epochs because its small slopes (≤ 0.25) shrink the training signal at every layer. **ReLU and tanh both learn fast here.** This network is shallow (5 weight layers) and the modern Adam optimizer helps, so tanh keeps up, even edging ahead. The gap grows with depth and with the plain SGD optimizer used in 2012. In AlexNet's paper a ReLU network reached the target error **about 6× faster** than the same network with tanh.

> **Why ReLU reduces vanishing gradients (Hard Q2):** the gradient of ReLU is exactly 1 for every positive input, so the error signal passes backwards through many layers without shrinking. Sigmoid and tanh have slopes well below 1 almost everywhere

> and near 0 when saturated, and multiplying many small numbers makes the gradient vanish. ReLU is also cheaper to compute (no exponentials), which made training faster.

Why GPUs mattered (Medium Q2)

Training a CNN is mostly **millions of independent multiply-adds** (every kernel at every position). A CPU has a few powerful cores. A GPU has **thousands of small cores** that do these in parallel. Let's time one AlexNet forward pass on this machine's CPU:

```
batch = torch.randn(16, 3, 224, 224)       # 16 photos of 224x224
anet.eval()
with torch.no_grad():
    t = time.time(); anet(batch); cpu_time = time.time() - t
print(f"AlexNet forward pass, 16 images, CPU: {cpu_time:.2f} s")
print(f"One pass over ImageNet (1.2 M images) would take about {cpu_time / 16 * 1.2e6 / 3600:.1f}
hours on this CPU - "
      "and training needs a backward pass too (about 2-3x more work), repeated ~90 times.")
print("GPU available here:", torch.cuda.is_available(), "- on a GPU the same work is typically
10-50x faster.")
```

```
AlexNet forward pass, 16 images, CPU: 0.08 s
One pass over ImageNet (1.2 M images) would take about 1.8 hours on this CPU - and training needs
a backward pass too (about 2-3x more work), repeated ~90 times.
GPU available here: False - on a GPU the same work is typically 10-50x faster.
```

4 · VGG (2014): deep and simple

VGG (Visual Geometry Group, Oxford). **Architecture:** very deep, **16–19 layers** (VGG-16 and VGG-19). **Design choice:** use **only small 3×3 filters**, stacked. No 11×11 or 5×5 like AlexNet. **Contribution:** showed that **depth improves accuracy**. Its uniform, simple design made it a standard **baseline** in research.

```
from torchvision.models import vgg16, vgg19

for name, fn in [("VGG-16", vgg16), ("VGG-19", vgg19)]:
    net = fn(weights=None)
    n_conv = sum(isinstance(m, nn.Conv2d) for m in net.modules())
    n_fc = sum(isinstance(m, nn.Linear) for m in net.modules())
    kernel_sizes = {m.kernel_size for m in net.modules() if isinstance(m, nn.Conv2d)}
    print(f"{name}: {n_conv} conv + {n_fc} FC = {n_conv + n_fc} weight layers, "
          f"kernel sizes used: {kernel_sizes}, parameters: {sum(p.numel() for p in
net.parameters()) / 1e6:.0f} M")
    del net
```

```
VGG-16: 13 conv + 3 FC = 16 weight layers, kernel sizes used: {(3, 3)}, parameters: 138 M
VGG-19: 16 conv + 3 FC = 19 weight layers, kernel sizes used: {(3, 3)}, parameters: 144 M
```

Why stack small 3×3 filters? (Medium Q4)

1. **Same view, fewer weights.** Two 3×3 layers in a row "see" a 5×5 area of the input, and three of them see 7×7. That's the same **receptive field** as one big 7×7 filter, with fewer parameters.
2. **More non-linearity.** Three layers means three ReLUs instead of one, so the network can learn more complex patterns.


Let's **measure** the receptive field. We ask: "which input pixels can change the centre output pixel?" Backpropagation answers exactly that.

```python
def receptive_field(layers, size=15):
    x = torch.zeros(1, 1, size, size, requires_grad=True)
    out = layers(x)
    out[0, 0, out.shape[2] // 2, out.shape[3] // 2].backward()     # nudge the centre output
    return (x.grad[0, 0] != 0).numpy()                              # which inputs affected it?

def stack(k, n):
    torch.manual_seed(0)
    layers = []
    for _ in range(n):
        conv = nn.Conv2d(1, 1, k, padding=k // 2, bias=False)
        nn.init.constant_(conv.weight, 1.0)
        layers.append(conv)
    return nn.Sequential(*layers)

fig, ax = plt.subplots(1, 4, figsize=(12, 3.2))
for a, (k, n) in zip(ax, [(3, 1), (3, 2), (3, 3), (7, 1)]):
    rf = receptive_field(stack(k, n))
    a.imshow(rf, cmap="Blues"); a.set_xticks([]); a.set_yticks([])
    a.set_title(f"{n} x ({k}x{k}) conv\nsees {rf.sum(1).max()}x{rf.sum(0).max()} pixels")
plt.tight_layout(); plt.show()

C = 64   # channels in and out
print(f"Parameters for C={C} channels in and out:")
print(f"  one 7x7 layer      : 7*7*C*C   = {49 * C * C:,}")
print(f"  three 3x3 layers   : 3*3*3*C*C = {27 * C * C:,}   ({27 / 49:.0%} of the 7x7 cost, with
3 ReLUs instead of 1)")
```




```
Parameters for C=64 channels in and out:
  one 7x7 layer      : 7*7*C*C   = 200,704
  three 3x3 layers   : 3*3*3*C*C = 110,592   (55% of the 7x7 cost, with 3 ReLUs instead of 1)
```

Three stacked 3×3 layers see the same 7×7 window as one 7×7 layer, with **45% fewer parameters** and **three** non-linearities. That's VGG's core idea, and almost every later CNN (ResNet included) uses 3×3 convolutions.

VGG's downside: about 138 million parameters (mostly in the FC layers again). It's slow and memory-hungry. ResNet and EfficientNet (next notebook) fix this.

Key takeaways (from the Key Concepts sheet)

- **LeNet:** proof of concept (conv → pool → FC). Digits, cheques.
- **AlexNet:** breakthrough in scale and performance. ReLU + dropout + GPUs, 5 conv + 3 FC, won ImageNet 2012 by about 10 points.
- **VGG:** depth and simplicity as design principles. 16–19 layers, all 3×3 filters, a research baseline.

- Together they form the **timeline of CNN evolution**, and that trend toward deeper and better-designed networks led to ResNet, EfficientNet and Vision Transformers (Hard Q10, answered in `practice/question_bank_answers.md`).

✅ Check yourself

1. Who invented LeNet, what was it for, and what dataset was it trained on? *(Yann LeCun; handwritten digit recognition for cheques and postal codes; MNIST)*
2. LeNet's layer pattern? *(conv → pool → conv → pool → FC → FC → output)*
3. AlexNet's biggest achievement and three innovations? *(won ImageNet 2012 by a huge margin; ReLU, dropout, GPU training)*
4. How many layers does AlexNet have? *(5 conv + 3 FC)*
5. How many layers does VGG have, and what filter size did it standardise? *(16–19; 3×3)*
6. What receptive field do three stacked 3×3 convs have? *(7×7)*
7. Why is most of AlexNet's/VGG's parameter count in the FC layers? *(every FC neuron connects to every input value; conv kernels are tiny and shared)*

03 · Modern CNNs: ResNet and EfficientNet

Covers (Week 3 Key Concepts, "Why Study Modern CNNs?"): ResNet (2015), EfficientNet (2019), plus MobileNet for "lightweight models for phones". **Questions answered here:** Easy 10–14 · Medium 5–9 · Hard 3–4, 7.

The story so far: VGG showed that deeper means more accurate. So why not 100 layers? People tried, and **very deep plain networks got *worse***, even on their *training* data. Two problems stood in the way:

1. **Depth:** gradients vanish, so the early layers stop learning. **ResNet** fixed this.
2. **Efficiency:** bigger networks are slow and wasteful if you grow them the wrong way. **EfficientNet** fixed this.


```
%matplotlib inline
import time
import numpy as np
import matplotlib.pyplot as plt
import torch
import torch.nn as nn
import torch.nn.functional as F
from sklearn.datasets import load_digits
from sklearn.model_selection import train_test_split

torch.manual_seed(0)
digits = load_digits()
X = torch.tensor(digits.images, dtype=torch.float32)[:, None] / 16.0
X = F.interpolate(X, size=(16, 16), mode="bilinear", align_corners=False)
y = torch.tensor(digits.target)
Xtr, Xte, ytr, yte = train_test_split(X, y, test_size=0.3, random_state=0, stratify=y)
print("data:", tuple(Xtr.shape), tuple(Xte.shape))
```

```
data: (1257, 1, 16, 16) (540, 1, 16, 16)
```

1 · ResNet (2015): the residual connection

The idea in one picture



- A **plain** block must learn the whole desired output **H(x)** (a "direct mapping").
- A **residual** block only learns the **difference** (the *residual*) **F(x) = H(x) − x**, i.e. what to *change* about its input. The input is then added back.

Analogy: instead of redrawing a picture from scratch at every layer, each layer only makes **corrections** to the picture it received. If a layer has nothing useful to add, it can learn F(x) ≈ 0 and simply pass the input through unchanged. That's very easy. For a plain block, learning to "do nothing" (H(x) = x) is surprisingly hard.

Why it fixes vanishing gradients

For output = F(x) + x, the gradient flowing backwards is:

d(output)/dx = F′(x) + 1

That **"+1"** is a direct highway for the gradient. Even if F′(x) is tiny, the signal still passes back through the skip connection unchanged. In a plain network the gradient is a **product** of many F′ terms, and the product of many small numbers vanishes.

Let's build both kinds of block and **prove it**.

```
class Block(nn.Module):
    def __init__(self, channels, residual):
        super().__init__()
        self.conv1 = nn.Conv2d(channels, channels, 3, padding=1)
        self.conv2 = nn.Conv2d(channels, channels, 3, padding=1)
        self.residual = residual

    def forward(self, x):
        out = self.conv2(F.relu(self.conv1(x)))      # F(x)
        if self.residual:
            out = out + x                            # the skip connection: F(x) + x
        return F.relu(out)

class Net(nn.Module):
    def __init__(self, n_blocks, residual, channels=32):
        super().__init__()
        self.stem = nn.Conv2d(1, channels, 3, padding=1)
        self.blocks = nn.Sequential(*[Block(channels, residual) for _ in range(n_blocks)])
        self.head = nn.Linear(channels, 10)

    def forward(self, x):
        x = F.relu(self.stem(x))
        x = self.blocks(x)
        return self.head(x.mean(dim=(2, 3)))         # global average pooling -> classifier

def first_layer_gradient(model):
    model.zero_grad()
    F.cross_entropy(model(Xtr[:128]), ytr[:128]).backward()
    return model.stem.weight.grad.norm().item()     # how big is the learning signal reaching
layer 1?

print(f"{'layers':>6} | {'plain net: gradient at layer 1':>32} | {'residual net: gradient at
layer 1':>34}")
for n_blocks in [2, 10, 25]:
    torch.manual_seed(0); g_plain = first_layer_gradient(Net(n_blocks, residual=False))
    torch.manual_seed(0); g_res = first_layer_gradient(Net(n_blocks, residual=True))
    print(f"{2 * n_blocks + 2:>6} | {g_plain:>32.2e} | {g_res:>34.2e}")
```

```
layers |   plain net: gradient at layer 1 |  residual net: gradient at layer 1
     6 |                         3.00e-04 |                             1.81e-02
    22 |                         1.92e-10 |                             1.00e-02
    52 |                         0.00e+00 |                             2.04e-02
```

Read the left column: the deeper the plain network, the smaller the learning signal that reaches the first layer. At 22 layers it's around 10^{-10}, and at 52 layers it's **exactly zero**: the first layer gets no information at all about how to improve. The residual network keeps a healthy signal at every depth.

Does it actually change training? (≈ 3 minutes on a laptop CPU)

```
def train_eval(model, epochs=15, lr=3e-3, batch=64):
    opt = torch.optim.Adam(model.parameters(), lr=lr)
    for _ in range(epochs):
        model.train()
        perm = torch.randperm(len(Xtr))
        for i in range(0, len(Xtr), batch):
            idx = perm[i:i + batch]
            loss = F.cross_entropy(model(Xtr[idx]), ytr[idx])
            opt.zero_grad(); loss.backward(); opt.step()
    model.eval()
    with torch.no_grad():
        return F.cross_entropy(model(Xtr), ytr).item(), (model(Xte).argmax(1) ==
yte).float().mean().item()

results = {}
t = time.time()
for n_blocks in [2, 10, 25]:
    for residual in [False, True]:
        torch.manual_seed(0)
        results[(2 * n_blocks + 2, residual)] = train_eval(Net(n_blocks, residual))
print(f"done in {time.time() - t:.0f} s\n")
print(f"{'layers':>6} | {'plain: train loss / test acc':>30} | {'residual: train loss / test
acc':>32}")
for L in [6, 22, 52]:
    (lp, ap), (lr_, ar) = results[(L, False)], results[(L, True)]
    print(f"{L:>6} | {lp:>15.3f} / {ap:>9.1%} | {lr_:>17.3f} / {ar:>9.1%}")
```

```
done in 214 s

layers |   plain: train loss / test acc |  residual: train loss / test acc
     6 |           0.687 /     78.1% |            0.291 /     88.0%
    22 |           2.303 /     10.2% |            0.587 /     76.1%
    52 |           2.303 /     10.2% |            0.816 /     66.1%
```

- At **6 layers** both train, and the residual one is already better.
- At **22 and 52 layers** the plain network is **stuck at 10%**, which is random guessing among 10 digits. Its training loss stays at 2.30 = ln(10), the loss of a model that knows nothing. **It cannot even fit its training data.** This is the *degradation problem* the ResNet paper described.
- The **residual** networks of the same depth train fine.

Our deep residual nets score lower than the 6-layer one only because they need more epochs and BatchNorm. Real ResNets add BatchNorm after every convolution, and that plus skip connections let them train with **50, 101, even 152 layers**.

> **Exam answer (Hard Q4):** In a plain deep network the gradient reaching early layers is a product of many per-layer factors, so it shrinks toward zero (vanishing gradients) and adding layers makes even *training* accuracy worse (degradation). A residual block outputs F(x) + x, so the gradient is F′(x) + 1. The identity path carries the gradient back unchanged, and a block that isn't useful can learn F(x) ≈ 0 and pass its input through. Extra depth therefore never hurts, and networks with 100+ layers become trainable.

Real ResNets

```
from torchvision.models import resnet18, resnet34, resnet50, resnet101, resnet152

print(f"{'model':<10}{'weight layers':>15}{'parameters':>14}")
for fn in [resnet18, resnet34, resnet50, resnet101, resnet152]:
    net = fn(weights=None)
```

```
    layers = sum(isinstance(m, (nn.Conv2d, nn.Linear)) for m in net.modules())
    downsample = sum(isinstance(m, nn.Conv2d) and m.kernel_size == (1, 1) and "downsample" in
name
                     for name, m in net.named_modules())
    params = sum(p.numel() for p in net.parameters())
    print(f"{fn.__name__:<10}{layers - downsample:>15}{params / 1e6:>12.1f} M")
    del net
```

```
model       weight layers    parameters
resnet18               18        11.7 M
resnet34               34        21.8 M
resnet50               50        25.6 M
resnet101             101        44.5 M
resnet152             152        60.2 M
```

The number in the name is the count of weight layers on the main path. The four 1×1 "downsample" convolutions on skip connections, which match sizes when the shape changes, are not counted. **ResNet-152 has 152 layers but fewer parameters (60 M) than VGG-16 (138 M)**, thanks to "bottleneck" blocks (1×1 → 3×3 → 1×1 convs) and **no giant fully connected layers**, just global average pooling and one FC layer.

Achievement: ResNet won ImageNet 2015 with **3.57% top-5 error**, better than the estimated human error of about 5%. **Real-world use (Medium Q8):** ResNet is the default backbone in **medical imaging**, e.g. classifying chest X-rays or skin lesions, often **pretrained on ImageNet and fine-tuned** on a smaller medical dataset. It's also the backbone inside Faster R-CNN and Mask R-CNN (notebooks 04–05).

Skip connections in ResNet vs U-Net (preview of Hard Q7)

	ResNet	U-Net (notebook 05)
Connects	a block's input to its output (short jumps)	encoder layer → matching decoder layer (long jumps)
Combines by	**adding** (F(x) + x)	**concatenating** feature maps
Main purpose	**gradient flow**: train very deep networks	**restore fine spatial detail** lost by downsampling

2 · EfficientNet (2019): scaling the smart way

Problem solved: to get a more accurate CNN, people scaled it up in **one** direction:

- **depth**: more layers (ResNet-18 → ResNet-152),
- **width**: more channels/filters per layer,
- **resolution**: bigger input images (224 → 600 pixels).

Scaling just one of these quickly hits **diminishing returns**: lots more computation for a tiny accuracy gain. It's like a bigger bike with only a bigger front wheel.

Innovation: compound scaling. Scale **all three together** with one formula, controlled by a single number φ ("phi", how much more compute you can afford):

depth × **α^φ**, width × **β^φ**, resolution × **γ^φ**, with **$\alpha \cdot \beta^2 \cdot \gamma^2 \approx 2$**

EfficientNet uses **α = 1.2, β = 1.1, γ = 1.15**. Each +1 in φ then roughly **doubles the computation** (FLOPs). Width and resolution are squared because doubling either one makes the work per layer about 4× bigger.

```
alpha, beta, gamma = 1.2, 1.1, 1.15
print(f"alpha * beta^2 * gamma^2 = {alpha * beta**2 * gamma**2:.3f}  (~2 -> each step doubles compute)\n")
print(f"{'phi':>3} | {'depth x':>8} | {'width x':>8} | {'resolution':>10} | {'compute x':>9}")
for phi in range(0, 8):
    d, w, r = alpha ** phi, beta ** phi, gamma ** phi
    print(f"{phi:>3} | {d:>8.2f} | {w:>8.2f} | {224 * r:>8.0f}px | {d * w**2 * r**2:>9.1f}")
```

```
alpha * beta^2 * gamma^2 = 1.920  (~2 -> each step doubles compute)

phi |  depth x |  width x | resolution | compute x
  0 |     1.00 |     1.00 |      224px |       1.0
  1 |     1.20 |     1.10 |      258px |       1.9
  2 |     1.44 |     1.21 |      296px |       3.7
  3 |     1.73 |     1.33 |      341px |       7.1
  4 |     2.07 |     1.46 |      392px |      13.6
  5 |     2.49 |     1.61 |      451px |      26.1
  6 |     2.99 |     1.77 |      518px |      50.1
  7 |     3.58 |     1.95 |      596px |      96.3
```

Every step grows depth, width *and* resolution a bit. The released models **B0 (φ = 0) to B7** follow this recipe, with input sizes from 224 up to 600 pixels.

Why is this better than just going deeper or wider? (Medium Q7, Hard Q3) The three dimensions **depend on each other**. A higher-resolution image has more detail, so the network needs **more layers** (a larger receptive field to cover bigger objects) **and more channels** (to capture the extra fine-grained patterns). Growing only one dimension leaves the others as the bottleneck. Balanced growth uses each extra FLOP where it helps most. The constants α, β and γ were found by a small grid search on the base model, then reused for all sizes.

The payoff: accuracy per parameter

```
from torchvision.models import efficientnet_b0, efficientnet_b7, resnet50, mobilenet_v3_large

def count(fn):
    net = fn(weights=None)
    n = sum(p.numel() for p in net.parameters())
    del net
    return n / 1e6

# ImageNet top-1 accuracies as reported in the papers (we can't train these here)
table = [("ResNet-50", count(resnet50), 76.0),
         ("EfficientNet-B0", count(efficientnet_b0), 77.1),
         ("EfficientNet-B7", count(efficientnet_b7), 84.3),
         ("MobileNetV3-Large", count(mobilenet_v3_large), 75.2)]
print(f"{'model':<20}{'parameters':>12}{'ImageNet top-1':>16}")
for name, p, acc in table:
    print(f"{name:<20}{p:>10.1f} M{acc:>15.1f}%")
```

```
model                parameters  ImageNet top-1
ResNet-50              25.6 M           76.0%
EfficientNet-B0         5.3 M           77.1%
EfficientNet-B7        66.3 M           84.3%
MobileNetV3-Large       5.5 M           75.2%
```

EfficientNet-B0 beats ResNet-50 with about 5× fewer parameters. In the paper, EfficientNet-B7 matched the best model of the time (84.3%) while being **8.4× smaller** and much faster.

Real-world use (Medium Q9): on-device **mobile apps**, e.g. a phone app that recognises plant diseases or food from the camera, and anything else needing good accuracy on limited hardware (drones, embedded cameras).

3 · Lightweight models for phones: MobileNet (Easy Q14)

The course's answer for "lightweight yet accurate for mobile vision apps" is **EfficientNet**. Its smallest versions (B0) are tiny. Its building block comes from **MobileNet**, the other classic mobile architecture, which uses **depthwise-separable convolutions**:

- **Normal conv:** every filter looks at all input channels at once, giving K × K × C_in × C_out weights.
- **Depthwise-separable:** ① one K×K filter **per channel** (depthwise), then ② a **1×1 conv** to mix the channels (pointwise), giving K × K × C_in + C_in × C_out weights.

```
C_in, C_out, K = 128, 128, 3
normal = nn.Conv2d(C_in, C_out, K, padding=1, bias=False)
separable = nn.Sequential(nn.Conv2d(C_in, C_in, K, padding=1, groups=C_in, bias=False),   # depthwise
                          nn.Conv2d(C_in, C_out, 1, bias=False))                          # pointwise 1x1
n1 = sum(p.numel() for p in normal.parameters())
n2 = sum(p.numel() for p in separable.parameters())
x = torch.randn(1, C_in, 56, 56)
print("same output shape:", normal(x).shape == separable(x).shape)
print(f"normal 3x3 conv     : {n1:>7,} weights")
print(f"depthwise-separable : {n2:>7,} weights  -> {n1 / n2:.1f}x fewer (and about that much less computation)")
```

```
same output shape: True
normal 3x3 conv     : 147,456 weights
depthwise-separable :  17,536 weights  -> 8.4x fewer (and about that much less computation)
```

Key takeaways (Key Concepts sheet)

- **ResNet:** made very deep networks trainable. **Learn residuals instead of direct mappings**; skip connections let gradients flow. 50/101/152 layers, state of the art on ImageNet 2015. Used in **medical imaging**.
- **EfficientNet:** made scaling efficient and practical. **Compound scaling** of depth, width and resolution with one formula: high accuracy with fewer parameters. Used in **mobile vision apps**.
- Together they represent the **modern era of CNNs** (solving depth and efficiency), and their ideas (skip connections, careful scaling) carried straight into **Vision Transformers**, which use residual connections in every block (notebook 07).

✅ Check yourself

1. What problem does ResNet solve? *(vanishing gradients / degradation when training very deep networks)*

2. ResNet's key innovation? *(residual (skip) connections: output = F(x) + x)*
3. Direct mapping vs residual? *(a plain block learns H(x) itself; a residual block learns only the change F(x) = H(x) − x)*
4. Why does the gradient survive in ResNet? *(d/dx [F(x) + x] = F′(x) + 1; the +1 path carries it backwards)*
5. Which architecture made 152-layer networks trainable? *(ResNet)*
6. What does EfficientNet's compound scaling balance? *(depth, width and resolution, all together via φ)*
7. Lightweight but accurate for phones? *(EfficientNet (B0) / MobileNet)*

04 · Object detection: R-CNN, YOLO, SSD

Covers (Week 3 Key Concepts, "Object Detection Architectures"): R-CNN (2014), YOLO (2016), SSD (2016) and the **accuracy vs speed** trade-off. **Questions answered here:** Easy 15–18 · Medium 10–14 · Hard 5–6.

> **Object detection = identifying *what* each object is AND *where* it is**: a **class label + a bounding box** for every object in the image.

Task	Output	Example
Classification	one label for the whole image	"cat"
Localization	one label + one box	"cat, at (40, 30, 120, 110)"
Detection	**a label + box for EVERY object**	"cat here, dog there, person there"
Segmentation (notebook 05)	a label for every **pixel**	exact outline of each object

In this notebook we **build tiny versions of R-CNN and YOLO ourselves** on a synthetic "shapes" dataset and race them. Both train on a laptop CPU in about 2 minutes.

```
%matplotlib inline
import time
import numpy as np
import matplotlib.pyplot as plt
import matplotlib.patches as mpatches
import cv2
import torch
import torch.nn as nn
import torch.nn.functional as F
from torchvision.ops import nms, box_iou, roi_align

torch.manual_seed(0)
print("torch", torch.__version__)
```

```
torch 2.14.1+cu130
```

1 · Two tools every detector uses: IoU and NMS


IoU (Intersection over Union): "how much do two boxes overlap?"

IoU = area of overlap / area of union: 1 = identical boxes, 0 = no overlap.

It's used to (a) decide whether a predicted box **counts as correct** (usually IoU ≥ 0.5 with the true box) and (b) remove duplicate boxes (NMS, below). Boxes are written as **(x1, y1, x2, y2)**: top-left and bottom-right corners.

```
def iou(a, b):
    x1, y1 = max(a[0], b[0]), max(a[1], b[1])          # overlap rectangle: the inner corners
    x2, y2 = min(a[2], b[2]), min(a[3], b[3])
    inter = max(0, x2 - x1) * max(0, y2 - y1)
    area_a = (a[2] - a[0]) * (a[3] - a[1])
    area_b = (b[2] - b[0]) * (b[3] - b[1])
    return inter / (area_a + area_b - inter)            # union = A + B - overlap (don't count it twice)
```

```
truth = (20, 20, 60, 60)
examples = [(20, 20, 60, 60), (30, 30, 70, 70), (40, 40, 80, 80), (70, 70, 90, 90)]
fig, ax = plt.subplots(1, 4, figsize=(13, 3.3))
for a, pred in zip(ax, examples):
    a.add_patch(mpatches.Rectangle(truth[:2], 40, 40, fill=False, ec="green", lw=2, label="true
box"))
    a.add_patch(mpatches.Rectangle(pred[:2], pred[2] - pred[0], pred[3] - pred[1], fill=False,
ec="red", lw=2, ls="--", label="prediction"))
    a.set_xlim(0, 100); a.set_ylim(100, 0); a.set_aspect("equal")
    a.set_title(f"IoU = {iou(truth, pred):.2f}")
ax[0].legend(loc="lower right", fontsize=8)
plt.tight_layout(); plt.show()
print("check with torchvision:", box_iou(torch.tensor([truth], dtype=torch.float32),
torch.tensor(examples, dtype=torch.float32)).numpy().round(2))
```




```
check with torchvision: [[1.   0.39 0.14 0.  ]]
```

NMS (Non-Maximum Suppression): "keep the best box, delete its duplicates"

Detectors usually fire **several overlapping boxes on the same object**. NMS cleans this up:

1. Sort boxes by confidence score.
2. Keep the highest-scoring box and **delete every other box that overlaps it** with IoU > threshold (e.g. 0.5).
3. Repeat with the next remaining box.


```
def my_nms(boxes, scores, thresh=0.5):
    order = list(np.argsort(scores)[::-1])          # best first
    keep = []
    while order:
        best = order.pop(0)
        keep.append(best)
        order = [i for i in order if iou(boxes[best], boxes[i]) <= thresh]   # drop the
duplicates of `best`
    return keep

boxes = [(10, 10, 50, 50), (12, 14, 52, 50), (8, 9, 48, 47), (60, 60, 90, 95), (62, 58, 92, 92)]
scores = [0.90, 0.75, 0.60, 0.85, 0.40]
kept = my_nms(boxes, scores)
print("kept boxes (mine)       :", sorted(kept))
print("kept boxes (torchvision):", sorted(nms(torch.tensor(boxes, dtype=torch.float32),
torch.tensor(scores), 0.5).tolist()))

fig, ax = plt.subplots(1, 2, figsize=(9, 4))
for a, idxs, title in [(ax[0], range(len(boxes)), "before NMS: 5 boxes"), (ax[1], kept, f"after
NMS: {len(kept)} boxes")]:
    for i in idxs:
        b = boxes[i]
        a.add_patch(mpatches.Rectangle(b[:2], b[2] - b[0], b[3] - b[1], fill=False, ec="C%d" % i,
lw=2))
        a.text(b[0], b[1] - 1, f"{scores[i]:.2f}", color="C%d" % i, fontsize=8)
```

```
    a.set_xlim(0, 100); a.set_ylim(100, 0); a.set_aspect("equal"); a.set_title(title)
plt.show()
```

```
kept boxes (mine)       : [np.int64(0), np.int64(3)]
kept boxes (torchvision): [0, 3]
```



2 · A dataset we can train on in minutes

Real detectors train on COCO (118,000 photos, 80 classes) for days on GPUs. We make our own: **96×96 scenes with 1–3 objects** (circle, square or triangle) of different sizes on a noisy background. We know the exact boxes because we drew them.

```
CLASSES = ["circle", "square", "triangle"]
IMG = 96

def draw_shape(img, cls, cx, cy, r, brightness):
    if cls == 0:
        cv2.circle(img, (cx, cy), r, brightness, -1)
    elif cls == 1:
        cv2.rectangle(img, (cx - r, cy - r), (cx + r, cy + r), brightness, -1)
    else:
        cv2.fillPoly(img, [np.array([[cx, cy - r], [cx - r, cy + r], [cx + r, cy + r]],
np.int32)], brightness)


def make_scene(rng, max_objects=3):
    img = rng.normal(40, 12, (IMG, IMG)).clip(0, 255).astype(np.uint8)       # noisy dark
background
    boxes, labels = [], []
    for _ in range(rng.integers(1, max_objects + 1)):
        for _attempt in range(20):                                           # find a spot that
doesn't overlap
            r = int(rng.integers(6, 16)); cx = int(rng.integers(r + 1, IMG - r - 1)); cy =
int(rng.integers(r + 1, IMG - r - 1))
            box = [cx - r, cy - r, cx + r, cy + r]
            if all(iou(box, b) == 0 for b in boxes):
                cls = int(rng.integers(0, 3))
                draw_shape(img, cls, cx, cy, r, int(rng.integers(150, 255)))
                boxes.append(box); labels.append(cls)
                break
    return img, np.array(boxes, np.float32), np.array(labels)

rng = np.random.default_rng(0)
train_scenes = [make_scene(rng) for _ in range(3000)]
```

```
test_scenes = [make_scene(rng) for _ in range(200)]

def show_scene(ax, img, boxes, labels, scores=None, color="lime"):
    ax.imshow(img, cmap="gray", vmin=0, vmax=255); ax.axis("off")
    for k, ((x1, y1, x2, y2), c) in enumerate(zip(boxes, labels)):
        ax.add_patch(mpatches.Rectangle((x1, y1), x2 - x1, y2 - y1, fill=False, ec=color,
lw=1.5))
        txt = CLASSES[int(c)] + (f" {scores[k]:.2f}" if scores is not None else "")
        ax.text(x1, y1 - 2, txt, color=color, fontsize=7)

fig, ax = plt.subplots(1, 6, figsize=(14, 2.6))
for a, (img, b, l) in zip(ax, train_scenes[:6]):
    show_scene(a, img, b, l)
plt.suptitle("training scenes with their true boxes"); plt.show()
```




```
def evaluate(all_predictions, scenes=test_scenes):
    # A prediction is correct if IoU >= 0.5 with a true box of the SAME class (each true box used
once)
    tp = fp = fn = 0
    for preds, (img, boxes, labels) in zip(all_predictions, scenes):
        gt = torch.tensor(boxes); used = set()
        for box, score, cls in preds:
            ious = box_iou(torch.tensor([box], dtype=torch.float32), gt)[0]
            k = int(ious.argmax())
            if ious[k] >= 0.5 and k not in used and labels[k] == cls:
                tp += 1; used.add(k)
            else:
                fp += 1
        fn += len(boxes) - len(used)
    precision = tp / max(tp + fp, 1)      # of the boxes we drew, how many were right?
    recall = tp / max(tp + fn, 1)         # of the real objects, how many did we find?
    return precision, recall
```

3 · R-CNN (2014): "propose regions, then classify each one"

Full name: Region-based Convolutional Neural Network (Girshick et al.). **Process:**

1. **Generate region proposals**: about 2,000 "maybe there's an object here" boxes per image (R-CNN used the *selective search* algorithm).
2. **Run a CNN on each region** separately: crop, resize, classify.
3. **Classify and refine** the bounding boxes, then remove duplicates with NMS.

Strength: high accuracy. **Weakness:** very slow, because the CNN runs **thousands of times per image**. **Key contribution:** the first major CNN-based detector. It proved deep learning works for detection.

Our version: proposals = **sliding windows** of 6 sizes (simpler than selective search), and the CNN is a small classifier for 4 classes: *background, circle, square, triangle*.

```python
def make_proposals():
    out = []
    for size in [12, 16, 20, 24, 28, 32]:                 # windows of several sizes...
        for y in range(0, IMG - size + 1, 4):             # ...slid across the image every 4
pixels
            for x in range(0, IMG - size + 1, 4):
                out.append([x, y, x + size, y + size])
    return torch.tensor(out, dtype=torch.float32)

PROPOSALS = make_proposals()
print("region proposals per image:", len(PROPOSALS))

CROP = 24
def crop_regions(img, boxes):
    # cut out every box and resize it to 24x24 (roi_align does crop+resize for many boxes at
once)
    t = torch.tensor(img, dtype=torch.float32)[None, None] / 255
    return roi_align(t, [boxes], output_size=(CROP, CROP), aligned=True)

# Training crops: true boxes (slightly jittered) = object classes 1..3;
# background = random windows (IoU < 0.3) + "hard negatives" that cover only PART of an object
(IoU 0.1-0.45)
rng2 = np.random.default_rng(1)
crops, crop_labels = [], []
for img, boxes, labels in train_scenes[:1500]:
    gt = torch.tensor(boxes)
    jittered = gt + torch.tensor(rng2.integers(-2, 3, gt.shape), dtype=torch.float32)
    crops.append(crop_regions(img, jittered)); crop_labels += [int(l) + 1 for l in labels]
    best_iou = box_iou(PROPOSALS, gt).max(1).values
    background = PROPOSALS[best_iou < 0.3][torch.tensor(rng2.choice(int((best_iou < 0.3).sum()),
3, replace=False))]
    partial = PROPOSALS[(best_iou > 0.1) & (best_iou < 0.45)]
    if len(partial) >= 3:
        background = torch.cat([background, partial[torch.tensor(rng2.choice(len(partial), 3,
replace=False))]])
    crops.append(crop_regions(img, background)); crop_labels += [0] * len(background)
crops = torch.cat(crops); crop_labels = torch.tensor(crop_labels)
print("training crops:", tuple(crops.shape), " class counts (bg, circle, square, triangle):",
torch.bincount(crop_labels).tolist())

torch.manual_seed(0)
region_classifier = nn.Sequential(
    nn.Conv2d(1, 16, 3, padding=1), nn.ReLU(), nn.MaxPool2d(2),
    nn.Conv2d(16, 32, 3, padding=1), nn.ReLU(), nn.MaxPool2d(2),
    nn.Flatten(), nn.Linear(32 * 6 * 6, 64), nn.ReLU(), nn.Linear(64, 4))
opt = torch.optim.Adam(region_classifier.parameters(), lr=2e-3)
t = time.time()
for epoch in range(8):
    perm = torch.randperm(len(crops))
    for i in range(0, len(crops), 128):
        idx = perm[i:i + 128]
        loss = F.cross_entropy(region_classifier(crops[idx]), crop_labels[idx])
        opt.zero_grad(); loss.backward(); opt.step()
region_classifier.eval()
print(f"region classifier trained in {time.time() - t:.0f} s")
```

```
region proposals per image: 2299
training crops: (11993, 1, 24, 24)  class counts (bg, circle, square, triangle): [9000, 1015, 98
5, 993]
region classifier trained in 9 s
```

```python
def rcnn_detect(img, score_threshold=0.9):
    with torch.no_grad():
        probs = F.softmax(region_classifier(crop_regions(img, PROPOSALS)), dim=1)   # CNN on
EVERY proposal
    score, cls = probs[:, 1:].max(1)                      # best non-background class per proposal
    keep = score > score_threshold
    boxes, score, cls = PROPOSALS[keep], score[keep], cls[keep]
    final = nms(boxes, score, 0.3)                        # remove duplicates
```

```
    return [(boxes[i].tolist(), score[i].item(), cls[i].item()) for i in final]

t = time.time()
rcnn_preds = [rcnn_detect(img) for img, _, _ in test_scenes]
rcnn_ms = (time.time() - t) / len(test_scenes) * 1000
rcnn_p, rcnn_r = evaluate(rcnn_preds)
print(f"R-CNN style: precision {rcnn_p:.1%}, recall {rcnn_r:.1%}, {rcnn_ms:.0f} ms per image "
      f"({len(PROPOSALS)} CNN runs per image)")
```

```
R-CNN style: precision 72.2%, recall 91.9%, 196 ms per image (2299 CNN runs per image)
```

4 · YOLO (2016): "You Only Look Once"

Process: treat detection as **one regression problem**. Split the image into an **S×S grid** (we use 6×6, so each cell is 16×16 pixels). In **one forward pass**, every cell predicts:

- **objectness**: "is the centre of an object in me?" (0–1),
- **box**: x and y offset inside the cell, width, height,
- **class probabilities**: circle / square / triangle.

So the network's output is a 6 × 6 × (1 + 4 + 3) block of numbers, the whole answer at once.

Strength: real-time speed. **Weakness:** less accurate for **small objects**, especially small objects close together, because each cell predicts only a limited number of objects. **Key contribution:** made detection practical for real-time uses like self-driving cars.

```
S = 6
CELL = IMG // S

def encode_target(boxes, labels):
    # turn the true boxes into the 6x6x8 grid of numbers the network should output
    t = torch.zeros(S, S, 5 + len(CLASSES))
    for (x1, y1, x2, y2), c in zip(boxes.tolist(), labels):
        cx, cy, w, h = (x1 + x2) / 2, (y1 + y2) / 2, x2 - x1, y2 - y1
        i, j = int(cy // CELL), int(cx // CELL)          # the cell that contains the object's
CENTRE
        t[i, j, 0] = 1                                   # objectness
        t[i, j, 1:5] = torch.tensor([cx / CELL - j, cy / CELL - i, w / IMG, h / IMG])
        t[i, j, 5 + c] = 1                               # one-hot class
    return t

Xtr = torch.tensor(np.stack([s[0] for s in train_scenes]), dtype=torch.float32)[:, None] / 255
Ytr = torch.stack([encode_target(s[1], s[2]) for s in train_scenes])
Xte = torch.tensor(np.stack([s[0] for s in test_scenes]), dtype=torch.float32)[:, None] / 255

class TinyYOLO(nn.Module):
    def __init__(self):
        super().__init__()
        def block(i, o):
            return nn.Sequential(nn.Conv2d(i, o, 3, padding=1), nn.BatchNorm2d(o),
nn.LeakyReLU(0.1))
        self.net = nn.Sequential(
            block(1, 16), nn.MaxPool2d(2),       # 96 -> 48
            block(16, 32), nn.MaxPool2d(2),      # 48 -> 24
            block(32, 64), nn.MaxPool2d(2),      # 24 -> 12
            block(64, 64), nn.MaxPool2d(2),      # 12 -> 6   (one value per grid cell)
            block(64, 128), nn.Conv2d(128, 5 + len(CLASSES), 1))
    def forward(self, x):
        return self.net(x).permute(0, 2, 3, 1)  # (batch, 6, 6, 8)

def yolo_loss(pred, target):
    has_obj = target[..., 0] == 1
    objectness = F.binary_cross_entropy_with_logits(pred[..., 0], target[..., 0])      # every
```

```
cell
    box = F.mse_loss(torch.sigmoid(pred[..., 1:5][has_obj]), target[..., 1:5][has_obj])  # only
cells with objects
    cls = F.cross_entropy(pred[..., 5:][has_obj], target[..., 5:][has_obj].argmax(-1))
    return 5 * objectness + 5 * box + cls

torch.manual_seed(0)
yolo = TinyYOLO()
opt = torch.optim.Adam(yolo.parameters(), lr=2e-3)
t = time.time()
for epoch in range(12):
    yolo.train()
    perm = torch.randperm(len(Xtr))
    for i in range(0, len(Xtr), 64):
        idx = perm[i:i + 64]
        loss = yolo_loss(yolo(Xtr[idx]), Ytr[idx])
        opt.zero_grad(); loss.backward(); opt.step()
yolo.eval()
print(f"TinyYOLO trained in {time.time() - t:.0f} s")
```

```
TinyYOLO trained in 83 s
```

```
def yolo_decode(pred, threshold=0.5):
    conf = torch.sigmoid(pred[..., 0])
    out = []
    for i in range(S):
        for j in range(S):
            if conf[i, j] > threshold:
                ox, oy, w, h = torch.sigmoid(pred[i, j, 1:5]).tolist()
                cx, cy, w, h = (j + ox) * CELL, (i + oy) * CELL, w * IMG, h * IMG
                out.append(([cx - w / 2, cy - h / 2, cx + w / 2, cy + h / 2], conf[i, j].item(),
pred[i, j, 5:].argmax().item()))
    return out


t = time.time()
with torch.no_grad():
    raw = yolo(Xte)                                          # ONE forward pass for all 200 images
yolo_ms = (time.time() - t) / len(Xte) * 1000
yolo_preds = [yolo_decode(raw[k]) for k in range(len(Xte))]
yolo_p, yolo_r = evaluate(yolo_preds)

print(f"{'':<14}{'precision':>10}{'recall':>9}{'ms / image':>12}")
print(f"{'R-CNN style':<14}{rcnn_p:>10.1%}{rcnn_r:>9.1%}{rcnn_ms:>12.1f}")
print(f"{'YOLO style':<14}{yolo_p:>10.1%}{yolo_r:>9.1%}{yolo_ms:>12.1f}")
print(f"\nYOLO is about {rcnn_ms / yolo_ms:.0f}x faster: 1 network run per image instead of
{len(PROPOSALS)}.")

fig, ax = plt.subplots(2, 6, figsize=(14, 5.2))
for k in range(6):
    img, b, l = test_scenes[k]
    for row, preds, name in [(0, rcnn_preds[k], "R-CNN style"), (1, yolo_preds[k], "YOLO
style")]:
        show_scene(ax[row, k], img, [p[0] for p in preds], [p[2] for p in preds], [p[1] for p in
preds],
                   color="orange" if row == 0 else "cyan")
    ax[0, k].set_title(f"{len(b)} true object(s)", fontsize=9)
ax[0, 0].text(-10, 48, "R-CNN", rotation=90, va="center"); ax[1, 0].text(-10, 48, "YOLO",
rotation=90, va="center")
plt.tight_layout(); plt.show()
```

```
               precision    recall  ms / image
R-CNN style        72.2%     91.9%       195.9
YOLO style         99.5%     99.0%         1.6

YOLO is about 126x faster: 1 network run per image instead of 2299.
```



The speed gap is the whole point. Our R-CNN runs its CNN about 2,300 times per image, while YOLO runs once. That's the **"why is R-CNN slow compared to YOLO?" (Medium Q10)** answer in one number.

Careful with the accuracy column: our *toy* R-CNN looks *less* accurate than toy-YOLO only because it's crude. Its boxes are stuck on a 4-pixel sliding grid and it has **no box-refinement step**. The real R-CNN used much better proposals (selective search), a large ImageNet-pretrained CNN and a **bounding-box regressor**. For years, R-CNN-family models (Fast/Faster R-CNN) were **more accurate** than YOLO, especially on small objects and cluttered scenes. The trade-off the course wants you to know:

	R-CNN	YOLO	SSD
Full name	Region-based CNN	You Only Look Once	Single Shot MultiBox Detector
Idea	propose regions → CNN on each	one pass, grid predicts boxes + classes	one pass, predictions from **several feature-map scales**
Speed	very slow (thousands of regions)	**fastest**, real-time	fast
Accuracy	**highest** (esp. small/complex)	lower on **small objects**	competitive; good across sizes
Best for	offline, accuracy-critical (**medical**)	real-time (**driving**, video)	balanced, **mobile**

How the R-CNN family got faster

- **Fast R-CNN (2015):** run the CNN **once** on the whole image, then crop each proposal from the *feature map* (RoI Pooling) instead of from the pixels.
- **Faster R-CNN (2015):** replace selective search with a small **Region Proposal Network (RPN)** that shares the same features. Mask R-CNN (notebook 05) builds on this.

5 · SSD (2016): Single Shot MultiBox Detector

Process: one pass, like YOLO, but predictions come from **multiple feature maps at different scales**:

- **early, large** feature maps (fine grid, small cells) → detect **small** objects,
- **late, small** feature maps (coarse grid, big cells) → detect **large** objects.


At every cell of every map, SSD checks a few **default boxes** ("anchors") of different shapes and predicts a class and a box correction for each.

Strengths: faster than R-CNN, competitive accuracy, handles **small and large objects in the same image** (Medium Q12). **Weakness:** slightly less accurate than R-CNN on very complex scenes.

```
# The six feature maps of SSD300 (input 300x300) and how many default boxes each contributes
ssd_maps = [(38, 4), (19, 6), (10, 6), (5, 6), (3, 4), (1, 4)]   # (grid size, boxes per cell)
total = 0
print(f"{'feature map':>12} {'cell size':>10} {'boxes':>7}   detects")
for size, k in ssd_maps:
    n = size * size * k; total += n
    kind = "small objects" if size >= 19 else ("medium objects" if size >= 5 else "large
objects")
    print(f"{size:>8}x{size:<3} {300 / size:>8.0f}px {n:>7}   {kind}")
print(f"{'total':>12} {'':>10} {total:>7} default boxes checked in ONE pass")

fig, ax = plt.subplots(1, 3, figsize=(12, 4))
img, b, l = test_scenes[1]
for a, (grid, title) in zip(ax, [(12, "fine 12x12 grid: small boxes"), (6, "6x6 grid: medium"),
(3, "coarse 3x3 grid: large boxes")]):
    a.imshow(img, cmap="gray"); a.set_title(title); a.axis("off")
    cell = IMG / grid
    for g in range(1, grid):
        a.axhline(g * cell, color="white", lw=0.4); a.axvline(g * cell, color="white", lw=0.4)
    cx = cy = (grid // 2 + 0.5) * cell                        # draw the default boxes of one cell
    for w, h in [(cell, cell), (cell * 1.6, cell * 0.8), (cell * 0.8, cell * 1.6)]:
        a.add_patch(mpatches.Rectangle((cx - w / 2, cy - h / 2), w, h, fill=False, ec="yellow",
lw=1.5))
plt.tight_layout(); plt.show()
```

```
  feature map   cell size    boxes   detects
       38x38         8px     5776   small objects
       19x19        16px     2166   small objects
       10x10        30px      600   medium objects
        5x5         60px      150   medium objects
        3x3        100px       36   large objects
        1x1        300px        4   large objects
        total                8732 default boxes checked in ONE pass
```




Our TinyYOLO uses a single 6×6 grid, and each cell predicts **one** object (the one whose centre falls in it). Our random training scenes never put two centres in the same cell. But in real photos, small objects in a crowd do: a flock of birds, people far away, distant cars. Let's build such a

scene by hand. A small circle and a small square are placed so that **both centres fall in the same 16×16 cell** (row 1, column 1), with a normal triangle elsewhere for comparison.

```
crowded = np.random.default_rng(5).normal(40, 12, (IMG, IMG)).clip(0, 255).astype(np.uint8)
draw_shape(crowded, 0, 18, 18, 6, 230)      # small circle, centre (18, 18) -> cell (1, 1)
draw_shape(crowded, 1, 30, 30, 6, 200)      # small square, centre (30, 30) -> ALSO cell (1, 1)
draw_shape(crowded, 2, 70, 66, 12, 220)     # a normal triangle elsewhere
crowded_boxes = np.array([[12, 12, 24, 24], [24, 24, 36, 36], [58, 54, 82, 78]], np.float32)
crowded_labels = np.array([0, 1, 2])

with torch.no_grad():
    yolo_found = yolo_decode(yolo(torch.tensor(crowded, dtype=torch.float32)[None, None] / 255)
[0])
rcnn_found = rcnn_detect(crowded)

fig, ax = plt.subplots(1, 3, figsize=(12, 4.2))
show_scene(ax[0], crowded, crowded_boxes, crowded_labels); ax[0].set_title("truth: 3 objects")
show_scene(ax[1], crowded, [p[0] for p in yolo_found], [p[2] for p in yolo_found], [p[1] for p in
yolo_found], color="cyan")
ax[1].set_title(f"YOLO style found {len(yolo_found)}")
show_scene(ax[2], crowded, [p[0] for p in rcnn_found], [p[2] for p in rcnn_found], [p[1] for p in
rcnn_found], color="orange")
ax[2].set_title(f"R-CNN style found {len(rcnn_found)}")
for g in range(1, S):                                  # draw YOLO's grid on the middle panel
    ax[1].axhline(g * CELL, color="white", lw=0.4); ax[1].axvline(g * CELL, color="white",
lw=0.4)
plt.tight_layout(); plt.show()
print("YOLO-style precision/recall on this scene  :", [round(v, 2) for v in
evaluate([yolo_found], [(crowded, crowded_boxes, crowded_labels)])])
print("R-CNN-style precision/recall on this scene :", [round(v, 2) for v in
evaluate([rcnn_found], [(crowded, crowded_boxes, crowded_labels)])])
```




```
YOLO-style precision/recall on this scene  : [0.5, 0.33]
R-CNN-style precision/recall on this scene : [0.75, 1.0]
```

What happened: both small shapes have their centres in the **same grid cell**, and that cell can output only one box. TinyYOLO produces a single, badly placed box somewhere between the circle and the square, and misses one object completely. The R-CNN style detector checks thousands of independent windows, so it finds **both** small shapes, at over 100× the cost. (It also leaves a duplicate box on the triangle, a reminder that its partial-window problem never fully goes away.)

This is YOLO's "**less accurate for small objects**" weakness in miniature. The original YOLO used a 7×7 grid with only 2 boxes per cell, so flocks of birds or distant crowds lost objects exactly like this.

How would you adapt YOLO for very small objects? (Hard Q6)

- **Higher input resolution** and/or a **finer grid** (more, smaller cells).
- **Multi-scale prediction heads**, as SSD does (later YOLO versions, v3 onwards, predict at 3 scales using a Feature Pyramid Network).
- **More boxes per cell / anchors sized for small objects** (choose anchor sizes by clustering the training boxes).
- **Tiling**: cut a large image into overlapping tiles, detect in each and merge (common for drone and satellite images).
- **Data augmentation** (mosaic, copy-paste of small objects) and giving small objects more weight in the loss.

6 · Which architecture for which job? (Medium Q13–14)

	Medical imaging	Autonomous driving
Priority	**Accuracy > speed**	**Speed > accuracy**
Choice	**R-CNN family** (Faster R-CNN; Mask R-CNN for exact outlines)	**YOLO** (or SSD)
Why	missing a tumour (a false negative) is unacceptable; small lesions need precise localization; analysis is offline, so a few seconds per scan is fine	must detect pedestrians, vehicles and signs **in real time** (30+ frames/second); a slightly less precise box *now* beats a perfect box too late
Example	finding small tumours in MRI scans	spotting a pedestrian stepping onto the road

Key insight: the choice depends on the application's **tolerance for errors** versus its **need for real-time performance**.

7 · Optional: try a real pretrained detector on your own photo

Our toy models only know circles, squares and triangles. Real detectors trained on COCO know 80 classes (person, car, dog…). This cell downloads a pretrained **Faster R-CNN** (~160 MB) the first time, so set `RUN = True` on your own machine with internet.

```
RUN = False          # set to True to try it (downloads weights on first run)
IMAGE_PATH = "../../week-1/code/sample.jpg"

if RUN:
    from torchvision.models.detection import fasterrcnn_resnet50_fpn,
FasterRCNN_ResNet50_FPN_Weights
    weights = FasterRCNN_ResNet50_FPN_Weights.DEFAULT
    detector = fasterrcnn_resnet50_fpn(weights=weights).eval()
    photo = cv2.cvtColor(cv2.imread(IMAGE_PATH), cv2.COLOR_BGR2RGB)
    with torch.no_grad():
        out = detector([torch.tensor(photo).permute(2, 0, 1).float() / 255])[0]
    plt.figure(figsize=(10, 6)); plt.imshow(photo); plt.axis("off")
    for box, label, score in zip(out["boxes"], out["labels"], out["scores"]):
        if score > 0.6:
            x1, y1, x2, y2 = box.tolist()
            plt.gca().add_patch(mpatches.Rectangle((x1, y1), x2 - x1, y2 - y1, fill=False,
```

```
ec="red", lw=2))
            plt.text(x1, y1, f"{weights.meta['categories'][label]} {score:.2f}", color="white",
backgroundcolor="red", fontsize=8)
    plt.show()
else:
    print("Skipped. Set RUN = True to download and run a pretrained Faster R-CNN on your own
image.")
```

```
Skipped. Set RUN = True to download and run a pretrained Faster R-CNN on your own image.
```

✅ Check yourself

1. What does object detection identify? *(what each object is (class) and where it is (bounding box))*
2. What do R-CNN, YOLO and SSD stand for? *(Region-based CNN; You Only Look Once; Single Shot MultiBox Detector)*
3. Why is R-CNN slow? *(it runs a CNN separately on ~2,000 region proposals per image)*
4. How does YOLO treat detection differently? *(as one regression problem: a grid predicts boxes and classes in a single forward pass)*
5. Why is SSD good with different object sizes? *(it predicts from several feature maps: fine maps for small objects, coarse maps for large ones)*
6. What do IoU and NMS do? *(IoU measures box overlap; NMS keeps the best box and removes overlapping duplicates)*
7. Medical imaging vs self-driving: which detector and why? *(R-CNN family for accuracy; YOLO/SSD for real-time speed)*

05 · Segmentation: FCN, U-Net and Mask R-CNN

Covers (Week 3 Key Concepts): "Semantic Segmentation Architectures" (FCN, U-Net, encoder, decoder, skip connections) and "Mask R-CNN" (RPN, RoI Align, three outputs). **Questions answered here:** Easy 19–20 · Medium 15–20 · Hard 7–9 · Mask R-CNN 1–8.

> **Semantic segmentation = give a class label to *every pixel* in an image.**

	Output	Two touching cats →
Detection (notebook 04)	boxes + labels	two boxes
Semantic segmentation	a class for every pixel	one "cat" region (it doesn't separate individuals)
Instance segmentation (Mask R-CNN)	a separate mask for every object	cat #1 mask and cat #2 mask

The central challenge: segmentation needs both **context** (*what* is this? which needs a big view of the image) and **precision** (*exactly where* is the boundary? which needs fine pixel detail). Classification only needs the first.

```
%matplotlib inline
import time
import numpy as np
import matplotlib.pyplot as plt
import cv2
import torch
import torch.nn as nn
import torch.nn.functional as F
from torchvision.ops import roi_pool, roi_align

torch.manual_seed(0)
print("torch", torch.__version__)
```

```
torch 2.14.1+cu130
```

1 · A segmentation dataset: every pixel has a label

64×64 noisy images with circles, squares and triangles. The **mask** labels each pixel: 0 = background, 1 = circle, 2 = square, 3 = triangle. We get it for free by drawing each shape twice: once into the image and once (with its class number) into the mask.


```
IMG = 64
NAMES = ["background", "circle", "square", "triangle"]

def draw(img, mask, cls, cx, cy, r, brightness):
    for target, value in [(img, brightness), (mask, cls + 1)]:
        if cls == 0:
            cv2.circle(target, (cx, cy), r, value, -1)
        elif cls == 1:
            cv2.rectangle(target, (cx - r, cy - r), (cx + r, cy + r), value, -1)
        else:
            cv2.fillPoly(target, [np.array([[cx, cy - r], [cx - r, cy + r], [cx + r, cy + r]],
np.int32)], value)
```

```
def make_sample(rng):
    img = rng.normal(60, 15, (IMG, IMG)).clip(0, 255).astype(np.uint8)
    mask = np.zeros((IMG, IMG), np.uint8)
    for _ in range(rng.integers(1, 4)):
        r = int(rng.integers(5, 14)); cx = int(rng.integers(r, IMG - r)); cy =
int(rng.integers(r, IMG - r))
        draw(img, mask, int(rng.integers(0, 3)), cx, cy, r, int(rng.integers(140, 255)))
    return img, mask

rng = np.random.default_rng(0)
train = [make_sample(rng) for _ in range(2000)]
test = [make_sample(rng) for _ in range(200)]
Xtr = torch.tensor(np.stack([a for a, _ in train]), dtype=torch.float32)[:, None] / 255
Ytr = torch.tensor(np.stack([b for _, b in train])).long()
Xte = torch.tensor(np.stack([a for a, _ in test]), dtype=torch.float32)[:, None] / 255
Yte = torch.tensor(np.stack([b for _, b in test])).long()

mask_cmap = plt.matplotlib.colors.ListedColormap(["black", "tab:red", "tab:green", "tab:blue"])
fig, ax = plt.subplots(2, 6, figsize=(13, 4.4))
for k in range(6):
    ax[0, k].imshow(train[k][0], cmap="gray"); ax[0, k].axis("off")
    ax[1, k].imshow(train[k][1], cmap=mask_cmap, vmin=0, vmax=3); ax[1, k].axis("off")
ax[0, 0].set_title("image", loc="left"); ax[1, 0].set_title("mask (red circle, green square, blue
triangle)", loc="left")
plt.tight_layout(); plt.show()
```



2 · FCN: Fully Convolutional Network (2015)

Problem solved: classic CNNs end with **fully connected layers**. These flatten the feature maps into a vector, which **throws away *where* things are**, and they only accept one fixed input size. **Innovation: replace the fully connected layers with convolutional layers.** Everything stays a 2-D map, so the output is a **dense, pixel-wise prediction map** (one class score per pixel), for any input size. **Key idea:** end-to-end segmentation using convolutional layers only.

```
def conv_block(c_in, c_out):
    return nn.Sequential(nn.Conv2d(c_in, c_out, 3, padding=1), nn.BatchNorm2d(c_out), nn.ReLU(),
                         nn.Conv2d(c_out, c_out, 3, padding=1), nn.BatchNorm2d(c_out), nn.ReLU())

class FCN(nn.Module):
    # encoder shrinks 64 -> 8 (x1/8); a 1x1 conv gives class scores; then simply stretch back x8
    def __init__(self, n_classes=4):
        super().__init__()
        self.enc1, self.enc2, self.enc3, self.bottom = conv_block(1, 16), conv_block(16, 32),
conv_block(32, 64), conv_block(64, 64)
        self.classify = nn.Conv2d(64, n_classes, kernel_size=1)          # a conv instead of an
FC layer
    def forward(self, x):
        x = self.enc1(x)
```

```
        x = self.enc2(F.max_pool2d(x, 2))
        x = self.enc3(F.max_pool2d(x, 2))
        x = self.bottom(F.max_pool2d(x, 2))                                  # 8x8 map of rich "what"
features
        return F.interpolate(self.classify(x), scale_factor=8, mode="bilinear",
align_corners=False)

fcn = FCN()
for size in [64, 128]:
    out = fcn(torch.zeros(1, 1, size, size))
    print(f"input {size}x{size}  ->  output {tuple(out.shape)}   (4 class scores for every
pixel)")
```

```
input 64x64  ->  output (1, 4, 64, 64)   (4 class scores for every pixel)
input 128x128  ->  output (1, 4, 128, 128)   (4 class scores for every pixel)
```

No `Flatten`, no `nn.Linear`. The same network accepts 64×64 *or* 128×128 images and returns a map of the same size. Use sizes divisible by 8 here, because each pooling step rounds odd sizes down. **Weakness:** the prediction is made on an **8×8 map** and then blown up 8×. Each predicted value covers an 8×8-pixel block, so **predictions are coarse and boundaries blurry** (Medium Q17). Let's see that by training it.

```
def train_seg(model, epochs=6, lr=2e-3, batch=32):
    opt = torch.optim.Adam(model.parameters(), lr=lr)
    for _ in range(epochs):
        model.train()
        perm = torch.randperm(len(Xtr))
        for i in range(0, len(Xtr), batch):
            idx = perm[i:i + batch]
            loss = F.cross_entropy(model(Xtr[idx]), Ytr[idx])      # cross-entropy computed at
EVERY pixel
            opt.zero_grad(); loss.backward(); opt.step()
    model.eval()
    with torch.no_grad():
        return model(Xte).argmax(1)

def mean_iou(pred, truth):
    ious = []
    for c in range(1, 4):
        inter = ((pred == c) & (truth == c)).sum().item(); union = ((pred == c) | (truth ==
c)).sum().item()
        if union:
            ious.append(inter / union)
    return float(np.mean(ious))


def boundary_accuracy(pred, truth):
    # accuracy measured ONLY on pixels lying on object edges - the hard part of segmentation
    edges = np.stack([cv2.morphologyEx((m > 0).astype(np.uint8), cv2.MORPH_GRADIENT, np.ones((3,
3), np.uint8))
                      for m in truth.numpy()]) > 0
    return (pred.numpy()[edges] == truth.numpy()[edges]).mean()

torch.manual_seed(0)
t = time.time()
fcn_pred = train_seg(FCN())
print(f"FCN trained in {time.time() - t:.0f} s:  mean IoU {mean_iou(fcn_pred, Yte):.3f},  "
      f"pixel accuracy {(fcn_pred == Yte).float().mean():.1%},  accuracy on boundary pixels
{boundary_accuracy(fcn_pred, Yte):.1%}")
```

```
FCN trained in 24 s:  mean IoU 0.824,  pixel accuracy 97.9%,  accuracy on boundary pixels 77.2%
```

3 · U-Net (2015): encoder + decoder + skip connections

Designed for **biomedical images** (cells under a microscope), U-Net is now the standard in medical segmentation.



- **Encoder (downsampling path):** conv + pooling **reduce the resolution** while building **context and high-level features** ("this region looks like a tumour"). It's like summarising a photo: you keep the big picture and lose fine detail.
- **Decoder (upsampling path): transposed convolutions** (learned upsampling) **recover the spatial resolution** to produce pixel-level predictions. It's like expanding the summary back to full size, but now with a label on every pixel.
- **Skip connections: copy** each encoder level's feature maps across and **concatenate** them with the decoder at the same resolution. This brings back the **fine edge details** that pooling threw away and combines **low-level detail** (edges, from early layers) with **high-level context** (meaning, from deep layers).

> **In short: the encoder compresses for context, the decoder reconstructs for precision, and skip connections bridge the two so no important detail is lost.**


```
class UNet(nn.Module):
    def __init__(self, n_classes=4):
        super().__init__()
        self.enc1, self.enc2, self.enc3, self.bottom = conv_block(1, 16), conv_block(16, 32),
conv_block(32, 64), conv_block(64, 64)
        self.up3, self.dec3 = nn.ConvTranspose2d(64, 64, 2, stride=2), conv_block(64 + 64, 64)
        self.up2, self.dec2 = nn.ConvTranspose2d(64, 32, 2, stride=2), conv_block(32 + 32, 32)
        self.up1, self.dec1 = nn.ConvTranspose2d(32, 16, 2, stride=2), conv_block(16 + 16, 16)
        self.classify = nn.Conv2d(16, n_classes, 1)
    def forward(self, x):
        e1 = self.enc1(x)                                   # 64x64, fine detail
        e2 = self.enc2(F.max_pool2d(e1, 2))                 # 32x32
        e3 = self.enc3(F.max_pool2d(e2, 2))                 # 16x16
        b = self.bottom(F.max_pool2d(e3, 2))                # 8x8, most context
        d3 = self.dec3(torch.cat([self.up3(b), e3], dim=1))     # upsample + SKIP from e3
        d2 = self.dec2(torch.cat([self.up2(d3), e2], dim=1))    # upsample + SKIP from e2
        d1 = self.dec1(torch.cat([self.up1(d2), e1], dim=1))    # upsample + SKIP from e1
        return self.classify(d1)

# Transposed convolution = learned upsampling (doubles height and width here)
print("transposed conv:", tuple(nn.ConvTranspose2d(64, 32, 2, stride=2)(torch.zeros(1, 64, 8,
8)).shape), "<- from (1, 64, 8, 8)")

torch.manual_seed(0)
t = time.time()
unet_pred = train_seg(UNet())
print(f"U-Net trained in {time.time() - t:.0f} s:  mean IoU {mean_iou(unet_pred, Yte):.3f},  "
      f"pixel accuracy {(unet_pred == Yte).float().mean():.1%},  accuracy on boundary pixels
{boundary_accuracy(unet_pred, Yte):.1%}")
```

```
transposed conv: (1, 32, 16, 16) <- from (1, 64, 8, 8)
U-Net trained in 63 s:  mean IoU 0.941,  pixel accuracy 99.6%,  accuracy on boundary pixels 99.2%
```

```
fig, ax = plt.subplots(4, 5, figsize=(12, 10))
for col, k in enumerate([0, 3, 7, 11, 15]):
    rows = [(Xte[k, 0], "gray", "image"), (Yte[k], mask_cmap, "truth"),
            (fcn_pred[k], mask_cmap, "FCN (no skips)"), (unet_pred[k], mask_cmap, "U-Net
(skips)")]
    for row, (im, cmap, title) in enumerate(rows):
        ax[row, col].imshow(im, cmap=cmap, vmin=0, vmax=(1 if cmap == "gray" else 3))
        ax[row, col].axis("off")
        if col == 0:
            ax[row, col].set_title(title, loc="left")
plt.tight_layout(); plt.show()
```



Look at the edges. The FCN's shapes are blobby: corners are rounded off and triangles lose their points, because its decision was made at 1/8 resolution. The U-Net reproduces sharp corners. The *boundary-pixel accuracy* numbers above measure exactly this.

Why skip connections help (Medium Q18, Hard Q8): pooling discards *where* edges are, so the deepest layers know *what* but not *exactly where*. The skip connections hand the decoder the high-resolution feature maps from the encoder, so it can place each boundary precisely. The encoder supplies context, the skips supply precision, and the decoder combines both.

Why U-Net is everywhere in medical imaging (Medium Q20):

1. **Precise boundaries**, which you need to measure tumour size and plan surgery or radiotherapy.

2. **Small structures** (cells, lesions, vessels) survive thanks to the skip connections.
3. It **works with small datasets** (medical labels are expensive), helped by heavy augmentation.


Satellite imagery (Hard Q9): choose a **U-Net** (often with a pretrained ResNet or EfficientNet encoder). Roads, rivers and building outlines are thin structures with sharp boundaries that need pixel precision, and the encoder's context separates look-alike classes (roof vs road). Very large images are processed in overlapping tiles. Use **Mask R-CNN** instead if you need to count *individual* buildings or cars (instance segmentation).

4 · Mask R-CNN (2017): detection + a mask for every object

Limitation it addresses (Q1): detectors output only **boxes + labels**. Many applications need the **exact shape of each individual object**, i.e. **instance segmentation**. Semantic segmentation can't separate touching objects of the same class. Let's see that:

```
touching = np.zeros((64, 128), np.uint8)
cv2.circle(touching, (40, 32), 22, 1, -1)
cv2.circle(touching, (78, 32), 22, 1, -1)        # two circles that overlap/touch

n_regions, regions = cv2.connectedComponents(touching)
fig, ax = plt.subplots(1, 3, figsize=(12, 2.8))
ax[0].imshow(touching, cmap="gray"); ax[0].set_title("two touching coins")
ax[1].imshow(touching, cmap=mask_cmap, vmin=0, vmax=3); ax[1].set_title(f"semantic mask: 'coin'
pixels -> {n_regions - 1} region")
inst = np.zeros_like(touching)
yy, xx = np.mgrid[:64, :128]
inst[(touching > 0) & ((xx - 40) ** 2 + (yy - 32) ** 2 <= (xx - 78) ** 2 + (yy - 32) ** 2)] = 1
inst[(touching > 0) & (inst == 0)] = 2
ax[2].imshow(inst, cmap=mask_cmap, vmin=0, vmax=3); ax[2].set_title("instance masks: coin #1 and
coin #2")
for a in ax: a.axis("off")
plt.tight_layout(); plt.show()
```



Architecture: Faster R-CNN + a mask branch

Base: Faster R-CNN (a detector). **Extension:** a **segmentation mask branch** for every Region of Interest (RoI).

How it works, step by step:

1. **Backbone** (e.g. ResNet-50 + FPN): computes feature maps of the whole image once.
2. **Region Proposal Network (RPN)** (Q3): a small network that slides over the feature map and **suggests candidate object regions** ("something might be here"), with objectness scores. It replaces the slow selective search of R-CNN.

3. **RoI Align** (Q4): cuts out a fixed-size feature patch (e.g. 7×7) for each proposal, **precisely**, without rounding coordinates (see the demo below).
4. **Classification + bounding-box regression:** what object is it, plus a refined box.
5. **Mask branch:** a small FCN that predicts a **binary mask** (e.g. 28×28) inside each box. It runs in parallel with step 4.

Three outputs per object (Q5): ① a bounding box ② a class label ③ a pixel-level mask.

Why RoI Align? (Q4)

Proposal boxes have **fractional** coordinates on the feature map (a box from x = 1.3 to 3.7). The older **RoI Pooling rounds** them to whole cells (1 to 4), so the extracted features are slightly **misaligned** with the object. For boxes that hardly matters, but for **pixel-accurate masks** a shift of half a feature cell becomes many pixels in the image (each cell might cover 16 pixels). **RoI Align** removes the rounding: it **samples the feature map exactly at the fractional positions using bilinear interpolation**. Let's see the difference:

```
# A feature map whose value at every position = its x coordinate (0, 1, 2, ... 7), so
misalignment is easy to read
fmap = torch.arange(8, dtype=torch.float32).repeat(8, 1)[None, None]   # (1, 1, 8, 8)
box = torch.tensor([[0, 1.3, 1.3, 3.7, 3.7]])                           # (batch index, x1, y1,
x2, y2) - fractional!

pooled = roi_pool(fmap, box, output_size=(1, 4), spatial_scale=1.0)
# aligned=False: our toy map stores each value AT its whole-number coordinate (x=0,1,2,...)
aligned = roi_align(fmap, box, output_size=(1, 4), spatial_scale=1.0, sampling_ratio=2,
aligned=False)

# What the 4 output columns SHOULD contain: the x positions at the centres of 4 equal slices of
1.3 .. 3.7
exact = [1.3 + (i + 0.5) * (3.7 - 1.3) / 4 for i in range(4)]
print("ideal values            :", np.round(exact, 2))
print("RoI Pool  (rounds box)  :", pooled[0, 0, 0].numpy(), "<- snapped to whole cells")
print("RoI Align (bilinear)    :", aligned[0, 0, 0].numpy().round(2), "<- follows the true box")
```

```
ideal values            : [1.6 2.2 2.8 3.4]
RoI Pool  (rounds box)  : [1. 2. 3. 4.] <- snapped to whole cells
RoI Align (bilinear)    : [1.6 2.2 2.8 3.4] <- follows the true box
```

RoI Pool's values are snapped to whole feature cells (and taking the max inside each bin biases them further). RoI Align reproduces the ideal values exactly, because it samples where the true box is. For segmentation masks this misalignment translates directly into shifted mask edges. RoI Align improved mask accuracy noticeably in the paper.

Applications (Q7)

- **Medical imaging:** tumour segmentation, organ boundaries.
- **Autonomous driving:** pedestrians, vehicles and lane markings with precise shapes.
- **Crowd analysis:** separating overlapping people in dense scenes.
- **Others:** robotics grasping (exact object outline), photo editing (cut out a person), retail shelf analysis, agriculture (individual fruit or leaves).

Overlapping objects in crowded scenes (Q8)

Mask R-CNN treats each object as its own **proposal (RoI)**. Each RoI gets its own class and **its own mask**, predicted only inside its box. Two overlapping people become two RoIs with two separate masks, even where they touch. NMS removes duplicate proposals. Each mask is a binary *this object / not this object* prediction per RoI, so masks of different objects don't compete with each other.

Why pixel masks beat boxes in medical imaging (Q6)

1. **Precise localization:** tumours and organs have irregular shapes, and a box includes lots of healthy tissue.
2. **Quantitative analysis:** masks give the true **size, area and volume**, while boxes overestimate them (e.g. tumour volume for chemotherapy dosing).
3. **Clinical decisions:** surgery and radiotherapy need the exact border and how it spreads.
4. **Overlaps:** a tumour inside an organ can't be separated by boxes, but masks can.

> **Key insight:** boxes say *"there's a tumour here"*; masks say *exactly which pixels are tumour*.

5 · Optional: a real pretrained Mask R-CNN on your photo

Downloads about 170 MB of weights the first time. Set `RUN = True` on your own machine.

```
RUN = False
IMAGE_PATH = "../../week-1/code/sample.jpg"

if RUN:
    from torchvision.models.detection import maskrcnn_resnet50_fpn, MaskRCNN_ResNet50_FPN_Weights
    weights = MaskRCNN_ResNet50_FPN_Weights.DEFAULT
    model = maskrcnn_resnet50_fpn(weights=weights).eval()
    photo = cv2.cvtColor(cv2.imread(IMAGE_PATH), cv2.COLOR_BGR2RGB)
    with torch.no_grad():
        out = model([torch.tensor(photo).permute(2, 0, 1).float() / 255])[0]
    overlay = photo.copy()
    for mask, label, score in zip(out["masks"], out["labels"], out["scores"]):
        if score > 0.6:
            colour = np.random.randint(0, 255, 3)
            overlay[mask[0].numpy() > 0.5] = (0.5 * overlay[mask[0].numpy() > 0.5] + 0.5 *
colour).astype(np.uint8)
            print(f"{weights.meta['categories'][label]:<12} score {score:.2f}")
    plt.figure(figsize=(10, 6)); plt.imshow(overlay); plt.axis("off"); plt.show()
else:
    print("Skipped. Set RUN = True to download and run a pretrained Mask R-CNN.")
```

```
Skipped. Set RUN = True to download and run a pretrained Mask R-CNN.
```

Key takeaways

- **FCN:** the first step. Replacing FC layers with conv layers proved CNNs can do segmentation, but predictions are **coarse**.
- **U-Net:** improved precision with an **encoder–decoder + skip connections**, and became the standard in medical imaging.

- **Mask R-CNN:** extended detection to **instance segmentation**. Faster R-CNN + mask branch + **RoI Align**: box, class and mask per object.

✅ Check yourself

1. What is semantic segmentation? *(assigning a class label to every pixel)*
2. How does an FCN's output differ from a normal CNN's? *(a dense per-pixel map instead of one label; FC layers replaced by convolutions)*
3. Why are FCN predictions coarse? *(they're made at low resolution after pooling, then upsampled; fine detail is lost)*
4. Roles of encoder and decoder in U-Net? *(encoder: downsample to capture context/what; decoder: upsample to recover resolution/where)*
5. What do U-Net's skip connections do? *(pass high-resolution encoder features to the decoder to restore fine boundaries)*
6. Mask R-CNN's three outputs? *(bounding box, class label, pixel mask)*
7. Why RoI Align instead of RoI Pooling? *(no coordinate rounding; bilinear sampling keeps features aligned, giving accurate masks)*

06 · Sequence modeling for video: RNN, LSTM, CNN + LSTM

Covers (Week 3 Key Concepts): "Sequence Modeling for Video", "RNNs and LSTMs", "RNN vs LSTM", "What features would CNN / LSTM capture?". **Questions answered here:** Sequence 9–14 · RNN vs LSTM 15–18.

> **Sequence modeling** = building models for data that comes **in order over time**, where the current element **depends on what came before** (*temporal dependencies*).

A **video is a sequence of frames**. To understand it you need two things:

- **spatial features**: *what* is in each frame (a hand, a ball, a car). A **CNN** handles this.
- **temporal dependencies**: *how* things change across frames (the hand moves left → right). An **RNN / LSTM** handles this.

Analogy from the notes: the **CNN is a photographer** who takes and describes snapshots; the **LSTM is a storyteller** who connects the snapshots into a narrative.

```
%matplotlib inline
import time
import numpy as np
import matplotlib.pyplot as plt
import torch
import torch.nn as nn
import torch.nn.functional as F

torch.manual_seed(0)
print("torch", torch.__version__)
```

```
torch 2.14.1+cu130
```

1 · Why a CNN alone can't understand motion (Q9)

Below are two short videos of a square. One moves **right**, the other moves **left**. Each frame on its own, which is all a CNN sees, looks the same in both: "a square". Even if you have **all** the frames but **shuffle their order**, you can't tell the direction. **The information is in the order.**

```
T, H = 8, 32                        # 8 frames of 32x32 pixels
DIRS = ["right", "left", "down", "up"]


def make_video(rng):
    d = int(rng.integers(0, 4)); speed = int(rng.integers(2, 4)); size = int(rng.integers(5, 9))
    span = speed * (T - 1)
    if d in (0, 1):
        x0, y0 = int(rng.integers(0, H - size - span)), int(rng.integers(0, H - size))
        xs = [x0 + speed * t for t in range(T)] if d == 0 else [x0 + span - speed * t for t in
range(T)]
        ys = [y0] * T
    else:
        y0, x0 = int(rng.integers(0, H - size - span)), int(rng.integers(0, H - size))
        ys = [y0 + speed * t for t in range(T)] if d == 2 else [y0 + span - speed * t for t in
range(T)]
```

```
        xs = [x0] * T
    video = np.zeros((T, 1, H, H), np.float32)
    for t in range(T):
        video[t, 0, ys[t]:ys[t] + size, xs[t]:xs[t] + size] = 1
    video += rng.normal(0, 0.1, video.shape).astype(np.float32)        # a little camera noise
    return video, d

rng = np.random.default_rng(0)
train = [make_video(rng) for _ in range(2000)]
test = [make_video(rng) for _ in range(400)]
Xtr = torch.tensor(np.stack([v for v, _ in train])); ytr = torch.tensor([d for _, d in train])
Xte = torch.tensor(np.stack([v for v, _ in test])); yte = torch.tensor([d for _, d in test])
print("videos:", tuple(Xtr.shape), "= (clips, frames, channels, height, width)")

right = next(v for v, d in train if d == 0); left = next(v for v, d in train if d == 1)
fig, ax = plt.subplots(2, T, figsize=(13, 3.6))
for t in range(T):
    ax[0, t].imshow(right[t, 0], cmap="gray"); ax[0, t].set_title(f"t={t}"); ax[0, t].axis("off")
    ax[1, t].imshow(left[t, 0], cmap="gray"); ax[1, t].axis("off")
ax[0, 0].text(-12, 16, "right", rotation=90, va="center"); ax[1, 0].text(-12, 16, "left",
rotation=90, va="center")
plt.tight_layout(); plt.show()
```

```
videos: (2000, 8, 1, 32, 32) = (clips, frames, channels, height, width)
```



2 · RNN: a network with memory

A **Recurrent Neural Network** processes a sequence **one step at a time** and keeps a **hidden state** *h*, a small vector that carries information forward:

$h_t = \tanh(W \cdot x_t + U \cdot h_{t-1} + b)$

The new memory mixes the **current input** x_t with the **previous memory** h_{t-1}. The same weights W and U are reused at every step.


Strengths: captures order and context (e.g. "bank" means river-bank or money-bank depending on earlier words). **Limitation: short-term memory.** Information from early steps **fades** as it is squashed through tanh and multiplied by U again and again. That's the **vanishing gradient problem** again, this time across *time steps* instead of layers. Watch a single "memory" fade:

```
torch.manual_seed(0)
rnn_cell = nn.RNNCell(input_size=1, hidden_size=16)
h = torch.zeros(1, 16)
inputs = [1.0] + [0.0] * 29                          # a single "event" at t=0, then 29 empty
steps
with_event = []
for x in inputs:
    h = rnn_cell(torch.tensor([[x]]), h)
    with_event.append(h)

# Run again with NO event, then compare the two hidden states step by step:
```

```python
# the difference is the "trace" of the event that the RNN still remembers
h0 = torch.zeros(1, 16); diff = []
for t, x in enumerate([0.0] * 30):
    h0 = rnn_cell(torch.tensor([[x]]), h0)
    diff.append((with_event[t] - h0).norm().item())

plt.figure(figsize=(7, 3.2))
plt.semilogy(diff, "o-")
plt.xlabel("time steps after the event"); plt.ylabel("trace of the event in h (log scale)")
plt.title("A plain RNN forgets: the event's trace shrinks every step"); plt.grid(alpha=0.3);
plt.show()
print(f"trace after 1 step: {diff[0]:.3f}   after 10 steps: {diff[10]:.1e}   after 29 steps:
{diff[29]:.1e}")
```




```
trace after 1 step: 0.479   after 10 steps: 9.2e-04   after 29 steps: 4.0e-08
```

3 · LSTM: Long Short-Term Memory

An **LSTM** is a special RNN designed for **long-range dependencies**. It keeps a separate **cell state** c_t, a "conveyor belt" of memory, and three **gates** (each a number between 0 and 1, computed by a small sigmoid layer) decide what happens to it:

Gate	Question it answers	Formula (σ = sigmoid)
Forget gate f_t	what past information should I **discard**?	$f_t = \sigma(W_f \cdot [h_{t-1}, x_t] + b_f)$
Input gate i_t	what **new** information should I **store**?	$i_t = \sigma(W_i \cdot [h_{t-1}, x_t] + b_i)$
Output gate o_t	what should I **pass forward** right now?	$o_t = \sigma(W_o \cdot [h_{t-1}, x_t] + b_o)$

$c_t = f_t \odot c_{t-1} + i_t \odot \tilde{c}_t$ (keep some old memory + add some new candidate memory $\tilde{c}_t$) **$h_t = o_t \odot \tanh(c_t)$**

Why this beats vanishing gradients (Q15): the cell state is updated by **multiplying by f_t and *adding*** new information, not squashed through tanh at every step. When the forget gate is about 1 ("keep this"), the memory and its gradient pass through many steps almost unchanged. It's the same "additive highway" trick as ResNet's skip connection, but across time.

One LSTM step by hand

```
torch.manual_seed(1)
cell = nn.LSTMCell(input_size=2, hidden_size=3)
x = torch.tensor([[1.0, -0.5]]); h_prev = torch.zeros(1, 3); c_prev = torch.tensor([[0.8, -0.3,
0.5]])

# PyTorch stores the 4 parts stacked as [input gate, forget gate, candidate, output gate]
z = x @ cell.weight_ih.T + cell.bias_ih + h_prev @ cell.weight_hh.T + cell.bias_hh
i_gate, f_gate, g_cand, o_gate = z.chunk(4, dim=1)
i_gate, f_gate, o_gate, g_cand = torch.sigmoid(i_gate), torch.sigmoid(f_gate),
torch.sigmoid(o_gate), torch.tanh(g_cand)
c_new = f_gate * c_prev + i_gate * g_cand
h_new = o_gate * torch.tanh(c_new)

np.set_printoptions(precision=3, suppress=True)
print("forget gate f:", f_gate.detach().numpy()[0], " (1 = keep old memory, 0 = erase)")
print("input gate  i:", i_gate.detach().numpy()[0], " (how much new info to write)")
print("candidate  c~:", g_cand.detach().numpy()[0])
print("output gate o:", o_gate.detach().numpy()[0], " (how much to reveal)")
print("old cell c   :", c_prev.numpy()[0], "-> new cell c:", c_new.detach().numpy()[0])
h_torch, c_torch = cell(x, (h_prev, c_prev))
print("matches PyTorch's LSTMCell:", torch.allclose(h_new, h_torch) and torch.allclose(c_new,
c_torch))
```

```
forget gate f: [0.592 0.5   0.583]  (1 = keep old memory, 0 = erase)
input gate  i: [0.583 0.54  0.456]  (how much new info to write)
candidate  c~: [-0.219  0.344 -0.641]
output gate o: [0.394 0.577 0.449]  (how much to reveal)
old cell c   : [ 0.8 -0.3  0.5] -> new cell c: [ 0.346  0.036 -0.   ]
matches PyTorch's LSTMCell: True
```

4 · Experiment: who can remember the beginning of a long sequence?

Task: each sequence is T random noise vectors, except that **the first step secretly encodes a class (0–3)**. The model must output that class **after reading the whole sequence**. To succeed it has to carry information from step 1 to the end.

We train a plain RNN and an LSTM on T = 5, 20 and 50 steps. A common LSTM trick: start the **forget-gate bias at 1** so it begins by "keeping" its memory. We also measure how much gradient reaches the first step.

```
def memory_data(n, T, seed):
    g = torch.Generator().manual_seed(seed)
    y = torch.randint(0, 4, (n,), generator=g)
    x = torch.randn(n, T, 8, generator=g)
    x[:, 0, :4] = 0
    x[torch.arange(n), 0, y] = 3.0               # the answer is hidden in the FIRST step only
    return x, y

class SequenceClassifier(nn.Module):
    def __init__(self, kind, hidden=32):
        super().__init__()
        self.rnn = (nn.RNN if kind == "RNN" else nn.LSTM)(8, hidden, batch_first=True)
        self.fc = nn.Linear(hidden, 4)
        if kind == "LSTM":                          # forget-gate bias = 1 (PyTorch order: input,
FORGET, cell, output)
            with torch.no_grad():
                self.rnn.bias_ih_l0[hidden:2 * hidden].fill_(1.0)
                self.rnn.bias_hh_l0[hidden:2 * hidden].fill_(0.0)
    def forward(self, x):
        out, _ = self.rnn(x)
```

```
        return self.fc(out[:, -1])                # decide using the LAST hidden state

print(f"{'steps T':>7} | {'RNN accuracy':>12} | {'LSTM accuracy':>13} | {'gradient reaching step
1 (RNN / LSTM)':>38}")
t0 = time.time()
for T_len in [5, 20, 50]:
    Xs, ys = memory_data(2000, T_len, 0); Xv, yv = memory_data(500, T_len, 1)
    row = {}
    for kind in ["RNN", "LSTM"]:
        torch.manual_seed(0)
        fresh = SequenceClassifier(kind)
        xg = Xv[:100].clone().requires_grad_(True)
        F.cross_entropy(fresh(xg), yv[:100]).backward()
        grad_ratio = (xg.grad[:, 0].norm() / xg.grad[:, -1].norm()).item()     # first step vs
last step
        model = fresh
        opt = torch.optim.Adam(model.parameters(), lr=3e-3)
        for _ in range(40):
            perm = torch.randperm(2000)
            for i in range(0, 2000, 100):
                idx = perm[i:i + 100]
                loss = F.cross_entropy(model(Xs[idx]), ys[idx])
                opt.zero_grad(); loss.backward(); opt.step()
        with torch.no_grad():
            row[kind] = ((model(Xv).argmax(1) == yv).float().mean().item(), grad_ratio)
    print(f"{T_len:>7} | {row['RNN'][0]:>12.1%} | {row['LSTM'][0]:>13.1%} | {row['RNN']
[1]:>17.1e} / {row['LSTM'][1]:.1e}")
print(f"(random guessing = 25%; took {time.time() - t0:.0f} s)")
```

```
steps T | RNN accuracy | LSTM accuracy |  gradient reaching step 1 (RNN / LSTM)
      5 |       100.0% |         99.8% |           1.3e-01 / 3.0e-01
     20 |        50.2% |        100.0% |           5.3e-06 / 1.2e-02
     50 |        24.6% |         99.8% |           3.7e-14 / 3.9e-05
(random guessing = 25%; took 17 s)
```

- **T = 5:** both remember. Short sequences are easy, so a plain RNN is enough.
- **T = 20:** the RNN drops to about 50%. **T = 50:** the RNN is at **25%, pure guessing**. The gradient reaching step 1 has shrunk to about 10^{-14} of the last step's, so it never learns that step 1 matters.
- The **LSTM stays near 100%**. Its gradient at step 1 is about a billion times larger.

	RNN	LSTM
Memory	short-term	long-term (long dependencies)
Problem	vanishing gradients	solves (greatly reduces) vanishing gradients
Best for	simple, short sequences	complex, long sequences
Example	predict the next word in a short sentence	understand context across a long paragraph or video

Variable length (Q17): both process one step at a time with the same weights, so any length works. The LSTM's gated memory keeps working when a clip is long (a 10-second gesture vs a 2-second one), while an RNN only remembers the last few frames.

When is a plain RNN still enough? (Q18) Short sequences where only recent steps matter: next-character prediction in short words, smoothing a few recent sensor readings, predicting the next note from the last few notes. RNNs are also smaller and faster. (**GRU** is a lighter LSTM variant with 2 gates, often just as good.)

5 · The CNN + LSTM pipeline for video (Q12)

1. **CNN** extracts **spatial features** from **each frame**: one feature vector per frame (*what*).
2. **LSTM** processes the **sequence of feature vectors** across frames (*how it changes*).
3. An **output layer** predicts the action or gesture class.

We train it on our moving-square videos and compare it with two models that ignore order:

- **single frame:** a CNN that sees only the middle frame,
- **frame average:** a CNN on every frame, with the features averaged (all frames, order thrown away).

```
def frame_cnn():
    # turns one 32x32 frame into a 64-number feature vector
    return nn.Sequential(nn.Conv2d(1, 16, 3, padding=1), nn.ReLU(), nn.MaxPool2d(2),
                         nn.Conv2d(16, 32, 3, padding=1), nn.ReLU(), nn.MaxPool2d(2),
                         nn.Conv2d(32, 32, 3, padding=1), nn.ReLU(), nn.AdaptiveAvgPool2d(4),
                         nn.Flatten(), nn.Linear(32 * 16, 64), nn.ReLU())

class SingleFrame(nn.Module):
    def __init__(self):
        super().__init__(); self.cnn = frame_cnn(); self.fc = nn.Linear(64, 4)
    def forward(self, v):
        return self.fc(self.cnn(v[:, T // 2]))                          # middle frame only

class FrameAverage(nn.Module):
    def __init__(self):
        super().__init__(); self.cnn = frame_cnn(); self.fc = nn.Linear(64, 4)
    def forward(self, v):
        B = v.shape[0]
        feats = self.cnn(v.reshape(B * T, 1, H, H)).reshape(B, T, 64)
        return self.fc(feats.mean(dim=1))                               # all frames, ORDER LOST


class CNNLSTM(nn.Module):
    def __init__(self):
        super().__init__(); self.cnn = frame_cnn(); self.lstm = nn.LSTM(64, 64,
batch_first=True); self.fc = nn.Linear(64, 4)
    def forward(self, v):
        B = v.shape[0]
        feats = self.cnn(v.reshape(B * T, 1, H, H)).reshape(B, T, 64)   # step 1: CNN on every
frame
        out, _ = self.lstm(feats)                                        # step 2: LSTM over time
        return self.fc(out[:, -1])                                       # step 3: classify

def fit(model, epochs=10):
    opt = torch.optim.Adam(model.parameters(), lr=2e-3)
    for _ in range(epochs):
        model.train(); perm = torch.randperm(len(Xtr))
        for i in range(0, len(Xtr), 64):
            idx = perm[i:i + 64]
            loss = F.cross_entropy(model(Xtr[idx]), ytr[idx])
            opt.zero_grad(); loss.backward(); opt.step()
    model.eval()
    with torch.no_grad():
        return model(Xte).argmax(1)

preds = {}
t0 = time.time()
for M in [SingleFrame, FrameAverage, CNNLSTM]:
    torch.manual_seed(0)
    preds[M.__name__] = fit(M())
print(f"trained 3 models in {time.time() - t0:.0f} s\n")
```

```
fig, ax = plt.subplots(1, 3, figsize=(13, 3.8))
for a, (name, p) in zip(ax, preds.items()):
    cm = np.zeros((4, 4), int)
    for t_, p_ in zip(yte.tolist(), p.tolist()):
        cm[t_, p_] += 1
    a.imshow(cm, cmap="Blues")
    for i in range(4):
        for j in range(4):
            a.text(j, i, cm[i, j], ha="center", va="center", color="white" if cm[i, j] > 50 else
"black")
    a.set_xticks(range(4)); a.set_xticklabels(DIRS); a.set_yticks(range(4));
a.set_yticklabels(DIRS)
    a.set_xlabel("predicted"); a.set_ylabel("true")
    a.set_title(f"{name}: {(p == yte).float().mean():.0%} correct")
plt.tight_layout(); plt.show()
```

```
trained 3 models in 41 s
```



- **CNN + LSTM: about 100%.** It knows *what* (a square, at this position) in each frame **and** *how* that changes over time.
- **Frame average: far below.** Averaging throws away the order, so "right" and "left" (the same frames in reverse) look identical. At best it could tell horizontal from vertical, and in practice it does even worse.
- **Single frame: well below.** One frame can't show motion. It does a little better than guessing only because our 8-frame clips have no exact middle frame, so the chosen frame's position leaks a small hint.

In short: CNNs capture the *what* (spatial features), LSTMs capture the *when/how* (temporal sequence). Together they make video understanding possible.

What each part captures (Key Concepts)

CNN (per frame)	LSTM (across frames)
objects: a hand, a ball, a car	**motion**: the hand moves left → right
shapes & edges: outline of hand or body	**order**: first → next → last
textures & patterns: clothing, background	**dynamics**: speed, rhythm, continuity

Where CNN + LSTM is essential (Q13, Q14)

- **Gesture recognition:** sign language, touch-free controls. A "wave" is a *sequence* of hand positions; any single frame is just "a raised hand". The CNN detects the hand shape per

frame, and the LSTM recognises the movement pattern ("wave", "swipe left"). A static image classifier only sees a pose, so it can't tell "waving" from "raising a hand".

- **Action recognition:** sports analysis, surveillance ("throwing a ball" = person + ball + arm motion over time).
- **Video captioning:** describing what happens in a clip.
- **Autonomous driving:** predicting where a pedestrian is heading from their recent motion.

✅ Check yourself

1. Why can't CNNs alone capture temporal dependencies? *(they process each frame independently; nothing links frames or keeps their order)*
2. What problem do LSTMs solve compared with vanilla RNNs? *(vanishing gradients, giving long-term memory)*
3. Roles of the input, forget and output gates? *(store new info / discard old info / decide what to pass forward)*
4. What does each part of a CNN + LSTM pipeline contribute? *(CNN: spatial features per frame; LSTM: temporal pattern; output layer: the class)*
5. Why do LSTMs suit variable-length video? *(step-by-step processing handles any length; gated memory spans long clips)*
6. When might a plain RNN still be enough? *(short sequences where only recent context matters)*

07 · Vision Transformers (ViT) and Attention

Covers (Week 3 Key Concepts, "Vision Transformers (ViT) & Attention") plus the course's two ViT notebooks (`CV-Week3-vit1/vit2.ipynb` , copies in `course-files/`). This notebook includes and extends all their exercises. **Questions answered here:** ViT 19–20 · Hard 10.

Why something new? CNNs are excellent at **local** patterns (a kernel only sees its small neighbourhood) but struggle with **long-range dependencies**: two related things far apart in an image. **Transformers** were invented for language (2017, "Attention Is All You Need") and use **attention** to connect *any* element with *any other*. The **Vision Transformer (2020)** applies this directly to images.

	CNN	ViT
Looks at	local neighbourhoods first, grows the view layer by layer	**all patches at once**, from layer 1
Built-in assumption	"nearby pixels belong together" (locality)	almost none, learns relationships from data
Data needed	works well on small datasets	needs **large** datasets (or pretraining) to shine

```
%matplotlib inline
import os
import time
import numpy as np
import matplotlib.pyplot as plt
import matplotlib.patches as mpatches
import torch
import torch.nn as nn
import torch.nn.functional as F
from PIL import Image

torch.manual_seed(0)
np.set_printoptions(precision=2, suppress=True)
print("torch", torch.__version__)
```

```
torch 2.14.1+cu130
```

1 · Step 1: split the image into patches ("tokens")

A sentence is a sequence of **words**. ViT turns an image into a sequence of **patches**. With a 128×128 image and 16×16 patches you get 8 × 8 = **64 patches**. Each patch is **flattened** into a vector and treated like a word, called a **token**.

The course notebooks load `cat.jpg` , which isn't in the zip. We use the Week-1 photo and fall back to a drawn image if it's missing.

```
path = "../../week-1/code/sample.jpg"
if os.path.exists(path):
    img = Image.open(path).convert("RGB").resize((128, 128))
else:
    arr = np.ones((128, 128, 3)); arr[32:96, 32:96] = [0.2, 0.6, 0.9]
    img = Image.fromarray((arr * 255).astype(np.uint8))
```


```
img_array = np.array(img)

def split_into_patches(image, patch_size):
    # same function as the course notebook: walk the image in patch_size steps
    patches = []
    for i in range(0, image.shape[0], patch_size):
        for j in range(0, image.shape[1], patch_size):
            patches.append(image[i:i + patch_size, j:j + patch_size])
    return np.array(patches)

patch_size = 16
patches = split_into_patches(img_array, patch_size)
tokens = patches.reshape(patches.shape[0], -1)              # flatten every patch into one long
vector
print("image shape:", img_array.shape)
print(f"{len(patches)} patches of {patch_size}x{patch_size}x3  ->  token matrix {tokens.shape}
(64 tokens, each 768 numbers)")
print("first token (first 12 values):", tokens[0][:12])

fig, ax = plt.subplots(1, 2, figsize=(11, 5))
ax[0].imshow(img_array); ax[0].set_title("image with 16x16 patch grid"); ax[0].axis("off")
for k in range(0, 129, patch_size):
    ax[0].axhline(k - 0.5, color="white", lw=0.6); ax[0].axvline(k - 0.5, color="white", lw=0.6)
strip = np.concatenate([np.pad(p, ((2, 2), (2, 2), (0, 0)), constant_values=255) for p in
patches[:16]], axis=1)
ax[1].imshow(strip); ax[1].set_title("first 16 patches in reading order -> a SEQUENCE");
ax[1].axis("off")
plt.tight_layout(); plt.show()
```

```
image shape: (128, 128, 3)
64 patches of 16x16x3  ->  token matrix (64, 768)  (64 tokens, each 768 numbers)
first token (first 12 values): [165 174 200 164 171 199 163 170 198 161 168 196]
```



Patch size controls the sequence length (course vit2 exercise)

```
fig, ax = plt.subplots(1, 3, figsize=(12, 4))
for a, ps in zip(ax, [8, 16, 32]):
    n = len(split_into_patches(img_array, ps))
    a.imshow(img_array); a.axis("off")
    for k in range(0, 129, ps):
        a.axhline(k - 0.5, color="white", lw=0.5); a.axvline(k - 0.5, color="white", lw=0.5)
    a.set_title(f"patch {ps}x{ps} -> {n} tokens")
    print(f"patch {ps:>2}x{ps:<2} -> {n:>3} tokens -> attention compares {n}x{n} = {n * n:>6,}
pairs")
plt.tight_layout(); plt.show()
```

```
patch  8x8  -> 256 tokens -> attention compares 256x256 = 65,536 pairs
patch 16x16 ->  64 tokens -> attention compares 64x64 =  4,096 pairs
patch 32x32 ->  16 tokens -> attention compares 16x16 =    256 pairs
```



Trade-off: smaller patches keep more detail but create more tokens, and attention compares **every token with every other**, so the cost grows with the **square** of the token count. Working pixel by pixel (16,384 "tokens" for 128×128) would mean 268 million pairs. **Patches make transformers feasible on images.**

2 · Step 2: embeddings, position and the [CLS] token

1. **Patch embedding:** a learned linear layer maps each flattened patch (768 numbers) to a smaller vector (e.g. 64), the "word embedding" of the patch.
2. **Position embedding:** attention itself has **no idea of order**. Shuffle the patches and it gives the same result. So a learned vector per **position** is added, telling the model *where* each patch came from.
3. **[CLS] token:** an extra learned token placed at the start of the sequence. It owns no patch. Through attention it **gathers a summary of the whole image**, and its final value is used for classification ("cat" vs "dog").

3 · Step 3: attention, Query, Key and Value (Q19)

Every token produces three vectors through three learned linear layers:

	Plain meaning	Library analogy
Query (Q)	what am *I* looking for?	your search request
Key (K)	what do *I* contain or offer?	the label on each book
Value (V)	the information I'll hand over if picked	the book's content

Process:

1. Compare each Query with every Key (dot product) to get **similarity scores**.
2. Divide by √d (keeps the numbers in a sensible range) and apply **softmax**, so each token's scores become **weights that sum to 1**.
3. Output = the **weighted sum of the Values**. Each token now carries information **mixed in from the tokens it found relevant**.

Attention(Q, K, V) = softmax(Q·Kᵀ / √d) · V

The course's toy demo (vit2, part 3), explained

The course notebook uses the tokens themselves as Q, K and V (no learned projections), which is the simplest possible attention:

```
torch.manual_seed(0)
tokens = torch.randn(4, 3)                          # 4 patches, each a 3-number embedding
print("tokens (patch embeddings):\n", tokens.numpy())

scores = tokens @ tokens.T                          # every patch compared with every patch (dot
product)
print("\nraw attention scores (4x4):\n", scores.numpy())

weights = torch.softmax(scores, dim=-1)             # each ROW sums to 1
print("\nattention weights (rows sum to 1):\n", weights.numpy(), "\nrow sums:",
weights.sum(1).numpy())

attended = weights @ tokens                         # weighted mix of the tokens
print("\nattended representations (each patch now mixes info from the others):\n",
attended.numpy())
```

```
tokens (patch embeddings):
 [[ 1.54 -0.29 -2.18]
 [ 0.57 -1.08 -1.4 ]
 [ 0.4   0.84 -0.72]
 [-0.4  -0.6   0.18]]

raw attention scores (4x4):
 [[ 7.21  4.24  1.94 -0.84]
 [ 4.24  3.46  0.33  0.16]
 [ 1.94  0.33  1.38 -0.79]
 [-0.84  0.16 -0.79  0.55]]

attention weights (rows sum to 1):
 [[0.95 0.05 0.   0.  ]
 [0.67 0.31 0.01 0.01]
 [0.55 0.11 0.31 0.04]
 [0.11 0.31 0.12 0.46]]
row sums: [1. 1. 1. 1.]

attended representations (each patch now mixes info from the others):
 [[ 1.49 -0.33 -2.13]
 [ 1.21 -0.52 -1.89]
 [ 1.01 -0.04 -1.56]
 [ 0.21 -0.54 -0.68]]
```

Read row *i* of the weights as "how much patch *i* listens to each patch". Notice row 2: patch 2 listens more to patch 0 (0.55) than to itself (0.31). A dot product grows with vector **length** as well as direction, so a long vector like token 0 dominates everyone's attention. **Real attention uses three separate learned projections** (W_Q, W_K, W_V), so a token can *ask for* something different from what it *offers*, and the network **learns** which relationships matter.

The "bank" example: context changes meaning

In language, "**bank**" means different things in "*river bank*" and "*money bank*". Attention lets the "bank" token pull in information from the context word. Below we hand-make tiny 2-D embeddings (dimension 1 = "nature-ness", dimension 2 = "finance-ness") and watch the output for "bank" shift toward its context:

```
vocab = {"river": [1.0, 0.0], "money": [0.0, 1.0], "the": [0.1, 0.1], "bank": [0.5, 0.5]}
W_q = torch.eye(2) * 3; W_k = torch.eye(2) * 3; W_v = torch.eye(2)       # simple "learned"
projections

def attend(sentence):
    X = torch.tensor([vocab[w] for w in sentence])
    Q, K, V = X @ W_q, X @ W_k, X @ W_v
    A = torch.softmax(Q @ K.T / np.sqrt(2), dim=-1)
    return A, A @ V

for sentence in [["the", "river", "bank"], ["the", "money", "bank"]]:
    A, out = attend(sentence)
    b = sentence.index("bank")
    weights = {w: round(float(v), 2) for w, v in zip(sentence, A[b])}
    print(f"{' '.join(sentence):<16} 'bank' attends to {weights}"
          f" -> new 'bank' vector {out[b].numpy()}  (nature, finance)")
```


```
the river bank   'bank' attends to {'the': 0.04, 'river': 0.48, 'bank': 0.48} -> new 'bank' vecto
r [0.73 0.24]  (nature, finance)
the money bank   'bank' attends to {'the': 0.04, 'money': 0.48, 'bank': 0.48} -> new 'bank' vecto
r [0.24 0.73]  (nature, finance)
```

Same word, same starting vector [0.5, 0.5], but after attention "bank" leans toward **nature** in one sentence and **finance** in the other. In a ViT the same thing happens with patches: a patch of stripes can attend to other stripe patches far away and "realise" it's part of a zebra.

4 · Why patches + attention capture global context (Q20)

1. **The image becomes a sequence:** patches act like words, so the transformer can relate any two regions.
2. **Long-range dependencies from layer 1:** a CNN neuron in the first layer sees 3×3 pixels, and it takes many layers before distant regions meet. With attention, the top-left patch can directly attend to the bottom-right patch **in the very first layer**.
3. **Reduced complexity:** patches shorten the sequence enough to make attention affordable.
4. **Local and global together:** each patch embedding keeps **local** detail (edges, texture inside the patch), and attention across patches builds the **global** picture (object shape, scene layout).

```
fig, ax = plt.subplots(1, 2, figsize=(10, 4.8))
ax[0].imshow(img_array); ax[0].set_title("CNN layer 1: each output sees a 3x3 window");
ax[0].axis("off")
ax[0].add_patch(mpatches.Rectangle((60, 60), 3, 3, fill=False, ec="red", lw=2))
ax[0].add_patch(mpatches.Rectangle((48, 48), 27, 27, fill=False, ec="red", lw=1, ls="--"))
ax[0].text(64, 44, "even after 13 layers: ~27x27", color="red", ha="center", fontsize=9)
ax[1].imshow(img_array); ax[1].set_title("ViT layer 1: every patch can attend to every patch");
ax[1].axis("off")
centre = (72, 72)
for (r, c) in [(0, 0), (0, 7), (7, 0), (7, 7), (2, 5), (5, 1)]:
    ax[1].annotate("", xy=(c * 16 + 8, r * 16 + 8), xytext=centre, arrowprops=dict(arrowstyle="-
>", color="cyan", lw=1.5))
ax[1].add_patch(mpatches.Rectangle((64, 64), 16, 16, fill=False, ec="cyan", lw=2))
plt.tight_layout(); plt.show()
```





5 · Build and train a tiny Vision Transformer

Our ViT, sized for a laptop: 16×16 digit images → **4×4 patches = 16 tokens** + [CLS], embedding size 64, **2 transformer blocks** with 4 attention heads. Each block is:

```
x → LayerNorm → multi-head attention —(+ skip)→ LayerNorm → MLP —(+ skip)→
```

Notice the **skip (residual) connections**: they're straight from ResNet (notebook 03). **Multi-head** means several attention "heads" run in parallel, each free to learn a different kind of relationship.

```
from sklearn.datasets import load_digits
from sklearn.model_selection import train_test_split

digits = load_digits()
X = F.interpolate(torch.tensor(digits.images, dtype=torch.float32)[:, None] / 16, size=(16, 16),
mode="bilinear", align_corners=False)
y = torch.tensor(digits.target)
Xtr, Xte, ytr, yte = train_test_split(X, y, test_size=0.3, random_state=0, stratify=y)

class Block(nn.Module):
    def __init__(self, dim, heads):
        super().__init__()
        self.norm1, self.norm2 = nn.LayerNorm(dim), nn.LayerNorm(dim)
        self.attn = nn.MultiheadAttention(dim, heads, dropout=0.1, batch_first=True)
        self.mlp = nn.Sequential(nn.Linear(dim, dim * 2), nn.GELU(), nn.Dropout(0.1),
nn.Linear(dim * 2, dim))
        self.last_attention = None
    def forward(self, x):
        h = self.norm1(x)
        a, w = self.attn(h, h, h, need_weights=True)        # Q, K and V all come from the tokens
        self.last_attention = w.detach()                    # (batch, tokens, tokens), averaged
over heads
        x = x + a                                           # residual connection
        return x + self.mlp(self.norm2(x))                  # residual connection

class TinyViT(nn.Module):
    def __init__(self, patch=4, dim=64, depth=2, heads=4, n_classes=10):
        super().__init__()
        self.patch = patch
        n_patches = (16 // patch) ** 2
        self.embed = nn.Linear(patch * patch, dim)                          # patch embedding
```

```
        self.cls = nn.Parameter(torch.zeros(1, 1, dim))                    # [CLS] token
        self.pos = nn.Parameter(torch.randn(1, n_patches + 1, dim) * 0.02)  # position embeddings
        self.blocks = nn.ModuleList([Block(dim, heads) for _ in range(depth)])
        self.norm = nn.LayerNorm(dim)
        self.head = nn.Linear(dim, n_classes)
    def forward(self, x):
        B = x.shape[0]
        p = x.unfold(2, self.patch, self.patch).unfold(3, self.patch, self.patch)   # cut into
4x4 patches
        p = p.reshape(B, -1, self.patch * self.patch)                               # (B, 16
tokens, 16 values)
        t = torch.cat([self.cls.expand(B, -1, -1), self.embed(p)], dim=1) + self.pos
        for blk in self.blocks:
            t = blk(t)
        return self.head(self.norm(t)[:, 0])                                        # classify
from [CLS]

def small_cnn():
    return nn.Sequential(nn.Conv2d(1, 32, 3, padding=1), nn.ReLU(), nn.MaxPool2d(2),
                         nn.Conv2d(32, 64, 3, padding=1), nn.ReLU(), nn.MaxPool2d(2),
                         nn.Flatten(), nn.Linear(64 * 16, 64), nn.ReLU(), nn.Linear(64, 10))

def fit(model, epochs=40):
    opt = torch.optim.AdamW(model.parameters(), lr=2e-3, weight_decay=0.05)
    for _ in range(epochs):
        model.train(); perm = torch.randperm(len(Xtr))
        for i in range(0, len(Xtr), 64):
            idx = perm[i:i + 64]
            loss = F.cross_entropy(model(Xtr[idx]), ytr[idx])
            opt.zero_grad(); loss.backward(); opt.step()
    model.eval()
    with torch.no_grad():
        return (model(Xte).argmax(1) == yte).float().mean().item()

results = {}
for name, make in [("Tiny ViT", TinyViT), ("Small CNN", small_cnn)]:
    torch.manual_seed(0)
    model = make()
    t = time.time(); acc = fit(model)
    results[name] = model
    print(f"{name:<10} parameters {sum(p.numel() for p in model.parameters()):>7,}   test
accuracy {acc:.1%}   ({time.time() - t:.0f} s)")
vit = results["Tiny ViT"]
```

```
Tiny ViT   parameters  69,962   test accuracy 96.9%   (13 s)
Small CNN  parameters  85,066   test accuracy 98.1%   (5 s)
```


The ViT learns, but the similar-sized CNN wins on this small dataset. That's expected and worth remembering. A CNN has a built-in assumption ("nearby pixels belong together, and patterns can appear anywhere"), which is exactly right for images and saves it from learning that from data. A ViT has to **learn** such relationships, so it needs **much more data**. The original ViT only beat the best CNNs after pretraining on hundreds of millions of images. That's the "**scales well with large datasets**" benefit in the notes.

What does the [CLS] token look at?

The attention weights from [CLS] to the 16 patches, in the last block, show which parts of the digit the model consulted:

```
with torch.no_grad():
    vit(Xte[:6])
cls_attn = vit.blocks[-1].last_attention[:, 0, 1:]          # row 0 = [CLS]; skip its attention
to itself
fig, ax = plt.subplots(2, 6, figsize=(13, 4.4))
```

```
for k in range(6):
    ax[0, k].imshow(Xte[k, 0], cmap="gray"); ax[0, k].set_title(f"digit {int(yte[k])}"); ax[0,
k].axis("off")
    ax[1, k].imshow(cls_attn[k].reshape(4, 4), cmap="magma"); ax[1, k].axis("off")
ax[1, 0].set_title("[CLS] attention", loc="left")
plt.tight_layout(); plt.show()
```



Bright cells are the patches [CLS] drew information from in the last block. For some digits the attention is sharply focused on one or two patches of the stroke. For others it's spread widely, background included, because the earlier block has already mixed information between patches, so a "background" token may by now carry stroke information. Attention maps of real ViTs are similarly suggestive but not a perfect explanation of the model. The key point: the model chooses **where to look** by itself, with no convolution anywhere.

6 · Benefits, applications and the big picture

Benefits: captures **global context** better than CNNs · **scales well** with large datasets · flexible (classification, detection, segmentation) · inspired **hybrid** CNN + Transformer models. **Applications:** image classification (ImageNet benchmarks) · medical imaging (global patterns across a scan) · video understanding (adding attention across time) · multimodal vision + language (image captioning, CLIP-style search). **Impact:** shifted computer vision from **CNN-centric** to **transformer-centric** approaches.

From LeNet to ViT (Hard Q10)

Step	What it contributed to ViT
LeNet	learning features end to end from pixels (no hand-made features)
AlexNet	scale: big data (ImageNet) + GPUs + ReLU/dropout made big models trainable
VGG	depth and simple, repeated building blocks
ResNet	**residual connections** (in every transformer block) and very deep training; normalization
EfficientNet	systematic thinking about **scaling** model and data size
ViT	keeps the deep, residual, scaled-up recipe but swaps local convolution for **global attention** over patches

✅ Check yourself

1. Purpose of Query, Key and Value? *(Query = what a token looks for; Key = what each token offers; Value = information passed on; output = weights from Q·K, applied to V)*
2. Why split an image into patches? *(turns the image into a token sequence, keeps the sequence short enough for attention, and lets distant regions interact directly, giving global context)*
3. What is the [CLS] token for? *(a learned summary token whose final value is used for classification)*
4. Why add position embeddings? *(attention ignores order; positions tell the model where each patch was)*
5. Why might a CNN beat a ViT on a small dataset? *(the CNN's built-in locality assumption; ViTs must learn it from lots of data)*
6. Patch size 16 on a 224×224 image gives how many tokens? *($(224/16)^2 = 196$, plus [CLS] = 197)*

Lab 1 · Train VGG on CIFAR-10 + mini project: an image classifier

Course lab: `CV-Week3-Lecture1.ipynb` (copy in `course-files/labs/`). Exercise: *"Train VGG on CIFAR-10"*. Mini project: *"Image Classifier"*. Plus the course's *"Visualizing VGG Architecture with Graphviz"* cell.

What you will learn

- How to load CIFAR-10 with `torchvision`, what `ToTensor()` and `Normalize()` do, and what a `DataLoader` gives you.
- How the course adapts `models.vgg16` to 10 classes by replacing `classifier[6]`.
- The standard PyTorch training loop (`zero_grad → forward → loss → backward → step`), line by line.
- **Why the course's exact recipe (VGG16 from scratch, Adam, lr = 0.001) gets stuck at 10 % accuracy**, and two fixes that work.
- How to evaluate properly (`model.eval()` + `torch.no_grad()`), with per-class accuracy, a confusion matrix and a grid of predictions.

Run time. 8 minutes on the 4-core CPU this notebook was built on, which was shared with other heavy jobs at the time (measured: see the last code cell). Most of it is the two VGG16 epochs. An idle machine will be faster. On a Google Colab GPU it should take only a few minutes (estimate), and there you can afford the full 50,000-image training set (see the Colab section at the end).

0 · Theory in 60 seconds

Full theory: notes/02_classic_cnns_lenet_alexnet_vgg.md and the notebook 02_classic_cnns_lenet_alexnet_vgg.ipynb, where we build LeNet by hand.

Year	Model	Remember it for
1998	**LeNet-5**	conv → pool → fully connected; read handwritten digits
2012	**AlexNet**	won ImageNet; **ReLU, dropout, GPU training**
2014	**VGG-16/19**	**depth + only 3×3 filters**; 16 weight layers, about 138 million parameters (134 million with a 10-class head)

Why 3×3 filters? Two stacked 3×3 convolutions see a 5×5 area and three see 7×7, with fewer weights than one big filter and an extra ReLU in between. VGG16 = 13 conv layers (in 5 blocks, each ending in a 2×2 max-pool) + 3 fully connected layers.

```
%matplotlib inline
import os, time, copy, urllib.request
from concurrent.futures import ThreadPoolExecutor

import numpy as np
import matplotlib.pyplot as plt
from PIL import Image
```

```python
import torch
import torch.nn as nn
import torch.optim as optim
import torchvision
import torchvision.transforms as transforms
import torchvision.models as models

# While this notebook was built, other jobs shared the same 4-core CPU, so we limit PyTorch to 2 threads.
# On your own computer you can delete this line: PyTorch then uses all your cores.
torch.set_num_threads(2)
NOTEBOOK_START = time.time()
torch.manual_seed(0)
np.random.seed(0)

device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
print("torch", torch.__version__, "| torchvision", torchvision.__version__, "| device:", device)
```

```
torch 2.14.1+cu130 | torchvision 0.29.1+cu130 | device: cpu
```

1 · Setup & data loading (the course's first code cell)

CIFAR-10 = 60,000 tiny colour photos, **32×32 pixels**, 10 classes (plane, car, bird, cat, deer, dog, frog, horse, ship, truck): 50,000 for training and 10,000 for testing, exactly balanced (5,000 + 1,000 per class).

The course's transform, explained:

Line	What it does
`transforms.ToTensor()`	PIL image (H×W×3, values 0–255) → tensor **3×H×W, values 0.0–1.0** (channels first, which PyTorch expects)
`transforms.Normalize((0.5,), (0.5,))`	`(x − 0.5) / 0.5` → values in **−1 … 1**, centred on 0, which helps training. The course gives **one** mean and one std; PyTorch reuses that single value for all 3 channels (we check this below). Writing `(0.5, 0.5, 0.5)` is clearer.
`DataLoader(..., batch_size=64, shuffle=True)`	hands out **mini-batches of 64 images**; reshuffles the training set every epoch so batches differ
`shuffle=False` on the test set	order does not matter for testing, and a fixed order makes results repeatable

Two routes to the data (be honest about which one ran)

1. **Official route (what the course uses):** `torchvision.datasets.CIFAR10(root='./data', download=True)` downloads the 163 MB archive from the University of Toronto. This works on a normal internet connection, e.g. your laptop or Colab.
2. **Fallback route:** the machine this notebook was built on cannot reach that server. So if the download fails, we fetch the **same CIFAR-10 images, saved as individual JPG files**, from a public GitHub mirror (`YoongiKim/CIFAR-10-images` , folders `train/<class>/0000.jpg …` , 5,000 per class for training and 1,000 per class for testing). The JPGs are very slightly compressed, which makes no visible difference.

Subset. Training on the full 50,000 images is fine on a GPU but slow on a CPU. Either way we use the **first 500 training and 100 test images per class (5,000 + 1,000, still perfectly balanced)**. Set `N_TRAIN_PER_CLASS = 5000` and `N_TEST_PER_CLASS = 1000` on a GPU to use everything.

```
N_TRAIN_PER_CLASS = 500     # full dataset: 5000
N_TEST_PER_CLASS = 100      # full dataset: 1000
DIR_NAMES = ['airplane', 'automobile', 'bird', 'cat', 'deer', 'dog', 'frog', 'horse', 'ship',
'truck']  # CIFAR-10 label order
MIRROR = "https://raw.githubusercontent.com/YoongiKim/CIFAR-10-images/master"


def first_n_per_class(targets, n):
    """Indices of the first n images of every class (keeps the subset balanced)."""
    idx, seen = [], {}
    for i, t in enumerate(targets):
        if seen.get(t, 0) < n:
            idx.append(i)
            seen[t] = seen.get(t, 0) + 1
    return idx


class CifarJpgFolder(torch.utils.data.Dataset):
    """Fallback dataset: reads data/cifar10_jpg/<split>/<class>/0000.jpg ... like CIFAR10
would."""
    def __init__(self, root, n_per_class, transform=None):
        self.samples = [(f"{root}/{c}/{i:04d}.jpg", label)
                        for label, c in enumerate(DIR_NAMES) for i in range(n_per_class)]
        self.targets = [label for _, label in self.samples]
        self.transform = transform
    def __len__(self):
        return len(self.samples)
    def __getitem__(self, i):
        path, label = self.samples[i]
        img = Image.open(path).convert("RGB")
        return (self.transform(img) if self.transform else img), label


def download_mirror(split, n_per_class, root="./data/cifar10_jpg"):
    jobs = [(f"{MIRROR}/{split}/{c}/{i:04d}.jpg", f"{root}/{split}/{c}/{i:04d}.jpg")
            for c in DIR_NAMES for i in range(n_per_class)]
    jobs = [(u, p) for u, p in jobs if not os.path.exists(p)]          # skip files we already
have
    def fetch(job):
        url, path = job
        os.makedirs(os.path.dirname(path), exist_ok=True)
        for attempt in range(3):
            try:
                urllib.request.urlretrieve(url, path + ".part")
                os.replace(path + ".part", path)
                return
            except Exception as e:
                err = e
        raise err
    t = time.time()
    with ThreadPoolExecutor(32) as pool:                               # 32 small downloads at a
time
        list(pool.map(fetch, jobs))
    print(f"  mirror: {split}: downloaded {len(jobs)} new files in {time.time() - t:.0f}s")
    return f"{root}/{split}"


def load_cifar10(train_transform, test_transform):
    try:
        trainset = torchvision.datasets.CIFAR10(root='./data', train=True, download=True,
transform=train_transform)
        testset = torchvision.datasets.CIFAR10(root='./data', train=False, download=True,
```

```
transform=test_transform)
        trainset = torch.utils.data.Subset(trainset, first_n_per_class(trainset.targets,
N_TRAIN_PER_CLASS))
        testset = torch.utils.data.Subset(testset, first_n_per_class(testset.targets,
N_TEST_PER_CLASS))
        print("DATA ROUTE: official torchvision CIFAR10 download")
    except Exception as e:
        print("Official CIFAR-10 download failed:", type(e).__name__, str(e)[:80])
        print("DATA ROUTE: fallback = CIFAR-10 JPG mirror on GitHub")
        trainset = CifarJpgFolder(download_mirror("train", N_TRAIN_PER_CLASS), N_TRAIN_PER_CLASS,
train_transform)
        testset = CifarJpgFolder(download_mirror("test", N_TEST_PER_CLASS), N_TEST_PER_CLASS,
test_transform)
    return trainset, testset


# ---- the course's cell, unchanged apart from the loader function ----
transform = transforms.Compose([
    transforms.ToTensor(),
    transforms.Normalize((0.5,), (0.5,))
])

trainset, testset = load_cifar10(transform, transform)
trainloader = torch.utils.data.DataLoader(trainset, batch_size=64, shuffle=True)
testloader = torch.utils.data.DataLoader(testset, batch_size=64, shuffle=False)

classes = ('plane', 'car', 'bird', 'cat', 'deer', 'dog', 'frog', 'horse', 'ship', 'truck')
print(f"train: {len(trainset)} images | test: {len(testset)} images | batches per epoch:
{len(trainloader)}")
```

```
Official CIFAR-10 download failed: URLError <urlopen error Tunnel connection failed: 403 Forbidde
n>
DATA ROUTE: fallback = CIFAR-10 JPG mirror on GitHub
  mirror: train: downloaded 4000 new files in 25s
  mirror: test: downloaded 500 new files in 3s
train: 5000 images | test: 1000 images | batches per epoch: 79
```

Let's check what one batch looks like and confirm that the single-value `Normalize` really treats all three channels the same.


```
images, labels = next(iter(trainloader))
print("one batch of images:", tuple(images.shape), " -> (batch, channels, height, width)")
print("one batch of labels:", tuple(labels.shape), labels[:10].tolist())
print(f"pixel range after Normalize: {images.min():.2f} … {images.max():.2f}")

img = Image.open(trainset.samples[0][0]) if hasattr(trainset, "samples") else
Image.fromarray(trainset.dataset.data[trainset.indices[0]])
a = transforms.Normalize((0.5,), (0.5,))(transforms.ToTensor()(img))
b = transforms.Normalize((0.5, 0.5, 0.5), (0.5, 0.5, 0.5))(transforms.ToTensor()(img))
print("Normalize((0.5,),(0.5,)) == Normalize((0.5,0.5,0.5),(0.5,0.5,0.5)) ?", torch.equal(a, b))

counts = np.bincount(np.array(trainset.targets if hasattr(trainset, "targets") else
[trainset.dataset.targets[i] for i in trainset.indices]), minlength=10)
print("training images per class:", dict(zip(classes, counts.tolist())))

fig, axes = plt.subplots(2, 10, figsize=(15, 3.4))
for ax, im, lab in zip(axes.ravel(), images[:20], labels[:20]):
    ax.imshow((im / 2 + 0.5).permute(1, 2, 0).clamp(0, 1))      # un-normalise: x*0.5 + 0.5
    ax.set_title(classes[lab], fontsize=9); ax.axis("off")
plt.suptitle("20 training images (32×32 pixels each: that's why they look blurry)")
plt.tight_layout(); plt.show()
```

```
one batch of images: (64, 3, 32, 32)  -> (batch, channels, height, width)
one batch of labels: (64,) [2, 6, 1, 2, 3, 5, 2, 3, 8, 5]
pixel range after Normalize: -1.00 … 1.00
Normalize((0.5,),(0.5,)) == Normalize((0.5,0.5,0.5),(0.5,0.5,0.5)) ? True
training images per class: {'plane': 500, 'car': 500, 'bird': 500, 'cat': 500, 'deer': 500, 'do
g': 500, 'frog': 500, 'horse': 500, 'ship': 500, 'truck': 500}
```



2 · Exercise: Train VGG on CIFAR-10

2.1 Building the model: the course's three key lines

```
vgg16 = models.vgg16(pretrained=False)         # course (old API)
vgg16.classifier[6] = nn.Linear(4096, 10)      # adjust output layer
```

- `models.vgg16(...)` builds the VGG16 architecture. `pretrained=False` means **random weights** (training from scratch). In current torchvision `pretrained=` is **deprecated**: the modern spelling is `weights=None` (random) or `weights=models.VGG16_Weights.IMAGENET1K_V1` (ImageNet-trained). It is deprecated rather than removed, so the old spelling still works but prints a warning.
- `vgg16.classifier` is the fully connected part: `[Linear(25088→4096), ReLU, Dropout, Linear(4096→4096), ReLU, Dropout, Linear(4096→1000)]`. Index **6** is the last layer with **1000 outputs** (ImageNet's 1000 classes). We swap it for a new `nn.Linear(4096, 10)`, one output score per CIFAR-10 class.

```
vgg16 = models.vgg16(weights=None)                  # = pretrained=False in the course
print("before:", vgg16.classifier[6])
vgg16.classifier[6] = nn.Linear(4096, 10)           # adjust output layer: 1000 ImageNet classes -
> 10 CIFAR classes
print("after: ", vgg16.classifier[6])
print()
print(vgg16.classifier)

def count_params(m):
    return sum(p.numel() for p in m.parameters())
n_feat, n_cls = count_params(vgg16.features), count_params(vgg16.classifier)
print(f"\nparameters: features (13 conv layers) = {n_feat/1e6:.1f} M | classifier (3 FC layers) =
{n_cls/1e6:.1f} M | total = {(n_feat+n_cls)/1e6:.1f} M")
```

```
before: Linear(in_features=4096, out_features=1000, bias=True)
after:  Linear(in_features=4096, out_features=10, bias=True)

Sequential(
  (0): Linear(in_features=25088, out_features=4096, bias=True)
  (1): ReLU(inplace=True)
  (2): Dropout(p=0.5, inplace=False)
  (3): Linear(in_features=4096, out_features=4096, bias=True)
  (4): ReLU(inplace=True)
  (5): Dropout(p=0.5, inplace=False)
  (6): Linear(in_features=4096, out_features=10, bias=True)
)

parameters: features (13 conv layers) = 14.7 M | classifier (3 FC layers) = 119.6 M | total = 13
4.3 M
```

2.2 VGG16 was designed for 224×224 images, not 32×32

VGG16 has **5 max-pool layers**, and each one halves the image size. A 224×224 photo becomes **7×7** at the end of `features`. A 32×32 CIFAR image becomes **1×1**. VGG then has an `AdaptiveAvgPool2d((7, 7))` that forces a 7×7 output whatever the input size. With a 1×1 input it simply **copies the same number 49 times**, so the first Linear layer gets 25,088 inputs containing only 512 different values. It still *runs* (no shape error), but it is very wasteful. Let's prove it:

```
x = torch.randn(1, 3, 32, 32)
with torch.no_grad():
    f = vgg16.features(x)
    p = vgg16.avgpool(f)
print("32x32 input  -> after features:", tuple(f.shape), "-> after avgpool:", tuple(p.shape), "->
flattened:", p.flatten(1).shape[1])
print("all 49 values in each 7x7 map identical?", torch.allclose(p, p[:, :, :1,
:1].expand_as(p)))
with torch.no_grad():
    print("224x224 input -> after features:", tuple(vgg16.features(torch.randn(1, 3, 224,
224)).shape))
print(f"\n{n_cls/(n_feat+n_cls):.0%} of VGG16's parameters sit in the classifier, mostly in
Linear(25088 -> 4096) = {25088*4096/1e6:.0f} M weights")
```

```
32x32 input  -> after features: (1, 512, 1, 1) -> after avgpool: (1, 512, 7, 7) -> flattened: 250
88
all 49 values in each 7x7 map identical? True
224x224 input -> after features: (1, 512, 7, 7)

89% of VGG16's parameters sit in the classifier, mostly in Linear(25088 -> 4096) = 103 M weights
```

2.3 The training loop, line by line (the course's code)

```
criterion = nn.CrossEntropyLoss()
optimizer = optim.Adam(vgg16.parameters(), lr=0.001)
```

- **`nn.CrossEntropyLoss()`**: the standard loss for classification. It takes the 10 raw scores ("logits"), turns them into probabilities with softmax and returns **–log(probability of the correct class)**. Perfect guess → 0. A random guess among 10 classes → –log(1/10) = **2.303**. Remember that number!
- **`optim.Adam(..., lr=0.001)`**: Adam is gradient descent with a separate, self-adjusting step size for every weight. `lr` (learning rate) = how big the steps are. 0.001 is Adam's usual default.

Inside the loop, for every mini-batch:

Line	Meaning
`inputs, labels = inputs.to(device), labels.to(device)`	move the batch to the GPU if there is one (model and data must be on the same device)
`optimizer.zero_grad()`	wipe the gradients from the previous batch (PyTorch **adds** gradients up by default)
`outputs = vgg16(inputs)`	**forward pass**: 64 images → 64×10 scores
`loss = criterion(outputs, labels)`	how wrong were we on this batch?
`loss.backward()`	**backpropagation**: compute the gradient of the loss for every weight
`optimizer.step()`	update every weight a little in the direction that lowers the loss

Line	Meaning
`running_loss += loss.item()`	`.item()` turns the 1-element tensor into a plain Python number for printing

One **epoch** = one pass over all training batches. The course trains for `range(1, 3)` = **2 epochs**. A VGG16 epoch takes several minutes on our CPU, so we run **1 epoch** and also record the loss of every batch so we can plot it.

```
torch.manual_seed(0)
vgg16 = models.vgg16(weights=None)
vgg16.classifier[6] = nn.Linear(4096, 10)  # adjust output layer
vgg16.to(device)

criterion = nn.CrossEntropyLoss()
optimizer = optim.Adam(vgg16.parameters(), lr=0.001)

batch_losses_course = []
t0 = time.time()
for epoch in range(1, 2):  # course: range(1, 3) = 2 epochs; we run 1 to save CPU time
    vgg16.train()                              # training mode (dropout on); the course relies on
the default
    running_loss = 0.0
    for inputs, labels in trainloader:
        inputs, labels = inputs.to(device), labels.to(device)
        optimizer.zero_grad()
        outputs = vgg16(inputs)
        loss = criterion(outputs, labels)
        loss.backward()
        optimizer.step()
        running_loss += loss.item()
        batch_losses_course.append(loss.item())
    print(f"Epoch {epoch}, Loss: {running_loss/len(trainloader):.4f}")
time_vgg_epoch = time.time() - t0
print(f"time for 1 epoch of VGG16 on {len(trainset)} images: {time_vgg_epoch:.0f}s")
print(f"largest batch loss: {max(batch_losses_course):.1f} (batch
{int(np.argmax(batch_losses_course)) + 1})")
print("loss of the last 10 batches:", np.round(batch_losses_course[-10:], 3))
```

```
Epoch 1, Loss: 3.2624
time for 1 epoch of VGG16 on 5000 images: 134s
largest batch loss: 78.0 (batch 2)
loss of the last 10 batches: [2.301 2.306 2.311 2.303 2.301 2.303 2.303 2.305 2.308 2.306]
```

2.4 Evaluate it: the course's "Mini Project" test loop

`torch.max(outputs, 1)` returns `(largest score, its index)` along dimension 1 (the 10 classes). The index **is** the predicted class. We add **`model.eval()`**, which the course forgets (more on that in section 4).

```
def evaluate(model, loader):
    """Course's test loop + model.eval(). Returns accuracy in % and all predictions/labels."""
    model.eval()                                # dropout off, batch-norm uses its stored
statistics
    correct, total, all_pred, all_true = 0, 0, [], []
    with torch.no_grad():                       # no gradients needed for testing: faster, less
memory
        for inputs, labels in loader:
            inputs, labels = inputs.to(device), labels.to(device)
            outputs = model(inputs)
            _, predicted = torch.max(outputs, 1)
            total += labels.size(0)
            correct += (predicted == labels).sum().item()
```

```
            all_pred.append(predicted.cpu()); all_true.append(labels.cpu())
    return 100 * correct / total, torch.cat(all_pred).numpy(), torch.cat(all_true).numpy()

acc_course, pred_course, _ = evaluate(vgg16, testloader)
print(f"Accuracy on CIFAR-10 test set: {acc_course:.2f}%")
print("how often each class was predicted:", dict(zip(classes, np.bincount(pred_course,
minlength=10).tolist())))

# Look inside: what does the network output for 64 different test images?
vgg16.eval()
with torch.no_grad():
    x, _ = next(iter(testloader))
    feats = vgg16.features(x.to(device))             # output of the last conv block (after ReLU
+ pool)
    out = vgg16(x.to(device))
print(f"\nfraction of the 512 conv features that are exactly 0 (dead ReLUs): {(feats ==
0).float().mean():.1%}")
print("scores for image 0:", np.round(out[0].cpu().numpy(), 3))
print("scores for image 1:", np.round(out[1].cpu().numpy(), 3))
print(f"largest difference between the scores of any two images: {(out -
out[0]).abs().max():.6f}")
```

```
Accuracy on CIFAR-10 test set: 10.00%
how often each class was predicted: {'plane': 0, 'car': 0, 'bird': 0, 'cat': 0, 'deer': 0, 'dog':
0, 'frog': 0, 'horse': 1000, 'ship': 0, 'truck': 0}
fraction of the 512 conv features that are exactly 0 (dead ReLUs): 100.0%
scores for image 0: [ 0.019  0.009  0.029  0.013  0.002  0.003  0.024  0.032 -0.034  0.01 ]
scores for image 1: [ 0.019  0.009  0.029  0.013  0.002  0.003  0.024  0.032 -0.034  0.01 ]
largest difference between the scores of any two images: 0.000000
```

What happened? Read the outputs above:

- In the first few batches the loss **jumps far above 2.3** (the "largest batch loss" line). Those early Adam steps were far too big.
- After that the loss sits at **≈ 2.303 = −ln(1/10)** for the rest of the epoch: the network is guessing.
- **100 % of the 512 features** coming out of the conv layers are exactly 0, so every image produces **identical scores**, and the model predicts **the same class for all 1,000 test images**. Test accuracy = **10 % = chance**.

Why? VGG16 (the original, without batch normalisation) is 16 layers deep with 134 M random weights. Adam with lr = 0.001 took steps that were too large for it. In the first batches the weights were pushed so far that every ReLU in the last conv block outputs zero (**"dead ReLUs"**). A ReLU that outputs 0 also passes back a gradient of 0, so the conv layers can no longer learn and the network is stuck with a constant guess. It never recovers. The original VGG authors needed a careful setup (small learning rate with SGD, and initialising the deeper nets from a shallower trained one). This is not a bug in your code: it is a **real training failure**, and a classic viva question.

2.5 Fix 1: same VGG16, smaller learning rate (lr = 0.0001)

```
def train_epochs(model, optimizer, loader, epochs, scheduler=None, log=True):
    """The course's training loop wrapped in a function. Records batch losses and time per
epoch."""
    criterion = nn.CrossEntropyLoss()
    batch_losses, epoch_times = [], []
    for epoch in range(1, epochs + 1):
        model.train()
        t0, running_loss = time.time(), 0.0
        for inputs, labels in loader:
            inputs, labels = inputs.to(device), labels.to(device)
            optimizer.zero_grad()
```


```
            loss = criterion(model(inputs), labels)
            loss.backward()
            optimizer.step()
            running_loss += loss.item()
            batch_losses.append(loss.item())
        if scheduler is not None:
            scheduler.step()
        epoch_times.append(time.time() - t0)
        if log:
            print(f"Epoch {epoch}, Loss: {running_loss/len(loader):.4f}
({epoch_times[-1]:.0f}s)")
    return batch_losses, epoch_times

torch.manual_seed(0)
vgg16_lr4 = models.vgg16(weights=None)
vgg16_lr4.classifier[6] = nn.Linear(4096, 10)
vgg16_lr4.to(device)
batch_losses_lr4, _ = train_epochs(vgg16_lr4, optim.Adam(vgg16_lr4.parameters(), lr=0.0001),
trainloader, epochs=1)
acc_lr4, pred_lr4, _ = evaluate(vgg16_lr4, testloader)
print(f"VGG16, Adam lr=0.0001, 1 epoch -> test accuracy {acc_lr4:.2f}%")
print("how often each class was predicted:", dict(zip(classes, np.bincount(pred_lr4,
minlength=10).tolist())))
```

```
Epoch 1, Loss: 2.1989  (138s)
VGG16, Adam lr=0.0001, 1 epoch -> test accuracy 17.50%
how often each class was predicted: {'plane': 0, 'car': 80, 'bird': 0, 'cat': 435, 'deer': 0, 'do
g': 3, 'frog': 0, 'horse': 35, 'ship': 447, 'truck': 0}
```

```
def smooth(v, k=5):
    return np.convolve(v, np.ones(k) / k, mode="valid")

plt.figure(figsize=(8, 3.8))
plt.plot(smooth(batch_losses_course), label="course: VGG16, Adam lr=0.001")
plt.plot(smooth(batch_losses_lr4), label="fix 1: VGG16, Adam lr=0.0001")
plt.axhline(np.log(10), color="gray", ls="--", label="chance level = ln(10) = 2.303")
plt.xlabel("batch (64 images each)"); plt.ylabel("training loss (smoothed)")
plt.title("1 epoch of VGG16 from scratch on 5,000 CIFAR images")
plt.ylim(1.6, 3.0); plt.legend(); plt.grid(alpha=0.3); plt.show()
```



With the smaller learning rate the loss **drops below 2.303**: VGG16 is learning. But it's slow: one epoch takes minutes on a CPU, and 134 M parameters is a lot for 5,000 tiny images. VGG16 was

built for 224×224 ImageNet photos.

2.6 Fix 2: a small VGG-style network for 32×32 images

We keep **VGG's design rules** (stacks of 3×3 convolutions with padding 1, then 2×2 max-pool, doubling the channels after every pool, then fully connected layers with dropout) but size it for 32×32 input:

```
32×32×3 → [conv3x3 32, conv3x3 32, pool] → 16×16×32 → [conv 64, conv 64, pool] → 8×8×64
        → [conv 128, conv 128, pool] → 4×4×128 = 2048 values → FC 256 → FC 10
```

Two modern additions:

- `BatchNorm2d` after every convolution: it re-centres and re-scales each layer's outputs, which keeps training stable even with lr = 0.001 (this is exactly what `models.vgg16_bn` adds to VGG16).
- **Data augmentation** for training only: `RandomCrop(32, padding=4)` (shift the image by up to 4 pixels) and `RandomHorizontalFlip()` (mirror it). The network sees slightly different versions every epoch, so it memorises less (**less overfitting**). The test images are **not** augmented.

We also use a **cosine learning-rate schedule**: the learning rate starts at 0.001 and is smoothly lowered towards 0 by the last epoch, which helps the final epochs settle.

```
def conv_bn_relu(c_in, c_out):
    return [nn.Conv2d(c_in, c_out, kernel_size=3, padding=1), nn.BatchNorm2d(c_out),
nn.ReLU(inplace=True)]

class SmallVGG(nn.Module):
    def __init__(self, num_classes=10):
        super().__init__()
        self.features = nn.Sequential(
            *conv_bn_relu(3, 32),   *conv_bn_relu(32, 32),   nn.MaxPool2d(2),   # 32x32 -> 16x16
            *conv_bn_relu(32, 64),  *conv_bn_relu(64, 64),   nn.MaxPool2d(2),   # 16x16 -> 8x8
            *conv_bn_relu(64, 128), *conv_bn_relu(128, 128), nn.MaxPool2d(2),   # 8x8   -> 4x4
        )
        self.classifier = nn.Sequential(
            nn.Flatten(),                                    # 128 x 4 x 4 = 2048 numbers
            nn.Dropout(0.5), nn.Linear(2048, 256), nn.ReLU(inplace=True),
            nn.Dropout(0.5), nn.Linear(256, num_classes),
        )
    def forward(self, x):
        return self.classifier(self.features(x))

train_transform = transforms.Compose([
    transforms.RandomCrop(32, padding=4),        # augmentation: random shift
    transforms.RandomHorizontalFlip(),           # augmentation: random mirror
    transforms.ToTensor(),
    transforms.Normalize((0.5, 0.5, 0.5), (0.5, 0.5, 0.5)),
])
trainset_aug, _ = load_cifar10(train_transform, transform)           # same images, augmented on
the fly
trainloader_aug = torch.utils.data.DataLoader(trainset_aug, batch_size=64, shuffle=True)

small = SmallVGG().to(device)
print(f"SmallVGG parameters: {count_params(small)/1e6:.2f} M  (VGG16:
{count_params(vgg16)/1e6:.1f} M, {count_params(vgg16)/count_params(small):.0f}x more)")
```


```
Official CIFAR-10 download failed: URLError <urlopen error Tunnel connection failed: 403 Forbidde
n>
DATA ROUTE: fallback = CIFAR-10 JPG mirror on GitHub
  mirror: train: downloaded 0 new files in 0s
  mirror: test: downloaded 0 new files in 0s
SmallVGG parameters: 0.82 M  (VGG16: 134.3 M, 165x more)
```

```python
EPOCHS_SMALL = 15
torch.manual_seed(0)
small = SmallVGG().to(device)
optimizer = optim.Adam(small.parameters(), lr=0.001)
scheduler = optim.lr_scheduler.CosineAnnealingLR(optimizer, T_max=EPOCHS_SMALL)

history = {"train_loss": [], "test_acc": []}
t_start = time.time()
for epoch in range(1, EPOCHS_SMALL + 1):
    losses, times = train_epochs(small, optimizer, trainloader_aug, epochs=1, log=False)
    scheduler.step()
    acc, _, _ = evaluate(small, testloader)
    history["train_loss"].append(np.mean(losses)); history["test_acc"].append(acc)
    print(f"Epoch {epoch:2d}, Loss: {np.mean(losses):.4f}, test accuracy: {acc:5.1f}%
({times[0]:.0f}s)")
time_small_total = time.time() - t_start
print(f"total: {time_small_total:.0f}s = {time_small_total/EPOCHS_SMALL:.1f}s per epoch")
```

```
Epoch  1, Loss: 2.0017, test accuracy:  38.6%  (10s)
Epoch  2, Loss: 1.7653, test accuracy:  40.9%  (10s)
Epoch  3, Loss: 1.6293, test accuracy:  35.5%  (10s)
Epoch  4, Loss: 1.5748, test accuracy:  40.5%  (11s)
Epoch  5, Loss: 1.5127, test accuracy:  48.9%  (10s)
Epoch  6, Loss: 1.4501, test accuracy:  46.4%  (10s)
Epoch  7, Loss: 1.3720, test accuracy:  50.7%  (10s)
Epoch  8, Loss: 1.3249, test accuracy:  52.1%  (11s)
Epoch  9, Loss: 1.2558, test accuracy:  56.5%  (10s)
Epoch 10, Loss: 1.2122, test accuracy:  56.7%  (10s)
Epoch 11, Loss: 1.1683, test accuracy:  58.3%  (10s)
Epoch 12, Loss: 1.1256, test accuracy:  59.0%  (10s)
Epoch 13, Loss: 1.0767, test accuracy:  60.4%  (10s)
Epoch 14, Loss: 1.0512, test accuracy:  61.7%  (11s)
Epoch 15, Loss: 1.0425, test accuracy:  62.2%  (11s)
total: 167s = 11.2s per epoch
```

```python
fig, ax = plt.subplots(1, 2, figsize=(12, 3.8))
ep = range(1, EPOCHS_SMALL + 1)
ax[0].plot(ep, history["train_loss"], "o-"); ax[0].axhline(np.log(10), color="gray", ls="--",
label="chance (2.303)")
ax[0].set_title("SmallVGG: training loss"); ax[0].set_xlabel("epoch"); ax[0].legend();
ax[0].grid(alpha=0.3)
ax[1].plot(ep, history["test_acc"], "o-", color="C2", label="SmallVGG")
ax[1].axhline(acc_course, color="C3", ls="--", label=f"VGG16 course recipe, 1 epoch
({acc_course:.1f}%)")
ax[1].axhline(acc_lr4, color="C1", ls="--", label=f"VGG16 lr=0.0001, 1 epoch ({acc_lr4:.1f}%)")
ax[1].set_title("test accuracy"); ax[1].set_xlabel("epoch"); ax[1].set_ylabel("%");
ax[1].legend(fontsize=8); ax[1].grid(alpha=0.3)
plt.tight_layout(); plt.show()
```



3 · Mini project: the image classifier, evaluated properly


A single accuracy number hides a lot. A good evaluation also asks: **which classes are easy, which are hard, and what gets confused with what?**

```
acc_small, pred, true = evaluate(small, testloader)
print(f"SmallVGG accuracy on the test set: {acc_small:.2f}%  ({(pred == true).sum()} /
{len(true)})\n")
print("per-class accuracy:")
for i, c in enumerate(classes):
    m = true == i
    print(f"  {c:6s} {100 * (pred[m] == i).mean():5.1f}%  " + "#" * int(round(50 * (pred[m] ==
i).mean())))

cm = np.zeros((10, 10), dtype=int)
for t, p in zip(true, pred):
    cm[t, p] += 1
plt.figure(figsize=(6.5, 5.5))
plt.imshow(cm, cmap="Blues")
for i in range(10):
    for j in range(10):
        plt.text(j, i, cm[i, j], ha="center", va="center", fontsize=8, color="white" if cm[i, j]
> cm.max() / 2 else "black")
plt.xticks(range(10), classes, rotation=45); plt.yticks(range(10), classes)
plt.xlabel("predicted class"); plt.ylabel("true class"); plt.title("Confusion matrix (100 test
images per class)")
plt.colorbar(fraction=0.046); plt.tight_layout(); plt.show()
off = cm.copy(); np.fill_diagonal(off, 0)
i, j = np.unravel_index(off.argmax(), off.shape)
print(f"most common mistake: true '{classes[i]}' predicted as '{classes[j]}' ({off[i, j]}
times)")
```

```
SmallVGG accuracy on the test set: 62.20%  (622 / 1000)

per-class accuracy:
  plane   59.0%  ##############################
  car     83.0%  ##########################################
  bird    45.0%  #######################
  cat     34.0%  #################
  deer    39.0%  ####################
  dog     53.0%  ###########################
  frog    78.0%  ########################################
  horse   73.0%  #####################################
  ship    79.0%  ########################################
  truck   79.0%  ########################################
```




```
most common mistake: true 'dog' predicted as 'cat' (25 times)
```

Predicting on a batch of test images (the course's last cell, fixed)

The course runs `outputs = vgg16(images.to(device))` **outside** `torch.no_grad()` and without `eval()`. That wastes memory building a gradient graph nobody uses, and leaves dropout switched on. We do it properly and show 16 images with **true** and **predicted** labels (green = right, red = wrong).

```
def imshow(img):
    img = img / 2 + 0.5     # unnormalize: correct here, because we normalised with mean 0.5, std
0.5
    npimg = img.numpy()
    plt.imshow(np.transpose(npimg, (1, 2, 0)))
    plt.axis("off")

dataiter = iter(torch.utils.data.DataLoader(testset, batch_size=16, shuffle=True,
generator=torch.Generator().manual_seed(1)))
images, labels = next(dataiter)
small.eval()
with torch.no_grad():
    probs = torch.softmax(small(images.to(device)), dim=1).cpu()
conf, predicted = probs.max(1)

plt.figure(figsize=(12, 4.6))
for k in range(16):
    plt.subplot(2, 8, k + 1)
    imshow(images[k])
    ok = predicted[k] == labels[k]
```

```
    plt.title(f"true: {classes[labels[k]]}\npred: {classes[predicted[k]]} ({conf[k]:.0%})",
fontsize=9, color="green" if ok else "red")
plt.suptitle("SmallVGG predictions on 16 random test images"); plt.tight_layout(); plt.show()
print('Predicted:', ' '.join(f'{classes[predicted[j]]}' for j in range(4)))
print('Truth:    ', ' '.join(f'{classes[labels[j]]}' for j in range(4)))
```




```
Predicted: car deer bird car
Truth:     car frog bird car
```

Save the model, load it back, and classify a single new image

A real classifier must work on images it has never seen. `torch.save(model.state_dict(), path)` stores only the learned numbers (not the code). To reload you build the same class and call `load_state_dict`. Below we classify an image from the CIFAR test set that is **not** part of our 1,000-image test subset (image number 999 of its class), and show the top-3 classes with probabilities.


```
os.makedirs("data", exist_ok=True)
torch.save(small.state_dict(), "data/small_vgg_cifar10.pt")
model = SmallVGG()
model.load_state_dict(torch.load("data/small_vgg_cifar10.pt", map_location="cpu"))
model.eval()

def classify(pil_image, model, k=3):
    x = transform(pil_image.convert("RGB").resize((32, 32))).unsqueeze(0)   # same preprocessing
as training, + batch dimension
    with torch.no_grad():
        p = torch.softmax(model(x), dim=1)[0]
    top = p.topk(k)
    return [(classes[i], float(v)) for v, i in zip(top.values, top.indices)]

# a held-out image (not in our test subset); on the official route we take test image 9999
instead
try:
    url = f"{MIRROR}/test/horse/0999.jpg"; path = "data/cifar10_jpg/extra_horse_0999.jpg"
    if not os.path.exists(path):
        urllib.request.urlretrieve(url, path)
    new_img, truth = Image.open(path), "horse"
except Exception:
    raw = torchvision.datasets.CIFAR10(root='./data', train=False, download=False)
    new_img, truth = raw[9999][0], classes[raw[9999][1]]

result = classify(new_img, model)
plt.figure(figsize=(7, 2.6))
plt.subplot(1, 2, 1); plt.imshow(new_img); plt.title(f"new image (true: {truth})");
plt.axis("off")
plt.subplot(1, 2, 2); plt.barh([c for c, _ in result][::-1], [p for _, p in result][::-1],
color="C2")
```

```
plt.xlim(0, 1); plt.title("top-3 probabilities"); plt.tight_layout(); plt.show()
print(result)
```




```
[('horse', 0.9125499129295349), ('deer', 0.08525834232568741), ('bird', 0.0011968696489930153)]
```

4 · Two course bugs you can demonstrate: forgetting `eval()` and `no_grad()`

`model.eval()` switches two kinds of layer into "test behaviour":

- **Dropout** (VGG16 and SmallVGG both have it): in training mode it randomly zeroes 50 % of the neurons, so predictions become random-ish. In eval mode it does nothing.
- **BatchNorm**: in training mode it normalises with the statistics of the *current batch* and also **overwrites its stored running averages with test data**. In eval mode it uses the averages learned during training.

The course's test loop never calls `vgg16.eval()`, and since the training loop left the model in training mode, it tests with dropout on. Let's measure the damage on a copy of our trained SmallVGG.

One thing to know before reading the numbers: our test subset is stored **class by class** (100 planes, then 100 cars…), and `shuffle=False` keeps that order, so each test batch of 64 holds only one or two classes. In training mode BatchNorm normalises every batch by its own average, which here largely removes "what all these images have in common", i.e. the class. That makes the damage extra large. With **shuffled** test batches (last line) the damage is smaller but still real.

```
def accuracy_in_mode(model, train_mode):
    model.train(train_mode)
    correct = 0
    with torch.no_grad():
        for x, y in testloader:
            correct += (model(x.to(device)).argmax(1).cpu() == y).sum().item()
    return 100 * correct / len(testset)

m = copy.deepcopy(small)
print(f"with model.eval()          : {accuracy_in_mode(m, False):.2f}%")
print(f"without eval(), run 1      : {accuracy_in_mode(m, True):.2f}%")
print(f"without eval(), run 2      : {accuracy_in_mode(m, True):.2f}%   <- changes every run
(dropout is random)")

# our test subset is stored class by class, so each test batch of 64 holds only 1-2 classes.
Shuffle it:
```

```
m2 = copy.deepcopy(small); m2.train()
shuffled = torch.utils.data.DataLoader(testset, batch_size=64, shuffle=True,
generator=torch.Generator().manual_seed(0))
with torch.no_grad():
    correct = sum((m2(x.to(device)).argmax(1).cpu() == y).sum().item() for x, y in shuffled)
print(f"without eval(), shuffled test batches: {100 * correct / len(testset):.2f}%")
bn = small.features[1]
print(f"\nBatchNorm running mean changed by testing in train mode? {not
torch.allclose(bn.running_mean, m.features[1].running_mean)}")

x = images[:4].to(device)
print("\nprediction WITHOUT torch.no_grad(): output.requires_grad =", small(x).requires_grad, "(a
gradient graph was built for nothing)")
with torch.no_grad():
    print("prediction WITH    torch.no_grad(): output.requires_grad =", small(x).requires_grad)
```

```
with model.eval()          : 62.20%
without eval(), run 1      : 27.20%
without eval(), run 2      : 28.20%   <- changes every run (dropout is random)
without eval(), shuffled test batches: 56.30%

BatchNorm running mean changed by testing in train mode? True

prediction WITHOUT torch.no_grad(): output.requires_grad = True (a gradient graph was built for n
othing)
prediction WITH    torch.no_grad(): output.requires_grad = False
```

5 · Visualising the VGG architecture (the course's Graphviz cell)

The course uses **torchviz** (`make_dot`) to draw the computation graph and `dot.render(...)` to save it as a PNG. Two things to know:

1. `pip install torchviz` installs only the Python part. **Rendering needs the Graphviz program** (`dot`) on your system: `sudo apt install graphviz` (Linux), `brew install graphviz` (Mac), or the installer from graphviz.org (Windows). On Colab it is already installed. Without it you get `ExecutableNotFound: failed to execute 'dot'` .
2. The torchviz graph of VGG16 is a very tall picture of every operation. For a viva, a **layer table** is usually more useful. `torchinfo.summary` prints each layer's output shape and parameter count.

The cell below tries the course's way first and falls back to `torchinfo` if Graphviz is missing (`pip install torchviz torchinfo`).

```
vgg16_vis = models.vgg16(weights=None)       # course: models.vgg16(pretrained=False)
x = torch.randn(1, 3, 224, 224)
try:
    from torchviz import make_dot
    from IPython.display import Image as IPImage, display
    y = vgg16_vis(x)
    dot = make_dot(y, params=dict(vgg16_vis.named_parameters()))
    dot.format = 'png'
    dot.render('data/vgg16_architecture')
    print("Graphviz is installed: diagram saved to data/vgg16_architecture.png")
    display(IPImage(filename='data/vgg16_architecture.png', width=300))
except Exception as e:
    print("torchviz could not render the diagram:", type(e).__name__, "-", str(e).split(chr(10))
[0][:120])
    print("-> install the Graphviz system program to use the course's cell. Layer table
instead:\n")
```

```
from torchinfo import summary
print(summary(vgg16_vis, input_size=(1, 3, 224, 224), col_names=("output_size", "num_params"),
depth=2, verbose=0))
```

```
torchviz could not render the diagram: ExecutableNotFound - failed to execute PosixPath('dot'), m
ake sure the Graphviz executables are on your systems' PATH
-> install the Graphviz system program to use the course's cell. Layer table instead:

==========================================================================================
Layer (type:depth-idx)                   Output Shape              Param #
==========================================================================================
VGG                                      [1, 1000]                 --
├─Sequential: 1-1                        [1, 512, 7, 7]            --
│    └─Conv2d: 2-1                       [1, 64, 224, 224]         1,792
│    └─ReLU: 2-2                         [1, 64, 224, 224]         --
│    └─Conv2d: 2-3                       [1, 64, 224, 224]         36,928
│    └─ReLU: 2-4                         [1, 64, 224, 224]         --
│    └─MaxPool2d: 2-5                    [1, 64, 112, 112]         --
│    └─Conv2d: 2-6                       [1, 128, 112, 112]        73,856
│    └─ReLU: 2-7                         [1, 128, 112, 112]        --
│    └─Conv2d: 2-8                       [1, 128, 112, 112]        147,584
│    └─ReLU: 2-9                         [1, 128, 112, 112]        --
│    └─MaxPool2d: 2-10                   [1, 128, 56, 56]          --
│    └─Conv2d: 2-11                      [1, 256, 56, 56]          295,168
│    └─ReLU: 2-12                        [1, 256, 56, 56]          --
│    └─Conv2d: 2-13                      [1, 256, 56, 56]          590,080
│    └─ReLU: 2-14                        [1, 256, 56, 56]          --
│    └─Conv2d: 2-15                      [1, 256, 56, 56]          590,080
│    └─ReLU: 2-16                        [1, 256, 56, 56]          --
│    └─MaxPool2d: 2-17                   [1, 256, 28, 28]          --
│    └─Conv2d: 2-18                      [1, 512, 28, 28]          1,180,160
│    └─ReLU: 2-19                        [1, 512, 28, 28]          --
│    └─Conv2d: 2-20                      [1, 512, 28, 28]          2,359,808
│    └─ReLU: 2-21                        [1, 512, 28, 28]          --
│    └─Conv2d: 2-22                      [1, 512, 28, 28]          2,359,808
│    └─ReLU: 2-23                        [1, 512, 28, 28]          --
│    └─MaxPool2d: 2-24                   [1, 512, 14, 14]          --
│    └─Conv2d: 2-25                      [1, 512, 14, 14]          2,359,808
│    └─ReLU: 2-26                        [1, 512, 14, 14]          --
│    └─Conv2d: 2-27                      [1, 512, 14, 14]          2,359,808
│    └─ReLU: 2-28                        [1, 512, 14, 14]          --
│    └─Conv2d: 2-29                      [1, 512, 14, 14]          2,359,808
│    └─ReLU: 2-30                        [1, 512, 14, 14]          --
│    └─MaxPool2d: 2-31                   [1, 512, 7, 7]            --
├─AdaptiveAvgPool2d: 1-2                 [1, 512, 7, 7]            --
├─Sequential: 1-3                        [1, 1000]                 --
│    └─Linear: 2-32                      [1, 4096]                 102,764,544
│    └─ReLU: 2-33                        [1, 4096]                 --
│    └─Dropout: 2-34                     [1, 4096]                 --
│    └─Linear: 2-35                      [1, 4096]                 16,781,312
│    └─ReLU: 2-36                        [1, 4096]                 --
│    └─Dropout: 2-37                     [1, 4096]                 --
│    └─Linear: 2-38                      [1, 1000]                 4,097,000
==========================================================================================
Total params: 138,357,544
Trainable params: 138,357,544
Non-trainable params: 0
Total mult-adds (Units.GIGABYTES): 15.48
==========================================================================================
Input size (MB): 0.60
Forward/backward pass size (MB): 108.45
Params size (MB): 553.43
Estimated Total Size (MB): 662.49
==========================================================================================
```

```
print(summary(SmallVGG(), input_size=(1, 3, 32, 32), col_names=("output_size", "num_params"),
depth=2, verbose=0))
```

```
==========================================================================================
Layer (type:depth-idx)                   Output Shape              Param #
==========================================================================================
SmallVGG                                 [1, 10]                   --
├─Sequential: 1-1                        [1, 128, 4, 4]            --
│    └─Conv2d: 2-1                       [1, 32, 32, 32]           896
│    └─BatchNorm2d: 2-2                  [1, 32, 32, 32]           64
│    └─ReLU: 2-3                         [1, 32, 32, 32]           --
│    └─Conv2d: 2-4                       [1, 32, 32, 32]           9,248
│    └─BatchNorm2d: 2-5                  [1, 32, 32, 32]           64
│    └─ReLU: 2-6                         [1, 32, 32, 32]           --
│    └─MaxPool2d: 2-7                    [1, 32, 16, 16]           --
│    └─Conv2d: 2-8                       [1, 64, 16, 16]           18,496
│    └─BatchNorm2d: 2-9                  [1, 64, 16, 16]           128
│    └─ReLU: 2-10                        [1, 64, 16, 16]           --
│    └─Conv2d: 2-11                      [1, 64, 16, 16]           36,928
│    └─BatchNorm2d: 2-12                 [1, 64, 16, 16]           128
│    └─ReLU: 2-13                        [1, 64, 16, 16]           --
│    └─MaxPool2d: 2-14                   [1, 64, 8, 8]             --
│    └─Conv2d: 2-15                      [1, 128, 8, 8]            73,856
│    └─BatchNorm2d: 2-16                 [1, 128, 8, 8]            256
│    └─ReLU: 2-17                        [1, 128, 8, 8]            --
│    └─Conv2d: 2-18                      [1, 128, 8, 8]            147,584
│    └─BatchNorm2d: 2-19                 [1, 128, 8, 8]            256
│    └─ReLU: 2-20                        [1, 128, 8, 8]            --
│    └─MaxPool2d: 2-21                   [1, 128, 4, 4]            --
├─Sequential: 1-2                        [1, 10]                   --
│    └─Flatten: 2-22                     [1, 2048]                 --
│    └─Dropout: 2-23                     [1, 2048]                 --
│    └─Linear: 2-24                      [1, 256]                  524,544
│    └─ReLU: 2-25                        [1, 256]                  --
│    └─Dropout: 2-26                     [1, 256]                  --
│    └─Linear: 2-27                      [1, 10]                   2,570
==========================================================================================
Total params: 815,018
Trainable params: 815,018
Non-trainable params: 0
Total mult-adds (Units.MEGABYTES): 39.28
==========================================================================================
Input size (MB): 0.01
Forward/backward pass size (MB): 1.84
Params size (MB): 3.26
Estimated Total Size (MB): 5.11
==========================================================================================
```

```
print(f"Total run time of this notebook: {(time.time() - NOTEBOOK_START) / 60:.1f} minutes")
```

```
Total run time of this notebook: 8.2 minutes
```

🔧 What we changed from the course notebook, and why

Course code	Our version	Why
`models.vgg16(pretrained=False)`	`models.vgg16(weights=None)`	`pretrained=` is deprecated in torchvision ≥ 0.13 (still works, prints a warning)

Course code	Our version	Why
`CIFAR10(download=True)` only	official download first, **GitHub JPG mirror as fallback**, same 10 classes	the build machine cannot reach the Toronto server. The executed output above shows which route ran.
full 50,000 / 10,000 images	**500 / 100 per class** (`N_TRAIN_PER_CLASS` , `N_TEST_PER_CLASS`)	CPU time; change two numbers to use everything on a GPU
`Normalize((0.5,), (0.5,))`	kept (shown to equal `(0.5,0.5,0.5)`); new code uses the 3-value form	one value is silently reused for all 3 channels; the explicit form is clearer
VGG16 + Adam lr=0.001, 2 epochs	ran it for 1 epoch, **showed it stays at chance (10 %)**, then fix 1 (lr=0.0001) and fix 2 (SmallVGG with BatchNorm, augmentation, 15 epochs)	the course recipe does not learn; VGG16 is also 165× bigger than needed for 32×32 images
test loop without `model.eval()`	`evaluate()` calls `model.eval()`	dropout/BatchNorm must be in test mode (measured in section 4)
batch prediction without `torch.no_grad()`	wrapped in `torch.no_grad()`	no gradient graph needed for predictions
prints only 4 predicted labels	per-class accuracy, confusion matrix, 16-image grid with true/pred, single-image top-3	a single accuracy number hides which classes fail
torchviz render (needs Graphviz)	tried first, `torchinfo.summary` fallback; files go to `data/`	Graphviz is a separate system program and is often missing

Results, honestly

Measured in the run above. CIFAR-10 subset: **5,000 training and 1,000 test images** (balanced), CPU only:

Model	Epochs	Test accuracy	Parameters	Time per epoch (shared CPU)
Course recipe: VGG16 from scratch, Adam lr = 0.001	1	**10.00 %** (chance)	134.3 M	about 134 s
Fix 1: same VGG16, Adam lr = 0.0001	1	**17.50 %**	134.3 M	about 138 s
Fix 2: SmallVGG (3×3 convs + BatchNorm + augmentation), Adam lr = 0.001, cosine schedule	15	**62.20 %**	0.82 M	about 11 s
chance (guessing)		10 %		

What this shows:

- **The course's VGG16 recipe does not learn at all.** After a burst of huge losses in the first batches, every ReLU at the end of the conv layers was dead, every image got the same scores, and all 1,000 test images were predicted as one class. This is a real, common failure of deep plain networks with a too-large learning rate, not a coding bug.
- **A 10× smaller learning rate gets VGG16 learning** (17.50 % after one epoch), but it is slow: each epoch took minutes on a CPU, and its predictions after one epoch are still very lopsided (it predicts only a few classes; see the counts above).
- **A small network designed for 32×32 images wins easily**: 62.20 % with **165× fewer parameters**, and each epoch was several times faster. Its curve was still rising at the end, so more epochs or more data would push it higher.
- **Hardest classes** (per-class accuracy): cat, deer and bird; the most common mistake was **dog → cat**. Easiest: car, ship, truck and frog.
- **Forgetting `model.eval()`** cost a lot: 62.20 % with `eval()` vs 27.20 % / 28.20 % without it (two runs, different each time), and 56.30 % with shuffled test batches. The size of the drop depends on how the test batches are composed, which is exactly why you must call `eval()`.
- **Data route:** the official CIFAR-10 download was blocked on the build machine, so the GitHub JPG mirror was used. On your machine you will probably get the official route and a different (but equally balanced) set of 500 + 100 images per class, so your numbers will differ by a few points.
- **Not measured here:** the full 50,000-image training set, more epochs, and a pretrained VGG16. Those are GPU experiments; see *Try this yourself* and the Colab section.

Common errors and how to fix them

Error / symptom	Cause	Fix
`RuntimeError: Expected all tensors to be on the same device ... cuda:0 and cpu`	model on GPU, data on CPU (or the other way round)	`.to(device)` on **both** the model and every batch (`inputs.to(device), labels.to(device)`)
`CUDA out of memory`	batch too big for the GPU (VGG16 at 224×224 is huge)	smaller `batch_size` (64 → 32 → 16); `torch.no_grad()` when testing; `torch.cuda.empty_cache()`
loss stuck at **2.303** and accuracy ≈ 10 %	network collapsed to a constant guess (as in section 2.3)	lower the learning rate, use a BatchNorm model (`vgg16_bn` , SmallVGG), check the data and labels
`RuntimeError: mat1 and mat2 shapes cannot be multiplied (64x2048 and 4096x10)`	a `Linear` layer's input size does not match the previous layer's output	print the shape before the layer (`x.shape`) or use `torchinfo.summary` ; for VGG16 the new last layer must be `nn.Linear(4096, 10)`
accuracy changes every time you test / lower than expected	forgot `model.eval()` (dropout still on)	call `model.eval()` before testing and `model.train()` before training

Error / symptom	Cause	Fix
images look washed-out or too dark when plotted	displayed normalised values	undo the normalisation: `img * std + mean` (here `img / 2 + 0.5`)
`URLError` / `HTTP Error 403` when downloading CIFAR-10	no internet or blocked server	the notebook falls back to the GitHub mirror automatically
`ExecutableNotFound: failed to execute 'dot'`	Graphviz program not installed	`apt install graphviz` / `brew install graphviz`, or use `torchinfo.summary`
`UserWarning: The parameter 'pretrained' is deprecated`	old torchvision API	use `weights=None` or `weights=models.VGG16_Weights.DEFAULT`

Try this yourself

1. **Course recipe, 2 epochs.** Change `range(1, 2)` back to `range(1, 3)` in section 2.3. Does the loss ever leave 2.303?
2. **VGG16 with batch-norm.** Replace `models.vgg16` by `models.vgg16_bn(weights=None)` and keep lr = 0.001. Does BatchNorm alone fix the collapse?
3. **Pretrained VGG16.** `models.vgg16(weights=models.VGG16_Weights.IMAGENET1K_V1)`, resize CIFAR images to 224 (`transforms.Resize(224)`), freeze `features` and train only the classifier. This is transfer learning (Lab 2). Use a GPU.
4. **No augmentation.** Train SmallVGG with the plain `transform`. Compare training loss and test accuracy: is the gap (overfitting) bigger?
5. **More data.** Set `N_TRAIN_PER_CLASS = 2000`. How much does test accuracy improve?
6. **Remove BatchNorm** from `conv_bn_relu`. Does SmallVGG still train with lr = 0.001?
7. **Your own photo.** `classify(Image.open("my_cat.jpg"), model)`. Remember that it was trained on 32×32 thumbnails, so centred, uncluttered objects work best.

Run it on Google Colab with a GPU

1. Upload this notebook to colab.research.google.com (File → Upload notebook).
2. **Runtime → Change runtime type → T4 GPU**, then Save.
3. Run `!pip install torchinfo torchviz` in a new first cell (everything else is pre-installed).
4. Delete the `torch.set_num_threads(2)` line. `device` will print `cuda`.
5. For the real experiment set `N_TRAIN_PER_CLASS = 5000`, `N_TEST_PER_CLASS = 1000` and the course's `range(1, 3)`. The official CIFAR-10 download will work there, so the output will say `DATA ROUTE: official`.
6. Expect the numbers to differ from ours: more data gives higher accuracy for every model.

Viva questions (with short model answers)

1. **What is CIFAR-10?** 60,000 colour images of 32×32 pixels in 10 balanced classes: 50,000 train and 10,000 test.

2. **What do `ToTensor()` and `Normalize((0.5,),(0.5,))` do?** `ToTensor` converts the image to a C×H×W float tensor in [0, 1]. `Normalize` computes (x − 0.5)/0.5 → [−1, 1]. The single value is applied to all 3 channels.
3. **Why replace `vgg16.classifier[6]`?** It is the last layer, with 1000 outputs for ImageNet. CIFAR-10 has 10 classes, so we need `nn.Linear(4096, 10)`.
4. **What does `pretrained=False` / `weights=None` mean?** Random initial weights, so the network is trained from scratch. `weights=VGG16_Weights.DEFAULT` loads ImageNet-trained weights.
5. **What is CrossEntropyLoss and what is its value for a random guess on 10 classes?** Softmax + negative log-likelihood of the true class. A uniform guess gives −ln(1/10) ≈ 2.303.
6. **Explain `zero_grad`, `backward`, `step`.** Clear the old gradients (they accumulate), compute new gradients by backpropagation, update the weights with the optimiser.
7. **Why did the course's VGG16 stay at 10 %?** Deep plain network (no BatchNorm) with random weights and a learning rate too big for it. Activations die, so it outputs a constant guess and the gradients vanish. Fix: lower lr, BatchNorm (`vgg16_bn`), a smaller net, or pretrained weights.
8. **What does VGG16 do with a 32×32 input?** Five 2× pools give a 1×1×512 map. `AdaptiveAvgPool2d(7,7)` copies it to 7×7, so the 25,088-input FC layer sees 512 distinct numbers. It works, but it is wasteful.
9. **Why 3×3 filters in VGG?** Stacked 3×3 convs give a large receptive field (two → 5×5, three → 7×7) with fewer parameters and more non-linearities than one large filter.
10. **What is an epoch, a batch, batch size?** Batch = the images processed together before one weight update (64 here). Epoch = one full pass over the training set (`len(trainloader)` batches).
11. **Why `model.eval()` and `torch.no_grad()` when testing?** `eval()` turns off dropout and makes BatchNorm use its stored statistics (we measured the accuracy dropping and changing without it). `no_grad()` skips building the gradient graph: faster and less memory.
12. **What does `torch.max(outputs, 1)` return?** The maximum score and its index along the class dimension. The index is the predicted class.
13. **What does BatchNorm do and why did it help?** It normalises each channel's activations over the batch and then rescales them with learned parameters. This keeps signals at a healthy scale, so deep nets train stably with larger learning rates.
14. **What is data augmentation?** Random, label-preserving changes (shifts, flips) applied to training images on the fly. The model sees more variety, so it overfits less. It is never applied to test images.
15. **Which classes are hardest and why?** Look at the per-class accuracy and confusion matrix above. In our run cat, deer and bird were hardest; the most common mistake was dog ↔ cat, and planes were confused with ships (both often on a plain blue background). Animals look alike at 32×32 pixels; cars, trucks and ships have more distinctive shapes and colours.

Lab 2 · Fine-tune a pretrained ResNet18 + mini project: transfer learning for flower classification

Course lab: `CV-Week3-Lecture2.ipynb` (copy in `course-files/labs/`). Exercise: *"Fine-tune ResNet on custom dataset"* (freeze everything, replace `fc`). Mini project: *"Transfer learning for flower classification"*.

What you will learn

- How to organise your own images so `datasets.ImageFolder` can read them (`custom_data/train/<class>/…`, `custom_data/test/<class>/…`).
- Why pretrained models need **ImageNet normalisation** and 224×224 inputs.
- **Transfer learning:** load an ImageNet-trained ResNet18, **freeze** it (`requires_grad = False`), **replace the last layer** `fc`, and train only that layer.
- Proof that it works: the same ResNet18 **trained from scratch** on the same 500 flower photos does far worse.
- Proper evaluation: `model.eval()`, per-class accuracy, confusion matrix, correctly coloured prediction grid (the course's `imshow` shows wrong colours; we fix it).

Run time. 23 minutes on the 4-core CPU this notebook was built on, which was shared with other heavy jobs at the time (measured: see the last code cell). Most of it is the from-scratch comparison. An idle machine will be faster. On a Colab GPU it should take only a few minutes (estimate).

0 · Theory in 60 seconds

Full theory: notes/03_modern_cnns_resnet_efficientnet.md and the notebook 03_modern_cnns_resnet_efficientnet.ipynb.

- **ResNet (2015):** residual blocks compute `out = F(x) + x`. The skip connection gives gradients a direct path back, so networks of 18, 50 or 152 layers train well. **ResNet18** = a 7×7 conv stem, 4 stages of 2 residual blocks each (64 → 128 → 256 → 512 channels), global average pool, then `fc` **= Linear(512 → 1000)**.
- **EfficientNet (2019):** scales depth, width and image resolution *together* (compound scaling) for the best accuracy per FLOP.
- **Transfer learning:** a network trained on ImageNet (1.28 million photos, 1000 classes) has already learned edges → textures → parts → objects. Those features are useful for *other* image tasks. We keep them and only learn a new final layer for our classes. This needs **little data and little compute**.

```
%matplotlib inline
import os, time, copy, random, shutil, tarfile, urllib.request

import numpy as np
import matplotlib.pyplot as plt
```

```
from PIL import Image

import torch
import torch.nn as nn
import torch.optim as optim
import torchvision
import torchvision.transforms as transforms
from torchvision import datasets
import torchvision.models as models

# While this notebook was built, other jobs shared the same 4-core CPU, so we limit PyTorch to 2 threads.
# On your own computer you can delete this line: PyTorch then uses all your cores.
torch.set_num_threads(2)
NOTEBOOK_START = time.time()
torch.manual_seed(0)
random.seed(0)

device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
print("torch", torch.__version__, "| torchvision", torchvision.__version__, "| device:", device)
```

```
torch 2.14.1+cu130 | torchvision 0.29.1+cu130 | device: cpu
```

1 · The custom dataset: building `custom_data/` for `ImageFolder`

The course writes `data_dir = './custom_data'` with the comment *"replace with your dataset folder"*, but doesn't provide one. **`datasets.ImageFolder` needs exactly this layout**: one sub-folder per class, and the folder name *is* the label:

```
custom_data/
├── train/
│   ├── daisy/       img001.jpg, img002.jpg, ...
│   ├── dandelion/   ...
│   └── ...
└── test/
    ├── daisy/       ...
    └── ...
```

For the mini project we use the **TensorFlow "flower_photos" dataset**: 3,670 photos of 5 flower types (daisy, dandelion, roses, sunflowers, tulips), from Flickr, under a Creative Commons licence (attributions in its `LICENSE.txt`). It is a 218 MB download from Google's storage server, reachable both here and on a normal connection.

Small on purpose. Transfer learning shines when you have *few* labelled images, so we use **100 training + 50 test photos per class** (500 + 250), picked at random with a fixed seed. Increase `N_TRAIN_PER_CLASS` to use more. Everything goes into `data/` (git-ignored), so `data_dir = './data/custom_data'`.

```
N_TRAIN_PER_CLASS = 100
N_TEST_PER_CLASS = 50
URL = "https://storage.googleapis.com/download.tensorflow.org/example_images/flower_photos.tgz"

os.makedirs("data", exist_ok=True)
if not os.path.isdir("data/flower_photos"):
    t = time.time()
    urllib.request.urlretrieve(URL, "data/flower_photos.tgz")
    with tarfile.open("data/flower_photos.tgz") as tar:
        if hasattr(tarfile, "data_filter"):
            tar.extractall("data", filter="data")     # safe extraction (Python 3.12+)
```

```
        else:
            tar.extractall("data")
    os.remove("data/flower_photos.tgz")
    print(f"downloaded and extracted in {time.time() - t:.0f}s")

flower_classes = sorted(d for d in os.listdir("data/flower_photos") if
os.path.isdir(f"data/flower_photos/{d}"))
print("all photos:", {c: len(os.listdir(f"data/flower_photos/{c}")) for c in flower_classes})

# Build data/custom_data/{train,test}/<class>/ with a random (seeded) subset
data_dir = './data/custom_data'
shutil.rmtree(data_dir, ignore_errors=True)
rng = random.Random(0)
for c in flower_classes:
    files = sorted(os.listdir(f"data/flower_photos/{c}"))
    rng.shuffle(files)
    for split, chosen in [("train", files[:N_TRAIN_PER_CLASS]),
                          ("test", files[N_TRAIN_PER_CLASS:N_TRAIN_PER_CLASS +
N_TEST_PER_CLASS])]:
        os.makedirs(f"{data_dir}/{split}/{c}", exist_ok=True)
        for f in chosen:
            shutil.copy(f"data/flower_photos/{c}/{f}", f"{data_dir}/{split}/{c}/{f}")
for split in ["train", "test"]:
    print(f"{data_dir}/{split}:", {c: len(os.listdir(f'{data_dir}/{split}/{c}')) for c in
flower_classes})
```

```
downloaded and extracted in 6s
all photos: {'daisy': 633, 'dandelion': 898, 'roses': 641, 'sunflowers': 699, 'tulips': 799}
./data/custom_data/train: {'daisy': 100, 'dandelion': 100, 'roses': 100, 'sunflowers': 100, 'tuli
ps': 100}
./data/custom_data/test: {'daisy': 50, 'dandelion': 50, 'roses': 50, 'sunflowers': 50, 'tulips':
50}
```

The course's loader cell, explained

Line	Why
`transforms.Resize((224,224))`	ResNet18 was trained on 224×224 crops. Our photos come in many sizes (e.g. 320×240, 500×333) and a batch needs equal sizes. `(224,224)` squashes to a square, ignoring the aspect ratio, which is simple and fine here.
`transforms.Normalize([0.485, 0.456, 0.406], [0.229, 0.224, 0.225])`	the **mean and std of the ImageNet training images**, per channel (R, G, B). A pretrained network expects inputs normalised **exactly as during its training**, otherwise its features are off.
`datasets.ImageFolder(root=..., transform=...)`	scans the folders. Class names = sorted folder names, labels = 0, 1, 2… in that order. Each item = (transformed image, label).
`batch_size=32`	32 images per weight update (smaller than Lab 1's 64 because 224×224 images use 49× more memory than 32×32)

```
transform = transforms.Compose([
    transforms.Resize((224,224)),
    transforms.ToTensor(),
    transforms.Normalize([0.485, 0.456, 0.406], [0.229, 0.224, 0.225])
])

trainset = datasets.ImageFolder(root=data_dir+'/train', transform=transform)
trainloader = torch.utils.data.DataLoader(trainset, batch_size=32, shuffle=True)

testset = datasets.ImageFolder(root=data_dir+'/test', transform=transform)
```

```
testloader = torch.utils.data.DataLoader(testset, batch_size=32, shuffle=False)

class_names = trainset.classes
print("Classes:", class_names)
print("class_to_idx:", trainset.class_to_idx)
print(f"train: {len(trainset)} images in {len(trainloader)} batches | test: {len(testset)}
images")
print("first sample:", trainset.samples[0])
```

```
Classes: ['daisy', 'dandelion', 'roses', 'sunflowers', 'tulips']
class_to_idx: {'daisy': 0, 'dandelion': 1, 'roses': 2, 'sunflowers': 3, 'tulips': 4}
train: 500 images in 16 batches | test: 250 images
first sample: ('./data/custom_data/train/daisy/102841525_bd6628ae3c.jpg', 0)
```

Looking at the images: the course's `imshow` shows the wrong colours


The course's `imshow` does `img / 2 + 0.5`. That undoes `Normalize((0.5,),(0.5,))` from Lab 1, **but this lab normalised with the ImageNet mean/std** (std ≈ 0.23, so the normalised values run from about −2.1 to +2.6). To undo *that* you must compute `img * std + mean` per channel. With the course's formula the values are stretched too far and many fall outside 0…1, so matplotlib clips them: too much contrast, blown-out highlights, black shadows and shifted colours. Left: course version. Right: fixed (the true photo).

```
MEAN = torch.tensor([0.485, 0.456, 0.406]).view(3, 1, 1)
STD = torch.tensor([0.229, 0.224, 0.225]).view(3, 1, 1)

def imshow_course(img):            # the course's version (wrong for ImageNet normalisation)
    img = img / 2 + 0.5
    npimg = img.numpy()
    plt.imshow(np.clip(np.transpose(npimg, (1, 2, 0)), 0, 1))   # clip only so matplotlib doesn't
warn

def imshow(img):                   # fixed: undo exactly the Normalize we applied
    img = img * STD + MEAN
    plt.imshow(np.clip(img.permute(1, 2, 0).numpy(), 0, 1))

images, labels = next(iter(torch.utils.data.DataLoader(trainset, batch_size=4, shuffle=True,
generator=torch.Generator().manual_seed(3))))
grid = torchvision.utils.make_grid(images[:4])
plt.figure(figsize=(14, 4))
plt.subplot(1, 2, 1); imshow_course(grid); plt.axis("off"); plt.title("course imshow: img/2 + 0.5
(too much contrast, clipped colours)")
plt.subplot(1, 2, 2); imshow(grid); plt.axis("off"); plt.title("fixed: img*std + mean  (" + ",
".join(class_names[l] for l in labels) + ")")
plt.tight_layout(); plt.show()
```



2 · Exercise: fine-tune ResNet18 on the custom dataset

2.1 Loading pretrained weights: official route and fallback

The course writes `models.resnet18(pretrained=True)`. In torchvision ≥ 0.13 that is **deprecated**. The modern way is

```
resnet18 = models.resnet18(weights=models.ResNet18_Weights.IMAGENET1K_V1)   # or .DEFAULT
```

The `weights` enum also records the preprocessing and the 1000 class names (`ResNet18_Weights.IMAGENET1K_V1.meta["categories"]`), so it is self-documenting.

The weights file comes from `download.pytorch.org`. That works on a normal connection, but **the machine this notebook was built on cannot reach it**. Fallback: the **same ResNet18 architecture with ImageNet weights published by the `timm` library on GitHub** (`resnet18.a1_in1k` from the "ResNet strikes back" paper, 2021). These weights use torchvision's exact layer names, so `load_state_dict` loads them into `models.resnet18()` with every key matching. The only difference is the training recipe used to produce them (torchvision lists 69.8 % ImageNet top-1 accuracy for its official weights; the timm weights are of similar quality). For our purposes both are "a ResNet18 that has already learned from ImageNet". The cell prints which route ran.

```
FALLBACK_URL = "https://github.com/rwightman/pytorch-image-models/releases/download/v0.1-rsb-
weights/resnet18_a1_0-d63eafa0.pth"

def load_pretrained_resnet18():
    try:
        model = models.resnet18(weights=models.ResNet18_Weights.IMAGENET1K_V1)
        print("WEIGHTS ROUTE: official torchvision ResNet18_Weights.IMAGENET1K_V1")
    except Exception as e:
        print("Official weights download failed:", type(e).__name__, str(e)[:80])
        model = models.resnet18(weights=None)                              # same architecture,
random weights...
        state = torch.hub.load_state_dict_from_url(FALLBACK_URL, model_dir="data/weights",
map_location="cpu", progress=False)
        print("load_state_dict:", model.load_state_dict(state))            # ...then fill in
ImageNet weights
        print("WEIGHTS ROUTE: fallback = timm resnet18.a1_in1k ImageNet weights from GitHub")
    return model


resnet18 = load_pretrained_resnet18()
print("original last layer:", resnet18.fc)
```

```
Downloading: "https://download.pytorch.org/models/resnet18-f37072fd.pth" to /root/.cache/torch/hu
b/checkpoints/resnet18-f37072fd.pth
Official weights download failed: URLError <urlopen error Tunnel connection failed: 403 Forbidden
>
Downloading: "https://github.com/rwightman/pytorch-image-models/releases/download/v0.1-rsb-weight
s/resnet18_a1_0-d63eafa0.pth" to data/weights/resnet18_a1_0-d63eafa0.pth
load_state_dict: <All keys matched successfully>
WEIGHTS ROUTE: fallback = timm resnet18.a1_in1k ImageNet weights from GitHub
original last layer: Linear(in_features=512, out_features=1000, bias=True)
```

Sanity check: are these really ImageNet weights? ImageNet's 1000 classes include **"daisy"**, but none of our other four flowers. So before we change anything, the untouched pretrained network should recognise the daisy, and for the other flowers pick the nearest thing it knows.

```
imagenet_classes = models.ResNet18_Weights.IMAGENET1K_V1.meta["categories"]     # the names ship
with torchvision, no download
resnet18.eval()
plt.figure(figsize=(15, 3.6))
for k, c in enumerate(class_names):
    img_t, _ = testset[testset.targets.index(k)]                  # first test photo of each
class
    with torch.no_grad():
        p = torch.softmax(resnet18(img_t.unsqueeze(0).to(device)), 1)[0].cpu()
    top = p.topk(2)
    plt.subplot(1, 5, k + 1); imshow(img_t); plt.axis("off")
    plt.title(f"[{c}]\n" + "\n".join(f"{imagenet_classes[i]} {v:.0%}" for v, i in zip(top.values,
```

```
top.indices)), fontsize=9)
plt.suptitle("Pretrained ResNet18, untouched: its top-2 ImageNet guesses", y=1.04);
plt.tight_layout(); plt.show()
```



2.2 Freeze, replace `fc`, train: the course's code, line by line

Course line	Meaning
`for param in resnet18.parameters(): param.requires_grad = False`	**freeze**: PyTorch will not compute gradients for these weights, so the optimiser can't change them. (The course comment says "freeze early layers", but this loop freezes **all** layers.)
`num_ftrs = resnet18.fc.in_features`	the old last layer is `Linear(512 → 1000)`, so `num_ftrs = 512`
`resnet18.fc = nn.Linear(num_ftrs, len(class_names))`	a **brand-new** layer `Linear(512 → 5)`. New layers are created with `requires_grad=True`, so this is the **only trainable part**.
`optim.Adam(resnet18.fc.parameters(), lr=0.001)`	give the optimiser only the new layer's weights

So the frozen ResNet acts as a fixed **feature extractor** (every image → 512 numbers) and we train a tiny classifier on top. This is the cheapest kind of transfer learning; "fine-tuning" usually means also unfreezing some layers later (see *Try this yourself*).

```
# Freeze early layers  (note: this loop freezes ALL layers)
for param in resnet18.parameters():
    param.requires_grad = False

# Replace final layer for custom classes
num_ftrs = resnet18.fc.in_features
resnet18.fc = nn.Linear(num_ftrs, len(class_names))

resnet18.to(device)

criterion = nn.CrossEntropyLoss()
optimizer = optim.Adam(resnet18.fc.parameters(), lr=0.001)

n_total = sum(p.numel() for p in resnet18.parameters())
n_train = sum(p.numel() for p in resnet18.parameters() if p.requires_grad)
print("new last layer:", resnet18.fc, "| num_ftrs =", num_ftrs)
print(f"trainable parameters: {n_train:,} of {n_total:,} ({100 * n_train / n_total:.3f}%)  =
512*5 weights + 5 biases")
```

```
new last layer: Linear(in_features=512, out_features=5, bias=True) | num_ftrs = 512
trainable parameters: 2,565 of 11,179,077 (0.023%)  = 512*5 weights + 5 biases
```

We wrap the course's training loop and its test loop in two small functions so that we can reuse them for the from-scratch model later. Changes from the course: we record losses and timings,

and `evaluate` calls **`model.eval()`**, which the course forgets. The loop body is exactly the course's. The course trains `range(1, 3)` = 2 epochs; we train **6**, so we can see the curve level off (and give the from-scratch model the same budget).

```
def train_one_epoch(model, optimizer, loader):
    model.train()
    running_loss = 0.0
    for inputs, labels in loader:                        # ---- course loop body ----
        inputs, labels = inputs.to(device), labels.to(device)
        optimizer.zero_grad()
        outputs = model(inputs)
        loss = criterion(outputs, labels)
        loss.backward()
        optimizer.step()
        running_loss += loss.item()
    return running_loss / len(loader)

def evaluate(model, loader):
    model.eval()                                         # <- missing in the course
    correct, total, preds, trues = 0, 0, [], []
    with torch.no_grad():
        for inputs, labels in loader:
            inputs, labels = inputs.to(device), labels.to(device)
            outputs = model(inputs)
            _, predicted = torch.max(outputs, 1)
            total += labels.size(0)
            correct += (predicted == labels).sum().item()
            preds.append(predicted.cpu()); trues.append(labels.cpu())
    return 100 * correct / total, torch.cat(preds).numpy(), torch.cat(trues).numpy()

def fit(model, optimizer, epochs, name):
    hist = {"loss": [], "acc": [], "time": []}
    for epoch in range(1, epochs + 1):
        t = time.time()
        loss = train_one_epoch(model, optimizer, trainloader)
        hist["time"].append(time.time() - t)
        acc, _, _ = evaluate(model, testloader)
        hist["loss"].append(loss); hist["acc"].append(acc)
        print(f"[{name}] Epoch {epoch}, Loss: {loss:.4f}, test accuracy: {acc:.1f}%  (train time
{hist['time'][-1]:.0f}s)")
    return hist

EPOCHS = 6
bn_before = resnet18.bn1.running_mean.clone()
hist_tl = fit(resnet18, optimizer, EPOCHS, "transfer")
```

```
[transfer] Epoch 1, Loss: 1.5400, test accuracy: 52.8%  (train time 76s)
[transfer] Epoch 2, Loss: 1.3628, test accuracy: 75.6%  (train time 69s)
[transfer] Epoch 3, Loss: 1.2202, test accuracy: 76.8%  (train time 41s)
[transfer] Epoch 4, Loss: 1.0976, test accuracy: 80.0%  (train time 57s)
[transfer] Epoch 5, Loss: 1.0111, test accuracy: 80.8%  (train time 42s)
[transfer] Epoch 6, Loss: 0.9193, test accuracy: 80.8%  (train time 28s)
```

A subtle point about "frozen" BatchNorm. `requires_grad = False` stops the *weights* from changing. But ResNet's BatchNorm layers also keep **running averages** of the data they see, and those are updated in `model.train()` mode **whether or not gradients are on**. So during training the "frozen" network still adapts its BatchNorm statistics a little to the flower photos:

```
print("bn1.weight.requires_grad:", resnet18.bn1.weight.requires_grad)
print(f"bn1.running_mean changed during training? {not torch.allclose(bn_before,
resnet18.bn1.running_mean.cpu())}  "
      f"(largest change {(bn_before - resnet18.bn1.running_mean.cpu()).abs().max():.4f})")
print("To freeze it completely, put the backbone in eval mode while training: resnet18.train();
resnet18.apply(lambda m: m.eval() if isinstance(m, nn.BatchNorm2d) else None)")
```

```
bn1.weight.requires_grad: False
bn1.running_mean changed during training? True  (largest change 5.3415)
To freeze it completely, put the backbone in eval mode while training: resnet18.train(); resnet1
8.apply(lambda m: m.eval() if isinstance(m, nn.BatchNorm2d) else None)
```

3 · Mini project: transfer learning for flower classification

3.1 How good is it? Accuracy, per class, confusion matrix


```python
acc_tl, pred_tl, true = evaluate(resnet18, testloader)
print(f"Accuracy on test set: {acc_tl:.2f}%  ({(pred_tl == true).sum()}/{len(true)})\n")

def per_class_and_confusion(pred, true, title):
    k = len(class_names)
    cm = np.zeros((k, k), dtype=int)
    for t, p in zip(true, pred):
        cm[t, p] += 1
    for i, c in enumerate(class_names):
        print(f"  {c:11s} {100 * cm[i, i] / cm[i].sum():5.1f}%")
    plt.figure(figsize=(5, 4.3))
    plt.imshow(cm, cmap="Greens")
    for i in range(k):
        for j in range(k):
            plt.text(j, i, cm[i, j], ha="center", va="center", color="white" if cm[i, j] >
cm.max() / 2 else "black")
    plt.xticks(range(k), class_names, rotation=30); plt.yticks(range(k), class_names)
    plt.xlabel("predicted"); plt.ylabel("true"); plt.title(title); plt.colorbar(fraction=0.046)
    plt.tight_layout(); plt.show()

print("per-class accuracy (transfer learning):")
per_class_and_confusion(pred_tl, true, f"Transfer learning: {acc_tl:.1f}%")
```

```
Accuracy on test set: 80.80%  (202/250)

per-class accuracy (transfer learning):
  daisy        84.0%
  dandelion    78.0%
  roses        74.0%
  sunflowers   88.0%
  tulips       80.0%
```



3.2 Forgetting `model.eval()`: what the course's test loop would do

The course's test loop runs right after training, so the model is still in **training mode**. ResNet18 has no dropout, but it has **BatchNorm**: in training mode BatchNorm normalises with the statistics of the current test batch, so a prediction depends on which *other* images share the batch. It also overwrites the stored running averages with test data.

`ImageFolder` lists the test images class by class and the test loader doesn't shuffle, so each batch of 32 holds mostly one kind of flower. Normalising such a batch by its own average largely removes what the images have in common, i.e. the class, so the damage is extra large. We also measure it with shuffled batches.

```
m = copy.deepcopy(resnet18)
m.train()                                   # the state the course leaves the model in
correct = 0
with torch.no_grad():
    for inputs, labels in testloader:
        correct += (m(inputs.to(device)).argmax(1).cpu() == labels).sum().item()
print(f"test accuracy WITH model.eval():    {acc_tl:.2f}%")
print(f"test accuracy WITHOUT model.eval(): {100 * correct / len(testset):.2f}%  (BatchNorm used
test-batch statistics)")


m = copy.deepcopy(resnet18); m.train()
shuffled = torch.utils.data.DataLoader(testset, batch_size=32, shuffle=True,
generator=torch.Generator().manual_seed(0))
with torch.no_grad():
    correct = sum((m(x.to(device)).argmax(1).cpu() == y).sum().item() for x, y in shuffled)
print(f"WITHOUT model.eval(), shuffled test batches: {100 * correct / len(testset):.2f}%")
```

```
test accuracy WITH model.eval():    80.80%
test accuracy WITHOUT model.eval(): 47.20%  (BatchNorm used test-batch statistics)
WITHOUT model.eval(), shuffled test batches: 80.40%
```

3.3 Predictions on a batch, with the correct colours

The course's last cell, fixed: un-normalise with the ImageNet mean/std, use `torch.no_grad()` and `eval()`, and show **true vs predicted** labels (green = right, red = wrong).

```
loader = torch.utils.data.DataLoader(testset, batch_size=16, shuffle=True,
generator=torch.Generator().manual_seed(0))
images, labels = next(iter(loader))
resnet18.eval()
with torch.no_grad():
    probs = torch.softmax(resnet18(images.to(device)), 1).cpu()
conf, predicted = probs.max(1)
plt.figure(figsize=(14, 7.5))
for k in range(16):
    plt.subplot(2, 8, k + 1); imshow(images[k]); plt.axis("off")
    plt.title(f"true: {class_names[labels[k]]}\npred: {class_names[predicted[k]]} {conf[k]:.0%}",
fontsize=9,
              color="green" if predicted[k] == labels[k] else "red")
plt.suptitle("Transfer-learning ResNet18 on 16 test flowers"); plt.tight_layout(); plt.show()
print('Predicted:', ' '.join(f'{class_names[predicted[j]]}' for j in range(4)))
```




```
Predicted: sunflowers roses tulips roses
```

3.4 Why does transfer learning work? Train the same ResNet18 from scratch

Same architecture, same 500 training photos, same transform, same 6 epochs, same Adam lr = 0.001. The only difference: **random weights** (`weights=None`) and **all** 11 million parameters trainable. The from-scratch model also has to compute gradients through the whole network, so each epoch is slower.


```
torch.manual_seed(0)
scratch = models.resnet18(weights=None, num_classes=len(class_names)).to(device)   # random
weights, fc already 512 -> 5
opt_scratch = optim.Adam(scratch.parameters(), lr=0.001)
print(f"trainable parameters: {sum(p.numel() for p in scratch.parameters() if
p.requires_grad):,}")
hist_sc = fit(scratch, opt_scratch, EPOCHS, "scratch")
```

```
trainable parameters: 11,179,077
[scratch] Epoch 1, Loss: 1.6889, test accuracy: 30.0%  (train time 139s)
[scratch] Epoch 2, Loss: 1.2848, test accuracy: 41.6%  (train time 144s)
```

```
[scratch] Epoch 3, Loss: 1.1813, test accuracy: 51.2%  (train time 143s)
[scratch] Epoch 4, Loss: 1.0748, test accuracy: 48.8%  (train time 143s)
[scratch] Epoch 5, Loss: 1.1280, test accuracy: 48.0%  (train time 63s)
[scratch] Epoch 6, Loss: 1.0823, test accuracy: 46.8%  (train time 59s)
```


```python
acc_sc, pred_sc, _ = evaluate(scratch, testloader)
fig, ax = plt.subplots(1, 2, figsize=(12, 3.8))
ep = range(1, EPOCHS + 1)
ax[0].plot(ep, hist_tl["loss"], "o-", label="pretrained + frozen (transfer)")
ax[0].plot(ep, hist_sc["loss"], "s-", label="from scratch")
ax[0].set_title("training loss"); ax[0].set_xlabel("epoch"); ax[0].legend();
ax[0].grid(alpha=0.3)
ax[1].plot(ep, hist_tl["acc"], "o-", label="pretrained + frozen (transfer)")
ax[1].plot(ep, hist_sc["acc"], "s-", label="from scratch")
ax[1].axhline(100 / len(class_names), color="gray", ls="--", label="chance (20%)")
ax[1].set_title("test accuracy (%)"); ax[1].set_xlabel("epoch"); ax[1].set_ylim(0, 100);
ax[1].legend(); ax[1].grid(alpha=0.3)
plt.tight_layout(); plt.show()

print(f"{'':32s}{'test acc':>9s}{'trainable params':>18s}{'train s/epoch':>15s}")
print(f"{'ResNet18 pretrained + frozen':32s}{acc_tl:8.1f}%{n_train:18,}
{np.mean(hist_tl['time']):15.0f}")
print(f"{'ResNet18 from scratch':32s}{acc_sc:8.1f}%{sum(p.numel() for p in
scratch.parameters()):18,}{np.mean(hist_sc['time']):15.0f}")
print("\nper-class accuracy (from scratch):")
per_class_and_confusion(pred_sc, true, f"From scratch: {acc_sc:.1f}%")
```




```
                                test acc  trainable params  train s/epoch
ResNet18 pretrained + frozen       80.8%             2,565             52
ResNet18 from scratch              46.8%        11,179,077            115

per-class accuracy (from scratch):
  daisy        30.0%
  dandelion    54.0%
  roses        54.0%
  sunflowers   52.0%
  tulips       44.0%
```




3.5 Use the classifier on a new photo

Save the trained model, load it back and classify a flower photo that was **in neither** our training nor our test subset (the full dataset has 3,670 photos and we used 750).

```
torch.save(resnet18.state_dict(), "data/resnet18_flowers.pt")
model = models.resnet18(weights=None)
model.fc = nn.Linear(512, len(class_names))
model.load_state_dict(torch.load("data/resnet18_flowers.pt", map_location="cpu"))
model.eval()

def predict_flower(path, model, k=3):
    x = transform(Image.open(path).convert("RGB")).unsqueeze(0)     # same transform as training,
+ batch dimension
    with torch.no_grad():
        p = torch.softmax(model(x), 1)[0]
    top = p.topk(k)
    return [(class_names[i], float(v)) for v, i in zip(top.values, top.indices)]

used = {f for split in ["train", "test"] for c in class_names for f in os.listdir(f"
{data_dir}/{split}/{c}")}
unseen = [(c, f) for c in class_names for f in sorted(os.listdir(f"data/flower_photos/{c}")) if f
not in used]
plt.figure(figsize=(15, 3.4))
for k, (c, f) in enumerate(random.Random(1).sample(unseen, 5)):
    path = f"data/flower_photos/{c}/{f}"
    res = predict_flower(path, model)
    plt.subplot(1, 5, k + 1); plt.imshow(Image.open(path)); plt.axis("off")
    plt.title(f"true: {c}\n" + "\n".join(f"{n} {p:.0%}" for n, p in res[:2]), fontsize=9,
color="green" if res[0][0] == c else "red")
plt.suptitle("Never-seen photos (top-2 predictions)"); plt.tight_layout(); plt.show()
```




```
print(f"Total run time of this notebook: {(time.time() - NOTEBOOK_START) / 60:.1f} minutes")
```

```
Total run time of this notebook: 23.3 minutes
```

🔧 What we changed from the course notebook, and why

Course code	Our version	
`data_dir = './custom_data'` (no data provided)	download TF *flower_photos*, build `data/custom_data/{train,test}/<class>/` with 100 + 50 photos per class	th da th fo
`models.resnet18(pretrained=True)`	`weights=models.ResNet18_Weights.IMAGENET1K_V1`, with a **fallback** to timm's ImageNet ResNet18 weights from GitHub	p d d is b o w
comment "Freeze early layers"	comment corrected: the loop freezes **all** layers	o tr
2 epochs, prints the loss only	6 epochs, test accuracy each epoch, time per epoch	to cu
test loop without `model.eval()`	`evaluate()` calls `model.eval()`	B u st in
`imshow` : `img / 2 + 0.5`	`img * std + mean` with the ImageNet values	th sl c c al
batch prediction without `torch.no_grad()`	wrapped in `no_grad()` + `eval()`	n n
4 predicted labels	per-class accuracy, confusion matrix, 16-image grid with true/pred, unseen-photo demo	a
(not in course)	same ResNet18 **from scratch**	sl le

Results, honestly

Measured in the run above. 5 flower classes, **500 training and 250 test photos**, CPU only, 6 epochs each:

Model	Test accuracy	Trainable parameters	Training time per epoch
ResNet18 **pretrained + frozen**, new `fc` (course exercise)	**80.8 %**	2,565	about 52 s
ResNet18 **from scratch** (same data, same epochs)	**46.8 %**	11,179,077	about 115 s
chance (guessing)	20 %		

What this shows:

- **Transfer learning works with very little data.** Training only 2,565 numbers on top of frozen ImageNet features reached 80.8 % after 6 short epochs. Its training loss was still falling (0.9193 at epoch 6), so more epochs, data augmentation or unfreezing `layer4` would probably add a few more points.
- **From scratch, the same network learns much less** from 500 photos (46.8 %). Its test accuracy peaked at 51.2 % in epoch 3 and then stopped improving (it drifted down a little), while its training loss levelled off around 1.1. 11 million weights are far too many to learn good visual features from 500 images; with longer training such a model would mostly start memorising the training photos (overfitting).
- **Forgetting `model.eval()` is not a small detail:** the course's test loop (model left in training mode) scored **47.2 %** instead of 80.8 %, because BatchNorm normalised each class-sorted test batch with its own statistics. With shuffled batches the damage almost vanished (80.4 %), because a mixed batch has statistics close to the stored ones. So the result without `eval()` depends on how the test batches happen to be put together; `eval()` makes it independent of that.
- **"Frozen" BatchNorm still moves:** `requires_grad=False` did not stop `bn1.running_mean` from changing during training (largest change 5.3415).
- The model is right but **not very confident** (many top probabilities in the grid are 35–60 %). With 5 classes and a briefly trained head that's expected; longer training sharpens it.
- **Which route ran:** the official torchvision weights could not be downloaded here, so the notebook used timm's ImageNet ResNet18 weights from GitHub. On a normal connection you'll get the official weights, and slightly different numbers.
- **Timing:** this notebook was run on a CPU shared with other jobs, which made every epoch slower than on an idle machine. The *ratio* is what matters: the from-scratch epochs took about 2.2× as long, because gradients had to flow through the whole network.

Common errors and how to fix them

Error / symptom	Cause	Fix
`FileNotFoundError: Couldn't find any class folder in ./custom_data/train`	wrong path or wrong layout	`ImageFolder` needs `root/<class_name>/<image>` ; check with `os.listdir(data_dir + '/train')`

Error / symptom	Cause	Fix
test classes in a different order from train	different folder names in train/test	use **identical** class folder names in both; compare `trainset.classes` and `testset.classes`
`RuntimeError: ... size mismatch for fc.weight: copying a param with shape torch.Size([1000, 512]) ... torch.Size([5, 512])`	loading a 1000-class checkpoint into a 5-class model (or the other way round)	replace `fc` *after* loading the ImageNet weights, and *before* loading your own fine-tuned `.pt`
`mat1 and mat2 shapes cannot be multiplied (32x512 and 2048x5)`	wrong `in_features` (2048 is for ResNet50)	always use `model.fc.in_features` rather than typing the number
accuracy poor with a pretrained model	forgot the ImageNet `Normalize` (or used different values)	normalise with `[0.485,0.456,0.406]` / `[0.229,0.224,0.225]`
plotted images have strange, over-contrasted colours	un-normalised with `/2 + 0.5` after an ImageNet `Normalize`	un-normalise with `img * std + mean`
`Expected all tensors to be on the same device`	replaced `fc` **after** `model.to(device)`, so the new layer is on the CPU	call `.to(device)` after replacing `fc` (the course does this correctly)
`CUDA out of memory`	224×224 images, batch too large	lower `batch_size` (32 → 16)
`URLError` downloading the weights	no access to download.pytorch.org	the notebook falls back to the GitHub copy automatically
`UserWarning: 'pretrained' is deprecated`	old API	`weights=models.ResNet18_Weights.DEFAULT`

Try this yourself

1. **Real fine-tuning.** After training `fc`, unfreeze the last stage: `for p in resnet18.layer4.parameters(): p.requires_grad = True`, then train again with `optim.Adam([{'params': resnet18.layer4.parameters(), 'lr': 1e-4}, {'params': resnet18.fc.parameters(), 'lr': 1e-3}])`. Does test accuracy rise? (Slower on a CPU.)
2. **Data augmentation.** Use `transforms.RandomResizedCrop(224)` + `transforms.RandomHorizontalFlip()` for the **training** transform only.
3. **Fewer images.** Set `N_TRAIN_PER_CLASS = 20`. How does transfer learning cope compared with training from scratch?
4. **EfficientNet.** Replace ResNet18 with `models.efficientnet_b0(weights=models.EfficientNet_B0_Weights.DEFAULT)`.

Its last layer is `model.classifier[1]` (`Linear(1280, 1000)`), so replace that instead of `fc`.

5. **Your own dataset.** Put photos in `data/custom_data/train/<class>/` and `data/custom_data/test/<class>/` (at least ~30 per class) and re-run from section 1's loader cell.
6. **Fully frozen BatchNorm.** Train with the BatchNorm layers in eval mode (see the tip in 2.2). Does accuracy change?

Run it on Google Colab with a GPU

1. Upload the notebook to colab.research.google.com; **Runtime → Change runtime type → T4 GPU**.
2. Delete the `torch.set_num_threads(2)` line; `device` will print `cuda`.
3. Run all. The official weights download works there, so the output will say `WEIGHTS ROUTE: official`.
4. With a GPU you can afford `N_TRAIN_PER_CLASS = 500` and unfreezing `layer4` (Try this 1).

Viva questions (with short model answers)

1. **What is transfer learning?** Reusing a model trained on a large dataset (ImageNet) as the starting point for a new task. Its general features (edges, textures, shapes) transfer, so we need little data and compute.
2. **What does `param.requires_grad = False` do?** It freezes the parameter: no gradient is computed for it, so the optimiser does not update it.
3. **Why replace `resnet18.fc`?** The original `fc` is `Linear(512, 1000)` for ImageNet's classes. We need one output per flower class, `Linear(512, 5)`. The new layer is trainable by default.
4. **Why pass only `resnet18.fc.parameters()` to the optimiser?** Only those are trainable. It also makes the intent explicit and avoids keeping optimiser state for frozen weights.
5. **Feature extraction vs fine-tuning?** Feature extraction = freeze the whole backbone and train only the new head (this lab). Fine-tuning = also unfreeze some or all pretrained layers and train them with a small learning rate.
6. **Why `Resize((224,224))` and ImageNet mean/std?** The network was pretrained on 224×224 images normalised with those statistics. Inputs must match what it saw during training.
7. **What folder structure does `ImageFolder` expect, and how are labels assigned?** `root/class_name/image.jpg`. Labels are the class folders in alphabetical order (`class_to_idx`).
8. **Why does the course's `imshow` show wrong colours?** It undoes a (0.5, 0.5) normalisation, but the data was normalised with the ImageNet mean/std, so values are stretched outside 0–1 and clipped. Correct: `img * std + mean` per channel.
9. **What is a residual connection and why does it help?** `out = F(x) + x`. The identity path lets gradients flow straight back (derivative has a "+1"), so very deep networks train without vanishing gradients.

10. **Why did the from-scratch ResNet18 do worse on the same data?** 11 M random weights cannot learn good visual features from 500 photos in 6 epochs (and would overfit with more). The pretrained one already has features learned from 1.28 M images, so only 2,565 weights need to be learned.
11. **Why is the transfer model faster per epoch?** No gradients are computed through the frozen backbone, only through the last layer. The forward pass is the same cost.
12. **Does `requires_grad=False` freeze BatchNorm completely?** No. The running mean/variance still update in `train()` mode (we measured this). Put the BatchNorm layers in `eval()` mode to freeze them fully.
13. **What happens if you test without `model.eval()`?** BatchNorm uses each test batch's own statistics (and dropout, if present, stays on), so results depend on which images share a batch. In 3.2: 80.8 % with `eval()`, 47.2 % without it on class-sorted batches, 80.4 % without it on shuffled batches.
14. **When would you *not* freeze the backbone?** When you have lots of data, or your images are very different from ImageNet (e.g. X-rays, satellite images). Then fine-tune more layers with a small learning rate.
15. **ResNet vs EfficientNet in one line each?** ResNet: skip connections make depth trainable. EfficientNet: compound scaling of depth, width and resolution together for the best accuracy per computation.

Lab 3 · Object detection with Faster R-CNN and YOLO

Course lab: `CV-Week3-Lecture3.ipynb` (in `course-files/labs/`) **Theory partner:** notes/04_object_detection_rcnn_yolo_ssd.md and notebooks/04_object_detection_rcnn_yolo_ssd.ipynb

The course notebook has three code cells. This lab runs all three for real, fixes what breaks, and explains every line:

Course cell	What it does	What you will see here
Setup: COCO dataset loader	load COCO images + box annotations with `CocoDetection`	the loader working on **real COCO images and labels**, plus the two bugs it hides
Exercise: pretrained Faster R-CNN	run a two-stage detector on a batch	the output format (`boxes` , `labels` , `scores`), score thresholds, drawn detections
Mini project: YOLO detector	`YOLO('yolov5s.pt')` on a picture	labelled boxes, a count per class, the `conf` / `iou` knobs, a speed race and a confidence-threshold sweep with precision and recall

What you will learn: how a detector's output is structured, how to load COCO properly, why a score threshold is needed, what NMS does in practice, and how to measure precision/recall rather than just looking at pictures.

Run time: several minutes on a 4-core laptop CPU (most of it is running two YOLO models over 128 images for the threshold sweep). On a Colab GPU: under a minute.

0 · Theory in 60 seconds (details in notes chapter 04)

- **Object detection = what + where:** for every object, a **class label**, a **bounding box** `(x1, y1, x2, y2)` and a **confidence score**.
- **Two-stage (R-CNN family → Faster R-CNN):** stage 1, a *Region Proposal Network* suggests ~1000 boxes that might contain something; stage 2 classifies each proposal and refines its box. Accurate, slower.
- **One-stage (YOLO, SSD):** a single network pass predicts boxes and classes for a grid of positions at once. Fast, nearly as accurate today.
- **Both** produce many overlapping guesses, then use a **score threshold** (drop unsure boxes) and **NMS** (*non-maximum suppression*: keep the best box, delete boxes that overlap it by more than an IoU threshold).
- **IoU** (*intersection over union*) = overlap area / union area. A detection counts as correct when IoU with a true box ≥ 0.5.

> **Two routes for the downloads.** The course uses torchvision's pretrained Faster R-CNN (weights from `download.pytorch.org`) and the full COCO dataset (from `images.cocodataset.org`, ~20 GB). On a normal internet connection both work and this notebook uses them. The machine that produced the outputs below **could not reach those two servers**, so every download cell tries the course's route first and, if it fails, falls back to something that *is* reachable (Ultralytics' **COCO128**: the first 128 images of COCO train2017 with their labels, and a **YOLOv8n** model instead of Faster R-CNN). Each cell prints which route ran.

```
%matplotlib inline
%config InlineBackend.figure_formats = ["jpeg"]   # photos as JPEG keep the notebook small
import os, json, time, glob, zipfile, urllib.request
from collections import Counter
import numpy as np
import matplotlib.pyplot as plt
import matplotlib.patches as patches
from PIL import Image
import torch
import torchvision
import torchvision.transforms as transforms

torch.manual_seed(0)
torch.set_num_threads(2)              # share the CPU politely; on your own laptop you can raise this
DATA = "data"                         # every download goes here (git-ignored)
os.makedirs(DATA, exist_ok=True)
device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
print("torch", torch.__version__, "| torchvision", torchvision.__version__, "| device:", device)

def download(url, dest):
    """Download url to dest once (skip if the file is already there)."""
    if not os.path.exists(dest):
        os.makedirs(os.path.dirname(dest) or ".", exist_ok=True)
        urllib.request.urlretrieve(url, dest)
    return dest
```

```
torch 2.14.1+cu130 | torchvision 0.29.1+cu130 | device: cpu
```

1 · Setup: the COCO dataset loader

COCO (*Common Objects in Context*) is the standard detection benchmark: 80 everyday classes (person, car, dog, cup, …), ~118,000 training photos and 5,000 validation photos, each with every object boxed. Annotations live in one big JSON file per split with three lists:

```
images:      [{"id": 9, "file_name": "000000000009.jpg", "width": 640, "height": 480},
...]
annotations: [{"image_id": 9, "bbox": [x, y, w, h], "category_id": 51, "area": ...,
"iscrowd": 0}, ...]
categories:  [{"id": 1, "name": "person"}, {"id": 2, "name": "bicycle"}, ...]
```

Two details trip everybody up:

- COCO boxes are **`[x, y, width, height]`** (top-left corner + size). torchvision models want **`[x1, y1, x2, y2]`** (two corners).
- Category ids run **1…90 with gaps** (80 real classes; 10 ids were dropped). **id 1 = person**, 3 = car, 18 = dog. torchvision detectors output these same ids.

On your own machine (the course's route): download `val2017.zip` (1 GB, 5,000 images) and `annotations_trainval2017.zip` (241 MB) from cocodataset.org and unzip so you have `data/coco_data/val2017/*.jpg` and `data/coco_data/annotations/instances_val2017.json`. Use **val2017**, not train2017 (18 GB): it is smaller *and* the pretrained models never trained on it, so results are honest. The cell below uses it automatically if it finds it.

Fallback (used here): COCO128 from Ultralytics' GitHub releases (7 MB) ships images + labels in YOLO's text format. We convert those labels into a real COCO-style JSON, so the course's `CocoDetection` loader runs **unchanged** on real COCO photos.

```
from ultralytics.data.converter import coco80_to_coco91_class     # YOLO class 0..79  ->  COCO id
1..90
COCO_NAMES =
torchvision.models.detection.FasterRCNN_ResNet50_FPN_Weights.DEFAULT.meta["categories"]  # index
= COCO id (no download needed)

coco_root = os.path.join(DATA, "coco_data")
official_imgs = os.path.join(coco_root, "val2017")
official_ann = os.path.join(coco_root, "annotations", "instances_val2017.json")

def build_coco128(coco_root):
    """Fallback: download COCO128 and write its labels as a COCO-format instances JSON."""
    z = download("https://github.com/ultralytics/assets/releases/download/v0.0.0/coco128.zip",
os.path.join(DATA, "coco128.zip"))
    if not os.path.isdir(os.path.join(DATA, "coco128")):
        zipfile.ZipFile(z).extractall(DATA)
    img_dir = os.path.join(DATA, "coco128", "images", "train2017")
    ann_file = os.path.join(coco_root, "annotations", "instances_coco128.json")
    if not os.path.exists(ann_file):
        to91 = coco80_to_coco91_class()
        images, anns = [], []
        for f in sorted(os.listdir(img_dir)):
            w, h = Image.open(os.path.join(img_dir, f)).size
            img_id = int(f.split(".")[0])
            images.append({"id": img_id, "file_name": f, "width": w, "height": h})
            lbl = os.path.join(DATA, "coco128", "labels", "train2017", f.replace(".jpg", ".txt"))
            if os.path.exists(lbl):
                for line in open(lbl).read().split("\n"):
                    if not line.strip():
                        continue
                    c, xc, yc, bw, bh = map(float, line.split())          # YOLO format: class,
centre x/y, w, h (all 0..1)
                    box = [(xc - bw / 2) * w, (yc - bh / 2) * h, bw * w, bh * h]   # -> COCO [x,
y, w, h] in pixels
                    anns.append({"id": len(anns) + 1, "image_id": img_id, "category_id":
to91[int(c)],
                                 "bbox": [round(v, 2) for v in box], "area": box[2] * box[3],
"iscrowd": 0})
        cats = [{"id": i, "name": n} for i, n in enumerate(COCO_NAMES) if n not in
("__background__", "N/A")]
        os.makedirs(os.path.dirname(ann_file), exist_ok=True)
        json.dump({"images": images, "annotations": anns, "categories": cats}, open(ann_file,
"w"))
    return img_dir, ann_file

if os.path.exists(official_ann):
    img_dir, ann_file = official_imgs, official_ann
    print("ROUTE: official COCO val2017 found on disk")
else:
    img_dir, ann_file = build_coco128(coco_root)
    print("ROUTE: fallback, COCO128 (first 128 images of COCO train2017) converted to COCO JSON")
print("images:", img_dir, "| annotations:", ann_file)
```

```
ROUTE: fallback, COCO128 (first 128 images of COCO train2017) converted to COCO JSON
images: data/coco128/images/train2017 | annotations: data/coco_data/annotations/instances_coco12
8.json
```

1a · The course's loader, exactly as written

```
transform = transforms.Compose([transforms.Resize((224,224)), transforms.ToTensor()])
trainset = CocoDetection(root=..., annFile=..., transform=transform)
trainloader = torch.utils.data.DataLoader(trainset, batch_size=4, shuffle=True)
```

- `CocoDetection(root, annFile, transform)` returns `(image, target)` where **`target` is a list of annotation dicts**, one per object in that image (needs `pip install pycocotools`).
- `transform` is applied **to the image only**. The boxes in `target` are not touched.
- `DataLoader(batch_size=4)` groups 4 samples. By default it tries to **stack** them into tensors (`default_collate`).

Let's run it and ask for one batch.

```
from torchvision.datasets import CocoDetection

transform = transforms.Compose([
    transforms.Resize((224,224)),
    transforms.ToTensor()
])
trainset = CocoDetection(root=img_dir, annFile=ann_file, transform=transform)
trainloader = torch.utils.data.DataLoader(trainset, batch_size=4, shuffle=True)
print("Loaded COCO dataset with", len(trainset), "images")

try:
    images, targets = next(iter(trainloader))
    print("batch loaded (this only happens if all 4 images have the same number of objects)")
except Exception as e:
    print("COURSE LOADER FAILS ->", type(e).__name__ + ":", str(e)[:160])
```

```
loading annotations into memory...
Done (t=0.00s)
creating index...
index created!
Loaded COCO dataset with 128 images
COURSE LOADER FAILS -> RuntimeError: each element in list of batch should be of equal size
```

Bug 1, the batch cannot be built. Image 1 may have 3 objects and image 2 may have 12. `default_collate` tries to stack the four `target` lists into one tensor and fails because their lengths differ. Detection data is *ragged*, so detection code always uses a custom `collate_fn` that simply keeps the samples in tuples:

```
collate_fn=lambda batch: tuple(zip(*batch))   # -> (img1, img2, img3, img4), (target1, ..., target4)
```


Bug 2, the boxes no longer match the picture. `Resize((224,224))` squashes the image, but the boxes in `target` are still in the original pixel coordinates. Look:

```
raw = CocoDetection(root=img_dir, annFile=ann_file)          # no transform: PIL image + annotation list
img, target = raw[1]
small = img.resize((224, 224))

fig, ax = plt.subplots(1, 2, figsize=(10, 4), dpi=80)
for a, im, title in [(ax[0], img, f"original {img.size[0]}x{img.size[1]}: boxes fit"),
                     (ax[1], small, "after Resize((224,224)): same boxes, wrong place")]:
    a.imshow(im); a.set_title(title, fontsize=10); a.axis("off")
```

```
    for t in target:
        x, y, w, h = t["bbox"]
        a.add_patch(patches.Rectangle((x, y), w, h, fill=False, ec="lime", lw=2))
    a.set_xlim(0, img.size[0] if im is img else 224); a.set_ylim(im.size[1], 0)
ax[1].set_xlim(0, img.size[0]); ax[1].set_ylim(img.size[1], 0)
plt.tight_layout(); plt.show()
print("objects in this image:", [COCO_NAMES[t['category_id']] for t in target])
```

```
loading annotations into memory...
Done (t=0.00s)
creating index...
index created!
```




```
objects in this image: ['giraffe', 'giraffe']
```

On the right the picture now covers only the top-left 224×224 pixels, but the boxes still use the original coordinates, so they no longer sit on the objects. If you trained on that, the model would learn nonsense. Two correct options:

1. **Don't resize at all** for torchvision detectors. Faster R-CNN resizes internally (shorter side → 800 px) and maps its boxes back to *your* image's coordinates. YOLO letterboxes to 640 internally and does the same.
2. If you must resize (e.g. for training your own model), resize the boxes by the same x and y factors (torchvision's `transforms.v2` can do this for you when boxes are wrapped as `tv_tensors.BoundingBoxes`).

1b · The fixed loader

```
transform = transforms.Compose([transforms.ToTensor()])        # FIX: no Resize - the detector
handles sizes itself
trainset = CocoDetection(root=img_dir, annFile=ann_file, transform=transform)
g = torch.Generator().manual_seed(0)
trainloader = torch.utils.data.DataLoader(trainset, batch_size=4, shuffle=True, generator=g,
                                          collate_fn=lambda batch: tuple(zip(*batch)))   # FIX:
keep ragged targets as tuples

images, targets = next(iter(trainloader))
print("Loaded COCO dataset with", len(trainset), "images")
for img, tgt in zip(images, targets):
    names = Counter(COCO_NAMES[t["category_id"]] for t in tgt)
    print(f"image {tuple(img.shape)} (C,H,W, values {img.min():.0f}..{img.max():.0f}) |
{len(tgt):2d} objects: {dict(names)}")

def coco_to_xyxy(tgt):
    """COCO [x,y,w,h] annotations -> tensor of [x1,y1,x2,y2] boxes + tensor of labels (what
torchvision models use)."""
    b = torch.tensor([t["bbox"] for t in tgt], dtype=torch.float32).reshape(-1, 4)
```

```
    b[:, 2:] += b[:, :2]
    return b, torch.tensor([t["category_id"] for t in tgt], dtype=torch.int64)
```

```
loading annotations into memory...
Done (t=0.00s)
creating index...
index created!
Loaded COCO dataset with 128 images
image (3, 480, 640) (C,H,W, values 0..1) | 11 objects: {'bed': 1, 'teddy bear': 10}
image (3, 480, 640) (C,H,W, values 0..1) |  3 objects: {'dog': 1, 'car': 1, 'frisbee': 1}
image (3, 640, 591) (C,H,W, values 0..1) |  2 objects: {'elephant': 2}
image (3, 488, 640) (C,H,W, values 0..1) |  5 objects: {'person': 3, 'elephant': 2}
```

Each image keeps its own size (COCO photos are about 640×480) and its own number of objects. That is exactly what detection models expect: **a list of `[3, H, W]` tensors with values 0–1**, not one stacked tensor.

2 · Exercise: detect objects with a pretrained Faster R-CNN

The course writes `detection.fasterrcnn_resnet50_fpn(pretrained=True)`. In torchvision ≥ 0.13 `pretrained=` is **deprecated** (and gives a warning, or an error in newer versions); the modern form is `weights="DEFAULT"` (= `FasterRCNN_ResNet50_FPN_Weights.COCO_V1`, 37.0 box mAP on COCO val2017, 41.8 M parameters, ~160 MB download).

What the model returns: for a list of N images, a list of N dicts:

key	shape	meaning
`boxes`	`[K, 4]` float	`x1, y1, x2, y2` in the pixel coordinates of **your** input image
`labels`	`[K]` int	COCO category id (1 = person, 3 = car, ...)
`scores`	`[K]` float	confidence 0–1, sorted high → low

torchvision keeps every box with score ≥ 0.05 (`box_score_thresh`) after NMS at IoU 0.5 (`box_nms_thresh`), up to 100 per image. So `len(output['boxes'])` (what the course prints) **counts lots of unsure junk**; you normally keep `scores > 0.5` or so.

The cell tries the course's model first. If the weights can't be downloaded it falls back to **YOLOv8n** wrapped so that it returns *exactly the same dict format*, so all the following code is identical for both routes.

```
import torchvision.models.detection as detection
from ultralytics import YOLO

def yolo_as_torchvision(yolo, conf=0.05, iou=0.5):
    """Wrap an Ultralytics YOLO model so it takes/returns the same things as a torchvision
detector."""
    to91 = coco80_to_coco91_class()
    def run(images):
        outs = []
        for img in images:                                      # img: [3,H,W] float tensor 0..1
(RGB)
            arr = (img.permute(1, 2, 0).cpu().numpy() * 255).astype(np.uint8)[:, :, ::-1]   # ->
HxWx3 uint8 BGR
            r = yolo.predict(arr, conf=conf, iou=iou, verbose=False)[0]
```

```
            outs.append({"boxes": r.boxes.xyxy.cpu(),
                         "labels": torch.tensor([to91[int(c)] for c in r.boxes.cls],
dtype=torch.int64),
                         "scores": r.boxes.conf.cpu()})
        return outs
    return run

try:
    model = detection.fasterrcnn_resnet50_fpn(weights="DEFAULT")    # FIX: weights= instead of
pretrained=True
    model.eval()                                                     # inference mode (batch-
norm/dropout frozen)
    model.to(device)
    detector, DETECTOR_NAME = model, "Faster R-CNN ResNet50-FPN (torchvision)"
    print("ROUTE: course model, Faster R-CNN with COCO weights")
except Exception as e:
    print("Faster R-CNN weights unavailable ->", type(e).__name__, str(e)[:90])
    w = download("https://github.com/ultralytics/assets/releases/download/v8.2.0/yolov8n.pt",
os.path.join(DATA, "yolov8n.pt"))
    yolo8 = YOLO(w)                                                  # 3.2 M-parameter YOLOv8
nano, COCO-trained
    detector, DETECTOR_NAME = yolo_as_torchvision(yolo8), "YOLOv8n (fallback)"
    print("ROUTE: fallback, YOLOv8n with the same output format")
```

```
Downloading: "https://download.pytorch.org/models/fasterrcnn_resnet50_fpn_coco-258fb6c6.pth" to /
root/.cache/torch/hub/checkpoints/fasterrcnn_resnet50_fpn_coco-258fb6c6.pth
Faster R-CNN weights unavailable -> URLError <urlopen error Tunnel connection failed: 403 Forbidd
en>
ROUTE: fallback, YOLOv8n with the same output format
```

```
# Run detection on a batch (the course's code, plus no_grad and a score threshold)
images_dev = [img.to(device) for img in images]
with torch.no_grad():                                    # FIX: no gradients needed for inference
(faster, less memory)
    outputs = detector(images_dev)

SCORE_THRESH = 0.5
print("Detector:", DETECTOR_NAME)
print("Detected objects in batch:")
for i, (output, tgt) in enumerate(zip(outputs, targets)):
    keep = output["scores"] > SCORE_THRESH
    print(f"Image {i}: {len(output['boxes']):3d} boxes returned, {int(keep.sum()):2d} with score
> {SCORE_THRESH}"
          f"  | ground truth: {len(tgt)} objects")

o = outputs[0]
print("\nkeys:", list(o.keys()))
print("first 3 detections of image 0:")
for b, l, s in zip(o["boxes"][:3], o["labels"][:3], o["scores"][:3]):
    print(f"  box={[round(v) for v in b.tolist()]}  label={int(l)} ({COCO_NAMES[int(l)]})  score=
{s:.2f}")
```

```
Detector: YOLOv8n (fallback)
Detected objects in batch:
Image 0:  19 boxes returned,  4 with score > 0.5  | ground truth: 11 objects
Image 1:   3 boxes returned,  3 with score > 0.5  | ground truth: 3 objects
Image 2:   2 boxes returned,  1 with score > 0.5  | ground truth: 2 objects
Image 3:   7 boxes returned,  1 with score > 0.5  | ground truth: 5 objects


keys: ['boxes', 'labels', 'scores']
first 3 detections of image 0:
  box=[181, 192, 286, 286]  label=88 (teddy bear)  score=0.65
  box=[398, 284, 527, 391]  label=88 (teddy bear)  score=0.59
  box=[261, 282, 336, 362]  label=88 (teddy bear)  score=0.54
```

```
def draw(ax, img, boxes, labels, scores=None, color="red", title=""):
    ax.imshow(img.permute(1, 2, 0) if torch.is_tensor(img) else img); ax.axis("off");
ax.set_title(title, fontsize=9)
    for k, (b, l) in enumerate(zip(boxes, labels)):
        x1, y1, x2, y2 = [float(v) for v in b]
```

```
        ax.add_patch(patches.Rectangle((x1, y1), x2 - x1, y2 - y1, fill=False, ec=color, lw=1.5))
        txt = COCO_NAMES[int(l)] + (f" {float(scores[k]):.2f}" if scores is not None else "")
        ax.text(x1, y1 - 3, txt, color="white", fontsize=7, bbox=dict(fc=color, ec="none", pad=1,
alpha=0.8))

fig, ax = plt.subplots(2, 4, figsize=(15, 6.5), dpi=60)
for i in range(4):
    gb, gl = coco_to_xyxy(targets[i])
    draw(ax[0, i], images[i], gb, gl, color="green", title=f"ground truth ({len(gl)} objects)")
    keep = outputs[i]["scores"] > SCORE_THRESH
    draw(ax[1, i], images[i], outputs[i]["boxes"][keep], outputs[i]["labels"][keep], outputs[i]
["scores"][keep],
         title=f"{DETECTOR_NAME.split(' (')[0]}, score > {SCORE_THRESH} ({int(keep.sum())}
boxes)")
plt.tight_layout(); plt.show()

for i in range(4):
    keep = outputs[i]["scores"] > SCORE_THRESH
    pred = Counter(COCO_NAMES[int(l)] for l in outputs[i]["labels"][keep])
    true = Counter(COCO_NAMES[t["category_id"]] for t in targets[i])
    print(f"image {i}: predicted {dict(pred)}\n         true      {dict(true)}")
```




```
image 0: predicted {'teddy bear': 3, 'vase': 1}
         true      {'bed': 1, 'teddy bear': 10}
image 1: predicted {'dog': 1, 'car': 1, 'frisbee': 1}
         true      {'dog': 1, 'car': 1, 'frisbee': 1}
image 2: predicted {'elephant': 1}
         true      {'elephant': 2}
image 3: predicted {'person': 1}
         true      {'person': 3, 'elephant': 2}
```

Green = the human annotation, red = the detector. Reading the counts side by side is the quickest sanity check: most objects are found; small, partly hidden or crowded objects (tiny people in the background, a pile of oranges) are the usual misses. We measure this properly in section 5.

3 · Mini project: a YOLO-based detector

The course cell is:

```
yolo_model = YOLO('yolov5s.pt')
results = yolo_model('sample.jpg')
results.show()
for r in results:
    print(r.names)
```

Three things to know:

1. **`YOLO('yolov5s.pt')`**: the `ultralytics` package no longer serves the original YOLOv5 weights; it silently **swaps in `yolov5su.pt`** (YOLOv5-small retrained with the newer anchor-free head) and prints a "PRO TIP". Same size class (9 M parameters), slightly better accuracy. We give it a path inside `data/` so the weight file doesn't land in your project folder.
2. **`results` is a Python list** (one `Results` object per input image), so `results.show()` raises `AttributeError: 'list' object has no attribute 'show'`. Use `results[0].show()` (opens a window) or `results[0].plot()` (returns the annotated image as a BGR numpy array, which works inside a notebook).
3. **`r.names` is the model's full class dictionary** `{0: 'person', 1: 'bicycle', …, 79: 'toothbrush'}`, the same 80 names for every image. It says nothing about what was detected. The detections are in `r.boxes`: `r.boxes.xyxy` (corners), `r.boxes.conf` (scores), `r.boxes.cls` (class index 0–79 → `r.names[int(c)]`).

```
# Two sample images from Ultralytics' public assets
sample_images = [download(f"https://github.com/ultralytics/assets/releases/download/v0.0.0/{n}",
os.path.join(DATA, n))
                 for n in ("bus.jpg", "zidane.jpg")]

# (we fetch the file ourselves so it lands in data/; YOLO('yolov5s.pt') alone would download it
into the current folder)
download("https://github.com/ultralytics/assets/releases/download/v8.2.0/yolov5su.pt",
os.path.join(DATA, "yolov5su.pt"))
yolo_model = YOLO(os.path.join(DATA, "yolov5s.pt"))      # the course's call -> actually loads
data/yolov5su.pt (see the PRO TIP)
sample_image = sample_images[0]
results = yolo_model(sample_image, verbose=False)

print("type(results):", type(results).__name__, "with", len(results), "element(s)")
try:
    results.show()
except AttributeError as e:
    print("course's results.show() ->", "AttributeError:", e)


for r in results:
    print("r.names has", len(r.names), "entries, e.g.", dict(list(r.names.items())[:4]), "...
(NOT the detections)")
```

```
PRO TIP 💡 Replace 'model=data/yolov5s.pt' with new 'model=data/yolov5su.pt'.
YOLOv5 'u' models are trained with https://github.com/ultralytics/ultralytics and feature improve
d performance vs standard YOLOv5 models trained with https://github.com/ultralytics/yolov5.
type(results): list with 1 element(s)
course's results.show() -> AttributeError: 'list' object has no attribute 'show'
r.names has 80 entries, e.g. {0: 'person', 1: 'bicycle', 2: 'car', 3: 'motorcycle'} ...  (NOT the
detections)
```

```
def yolo_report(model, path, conf=0.25, iou=0.7):
    r = model(path, conf=conf, iou=iou, verbose=False)[0]
    counts = Counter(r.names[int(c)] for c in r.boxes.cls)
    return r, counts

fig, ax = plt.subplots(1, 2, figsize=(14, 6), dpi=70)
for a, path in zip(ax, sample_images):
    r, counts = yolo_report(yolo_model, path)
    a.imshow(r.plot()[:, :, ::-1]); a.axis("off")            # plot() draws boxes+labels+scores;
BGR -> RGB
    a.set_title(f"{os.path.basename(path)}: {sum(counts.values())} objects", fontsize=10)
    print(f"{os.path.basename(path)} ({r.orig_shape[1]}x{r.orig_shape[0]}) -> count per class:
{dict(counts)}")
    for b, c, s in zip(r.boxes.xyxy, r.boxes.cls, r.boxes.conf):
        print(f"   {r.names[int(c)]:10s} score {s:.2f}  box {[round(v) for v in b.tolist()]}")
plt.tight_layout(); plt.show()
```

```
bus.jpg (810x1080) -> count per class: {'person': 4, 'bus': 1}
   person     score 0.88  box [49, 402, 245, 905]
   bus        score 0.87  box [3, 231, 805, 740]
   person     score 0.84  box [670, 393, 809, 880]
   person     score 0.84  box [221, 406, 345, 859]
   person     score 0.63  box [0, 546, 70, 872]
zidane.jpg (1280x720) -> count per class: {'person': 2, 'tie': 2}
   person     score 0.89  box [749, 40, 1149, 707]
   person     score 0.84  box [139, 201, 1145, 714]
   tie        score 0.67  box [435, 436, 529, 719]
   tie        score 0.29  box [434, 439, 490, 719]
```





3a · The two knobs: `conf` and `iou`

- **`conf`** (default 0.25): the **score threshold**. Lower → more boxes, more of them wrong (false positives). Higher → fewer, surer boxes, but faint/small objects get missed (false negatives).
- **`iou`** (default 0.7): the **NMS threshold**. After scoring, YOLO sorts boxes and deletes any box that overlaps a better box of the same class by more than `iou`. A *low* `iou` deletes aggressively (can merge two people standing close together); a value near 1 deletes almost nothing, so **duplicate boxes on the same object survive**.

```
path = sample_images[0]
settings = [(0.25, 0.7, "default"), (0.05, 0.7, "low conf"), (0.6, 0.7, "high conf"), (0.05,
0.99, "low conf + almost no NMS")]
fig, ax = plt.subplots(1, 4, figsize=(16, 5.5), dpi=60)
for a, (c, i, label) in zip(ax, settings):
    r, counts = yolo_report(yolo_model, path, conf=c, iou=i)
    a.imshow(r.plot(font_size=8, line_width=1)[:, :, ::-1]); a.axis("off")
    a.set_title(f"{label}\nconf={c}, iou={i}: {len(r.boxes)} boxes", fontsize=10)
    print(f"conf={c:<4} iou={i:<4} ({label:24s}) -> {len(r.boxes):3d} boxes {dict(counts)}")
plt.tight_layout(); plt.show()
```

```
conf=0.25 iou=0.7  (default                 ) ->   5 boxes {'person': 4, 'bus': 1}
conf=0.05 iou=0.7  (low conf                ) ->   6 boxes {'person': 4, 'bus': 1, 'fire hydran
t': 1}
conf=0.6  iou=0.7  (high conf               ) ->   5 boxes {'person': 4, 'bus': 1}
conf=0.05 iou=0.99 (low conf + almost no NMS) ->  48 boxes {'person': 40, 'bus': 7, 'fire hydran
t': 1}
```



4 · Speed: how long does one image take?

The theory says one-stage detectors are fast and two-stage ones are slow. We time each available model on the same 20 COCO images (after one warm-up run, because the first call includes set-up work), taking turns image by image and reporting the median time. Times are wall-clock on this machine's CPU limited to 2 threads; on a GPU every number drops by 10–50×.

```
yolo8 =
YOLO(download("https://github.com/ultralytics/assets/releases/download/v8.2.0/yolov8n.pt",
os.path.join(DATA, "yolov8n.pt")))
models = {"YOLOv5su (course's yolov5s)": yolo_as_torchvision(yolo_model, conf=0.25),
          "YOLOv8n": yolo_as_torchvision(yolo8, conf=0.25)}
if DETECTOR_NAME.startswith("Faster"):
    models["Faster R-CNN R50-FPN"] = detector
params = {"YOLOv5su (course's yolov5s)": sum(p.numel() for p in yolo_model.model.parameters()),
          "YOLOv8n": sum(p.numel() for p in yolo8.model.parameters()),
          "Faster R-CNN R50-FPN": sum(p.numel() for p in detector.parameters()) if
DETECTOR_NAME.startswith("Faster") else None}

speed_imgs = [trainset[k][0].to(device) for k in range(20)]
per_image = {name: [] for name in models}
with torch.no_grad():
    for m in models.values():
        m(speed_imgs[:1])                                    # warm-up
    for im in speed_imgs:                                    # take turns image by image, so
background load hits all models equally
        for name, m in models.items():
            t = time.perf_counter(); m([im]); per_image[name].append((time.perf_counter() - t) *
1000)
speed = {name: float(np.median(v)) for name, v in per_image.items()}   # median: robust to a few
slow outliers
for name in models:
    print(f"{name:30s} {params[name]/1e6:5.1f} M parameters   {speed[name]:6.0f} ms / image
(median)   ({1000/speed[name]:4.1f} images/s)")
base = speed["YOLOv8n"]
print("relative to YOLOv8n:", {n: f"{v/base:.1f}x" for n, v in speed.items()})
```

```
YOLOv5su (course's yolov5s)      9.2 M parameters      328 ms / image (median)   ( 3.0 images/s)
YOLOv8n                          3.2 M parameters      102 ms / image (median)   ( 9.8 images/s)
relative to YOLOv8n: {"YOLOv5su (course's yolov5s)": '3.2x', 'YOLOv8n': '1.0x'}
```

5 · Confidence-threshold sweep: precision vs recall

Pictures can fool you, so let's count. For every image we match each predicted box to an unmatched true box **of the same class** with IoU ≥ 0.5 (best score first):

- **precision** = correct boxes / all predicted boxes ("when it says *dog*, how often is it right?")
- **recall** = found true objects / all true objects ("how many of the dogs did it find?")

We run each YOLO model **once** at a very low threshold (0.01) on all 128 images, then apply every threshold afterwards, so the sweep costs one pass per model.

> **Honesty warning (fallback route):** COCO128 images come from COCO **train**2017, which these models were trained on, so the numbers below are **optimistic**. With the official val2017 images (the course route on your machine) you would get honest, somewhat lower numbers.

```
from torchvision.ops import box_iou

def match(pred_boxes, pred_labels, pred_scores, gt_boxes, gt_labels, iou_thr=0.5):
    """Return a True/False 'correct' flag for every prediction (greedy, best score first)."""
    correct = torch.zeros(len(pred_boxes), dtype=torch.bool)
    if len(pred_boxes) == 0 or len(gt_boxes) == 0:
        return correct
    ious = box_iou(pred_boxes, gt_boxes)
    used = torch.zeros(len(gt_boxes), dtype=torch.bool)
    for p in torch.argsort(pred_scores, descending=True):
        cand = (gt_labels == pred_labels[p]) & ~used & (ious[p] >= iou_thr)
        if cand.any():
            g = torch.where(cand)[0][ious[p][cand].argmax()]
            used[g] = True; correct[p] = True
    return correct


N_EVAL = len(trainset)
sweep_models = {"YOLOv5su": yolo_as_torchvision(yolo_model, conf=0.01), "YOLOv8n":
yolo_as_torchvision(yolo8, conf=0.01)}
gts = [coco_to_xyxy(trainset[k][1]) for k in range(N_EVAL)]
n_true = sum(len(l) for _, l in gts)
records = {}
t0 = time.time()
for name, m in sweep_models.items():
    scores_all, correct_all = [], []
    for k in range(N_EVAL):
        with torch.no_grad():
            o = m([trainset[k][0]])[0]
        scores_all.append(o["scores"]); correct_all.append(match(o["boxes"], o["labels"],
o["scores"], *gts[k]))
    records[name] = (torch.cat(scores_all), torch.cat(correct_all))
print(f"{N_EVAL} images, {n_true} true objects, both models evaluated in {time.time()-t0:.0f} s")

thresholds = [0.05, 0.1, 0.25, 0.4, 0.5, 0.6, 0.75, 0.9]
print(f"\n{'thresh':>6} | " + " | ".join(f"{n:^27s}" for n in records))
print(f"{'':>6} | " + " | ".join(f"{'boxes':>6} {'precision':>9} {'recall':>8}" for _ in
records))
curves = {n: ([], []) for n in records}
for t in np.linspace(0.01, 0.95, 60):
    for n, (s, c) in records.items():
        k = s >= t
        curves[n][0].append(c[k].float().mean().item() if k.any() else 1.0); curves[n]
[1].append(c[k].sum().item() / n_true)
for t in thresholds:
    row = []
    for n, (s, c) in records.items():
        k = s >= t
        row.append(f"{int(k.sum()):6d} {c[k].float().mean().item():9.2f}
{c[k].sum().item()/n_true:8.2f}")
    print(f"{t:6.2f} | " + " | ".join(row))
```

```
128 images, 929 true objects, both models evaluated in 101 s

thresh |          YOLOv5su           |          YOLOv8n
       |  boxes precision   recall |  boxes precision   recall
  0.05 |   1526      0.46     0.75 |   1533      0.41     0.67
  0.10 |   1067      0.61     0.70 |    999      0.56     0.60
  0.25 |    688      0.80     0.59 |    604      0.76     0.50
  0.40 |    530      0.87     0.50 |    451      0.85     0.41
  0.50 |    455      0.90     0.44 |    372      0.89     0.36
  0.60 |    379      0.93     0.38 |    297      0.93     0.30
  0.75 |    259      0.97     0.27 |    203      0.97     0.21
  0.90 |     68      1.00     0.07 |     56      1.00     0.06
```

```python
fig, ax = plt.subplots(1, 2, figsize=(12, 4.2), dpi=80)
ts = np.linspace(0.01, 0.95, 60)
for n, (p, r) in curves.items():
    ax[0].plot(ts, p, label=f"{n} precision"); ax[0].plot(ts, r, "--", label=f"{n} recall")
    ax[1].plot(r, p, label=n)
ax[0].axvline(0.25, color="grey", lw=0.8); ax[0].text(0.26, 0.05, "YOLO default conf",
fontsize=8)
ax[0].set_xlabel("confidence threshold"); ax[0].set_ylabel("value"); ax[0].legend(fontsize=8);
ax[0].set_title("raising the threshold trades recall for precision")
ax[1].set_xlabel("recall"); ax[1].set_ylabel("precision"); ax[1].set_title("precision-recall
curve (IoU >= 0.5)"); ax[1].legend()
for a in ax: a.grid(alpha=0.3)
plt.tight_layout(); plt.show()
```



🔧 What we changed from the course notebook, and why

Course code	Problem	Fix here
`CocoDetection(.., transform=Resize((224,224))+ToTensor)`	resizes the image but **not the boxes** → boxes point at the wrong pixels	`ToTensor()` only; detectors resize internally and return boxes in your image's coordinates
`DataLoader(trainset, batch_size=4, shuffle=True)`	default collate can't stack ragged target lists → `RuntimeError` on the first batch	`collate_fn=lambda batch: tuple(zip(*batch))`
`instances_train2017.json` / `train2017` (18 GB)	huge download; the pretrained model saw these images → optimistic results	`val2017` (1 GB) on your machine; COCO128 fallback here (clearly labelled optimistic)

Course code	Problem	Fix here
`fasterrcnn_resnet50_fpn(pretrained=True)`	`pretrained=` is deprecated	`weights="DEFAULT"`
`outputs = model(images)`	builds a gradient graph for nothing	wrapped in `torch.no_grad()`
`print(len(output['boxes']))`	counts every box with score ≥ 0.05, mostly junk	also report boxes with `scores > 0.5`, draw them, compare with ground truth
`YOLO('yolov5s.pt')`	silently becomes `yolov5su.pt`, downloaded into the current folder	explained; saved under `data/`
`results.show()`	`results` is a **list** → `AttributeError`	`results[0].plot()` (or `results[0].show()` outside notebooks)
`print(r.names)`	prints all 80 class names, not the detections	loop over `r.boxes` (`xyxy`, `conf`, `cls`) and count per class
`sample.jpg` placeholder	file does not exist	downloads `bus.jpg` and `zidane.jpg`

Results, honestly

What this run (fallback route: COCO128 + YOLO, no Faster R-CNN weights reachable) actually showed:

- **The course's loader fails as written**: the first batch raises `RuntimeError: each element in list of batch should be of equal size`. With `collate_fn` it works and gives a tuple of differently sized images (480×640, 640×591, …) with 2 to 11 objects each.
- **Section 2 (YOLOv8n standing in for Faster R-CNN)**: on the first batch the model returned 19, 3, 2 and 7 boxes, but only 4, 3, 1 and 1 had a score above 0.5. The dog/car/frisbee picture was found perfectly; the picture with **10 overlapping teddy bears** got only 3 of them, and the jungle picture found 1 of 3 people and neither elephant. Crowded and small objects are the hard cases.
- **Mini project**: `YOLO('yolov5s.pt')` really loaded `yolov5su.pt`; `results.show()` really raised `AttributeError`; `r.names` really is an 80-entry dictionary. On `bus.jpg` it found **4 people + 1 bus**, on `zidane.jpg` **2 people + 2 ties** (the second tie, at score 0.29, is a duplicate of the first, a reminder that NMS works per class and can still leave near-duplicates).
- **NMS matters**: lowering `conf` from 0.25 to 0.05 added just one wrong box (a "fire hydrant"), but switching NMS almost off (`iou=0.99`) exploded 5 boxes into **48**, mostly duplicates of the same four people and the bus.
- **Speed (CPU, 2 threads)**: YOLOv8n (3.2 M parameters) was about **3–4× faster** than YOLOv5su (9.2 M parameters); see the exact milliseconds in section 4. Other programs were

running on the machine, so treat these as rough. Faster R-CNN (41.8 M parameters) could not be timed here; on a CPU expect several seconds per image.

- **Threshold sweep on 128 images / 929 objects**: at the default `conf=0.25`, YOLOv5su had precision **0.80** and recall **0.59**, YOLOv8n **0.76** and **0.50**. Raising the threshold to 0.75 pushes precision to 0.97 but recall drops to 0.27 / 0.21. The bigger model is better at every threshold, which is the accuracy-vs-speed trade-off in numbers.
- **Caveat:** these 128 images were part of the models' training set, so real-world recall will be lower. Even so, half the labelled objects are missed at the default threshold, mostly small background objects and objects in dense groups.

Common errors and how to fix them

Error	Cause	Fix
`ModuleNotFoundError: No module named 'pycocotools'`	`CocoDetection` needs it	`pip install pycocotools`
`RuntimeError: each element in list of batch should be of equal size`	default collate on detection targets	`collate_fn=lambda b: tuple(zip(*b))`
`AttributeError: 'list' object has no attribute 'show'`	`results` is a list	`results[0].show()` / `results[0].plot()`
`UserWarning: The parameter 'pretrained' is deprecated`	old torchvision API	`weights="DEFAULT"`
`URLError … download.pytorch.org`	no internet / blocked server	download the `.pth` elsewhere and put it in `~/.cache/torch/hub/checkpoints/`, or use the YOLO fallback
`TypeError: … expected Tensor as element 0 in argument 0` when calling the model	passed a stacked tensor or PIL images	pass a **list** of `[3,H,W]` float tensors in 0–1
boxes drawn in the wrong place	resized image but not boxes, or mixed `[x,y,w,h]` with `[x1,y1,x2,y2]`	convert with `coco_to_xyxy`; don't resize for inference
everything detected twice	NMS `iou` set too high	keep `iou` ≈ 0.5–0.7

Try this yourself

1. Change `SCORE_THRESH` to 0.3 and 0.8 in section 2. Which objects appear/disappear?
2. Run `yolo_model` on your own photo: `yolo_report(yolo_model, "my_photo.jpg")`.
3. Add `classes=[0]` to a YOLO call (`yolo_model(path, classes=[0])`) to detect only people, and count them.

4. Swap `yolov8n.pt` for `yolov8s.pt` (bigger) and redo sections 4 and 5: is the extra accuracy worth the time?
5. With the official val2017 files on disk, re-run the notebook and compare the precision/recall table with the COCO128 one.

Run it on Google Colab with a GPU

1. Upload this notebook to Colab, then *Runtime → Change runtime type → T4 GPU*.
2. First cell: `!pip install ultralytics pycocotools`.
3. Optional (course route with real COCO val2017): `!mkdir -p data/coco_data && cd data/coco_data && wget -q http://images.cocodataset.org/zips/val2017.zip http://images.cocodataset.org/annotations/annotations_trainval2017.zip && unzip -q val2017.zip && unzip -q annotations_trainval2017.zip`
4. *Run all*. Faster R-CNN will download (~160 MB) and be used for section 2 and the speed race; `device` will print `cuda`.

Viva questions

1. **What does a detector output for each object?** A box `(x1, y1, x2, y2)`, a class label and a confidence score.
2. **What is the difference between Faster R-CNN and YOLO?** Faster R-CNN is two-stage: a Region Proposal Network proposes regions, then a second head classifies/refines each. YOLO is one-stage: one pass predicts boxes and classes over a grid. Faster R-CNN is traditionally more accurate on small objects; YOLO is much faster.
3. **What do `boxes`, `labels`, `scores` contain in torchvision's output?** `[K,4]` corner coordinates in input-image pixels, `[K]` COCO category ids (1 = person), `[K]` confidences sorted high to low.
4. **Why apply a score threshold?** torchvision returns every box above 0.05; most low-score boxes are wrong. A threshold (e.g. 0.5) trades recall for precision.
5. **What is NMS and what does YOLO's `iou` parameter control?** Non-maximum suppression keeps the highest-scoring box and removes same-class boxes overlapping it by more than the IoU threshold; `iou` is that threshold.
6. **What is IoU and why 0.5?** Intersection area / union area; 0.5 is the conventional "this box found that object" cut-off (COCO also averages over 0.5–0.95).
7. **Why does the course's DataLoader crash?** Each image has a different number of objects, so the default collate can't stack targets; a custom `collate_fn` keeps them as tuples.
8. **Why is `Resize((224,224))` wrong here?** It changes image coordinates but not the box annotations; also detectors resize internally (Faster R-CNN to ~800 px, YOLO to 640) and squashing to 224 makes small objects vanish.
9. **COCO box format vs torchvision box format?** COCO `[x, y, w, h]`; torchvision `[x1, y1, x2, y2]`.
10. **Why `model.eval()` and `torch.no_grad()`?** `eval()` puts the model into inference behaviour (detection models return predictions instead of losses, batch-norm uses stored statistics); `no_grad()` skips building the gradient graph, saving memory and time.

11. **Precision vs recall?** Precision = fraction of predicted boxes that are right; recall = fraction of true objects found. Raising the confidence threshold raises precision and lowers recall.
12. **Why are results on COCO128 optimistic?** Its images are from COCO train2017, which the pretrained models trained on; evaluate on val2017 for honest numbers.
13. **What is `yolov5su.pt`?** YOLOv5-small retrained by Ultralytics with an anchor-free, YOLOv8-style head; `YOLO('yolov5s.pt')` is mapped to it.
14. **Why are COCO category ids not 0–79?** The original 91-id list had 11 ids that were never used, so the 80 real classes keep ids 1–90 with gaps; YOLO renumbers them 0–79.

Lab 4 · U-Net for medical image segmentation

Course lab: `CV-Week3-Lecture4.ipynb` (in `course-files/labs/`) **Theory partner:** notes/05_segmentation_fcn_unet_mask_rcnn.md and notebooks/05_segmentation_fcn_unet_mask_rcnn.ipynb

Course cell	What it does	What you will see here
Setup: `MedicalDataset` loader	pairs each image with its mask from two folders	the loader running on **real microscopy data** (the dataset from the original U-Net paper), plus the mask-resizing bug
Exercise: "U-Net"	trains a small network with `BCEWithLogitsLoss`	the course's model trained properly **and** a real U-Net with skip connections, compared on held-out images (Dice, IoU, boundary sharpness)
Mini project: tumour segmentation	shows image / true mask / predicted mask	a tumour-segmentation prototype on a **synthetic** MRI-like dataset (clearly fake data, real method), with Dice and tumour-area estimates

What you will learn: how a segmentation dataset is organised, why masks need special handling, what `BCEWithLogitsLoss`, `sigmoid > 0.5`, `ConvTranspose2d(stride=2)`, Dice and IoU mean, and **why the course's model is not really a U-Net**.

Run time: about 5–6 minutes on a laptop CPU (three small networks are trained). On a Colab GPU: about 1 minute.

0 · Theory in 60 seconds (details in notes chapter 05)

- **Semantic segmentation** = a class for **every pixel**. Output = a mask the same size as the image.
- **FCN**: replace the fully connected layers of a classifier with convolutions, so the output is a (coarse) map, then upsample it.
- **U-Net**: an **encoder** (conv + pool, repeated) shrinks the image and learns *what* is there; a **decoder** (upsample + conv, repeated) grows it back to full size; **skip connections** copy each encoder feature map across and **concatenate** it with the decoder map of the same size, so fine detail (*where exactly*) is not lost. Drawn, it looks like a "U".
- **`ConvTranspose2d(in, out, kernel_size=2, stride=2)`**: a learned upsampling that doubles height and width (each input pixel "paints" a 2×2 patch with learned weights).
- **Loss**: `BCEWithLogitsLoss` = sigmoid + binary cross-entropy in one numerically safe step. The network outputs **logits** (any real number); `sigmoid(logit)` gives a probability 0–1; **`> 0.5`** turns it into a yes/no mask.
- **Metrics**: **IoU** = |pred ∩ true| / |pred ∪ true|; **Dice** = 2|pred ∩ true| / (|pred| + |true|). Both 0 (no overlap) to 1 (perfect). Dice is always ≥ IoU (Dice = 2·IoU / (1 + IoU)).

The dataset

The course leaves the dataset as a placeholder (`./medical/train/images`). We use the **ISBI 2012 electron-microscopy (EM) segmentation challenge** data, the very dataset the original U-Net paper (Ronneberger et al., 2015) won with: 30 grey-scale 512×512 slices of a fruit-fly nerve cord with hand-drawn masks of the **cell membranes**. It is small (about 8 MB), real and medical-research grade. We download it from the copy in the public `zhixuhao/unet` GitHub repository and arrange it in **exactly the folder layout the course's loader expects**, holding out the last 6 slices as a test set the model never trains on.


```
%matplotlib inline
import os, time, random, urllib.request
import numpy as np
import matplotlib.pyplot as plt
from PIL import Image
import torch
import torch.nn as nn
import torch.nn.functional as F
import torchvision.transforms as transforms
from torch.utils.data import DataLoader, Dataset

torch.manual_seed(0); np.random.seed(0); random.seed(0)
torch.set_num_threads(2)                    # share the CPU politely; raise on your own machine
device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
print("torch", torch.__version__, "| device:", device)

DATA = "data"
root = os.path.join(DATA, "medical")
BASE = "https://raw.githubusercontent.com/zhixuhao/unet/master/data/membrane/train"
N_TEST = 6                                  # slices 24..29 are held out
for i in range(30):
    split = "test" if i >= 30 - N_TEST else "train"
    for kind, sub in (("image", "images"), ("label", "masks")):
        dest = os.path.join(root, split, sub, f"{i:02d}.png")
        if not os.path.exists(dest):
            os.makedirs(os.path.dirname(dest), exist_ok=True)
            urllib.request.urlretrieve(f"{BASE}/{kind}/{i}.png", dest + ".tmp")
            im = Image.open(dest + ".tmp")
            if kind == "label":                 # original: white = cell inside, black =
membrane.
                im = Image.eval(im.convert("L"), lambda v: 255 - v)   # we segment the MEMBRANE,
so make it white (= 1)
            im.save(dest); os.remove(dest + ".tmp")
for split in ("train", "test"):
    print(split, {sub: len(os.listdir(os.path.join(root, split, sub))) for sub in ("images",
"masks")})
```

```
torch 2.14.1+cu130 | device: cpu
train {'images': 24, 'masks': 24}
test {'images': 6, 'masks': 6}
```

```
fig, ax = plt.subplots(1, 4, figsize=(13, 3.4), dpi=80)
img0 = Image.open(os.path.join(root, "train", "images", "00.png")); m0 =
Image.open(os.path.join(root, "train", "masks", "00.png"))
ax[0].imshow(img0, cmap="gray"); ax[0].set_title("EM slice 512x512")
ax[1].imshow(m0, cmap="gray"); ax[1].set_title("mask: white = membrane")
ax[2].imshow(np.array(img0)[150:278, 150:278], cmap="gray"); ax[2].set_title("zoom 128x128")
ax[3].imshow(np.array(m0)[150:278, 150:278], cmap="gray"); ax[3].set_title("zoomed mask")
for a in ax: a.axis("off")
plt.tight_layout(); plt.show()
print(f"membrane pixels: {(np.array(m0) > 127).mean():.1%} of the slice; pixel values in the
mask: {np.unique(np.array(m0))}")
```




```
membrane pixels: 21.9% of the slice; pixel values in the mask: [  0 255]
```

The task: draw every cell wall. It is hard because the walls are thin (a few pixels), sometimes faint, and the inside of cells contains dark blobs (mitochondria, vesicles) that look like membrane but are not.

1 · Setup: the course's `MedicalDataset` loader

```
class MedicalDataset(Dataset):
    def __init__(self, image_dir, mask_dir, transform=None):
        self.images = os.listdir(image_dir)            # file names; the mask has the SAME name
in mask_dir
    def __getitem__(self, idx):
        image = Image.open(img_path).convert("RGB")    # 3 channels
        mask  = Image.open(mask_path).convert("L")     # 1 channel, 0..255
        if self.transform:
            image = self.transform(image)
            mask  = self.transform(mask)               # <- the SAME transform for the mask
        return image, mask
```

`Dataset` needs only `__len__` (how many samples) and `__getitem__` (return sample number `idx`); `DataLoader` then shuffles and batches. `ToTensor()` turns a PIL image (H×W×C, 0–255) into a float tensor (C×H×W, 0–1). Let's run it exactly as written and look at the mask values it produces.

```
# The course's dataset class, unchanged
class MedicalDataset(Dataset):
    def __init__(self, image_dir, mask_dir, transform=None):
        self.image_dir = image_dir
        self.mask_dir = mask_dir
        self.transform = transform
        self.images = os.listdir(image_dir)
    def __len__(self):
        return len(self.images)
    def __getitem__(self, idx):
        img_path = os.path.join(self.image_dir, self.images[idx])
        mask_path = os.path.join(self.mask_dir, self.images[idx])
        image = Image.open(img_path).convert("RGB")
        mask = Image.open(mask_path).convert("L")
        if self.transform:
            image = self.transform(image)
            mask = self.transform(mask)
        return image, mask

transform = transforms.Compose([
    transforms.Resize((128,128)),
    transforms.ToTensor()
])

train_dataset = MedicalDataset(os.path.join(root, "train", "images"), os.path.join(root, "train",
"masks"), transform=transform)
```

```
train_loader = DataLoader(train_dataset, batch_size=4, shuffle=True)
print("Loaded medical dataset with", len(train_dataset), "images")

images, masks = next(iter(train_loader))
print("images:", tuple(images.shape), "masks:", tuple(masks.shape))
u = torch.unique(masks)
print(f"mask contains {len(u)} different values, e.g. {[round(v, 3) for v in u[1:6].tolist()]}
...")
print(f"pixels that are neither 0 nor 1: {((masks > 0) & (masks < 1)).float().mean():.1%}")
```

```
Loaded medical dataset with 24 images
images: (4, 3, 128, 128) masks: (4, 1, 128, 128)
mask contains 256 different values, e.g. [0.004, 0.008, 0.012, 0.016, 0.02] ...
pixels that are neither 0 nor 1: 40.0%
```

Bug: the mask is no longer a mask. `Resize` uses **bilinear interpolation** by default, which averages neighbouring pixels. That is right for a photo but wrong for a label map: on every membrane edge the mask now holds in-between values like 0.3 or 0.7 ("30 % membrane"?). With `BCEWithLogitsLoss` this quietly becomes a soft target and blurs what the network learns; with a multi-class mask (0 = background, 1 = liver, 2 = tumour) averaging would invent wrong classes (1.5?).

Fix: give the mask its own transform with **nearest-neighbour** resizing (it only copies existing values), then threshold to make it exactly 0/1. Two more improvements:

- **`sorted(os.listdir(...))`**: `os.listdir` returns files in an arbitrary order; sorting makes runs reproducible.
- **Augmentation applied to image and mask together**: with only 24 training slices, random flips and 90° rotations are almost free extra data, but they must be the *same* random flip for both, so they live inside `__getitem__`, not in two independent `transforms` pipelines.

```
class MedicalDataset(Dataset):
    """Fixed version: separate mask transform (nearest + binarise) and joint augmentation."""
    def __init__(self, image_dir, mask_dir, size=128, augment=False):
        self.image_dir, self.mask_dir, self.augment = image_dir, mask_dir, augment
        self.images = sorted(os.listdir(image_dir))                                    # FIX:
fixed order
        self.img_tf = transforms.Compose([transforms.Resize((size, size)),
transforms.ToTensor()])
        self.mask_tf = transforms.Compose([transforms.Resize((size, size)),
interpolation=transforms.InterpolationMode.NEAREST),
                                           transforms.ToTensor()])                     #
FIX: nearest for labels
    def __len__(self):
        return len(self.images)
    def __getitem__(self, idx):
        name = self.images[idx]
        image = self.img_tf(Image.open(os.path.join(self.image_dir, name)).convert("RGB"))
        mask = (self.mask_tf(Image.open(os.path.join(self.mask_dir, name)).convert("L")) >
0.5).float()   # FIX: exactly 0/1
        if self.augment:                                                               #
same random flip/rotation for both
            if random.random() < 0.5:
                image, mask = image.flip(-1), mask.flip(-1)
            if random.random() < 0.5:
                image, mask = image.flip(-2), mask.flip(-2)
            k = random.randint(0, 3)
            image, mask = torch.rot90(image, k, (1, 2)), torch.rot90(mask, k, (1, 2))
        return image, mask

train_dataset = MedicalDataset(os.path.join(root, "train", "images"), os.path.join(root, "train",
"masks"), augment=True)
test_dataset = MedicalDataset(os.path.join(root, "test", "images"), os.path.join(root, "test",
```

```
"masks"))   # FIX: a held-out split
train_loader = DataLoader(train_dataset, batch_size=4, shuffle=True)
test_loader = DataLoader(test_dataset, batch_size=6, shuffle=False)

images, masks = next(iter(train_loader))
print("train:", len(train_dataset), "slices | test:", len(test_dataset), "slices (never used for
training)")
print("mask values now:", torch.unique(masks).tolist(), "| membrane fraction at 128x128:", f"
{masks.mean():.1%}")
```

```
train: 24 slices | test: 6 slices (never used for training)
mask values now: [0.0, 1.0] | membrane fraction at 128x128: 22.5%
```

2 · Exercise: the course's "U-Net"

```
self.encoder = nn.Sequential(nn.Conv2d(3, 64, 3, padding=1), nn.ReLU(), nn.MaxPool2d(2))
# 3x128x128 -> 64x64x64
self.decoder = nn.Sequential(nn.ConvTranspose2d(64, 32, 2, stride=2), nn.ReLU(), nn.Conv2d(32,
1, 1))  # -> 32x128x128 -> 1x128x128
```

Line by line:

- `Conv2d(3, 64, 3, padding=1)` : 64 learned 3×3 filters over the RGB input; `padding=1` keeps 128×128.
- `MaxPool2d(2)` : halves the size to 64×64 (keeps the strongest response in each 2×2 block).
- `ConvTranspose2d(64, 32, 2, stride=2)` : learned upsampling back to 128×128.
- `Conv2d(32, 1, 1)` : a 1×1 convolution that mixes the 32 channels into **one logit per pixel**.

This is not a U-Net. It has **one** level down and one up, so every output pixel sees only a 4×4-pixel neighbourhood of the input (too little context to tell a membrane from a dark blob inside a cell), and it has **no skip connections**: nothing is concatenated from encoder to decoder. It is a tiny encoder–decoder (closer to a shallow FCN). We'll keep it as the course wrote it, train it properly, and compare it with:

1. **`DeepNoSkip`** : a 4-level encoder–decoder, same depth as our U-Net but *without* skip connections, to separate the effect of **depth** from the effect of **skips**.
2. **`UNet`** : a real (small) U-Net: 4 levels (3 poolings), two 3×3 convs + BatchNorm + ReLU per level, `ConvTranspose2d(stride=2)` up, and the encoder features **concatenated** in at every level.

```
# The course's model, unchanged except for the class name
class CourseUNet(nn.Module):
    def __init__(self):
        super(CourseUNet, self).__init__()
        self.encoder = nn.Sequential(
            nn.Conv2d(3, 64, 3, padding=1),
            nn.ReLU(),
            nn.MaxPool2d(2)
        )
        self.decoder = nn.Sequential(
            nn.ConvTranspose2d(64, 32, 2, stride=2),
            nn.ReLU(),
            nn.Conv2d(32, 1, 1)
        )
    def forward(self, x):
        x = self.encoder(x)
        x = self.decoder(x)
        return x

def double_conv(cin, cout):
```

```
    """Two 3x3 conv + BatchNorm + ReLU: the basic U-Net block."""
    return nn.Sequential(nn.Conv2d(cin, cout, 3, padding=1), nn.BatchNorm2d(cout),
nn.ReLU(inplace=True),
                         nn.Conv2d(cout, cout, 3, padding=1), nn.BatchNorm2d(cout),
nn.ReLU(inplace=True))

class UNet(nn.Module):
    """A real U-Net: encoder, bottleneck, decoder, and skip connections (concatenation) at every
level."""
    def __init__(self, in_ch=3, out_ch=1, base=8, skips=True):
        super().__init__()
        self.skips = skips
        c = [base, base * 2, base * 4, base * 8]                    # 8, 16, 32, 64 channels
(kept small for a CPU)
        self.down = nn.ModuleList([double_conv(in_ch, c[0]), double_conv(c[0], c[1]),
double_conv(c[1], c[2])])
        self.bottleneck = double_conv(c[2], c[3])                  # 16x16 at 128x128 input: wide
context
        self.up = nn.ModuleList([nn.ConvTranspose2d(c[3], c[2], 2, stride=2),
                                 nn.ConvTranspose2d(c[2], c[1], 2, stride=2),
                                 nn.ConvTranspose2d(c[1], c[0], 2, stride=2)])
        k = 2 if skips else 1                                       # concatenation doubles the
channels
        self.dec = nn.ModuleList([double_conv(c[2] * k, c[2]), double_conv(c[1] * k, c[1]),
double_conv(c[0] * k, c[0])])
        self.head = nn.Conv2d(c[0], out_ch, 1)                      # 1x1 conv -> one logit per
pixel
    def forward(self, x):
        saved = []
        for block in self.down:                                     # encoder: conv, remember,
pool
            x = block(x); saved.append(x); x = F.max_pool2d(x, 2)
        x = self.bottleneck(x)
        for up, dec, s in zip(self.up, self.dec, reversed(saved)):  # decoder: upsample, (concat
skip), conv
            x = up(x)
            if self.skips:
                x = torch.cat([s, x], dim=1)                        # <- THE skip connection
            x = dec(x)
        return self.head(x)

for name, m in [("CourseUNet", CourseUNet()), ("DeepNoSkip", UNet(skips=False)), ("UNet",
UNet())]:
    out = m(torch.zeros(1, 3, 128, 128))
    print(f"{name:11s} {sum(p.numel() for p in m.parameters()):>9,} parameters | output
{tuple(out.shape)}")
```

```
CourseUNet     10,049 parameters | output (1, 1, 128, 128)
DeepNoSkip    109,433 parameters | output (1, 1, 128, 128)
UNet          121,529 parameters | output (1, 1, 128, 128)
```

Training (the course's loop, plus evaluation on the held-out slices)

The course's loop is correct as a loop: `zero_grad → forward → loss → backward → step`. What it lacks is (a) more than 2 epochs (24 images × 2 epochs = 12 weight updates, nowhere near enough), (b) any measurement on data the model has not seen, and (c) `model.eval()` + `torch.no_grad()` when predicting (BatchNorm must use its stored statistics at test time).

We train all three models with the same loss (`BCEWithLogitsLoss`), optimiser (Adam, lr = 0.001), augmentation and number of epochs, and after every epoch compute **Dice on the 6 test slices**.

```
def dice_iou(logits, target, thr=0.5):
    pred = (torch.sigmoid(logits) > thr).float()                    # probability > 0.5  ->
```

```
membrane
    inter = (pred * target).sum().item(); p, t = pred.sum().item(), target.sum().item()
    return 2 * inter / (p + t + 1e-8), inter / (p + t - inter + 1e-8)

@torch.no_grad()
def evaluate(model, loader):
    model.eval()                                                    # FIX: inference mode
(BatchNorm uses running stats)
    logits, targets = [], []
    for images, masks in loader:
        logits.append(model(images.to(device)).cpu()); targets.append(masks)
    logits, targets = torch.cat(logits), torch.cat(targets)
    return (*dice_iou(logits, targets), logits, targets)


def train(model, epochs, lr=0.001):
    model.to(device)
    criterion = nn.BCEWithLogitsLoss()
    optimizer = torch.optim.Adam(model.parameters(), lr=lr)
    hist = {"loss": [], "dice": []}
    for epoch in range(1, epochs + 1):
        model.train()
        running_loss = 0.0
        for images, masks in train_loader:
            images, masks = images.to(device), masks.to(device)
            optimizer.zero_grad()
            outputs = model(images)
            loss = criterion(outputs, masks)
            loss.backward()
            optimizer.step()
            running_loss += loss.item()
        hist["loss"].append(running_loss / len(train_loader))
        hist["dice"].append(evaluate(model, test_loader)[0])
        if epoch in (1, 2) or epoch % 10 == 0:
            print(f"  Epoch {epoch:3d}, Loss: {hist['loss'][-1]:.4f}, test Dice: {hist['dice']
[-1]:.3f}")
    return hist

EPOCHS = 40
models, hists, times = {}, {}, {}
for name, make in [("CourseUNet", CourseUNet), ("DeepNoSkip", lambda: UNet(skips=False)),
("UNet", UNet)]:
    torch.manual_seed(0); random.seed(0)
    print(name)
    t = time.time()
    models[name] = make()
    hists[name] = train(models[name], EPOCHS)
    times[name] = time.time() - t
    print(f"  trained in {times[name]:.0f} s")
```

```
CourseUNet
  Epoch   1, Loss: 0.6688, test Dice: 0.000
  Epoch   2, Loss: 0.6406, test Dice: 0.000
  Epoch  10, Loss: 0.5042, test Dice: 0.000
  Epoch  20, Loss: 0.4904, test Dice: 0.000
  Epoch  30, Loss: 0.4581, test Dice: 0.009
  Epoch  40, Loss: 0.4090, test Dice: 0.160
  trained in 26 s
DeepNoSkip
  Epoch   1, Loss: 0.7144, test Dice: 0.329
  Epoch   2, Loss: 0.6793, test Dice: 0.298
  Epoch  10, Loss: 0.5735, test Dice: 0.009
  Epoch  20, Loss: 0.5055, test Dice: 0.000
  Epoch  30, Loss: 0.4566, test Dice: 0.000
  Epoch  40, Loss: 0.4225, test Dice: 0.249
  trained in 24 s
UNet
  Epoch   1, Loss: 0.7297, test Dice: 0.000
  Epoch   2, Loss: 0.6499, test Dice: 0.000
  Epoch  10, Loss: 0.4922, test Dice: 0.707
```

```
  Epoch  20, Loss: 0.4104, test Dice: 0.735
  Epoch  30, Loss: 0.3514, test Dice: 0.740
  Epoch  40, Loss: 0.3089, test Dice: 0.736
  trained in 26 s
```

```
fig, ax = plt.subplots(1, 2, figsize=(12, 3.8), dpi=80)
for name, h in hists.items():
    ax[0].plot(range(1, EPOCHS + 1), h["loss"], label=name)
    ax[1].plot(range(1, EPOCHS + 1), h["dice"], label=name)
ax[0].set_title("training loss (BCE)"); ax[1].set_title("Dice on the 6 held-out slices (higher is
better)")
for a in ax: a.set_xlabel("epoch"); a.grid(alpha=0.3); a.legend()
ax[1].axvline(2, color="grey", ls=":"); ax[1].text(3, 0.05, "the course stops here (epoch 2)",
fontsize=8)
plt.tight_layout(); plt.show()
```



Held-out comparison: Dice, IoU and boundary sharpness

Four measurements on the 6 test slices:

- **Dice and IoU at the standard threshold 0.5.**
- **Best-threshold Dice**: a model can draw the right structure but be *under-confident* (membrane probabilities around 0.3, never above 0.5). Trying thresholds 0.05–0.95 and keeping the best separates "wrong shape" from "wrong confidence". (Choosing the threshold on the test set flatters every model a little; in a real project you'd choose it on a separate validation set.)
- **Boundary F1** (at that best threshold): take the outline pixels of the predicted mask and of the true mask; precision = share of predicted outline pixels within 1 pixel of a true outline, recall = the reverse, F1 = their harmonic mean. **Blurry, smeared predictions score low** even when they cover roughly the right area: this is our "boundary sharpness" number.
- **Contrast**: mean predicted probability on true membrane pixels minus mean on the other pixels (1 = perfect separation, 0 = can't tell them apart).

For reference, a "model" that marks **every** pixel as membrane would get Dice ≈ 2·f/(1+f), where f is the membrane fraction; we print that too, so you can see what *zero skill* looks like.

```
from scipy.ndimage import binary_dilation, binary_erosion


def boundary_f1(pred, true):
    """Outline-based F1 with 1-pixel tolerance, averaged over images. pred/true: [N,1,H,W] 0/1
tensors."""
    scores = []
    for p, t in zip(pred[:, 0].numpy().astype(bool), true[:, 0].numpy().astype(bool)):
        pb, tb = p & ~binary_erosion(p), t & ~binary_erosion(t)          # outline pixels
        if pb.sum() == 0:
```

```
            scores.append(0.0); continue
        prec = (pb & binary_dilation(tb, iterations=1)).sum() / pb.sum()
        rec = (tb & binary_dilation(pb, iterations=1)).sum() / tb.sum()
        scores.append(2 * prec * rec / (prec + rec + 1e-8))
    return float(np.mean(scores))

print(f"{'model':11s} {'params':>8s} {'time':>5s} | {'Dice@0.5':>8s} {'IoU@0.5':>7s} | {'best
thr':>8s} {'Dice':>5s} {'boundary F1':>11s} | {'contrast':>8s}")
res = {}
for name, m in models.items():
    d, i, logits, targets = evaluate(m, test_loader)
    prob = torch.sigmoid(logits)
    ths = np.arange(0.05, 0.96, 0.05)
    dices = [dice_iou(logits, targets, thr=t)[0] for t in ths]
    bt = float(ths[int(np.argmax(dices))])
    bf = boundary_f1((prob > bt).float(), targets)
    contrast = (prob[targets == 1].mean() - prob[targets == 0].mean()).item()
    res[name] = (d, i, prob, targets, bt, max(dices), bf)
    print(f"{name:11s} {sum(p.numel() for p in m.parameters()):>8,} {times[name]:>4.0f}s |
{d:8.3f} {i:7.3f} | {bt:8.2f} {max(dices):5.3f} {bf:11.3f} | {contrast:8.3f}")
f = targets.mean().item(); allm = torch.ones_like(targets)
print(f"{'all-membrane':11s} {'-':>8s} {'-':>5s} | {2*f/(1+f):8.3f} {f:7.3f} | {'-':>8s}
{2*f/(1+f):5.3f} {boundary_f1(allm, targets):11.3f} | {0:8.3f}"
      f"   <- zero-skill reference (membrane = {f:.1%} of test pixels)")
```

```
model          params  time | Dice@0.5 IoU@0.5 | best thr  Dice boundary F1 | contrast
CourseUNet     10,049   26s |    0.160   0.087 |     0.25 0.583       0.838 |    0.171
DeepNoSkip    109,433   24s |    0.249   0.142 |     0.35 0.549       0.675 |    0.188
UNet          121,529   26s |    0.736   0.582 |     0.50 0.736       0.932 |    0.469
all-membrane        -     - |    0.329   0.197 |        - 0.329       0.119 |    0.000   <- zero-
skill reference (membrane = 19.7% of test pixels)
```

```
k = 2                                                  # one held-out slice
fig, ax = plt.subplots(2, 5, figsize=(16, 6.6), dpi=70)
crop = (slice(30, 94), slice(30, 94))                  # 64x64 zoom
panels = [("test image", test_dataset[k][0].permute(1, 2, 0), None), ("ground truth", res["UNet"]
[3][k, 0], "gray")] + \
         [(f"{n}\nDice@0.5 {res[n][0]:.2f} | best-thr {res[n][5]:.2f}", res[n][2][k, 0], "gray")
for n in models]
for j, (title, im, cmap) in enumerate(panels):
    ax[0, j].imshow(im, cmap=cmap, vmin=0, vmax=1); ax[0, j].set_title(title, fontsize=10)
    ax[1, j].imshow(im[crop[0], crop[1]] if im.dim() == 2 else im[crop[0], crop[1], :],
cmap=cmap, vmin=0, vmax=1)
    ax[1, j].set_title("zoom", fontsize=9)
for a in ax.ravel(): a.axis("off")
plt.suptitle("predicted membrane probability (white = 1) on a slice the models never saw",
fontsize=11)
plt.tight_layout(); plt.show()
```



3 · Mini project: tumour segmentation prototype

The course asks for a "tumour segmentation prototype". Real tumour datasets (BraTS, LiTS, medical decathlon) are gigabytes in size and need a registration or licence, so to keep the lab self-contained we use **synthetic, MRI-like images**.

> ⚠️ **This data is fake.** Each 128×128 image is a computer-drawn "brain" (a textured ellipse with dark ventricles, blurred and noisy like a scan), and 80 % of them contain one irregular, slightly brighter "tumour" blob of random size, shape and position. It is useful for learning the *pipeline* (data → U-Net → mask → measurements); **nothing learned here says anything about real tumours.** For a real project swap in a real dataset with the same folder layout.

We save it in the same `images/` + `masks/` layout and reuse the **fixed `MedicalDataset` class unchanged**.


```
from scipy.ndimage import gaussian_filter

def fake_mri(rng, size=128, p_tumour=0.8):
    yy, xx = np.mgrid[:size, :size] / size
    cx, cy = 0.5 + rng.normal(0, 0.03), 0.5 + rng.normal(0, 0.03)
    ax_, ay_ = rng.uniform(0.33, 0.42), rng.uniform(0.38, 0.46)
    brain = ((xx - cx) / ax_) ** 2 + ((yy - cy) / ay_) ** 2 < 1
    img = np.zeros((size, size)); img[brain] = 0.45
    img += gaussian_filter(rng.normal(0, 1, (size, size)), 3) * 0.08 * brain           # tissue
texture
    for sx in (-1, 1):                                                                  # two
dark ventricles
        v = ((xx - cx - sx * 0.06) / 0.04) ** 2 + ((yy - cy) / rng.uniform(0.08, 0.12)) ** 2 < 1
        img[v] = 0.15
    mask = np.zeros((size, size), bool)
    if rng.random() < p_tumour:
        r = rng.uniform(0.04, 0.12)
        while True:                                                                     #
tumour centre inside the brain
            tx, ty = rng.uniform(0.25, 0.75), rng.uniform(0.2, 0.8)
            if ((tx - cx) / ax_) ** 2 + ((ty - cy) / ay_) ** 2 < 0.5:
                break
        ang = np.arctan2(yy - ty, xx - tx)
        wobble = 1 + 0.25 * np.sin(3 * ang + rng.uniform(0, 6)) + 0.15 * np.sin(5 * ang +
rng.uniform(0, 6))
        mask = (np.hypot(xx - tx, yy - ty) < r * wobble) & brain                        #
irregular blob
        img[mask] += rng.uniform(0.12, 0.3)                                             #
slightly brighter
    img = gaussian_filter(img, 1.0) + rng.normal(0, 0.05, img.shape)                    #
scanner blur + noise
    return (np.clip(img, 0, 1) * 255).astype(np.uint8), (mask * 255).astype(np.uint8)

import shutil
troot = os.path.join(DATA, "tumour_synthetic")
shutil.rmtree(troot, ignore_errors=True)                            # regenerate from scratch every
run
rng = np.random.default_rng(42)
for split, n in (("train", 240), ("test", 60)):
    for sub in ("images", "masks"):
        os.makedirs(os.path.join(troot, split, sub), exist_ok=True)
    for i in range(n):
        im, mk = fake_mri(rng)
        Image.fromarray(im).save(os.path.join(troot, split, "images", f"{i:03d}.png"))
        Image.fromarray(mk).save(os.path.join(troot, split, "masks", f"{i:03d}.png"))
```

```
t_train = MedicalDataset(os.path.join(troot, "train", "images"), os.path.join(troot, "train",
"masks"), augment=True)
t_test = MedicalDataset(os.path.join(troot, "test", "images"), os.path.join(troot, "test",
"masks"))
print("synthetic tumour set: train", len(t_train), "| test", len(t_test))
fig, ax = plt.subplots(2, 6, figsize=(14, 4.8), dpi=70)
for j in range(6):
    im, mk = t_test[j]
    ax[0, j].imshow(im[0], cmap="gray"); ax[1, j].imshow(mk[0], cmap="gray")
    ax[0, j].set_title(f"synthetic scan {j}", fontsize=9); ax[1, j].set_title(f"tumour mask
({int(mk.sum())} px)", fontsize=9)
for a in ax.ravel(): a.axis("off")
plt.tight_layout(); plt.show()
```

```
synthetic tumour set: train 240 | test 60
```




```
train_loader = DataLoader(t_train, batch_size=16, shuffle=True)        # train() above uses the
global train_loader
t_test_loader = DataLoader(t_test, batch_size=60, shuffle=False)

torch.manual_seed(0); random.seed(0)
tumour_model = UNet()
criterion = nn.BCEWithLogitsLoss()
optimizer = torch.optim.Adam(tumour_model.parameters(), lr=0.001)
t0 = time.time()
tumour_hist = []
for epoch in range(1, 9):
    tumour_model.train(); running = 0.0
    for images, masks in train_loader:
        optimizer.zero_grad()
        loss = criterion(tumour_model(images), masks)
        loss.backward(); optimizer.step(); running += loss.item()
    d, i, _, _ = evaluate(tumour_model, t_test_loader)
    tumour_hist.append((running / len(train_loader), d))
    print(f"Epoch {epoch:2d}, Loss: {running/len(train_loader):.4f}, test Dice: {d:.3f}")
print(f"trained in {time.time()-t0:.0f} s")
```


```
Epoch  1, Loss: 0.7090, test Dice: 0.000
Epoch  2, Loss: 0.5722, test Dice: 0.000
Epoch  3, Loss: 0.5220, test Dice: 0.761
Epoch  4, Loss: 0.4887, test Dice: 0.818
Epoch  5, Loss: 0.4631, test Dice: 0.842
Epoch  6, Loss: 0.4387, test Dice: 0.845
Epoch  7, Loss: 0.4139, test Dice: 0.861
Epoch  8, Loss: 0.3894, test Dice: 0.861
trained in 37 s
```

```
# The course's visualisation, done on the TEST set, in eval mode, with a 0.5 threshold, plus per-
scan numbers
d, i, logits, targets = evaluate(tumour_model, t_test_loader)
preds = torch.sigmoid(logits)
binary = (preds > 0.5).float()
print(f"pixel-level on {len(t_test)} held-out synthetic scans: Dice {d:.3f}, IoU {i:.3f}")
```

```
true_area = targets.sum((1, 2, 3)); pred_area = binary.sum((1, 2, 3))
has_t, said_t = true_area > 0, pred_area > 20                    # "tumour present" if > 20
predicted pixels
tp = int((has_t & said_t).sum()); tn = int((~has_t & ~said_t).sum())
fp = int((~has_t & said_t).sum()); fn = int((has_t & ~said_t).sum())
print(f"scan-level 'is there a tumour?': {tp} TP, {tn} TN, {fp} FP, {fn} FN  -> accuracy
{(tp+tn)/len(t_test):.0%}")
rel = ((pred_area - true_area).abs() / true_area.clamp(min=1))[has_t]
print(f"tumour area error on scans with a tumour: median {rel.median():.1%}, 90th percentile
{rel.quantile(0.9):.1%}")

fig, axs = plt.subplots(4, 4, figsize=(11, 11), dpi=60)
for row, k in enumerate([0, 1, 2, 3]):
    per = dice_iou(logits[k:k+1], targets[k:k+1])[0] if targets[k].sum() > 0 else float("nan")
    axs[row, 0].imshow(t_test[k][0].permute(1, 2, 0)); axs[row, 0].set_title('Original Image',
fontsize=9)
    axs[row, 1].imshow(targets[k][0], cmap='gray'); axs[row, 1].set_title('Ground Truth Mask',
fontsize=9)
    axs[row, 2].imshow(preds[k][0], cmap='gray', vmin=0, vmax=1); axs[row,
2].set_title('Predicted probability', fontsize=9)
    over = t_test[k][0].permute(1, 2, 0).numpy().copy()
    over[binary[k, 0].bool().numpy()] = 0.6 * over[binary[k, 0].bool().numpy()] + 0.4 *
np.array([1, 0, 0])
    axs[row, 3].imshow(over); axs[row, 3].contour(targets[k][0], levels=[0.5], colors="lime",
linewidths=1)
    axs[row, 3].set_title(f"pred > 0.5 (red) vs truth (green)\nDice {per:.2f}", fontsize=9)
for a in axs.ravel(): a.axis("off")
plt.tight_layout(); plt.show()
```

```
pixel-level on 60 held-out synthetic scans: Dice 0.861, IoU 0.756
scan-level 'is there a tumour?': 51 TP, 8 TN, 0 FP, 1 FN  -> accuracy 98%
tumour area error on scans with a tumour: median 11.3%, 90th percentile 32.3%
```



🔧 What we changed from the course notebook, and why

Course code	Problem	Fix here
`./medical/train/images` placeholder	no data	ISBI-2012 EM membrane slices (the U-Net paper's dataset), arranged in the course's folder layout, 24 train / 6 test
`mask = self.transform(mask)` with `Resize((128,128))`	bilinear resize creates **non-binary mask values** on every edge	separate mask transform: `InterpolationMode.NEAREST` + `> 0.5`
`os.listdir(...)`	arbitrary file order	`sorted(...)`
no augmentation	24 images is very little data	random flips/90° rotations applied **identically** to image and mask

Course code	Problem	Fix here
`class UNet` = 1 conv + pool + 1 transposed conv	**not a U-Net**: no skip connections, one level, 4×4-pixel view	kept as `CourseUNet` for comparison; added a real 4-level `UNet` with skip connections, plus `DeepNoSkip` to isolate the skips' effect
2 epochs	12 weight updates, far from converged	40 epochs, with the curve shown
evaluation with `next(iter(train_loader))`	judges the model on images it trained on	separate **test** split; Dice/IoU on it
no `model.eval()` / `torch.no_grad()`	BatchNorm would use batch statistics; gradients tracked for nothing	both added in `evaluate()`
shows `sigmoid` output only	a probability map isn't a mask	also `> 0.5`, overlays, Dice per scan, tumour-present accuracy and area error
"tumour" prototype on the same data	no tumour data	clearly labelled **synthetic** MRI-like tumour set

Results, honestly

Measured in the run above: 24 training and **6 held-out** EM slices at 128×128, 40 epochs each, same loss, optimiser and augmentation for all three models.

Model	Parameters	Dice @ 0.5	IoU @ 0.5	Best-threshold Dice	Boundary F1	Contrast
course "U-Net" (1 level, no skips)	10,049	0.160	0.087	0.583 (thr 0.25)	0.838	0.171
DeepNoSkip (4 levels, no skips)	109,433	0.249	0.142	0.549 (thr 0.35)	0.675	0.188
real U-Net (4 levels + skips)	121,529	**0.736**	**0.582**	0.736 (thr 0.50)	**0.932**	**0.469**
zero-skill "everything is membrane"	–	0.329	0.197	–	0.119	0

What this shows:

- **At the standard 0.5 threshold, both models without skip connections score *below* the zero-skill reference** (0.160 and 0.249 vs 0.329). They are **under-confident**: their membrane probabilities rarely pass 0.5. Their best-threshold Dice (0.58 and 0.55) shows they pick up some structure, but their low contrast (≈ 0.17–0.19) means they barely separate membrane from background.
- **The real U-Net is the only model that clearly works**: Dice 0.736 at the normal threshold, more than twice the contrast, and the sharpest outlines (boundary F1 0.932).
- **Depth alone did not help.** DeepNoSkip has almost as many parameters as the U-Net and sees much more context, yet it did no better than the tiny course model, and its outlines were

blurrier (boundary F1 0.675 vs 0.838). Its test Dice also jumped around during training (0.33 → 0.00 → 0.25). What made the difference is the **skip connections**, which carry the fine detail lost by pooling straight to the decoder. That's the point of the U-Net design.

- **The course model learned slowly:** its test Dice was 0.000 for the first 20 epochs. The course's 2 epochs (12 weight updates) would show nothing at all.
- **Tumour prototype (synthetic data):** Dice **0.861**, IoU 0.756 on 60 held-out fake scans. Asked "is there a tumour?", it was right on 59 of 60 (51 found, 8 correctly empty, 0 false alarms, 1 missed). The estimated tumour area was off by a median of 11.3% (90th percentile 32.3%). **Synthetic data says nothing about real tumours**; it only shows the pipeline works.
- **Caveats:** 6 test slices is very few, so treat the numbers as a ranking, not precise values. Picking the best threshold on the test set flatters the first two models slightly (a real project would choose it on validation data). CPU timings were on a shared machine.

Common errors and how to fix them

Error	Cause	Fix
`ValueError: Target size (torch.Size([4, 1, 128, 128])) must be the same as input size (...)`	output and mask sizes differ (e.g. odd input size with pooling)	use sizes divisible by 2^(number of pools), e.g. 128, 256
`RuntimeError: Sizes of tensors must match except in dimension 1` in `torch.cat`	skip and upsampled maps differ by a pixel	same: input divisible by 16 for 4 levels (or crop/pad before `cat`)
loss goes down but mask is all black	heavy class imbalance (few foreground pixels)	train longer, use Dice loss or `pos_weight` in `BCEWithLogitsLoss`
mask looks "fuzzy" / has values like 0.3	bilinear resize of the mask	nearest-neighbour + threshold
`FileNotFoundError` for a mask	image and mask file names differ	the loader assumes identical names in both folders
image and mask don't line up after augmentation	two independent random transforms	apply the same random op to both inside `__getitem__`
very different test results each run	BatchNorm in train mode during evaluation	`model.eval()` before predicting

Try this yourself

1. Change `EPOCHS = 40` to 15: how much worse is each model? (Look at the Dice curve first.)
2. Remove `augment=True` from the membrane training set. Does the gap between train loss and test Dice grow?
3. Train at 256×256 instead of 128 (`MedicalDataset(..., size=256)`): membranes are thicker in pixels; does Dice improve? (About 4× slower.)
4. Change the threshold 0.5 to 0.3 and 0.7 inside `dice_iou`. Which threshold gives the best Dice for the membrane task?

5. Replace `BCEWithLogitsLoss` with BCE + Dice loss: `loss = bce + (1 - soft_dice)` where `soft_dice` uses `sigmoid(outputs)` directly.

Run it on Google Colab with a GPU

1. Upload the notebook, *Runtime → Change runtime type → T4 GPU*.
2. Everything it needs (`torch` , `torchvision` , `scipy` , `PIL`) is preinstalled; the data downloads from GitHub.
3. *Run all*. `device` prints `cuda` ; on a GPU you can afford `EPOCHS = 200` , `UNet(base=32)` and `size=256` .

Viva questions

1. **What is semantic segmentation?** Assigning a class to every pixel; the output is a mask the size of the image.
2. **Why is the course's `UNet` not a real U-Net?** It has one down/up level and no skip connections; a U-Net has several levels and concatenates encoder features into the decoder at each level.
3. **What do skip connections give U-Net?** The decoder gets the encoder's high-resolution features directly, so it can place boundaries precisely instead of guessing them from a coarse map.
4. **What does `ConvTranspose2d(64, 32, 2, stride=2)` do?** Learned upsampling: doubles height and width, turns 64 channels into 32.
5. **What does the final `Conv2d(32, 1, 1)` do?** A 1×1 convolution that combines the channels into one logit per pixel.
6. **Why `BCEWithLogitsLoss` rather than `Sigmoid` + `BCELoss` ?** It combines both in a numerically stable way; the model outputs raw logits.
7. **How do you turn the output into a mask?** `torch.sigmoid(logits) > 0.5` .
8. **Define Dice and IoU.** Dice = $2|A \cap B| / (|A|+|B|)$; IoU = $|A \cap B| / |A \cup B|$; Dice = $2 \cdot IoU/(1+IoU)$, so Dice ≥ IoU.
9. **Why not pixel accuracy?** With 22 % membrane (or 1 % tumour), predicting "all background" already scores 78 % (or 99 %) accuracy; Dice/IoU focus on the foreground.
10. **Why resize masks with nearest-neighbour?** Bilinear interpolation averages labels and creates values that are not valid classes.
11. **Why `model.eval()` at test time?** BatchNorm switches to its stored running statistics (and dropout turns off), so predictions don't depend on the batch.
12. **Why is U-Net popular in medicine?** It works with very little training data (heavy augmentation + skip connections) and gives precise boundaries, which matter for measuring organs and tumours.
13. **Why did we hold out test slices?** A model can memorise training images; only unseen images show whether it generalises.
14. **What did the `DeepNoSkip` experiment show?** See "Results, honestly": it separates the benefit of depth (context) from the benefit of skip connections (detail).

Lab 5 · Instance segmentation with Mask R-CNN: people in a crowd

Course lab: `CV-Week3-Lecture5.ipynb` (in `course-files/labs/`) **Theory partner:** notes/05_segmentation_fcn_unet_mask_rcnn.md (Mask R-CNN section) and notebooks/05_segmentation_fcn_unet_mask_rcnn.ipynb. The COCO loader is explained in detail in Lab 3.

Course cell	What it does	What you will see here
Setup: COCO loader (for segmentation)	`CocoDetection` with polygon annotations	real COCO images with their **instance masks** decoded from polygons
Exercise: segment multiple objects	pretrained Mask R-CNN on a batch	the output format (`boxes` , `labels` , `scores` , `masks`), coloured instance masks, and a mask precision/recall measurement on 128 labelled images
Mini project: people in crowd images	keep the `person` masks	every person in a distinct colour, a **people count**, what the course's 224×224 resize does to that count, and a score-threshold sweep

What you will learn: what an instance mask is, how Mask R-CNN's soft masks become binary masks, why a score threshold matters, how to count objects reliably, and how to fail gracefully when nothing is found.

Run time: about 8–10 minutes on the shared CPU this was built on (evaluating masks on all 128 images took 361 s); an idle laptop will be faster. On Colab with a GPU: under a minute.

0 · Theory in 60 seconds

- **Instance segmentation** = detection + a pixel mask **per object**. Two people standing together give **two** masks (semantic segmentation would give one "person" blob).
- **Mask R-CNN** = **Faster R-CNN + a third head**. For each proposed region (RoI) it predicts a class, a refined box **and** a small 28×28 mask. **RoI Align** samples the feature map at exact (non-rounded) positions so the small mask lines up with the object. The mask is then resized and pasted into the box.
- **torchvision's output** (one dict per image): `boxes [N,4]` , `labels [N]` (COCO ids, **1 = person**), `scores [N]` , and `masks [N,1,H,W]` : **soft probabilities 0–1 at the full image size**, so you threshold them with `> 0.5` .
- **YOLOv8-seg** (the fallback here) is a one-stage instance segmenter: it predicts a set of shared "prototype" masks for the whole image plus, per detected object, coefficients that mix the prototypes into that object's mask (the YOLACT idea). Same kind of output, much faster.

> **Two routes for the downloads.** The course uses torchvision's `maskrcnn_resnet50_fpn` (weights from `download.pytorch.org`) and full COCO (`images.cocodataset.org`). With normal internet this notebook uses both. The machine that ran it **could not reach those servers**, so each cell tries the

> course's route first and otherwise falls back to **Ultralytics COCO128-seg** (the first 128 COCO train2017 images with their polygon labels) and **YOLOv8n-seg**, wrapped to return exactly the torchvision dict format. Each cell prints which route ran.

```
%matplotlib inline
%config InlineBackend.figure_formats = ["jpeg"]   # photos as JPEG keep the notebook small
import os, json, time, zipfile, urllib.request
from collections import Counter
import numpy as np
import matplotlib.pyplot as plt
import cv2
from PIL import Image
import torch
import torchvision
import torchvision.transforms as transforms
import torchvision.models.detection as detection
from torchvision.datasets import CocoDetection

torch.manual_seed(0)
torch.set_num_threads(2)                        # share the CPU politely; raise on your own machine
device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
DATA = "data"; os.makedirs(DATA, exist_ok=True)
COCO_NAMES = detection.MaskRCNN_ResNet50_FPN_Weights.DEFAULT.meta["categories"]   # index = COCO id, 1 = 'person'
print("torch", torch.__version__, "| torchvision", torchvision.__version__, "| device:", device, "| COCO_NAMES[1] =", COCO_NAMES[1])

def download(url, dest):
    if not os.path.exists(dest):
        os.makedirs(os.path.dirname(dest) or ".", exist_ok=True)
        urllib.request.urlretrieve(url, dest)
    return dest
```

```
torch 2.14.1+cu130 | torchvision 0.29.1+cu130 | device: cpu | COCO_NAMES[1] = person
```

1 · Setup: COCO loader for segmentation

In COCO, each annotation has, besides `bbox` and `category_id`, a **`segmentation`** field: a polygon `[[x1, y1, x2, y2, …]]` tracing the object's outline (or, for crowds, a run-length-encoded mask). `pycocotools`' `coco.annToMask(ann)` turns it into an H×W 0/1 array.

On your machine (course route): put `val2017/` and `annotations/instances_val2017.json` under `data/coco_data/` (see Lab 3); the cell below picks them up. **Fallback (here):** COCO128-seg's polygon labels converted into a COCO-format JSON.

```
from ultralytics.data.converter import coco80_to_coco91_class
coco_root = os.path.join(DATA, "coco_data")
official_ann = os.path.join(coco_root, "annotations", "instances_val2017.json")

def build_coco128_seg():
    z = download("https://github.com/ultralytics/assets/releases/download/v0.0.0/coco128-seg.zip", os.path.join(DATA, "coco128-seg.zip"))
    if not os.path.isdir(os.path.join(DATA, "coco128-seg")):
        zipfile.ZipFile(z).extractall(DATA)
    img_dir = os.path.join(DATA, "coco128-seg", "images", "train2017")
    ann_file = os.path.join(coco_root, "annotations", "instances_coco128_seg.json")
    if not os.path.exists(ann_file):
        to91 = coco80_to_coco91_class(); images, anns = [], []
        for f in sorted(os.listdir(img_dir)):
            w, h = Image.open(os.path.join(img_dir, f)).size
```

```
            img_id = int(f.split(".")[0])
            images.append({"id": img_id, "file_name": f, "width": w, "height": h})
            lbl = os.path.join(DATA, "coco128-seg", "labels", "train2017", f.replace(".jpg",
".txt"))
            for line in (open(lbl).read().split("\n") if os.path.exists(lbl) else []):
                v = line.split()
                if len(v) < 7:
                    continue
                xy = np.array(v[1:], float).reshape(-1, 2) * [w, h]           # normalised
polygon -> pixels
                x1, y1 = xy.min(0); x2, y2 = xy.max(0)
                area = 0.5 * abs(np.dot(xy[:, 0], np.roll(xy[:, 1], 1)) - np.dot(xy[:, 1],
np.roll(xy[:, 0], 1)))  # shoelace formula
                anns.append({"id": len(anns) + 1, "image_id": img_id, "category_id":
to91[int(v[0])], "iscrowd": 0,
                             "segmentation": [xy.round(2).ravel().tolist()], "bbox": [x1, y1, x2
- x1, y2 - y1], "area": area})
        cats = [{"id": i, "name": n} for i, n in enumerate(COCO_NAMES) if n not in
("__background__", "N/A")]
        os.makedirs(os.path.dirname(ann_file), exist_ok=True)
        json.dump({"images": images, "annotations": anns, "categories": cats}, open(ann_file,
"w"))
    return img_dir, ann_file

if os.path.exists(official_ann):
    img_dir, ann_file = os.path.join(coco_root, "val2017"), official_ann
    print("ROUTE: official COCO val2017")
else:
    img_dir, ann_file = build_coco128_seg()
    print("ROUTE: fallback, COCO128-seg (first 128 images of COCO train2017, polygon labels) as
COCO JSON")


# Course loader: Resize((224,224)) + default collate. Same two bugs as in Lab 3:
course_set = CocoDetection(root=img_dir, annFile=ann_file,
                           transform=transforms.Compose([transforms.Resize((224,224)),
transforms.ToTensor()]))
try:
    next(iter(torch.utils.data.DataLoader(course_set, batch_size=2, shuffle=True)))
    print("course loader: this batch happened to work (both images had the same number of
objects)")
except Exception as e:
    print("course loader ->", type(e).__name__ + ":", str(e)[:100])

# Fixed loader: no resize (Mask R-CNN resizes internally), tuple collate
trainset = CocoDetection(root=img_dir, annFile=ann_file, transform=transforms.ToTensor())
trainloader = torch.utils.data.DataLoader(trainset, batch_size=2, shuffle=True,
generator=torch.Generator().manual_seed(1),
                                          collate_fn=lambda batch: tuple(zip(*batch)))
print("Loaded COCO dataset with", len(trainset), "images")
```

```
ROUTE: fallback, COCO128-seg (first 128 images of COCO train2017, polygon labels) as COCO JSON
loading annotations into memory...
Done (t=0.01s)
creating index...
index created!
course loader -> RuntimeError: each element in list of batch should be of equal size
loading annotations into memory...
Done (t=0.01s)
creating index...
index created!
Loaded COCO dataset with 128 images
```

```
# How a polygon becomes a mask
img, anns = trainset[0]
coco = trainset.coco
fig, ax = plt.subplots(1, 3, figsize=(13, 3.8), dpi=70)
ax[0].imshow(img.permute(1, 2, 0)); ax[0].set_title("COCO image")
ax[1].imshow(img.permute(1, 2, 0))
for a in anns:
```

```
    poly = np.array(a["segmentation"][0]).reshape(-1, 2)
    ax[1].plot(*np.vstack([poly, poly[:1]]).T, lw=1.5)
ax[1].set_title("polygons from the JSON")
inst = np.zeros(img.shape[1:], int)
for k, a in enumerate(anns, 1):
    inst[coco.annToMask(a) > 0] = k                                  # polygon -> HxW 0/1 mask
ax[2].imshow(img.permute(1, 2, 0) * 0.35)
ax[2].imshow(np.ma.masked_equal(inst, 0), cmap="tab10", interpolation="nearest", vmin=1, vmax=10)
ax[2].set_title("annToMask: one colour per object")
for a in ax: a.axis("off")
plt.tight_layout(); plt.show()
print("objects:", [COCO_NAMES[a["category_id"]] for a in anns])
```




```
objects: ['bowl', 'bowl', 'broccoli', 'bowl', 'orange', 'orange', 'orange', 'orange']
```

2 · Exercise: segment multiple objects with Mask R-CNN

The course's `maskrcnn_resnet50_fpn(pretrained=True)` becomes `weights="DEFAULT"` (COCO-trained, 37.9 box mAP / 34.6 mask mAP, 44.4 M parameters, ~170 MB). If the download fails we use YOLOv8n-seg through a small wrapper that returns the same dict, including `masks` as `[N, 1, H, W]` at the full image size.

```
from ultralytics import YOLO

def yolo_seg_as_torchvision(yolo, conf=0.05, iou=0.5):
    """Make an Ultralytics *-seg model look like torchvision's Mask R-CNN (same inputs, same
output dict)."""
    to91 = coco80_to_coco91_class()
    def run(images):
        outs = []
        for img in images:                                                  # [3,H,W] float 0..1
RGB
            arr = (img.permute(1, 2, 0).cpu().numpy() * 255).astype(np.uint8)[:, :, ::-1]
            r = yolo.predict(arr, conf=conf, iou=iou, retina_masks=True, verbose=False)[0]   #
retina_masks: full-size masks
            H, W = arr.shape[:2]
            masks = r.masks.data.float().unsqueeze(1).cpu() if r.masks is not None else
torch.zeros(0, 1, H, W)
            outs.append({"boxes": r.boxes.xyxy.cpu(), "scores": r.boxes.conf.cpu(), "masks":
masks,
                         "labels": torch.tensor([to91[int(c)] for c in r.boxes.cls],
dtype=torch.int64)})
        return outs
    return run

try:
    model = detection.maskrcnn_resnet50_fpn(weights="DEFAULT")        # FIX: weights= instead of
pretrained=True
    model.eval(); model.to(device)
    segmenter, SEG_NAME = model, "Mask R-CNN R50-FPN"
    print("ROUTE: course model, Mask R-CNN with COCO weights")
```

```
except Exception as e:
    print("Mask R-CNN weights unavailable ->", type(e).__name__, str(e)[:90])
    w = download("https://github.com/ultralytics/assets/releases/download/v8.2.0/yolov8n-seg.pt",
os.path.join(DATA, "yolov8n-seg.pt"))
    yolo_seg = YOLO(w)
    segmenter, SEG_NAME = yolo_seg_as_torchvision(yolo_seg), "YOLOv8n-seg (fallback)"
    print("ROUTE: fallback, YOLOv8n-seg with the same output format")
```

```
Downloading: "https://download.pytorch.org/models/maskrcnn_resnet50_fpn_coco-bf2d0c1e.pth" to /ro
ot/.cache/torch/hub/checkpoints/maskrcnn_resnet50_fpn_coco-bf2d0c1e.pth
Mask R-CNN weights unavailable -> URLError <urlopen error Tunnel connection failed: 403 Forbidden
>
ROUTE: fallback, YOLOv8n-seg with the same output format
```

```
images, targets = next(iter(trainloader))
with torch.no_grad():                                                    # FIX: inference only
    outputs = segmenter([img.to(device) for img in images])

SCORE_THRESH = 0.5
print("Segmenter:", SEG_NAME)
print("Segmented objects in batch:")
for i, (output, tgt) in enumerate(zip(outputs, targets)):
    keep = output["scores"] > SCORE_THRESH
    print(f"Image {i}: {len(output['masks'])} masks generated, {int(keep.sum())} with score >
{SCORE_THRESH} | ground truth: {len(tgt)} objects")
o = outputs[0]
print("\nmasks tensor:", tuple(o["masks"].shape), o["masks"].dtype, "| value range",
float(o["masks"].min()), "to", float(o["masks"].max()))
```

```
Segmenter: YOLOv8n-seg (fallback)
Segmented objects in batch:
Image 0: 19 masks generated, 2 with score > 0.5 | ground truth: 8 objects
Image 1: 30 masks generated, 6 with score > 0.5 | ground truth: 16 objects

masks tensor: (19, 1, 426, 640) torch.float32 | value range 0.0 to 1.0
```

```
PALETTE = plt.cm.tab10(np.arange(10))[:, :3]                             # 10 clearly different
colours

def overlay(img, masks, alpha=0.55):
    """Paint each binary mask in its own colour on top of the image (HxWx3 float in 0..1)."""
    out = img.copy()
    for k, m in enumerate(masks):
        out[m] = (1 - alpha) * out[m] + alpha * PALETTE[k % 10]
    return out

fig, ax = plt.subplots(2, 2, figsize=(12, 8.5), dpi=60)
for i in range(2):
    im = images[i].permute(1, 2, 0).numpy()
    gt = [coco.annToMask(a).astype(bool) for a in targets[i]]
    ax[0, i].imshow(overlay(im, gt)); ax[0, i].set_title(f"ground truth: {len(gt)} instances",
fontsize=10)
    keep = outputs[i]["scores"] > SCORE_THRESH
    pm = (outputs[i]["masks"][keep, 0] > 0.5).numpy()                    # soft mask -> binary
mask
    ax[1, i].imshow(overlay(im, pm))
    for b, l, s in zip(outputs[i]["boxes"][keep], outputs[i]["labels"][keep], outputs[i]
["scores"][keep]):
        ax[1, i].text(float(b[0]), float(b[1]) - 3, f"{COCO_NAMES[int(l)]} {s:.2f}", fontsize=7,
color="white",
                      bbox=dict(fc="black", alpha=0.5, pad=1, ec="none"))
    ax[1, i].set_title(f"{SEG_NAME.split(' (')[0]}, score > {SCORE_THRESH}: {len(pm)} instances",
fontsize=10)
    print(f"image {i}: predicted {dict(Counter(COCO_NAMES[int(l)] for l in outputs[i]['labels']
[keep]))}")
    print(f"         true      {dict(Counter(COCO_NAMES[a['category_id']] for a in
targets[i]))}")
for a in ax.ravel(): a.axis("off")
plt.tight_layout(); plt.show()
```

```
image 0: predicted {'dog': 1, 'bicycle': 1}
         true      {'dog': 1, 'bicycle': 1, 'person': 6}
image 1: predicted {'person': 5, 'baseball glove': 1}
         true      {'sports ball': 1, 'person': 13, 'baseball bat': 1, 'baseball glove': 1}
```



How good are the masks? Mask precision and recall on all labelled images

Same idea as Lab 3's box evaluation, but the overlap is measured between **masks** (pixel IoU): a predicted mask counts as correct if it overlaps an unmatched true mask of the same class with IoU ≥ 0.5.

> COCO128 images are from COCO **train**2017, which the pretrained models saw during training, so these numbers are optimistic.

```
def mask_match(pm, pl, ps, gm, gl, thr=0.5):
    correct = np.zeros(len(pm), bool)
    if len(pm) == 0 or len(gm) == 0:
        return correct
    P = pm.reshape(len(pm), -1).astype(np.float32); G = gm.reshape(len(gm),
-1).astype(np.float32)
    inter = P @ G.T; union = P.sum(1)[:, None] + G.sum(1)[None, :] - inter
    ious = inter / np.maximum(union, 1); used = np.zeros(len(gm), bool)
    for p in np.argsort(-ps):
        cand = (gl == pl[p]) & ~used & (ious[p] >= thr)
        if cand.any():
            g = np.where(cand)[0][ious[p][cand].argmax()]; used[g] = True; correct[p] = True
    return correct

# Fallback model: ask YOLO for score > 0.5 directly (identical result, much faster than computing
then discarding low scores)
eval_segmenter = yolo_seg_as_torchvision(yolo_seg, conf=SCORE_THRESH) if
```

```
SEG_NAME.startswith("YOLO") else segmenter
t0 = time.time(); n_true = 0; n_pred = 0; n_ok = 0; per_class = Counter(); per_class_true =
Counter()
for k in range(len(trainset)):
    img, anns = trainset[k]
    with torch.no_grad():
        o = eval_segmenter([img.to(device)])[0]
    keep = o["scores"] > SCORE_THRESH
    pm = (o["masks"][keep, 0] > 0.5).cpu().numpy(); pl = o["labels"][keep].numpy(); ps =
o["scores"][keep].numpy()
    gm = np.array([coco.annToMask(a) for a in anns]).astype(bool) if anns else np.zeros((0,) +
img.shape[1:], bool)
    gl = np.array([a["category_id"] for a in anns])
    ok = mask_match(pm, pl, ps, gm, gl)
    n_true += len(gl); n_pred += len(pl); n_ok += int(ok.sum())
    per_class.update(pl[ok].tolist()); per_class_true.update(gl.tolist())
print(f"{len(trainset)} images in {time.time()-t0:.0f} s | {n_true} true instances, {n_pred}
predicted (score > {SCORE_THRESH})")
print(f"mask precision {n_ok/n_pred:.2f} | mask recall {n_ok/n_true:.2f}  (IoU >= 0.5, same
class)")
print("recall for the most common classes:",
      {COCO_NAMES[c]: f"{per_class[c]}/{n} = {per_class[c]/n:.2f}" for c, n in
per_class_true.most_common(5)})
```

```
128 images in 361 s | 929 true instances, 361 predicted (score > 0.5)
mask precision 0.86 | mask recall 0.33  (IoU >= 0.5, same class)
recall for the most common classes: {'person': '120/254 = 0.47', 'car': '4/46 = 0.09', 'cup': '7/
36 = 0.19', 'chair': '6/35 = 0.17', 'book': '0/29 = 0.00'}
```

3 · Mini project: people segmentation in crowd images

The course's cell resizes the crowd photo to 224×224, runs Mask R-CNN, keeps masks with `label == 1` (person) and shows `person_masks[0]`. Problems:

1. **`Resize((224,224))`** squashes the photo (a 4:3 image becomes 1:1) and throws away ~90 % of the pixels. Mask R-CNN resizes internally anyway (shorter side → 800 px), so a small far-away person who was 20 px tall becomes 8 px: **people disappear**. Also the masks come back at 224×224 and no longer line up with the original image.
2. **No score threshold**: every person-box above 0.05 is kept, so the "count" includes junk.
3. **Masks are soft probabilities**: Mask R-CNN's `masks` are 0–1 values; `> 0.5` makes them binary.
4. **`person_masks[0]` crashes** with `IndexError` when no person is found, and shows only **one** person even when there are twenty.
5. **No `torch.no_grad()`**: gradients are tracked for nothing.

Our crowd images: a frame from OpenCV's `vtest.avi` sample (a campus scene with walking pedestrians, used in OpenCV's people-tracking demos) and the COCO128 image with the most labelled people (so we know the true count).

```
vid = download("https://raw.githubusercontent.com/opencv/opencv/4.x/samples/data/vtest.avi",
os.path.join(DATA, "vtest.avi"))
cap = cv2.VideoCapture(vid); cap.set(cv2.CAP_PROP_POS_FRAMES, 720); ok, frame = cap.read();
cap.release()
crowd_path = os.path.join(DATA, "crowd_vtest.jpg"); cv2.imwrite(crowd_path, frame)

n_people = [sum(a["category_id"] == 1 for a in trainset.coco.imgToAnns[i]) for i in trainset.ids]
k_crowd = int(np.argmax(n_people)); coco_crowd_path = os.path.join(img_dir,
trainset.coco.imgs[trainset.ids[k_crowd]]["file_name"])
print(f"vtest.avi frame 720: {frame.shape[1]}x{frame.shape[0]}")
```


```
print(f"most crowded COCO128 image: {os.path.basename(coco_crowd_path)} with {n_people[k_crowd]} labelled people")
```

```
vtest.avi frame 720: 768x576
most crowded COCO128 image: 000000000257.jpg with 13 labelled people
```

```
_cache = {}
def people_masks(image_pil, score_thresh=0.5, resize_224=False):
    """Fixed version of the course's mini project. Returns binary person masks, scores and boxes."""
    key = (id(image_pil), resize_224)
    if key not in _cache:                                              # run the model once per image, reuse for every threshold
        tf = transforms.Compose([transforms.Resize((224,224)), transforms.ToTensor()]) if resize_224 else transforms.ToTensor()
        input_tensor = tf(image_pil).to(device)
        with torch.no_grad():                                          # FIX
            _cache[key] = segmenter([input_tensor])[0]
    output = _cache[key]
    keep = (output["labels"] == 1) & (output["scores"] > score_thresh)    # COCO class id 1 = person, FIX: threshold
    masks = (output["masks"][keep, 0] > 0.5).cpu().numpy()                # FIX: soft -> binary
    return masks, output["scores"][keep].cpu().numpy(), output["boxes"][keep].cpu().numpy()

crowd_images = {"vtest frame": Image.open(crowd_path).convert("RGB"), "COCO crowd": Image.open(coco_crowd_path).convert("RGB")}
fig, ax = plt.subplots(2, 3, figsize=(16, 8.5), dpi=60)
for row, (name, crowd_image) in enumerate(crowd_images.items()):
    im = np.asarray(crowd_image) / 255.0
    masks, scores, boxes = people_masks(crowd_image)
    masks224, _, _ = people_masks(crowd_image, resize_224=True)
    ax[row, 0].imshow(crowd_image); ax[row, 0].set_title(f"{name} ({crowd_image.size[0]}x{crowd_image.size[1]})", fontsize=10)
    if len(masks) == 0:                                                # FIX: no IndexError when nobody is found
        ax[row, 1].imshow(crowd_image); ax[row, 1].set_title("No people found", fontsize=10)
    else:
        ax[row, 1].imshow(overlay(im, masks))
        for k, b in enumerate(boxes):
            ax[row, 1].text(b[0], b[1] - 2, str(k + 1), color="white", fontsize=8, bbox=dict(fc=PALETTE[k % 10], pad=1, ec="none"))
        ax[row, 1].set_title(f"fixed: {len(masks)} people (score > 0.5), one colour each", fontsize=10)
    ax[row, 2].imshow(crowd_image.resize((224, 224)))
    if len(masks224):
        ax[row, 2].imshow(np.ma.masked_where(~masks224.any(0), masks224.any(0)), cmap="autumn", alpha=0.6)
    ax[row, 2].set_title(f"course's 224x224 squash: {len(masks224)} people", fontsize=10)
    print(f"{name}: {len(masks)} people at full size vs {len(masks224)} after the course's Resize((224,224))"
          + (f" | true count {n_people[k_crowd]}" if name == "COCO crowd" else ""))
for a in ax.ravel(): a.axis("off")
plt.tight_layout(); plt.show()
```

```
vtest frame: 8 people at full size vs 8 after the course's Resize((224,224))
COCO crowd: 4 people at full size vs 3 after the course's Resize((224,224)) | true count 13
```



Instance vs semantic: why separate masks matter for counting

If we merged all person masks into one "person" region (what semantic segmentation gives you), touching people would melt into one blob and you could not count them. Counting connected blobs in the merged mask shows the difference:

```
for name, crowd_image in crowd_images.items():
    masks, _, _ = people_masks(crowd_image)
    union = masks.any(0).astype(np.uint8) if len(masks) else np.zeros(crowd_image.size[::-1],
np.uint8)
    n_blobs = cv2.connectedComponents(union)[0] - 1                    # minus the background
component
    print(f"{name}: {len(masks)} instance masks  ->  {n_blobs} connected blobs if merged into one
semantic mask")
```


```
vtest frame: 8 instance masks  ->  8 connected blobs if merged into one semantic mask
COCO crowd: 4 instance masks  ->  3 connected blobs if merged into one semantic mask
```

Score-threshold sweep: how many "people" at each threshold?

```
ths = [0.05, 0.1, 0.25, 0.4, 0.5, 0.6, 0.75, 0.9]
print(f"{'threshold':>9} | " + " | ".join(f"{n:>11s}" for n in crowd_images))
counts = {n: [] for n in crowd_images}
for t in ths:
    for n, im in crowd_images.items():
        counts[n].append(len(people_masks(im, score_thresh=t)[0]))
    print(f"{t:9.2f} | " + " | ".join(f"{counts[n][-1]:11d}" for n in crowd_images))
fig, a = plt.subplots(figsize=(6, 3.2), dpi=80)
for n in crowd_images:
    a.plot(ths, counts[n], "o-", label=n)
a.axhline(n_people[k_crowd], color="C1", ls=":", label="COCO crowd: labelled count")
a.set_xlabel("score threshold"); a.set_ylabel("people counted"); a.legend(fontsize=8);
a.grid(alpha=0.3)
plt.tight_layout(); plt.show()
```

```
threshold | vtest frame |  COCO crowd
     0.05 |          11 |           26
     0.10 |           9 |           19
```

```
0.25 |           9 |          14
0.40 |           8 |          11
0.50 |           8 |           4
0.60 |           8 |           3
0.75 |           6 |           0
0.90 |           0 |           0
```



🔧 What we changed from the course notebook, and why

Course code	Problem	Fix here
`Resize((224,224))` in the COCO loader + default collate	boxes/polygons don't follow the resize; ragged targets crash the batch	`ToTensor()` only + `collate_fn=lambda b: tuple(zip(*b))` (see Lab 3)
`train2017` (18 GB)	huge, and the model trained on it	`val2017` on your machine; COCO128-seg fallback here
`maskrcnn_resnet50_fpn(pretrained=True)`	deprecated argument	`weights="DEFAULT"`
`outputs = model(images)`	gradients tracked	`torch.no_grad()`
`print(len(output['masks']))`	counts every mask down to score 0.05	also count `scores > 0.5` ; measure mask precision/recall against the ground truth
crowd image → `Resize((224,224))`	squashes the aspect ratio, shrinks people below detectable size, masks no longer fit the original	pass the full-size image; the model resizes internally
`if label.item() == 1` only	no score threshold	`(labels == 1) & (scores > 0.5)`
`mask.squeeze()` used as is	soft probabilities, not a mask	`> 0.5`

Course code	Problem	Fix here
`person_masks[0]`	`IndexError` when nobody is found; shows only one person	handle the empty case; draw **all** people in distinct colours with a count
`'crowd.jpg'` placeholder	file does not exist	a frame of OpenCV's `vtest.avi` and the most crowded COCO128 image

Results, honestly

What this run (fallback route: COCO128-seg + YOLOv8n-seg, because Mask R-CNN's weights could not be downloaded) actually showed:

- **The course's loader crashed** on its first batch (`RuntimeError: each element in list of batch should be of equal size`), exactly as in Lab 3; the fixed loader works and `annToMask` turns the JSON polygons into clean per-object masks.
- **Exercise batch:** the model returned 19 and 30 masks for the two images, but only 2 and 6 had a score above 0.5. It segmented the dog, the bicycle, the batter and the catcher well, but **missed all 6 small, blurred people** in the background of the street photo and most of the crowd in the stadium stands. The returned `masks` tensor is `[N, 1, H, W]` at the full image size (426×640 here).
- **Mask quality over all 128 images** (score > 0.5, mask IoU ≥ 0.5): precision **0.86**, recall **0.33**. So when it draws a mask it is usually right, but it misses two thirds of the labelled objects, mostly small ones: recall was 0.47 for people but 0.09 for cars, 0.19 for cups and 0.00 for books. That is the price of the smallest (nano) model, and these are training-set images, so honest val2017 numbers would be lower still.
- **People counting:** on the `vtest.avi` frame it found **8 people** (one colour each), which matches what you can count by eye. On the most crowded COCO128 image (13 labelled people) it found only **4** at score > 0.5. The **threshold sweep** shows why the threshold must be chosen per model: on that image the count goes 26 → 19 → 14 → 11 → 4 as the threshold rises from 0.05 to 0.5. At 0.25 (YOLO's own default) it reports 14, close to the true 13 (though a count being close does not prove every mask is a real person). The vtest count is stable at 8 between 0.4 and 0.6.
- **The course's 224×224 squash:** here it cost less than expected: still 8 people on vtest, 3 instead of 4 on the COCO image. (YOLO scales the 224×224 input back up to 640, so a fair amount survives.) The bigger problem is visible in the right-hand column: the image is distorted, and masks computed on it no longer line up with the original photo. With Mask R-CNN, which upsamples to 800 px, small people suffer in the same way.
- **Instance vs semantic:** on the COCO crowd image the 4 person masks merge into 3 blobs once combined into one semantic mask, because two people overlap. Counting blobs would undercount; instance masks don't.

Common errors and how to fix them

Error	Cause	Fix
`IndexError: list index out of range` at `person_masks[0]`	no person above threshold	check `len(person_masks) == 0` first
masks look like blurry clouds	plotted the soft probabilities	threshold: `mask > 0.5`
masks don't line up with the photo	resized the input before the model	give the model the original image
`ModuleNotFoundError: pycocotools`	needed by `CocoDetection` / `annToMask`	`pip install pycocotools`
`RuntimeError: each element in list of batch should be of equal size`	default collate	`collate_fn=lambda b: tuple(zip(*b))`
very slow on CPU (several s/image)	Mask R-CNN is a large two-stage model at ~800 px	use a GPU, fewer images, or a lighter model such as YOLOv8n-seg
`CUDA out of memory`	`masks` are `[N,1,H,W]` full-size floats	process one image at a time, move masks to CPU, threshold early

Try this yourself

1. Change `SCORE_THRESH` in section 2 to 0.3 and 0.8 and re-run the mask evaluation: how do precision and recall move?
2. Count **cars** instead of people (COCO id 3) on `vtest` frames or your own street photo.
3. Run `people_masks` on every 50th frame of `vtest.avi` and plot the people count over time.
4. Compute each person's mask area in pixels: who is closest to the camera?
5. Swap `yolov8n-seg.pt` for `yolov8s-seg.pt` (or, with internet, compare with Mask R-CNN) and compare people counts and speed.

Run it on Google Colab with a GPU

1. Upload the notebook, *Runtime → Change runtime type → T4 GPU*.
2. First cell: `!pip install ultralytics pycocotools`.
3. *Run all*. Mask R-CNN's weights download automatically and the course route runs; for real COCO val2017 data use the `wget` commands from Lab 3.

Viva questions

1. **Semantic vs instance segmentation?** Semantic labels each pixel with a class; instance also separates individual objects of the same class (person #1, person #2).
2. **How does Mask R-CNN extend Faster R-CNN?** It adds a third head that predicts a small binary mask for every region, in parallel with the class and box heads.

3. **What is RoI Align and why is it needed?** It samples features at exact fractional positions (bilinear interpolation) instead of rounding like RoI Pool, so masks line up with objects pixel-accurately.
4. **What does torchvision's Mask R-CNN return?** Per image: `boxes [N,4]`, `labels [N]`, `scores [N]`, `masks [N,1,H,W]` soft probabilities at input size.
5. **Why `masks > 0.5`?** The masks are per-pixel probabilities; thresholding gives a binary mask.
6. **Which label is "person" in COCO?** Category id 1 in torchvision/COCO (class 0 in YOLO's 0–79 numbering).
7. **Why not resize the crowd image to 224×224 first?** It distorts the aspect ratio, makes small people too small to detect, and the masks no longer match the original; the model already resizes internally.
8. **Why a score threshold?** Low-score detections are mostly false; without a threshold the people count is inflated.
9. **Why does the course's `person_masks[0]` crash sometimes?** If no person is detected the list is empty.
10. **Why can't you count people from a semantic mask?** Touching people merge into one connected region; instance masks keep them separate.
11. **How are COCO masks stored?** As polygons (or RLE for crowds) in the JSON; `annToMask` rasterises them.
12. **How is a mask evaluated?** Mask IoU with the true mask; ≥ 0.5 counts as a match (COCO mask AP averages over IoU 0.5–0.95).
13. **YOLOv8-seg vs Mask R-CNN?** One-stage: prototype masks + per-object coefficients, much faster; Mask R-CNN is two-stage with a per-RoI mask head, typically more precise boundaries on large objects.

Lab 6 · CNN + LSTM for action and gesture recognition

Course lab: `CV-Week3-Lecture6.ipynb` (in `course-files/labs/`) **Theory partner:** notes/06_video_rnn_lstm.md and notebooks/06_video_sequence_models_rnn_lstm.ipynb

Course cell	What it does	What you will see here
Setup: `VideoDataset` loader	reads frames from video files with OpenCV	the loader reading **real `.mp4` files** from disk, plus three bugs that stop it from working
Exercise: CNN + LSTM	a small CNN per frame, an LSTM over time	the course's model trained on labelled videos, with a training curve and **held-out** accuracy
Mini project: gesture recognition	predict a gesture class	a confusion matrix, per-video predictions, and a comparison with two **order-blind** baselines that shows *why* the LSTM is needed

What you will learn: how a video becomes a `[batch, time, channels, height, width]` tensor, what `batch_first=True` means, where the `32*16*16` comes from, and how to prove that a model is really using the order of frames.

Run time: about 15–20 minutes on the shared CPU this was built on (the CNN + LSTM alone trained for 887 s); expect less on an idle laptop. On a Colab GPU: under a minute.

0 · Theory in 60 seconds (details in notes chapter 06)

- A **video** is a sequence of frames. Recognising an **action** needs *what* is in each frame (**spatial** features: a hand, its shape) and *how it changes over time* (**temporal** features: the hand moves left).
- **CNN + LSTM pipeline:** run the same CNN on every frame to get one feature vector per frame, feed the sequence of vectors into an **LSTM**, and classify from the LSTM's final hidden state.
- **LSTM** (*Long Short-Term Memory*): an RNN with a **cell state** and three **gates** (forget, input, output) that decide what to drop, what to add and what to output at each step, so information can survive many time steps without the vanishing-gradient problem of a plain RNN.

The dataset: why synthetic, and what it contains

The course leaves the video folder as a placeholder (`./videos/train`) and every label as `0`. Real action datasets (UCF101: 6.5 GB, HMDB51, Jester gestures: 22 GB) are far too big for a quick lab, so we **generate a small synthetic gesture dataset** and **write it as real `.mp4` files**, so the course's OpenCV reading code is exercised for real.

> ⚠️ **Synthetic data.** Each clip shows a skin-coloured "hand" blob on a noisy background with a static distractor object, performing one of **5 gestures**: `swipe_left`, `swipe_right`, `swipe_up`, `swipe_down`, `circle`. Start

> position, size, speed, clip length (10–24 frames) and colours are random. Every swipe passes through a random centre point, so **`swipe_left` and `swipe_right` contain exactly the same kind of frames, only in opposite order** (likewise up/down). That is deliberate: a model can only tell them apart by using **time order**, which is exactly what the LSTM is for.

```
%matplotlib inline
import os, time, random, shutil
import numpy as np
import matplotlib.pyplot as plt
import cv2
import torch
import torch.nn as nn
import torchvision.transforms as transforms
from torch.utils.data import Dataset, DataLoader

torch.manual_seed(0); np.random.seed(0); random.seed(0)
torch.set_num_threads(2)                    # share the CPU politely; raise on your own machine
device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
print("torch", torch.__version__, "| OpenCV", cv2.__version__, "| device:", device)

CLASSES = ["swipe_left", "swipe_right", "swipe_up", "swipe_down", "circle"]
VID_ROOT = os.path.join("data", "videos")
SIZE = 64

def make_clip(cls, rng):
    """Return a list of HxWx3 uint8 BGR frames showing one gesture."""
    n = int(rng.integers(10, 25))                                  # clip length varies: 10..24
frames
    bg = np.full((SIZE, SIZE, 3), rng.integers(20, 90, 3), np.float32)
    bg += cv2.GaussianBlur(rng.normal(0, 25, (SIZE, SIZE, 3)).astype(np.float32), (0, 0), 3)   #
blotchy background
    dx, dy = int(rng.integers(6, 58)), int(rng.integers(6, 58))     # a static distractor square
    cv2.rectangle(bg, (dx - 4, dy - 4), (dx + 4, dy + 4), tuple(float(v) for v in
rng.integers(100, 255, 3)), -1)
    cx, cy = rng.uniform(22, 42, 2)                                  # centre of the gesture
    amp = rng.uniform(12, 20); r = int(rng.integers(5, 9))
    skin = np.array([rng.uniform(60, 120), rng.uniform(110, 170), rng.uniform(170, 240)])   # BGR
skin-ish tone
    t = np.linspace(-1, 1, n)
    if cls == "swipe_left":  xs, ys = cx - amp * t, cy + 0 * t
    if cls == "swipe_right": xs, ys = cx + amp * t, cy + 0 * t
    if cls == "swipe_up":    xs, ys = cx + 0 * t, cy - amp * t
    if cls == "swipe_down":  xs, ys = cx + 0 * t, cy + amp * t
    if cls == "circle":
        a0 = rng.uniform(0, 2 * np.pi)
        xs, ys = cx + 0.8 * amp * np.cos(a0 + np.pi * (t + 1)), cy + 0.8 * amp * np.sin(a0 +
np.pi * (t + 1))
    frames = []
    for x, y in zip(xs, ys):
        f = bg.copy()
        cv2.ellipse(f, (int(x), int(y)), (r, int(r * 1.3)), 0, 0, 360, tuple(float(v) for v in
skin), -1)
        f += rng.normal(0, 8, f.shape)                               # sensor noise
        frames.append(np.clip(f, 0, 255).astype(np.uint8))
    return frames

def write_video(path, frames, fps=10):
    w = cv2.VideoWriter(path, cv2.VideoWriter_fourcc(*"mp4v"), fps, (SIZE, SIZE))
    for f in frames:
        w.write(f)
    w.release()


N_PER_CLASS = {"train": 60, "test": 20}
rng = np.random.default_rng(0)
if os.path.isdir(VID_ROOT):
```

```
    shutil.rmtree(VID_ROOT)                                    # regenerate from scratch
every run
for split, n in N_PER_CLASS.items():
    for cls in CLASSES:
        os.makedirs(os.path.join(VID_ROOT, split, cls), exist_ok=True)
        for i in range(n):
            write_video(os.path.join(VID_ROOT, split, cls, f"{cls}_{i:03d}.mp4"), make_clip(cls,
rng))
for split in N_PER_CLASS:
    print(split, {c: len(os.listdir(os.path.join(VID_ROOT, split, c))) for c in CLASSES})
```

```
torch 2.14.1+cu130 | OpenCV 5.0.0 | device: cpu
train {'swipe_left': 60, 'swipe_right': 60, 'swipe_up': 60, 'swipe_down': 60, 'circle': 60}
test {'swipe_left': 20, 'swipe_right': 20, 'swipe_up': 20, 'swipe_down': 20, 'circle': 20}
```

```
def read_all_frames(path):
    cap = cv2.VideoCapture(path); frames = []
    while True:
        ok, f = cap.read()
        if not ok:
            break
        frames.append(cv2.cvtColor(f, cv2.COLOR_BGR2RGB))
    cap.release()
    return frames

fig, ax = plt.subplots(len(CLASSES), 8, figsize=(12, 7.5), dpi=70)
for row, cls in enumerate(CLASSES):
    fr = read_all_frames(os.path.join(VID_ROOT, "train", cls, f"{cls}_000.mp4"))
    for j, k in enumerate(np.linspace(0, len(fr) - 1, 8).astype(int)):
        ax[row, j].imshow(fr[k]); ax[row, j].axis("off")
        ax[row, j].set_title(f"t={k}", fontsize=7)
    ax[row, 0].text(-8, 32, cls, fontsize=9, ha="right", va="center")
plt.suptitle("one training video per class, 8 frames each (read back from the .mp4 files)",
fontsize=10)
plt.tight_layout(); plt.show()
```



1 · Setup: the course's `VideoDataset`

```
self.videos = os.listdir(video_dir)                    # every entry in the folder is assumed
to be a video file
cap = cv2.VideoCapture(video_path)                     # open the video
while len(frames) < self.seq_len and cap.isOpened():   # read up to seq_len (16) frames from
the START
    ret, frame = cap.read()                            # ret = False when the video has ended
    frame = cv2.cvtColor(frame, cv2.COLOR_BGR2RGB)     # OpenCV gives BGR, PyTorch/matplotlib
expect RGB
    frame = self.transform(frame)                      # ToTensor -> [3,H,W] in 0..1, then
Resize((64,64))
frames = torch.stack(frames)                           # -> [T, 3, 64, 64]
label = 0                                              # placeholder, replace with actual
label
```

Three problems, which we demonstrate one at a time:

1. **Folder layout.** Pointed at a folder that contains class *sub-folders*, `os.listdir` returns folder names; OpenCV cannot open a folder, zero frames are read and `torch.stack([])` fails.
2. **`label = 0` for every video.** Even pointed at a flat folder of videos it loads, but **every label is 0**. Training would quickly learn "always answer 0": loss → 0, knowledge → 0.
3. **Clips shorter than `seq_len`.** A 12-frame clip gives a `[12,3,64,64]` tensor, a 20-frame clip gives `[16,3,64,64]`. The `DataLoader` cannot stack different lengths into a batch.

```
# The course's dataset class, unchanged
class VideoDataset(Dataset):
    def __init__(self, video_dir, transform=None, seq_len=16):
        self.video_dir = video_dir
        self.videos = os.listdir(video_dir)
        self.transform = transform
        self.seq_len = seq_len
    def __len__(self):
        return len(self.videos)
    def __getitem__(self, idx):
        video_path = os.path.join(self.video_dir, self.videos[idx])
        cap = cv2.VideoCapture(video_path)
        frames = []
        while len(frames) < self.seq_len and cap.isOpened():
            ret, frame = cap.read()
            if not ret:
                break
            frame = cv2.cvtColor(frame, cv2.COLOR_BGR2RGB)
            if self.transform:
                frame = self.transform(frame)
            frames.append(frame)
        cap.release()
        frames = torch.stack(frames)
        label = 0  # placeholder, replace with actual label
        return frames, label

transform = transforms.Compose([
    transforms.ToTensor(),
    transforms.Resize((64,64))
])

# Problem 1: the class-folder layout
train_dataset = VideoDataset(os.path.join(VID_ROOT, "train"), transform=transform)
print("Loaded video dataset with", len(train_dataset), "videos   <- these are the 5 class
folders:", train_dataset.videos)
try:
    train_dataset[0]
except Exception as e:
    print("  reading item 0 ->", type(e).__name__ + ":", str(e)[:80])

# Problems 2 and 3: a flat folder of mixed-length videos
flat = VideoDataset(os.path.join(VID_ROOT, "train", "swipe_right"), transform=transform)
```

```
lengths = [flat[i][0].shape[0] for i in range(10)]
print("\nflat folder:", len(flat), "videos | labels of the first 10:", [flat[i][1] for i in
range(10)])
print("frames returned for the first 10 videos:", lengths)
try:
    for frames, labels in DataLoader(flat, batch_size=2, shuffle=False):
        pass
    print("all batches stacked fine")
except Exception as e:
    print("DataLoader ->", type(e).__name__ + ":", str(e)[:110])
```

```
Loaded video dataset with 5 videos   <- these are the 5 class folders: ['swipe_right', 'swipe_lef
t', 'swipe_down', 'swipe_up', 'circle']
  reading item 0 -> RuntimeError: stack expects a non-empty TensorList
flat folder: 60 videos | labels of the first 10: [0, 0, 0, 0, 0, 0, 0, 0, 0, 0]
frames returned for the first 10 videos: [16, 16, 16, 10, 16, 16, 16, 16, 14, 11]
DataLoader -> RuntimeError: stack expects each tensor to be equal size, but got [16, 3, 64, 64] a
t entry 0 and [10, 3, 64, 64] at entry 1
```

The fixed `VideoDataset`

- **Labels from folder names:** `videos/train/<class_name>/*.mp4`, label = index of the class name. This is the same convention as `torchvision.datasets.ImageFolder`.
- **Every clip → exactly `seq_len` frames by uniform temporal sampling:** read all frames, pick `seq_len` indices spread evenly from the first to the last frame (`np.linspace`). Short clips repeat some frames, long clips skip some. Unlike "the first 16 frames", this always covers the **whole gesture**, and every sample has the same shape so batching works.
- **A held-out test split** in `videos/test/`, never used for training.
- **A RAM cache**: decoding the same 300 videos again in every epoch is wasted work, so each clip is decoded once and kept in memory (400 clips × 16 × 3 × 64 × 64 floats ≈ 315 MB). Turn it off (`cache=False`) for a large dataset that doesn't fit in RAM. (No random augmentation here, so caching changes nothing about the training.)
- `transform` stays the course's `ToTensor()` + `Resize((64,64))` (our frames are already 64×64, so the resize does nothing here, but it would for real camera video).

```
class VideoDataset(Dataset):
    """Fixed: labels from class folders, fixed-length uniform temporal sampling, optional RAM
cache."""
    def __init__(self, video_dir, transform=None, seq_len=16, cache=True):
        self.classes = sorted(d for d in os.listdir(video_dir) if
os.path.isdir(os.path.join(video_dir, d)))
        self.samples = [(os.path.join(video_dir, c, f), i)                        # (path, label)
                        for i, c in enumerate(self.classes) for f in
sorted(os.listdir(os.path.join(video_dir, c)))]
        self.transform = transform
        self.seq_len = seq_len
        self.cache = {} if cache else None                                        # decoded clips
kept in RAM
    def __len__(self):
        return len(self.samples)
    def __getitem__(self, idx):
        if self.cache is not None and idx in self.cache:
            return self.cache[idx]
        video_path, label = self.samples[idx]
        cap = cv2.VideoCapture(video_path)
        frames = []
        while cap.isOpened():                                                     # read the WHOLE
clip
            ret, frame = cap.read()
            if not ret:
                break
```

```
            frames.append(cv2.cvtColor(frame, cv2.COLOR_BGR2RGB))
        cap.release()
        if len(frames) == 0:
            raise IOError(f"could not read any frame from {video_path}")
        idxs = np.linspace(0, len(frames) - 1, self.seq_len).round().astype(int)   # uniform
sampling
        frames = [self.transform(frames[i]) if self.transform else torch.from_numpy(frames[i])
for i in idxs]
        item = (torch.stack(frames), label)
        if self.cache is not None:
            self.cache[idx] = item
        return item

train_dataset = VideoDataset(os.path.join(VID_ROOT, "train"), transform=transform)
test_dataset = VideoDataset(os.path.join(VID_ROOT, "test"), transform=transform)
assert train_dataset.classes == sorted(CLASSES)
CLASS_NAMES = train_dataset.classes
train_loader = DataLoader(train_dataset, batch_size=8, shuffle=True)
test_loader = DataLoader(test_dataset, batch_size=20, shuffle=False)

frames, labels = next(iter(train_loader))
print("Loaded video dataset with", len(train_dataset), "training and", len(test_dataset), "test
videos")
print("classes:", CLASS_NAMES)
print("one batch: frames", tuple(frames.shape), "= [batch, time, channels, height, width] |
labels", labels.tolist())
```

```
Loaded video dataset with 300 training and 100 test videos
classes: ['circle', 'swipe_down', 'swipe_left', 'swipe_right', 'swipe_up']
one batch: frames (8, 16, 3, 64, 64) = [batch, time, channels, height, width] | labels [0, 1, 1,
3, 2, 0, 0, 0]
```

2 · Exercise: action recognition with CNN + LSTM

The course's model, line by line:

```
self.cnn = nn.Sequential(nn.Conv2d(3, 16, 3, padding=1), nn.ReLU(), nn.MaxPool2d(2),     #
3x64x64  -> 16x32x32
                         nn.Conv2d(16, 32, 3, padding=1), nn.ReLU(), nn.MaxPool2d(2))    #
16x32x32 -> 32x16x16
self.lstm = nn.LSTM(32*16*16, hidden_dim, batch_first=True)
self.fc = nn.Linear(hidden_dim, num_classes)
```

- **Why `32*16*16`?** Each frame is 64×64; two `MaxPool2d(2)` halve it twice → 16×16, and the last conv has 32 channels. Flattened, each frame becomes a vector of **32 × 16 × 16 = 8,192** numbers. That is the LSTM's `input_size`. Change the frame size (say to 128×128) and this must become `32*32*32`, otherwise you get a shape error.
- `batch_first=True`: the LSTM expects input shaped `[batch, time, features]` (here `[8, 16, 8192]`). Without it PyTorch expects `[time, batch, features]`, and the batch and time axes would be silently swapped.
- `forward`: a loop over the 16 time steps runs the *same* CNN on each frame (`x[:, t]` = frame t of every video in the batch, `[B,3,64,64]`), flattens it (`.view(batch_size, -1)`), and `torch.stack(..., dim=1)` rebuilds `[B, T, 8192]`.
- `lstm_out[:, -1, :]`: the LSTM returns a hidden state for **every** time step (`[B, T, 128]`); we keep the **last** one, which has "seen" the whole clip, and the `Linear` layer maps it to 5 class scores (logits).
- `CrossEntropyLoss` takes these logits and the integer labels (it applies softmax internally).

```
# The course's model, unchanged
class CNN_LSTM(nn.Module):
```

```
    def __init__(self, hidden_dim=128, num_classes=5):
        super(CNN_LSTM, self).__init__()
        self.cnn = nn.Sequential(
            nn.Conv2d(3, 16, 3, padding=1),
            nn.ReLU(),
            nn.MaxPool2d(2),
            nn.Conv2d(16, 32, 3, padding=1),
            nn.ReLU(),
            nn.MaxPool2d(2)
        )
        self.lstm = nn.LSTM(32*16*16, hidden_dim, batch_first=True)
        self.fc = nn.Linear(hidden_dim, num_classes)
    def forward(self, x):
        batch_size, seq_len, c, h, w = x.size()
        cnn_out = []
        for t in range(seq_len):
            out = self.cnn(x[:,t])
            out = out.view(batch_size, -1)
            cnn_out.append(out)
        cnn_out = torch.stack(cnn_out, dim=1)
        lstm_out, _ = self.lstm(cnn_out)
        out = self.fc(lstm_out[:,-1,:])
        return out

m = CNN_LSTM()
x = torch.zeros(2, 16, 3, 64, 64)
feats = torch.stack([m.cnn(x[:, t]).view(2, -1) for t in range(16)], dim=1)
print("input", tuple(x.shape), "-> CNN per frame", tuple(m.cnn(x[:, 0]).shape), "-> flattened
sequence", tuple(feats.shape),
      "-> LSTM out", tuple(m.lstm(feats)[0].shape), "-> logits", tuple(m(x).shape))
print(f"parameters: CNN {sum(p.numel() for p in m.cnn.parameters()):,} | LSTM {sum(p.numel() for
p in m.lstm.parameters()):,} | FC {sum(p.numel() for p in m.fc.parameters()):,}")
```

```
input (2, 16, 3, 64, 64) -> CNN per frame (2, 32, 16, 16) -> flattened sequence (2, 16, 8192) ->
LSTM out (2, 16, 128) -> logits (2, 5)
parameters: CNN 5,088 | LSTM 4,260,864 | FC 645
```

Two order-blind baselines

To check that the LSTM really uses *motion*, we train two models with the **same CNN** but no sequence model:

- `FrameAverage` : CNN features of all 16 frames are **averaged** over time, then a `Linear` layer classifies. It sees every frame but **not their order** (shuffle the frames and the output is identical).
- `SingleFrame` : classifies from the **middle frame only**, like an image classifier.

If the LSTM is doing its job it should beat both, and the baselines should confuse exactly the pairs that differ only in direction (left/right, up/down).

```
class FrameAverage(nn.Module):
    def __init__(self, num_classes=5):
        super().__init__()
        self.cnn = CNN_LSTM().cnn                                # same CNN architecture
        self.fc = nn.Linear(32*16*16, num_classes)
    def forward(self, x):
        b, t = x.shape[:2]
        f = self.cnn(x.flatten(0, 1)).view(b, t, -1)             # all frames in one go:
[B*T,3,64,64] -> [B,T,8192]
        return self.fc(f.mean(dim=1))                            # average over time: order is
lost

class SingleFrame(nn.Module):
    def __init__(self, num_classes=5):
```

```
        super().__init__()
        self.cnn = CNN_LSTM().cnn
        self.fc = nn.Linear(32*16*16, num_classes)
    def forward(self, x):
        return self.fc(self.cnn(x[:, x.shape[1] // 2]).flatten(1))  # the middle frame only

@torch.no_grad()
def evaluate(model, loader):
    model.eval()                                                # FIX: evaluation mode
    preds, ys = [], []
    for frames, labels in loader:
        preds.append(model(frames.to(device)).argmax(1).cpu()); ys.append(labels)
    preds, ys = torch.cat(preds), torch.cat(ys)
    return (preds == ys).float().mean().item(), preds, ys

def train(model, epochs=15, lr=0.001):
    model.to(device)
    criterion = nn.CrossEntropyLoss()
    optimizer = torch.optim.Adam(model.parameters(), lr=lr)
    hist = {"loss": [], "train_acc": [], "test_acc": []}
    for epoch in range(1, epochs + 1):
        model.train()
        running_loss, correct, seen = 0.0, 0, 0
        for frames, labels in train_loader:
            frames, labels = frames.to(device), labels.to(device)
            optimizer.zero_grad()
            outputs = model(frames)
            loss = criterion(outputs, labels)
            loss.backward()
            optimizer.step()
            running_loss += loss.item()
            correct += (outputs.argmax(1) == labels).sum().item(); seen += len(labels)
        hist["loss"].append(running_loss / len(train_loader)); hist["train_acc"].append(correct /
seen)
        hist["test_acc"].append(evaluate(model, test_loader)[0])
        print(f"  Epoch {epoch:2d}, Loss: {hist['loss'][-1]:.4f}, train acc {hist['train_acc']
[-1]:.2f}, test acc {hist['test_acc'][-1]:.2f}")
    return hist


EPOCHS = 12
models, hists, times = {}, {}, {}
for name, make in [("CNN_LSTM", CNN_LSTM), ("FrameAverage", FrameAverage), ("SingleFrame",
SingleFrame)]:
    torch.manual_seed(0)
    print(name)
    t = time.time()
    models[name] = make()
    hists[name] = train(models[name], EPOCHS)
    times[name] = time.time() - t
```

```
CNN_LSTM
  Epoch  1, Loss: 1.3502, train acc 0.49, test acc 0.64
  Epoch  2, Loss: 0.7465, train acc 0.69, test acc 0.67
  Epoch  3, Loss: 0.5424, train acc 0.77, test acc 0.75
  Epoch  4, Loss: 0.3481, train acc 0.87, test acc 0.85
  Epoch  5, Loss: 0.1919, train acc 0.96, test acc 0.87
  Epoch  6, Loss: 0.1016, train acc 0.99, test acc 0.85
  Epoch  7, Loss: 0.0471, train acc 0.99, test acc 0.91
  Epoch  8, Loss: 0.0223, train acc 1.00, test acc 0.91
  Epoch  9, Loss: 0.0150, train acc 1.00, test acc 0.91
  Epoch 10, Loss: 0.0094, train acc 1.00, test acc 0.92
  Epoch 11, Loss: 0.0070, train acc 1.00, test acc 0.92
  Epoch 12, Loss: 0.0050, train acc 1.00, test acc 0.91
FrameAverage
  Epoch  1, Loss: 1.6380, train acc 0.20, test acc 0.33
  Epoch  2, Loss: 1.5496, train acc 0.32, test acc 0.27
  Epoch  3, Loss: 1.3548, train acc 0.45, test acc 0.30
  Epoch  4, Loss: 1.1815, train acc 0.51, test acc 0.34
  Epoch  5, Loss: 1.0284, train acc 0.61, test acc 0.34
```

```
  Epoch  6, Loss: 0.8747, train acc 0.68, test acc 0.38
  Epoch  7, Loss: 0.7647, train acc 0.71, test acc 0.41
  Epoch  8, Loss: 0.5996, train acc 0.78, test acc 0.43
  Epoch  9, Loss: 0.5293, train acc 0.83, test acc 0.42
  Epoch 10, Loss: 0.5411, train acc 0.81, test acc 0.42
  Epoch 11, Loss: 0.3682, train acc 0.88, test acc 0.42
  Epoch 12, Loss: 0.3026, train acc 0.90, test acc 0.44
SingleFrame
  Epoch  1, Loss: 1.6405, train acc 0.21, test acc 0.17
  Epoch  2, Loss: 1.5832, train acc 0.33, test acc 0.23
  Epoch  3, Loss: 1.4741, train acc 0.42, test acc 0.23
  Epoch  4, Loss: 1.3838, train acc 0.46, test acc 0.23
  Epoch  5, Loss: 1.2909, train acc 0.48, test acc 0.23
  Epoch  6, Loss: 1.1745, train acc 0.54, test acc 0.25
  Epoch  7, Loss: 1.0610, train acc 0.58, test acc 0.23
  Epoch  8, Loss: 0.9525, train acc 0.62, test acc 0.24
  Epoch  9, Loss: 0.7988, train acc 0.74, test acc 0.25
  Epoch 10, Loss: 0.7733, train acc 0.72, test acc 0.20
  Epoch 11, Loss: 0.6038, train acc 0.78, test acc 0.18
  Epoch 12, Loss: 0.4941, train acc 0.82, test acc 0.25
```

```
fig, ax = plt.subplots(1, 2, figsize=(12, 3.8), dpi=80)
for name, h in hists.items():
    ax[0].plot(range(1, EPOCHS + 1), h["loss"], label=name)
    ax[1].plot(range(1, EPOCHS + 1), h["test_acc"], label=name)
ax[1].axhline(1 / len(CLASSES), color="grey", ls=":", label="chance (20%)")
ax[0].set_title("training loss"); ax[1].set_title("accuracy on the 100 held-out test videos")
for a in ax: a.set_xlabel("epoch"); a.grid(alpha=0.3); a.legend(fontsize=8)
plt.tight_layout(); plt.show()

print(f"{'model':13s} {'params':>10s} {'train time':>10s} {'test accuracy':>14s}")
for name, m in models.items():
    acc = evaluate(m, test_loader)[0]
    print(f"{name:13s} {sum(p.numel() for p in m.parameters()):>10,} {times[name]:>9.0f}s
{acc:>14.1%}")
```




```
model            params train time  test accuracy
CNN_LSTM      4,266,597       887s          91.0%
FrameAverage     46,053       111s          44.0%
SingleFrame      46,053         4s          25.0%
```

3 · Mini project: gesture recognition


The course's mini-project cell takes a batch **from the training loader**, predicts, and prints the class of the first video. We evaluate on the **test** videos instead and look at *which* gestures get confused.

```
from sklearn.metrics import confusion_matrix

fig, ax = plt.subplots(1, 3, figsize=(16, 4.6), dpi=75)
for a, name in zip(ax, models):
```

```
    acc, preds, ys = evaluate(models[name], test_loader)
    cm = confusion_matrix(ys, preds, labels=range(len(CLASS_NAMES)))
    a.imshow(cm, cmap="Blues")
    for i in range(len(CLASS_NAMES)):
        for j in range(len(CLASS_NAMES)):
            a.text(j, i, cm[i, j], ha="center", va="center", color="white" if cm[i, j] > 10 else
"black", fontsize=9)
    a.set_xticks(range(5)); a.set_xticklabels(CLASS_NAMES, rotation=40, ha="right", fontsize=8)
    a.set_yticks(range(5)); a.set_yticklabels(CLASS_NAMES, fontsize=8)
    a.set_xlabel("predicted"); a.set_ylabel("true"); a.set_title(f"{name}: {acc:.0%} on test",
fontsize=10)
    pair = lambda i, j: cm[i, j] + cm[j, i]
    L, Rr, U, D = (CLASS_NAMES.index(c) for c in ("swipe_left", "swipe_right", "swipe_up",
"swipe_down"))
    print(f"{name:13s}: left<->right confusions {pair(L, Rr):2d}/40, up<->down confusions
{pair(U, D):2d}/40")
plt.tight_layout(); plt.show()
```


```
CNN_LSTM     : left<->right confusions  0/40, up<->down confusions  1/40
FrameAverage : left<->right confusions 17/40, up<->down confusions 15/40
SingleFrame  : left<->right confusions 12/40, up<->down confusions  3/40
```




```
# The course's mini-project cell, done on TEST videos, with class names and confidence
model = models["CNN_LSTM"].eval()
frames, labels = next(iter(DataLoader(test_dataset, batch_size=6, shuffle=True,
generator=torch.Generator().manual_seed(3))))
with torch.no_grad():
    probs = torch.softmax(model(frames.to(device)), dim=1).cpu()
_, predicted = torch.max(probs, 1)

fig, ax = plt.subplots(6, 6, figsize=(9, 9.5), dpi=65)
for i in range(6):
    for j, t in enumerate([0, 3, 6, 9, 12, 15]):
        ax[i, j].imshow(frames[i][t].permute(1, 2, 0)); ax[i, j].axis("off")
    ok = "correct" if predicted[i] == labels[i] else "WRONG"
    ax[i, 0].set_title(f"true {CLASS_NAMES[labels[i]]} | predicted {CLASS_NAMES[predicted[i]]}
({probs[i, predicted[i]]:.0%}, {ok})",
                       fontsize=8, loc="left")
    print(f"video {i}: Predicted gesture class: {predicted[i].item()} =
{CLASS_NAMES[predicted[i]]:11s} "
          f"(true: {CLASS_NAMES[labels[i]]}, confidence {probs[i, predicted[i]]:.0%})")
plt.tight_layout(); plt.show()
```

```
video 0: Predicted gesture class: 1 = swipe_down  (true: swipe_down, confidence 98%)
video 1: Predicted gesture class: 0 = circle      (true: circle, confidence 99%)
video 2: Predicted gesture class: 2 = swipe_left  (true: swipe_left, confidence 94%)
video 3: Predicted gesture class: 2 = swipe_left  (true: swipe_left, confidence 67%)
video 4: Predicted gesture class: 0 = circle      (true: circle, confidence 100%)
video 5: Predicted gesture class: 3 = swipe_right (true: swipe_right, confidence 100%)
```



Proof that the LSTM uses frame order: play the test videos backwards

If we **reverse** each test clip in time, a model that understands motion should now call a left swipe a *right* swipe (and up ↔ down), while `circle` stays `circle` (it is still a circle, only the other way round). The order-blind `FrameAverage` model, by construction, gives exactly the same answers as before.

```
@torch.no_grad()
def predict_all(model, reverse=False):
    model.eval(); out = []
    for frames, _ in test_loader:
        if reverse:
            frames = frames.flip(1)                          # flip the time axis
        out.append(model(frames.to(device)).argmax(1).cpu())
    return torch.cat(out)

swap = {"swipe_left": "swipe_right", "swipe_right": "swipe_left", "swipe_up": "swipe_down",
"swipe_down": "swipe_up", "circle": "circle"}
ys = torch.tensor([lab for _, lab in test_dataset.samples])
expected_rev = torch.tensor([CLASS_NAMES.index(swap[CLASS_NAMES[y]]) for y in ys])
for name in ("CNN_LSTM", "FrameAverage"):
    fwd, rev = predict_all(models[name]), predict_all(models[name], reverse=True)
    print(f"{name:13s}: accuracy forwards {(fwd == ys).float().mean():.0%} | reversed clips
```

```
classified as the "
          f"mirror gesture {(rev == expected_rev).float().mean():.0%} | prediction unchanged by
reversing {(rev == fwd).float().mean():.0%}")
```

```
CNN_LSTM     : accuracy forwards 91% | reversed clips classified as the mirror gesture 76% | pred
iction unchanged by reversing 4%
FrameAverage : accuracy forwards 44% | reversed clips classified as the mirror gesture 48% | pred
iction unchanged by reversing 100%
```

🔧 What we changed from the course notebook, and why

Course code	Problem	Fix here
`./videos/train` placeholder	no data	400 synthetic gesture clips written as `.mp4` files (300 train / 100 test), clearly labelled synthetic
`self.videos = os.listdir(video_dir)`	lists class folders as if they were videos → 0 frames → `torch.stack` crash	walk `video_dir/<class>/*.mp4`
`label = 0  # placeholder`	every video has the same label; the model can only learn "always 0"	label = index of the class folder
read the first `seq_len` frames	short clips give fewer frames → batch can't be stacked; long clips are cut off half-way	read all frames, sample exactly `seq_len` frames uniformly over the whole clip
`for epoch in range(1, 3)`	2 epochs	12 epochs with loss and test-accuracy curves
mini project uses `next(iter(train_loader))`	evaluates on training data	a separate **test** split, `model.eval()`, `torch.no_grad()`
prints `predicted[0].item()`	a bare number for one video	class names, confidence, a confusion matrix for all 100 test videos
no baseline	can't tell whether the LSTM matters	`FrameAverage` and `SingleFrame` baselines + a time-reversal test
`CNN_LSTM` model	**kept unchanged** (it is correct for 64×64 input)	explained `32*16*16`, `batch_first`, `lstm_out[:, -1, :]`

Results, honestly

Measured in the run above: synthetic gesture videos, **300 training and 100 held-out test clips** (5 classes, 20 test clips each; chance = 20%), 12 epochs per model.

Model	Parameters	Train time (shared CPU)	Test accuracy	left↔right confusions	up↔down confusions
CNN + LSTM (course model, fixed loader)	4,266,597	887 s	**91.0%**	0 / 40	1 / 40

Model	Parameters	Train time (shared CPU)	Test accuracy	left↔right confusions	up↔down confusions
FrameAverage (same CNN, frame order ignored)	46,053	111 s	44.0%	17 / 40	15 / 40
SingleFrame (middle frame only)	46,053	4 s	25.0%	12 / 40	3 / 40

What this shows:

- **The LSTM is what makes the gestures recognisable.** With the same per-frame CNN, the model that reads the frames *in order* reached 91%. The model that averages them reached 44% and the single-frame model 25%, barely above chance.
- **The order-blind models fail exactly where the gestures differ only in direction.** The frame-average model mixed up left/right swipes 17 times out of 40 and up/down swipes 15 times. The LSTM confused left/right never and up/down once.
- **Playing the test clips backwards proves the LSTM uses frame order.** For 76% of reversed clips it now predicted the *mirror* gesture (left ↔ right, up ↔ down), and only 4% of its predictions stayed the same. The frame-average model gave identical answers for 100% of reversed clips, as it must.
- **The LSTM model overfits.** Training accuracy reached 100% by epoch 8 while test accuracy levelled off around 91%. Almost all of its 4.27 M parameters are in the LSTM, because each frame is flattened to 8,192 numbers before entering it. A smaller input (e.g. global average pooling of the CNN features) would cut that drastically.
- **The single-frame model memorised its training clips** (training accuracy kept rising while test stayed at about 25%): one still image simply doesn't contain the direction of motion.
- **Caveats:** the data is synthetic (a skin-coloured blob on noise), so these numbers say nothing about real hands or webcams. Timings come from a CPU shared with other jobs, so expect it to be faster on your own machine.

Common errors and how to fix them

Error	Cause	Fix
`RuntimeError: stack expects a non-empty TensorList`	no frames read: wrong path, a folder instead of a file, or a codec OpenCV can't decode	check `cap.isOpened()` and the path; re-encode the video (`ffmpeg -i in.avi -c:v libx264 out.mp4`)
`RuntimeError: stack expects each tensor to be equal size`	clips with different numbers of frames	sample a fixed `seq_len` per clip (uniform sampling or padding)
`RuntimeError: input.size(-1) must be equal to input_size. Expected 8192`	frame size is not 64×64, so CNN output ≠ `32*16*16`	resize frames to 64×64, or set `input_size = 32*(H/4)*(W/4)`
loss drops to ~0 immediately, accuracy meaningless	all labels are the same (the `label = 0` placeholder)	read labels from folder names or an annotation file

Error	Cause	Fix
colours look wrong (blue skin)	OpenCV gives BGR	`cv2.cvtColor(frame, cv2.COLOR_BGR2RGB)`
training is very slow	Python loop over time steps on CPU	run the CNN on all frames at once: `x.flatten(0, 1)` (see `FrameAverage`)
LSTM learns nothing, batch and time mixed up	forgot `batch_first=True`	input `[B, T, F]` with `batch_first=True`, or permute to `[T, B, F]`

Try this yourself

1. Add a sixth class, `circle_anticlockwise` (reverse the angle direction in `make_clip`), and set `num_classes=6`. Can `FrameAverage` tell the two circles apart? Can the LSTM?
2. Replace `lstm_out[:,-1,:]` with `lstm_out.mean(dim=1)`. Does accuracy change?
3. Change `seq_len` to 8 and to 24. How few frames are enough?
4. Swap `nn.LSTM` for `nn.GRU` (same arguments) or `nn.RNN`, and compare.
5. Record a 2-second clip of your own hand swiping in front of a webcam, save it in `data/videos/test/swipe_left/`, and see what the model says (expect it to fail: it only knows blobs on noise. Why?).

Run it on Google Colab with a GPU

1. Upload the notebook, *Runtime → Change runtime type → T4 GPU*.
2. Nothing to install: `torch`, `opencv-python` and `scikit-learn` are preinstalled; the videos are generated in the first cell.
3. *Run all*. For a real dataset, put UCF101 or Jester clips into `data/videos/{train,test}/<class>/` and the fixed `VideoDataset` reads them unchanged (use `num_classes = number of folders`).

Viva questions

1. **Why combine a CNN with an LSTM for video?** The CNN extracts spatial features from each frame (what is there); the LSTM models how those features change over time (motion, order).
2. **What is the shape of a video batch?** `[batch, time, channels, height, width]`, here `[8, 16, 3, 64, 64]`.
3. **Why is the LSTM input size `32*16*16`?** Two 2×2 max-pools shrink 64×64 frames to 16×16, and the last conv has 32 channels; flattened that is 8,192 features per frame.
4. **What does `batch_first=True` do?** Makes the LSTM accept `[batch, time, features]` instead of the default `[time, batch, features]`.
5. **Why use `lstm_out[:, -1, :]`?** The last time step's hidden state summarises the whole sequence; it is fed to the classifier.
6. **What are the LSTM gates?** Forget gate (what to erase from the cell state), input gate (what new information to store), output gate (what to output as the hidden state).

7. **Why does an LSTM handle long sequences better than a plain RNN?** The additive cell-state path lets gradients flow over many steps without vanishing.
8. **What is wrong with `label = 0`?** All samples share one label, so the model learns a constant answer; real labels must come from folder names or annotation files.
9. **Why sample frames uniformly instead of taking the first 16?** It covers the whole action regardless of clip length and guarantees a fixed tensor size for batching.
10. **How did we show the LSTM uses temporal order?** Order-blind baselines (frame averaging, a single frame) confuse left/right and up/down; reversing test clips flips the LSTM's answers to the mirror gesture, while the frame-average model's answers stay the same.
11. **Why convert BGR to RGB?** OpenCV decodes frames as BGR; PyTorch models and matplotlib assume RGB.
12. **What are alternatives to CNN + LSTM?** 3D CNNs (C3D, I3D) that convolve over time, two-stream networks with optical flow, and video transformers.
13. **Why `CrossEntropyLoss` without a softmax layer?** It expects raw logits and applies log-softmax internally.

Lab 7 · Train a Vision Transformer (ViT) on CIFAR-10 + mini project: ViT image classifier

Course lab: `CV-Week3-Lecture7.ipynb` (copy in `course-files/labs/`). Exercise: *"Train ViT on CIFAR-10"* with `timm.create_model('vit_base_patch16_224', pretrained=True, num_classes=10)`. Mini project: *"Image classifier with ViT"*.

What you will learn

- How `timm` builds a pretrained ViT, and what `vit_base_patch16_224` means (Base size, 16×16 patches, 224×224 input).
- Why the course **resizes 32×32 CIFAR images to 224×224**, and what that costs.
- Why **fully fine-tuning ViT-Base (86 million parameters) is a GPU job**: we measure it.
- A CPU-friendly version of the same idea: **frozen pretrained ViT + a new linear head**.
- The key ViT lesson, measured on the same small dataset: **pretrained ViT ≫ CNN from scratch > ViT from scratch**. Transformers need lots of data or pretraining.

Run time. 24 minutes on the 4-core CPU this notebook was built on, which was shared with other heavy jobs at the time (measured: see the last code cell). Most of it is pushing 1,500 images through ViT-Base. An idle machine will be faster. On a Colab GPU the same steps should take only a few minutes. The course's full fine-tuning (flag `FULL_FINETUNE = True`) is a GPU job: our rough estimate for a T4 is 10–20 minutes per epoch on all 50,000 images (not measured; we could not run it here).

0 · Theory in 60 seconds

Full theory: notes/07_attention_and_vision_transformers.md and the notebook 07_vision_transformers_attention.ipynb, where we build attention and a mini-ViT by hand.

1. **Patches → tokens.** Cut the image into 16×16 patches. A 224×224 image gives 14 × 14 = **196 patches**. Each patch (16·16·3 = 768 numbers) is mapped by a linear layer to a 768-long **embedding**.
2. **[CLS] token + position embeddings.** A learnable extra token is prepended (197 tokens), and a learned **position embedding** is added so the model knows where each patch came from.
3. **Transformer encoder** (12 blocks in ViT-Base): **multi-head self-attention** lets every token look at every other token ($\mathrm{softmax}(Q \cdot K^T/\sqrt{d}) \cdot V$), then an MLP; each with a residual connection + LayerNorm.
4. **Classification:** the final [CLS] token → `head` = `Linear(768 → num_classes)`.

The catch: ViT has almost no built-in assumptions about images (CNNs assume locality). So it needs **huge datasets** (ImageNet-21k with 14 M images, or JFT-300M) to learn them, or a model pretrained on such data. That is exactly what this lab measures.

```
%matplotlib inline
import os, time, urllib.request
from concurrent.futures import ThreadPoolExecutor
```

```
import numpy as np
import matplotlib.pyplot as plt
from PIL import Image

import torch
import torch.nn as nn
import torch.optim as optim
import torchvision
import torchvision.transforms as transforms
from torch.utils.data import DataLoader
import warnings
warnings.filterwarnings("ignore", message="IProgress not found")    # harmless notice from timm's
progress bar
import timm                     # PyTorch Image Models:  pip install timm

# While this notebook was built, other jobs shared the same 4-core CPU, so we limit PyTorch to 2
threads.
# On your own computer you can delete this line: PyTorch then uses all your cores.
torch.set_num_threads(2)
NOTEBOOK_START = time.time()
torch.manual_seed(0)

device = torch.device("cuda" if torch.cuda.is_available() else "cpu")
print("torch", torch.__version__, "| timm", timm.__version__, "| device:", device)
```

```
torch 2.14.1+cu130 | timm 1.0.30 | device: cpu
```

1 · Setup: CIFAR-10 loader (the course's first cell)

The course's transform:

Line	Why
`transforms.Resize((224,224))`	`vit_base_patch16_224` was pretrained on **224×224** images and its position embeddings are for exactly **14×14 = 196 patches**. A 32×32 CIFAR image would give only 2×2 = 4 patches of 16×16, so we blow it up 7× (each 16×16 patch then covers a blurry ~2.3×2.3 pixels of the original).
`transforms.Normalize([0.5,0.5,0.5], [0.5,0.5,0.5])`	→ values in −1…1. Correct for this model: these ViT weights were trained with mean = std = 0.5 (timm stores this in `model.pretrained_cfg`).
`batch_size=32`	224×224 images through an 86 M-parameter model use a lot of memory

Data routes (same as Lab 1): the official `torchvision.datasets.CIFAR10(download=True)` first; if the Toronto server cannot be reached (as on our build machine), the same images as JPG files from a GitHub mirror. The executed output says which route ran.

Subset. ViT-Base is slow on a CPU (we measure it below), so this lab uses **100 training + 50 test images per class (1,000 + 500)**. That is also a realistic "small dataset" setting, where the pretraining question matters most.

```
N_TRAIN_PER_CLASS = 100     # full dataset: 5000
N_TEST_PER_CLASS = 50       # full dataset: 1000
DIR_NAMES = ['airplane', 'automobile', 'bird', 'cat', 'deer', 'dog', 'frog', 'horse', 'ship',
'truck']  # CIFAR-10 label order
MIRROR = "https://raw.githubusercontent.com/YoongiKim/CIFAR-10-images/master"
```

```python
def first_n_per_class(targets, n):
    idx, seen = [], {}
    for i, t in enumerate(targets):
        if seen.get(t, 0) < n:
            idx.append(i); seen[t] = seen.get(t, 0) + 1
    return idx

class CifarJpgFolder(torch.utils.data.Dataset):
    """Fallback dataset: data/cifar10_jpg/<split>/<class>/0000.jpg ..."""
    def __init__(self, root, n_per_class, transform=None):
        self.samples = [(f"{root}/{c}/{i:04d}.jpg", label) for label, c in enumerate(DIR_NAMES)
for i in range(n_per_class)]
        self.targets = [label for _, label in self.samples]
        self.classes = DIR_NAMES
        self.transform = transform
    def __len__(self):
        return len(self.samples)
    def __getitem__(self, i):
        path, label = self.samples[i]
        img = Image.open(path).convert("RGB")
        return (self.transform(img) if self.transform else img), label

def download_mirror(split, n_per_class, root="./data/cifar10_jpg"):
    jobs = [(f"{MIRROR}/{split}/{c}/{i:04d}.jpg", f"{root}/{split}/{c}/{i:04d}.jpg") for c in
DIR_NAMES for i in range(n_per_class)]
    jobs = [(u, p) for u, p in jobs if not os.path.exists(p)]
    def fetch(job):
        url, path = job
        os.makedirs(os.path.dirname(path), exist_ok=True)
        for attempt in range(3):
            try:
                urllib.request.urlretrieve(url, path + ".part"); os.replace(path + ".part",
path); return
            except Exception as e:
                err = e
        raise err
    t = time.time()
    with ThreadPoolExecutor(32) as pool:
        list(pool.map(fetch, jobs))
    print(f"  mirror: {split}: downloaded {len(jobs)} new files in {time.time() - t:.0f}s")
    return f"{root}/{split}"

def load_cifar10(train_transform, test_transform, verbose=True):
    try:
        trainset = torchvision.datasets.CIFAR10(root='./data', train=True, download=True,
transform=train_transform)
        testset = torchvision.datasets.CIFAR10(root='./data', train=False, download=True,
transform=test_transform)
        classes = trainset.classes
        trainset = torch.utils.data.Subset(trainset, first_n_per_class(trainset.targets,
N_TRAIN_PER_CLASS))
        testset = torch.utils.data.Subset(testset, first_n_per_class(testset.targets,
N_TEST_PER_CLASS))
        if verbose: print("DATA ROUTE: official torchvision CIFAR10 download")
    except Exception as e:
        if verbose:
            print("Official CIFAR-10 download failed:", type(e).__name__, str(e)[:80])
            print("DATA ROUTE: fallback = CIFAR-10 JPG mirror on GitHub")
        trainset = CifarJpgFolder(download_mirror("train", N_TRAIN_PER_CLASS), N_TRAIN_PER_CLASS,
train_transform)
        testset = CifarJpgFolder(download_mirror("test", N_TEST_PER_CLASS), N_TEST_PER_CLASS,
test_transform)
        classes = DIR_NAMES
    return trainset, testset, classes

def targets_of(ds):
    # labels of a dataset, for both routes (a Subset of CIFAR10, or our JPG folder)
    return list(ds.targets) if hasattr(ds, "targets") else [ds.dataset.targets[i] for i in
ds.indices]
```

```
# ---- the course's cell ----
transform = transforms.Compose([
    transforms.Resize((224,224)),
    transforms.ToTensor(),
    transforms.Normalize([0.5,0.5,0.5],[0.5,0.5,0.5])
])

trainset, testset, classes = load_cifar10(transform, transform)
trainloader = DataLoader(trainset, batch_size=32, shuffle=True)
testloader = DataLoader(testset, batch_size=32, shuffle=False)

print("Classes:", classes)
print(f"train: {len(trainset)} images | test: {len(testset)} images")
x, y = trainset[0]
print("one transformed image:", tuple(x.shape), f"(was 32x32) -> 224/16 = {224 // 16} patches per
side = {(224 // 16) ** 2} patches")
```

```
Official CIFAR-10 download failed: URLError <urlopen error Tunnel connection failed: 403 Forbidde
n>
DATA ROUTE: fallback = CIFAR-10 JPG mirror on GitHub
  mirror: train: downloaded 1000 new files in 8s
  mirror: test: downloaded 500 new files in 4s
Classes: ['airplane', 'automobile', 'bird', 'cat', 'deer', 'dog', 'frog', 'horse', 'ship', 'truc
k']
train: 1000 images | test: 500 images
one transformed image: (3, 224, 224) (was 32x32) -> 224/16 = 14 patches per side = 196 patches
```

2 · Exercise: "Train ViT on CIFAR-10"

2.1 Loading the pretrained ViT: official route and fallback

```
model = timm.create_model('vit_base_patch16_224', pretrained=True, num_classes=10)
```

- **`'vit_base_patch16_224'`**: ViT-**Base** (12 blocks, 768-dim embeddings, 12 attention heads, ≈ 86 M parameters), **patch 16**, input **224**.
- **`pretrained=True`**: download ImageNet weights. In `timm` this argument is current (unlike torchvision's deprecated `pretrained=`).
- **`num_classes=10`**: timm loads every pretrained weight **except** the final `head`, which it replaces with a new, randomly initialised `Linear(768 → 10)`. That's the timm equivalent of Lab 1's `classifier[6] = ...` and Lab 2's `fc = ...`.

`timm` downloads the weights from the **Hugging Face Hub**, which the build machine cannot reach. Fallback: the **original ViT-B/16 weights released by the ViT authors** (pretrained on ImageNet-21k, fine-tuned on ImageNet-1k at 224×224), converted to PyTorch by timm's author and published on GitHub. Their layer names match timm's model exactly. These were timm's default weights for this model name in earlier versions; today's default (`augreg2_in21k_ft_in1k`) is a newer training recipe of the same architecture. Both use mean = std = 0.5.

The fallback loads them in three steps: create the model with random weights → `load_state_dict` → `reset_classifier(10)` to swap in a new 10-class head. The result is the same as what the course's one-liner does.

```
FALLBACK_URL = "https://github.com/rwightman/pytorch-image-models/releases/download/v0.1-
vitjx/jx_vit_base_p16_224-80ecf9dd.pth"

def load_pretrained_vit(num_classes=10):
```

```
    try:
        model = timm.create_model('vit_base_patch16_224', pretrained=True,
num_classes=num_classes)
        print("WEIGHTS ROUTE: official timm / Hugging Face download")
        return model, None
    except Exception as e:
        print("Official timm download failed:", type(e).__name__, str(e)[:80])
        model = timm.create_model('vit_base_patch16_224', pretrained=False)          # random
weights, 1000-class head
        t = time.time()
        state = torch.hub.load_state_dict_from_url(FALLBACK_URL, model_dir="data/weights",
map_location="cpu", progress=False)
        print(f"  checkpoint loaded in {time.time() - t:.0f}s;", "load_state_dict:",
model.load_state_dict(state))
        print("WEIGHTS ROUTE: fallback = original ViT-B/16 ImageNet weights from GitHub")
        imagenet_model = model
        return model, imagenet_model

model, imagenet_model = load_pretrained_vit()
```

```
Official timm download failed: ProxyError 403 Forbidden
Downloading: "https://github.com/rwightman/pytorch-image-models/releases/download/v0.1-vitjx/jx_v
it_base_p16_224-80ecf9dd.pth" to data/weights/jx_vit_base_p16_224-80ecf9dd.pth
  checkpoint loaded in 3s; load_state_dict: <All keys matched successfully>
WEIGHTS ROUTE: fallback = original ViT-B/16 ImageNet weights from GitHub
```

Sanity check (fallback route only). Before replacing the head, the fallback model still has its 1000 ImageNet outputs, so we can check that the weights are real. ImageNet has classes like "speedboat", "moving van" and "sorrel" (a chestnut horse), so some upscaled CIFAR images should get sensible guesses. Others won't: a 32×32 image blown up to 224×224 is very blurry, and many ImageNet classes are very specific. Then we call `reset_classifier(10)`.

```
imagenet_names = torchvision.models.ViT_B_16_Weights.IMAGENET1K_V1.meta["categories"]   # 1000
ImageNet names, shipped with torchvision
if imagenet_model is not None:
    imagenet_model.eval()
    test_targets = targets_of(testset)
    picks = [test_targets.index(k) for k in (0, 1, 8, 9, 7)]      # first plane, car, ship,
truck, horse
    batch = torch.stack([testset[i][0] for i in picks])
    with torch.no_grad():
        p = torch.softmax(imagenet_model(batch), 1)
    plt.figure(figsize=(14, 3.3))
    for k, i in enumerate(picks):
        top = p[k].topk(2)
        plt.subplot(1, 5, k + 1); plt.imshow((batch[k] / 2 + 0.5).permute(1, 2, 0).clamp(0, 1));
plt.axis("off")
        plt.title(f"[{classes[test_targets[i]]}]\n" + "\n".join(f"{imagenet_names[j][:18]}
{v:.0%}" for v, j in zip(top.values, top.indices)), fontsize=9)
    plt.suptitle("Untouched pretrained ViT-B/16: top-2 ImageNet guesses for upscaled CIFAR
images", y=1.04); plt.tight_layout(); plt.show()
    model.reset_classifier(10)                      # new random Linear(768 -> 10), as
num_classes=10 does
print("head:", model.head)
print(f"parameters: {sum(p.numel() for p in model.parameters())/1e6:.1f} M | pretrained_cfg
mean/std: {model.pretrained_cfg.get('mean')}, {model.pretrained_cfg.get('std')}")
```




```
head: Linear(in_features=768, out_features=10, bias=True)
parameters: 85.8 M | pretrained_cfg mean/std: (0.5, 0.5, 0.5), (0.5, 0.5, 0.5)
```

2.2 Inside the model: from image to 197 tokens

The same steps as the theory, on the real model:

```
model.eval()
x = torch.stack([testset[0][0]])                                    # (1, 3, 224, 224)
with torch.no_grad():
    patches = model.patch_embed(x)                                  # conv 16x16 stride 16 = "cut
into patches + linear map"
    print("image                  :", tuple(x.shape))
    print("patch_embed (tokens)   :", tuple(patches.shape), " -> 196 patches, each a 768-long
vector")
    print("cls_token              :", tuple(model.cls_token.shape))
    print("pos_embed              :", tuple(model.pos_embed.shape), " -> one position vector per
token (196 + CLS)")
    tokens = model.forward_features(x)
    print("after 12 encoder blocks:", tuple(tokens.shape))
    print("CLS token -> head      :", tuple(model.forward_head(tokens, pre_logits=True).shape),
"->", tuple(model.forward_head(tokens).shape))
print(f"number of encoder blocks: {len(model.blocks)}, attention heads per block:
{model.blocks[0].attn.num_heads}")
```

```
image                  : (1, 3, 224, 224)
patch_embed (tokens)   : (1, 196, 768)  -> 196 patches, each a 768-long vector
cls_token              : (1, 1, 768)
pos_embed              : (1, 197, 768)  -> one position vector per token (196 + CLS)
after 12 encoder blocks: (1, 197, 768)
CLS token -> head      : (1, 768) -> (1, 10)
number of encoder blocks: 12, attention heads per block: 12
```

2.3 The course's full fine-tuning: how long would it take here?

The course trains **all 86 M parameters** (`optim.Adam(model.parameters(), lr=0.0001)`) for 2 epochs on 50,000 images resized to 224×224. `lr = 0.0001` is 10× smaller than in Labs 1–2 on purpose: when fine-tuning pretrained weights you only want to *nudge* them, because big steps would destroy what was learned.

Rather than guess, we **time one real training step** (forward + backward + Adam update) on a batch of 8 and extrapolate:

```
FULL_FINETUNE = False      # True = run the course's loop (needs a GPU, e.g. Google Colab)

model.to(device)
criterion = nn.CrossEntropyLoss()
optimizer = optim.Adam(model.parameters(), lr=0.0001)

# time 2 real training steps on 8 images (the first step includes warm-up)
model.train()
```

```
xb, yb = next(iter(DataLoader(trainset, batch_size=8)))
for step in range(2):
    t = time.time()
    optimizer.zero_grad()
    loss = criterion(model(xb.to(device)), yb.to(device))
    loss.backward()
    optimizer.step()
    step_time = time.time() - t
per_img = step_time / 8
print(f"one training step on 8 images: {step_time:.1f}s  ->  {per_img*1000:.0f} ms per image")
print(f"estimated time for ONE epoch of the course (50,000 images) on this CPU:
{per_img*50000/3600:.1f} hours")
print(f"... and for one epoch of our 1,000-image subset: {per_img*1000/60:.1f} minutes")

if FULL_FINETUNE:
    # ---- the course's training loop (unchanged) ----
    for epoch in range(1, 3):
        running_loss = 0.0
        for inputs, labels in trainloader:
            inputs, labels = inputs.to(device), labels.to(device)
            optimizer.zero_grad()
            outputs = model(inputs)
            loss = criterion(outputs, labels)
            loss.backward()
            optimizer.step()
            running_loss += loss.item()
        print(f"Epoch {epoch}, Loss: {running_loss/len(trainloader):.4f}")
else:
    print("FULL_FINETUNE = False: skipping the course's full fine-tuning loop (set True on a
GPU).")
```

```
one training step on 8 images: 17.9s  ->  2237 ms per image
estimated time for ONE epoch of the course (50,000 images) on this CPU: 31.1 hours
... and for one epoch of our 1,000-image subset: 37.3 minutes
FULL_FINETUNE = False: skipping the course's full fine-tuning loop (set True on a GPU).
```

2.4 The CPU-friendly version: frozen pretrained ViT + new linear head

This is **Lab 2's trick applied to a transformer**: freeze every pretrained weight and train only the new `head`. Because the backbone never changes, each image's 768-number [CLS] feature is always the same. So we compute it **once**, store it, and train the head on the stored features. That's mathematically the same as running the course's loop with a frozen backbone, but we pay the expensive ViT forward pass only once per image instead of once per epoch.

(Before extracting we reload the pretrained weights, so the single training step above leaves no trace.)

```
del optimizer, model                    # free the fine-tuning model and its Adam state (about 1
GB)
model, _ = load_pretrained_vit()
model.reset_classifier(10)
for param in model.parameters():
    param.requires_grad = False         # freeze everything ...
for param in model.head.parameters():
    param.requires_grad = True          # ... except the new head
model.to(device).eval()                 # eval(): always the right habit for testing / feature
extraction
print(f"trainable: {sum(p.numel() for p in model.parameters() if p.requires_grad):,} of
{sum(p.numel() for p in model.parameters()):,} parameters")

def extract_features(loader):
    feats, labels = [], []
    with torch.no_grad():
```

```
        for inputs, y in loader:
            f = model.forward_head(model.forward_features(inputs.to(device)), pre_logits=True)
# the [CLS] vector
            feats.append(f.cpu()); labels.append(y)
    return torch.cat(feats), torch.cat(labels)

t = time.time()
Ftr, Ytr = extract_features(trainloader)
Fte, Yte = extract_features(testloader)
vit_feature_time = time.time() - t
print(f"features: train {tuple(Ftr.shape)}, test {tuple(Fte.shape)} in {vit_feature_time:.0f}s "
      f"= {1000 * vit_feature_time / (len(Ftr) + len(Fte)):.0f} ms per image (inference only)")
```

```
Official timm download failed: ProxyError 403 Forbidden
  checkpoint loaded in 0s; load_state_dict: <All keys matched successfully>
WEIGHTS ROUTE: fallback = original ViT-B/16 ImageNet weights from GitHub
trainable: 7,690 of 85,806,346 parameters
features: train (1000, 768), test (500, 768) in 530s = 354 ms per image (inference only)
```

```
torch.manual_seed(0)
head = model.head                                   # the new Linear(768 -> 10)
opt_head = optim.Adam(head.parameters(), lr=0.001)
hist_vit = {"loss": [], "acc": []}
feat_loader = DataLoader(torch.utils.data.TensorDataset(Ftr, Ytr), batch_size=32, shuffle=True)
for epoch in range(1, 31):
    running_loss = 0.0
    for f, y in feat_loader:                        # the course's loop, on stored features
        opt_head.zero_grad()
        loss = criterion(head(f.to(device)), y.to(device))
        loss.backward()
        opt_head.step()
        running_loss += loss.item()
    with torch.no_grad():
        acc = 100 * (head(Fte.to(device)).argmax(1).cpu() == Yte).float().mean().item()
    hist_vit["loss"].append(running_loss / len(feat_loader)); hist_vit["acc"].append(acc)
    if epoch in (1, 2, 5, 10, 20, 30):
        print(f"Epoch {epoch:2d}, Loss: {hist_vit['loss'][-1]:.4f}, test accuracy: {acc:.1f}%")
acc_vit_pre = hist_vit["acc"][-1]
```

```
Epoch  1, Loss: 1.1075, test accuracy: 84.0%
Epoch  2, Loss: 0.3998, test accuracy: 84.8%
Epoch  5, Loss: 0.1903, test accuracy: 87.4%
Epoch 10, Loss: 0.0757, test accuracy: 88.0%
Epoch 20, Loss: 0.0255, test accuracy: 88.2%
Epoch 30, Loss: 0.0132, test accuracy: 88.2%
```

3 · Does pretraining matter? ViT from scratch vs CNN from scratch

Now the experiment that explains *why* the course loads `pretrained=True`. On the **same 1,000 training images** and the same 500 test images we train two small models **from random weights**, at CIFAR's native 32×32 (no resizing):

- **Tiny ViT**: timm's own `VisionTransformer` class, sized for 32×32 images: patch 4 → 8×8 = 64 patches + CLS, 96-dim embeddings, 4 blocks, 3 heads.
- **Small CNN**: VGG-style, 3 blocks of two 3×3 convs + BatchNorm + max-pool (as in Lab 1, but narrower).

Both have a similar number of parameters (printed below), get the same light augmentation (random crop + flip), Adam lr = 0.001, 30 epochs, cosine learning-rate schedule.

```
from timm.models.vision_transformer import VisionTransformer

def conv_bn_relu(c_in, c_out):
    return [nn.Conv2d(c_in, c_out, 3, padding=1), nn.BatchNorm2d(c_out), nn.ReLU(inplace=True)]

def make_small_cnn():
    return nn.Sequential(
        *conv_bn_relu(3, 32), *conv_bn_relu(32, 32), nn.MaxPool2d(2),       # 32 -> 16
        *conv_bn_relu(32, 64), *conv_bn_relu(64, 64), nn.MaxPool2d(2),      # 16 -> 8
        *conv_bn_relu(64, 96), *conv_bn_relu(96, 96), nn.MaxPool2d(2),      # 8 -> 4
        nn.Flatten(), nn.Dropout(0.3), nn.Linear(96 * 4 * 4, 10))

def make_tiny_vit():
    return VisionTransformer(img_size=32, patch_size=4, num_classes=10, embed_dim=96, depth=4,
num_heads=3, mlp_ratio=2.0)

small_tf_train = transforms.Compose([transforms.RandomCrop(32, padding=4),
transforms.RandomHorizontalFlip(),
                                     transforms.ToTensor(), transforms.Normalize([0.5] * 3, [0.5]
* 3)])
small_tf_test = transforms.Compose([transforms.ToTensor(), transforms.Normalize([0.5] * 3, [0.5]
* 3)])
train32, test32, _ = load_cifar10(small_tf_train, small_tf_test, verbose=False)        # same
images, kept at 32x32
train32_loader = DataLoader(train32, batch_size=64, shuffle=True)
test32_loader = DataLoader(test32, batch_size=100, shuffle=False)

for name, fn in [("tiny ViT", make_tiny_vit), ("small CNN", make_small_cnn)]:
    print(f"{name:9s}: {sum(p.numel() for p in fn().parameters())/1e6:.2f} M parameters")
```

```
  mirror: train: downloaded 0 new files in 0s
  mirror: test: downloaded 0 new files in 0s
tiny ViT : 0.31 M parameters
small CNN: 0.22 M parameters
```

```
def evaluate(net, loader):
    net.eval(); correct = 0; preds = []
    with torch.no_grad():
        for x, y in loader:
            p = net(x.to(device)).argmax(1).cpu()
            correct += (p == y).sum().item(); preds.append(p)
    return 100 * correct / len(loader.dataset), torch.cat(preds)

def train_from_scratch(net, epochs=30, name=""):
    torch.manual_seed(0)
    net.to(device)
    opt = optim.Adam(net.parameters(), lr=0.001)
    sched = optim.lr_scheduler.CosineAnnealingLR(opt, T_max=epochs)
    hist = {"loss": [], "acc": []}
    t0 = time.time()
    for epoch in range(1, epochs + 1):
        net.train(); running = 0.0
        for x, y in train32_loader:
            x, y = x.to(device), y.to(device)
            opt.zero_grad(); loss = criterion(net(x), y); loss.backward(); opt.step()
            running += loss.item()
        sched.step()
        acc, _ = evaluate(net, test32_loader)
        hist["loss"].append(running / len(train32_loader)); hist["acc"].append(acc)
        if epoch in (1, 5, 10, 20, 30):
            print(f"[{name}] Epoch {epoch:2d}, Loss: {hist['loss'][-1]:.4f}, test accuracy:
{acc:.1f}%")
    hist["time"] = time.time() - t0
    print(f"[{name}] {hist['time']:.0f}s total, {hist['time']/epochs:.1f}s per epoch")
    return hist

torch.manual_seed(0); tiny_vit = make_tiny_vit()
hist_tvit = train_from_scratch(tiny_vit, name="tiny ViT, scratch")
```


```
torch.manual_seed(0); small_cnn = make_small_cnn()
hist_cnn = train_from_scratch(small_cnn, name="small CNN, scratch")
```

```
[tiny ViT, scratch] Epoch  1, Loss: 2.1804, test accuracy: 16.4%
[tiny ViT, scratch] Epoch  5, Loss: 1.9766, test accuracy: 24.4%
[tiny ViT, scratch] Epoch 10, Loss: 1.8648, test accuracy: 24.6%
[tiny ViT, scratch] Epoch 20, Loss: 1.6686, test accuracy: 32.2%
[tiny ViT, scratch] Epoch 30, Loss: 1.5527, test accuracy: 31.0%
[tiny ViT, scratch] 653s total, 21.8s per epoch
[small CNN, scratch] Epoch  1, Loss: 2.2214, test accuracy: 15.0%
[small CNN, scratch] Epoch  5, Loss: 1.5901, test accuracy: 39.2%
[small CNN, scratch] Epoch 10, Loss: 1.3352, test accuracy: 41.4%
[small CNN, scratch] Epoch 20, Loss: 0.8774, test accuracy: 51.2%
[small CNN, scratch] Epoch 30, Loss: 0.6761, test accuracy: 53.4%
[small CNN, scratch] 129s total, 4.3s per epoch
```

```
acc_tvit, _ = evaluate(tiny_vit, test32_loader)
acc_cnn, _ = evaluate(small_cnn, test32_loader)

fig, ax = plt.subplots(1, 2, figsize=(12, 3.8))
ep = range(1, 31)
ax[0].plot(ep, hist_vit["loss"], label="ViT-B/16 pretrained, frozen + new head")
ax[0].plot(ep, hist_cnn["loss"], label="small CNN from scratch")
ax[0].plot(ep, hist_tvit["loss"], label="tiny ViT from scratch")
ax[0].axhline(np.log(10), color="gray", ls="--", label="chance (2.303)")
ax[0].set_title("training loss"); ax[0].set_xlabel("epoch"); ax[0].legend(fontsize=8);
ax[0].grid(alpha=0.3)
ax[1].plot(ep, hist_vit["acc"], label="ViT-B/16 pretrained, frozen + new head")
ax[1].plot(ep, hist_cnn["acc"], label="small CNN from scratch")
ax[1].plot(ep, hist_tvit["acc"], label="tiny ViT from scratch")
ax[1].axhline(10, color="gray", ls="--", label="chance (10%)")
ax[1].set_ylim(0, 100); ax[1].set_title("test accuracy (%) on the same 500 images");
ax[1].set_xlabel("epoch"); ax[1].legend(fontsize=8); ax[1].grid(alpha=0.3)
plt.tight_layout(); plt.show()

print(f"{'model (1,000 training images)':40s}{'test acc':>9s}{'params':>10s}{'trained':>10s}")
print(f"{'ViT-B/16 pretrained, frozen + head':40s}{acc_vit_pre:8.1f}%{'85.8 M':>10s}
{'7,690':>10s}")
print(f"{'small CNN from scratch':40s}{acc_cnn:8.1f}%{sum(p.numel() for p in
small_cnn.parameters())/1e6:8.2f} M{'all':>10s}")
print(f"{'tiny ViT from scratch':40s}{acc_tvit:8.1f}%{sum(p.numel() for p in
tiny_vit.parameters())/1e6:8.2f} M{'all':>10s}")
```




```
model (1,000 training images)            test acc    params   trained
ViT-B/16 pretrained, frozen + head          88.2%    85.8 M     7,690
small CNN from scratch                      53.4%    0.22 M       all
tiny ViT from scratch                       31.0%    0.31 M       all
```

4 · Mini project: the ViT image classifier, evaluated

The classifier is the frozen ViT-B/16 + our trained head. The head was trained on stored features, and it *is* `model.head`, so `model(images)` now runs the complete pretrained ViT plus our new

head on raw images. First the course's test loop (with `model.eval()` added) on the first 4 test batches, to check that the full model agrees with the stored-feature route. Running all 500 images again would cost several more CPU minutes for the same answer. Then per-class results and the confusion matrix for all 500 test images, from the stored features.

```
model.eval()
correct, total, all_pred = 0, 0, []
t = time.time()
with torch.no_grad():
    for b, (inputs, labels) in enumerate(testloader):
        if b == 4:                      # 4 batches x 32 = 128 images are enough for the check
            break
        inputs, labels = inputs.to(device), labels.to(device)
        outputs = model(inputs)
        _, predicted = torch.max(outputs, 1)
        total += labels.size(0)
        correct += (predicted == labels).sum().item()
        all_pred.append(predicted.cpu())
full_pred = torch.cat(all_pred)
with torch.no_grad():
    feat_pred = head(Fte[:total].to(device)).argmax(1).cpu()
print(f"full model on the first {total} raw test images: accuracy {100 * correct / total:.2f}%
({time.time() - t:.0f}s)")
print(f"same predictions as the stored-feature route? {torch.equal(full_pred, feat_pred)}")


with torch.no_grad():
    pred = head(Fte.to(device)).argmax(1).cpu().numpy()
true = Yte.numpy()
print(f"\nAccuracy on the whole CIFAR-10 test subset ({len(true)} images): {100 * (pred ==
true).mean():.2f}%")

cm = np.zeros((10, 10), dtype=int)
for a, b in zip(true, pred):
    cm[a, b] += 1
print("\nper-class accuracy:")
for i, c in enumerate(classes):
    print(f"  {c:10s} {100 * cm[i, i] / cm[i].sum():5.1f}%")
plt.figure(figsize=(6.5, 5.5))
plt.imshow(cm, cmap="Purples")
for i in range(10):
    for j in range(10):
        plt.text(j, i, cm[i, j], ha="center", va="center", fontsize=8, color="white" if cm[i, j]
> cm.max() / 2 else "black")
plt.xticks(range(10), classes, rotation=45); plt.yticks(range(10), classes)
plt.xlabel("predicted"); plt.ylabel("true"); plt.title("Pretrained ViT + new head: confusion
matrix (50 per class)")
plt.colorbar(fraction=0.046); plt.tight_layout(); plt.show()
```

```
full model on the first 128 raw test images: accuracy 87.50%  (19s)
same predictions as the stored-feature route? True


Accuracy on the whole CIFAR-10 test subset (500 images): 88.20%

per-class accuracy:
  airplane    88.0%
  automobile  90.0%
  bird        86.0%
  cat         80.0%
  deer        94.0%
  dog         86.0%
  frog        90.0%
  horse       92.0%
  ship        88.0%
  truck       88.0%
```




```
def imshow(img):
    img = img / 2 + 0.5          # correct un-normalisation here (we normalised with mean 0.5,
std 0.5)
    npimg = img.numpy()
    plt.imshow(np.clip(np.transpose(npimg, (1, 2, 0)), 0, 1)); plt.axis("off")

rng = np.random.default_rng(0)
idx = rng.choice(len(testset), 16, replace=False)
with torch.no_grad():
    probs = torch.softmax(head(Fte[idx].to(device)), 1).cpu()      # stored features of these
images -> same result as model(images)
conf, p = probs.max(1)
plt.figure(figsize=(14, 5.2))
for k, i in enumerate(idx):
    plt.subplot(2, 8, k + 1); imshow(testset[i][0])
    plt.title(f"true: {classes[Yte[i]]}\npred: {classes[p[k]]} {conf[k]:.0%}", fontsize=9,
color="green" if p[k] == Yte[i] else "red")
plt.suptitle("Pretrained ViT + new head: 16 test images (shown at 224x224, i.e. upscaled)");
plt.tight_layout(); plt.show()
```




```
print(f"Total run time of this notebook: {(time.time() - NOTEBOOK_START) / 60:.1f} minutes")
```

```
Total run time of this notebook: 23.8 minutes
```

🔧 What we changed from the course notebook, and why

Course code	Our version	Why
`CIFAR10(download=True)` only	official first, **GitHub JPG mirror fallback**	the build machine cannot reach the Toronto server (output shows the route)
full 50,000 / 10,000 images	**100 / 50 per class**	ViT-Base costs about 0.1–0.2 s per image on our CPU just for inference
`timm.create_model(..., pretrained=True, num_classes=10)`	same call first; **fallback**: original ViT-B/16 ImageNet weights from GitHub + `reset_classifier(10)`	Hugging Face is blocked on the build machine
full fine-tuning of all 86 M parameters, 2 epochs	kept behind `FULL_FINETUNE = False` ; we **time one real step** instead	measured cost on this CPU: hours per epoch
(training of the whole model)	**frozen backbone + new head**, trained on stored [CLS] features	same model as freezing all but `head` in the course loop, at a fraction of the cost
test loop without `model.eval()`	`model.eval()` added	the right habit. timm's ViT-B has dropout layers but with probability 0 by default, so here it makes no numerical difference (unlike Labs 1–2)
batch prediction without `torch.no_grad()`	wrapped in `no_grad()`	no gradient graph for predictions
(not in course)	tiny ViT and small CNN **from scratch** on the same data	shows why ViTs need pretraining
`imshow` : `img / 2 + 0.5`	kept	correct here, because this lab normalises with mean = std = 0.5

Results, honestly

Measured in the run above. All three models learned from the **same 1,000 CIFAR-10 training images** (100 per class) and were tested on the **same 500 test images**:

Model	Test accuracy	Parameters (trained)	Input
ViT-B/16 pretrained on ImageNet, frozen + new head (CPU version of the course exercise)	**88.2 %**	85.8 M (only 7,690 trained)	224×224 (upscaled)
small CNN from scratch, 30 epochs	**53.4 %**	0.22 M (all)	32×32
tiny ViT from scratch, 30 epochs	**31.0 %**	0.31 M (all)	32×32
chance	10 %		

What this shows:

- **Pretraining is what makes ViT work on small data.** The frozen pretrained ViT with a linear head reached 84.0 % after a single epoch and 88.2 % after 30, from just 100 images per class. Every class was at least 80 % (per-class list above).
- **From scratch, the transformer is the worst of the three** (31.0 %), clearly behind a CNN of similar size (53.4 %). With only 1,000 images the tiny ViT cannot learn what a CNN gets for free from its design (nearby pixels belong together, the same pattern can appear anywhere). This matches the original ViT paper, which found that ViTs trained only on ImageNet-sized data lag behind CNNs and pull ahead only after pretraining on much larger datasets (14 M to 300 M images).
- **The cost of ViT-Base on a CPU is real.** Feature extraction ran at about 354 ms per image (inference only). One full fine-tuning step measured 2237 ms per image, which extrapolates to about **31.1 hours for one epoch** of the course's full 50,000-image training. That's why the course's exercise needs a GPU, and why we ran the frozen-feature version instead.
- **The 224×224 resize is required, not optional:** the pretrained position embeddings expect 196 patches. But it means the model works on a blurry, 7× enlarged image, and it costs about 49× more pixels than the original.
- **Caveats:** our timings come from a CPU shared with other jobs, so expect them to be faster on your own machine. Only 500 test images (50 per class), so each class's accuracy moves in steps of 2 %. The fallback weights (original ViT-B/16) are not the same file as timm's current default, so with the official route your numbers will differ slightly. We did not run the full fine-tuning: no accuracy is claimed for it.

Common errors and how to fix them

Error / symptom	Cause	Fix
`AssertionError: Input height (32) doesn't match model (224)`	fed 32×32 images to `vit_base_patch16_224`	`transforms.Resize((224,224))`, as the does (or create the model with `img_size=32` train from scratch)

Error / symptom	Cause	Fix
`CUDA out of memory`	ViT-Base + 224×224 + batch 32 + full fine-tuning	`batch_size=16` or `8`; mixed precision (`torch.autocast("cuda")`); or freeze the backbone
`ProxyError` / `LocalEntryNotFoundError` / `OSError` when `pretrained=True`	no access to huggingface.co	the notebook falls back to the GitHub checkpo download the weights elsewhere and pass `pretrained_cfg_overlay=dict(file='p`
`ModuleNotFoundError: No module named 'timm'`	timm not installed	`pip install timm`
`size mismatch for head.weight: [1000, 768] vs [10, 768]`	loading a 1000-class checkpoint into a 10-class model	load into the 1000-class model first, then `reset_classifier(10)` (as our fallback do
training extremely slow	running ViT-Base on a CPU	use a GPU (Colab) or frozen features as in 2.4
accuracy changes between runs of the test loop	forgot `model.eval()` in a model with active dropout or BatchNorm	`model.eval()` before testing
ViT from scratch stuck at low accuracy	not enough data for a transformer	use pretrained weights, more data, stronger augmentation, or a CNN

Try this yourself

1. **More data for the head.** Set `N_TRAIN_PER_CLASS = 300`. How much does the pretrained ViT improve? And the from-scratch models?
2. **Full fine-tuning on a GPU.** On Colab set `FULL_FINETUNE = True` (and `N_TRAIN_PER_CLASS = 5000`). Compare with the frozen version. The course reports only the loss, so add the test loop after it.
3. **CNN features instead.** Replace ViT with `timm.create_model('resnet50', pretrained=True, num_classes=0)` (gives 2048-dim features) and repeat section 2.4. Which pretrained backbone gives better features for CIFAR?
4. **Patch size.** Make the tiny ViT use `patch_size=8` (16 tokens) or `patch_size=2` (256 tokens). Accuracy vs speed?
5. **Look at attention.** Notebook 07 builds attention by hand; try visualising `model.blocks[-1].attn` on one of these images.

Run it on Google Colab with a GPU

1. Upload the notebook to colab.research.google.com; **Runtime → Change runtime type → T4 GPU**.
2. Delete the `torch.set_num_threads(2)` line. `timm` is usually pre-installed; if not, `!pip install timm`.
3. Run all. Both official downloads work there, so the outputs will say `DATA ROUTE: official` and `WEIGHTS ROUTE: official timm`.

4. Now the course's real exercise is affordable: `FULL_FINETUNE = True`. Our rough estimate is 10–20 minutes per epoch on 50,000 images with a T4 at batch size 32 (estimated from the GPU's compute, not measured). Start with `N_TRAIN_PER_CLASS = 1000` to see results sooner.

Viva questions (with short model answers)

1. **How does ViT turn an image into a sequence?** It cuts the image into fixed-size patches (16×16), flattens each and projects it linearly to an embedding. Each patch is one token.
2. **How many tokens does `vit_base_patch16_224` use?** $(224/16)^2$ = 196 patch tokens + 1 [CLS] token = 197, each 768-dimensional.
3. **Why does the course resize CIFAR from 32×32 to 224×224?** The pretrained model expects 224×224, matching its 196 learned position embeddings (and timm checks the size). The cost: about 49× more pixels and far more compute per image, and the upscaled patches are blurry.
4. **What is self-attention?** Each token makes a query, key and value. Attention weights = $\text{softmax}(Q \cdot K^T/\sqrt{d})$ say how much each token looks at every other token, and the output is the weighted sum of values. It captures long-range relations from the first layer.
5. **Why multi-head attention?** Several attention heads in parallel, each with its own Q/K/V projections, so different heads can focus on different relationships. ViT-Base has 12 heads.
6. **What is the [CLS] token?** A learnable token prepended to the patches. After the encoder, its output summarises the whole image and is fed to the classification head.
7. **Why position embeddings?** Attention treats tokens as an unordered set. Position embeddings tell the model where each patch was.
8. **What does `num_classes=10` do in `timm.create_model`?** It keeps all pretrained weights except the final head, which becomes a new random `Linear(768, 10)`.
9. **Why lr = 0.0001 for ViT fine-tuning instead of 0.001?** Fine-tuning should only nudge pretrained weights. Large steps destroy the pretrained features, and transformers are especially sensitive to the learning rate.
10. **Why did the tiny ViT trained from scratch do worse than the small CNN on 1,000 images?** ViT lacks the CNN's built-in assumptions (locality, translation equivariance) and must learn them from data. With little data it cannot, so it overfits or underfits. This is why ViTs need huge datasets or pretraining.
11. **Why did the frozen pretrained ViT win by so much?** Its features were learned from millions of images (ImageNet-21k + ImageNet-1k). Only the 7,690-parameter head had to be learned from our 1,000 images.
12. **Feature extraction vs full fine-tuning?** Feature extraction: freeze the backbone and train only the head (cheap, works with little data). Full fine-tuning: update all weights with a small lr (better accuracy with enough data, needs a GPU).
13. **CNN vs ViT in one line each?** CNN: local filters, strong image assumptions, data-efficient. ViT: global attention from layer 1, few assumptions, needs lots of data but scales very well.
14. **Why can we cache features in 2.4?** The frozen backbone gives the same output for the same image every epoch, so computing it once is mathematically identical to recomputing it each epoch (no augmentation, model in eval mode).

15. **What is the computational problem of attention?** Its cost grows with the **square** of the number of tokens (every token attends to every token). Smaller patches or bigger images quickly become expensive.

Week 2 & 3 Question Bank: Model Answers

Answers to every question in **CV-Week2-3-Questions.pdf** (original in `course-files/`). Each answer is eval-length and points to the notebook (`notebooks/0X_…`) where you can **see it happen**.

> Cover the answer, say yours out loud, then check. For "Hard" questions, aim for 5–8 lines with an example.

Easy

1. Who invented LeNet and what was its primary application?
Yann LeCun (Bell Labs, LeNet-5 in 1998). Primary application: **handwritten digit recognition**, used for reading **bank cheques and postal (zip) codes**. → nb 02

2. What dataset was LeNet trained on?
MNIST: 60,000 training + 10,000 test images of handwritten digits, 28×28 grayscale (padded to 32×32 for LeNet).

3. What was AlexNet's biggest achievement in 2012?
It **won the ImageNet competition (ILSVRC 2012) by a huge margin**: about 15.3% top-5 error vs about 26% for the runner-up. That **sparked the deep-learning revolution** in computer vision.

4. Name two innovations introduced in AlexNet.
Any two of: **ReLU activation** (faster training), **dropout** (less overfitting), **GPU training** (massive speed-up). Also heavy data augmentation and overlapping max-pooling.

5. What activation function replaced sigmoid/tanh in AlexNet?
ReLU (Rectified Linear Unit), f(x) = max(0, x). → nb 01, 02

6. What does ReLU do to negative input values?
Sets them to **zero**. Positive values pass through unchanged.

7. What is the purpose of dropout?
To **prevent overfitting** (a regularization technique). During training it randomly switches off (zeros) a fraction of neurons each pass, so the network can't rely on a few specific neurons and must learn robust, distributed features. It's switched off at test time. → nb 01

8. How many layers does VGG typically have?
16 to 19 weight layers (VGG-16: 13 conv + 3 FC; VGG-19: 16 conv + 3 FC).

9. What filter size did VGG standardize?
Small **3×3** convolution filters, stacked one after another.

10. What problem does ResNet solve?
Training **very deep networks**: the **vanishing gradient / degradation** problem. Plain networks got *worse* (even on training data) as layers were added, because gradients faded before reaching the early layers. → nb 03

11. What is the key innovation in ResNet?
Residual (skip) connections: each block outputs **F(x) + x**, so it learns only the *residual* F(x) = H(x) − x, and gradients flow through the identity path.

12. What does EfficientNet's compound scaling balance?
The network's **depth** (layers), **width** (channels) and input **resolution**, scaled **together** with one coefficient φ: depth α^φ, width β^φ, resolution γ^φ.

13. Which CNN architecture enabled training of networks with 152 layers?
ResNet (ResNet-152).

14. Which architecture is lightweight yet accurate for mobile vision apps?
EfficientNet (e.g. EfficientNet-B0: about 5.3 M parameters, more accurate than ResNet-50). **MobileNet** is the other classic answer; EfficientNet is built from its depthwise-separable blocks.

15. What does object detection aim to identify in an image?
What each object is (class label) and **where** it is (bounding box), for **every** object in the image.

16. What does R-CNN stand for?
Region-based Convolutional Neural Network.

17. Why is YOLO considered fast?
It looks at the image **once**: a single forward pass of one network predicts all bounding boxes and class probabilities together (detection as one regression problem). There's no separate stage of thousands of region proposals. → nb 04 (our toy YOLO was over 100× faster than our toy R-CNN)

18. What does SSD stand for?
Single Shot MultiBox Detector.

19. What is semantic segmentation?
Assigning a class label to every pixel in an image (e.g. road / car / person / sky), giving a dense label map. It doesn't separate individual objects of the same class. → nb 05

20. What is the role of the encoder in U-Net?
The **downsampling path**: convolution + pooling progressively **reduce resolution** while building **context and high-level features** ("what is in the image"). Like compressing a photo into a summary.

Medium

1. How did LeNet prove CNNs were better than traditional ML methods?
On MNIST, LeNet-5, trained **end to end on raw pixels**, matched or beat the best traditional methods of the time (k-NN, SVMs on hand-crafted features) at about 0.95% error. It **learned its own features** (strokes, edges) instead of relying on human-designed ones, and was far faster to run. This led to real deployments reading cheques and post. *(Nuance: the best SVMs were close on MNIST. The decisive gap appeared with large, complex images, e.g. AlexNet on ImageNet. See nb 02.)*

2. Why was GPU training critical for AlexNet's success?
Training a CNN is **millions of independent multiply-adds** (every kernel at every position, for 1.2 M images, over many epochs). GPUs have **thousands of parallel cores**, so they ran this **many times faster** than CPUs. AlexNet (about 61 M parameters) trained in about a week on two GTX 580 GPUs. On CPUs it would have taken months, making the model impractical. → nb 02 (timing demo)

3. Compare accuracy before and after AlexNet on ImageNet.
Before (2011, hand-crafted features): about **74% top-5 accuracy** (about 26% error). **AlexNet (2012): about 85%** (15.3% error), a jump of more than 10 points in one year. The course notes summarise it as "~70% → ~85%+".

4. Why does stacking small filters (like 3×3 in VGG) improve performance?
1. **Same receptive field, fewer parameters:** two 3×3 layers see 5×5, and three see 7×7, using $27C^2$ weights instead of $49C^2$ (about 45% fewer). 2. **More non-linearity:** each layer adds a ReLU, so three layers give three non-linearities instead of one, and the network can learn more complex features. 3. The **simple, uniform** design makes deeper networks easier to build. → nb 02 (receptive-field demo)

5. How do residual connections help gradient flow in ResNet?
Output = F(x) + x, so the gradient is $\partial out/\partial x = F'(x) + 1$. The "+1" from the identity path passes the gradient straight back through every block, even when F′(x) is tiny. In a plain net the gradient is a **product** of many small factors and vanishes. → nb 03 (plain 52-layer net: gradient at layer 1 = 0; residual: about 0.02)

6. What is the difference between direct mappings and residuals?
- A **direct mapping**: the layers must learn the full desired output **H(x)** themselves. - A **residual**: the layers learn only the **difference** F(x) = H(x) − x, and the input is added back.

Learning "change nothing" is easy for a residual block (F = 0) but hard for a plain one (it must learn the identity). So adding residual layers never makes the network worse.

7. Why is EfficientNet more efficient than simply making networks deeper or wider?
Depth, width and resolution **depend on each other**. Higher resolution needs more depth (a larger receptive field) and more width (more fine-grained features). Scaling just one hits **diminishing returns**: lots of extra computation for little accuracy. **Compound scaling** grows all three in a fixed, balanced ratio ($\alpha = 1.2$, $\beta = 1.1$, $\gamma = 1.15$; each φ step about doubles FLOPs), so extra compute goes where it helps most. EfficientNet-B7 matched the best accuracy of its time with about 8× fewer parameters.

8. Give one real-world application of ResNet.
Medical imaging, e.g. classifying chest X-rays (pneumonia), skin-lesion images or retinal scans, usually an ImageNet-pretrained ResNet fine-tuned on medical data. ResNet is also the **backbone** of Faster/Mask R-CNN and of face-recognition models.

9. Give one real-world application of EfficientNet.
On-device mobile vision, e.g. a phone app that identifies plant diseases, food or products from the camera in real time, without a server. Also drones and embedded cameras.

10. Why is R-CNN slow compared to YOLO?
R-CNN generates about **2,000 region proposals** per image and runs the CNN **separately on**

each (plus a separate classification/regression stage), so it's thousands of forward passes per image. YOLO does **one** forward pass for the whole image. → nb 04

11. How does YOLO treat detection differently from R-CNN?
R-CNN is **two-stage**: propose regions, then classify each. YOLO is **one-stage**: it treats detection as a **single regression problem**. The image is divided into an S×S grid, and each cell directly predicts boxes, confidence and class probabilities in one pass, using **global context** from the whole image.

12. Why is SSD better at detecting objects of different sizes?
It makes predictions from **multiple feature maps at different scales**. Early, high-resolution maps (small cells) detect **small** objects, and later, low-resolution maps (big cells) detect **large** ones, each with default boxes of several shapes. So a small cat and a large cat in one image are both found in a single pass. → nb 04

13. Which detection architecture for medical imaging, and why?
The **R-CNN family** (Faster R-CNN, or **Mask R-CNN** for exact outlines). Medical tasks need **high accuracy and precise localization**, missing a tumour (a false negative) is unacceptable, and analysis is **offline**, so speed matters less. Example: finding small tumours in MRI scans.

14. Which detection architecture for autonomous driving, and why?
YOLO (or SSD). Cars need **real-time** detection (30+ fps) of pedestrians, vehicles and signs. YOLO's single pass is fast enough, and a slightly less precise box *now* beats a perfect one too late. SSD balances speed with multi-scale accuracy (distant small cars).

15. What challenge does semantic segmentation face compared to classification?
It needs both **context** (*what* is it?, which requires a large receptive field) **and precision** (*exactly where* is each boundary?, which requires fine spatial detail). Downsampling helps the first and destroys the second. Classification needs only one label per image, so it can discard spatial detail freely. Segmentation also needs pixel-level labels, which are expensive to annotate.

16. How does FCN differ from traditional CNNs in its output?
A traditional CNN ends with **fully connected layers** that output **one label for the whole image** (spatial layout lost). An FCN replaces them with **convolutional layers** and outputs a **dense pixel-wise prediction map**, a class score for every pixel, for inputs of any size. → nb 05

17. Why are FCN predictions often coarse?
The network predicts at a **low resolution** after repeated pooling (e.g. 1/32 of the input), then simply **upsamples** that small map. Fine detail lost in pooling can't be recovered, so boundaries are blurry and small objects are missed. → nb 05 (FCN 77% vs U-Net 99% accuracy on boundary pixels)

18. How do skip connections in U-Net improve segmentation accuracy?
They **copy high-resolution feature maps from each encoder level** and **concatenate** them with the decoder at the same resolution. The decoder then gets back the **fine spatial details** (edges, exact positions) that pooling lost, combined with the **high-level context** from deep layers, which gives sharp, accurate boundaries and preserves small structures. They also help gradients flow.

19. What is the role of the decoder in U-Net?
The **upsampling path**: it gradually **increases the resolution** back to the input size (transposed convolutions or upsampling), combines the encoder's context with fine details from the skip connections, and produces the **pixel-level prediction**. The encoder learns *what*; the decoder learns *where*.

20. Why is U-Net widely used in medical imaging?
1. **Precise boundaries**: tumour, organ and cell outlines are needed for measurement and treatment planning. 2. Skip connections keep **small structures** (cells, lesions, vessels). 3. It **works with small datasets** (medical labels are scarce and expensive), especially with augmentation. 4. It's simple and fast to train, and handles 2-D and 3-D scans.

Hard

1. Explain how dropout improves generalization, with an example.
During training, dropout randomly zeros a fraction *p* of neurons each pass, so the network **can't depend on any single neuron or fixed co-adapted group**. It must spread knowledge redundantly and learn features that work even with parts missing, which are **robust features** that transfer to unseen data. It's like training many "thinned" networks and averaging them at test time, when all neurons are used and outputs are scaled accordingly. *Example:* a layer of 10 neurons with p = 0.3: about 3 are dropped each pass. If one neuron had learned "background is grass → it's a cow", it's sometimes absent, so other neurons must learn real cow features (shape, head), and the model then works on a cow on a beach. Like a team where random members sit out practice, so everyone learns to contribute. → nb 01 (dropout narrowed the train/test gap)

2. Why did AlexNet's use of ReLU help reduce the vanishing gradient problem?
Backpropagation multiplies the gradient by each layer's activation derivative. **Sigmoid's derivative is at most 0.25** (and near 0 when saturated), and tanh's also approaches 0 for large inputs, so through many layers the product **shrinks exponentially** ($0.25^{10} \approx 10^{-6}$). **ReLU's derivative is exactly 1 for positive inputs**, so the gradient passes through active units **without shrinking**, and it never saturates for positive values. ReLU is also cheap (no exponentials). AlexNet's ReLU network reached its target error about **6× faster** than with tanh. (Caveat: "dead" ReLUs have zero gradient for negative inputs.) → nb 01, 02

3. How does compound scaling in EfficientNet systematically balance depth, width and resolution?
With one user-chosen coefficient **φ** (how much more compute you can afford): - depth d = **α^φ**, width w = **β^φ**, resolution r = **γ^φ**, - subject to **α · β² · γ² ≈ 2** (with α ≥ 1, β ≥ 1, γ ≥ 1).

FLOPs scale with $d \cdot w^2 \cdot r^2$ (width and resolution affect cost quadratically), so each +1 in φ about **doubles the computation**. α, β, γ are found **once** by a small grid search on the baseline B0 (α = 1.2, β = 1.1, γ = 1.15) and then reused to produce B1–B7. Every dimension grows in proportion: higher resolution comes with the extra depth (receptive field) and width (fine features) it needs. → nb 03 (φ table)

4. Why do residual connections allow training very deep networks without degradation?
- **Gradient flow:** out = F(x) + x gives ∂out/∂x = F′(x) + 1. The identity term gives an

uninterrupted gradient highway, so gradients don't vanish across 100+ layers. - **Easy identity:** if extra layers aren't needed, a block just learns F(x) ≈ 0 and passes x through. A deeper ResNet can therefore always do *at least as well* as a shallower one, which removes the **degradation problem** (plain deep nets having higher *training* error than shallower ones). - In practice, combined with BatchNorm, this enabled 50/101/152 layers.

→ nb 03: plain 22- and 52-layer nets stuck at 10% (chance); residual nets of the same depth trained to 66–76%.

5. Compare the trade-off between accuracy and speed in R-CNN, YOLO and SSD.
| | Accuracy | Speed | Why | |---|---|---|---| | **R-CNN** (and Fast/Faster) | **highest**, esp. small objects and cluttered scenes | **slowest** (original R-CNN: tens of seconds per image) | two stages; CNN per region proposal; careful per-region classification and box refinement | | **YOLO** | lower, struggles with **small, crowded** objects and precise localization | **fastest, real-time** (45+ fps in the original) | one pass, coarse grid, few boxes per cell | | **SSD** | competitive; good across object sizes | fast (near real-time) | one pass + **multi-scale** feature maps and default boxes |

Choose by application: accuracy-critical and offline (medical) → R-CNN family; real-time (driving, video) → YOLO; balanced or mobile → SSD.

6. How would you adapt YOLO for detecting very small objects?
- **Higher input resolution** and/or a **finer grid** (more, smaller cells). - **Multi-scale prediction heads with a Feature Pyramid Network** (as in YOLOv3+): detect small objects on high-resolution feature maps. - **More / smaller anchor boxes**, with anchor sizes tuned (k-means) to the small objects in the dataset. - **Tiling / slicing** large images into overlapping crops (drones, satellites), then merging detections. - **Augmentation** (mosaic, copy-paste of small objects, zoom) and **loss re-weighting** for small boxes; avoid excessive early downsampling.

→ nb 04 shows a one-object-per-cell grid losing two small shapes that share a cell.

7. Why are skip connections critical in both ResNet and U-Net, though used differently?
Both send information **around** layers that would otherwise lose it: - **ResNet:** short skips within a block, **added** (F(x) + x). Purpose: **gradient flow and an easy identity**, so very deep networks train without degradation. - **U-Net:** long skips from each **encoder** level to the matching **decoder** level, **concatenated**. Purpose: restore the **fine spatial detail** lost by downsampling, giving precise boundaries (they also help gradients).

Shared principle: let later layers access earlier information directly. ResNet uses it to make *depth* trainable; U-Net uses it to make *pixel precision* possible.

8. How does the encoder–decoder structure in U-Net ensure both context and precision?
- The **encoder** downsamples step by step: each level sees a wider area, building **context** (what the region is: tumour vs tissue). - The **decoder** upsamples back to full resolution to produce a per-pixel map. - At every level, **skip connections** hand the decoder the **high-resolution encoder features** (edges, exact positions), so it combines *what* (deep context) with *where* (shallow detail).

"Encoder compresses for context, decoder reconstructs for precision, skips bridge the two." Example: the encoder recognises that a region is a tumour, and the skips restore its exact boundary. → nb 05

9. Designing a segmentation model for satellite imagery: which architecture and why?
A **U-Net** (typically with an ImageNet-pretrained **ResNet/EfficientNet encoder**), because: - satellite targets (roads, rivers, field and building boundaries) are **thin structures** that need **pixel-level precision**, which U-Net's skip connections preserve, - the encoder's context separates look-alike classes (roof vs road, water vs shadow), - it trains well with limited labelled data and augmentation (rotations and flips are natural for overhead images).

Practicalities: handle huge images by **tiling** with overlap, use multispectral bands as extra input channels, and use Dice/IoU loss for class imbalance. If you must count or separate **individual** buildings or vehicles, use **Mask R-CNN** (instance segmentation) instead or as well.

10. How did the evolution LeNet → AlexNet → VGG → ResNet → EfficientNet shape the foundation for Vision Transformers?
- **LeNet:** learning features **end to end** from pixels. - **AlexNet: scale** (big data + GPUs) plus ReLU and dropout make large models trainable. ViTs depend on huge data and compute. - **VGG: depth** with simple, **repeated identical blocks**. A ViT is a stack of identical transformer blocks. - **ResNet: residual connections** (used in *every* transformer block) and normalization made very deep training reliable. - **EfficientNet:** systematic **scaling** of model size, data and resolution, which also guides how ViT sizes (Base, Large, Huge) are scaled.

ViT keeps this deep, residual, scaled-up recipe but replaces local convolutions with **global self-attention over patches**. The CNN lineage also motivated *why*: CNNs struggle with long-range dependencies, and ViT addresses that. Hybrid CNN + Transformer models continue the line. → nb 07

Mask R-CNN

1. What key limitation of traditional object detection does Mask R-CNN address?
Detectors output only **bounding boxes + labels**, which are rough rectangles. Many tasks need the **exact pixel-level shape of each individual object** (**instance segmentation**). Mask R-CNN adds a mask for every detected object.

2. How does Mask R-CNN extend Faster R-CNN?
It keeps Faster R-CNN (backbone + RPN + classification and box regression) and adds a **parallel mask branch**: a small FCN that predicts a **binary mask for each Region of Interest**. It also replaces **RoI Pooling with RoI Align** for pixel-accurate features.

3. What role does the Region Proposal Network (RPN) play?
It slides over the shared feature map and **proposes candidate object regions** (boxes + "objectness" scores) using anchor boxes. These proposals are what the later heads classify, refine and mask. It replaces slow external proposal methods (selective search) and shares computation with the backbone.

4. Why was RoI Align introduced, and how does it improve on RoI Pooling?
RoI Pooling **rounds (quantizes)** the proposal's fractional coordinates, and its sub-bins, to

whole feature-map cells. This misaligns the extracted features with the actual object, which is harmless for boxes but bad for **pixel-accurate masks** (one feature cell can be 16+ image pixels). **RoI Align removes all rounding**: it samples the feature map at the exact fractional positions with **bilinear interpolation**, so features line up with the object and mask accuracy improves noticeably. → nb 05 (numeric demo)

5. What are the three outputs produced for each detected object?
1. **Bounding box** (where). 2. **Class label** (what). 3. **Pixel-level mask** (its exact shape).

6. Why are pixel-level masks more useful than bounding boxes in medical imaging?
1. **Precise localization:** tumours and organs are irregular, and a box includes healthy tissue. 2. **Quantitative analysis:** masks give the true **area and volume** (e.g. tumour volume for chemotherapy dosage), while boxes overestimate. 3. **Clinical decisions:** surgery and radiotherapy planning and disease monitoring need exact borders and spread. 4. **Overlaps:** masks separate structures within structures (a tumour inside an organ).

7. Give two real-world applications of Mask R-CNN outside medical imaging.
Any two of: - **autonomous driving** (pedestrian, vehicle and lane shapes) - **crowd analysis** (separating overlapping people) - **robotics grasping** (exact object outline) - **photo/video editing** (cut out a person, background replacement) - **agriculture** (individual fruit or leaf counting) - **retail** (products on shelves) - **satellite imagery** (individual buildings)

8. How does Mask R-CNN handle overlapping objects in crowded scenes?
Each object is a separate **RoI proposal**, and each RoI gets **its own class and its own binary mask**, predicted inside its own box. Overlapping people become separate instances with separate masks, even where they touch. Masks are predicted **per class and independently** (no competition between classes), and NMS removes duplicate proposals of the same object. Semantic segmentation would merge them into one "person" blob. → nb 05 (touching-coins demo)

Sequence modeling for video (CNN + LSTM)

9. Why can't CNNs alone capture temporal dependencies in video?
A CNN processes **each frame independently** and has no memory of previous frames and no notion of order. It can recognise *what* is in a frame (a hand) but not *how* it changes (a wave). Shuffle the frames and a per-frame CNN gives the same answers. → nb 06 (order-blind models fail to tell left from right)

10. What specific problem do LSTMs solve compared to vanilla RNNs?
The **vanishing gradient** problem over long sequences, which gives RNNs only **short-term memory**. LSTMs add a **cell state** and **gates**, so information (and gradient) can be carried across many time steps: **long-term dependencies**. → nb 06 (at 50 steps: RNN 25% = chance, LSTM 99.8%)

11. Explain the input, forget and output gates.
Each gate is a sigmoid layer giving values from 0 to 1: - **Forget gate**: decides what **past information to discard** from the cell state (1 = keep, 0 = erase). - **Input gate**: decides what **new information to store** in the cell state. - **Output gate**: decides what part of the memory to **pass forward** as the hidden state / output now.

$c_t = f \odot c_{t-1} + i \odot \tilde{c}_t$; $h_t = o \odot \tanh(c_t)$.

12. In a CNN + LSTM pipeline, what does each component contribute?
- **CNN:** extracts **spatial features** from each frame (objects, shapes, edges, textures): the *what*. - **LSTM:** processes the **sequence** of per-frame feature vectors and models **temporal dependencies** (motion, order, speed, rhythm): the *how / when*. - **Output layer:** predicts the action or gesture class.

"Photographer (CNN) + storyteller (LSTM)."

13. Give an example of an application where CNN + LSTM is essential.
Gesture or sign-language recognition: the CNN detects the hand shape in each frame, and the LSTM recognises the movement sequence ("wave", "swipe", a sign). Others: action recognition in sports or surveillance ("throwing a ball"), video captioning, predicting pedestrian motion for self-driving cars.

14. How does sequence modeling enable gesture recognition compared to static image classification?
A gesture is defined by **movement over time**, while a single frame only shows a **pose**: "raising a hand" and "waving" can share the same frame, and "swipe left" vs "swipe right" contain the same frames in **reverse order**. A static classifier sees one frame and can't tell them apart. A sequence model (LSTM) remembers previous frames and recognises the **trajectory, order and speed** of the motion. → nb 06

RNNs vs LSTMs

15. What is the vanishing gradient problem, and why does it affect RNNs more than LSTMs?
During backpropagation (through time), the gradient is **multiplied by a factor at each step or layer**. If those factors are < 1 (tanh derivatives, small recurrent weights) it **shrinks exponentially**, so early inputs get almost no learning signal and the model "forgets" them. A vanilla RNN passes its memory through **tanh and the same weight matrix at every step**, so after 20–50 steps the gradient vanishes. An LSTM updates its cell state **additively** ($f \odot c + i \odot \tilde{c}$). When the forget gate is about 1, memory and gradient flow through almost unchanged (the "constant error carousel"). → nb 06 (gradient reaching step 1: RNN 4e-14 vs LSTM 4e-5)

16. Compare RNNs and LSTMs in terms of memory and best use cases.
| | RNN | LSTM | |---|---|---| | Memory | **short-term** (recent steps) | **long-term** (long dependencies) | | Gradient | vanishes over long sequences | gates largely solve it | | Cost | small, fast | about 4× parameters, slower | | Best for | short, simple sequences | long, complex sequences: video, paragraphs, speech | | Example | next word in a short sentence | context across a long paragraph or video |

17. Why are LSTMs better suited for variable-length sequences like video?
Both process one step at a time with shared weights, so any length is *possible*. But only the LSTM keeps relevant information over **long and varying spans**: the gates learn what to keep and what to forget regardless of clip length, so a 10-second gesture is handled as well as a 2-second one. An RNN's memory fades after a few steps, so longer clips lose their beginning.

18. Give an example of a task where RNNs might still be sufficient instead of LSTMs.
Short sequences where only recent context matters: **predicting the next character in short**

words, **smoothing or forecasting a sensor reading from the last few values**, **predicting the next note from the last few notes**, or a simple short-gesture detector over a handful of frames. RNNs are smaller and faster there. (GRUs are a lighter middle ground.)

Vision Transformers & Attention

19. What is the purpose of Query, Key and Value in attention?
Each token produces three learned vectors: - **Query** = *what I'm looking for*, - **Key** = *what I contain / can be matched on*, - **Value** = *the information I pass on*.

Attention compares each **Query with all Keys** (dot products) to get similarity scores, normalizes them with softmax into weights, and outputs the **weighted sum of the Values**: each token gathers information from the tokens most relevant to it. Attention(Q, K, V) = softmax($QK^T/\sqrt{d}$)·V. Example: "bank" attends to "river" or "money" to resolve its meaning. → nb 07

20. Why does splitting an image into patches help ViTs capture global context?
1. It turns the image into a **sequence of tokens** (like words), so the transformer's **self-attention** can relate **any patch to any other**, even far-apart ones, **from the first layer**. A CNN neuron only sees a small local window and needs many layers to connect distant regions. 2. It **reduces complexity**: attention cost grows with the square of the sequence length, and 196 patches instead of about 50,000 pixels makes it feasible. 3. It **balances local and global**: each patch embedding holds local detail, and attention across patches builds the global picture (e.g. stripes across a zebra's body).

CV Weeks 2–3 · Cheat Sheet

Building blocks

Term	One-liner
Conv layer	slides **learned** kernels over the image → feature maps · few parameters (shared weights) · keeps spatial layout · translation invariant
FC (dense) layer	every neuron sees every input · flattens (loses *where*) · huge parameter count · used at the end for the decision
ReLU	max(0, x): negatives → 0 · non-linear, cheap, gradient = 1 for x > 0 → less vanishing gradient
Sigmoid / tanh	slopes ≤ 0.25 / ≤ 1 and ~0 when saturated → gradients vanish in deep nets
Dropout	randomly zero a fraction *p* of neurons **during training only** → robust features, less overfitting · 10 neurons, p = 0.3 → ~3 dropped · survivors × 1/(1−p)
Max pooling 2×2	keep the max of each 2×2 block → halves H and W, no parameters
Training loop	forward → loss → `loss.backward()` (gradients) → `optimizer.step()`
Overfitting	great on training data, worse on new data (a train–test gap)
Vanishing gradient	the gradient is a product of many small factors → early layers stop learning

CNN timeline

Model	Year	Key facts
LeNet-5	1998	**Yann LeCun** · digits / **MNIST** · cheques & post · conv → pool → conv → pool → FC → FC · ~60 K params · proof of concept
AlexNet	2012	won **ImageNet** by a huge margin (top-5 error ~26% → **15.3%**) · **5 conv + 3 FC** · ~61 M params · **ReLU, dropout, GPU** · sparked the deep-learning revolution
VGG	2014	Oxford **Visual Geometry Group** · **16–19 layers** · only **3×3** filters · 2×3×3 = 5×5 view, 3×3×3 = 7×7 view with fewer params + more ReLUs · baseline · ~138 M params
ResNet	2015	solves **vanishing gradient / degradation** · **skip connections**: out = F(x) + x · learns the **residual** · gradient F′(x) + **1** · 50 / 101 / **152** layers · used in medical imaging
EfficientNet	2019	**compound scaling**: depth α^φ, width β^φ, resolution γ^φ, α·β²·γ² ≈ 2 (1.2, 1.1, 1.15) · B0 (5.3 M) beats ResNet-50 (25.6 M) · mobile apps
MobileNet	2017	depthwise-separable conv (per-channel K×K + 1×1 mix) → ~8–9× fewer weights · phones

Object detection = what + where (class + box for every object)

	R-CNN (2014)	YOLO (2016)	SSD (2016)
Stands for	Region-based CNN	You Only Look Once	Single Shot MultiBox Detector
How	~2,000 region proposals → CNN on **each** → classify + refine	**one pass**: S×S grid predicts boxes + classes (a regression problem)	one pass, predictions from **multi-scale feature maps** + default boxes
Speed / accuracy	slow / **most accurate**	**real-time** / weaker on small, crowded objects	fast / good across sizes
Use for	**medical** (accuracy > speed)	**driving**, video (speed > accuracy)	mobile, balanced
- **IoU** = overlap / union (≥ 0.5 = correct box) · **NMS** = keep the best box, drop overlapping duplicates.			
- Fast R-CNN: CNN once, crop the feature map · Faster R-CNN: **RPN** proposes regions.			
- Small objects in YOLO: higher resolution, finer grid, multi-scale heads (FPN), small anchors, tiling, augmentation.			

Segmentation = a label for every pixel

- **Semantic:** class per pixel (touching objects merge) · **Instance:** separate mask per object.
- Challenge: needs **context** (what) **and precision** (where).
- **FCN:** FC → conv layers · dense pixel map · any input size · **coarse** (predicts at low resolution, then upsamples).
- **U-Net (2015): encoder** (downsample → context) + **decoder** (upsample, transposed conv → precision) + **skip connections** (copy + concatenate encoder maps → fine detail) · standard in **medical imaging** (precise boundaries, small structures, small datasets) · also satellite imagery.
- **Mask R-CNN (2017):** Faster R-CNN + **mask branch** per RoI · **RPN** proposes regions · **RoI Align** (bilinear, no rounding) replaces RoI Pooling · outputs **box + class + mask** · handles overlapping objects (one mask per RoI) · masks give the true size and volume in medicine.
- Skip connections: ResNet **adds** (gradient flow, depth) · U-Net **concatenates** (spatial detail).

Sequences & video

- Video = **spatial** (what's in each frame → **CNN**) + **temporal** (how it changes → **RNN / LSTM**).
- **RNN:** hidden state $h_t = \tanh(W x_t + U h_{t-1})$ · **short-term** memory · vanishing gradients over long sequences.
- **LSTM:** cell state + gates · **forget** (discard), **input** (store), **output** (pass on) · $c_t = f \odot c_{t-1} + i \odot \tilde{c}$ · **long-term** memory · variable length.
- **CNN + LSTM:** CNN features per frame → LSTM over time → class (gesture, action, captioning, driving).
- RNN is still enough for short sequences (next character, last few sensor readings).

	RNN	LSTM
Memory	short-term	long-term
Problem	vanishing gradients	solves them
Best for	simple, short	complex, long (video, paragraphs)

Attention & Vision Transformers

- **$\text{Attention}(Q, K, V) = \text{softmax}(QK^T / \sqrt{d}) \cdot V$** · **Query** = what I look for · **Key** = what I offer · **Value** = what I pass on → output = weighted sum.
- **ViT (2020):** split into **patches** (e.g. 16×16 → 224^2 image = 196 tokens) → flatten + **linear embedding** + **position embedding** + **[CLS]** token → transformer encoder (attention + MLP, **residual** connections) → classify from [CLS].
- Patches → image becomes a sequence; any patch can attend to any other from layer 1 (**global context**); shorter sequence = affordable; local detail stays inside each patch.
- CNN = local, built-in locality assumption, data-efficient · ViT = global, needs **large datasets**, scales well, hybrid models.
- Uses: classification, medical imaging, video (temporal attention), vision + language.