Index.cshtml

```
@model IEnumerable<ASPPractical3.Models.tblStud>

<p>
    @Html.ActionLink("Create New", "Create")
</p>
<table class="table">
    <tr>
        <th>
            @Html.DisplayNameFor(model => model.sid)
        </th>
        <th>
            @Html.DisplayNameFor(model => model.sname)
        </th>
        <th>
            @Html.DisplayNameFor(model => model.rollno)
        </th>
        <th></th>
    </tr>

@foreach (var item in Model) {
    <tr>
        <td>
            @Html.DisplayFor(modelItem => item.sid)
        </td>
        <td>
            @Html.DisplayFor(modelItem => item.sname)
        </td>
        <td>
            @Html.DisplayFor(modelItem => item.rollno)
        </td>
        <td>
            @Html.ActionLink("Edit", "Edit", new { id=item.sid }) |
            @Html.ActionLink("Details", "Details", new { id=item.sid }) |
            @Html.ActionLink("Delete", "Delete", new { id = item.sid })
        </td>
    </tr>
}

</table>
```

Details.cshtml

```
@model ASPPractical3.Models.tblStud

<div>
    <h4>tblStud</h4>
    <hr />
    <dl class="dl-horizontal">
        <dt>
            @Html.DisplayNameFor(model => model.sid)
        </dt>

        <dd>
            @Html.DisplayFor(model => model.sid)
        </dd>

        <dt>
            @Html.DisplayNameFor(model => model.sname)
        </dt>

        <dd>
            @Html.DisplayFor(model => model.sname)
        </dd>

        <dt>
            @Html.DisplayNameFor(model => model.rollno)
        </dt>

        <dd>
            @Html.DisplayFor(model => model.rollno)
        </dd>

    </dl>
</div>
<p>
    @Html.ActionLink("Edit", "Edit", new { id = Model.sid }) |
    @Html.ActionLink("Back to List", "Index")
</p>
```

Delete.cshtml

```
@model ASPPractical3.Models.tblStud

<h3>Are you sure you want to delete this?</h3>
<div>
    <h4>tblStud</h4>
    <hr />
    <dl class="dl-horizontal">
        <dt>
            @Html.DisplayNameFor(model => model.sid)
        </dt>

        <dd>
            @Html.DisplayFor(model => model.sid)
        </dd>

        <dt>
            @Html.DisplayNameFor(model => model.sname)
        </dt>

        <dd>
            @Html.DisplayFor(model => model.sname)
        </dd>

        <dt>
            @Html.DisplayNameFor(model => model.rollno)
        </dt>

        <dd>
            @Html.DisplayFor(model => model.rollno)
        </dd>

    </dl>

    @using (Html.BeginForm()) {
        @Html.AntiForgeryToken()

        <div class="form-actions no-color">
            <input type="submit" value="Delete" class="btn btn-default" /> |
            @Html.ActionLink("Back to List", "Index")
        </div>
    }
</div>
```

Edit.cshtml

```
@model ASPPractical3.Models.tblStud


@using (Html.BeginForm())
{
    @Html.AntiForgeryToken()

    <div class="form-horizontal">
        <h4>tblStud</h4>
        <hr />
        @Html.ValidationSummary(true, "", new { @class = "text-danger" })
        <div class="form-group">
            @Html.LabelFor(model => model.sid, htmlAttributes: new { @class = "control-label col-md-
2" })
            <div class="col-md-10">
                @Html.EditorFor(model => model.sid, new { htmlAttributes = new { @class = "form-
control" } })
                @Html.ValidationMessageFor(model => model.sid, "", new { @class = "text-danger" })
            </div>
        </div>

        <div class="form-group">
            @Html.LabelFor(model => model.sname, htmlAttributes: new { @class = "control-label col-
md-2" })
            <div class="col-md-10">
                @Html.EditorFor(model => model.sname, new { htmlAttributes = new { @class = "form-
control" } })
                @Html.ValidationMessageFor(model => model.sname, "", new { @class = "text-danger" })
            </div>
        </div>

        <div class="form-group">
            @Html.LabelFor(model => model.rollno, htmlAttributes: new { @class = "control-label col-
md-2" })
            <div class="col-md-10">
                @Html.EditorFor(model => model.rollno, new { htmlAttributes = new { @class = "form-
control" } })
                @Html.ValidationMessageFor(model => model.rollno, "", new { @class = "text-danger"
})
            </div>
        </div>

        <div class="form-group">
            <div class="col-md-offset-2 col-md-10">
                <input type="submit" value="Save" class="btn btn-default" />
            </div>
        </div>
    </div>
}

<div>
    @Html.ActionLink("Back to List", "Index")
</div>

@section Scripts {
    @Scripts.Render("~/bundles/jqueryval")
}
```

Create.cshtml

```
@model ASPPractical3.Models.tblStud


@using (Html.BeginForm())
{
    @Html.AntiForgeryToken()

    <div class="form-horizontal">
        <h4>tblStud</h4>
        <hr />
        @Html.ValidationSummary(true, "", new { @class = "text-danger" })
        <div class="form-group">
            @Html.LabelFor(model => model.sid, htmlAttributes: new { @class = "control-label col-md-
2" })
            <div class="col-md-10">
                @Html.EditorFor(model => model.sid, new { htmlAttributes = new { @class = "form-
control" } })
                @Html.ValidationMessageFor(model => model.sid, "", new { @class = "text-danger" })
            </div>
        </div>

        <div class="form-group">
            @Html.LabelFor(model => model.sname, htmlAttributes: new { @class = "control-label col-
md-2" })
            <div class="col-md-10">
                @Html.EditorFor(model => model.sname, new { htmlAttributes = new { @class = "form-
control" } })
                @Html.ValidationMessageFor(model => model.sname, "", new { @class = "text-danger" })
            </div>
        </div>

        <div class="form-group">
            @Html.LabelFor(model => model.rollno, htmlAttributes: new { @class = "control-label col-
md-2" })
            <div class="col-md-10">
                @Html.EditorFor(model => model.rollno, new { htmlAttributes = new { @class = "form-
control" } })
                @Html.ValidationMessageFor(model => model.rollno, "", new { @class = "text-danger"
})
            </div>
        </div>

        <div class="form-group">
            <div class="col-md-offset-2 col-md-10">
                <input type="submit" value="Create" class="btn btn-default" />
            </div>
        </div>
    </div>
}

<div>
    @Html.ActionLink("Back to List", "Index")
</div>

@section Scripts {
    @Scripts.Render("~/bundles/jqueryval")
}
```

tblStudsController.cs

```
using System;
using System.Collections.Generic;
using System.Data;
using System.Data.Entity;
using System.Data.Entity.Infrastructure;
using System.Linq;
using System.Net;
using System.Net.Http;
using System.Web.Http;
using System.Web.Http.Description;
using ASPPractical3.Models;

namespace ASPPractical3.Controllers
{
    public class tblStudsController : ApiController
    {
        private StudDBEntities db = new StudDBEntities();

        // GET: api/tblStuds
        public IQueryable<tblStud> GettblStuds()
        {
            return db.tblStuds;
        }

        // GET: api/tblStuds/5
        [ResponseType(typeof(tblStud))]
        public IHttpActionResult GettblStud(int id)
        {
            tblStud tblStud = db.tblStuds.Find(id);
            if (tblStud == null)
            {
                return NotFound();
            }

            return Ok(tblStud);
        }

        // PUT: api/tblStuds/5
        [ResponseType(typeof(void))]
        public IHttpActionResult PuttblStud(int id, tblStud tblStud)
        {
            if (!ModelState.IsValid)
            {
                return BadRequest(ModelState);
            }

            if (id != tblStud.sid)
            {
                return BadRequest();
            }

            db.Entry(tblStud).State = EntityState.Modified;

            try
            {
                db.SaveChanges();
            }
            catch (DbUpdateConcurrencyException)
            {
                if (!tblStudExists(id))
                {
                    return NotFound();
                }
                else
                {
                    throw;
```

```
                }
            }

            return StatusCode(HttpStatusCode.NoContent);
        }

        // POST: api/tblStuds
        [ResponseType(typeof(tblStud))]
        public IHttpActionResult PosttblStud(tblStud tblStud)
        {
            if (!ModelState.IsValid)
            {
                return BadRequest(ModelState);
            }

            db.tblStuds.Add(tblStud);

            try
            {
                db.SaveChanges();
            }
            catch (DbUpdateException)
            {
                if (tblStudExists(tblStud.sid))
                {
                    return Conflict();
                }
                else
                {
                    throw;
                }
            }

            return CreatedAtRoute("DefaultApi", new { id = tblStud.sid }, tblStud);
        }

        // DELETE: api/tblStuds/5
        [ResponseType(typeof(tblStud))]
        public IHttpActionResult DeletetblStud(int id)
        {
            tblStud tblStud = db.tblStuds.Find(id);
            if (tblStud == null)
            {
                return NotFound();
            }

            db.tblStuds.Remove(tblStud);
            db.SaveChanges();

            return Ok(tblStud);
        }

        protected override void Dispose(bool disposing)
        {
            if (disposing)
            {
                db.Dispose();
            }
            base.Dispose(disposing);
        }

        private bool tblStudExists(int id)
        {
            return db.tblStuds.Count(e => e.sid == id) > 0;
        }
    }
}
```

StudentController.cs

```
using ASPPractical3.Models;
using Newtonsoft.Json;
using System;
using System.Collections.Generic;
using System.Linq;
using System.Net.Http;
using System.Text;
using System.Threading.Tasks;
using System.Web;
using System.Web.Mvc;

namespace ASPPractical3.Controllers
{
    public class StudentController : Controller
    {
        StudDBEntities obj = new StudDBEntities();

        // GET: Student
        public ActionResult Index()
        {
            List<tblStud> students = null;

            using (var client = new HttpClient())
            {
                client.BaseAddress = new Uri("http://localhost:44379/api/");
                //HTTP GET
                var responseTask = client.GetAsync("tblStuds");
                responseTask.Wait();

                var result = responseTask.Result;
                if (result.IsSuccessStatusCode)
                {
                    var readTask = result.Content.ReadAsAsync<List<tblStud>>();
                    readTask.Wait();

                    students = readTask.Result;
                }
            }

            return View(students.ToList());
        }

        // GET: Student/Details/5
        public ActionResult Details(int id)
        {
            tblStud students = null;

            using (var client = new HttpClient())
            {
                client.BaseAddress = new Uri("http://localhost:44379/api/tblStuds/");
                //HTTP GET
                var responseTask = client.GetAsync(id.ToString());
                responseTask.Wait();

                var result = responseTask.Result;
                if (result.IsSuccessStatusCode)
                {
                    var readTask = result.Content.ReadAsAsync<tblStud>();
                    readTask.Wait();

                    students = readTask.Result;
                }
            }
```

```
            return View(students);
        }


        // GET: Student/Create
        public ActionResult Create()
        {
            return View();
        }

        // POST: Student/Create
        [HttpPost]
        public ActionResult Create(tblStud sobj)
        {
            try
            {
                // TODO: Add insert logic here
                HttpClient client = new HttpClient();
                var JsonData = JsonConvert.SerializeObject(sobj);
                HttpContent data = new StringContent(JsonData,
                    Encoding.UTF8, "application/json");

                var restul = client
                    .PostAsync("http://localhost:44379/api/tblStuds/", data).ToString();

                return RedirectToAction("Index");
            }
            catch
            {
                return View();
            }
        }

        // GET: Student/Edit/5
        public ActionResult Edit(int id)
        {
            tblStud students = null;

            using (var client = new HttpClient())
            {
                client.BaseAddress = new Uri("http://localhost:44379/api/tblStuds/");
                //HTTP GET
                var responseTask = client.GetAsync(id.ToString());
                responseTask.Wait();

                var result = responseTask.Result;
                if (result.IsSuccessStatusCode)
                {
                    var readTask = result.Content.ReadAsAsync<tblStud>();
                    readTask.Wait();

                    students = readTask.Result;
                }
            }

            return View(students);
        }

        // POST: Student/Edit/5
        [HttpPost]
        public ActionResult Edit(int id, tblStud sobj)
        {
            try
            {
                // TODO: Add update logic here

                tblStud students = null;
```

```
                using (var client = new HttpClient())
                {
                    client.BaseAddress = new Uri("http://localhost:44379/api/tblStuds/");
                    //HTTP PUT

                    var JsonData = JsonConvert.SerializeObject(sobj);
                    HttpContent data = new StringContent(JsonData,
                        Encoding.UTF8, "application/json");

                    var responseTask = client.PutAsync(id.ToString(),data);
                    responseTask.Wait();

                    var result = responseTask.Result;
                    if (result.IsSuccessStatusCode)
                    {
                        var readTask = result.Content.ReadAsAsync<tblStud>();
                        readTask.Wait();

                        students = readTask.Result;
                    }
                }

                return RedirectToAction("Index");
            }
            catch
            {
                return View();
            }
        }

        // GET: Student/Delete/5
        public ActionResult Delete(int id)
        {
            tblStud students = null;

            using (var client = new HttpClient())
            {
                client.BaseAddress = new Uri("http://localhost:44379/api/tblStuds/");
                //HTTP GET
                var responseTask = client.GetAsync(id.ToString());
                responseTask.Wait();

                var result = responseTask.Result;
                if (result.IsSuccessStatusCode)
                {
                    var readTask = result.Content.ReadAsAsync<tblStud>();
                    readTask.Wait();

                    students = readTask.Result;
                }
            }

            return View(students);
        }

        // POST: Student/Delete/5
        [HttpPost]
        public ActionResult Delete(int id, FormCollection collection)
        {
            try
            {
                // TODO: Add delete logic here

                tblStud students = null;

                using (var client = new HttpClient())
                {
                    client.BaseAddress = new Uri("http://localhost:44379/api/tblStuds/");
```

```
                    //HTTP GET
                    var responseTask = client.DeleteAsync(id.ToString());
                    responseTask.Wait();

                    var result = responseTask.Result;
                    if (result.IsSuccessStatusCode)
                    {
                        var readTask = result.Content.ReadAsAsync<tblStud>();
                        readTask.Wait();

                        students = readTask.Result;
                    }
                }

                return RedirectToAction("Index");
            }
            catch
            {
                return View();
            }
        }
    }
}
```

Output

Application name Home About Contact

tblStud

sid 1

sname Darshit

rollno 2

Create

Back to List

© 2021 - My ASP.NET Application

Application name Home About Contact

Create New

sid	sname	rollno	
1	Darshit	2	Edit | Details | Delete
2	John	3	Edit | Details | Delete

© 2021 - My ASP.NET Application

Application name Home About Contact

tblStud

sid	2
sname	John
rollno	3

Edit | Back to List

© 2021 - My ASP.NET Application

Application name Home About Contact

tblStud

sid	2
sname	John Deo
rollno	3

Save

Back to List

© 2021 - My ASP.NET Application

Application name Home About Contact

Are you sure you want to delete this?

tblStud

sid	1
sname	Darshit
rollno	2

Delete | Back to List

© 2021 - My ASP.NET Application