

Save file at /usr/local/bin/show-port-status
Open file sudo nano /usr/local/bin/show-port-status
To make file runnable run: sudo chmod +x /usr/local/bin/show-port-status
Transfer script to file show-port-status > /var/log/port-status.txt
To view the file: sudo nano /var/log/port-status.txt

BELOW SCRIPT TO BE WRITTEN ON EACH SWITCH

```
#####  
# Switch status and Port configuration report  
# Custom OVS audit script to emulate a Cisco Catalyst-style switch  
# Author: Duane Van Itallie  
#####  
  
# Align port details  
COLW=22  
  
# Show hostname of the switch  
echo "### SWITCH NAME ###"  
hostname  
  
# Show switch timezone  
echo -e "\n### TIMEZONE ###"  
timedatectl | grep "Time zone"  
  
# Show if RSTP, STP and multicasting snooping is enabled  
echo -e "\n### BRIDGE (RSTP, LLDP) ###"  
ovs-vsctl list bridge | egrep "name|rstp_enable|stp_enable|mcast_snooping_enable"  
  
# Check if LLDP is running  
lldp_status=$(systemctl is-active lldpd 2>/dev/null)  
cdp_enabled='Disabled'  
if grep -q "\-c" /etc/default/lldpd 2>/dev/null; then  
    cdp_enabled='Enabled'  
fi  
  
if [ "$lldp_status" = "active" ]; then  
    echo "LLDP/CDP Status: LLDP Enabled, CDP $cdp_enabled"  
else  
    echo "LLDP/CDP Status: LLDP Disabled, CDP $cdp_enabled"  
fi  
  
# Display port titles  
echo -e "\n### PORTS (VLANs, trunks, speed limits, LLDP) ###"  
  
# Loop through all OVS ports in sorted order  
for i in $(ovs-vsctl list-ports br0 | sort -V); do  
    echo -e "\n### $i ###"  
  
# Extract port fields manually (to align responses in final report)  
port_name=$(ovs-vsctl get port $i name 2>/dev/null | tr -d '')
```

```

port_tag=$(ovs-vsctl get port $i tag 2>/dev/null | tr -d ' ')
port_trunks=$(ovs-vsctl get port $i trunks 2>/dev/null | tr -d ' ')

printf "%-${COLW}s : %s\n" "Name" "${port_name:-None}"
printf "%-${COLW}s : %s\n" "VLAN Tag" "${port_tag:-None}"
printf "%-${COLW}s : %s\n" "Trunks" "${port_trunks:-None}"

# Show the port speed limit set via QoS (if configured)
qos_uuid=$(ovs-vsctl get port $i qos 2>/dev/null)
if [ "$qos_uuid" != "[]" ] && [ -n "$qos_uuid" ]; then
    raw_rate=$(ovs-vsctl get qos $qos_uuid other-config:max-rate 2>/dev/null | tr
-d ' ')
    case "$raw_rate" in
        10000000) speed_label="10Mbps" ;;
        100000000) speed_label="100Mbps" ;;
        1000000000) speed_label="1Gbps" ;;
        10000000000) speed_label="10Gbps" ;;
        "") speed_label="Unlimited" ;;
        *) speed_label="${raw_rate}bps" ;;
    esac
else
    speed_label="Unlimited"
fi
printf "%-${COLW}s : %s\n" "Port Speed (QoS)" "$speed_label"

# Show port description (name)
port_desc=$(ovs-vsctl get interface $i external_ids:port-desc 2>/dev/null | tr -d
' ')
[ -z "$port_desc" ] && port_desc=$(ovs-vsctl get port $i external_ids:port-desc
2>/dev/null | tr -d ' ')
[ -z "$port_desc" ] && port_desc="None"
printf "%-${COLW}s : %s\n" "Port Description" "${port_desc:-None}"

# Show LLDP neighbour (short version)
if [ "$i" = "bond-ring" ]; then
    # Get bond members
    members=""
    for u in $(ovs-vsctl get port bond-ring interfaces | tr -d '[],'); do
        members="$members $(ovs-vsctl get interface "$u" name | tr -d ' ')"
    done

# One labelled line per bond member
found=0
for iface in $members; do
    nei=$(lldpcli show neighbors ports "$iface" 2>/dev/null \
| awk -F':' ' /SysName|System Name/ {gsub(/\^[ \t]+/, "", $2); print $2
exit}')
    if [ -n "$nei" ]; then
        printf "%-${COLW}s : %s -> %s\n" "LLDP Neighbour" "$iface" "$nei"
        found=1
    fi
fi

```

done

If no neighbour found on any member

[\$found -eq 0] && printf "%-\${COLW}s : %s\n" "LLDP Neighbour" "None"

else

Normal single-port LLDP

lldp_nei=\$(lldpcli show neighbors ports "\$i" 2>/dev/null \
| awk -F':' '/SysName|System Name/ {gsub(/^[\t]+/, "", \$2); print \$2;
exit}'))

[-z "\$lldp_nei"] && lldp_nei="None"

printf "%-\${COLW}s : %s\n" "LLDP Neighbour" "\$lldp_nei"

fi

Display local port MAC address

port_mac=\$(cat /sys/class/net/"\$i"/address 2>/dev/null)

if ["\$i" = "bond-ring"]; then

port_mac="bond-ring link"

elif [-z "\$port_mac"]; then

port_mac="None"

fi

printf "%-\${COLW}s : %s\n" "Port MAC" "\$port_mac"

done