

Access Control Policy

PrimeCore Minerals | Secure Multi Office Network

PC-03 | Version 0.1 | 23 September 2026

Status: Proposed policy for approval

Owner: IT Administrator | Approver: Project lead | Approval date: Pending

Define who may access PrimeCore systems, who approves access and how access is removed. This policy covers staff, contractors, service identities, cloud resources, network devices and shared information.

Required controls

- Use a unique named identity for each person. Keep administrative identities separate from ordinary work. Grant only the rights required for the current role and approved resource.
- Resource owners approve access before the administrator implements it. The requester must not approve their own privileged access. Record the requested role, resource, duration and business purpose.
- Use MFA for remote access and privileged services where supported. Prefer phishing resistant methods when the selected service supports them. Document service limitations and compensating controls.
- Store passwords in an approved password manager. Proposed baseline: unique passphrases of at least 15 characters where supported, block known compromised values, and change credentials after suspected compromise or an authorised reset. Do not share passwords or embed them in scripts.
- Service identities must have a named owner, narrow scope and a documented rotation and dependency plan. Use managed identities where available. Store recovery secrets separately from ordinary user access.

Access lifecycle

Event	Required action	Proposed target
Joiner	Manager confirms identity and role; data owner approves groups; administrator tests access	Before first access
Role change	Review old and new access together; remove superseded groups	At role change
Leaver	Disable access, revoke sessions where supported, recover devices and transfer data ownership	At agreed departure time; urgent on notice for immediate termination
Temporary access	Record sponsor and expiry; remove automatically where supported	At approved expiry
Emergency access	Record reason, custodian, use and post-event review	Review next working day

Permission governance and assurance

Role	Default entitlement	Restriction
Staff	Approved business applications and team files	No infrastructure administration
Contractor or visitor	Sponsored, time limited resources or guest Internet	No implied internal network rights
Network administrator	Named management systems from approved endpoint	Separate privileged account
Security analyst	Read relevant logs and incident records	No routine alteration of source records
Backup operator	Run approved backup and recovery actions	Restore disclosure requires data-owner approval

Authentication proves identity; authorisation determines which resource and operation that identity may use. Network reachability, VPN connection and domain membership must not be treated as permission to every share or management interface.

Monitoring and review

Review privileged membership monthly and all resource memberships each term or every three months, whichever is sooner. Owners must confirm continuing need. Retain access requests, approvals, effective permission tests and removal records in a restricted register. Use the proposed SEC-04 schedule for associated security logs.

Proposed ordinary-account lockout is 10 failures in 15 minutes with a 15 minute lockout, subject to supported settings and testing. The separate proposed authentication alert is five failures in five minutes. Neither threshold is proven by the existing R06 network block alert. Never unlock an account until identity and the failure source are checked. [S5]

Acceptance and evidence

The owner accepts implementation after one allowed and one denied test for each role, demonstrated leaver removal, a tested emergency account, and a documented exception register. PC-02 provides the test matrix. Record actual results rather than treating this policy as evidence of deployment.

Review and exceptions

The owner reviews this document every six months and after a significant incident or system change. Record exceptions with the affected asset, business reason, risk, compensating control, approver and expiry. Approval does not replace a successful implementation test.

References and linked artefacts

[S1] HQ Network Addressing Artefact.md, project deliverables, evidence dated 13 September 2026.


[S3] Security Test Results.md, project deliverables, 13 September 2026, tests T01 to T05 and their evidence limitations.

[S5] SEC-01 to SEC-05 procedures: 01_Network_Access_Procedure.docx; 02_Shared_File_Procedure.docx; 03 Notification Escalation Procedure.docx; 04 Logging Evidence Procedure.docx; 05 Authentication Lockout Procedure.docx. Proposed operating requirements are distinct from implemented controls.

Implementation Evidence

The following HQ configuration capture supports the network segmentation requirements in this policy. It records separate VLAN interfaces for employee, visitor, device, server, backup and management networks.

Figure E1 Brisbane HQ pfSense interface configuration showing VLAN tags and gateway addresses



Interface	Parent Adapter	VLAN Tag	Gateway Address
WAN (wan)	vtnet0	-	172.16.100.2/30
LAN (lan)	vtnet1	-	10.10.10.1/24
EMPLOYEE_VLAN (opt1)	vtnet2.10	10	192.168.10.1/24
VISITOR_VLAN (opt2)	vtnet2.20	20	192.168.20.1/24
EMPLOYEE_WIFI_VLAN (opt3)	vtnet2.11	11	192.168.11.1/24
PRINTER_VLAN (opt4)	vtnet2.30	30	192.168.30.1/24
VIDEO_VLAN (opt5)	vtnet2.40	40	192.168.40.1/24
CCTV_VLAN (opt6)	vtnet2.41	41	192.168.41.1/24
IOT_VLAN (opt7)	vtnet2.50	50	192.168.50.1/24
SERVER_VLAN (opt8)	vtnet2.90	90	192.168.90.1/24
BACKUP_VLAN (opt9)	vtnet2.91	91	192.168.91.1/24
MANAGEMENT_VLAN (opt10)	vtnet2.99	99	192.168.99.1/24


The VLAN interfaces use parent adapter vtnet2. Employee wired VLAN 10, employee Wi-Fi VLAN 11, visitor VLAN 20 and management VLAN 99 have gateways 192.168.10.1/24, 192.168.11.1/24, 192.168.20.1/24 and 192.168.99.1/24 respectively. The capture also shows printer, video, CCTV, IoT, server and backup interfaces. The untagged LAN is a separate interface on vtnet1 at 10.10.10.1/24.

This screenshot establishes the recorded HQ interface configuration. Firewall rules and permitted and denied traffic tests are required to demonstrate effective access restrictions. It does not establish Site A configuration, identity permissions, MFA enforcement or account lockout. Screenshot supplied by the project team on 3 October 2026. The capture itself does not display a capture date.

Mine Site A Interface Evidence

The Site A configuration uses the same VLAN tags as HQ with separate site subnets. This capture supports the policy requirement to separate employee, visitor, device, server, backup and management networks at the remote site.

Figure E2 Mine Site A pfSense VLAN interfaces and gateway addresses



WAN (wan)	-> vtnet0	-> v4: 172.16.101.2/30
SITEA_MGMT (lan)	-> vtnet1.99	-> v4: 192.168.199.1/24
SITEA_EMPLOYEE (opt1)	-> vtnet1.10	-> v4: 192.168.110.1/24
SITEA_EMP_WIFI (opt2)	-> vtnet1.11	-> v4: 192.168.111.1/24
SITEA_VISITOR (opt3)	-> vtnet1.20	-> v4: 192.168.120.1/24
SITEA_PRINTER (opt4)	-> vtnet1.30	-> v4: 192.168.130.1/24
SITEA_VIDEO (opt5)	-> vtnet1.40	-> v4: 192.168.140.1/24
SITEA_CCTV (opt6)	-> vtnet1.41	-> v4: 192.168.141.1/24
SITEA_IOT (opt7)	-> vtnet1.50	-> v4: 192.168.150.1/24
SITEA_SERVER (opt8)	-> vtnet1.90	-> v4: 192.168.190.1/24
SITEA_BACKUP (opt9)	-> vtnet1.91	-> v4: 192.168.191.1/24

The VLAN interfaces use parent adapter vtnet1. Management VLAN 99 uses 192.168.199.1/24, employee VLAN 10 uses 192.168.110.1/24, employee Wi-Fi VLAN 11 uses 192.168.111.1/24 and visitor VLAN 20 uses 192.168.120.1/24. Server VLAN 90 and backup VLAN 91 use 192.168.190.1/24 and 192.168.191.1/24. SITEA_MGMT is the renamed LAN interface. The WAN interface is vtnet0 at 172.16.101.2/30.

The capture records interface assignments and addressing. Firewall rules and permitted and denied traffic tests are still required to establish effective access restrictions. It does not demonstrate DHCP isolation, site-to-site VPN operation or successful remediation of the previously recorded DHCP incident. Screenshot supplied by the project team on 3 October 2026. The capture itself does not display a capture date.

HQ Employee Wi Fi Firewall Rules

The employee Wi-Fi rule list places R06 Block Employee WIFI Access to Management above the permitted traffic rules. R06 blocks IPv4 traffic from EMPLOYEE_WIFI_VLAN subnets to the MANAGEMENT_NETWORK alias. The displayed logging indicator supports recording matching blocks.

Figure E3 HQ employee Wi-Fi firewall rules showing R06 and permitted service traffic

Rules (Drag to Change Order)											
	States	Protocol	Source	Port	Destination	Port	Gateway	Queue	Schedule	Description	Actions
☐	0/0 B	IPv4 *	EMPLOYEE_WIFI_VLAN subnets	*	MANAGEMENT_NETWORK	*	*	none		R06 - Block Employee WIFI Access to Management	
☐	0/356 B	IPv4 ICMP any	EMPLOYEE_WIFI_VLAN subnets	*	*	*	*	none		TEMP - Employee wifi connection	
☐	0/759.19 MiB	IPv4 TCP	EMPLOYEE_WIFI_VLAN subnets	*	*	WEB_PORTS	*	none		R03a - Allow Employee WIFI Web Access	
☐	0/0 B	IPv4 TCP	EMPLOYEE_WIFI_VLAN subnets	*	PRINTER_NETWORK	PRINT_PORTS	*	none		R09b - Allow Employee WIFI for Printers	
☐	0/17.23 MiB	IPv4 TCP/UDP	EMPLOYEE_WIFI_VLAN subnets	*	*	DNS_PORT	*	none		R03b - Allow Employee WIFI DNS	
☐	1/22.19 MiB	IPv4 TCP	EMPLOYEE_WIFI	*	AD_SERVER	AD_TCP_PORTS	*	none			
☐	0/0 B	IPv4 UDP	EMPLOYEE_WIFI	*	AD_SERVER	AD_UDP_PORTS	*	none			


The list also contains a temporary ICMP allow rule, web access through WEB_PORTS, printer access through PRINT_PORTS, DNS through DNS_PORT and TCP/UDP access to AD_SERVER. The temporary ICMP rule permits traffic to any destination subject to preceding rules. Its removal or continued justification requires review. Several service rules also use any destination, so their presence alone does not establish that access is limited to approved servers.

This screenshot records configured IPv4 rules and their order. It does not reveal alias membership, establish IPv6 restrictions or demonstrate the outcome of a traffic test. The R06 counter shows 0 B in this capture. Matching blocked-traffic logs and endpoint test results are needed to show enforcement. Screenshot supplied by the project team on 3 October 2026. The capture itself does not display a capture date.

Employee Wi Fi Management Access Test

The HQ employee laptop attempted ICMP access to the firewall management address 192.168.99.1. The terminal reports 34 packets transmitted, zero received and 100% packet loss. The filtered firewall log in Figure E5 reports 34 matching blocked entries from 192.168.11.100 to that destination under R06.

Figure E4 HQ employee laptop ping test with 34 requests and no replies

A terminal window titled 'pc-admin@hq-emp-laptop: ~' with standard window controls. The terminal shows a ping command being executed: 'pc-admin@hq-emp-laptop:~\$ ping 192.168.99.1'. The output shows 'PING 192.168.99.1 (192.168.99.1) 56(84) bytes of data.' followed by a carriage return '^C'. Then it shows '--- 192.168.99.1 ping statistics ---' and '34 packets transmitted, 0 received, 100% packet loss, time 33791ms'. The prompt returns to 'pc-admin@hq-emp-laptop:~\$' with a cursor.


```
pc-admin@hq-emp-laptop:~$ ping 192.168.99.1
PING 192.168.99.1 (192.168.99.1) 56(84) bytes of data.
^C
--- 192.168.99.1 ping statistics ---
34 packets transmitted, 0 received, 100% packet loss, time 33791ms

pc-admin@hq-emp-laptop:~$
```

The failed ping alone does not identify the cause. The corresponding R06 log entries provide evidence that the firewall blocked the tested traffic. This test supports the management-access restriction for this source, destination and protocol.

R06 Firewall Enforcement Evidence

Figure E5 Filtered HQ firewall logs reporting 34 R06 ICMP blocks



The log identifies EMPLOYEE_WIFI_VLAN, source 192.168.11.100, destination 192.168.99.1 and rule R06 Block Employee WIFI Access to Management, tracker 1787829015. The visible entries are dated Oct 3, starting at 07:03:10. The screenshot displays a matched count of 34, with only part of the entry list visible. The displayed time zone is not established.

Together, Figures E4 and E5 demonstrate the tested ICMP restriction and local firewall logging. They do not establish restrictions for every management service, IPv6, other sources or all destinations in the management alias. They also do not establish central log ingestion or alert delivery for this test. Screenshots supplied by the project team on 3 October 2026.