

Open-Set Domain Adaptation through Self-Supervision

Daniele Rege Cambrin, Kylie Bedwell, Tommaso Natta, Ehsan Ansari Nejad
Politecnico di Torino
Corso Duca degli Abruzzi, 24
10129 Torino, ITALY

s290144@studenti.polito.it, s287581@studenti.polito.it
s282478@studenti.polito.it, s288903@studenti.polito.it

Abstract

- sentence describing the problem - sentence describing our proposed method - sentence summarising the results - sentence about the variations - sentence about the variation results

1. Introduction

In the computer vision research area large amounts of unlabeled data are available, however the cost of labeling this data is high [3]. Domain adaptation is one technique that can be used to exploit the unlabeled data by first training a model on labeled data from a different but similar domain (the *source* domain), and then applying this model to the unlabeled data (the *target* domain). This technique assumes the distribution of both source and target domains are similar and describe the same class labels, also known as the *closed-set* scenario [1]. When applied to real-world scenarios however it is possible that the target domain includes previously unseen classes, known as the *open-set* scenario. These extra class labels in the target domain will cause performance degradation of the classification model and should be identified and isolated. The problem thus consists of two steps: first separating the target domain into known and unknown samples; then conducting domain alignment between the source domain and the known samples of the target domain.

Self-supervised learning can be used to separate the known class samples in the target domain from the unknown samples. Self-supervised learning involves the transformation of data using a known transform (for example by using image rotation), then training a model to predict the transformation [5]. When used in an object classification task and considering the image rotation transformation, the correct orientation of an object is domain-invariant. In this way the model can be trained to predict the correct orientation of

the image using data from the source domain, then applied to the images of the target domain. If the orientation of a sample in the target domain is predicted correctly then it is considered to be of a *known* class. Contrarily if the orientation is not predicted correctly it is labelled as *unknown*.

Domain adaptation can then be performed between the samples in the source domain and the samples recognized as known in the target domain. When applying domain adaptation to an open-set scenario (Open-Set Domain Adaptation or OSDA) the samples classified as unknown can be treated as a separate class and incorporated into the Closed-Set Domain Adaptation (CSDA) task [2]. The self-supervised rotation task can also be used to reduce the domain shift during this step, using the Rotation-based Open Set (ROS) method developed by Bucci *et al.* [1].

This study investigates the use of a simplified ROS method for object classification on the *Office-Home* dataset [4]. Alternative self-supervised tasks **as well as the inclusion of center-loss** are also considered and their performance on the object classification task is evaluated.

2. Related Work

- what's been done in the past on this topic - Summarise each of the cited references - Cite some papers about the variations we did - other variations which might be interesting (but that we didn't do) - if space -

3. Method

- describe in detail the method used - the network used - include the diagrams here and explain them - explain the evaluation parameters that will be used

4. Experiments

- start with parameter tuning of learning rate and epochs, include graph to justify decision - ablation study: hyperparameter tuning of weights and threshold value, include graphs or tables of values

5. Variations

- describe each of the variations - present results of the performance of the model and compare with the baseline for each of the variations

6. Conclusions

- summarise the results - add future recommendations

6.1. Acknowledgements

The authors would like to thank Silvia Bucci for her assistance and guidance in completing this study.

References

- [1] Silvia Bucci, Mohammad Reza Loghmani, and Tatiana Tommasi. On the effectiveness of image rotation for open set domain adaptation. In *CVPR*, 2020. [1](#)
- [2] Pau Panareda Busto, Ahsan Iqbal, and Juergen Gall. Open set domain adaptation for image and action recognition. *IEEE*, 42(2):413–429, 2020. [1](#)
- [3] Gabriela Csurka. Domain adaptation for visual applications: A comprehensive survey. In *CVPR*, 2017. [1](#)
- [4] Hemanth Venkateswara, Jose Eusebio, Shayok Chakraborty, and Sethuraman Panchanathan. Deep hashing network for unsupervised domain adaptation. In *CVPR*, 2017. [1](#)
- [5] Jiaolong Xu, Liang Xiao, and Antonio M. Lopez. Self-supervised domain adaptation for computer vision tasks. *IEEE*, 7:156694–156706, 2019. [1](#)