

# WHAT IS CREATE-REACT-APP

**Not required for React** but very convenient

create-react-app (CRA) is a **program**

- Creates a directory for a new react application
- Creates/configures package.json
- Installs npm packages
- Common configs
- Webpack for bundling
- Eslint for linting
- Babel for transpiling
- Notable: fairly un-opinionated

# INSTALLING AND USING CRA

```
npm install -g create-react-app
```

**WAIT!!!**

What do you mean, a global install !?

Yes - this is a tool, not part of the code we're writing

```
create-react-app demo
```

# WHAT DID THAT DO?

- Took a long time to install a lot
- Gave instructions (these are in the README)
- Installed a `package.json` and the dependencies
  - "react-scripts" package wraps webpack/babel/etc
  - "react-scripts" ALSO has the configs for those
  - Some config is in package.json directly
- Created a `/src` directory
- Created a `/public` directory

# WHAT NOW?

Some commands are defined in `package.json`:

- `npm run eject` - removes CRA, leaves code/configs
  - Don't use this, but try it out on a test project
- `npm run build` - creates static files in `/build`
  - NOT `public/`! Like `/src`, `/public` is **input** here
  - NO SERVER - you have to write or use one
- `npm start` - starts a dev server
  - Auto reloads/rebuilds when the code changes
  - Not for final use - use `npm run build` and use the `/build` results for a real server

# WHAT DO WE HAVE?

- in `/public` the `index.html` file has no real content
  - but does have `<div id="root"></div>`
- `/src/index.js` loads `App` and injects into `#root`

But what is `App`?

**To make ME happy**, rename `src/App.js` to `src/App.jsx`

# BUILD PROCESS

All bundled using `webpack` and transpiled by `babel`

Run `npm start`

- This starts a dev-server (keeps terminal busy)
- This transpiles and bundles the code

This is just pre-configured work we've done before

# NON-JS IMPORTS

`import` is a standard, despite requiring a bundler

Some **non-standard** transpiling extensions are often used to bring CSS and/or images into a web-page

- requires a **configured** transpiler/bundler to do
- CRA gives you that config

```
import React from 'react'; // standard library import
import ReactDOM from 'react-dom'; // standard library import
import logo from './logo.svg'; // NON-STANDARD, path to img
import './index.css'; // NON-STANDARD, adds CSS to page
import App from './App'; // standard local file import
```