

# **AUTHENTICATION / AUTHORIZATION**

- Authentication (Auth)
  - Who are you?
- Authorization (Authz)
  - What are you allowed to do?

# FACTORS

A way of proving auth/authz

- Something you know
  - passwords, PIN
- Something you have
  - keycards, yubikey, RSA token, cellphone
- Something you are
  - fingerprints, iris, face

2FA is "two factor auth", MFA is "multi-factor (2+) auth"

# LOGIN

Authenticates, possibly authorizes

- Username
- Password

Send both. Per security discussion, server will compare hashed password+salt to stored salt+hash for that username.

But then what?

# **BEYOND STATELESS**

Web requests are stateless

How do you let the server know a later request is from someone that has already authenticated?

# SESSION ID

How to solve with session id

When user successfully authenticates:

- create a random string (session id)
- on the server:
  - connect the username and authz info with id
    - often a DB entry. For class just keep in memory
  - return this session id to the client
- on the client:
  - send this session id with any later requests

# OTHER TOKENS

Session Id is a "token" that by itself is random

Other tokens contain usable info directly, but are "signed" to prove who created them

Example: JWT (JSON Web Token) ("jot")

Basically a text file saying "Whoever has this token has proven themselves to be X or be allowed to Y", with a digital signature to prove it came from the owner of some private key.

# JWT

## Advantages

- No DB check each time used
- Can be passed to others
  - This is how many 3rd party login systems work

## Disadvantages

- Good for their lifetime, even if user "logs out"
- Don't want to store changing info in them

# WAYS TO SEND AUTH TOKEN BACK AND FORTH

- Cookies
  - header of a request/response
  - connected to a domain
  - server can "set" in a response
  - stored in browser
  - browsers auto send on later requests
  - Works across tabs/browser windows
    - Not across profiles/incognito mode
- Forms (rough)
  - send as hidden field
- Front end JS to include on requests



# COOKIE DETAILS

- "Remember me"?
  - sets cookie to expire(or not) after a long time
  - Otherwise cookie gone when browser exits
- Logout
  - Server can overwrite with new stored value/expiration date
- Other cookie config options
  - A path root (rare)
  - HTTPS only ("secure", recommended)
  - Be unseen by browser JS (confusing name)
  - Not interact with 3rd party pages (recommended)

# EXPRESS COOKIE EXAMPLE

```
// express "middleware", this time as an extra library
const cookieParser = require('cookie-parser');
app.use(cookieParser());

// (skipping over other express stuff)
app.get('/', (req, res) => {
  const store = req.query.store;
  if(store) {
    res.cookie('saved', store, { maxAge: 15000 });
  }

  const saw = req.cookies.saved;
  res.send(`

Request had cookie "saved": ${saw}</p>`);
});


```

# STEPS

1. Inside new project directory:

- `npm init -y`
- `npm install express`
- `npm install cookie-parser`

2. Create the `server.js` (or whatever you call it) file

3. run `node server.js`

4. go to `localhost:3000` in the browser

5. use `?store=SOMEVAL` at end of url to set the cookie

6. DevTools-Network-Headers to see the `Set-Cookie` in the response and the `Cookie` in the request

7. DevTools-Application-Cookies (left) to see cookies

8. Remember this is a 15 sec expiration time

# CHANGING THE COOKIE EXAMPLE

Do you know how to:

- Store the cookie under a different name
  - not `"saved"`?
- Change the expiration time of the cookie?
- Change the name of the query param you are sending to set the cookie value?
  - instead of `"store"`
- Redirect the user to `'/'` (no query param) after setting the cookie?