

API Documentation

STP API supports visa processing for StampThePassport, primarily using GraphQL for content queries and REST for user journey management.

Base URLs are <https://cms.stampthepassport.com> (GraphQL content) and <https://dev-api.stampthepassport.com> (user actions).

Authentication uses Token headers for REST endpoints; GraphQL appears public.

User Journey

Country List

GET /graphql (GraphQL query: `categoriesList { id categoryName countries { id name code ... } }`)

Retrieves countries grouped by visa categories like Tourist Visa, Student Visa.

Parameters: None.

Sample Response:

json

```
{
  "data": {
    "categoriesList": [
      {
        "id": 22,
        "categoryName": "Tourist Visa",
        "countries": [{"id": 2, "name": "United States",
"code": "US", "countryUrl": "usa", "categoryUrl":
"usa-tourist", "type": "visa"}]
      }
    ]
  }
}
```

Category

GET /graphql (GraphQL query: `category(countryUrl: "usa") { country { id name } categoryUrl uniqueId }`)

Fetches category URLs (e.g., usa-tourist, usa-student) for a specific country.

Parameters: `countryUrl` (String, required, e.g., "usa").

Sample Response:

json

```
{
  "data": {
    "category": [
      {"name": "Tourist Visa", "categoryUrl": "usa-tourist"},
      {"name": "Student Visa", "categoryUrl": "usa-student"}
    ]
  }
}
```

Product Filter

GET /graphql (GraphQL query: `productFilters(category: "usa-business") { entryType processingTime stayDuration }`)

Returns filter options like entry types (Multiple), processing times (45 working Days), stay durations for products.

Parameters: `category` (String, required, e.g., "usa-business").

Sample Response:

json

```
{
  "data": {
    "productFilters": {
      "entryType": "Multiple",
      "processingTime": ["45 working Days", "300 Working Days"],
      "stayDuration": "6 Months"
    }
  }
}
```

Product Result

GET /graphql (GraphQL query: `productResults(category: "usa-student", entryType: "All", ...)`)

Lists products with pricing, images, apply URLs, discounts under a category and filters.

Parameters: `category` (String), `entryType/processingTime/stayDuration` (String, e.g., "All").

Sample Response:

json

```
{
  "data": {
    "productResults": {
      "productDetails": [
        {
          "heading": "10 Years Multiple Entry B1B2 Visa - Express",
          "price": 36095,
          "buttonUrl": "https://stampthepassport.com/visa/usa-express-...",
          "keyValues": {"Entry Type": "Multiple", "Visa Validity": "10 Years"}
        }
      ]
    }
  }
}
```

Visa Process Management

Primary Customer

POST /primary-customer

Creates visa process with travel dates, product ID, DIY flag for primary customer.

Headers: `Authorization: Token <token>`.

Body Parameters: `dotfrom/dotto` (Date, e.g., "16-02-2026"), `productid` (Int), `diy` (Boolean).

Sample Response: `{"success": true, "visaprocessid": 7837}`

Journey Index

POST `/journey-index`

Saves user progress index for resuming journey.

Headers: `Authorization: Token <token>`.

Body Parameters: `primarycustomerid` (Int), `index` (Int, increments per step).

Sample Response: `{"visaprocessid": 7837}`

Co-Traveller List

GET `/co-traveller-list?visaprocessid=<id>`

Lists co-travellers associated with a visa process.

Headers: `Authorization: Token <token>`.

Query Parameters: `visaprocessid` (Int, required).

Sample Response: Array of co-traveller details.

Supporting Content

Documents for Category

GET `/graphql` (GraphQL: `categoryRequiredDocuments(category: "usa-business")`)

Lists required documents with headings, descriptions, images for a category.

Parameters: `category` (String).

FAQ for Category

GET `/graphql` (GraphQL: `categoryFaqEntity(categoryUrl: "usa-business")`)

Retrieves FAQs (questions/answers) specific to a category.

Parameters: `categoryUrl` (String).

Visa Flows

These APIs power the end-to-end online visa journey: creating a visa process, managing travellers, extracting passport data, payments, and post-purchase utilities.

Create Visa Process

POST `baseurl/primary-customer`

Creates a new visa process with travel dates and selected product for the primary customer.

- Headers: `Authorization` (Token), optional `Source` (channel identifier).

- Body (JSON):
 - `dotfrom` (String, travel start date, e.g., "01-08-2024")
 - `dotto` (String, travel end date)
 - `productid` (Integer, selected visa product)
 - `products / diy` flags to indicate DIY vs full-service.
- Sample Request:

json

```
{
  "dotfrom": "01-08-2024",
  "dotto": "01-08-2025",
  "productid": 836,
  "diy": false
}
```

- Sample Response:

json

```
{
  "success": true,
  "visaprocessid": 9238
}
```

Save/Resume Journey (Index)

POST `baseurl/journey-index`

Stores the current step index for a user so the journey can be resumed later.

- Headers: `Authorization` (Token).
- Body (JSON):
 - `primarycustomerid` (Integer)
 - `index` (Integer, increments with each step).
- Sample Request:

json

```
{
  "primarycustomerid": 7837,
  "index": 1
}
```

- Sample Response:

json

```
{"success": true}
```

Co-Traveller Management

GET `baseurl/co-traveller-list?visaprocessid={id}`

Returns all co-travellers added to a given visa process.

- Headers: `Authorization` (Token).
- Query: `visaprocessid` (Integer, required).
- Sample Response: List of traveller profiles (names, passport numbers, types like “signzy” or “cotraveller”).

POST `baseurl/add-to-pax`

Adds one or more travellers to the visa process (moves them into the active passenger list).

- Headers: `Authorization` (Token).
- Body (JSON):
 - `primarycustomerid` (Integer)
 - `productid` (Integer)
 - `travellers` (Object of travellers: `travellerno`, `passportno`, `type` like `signzy` or `cotraveller`, `profileid` etc.).
- Sample Request:

json

```
{
  "primarycustomerid": 3645,
  "productid": 771,
  "travellers": {
    "travellerno1": {"passportno": "X5234261", "type": "signzy"},
    "travellerno4": {"passportno": "M9239054", "type":
"cotraveller"}
  }
}
```

- Sample Response: A success flag and updated passenger info.

GET `baseurl/get-all-pax?primarycustomerid={id}`

Returns all passengers (primary + co-travellers) under a visa process.

- Headers: `Authorization` (Token).
- Query: `primarycustomerid` (Integer).
- Sample Response: Array of passenger records with linkage to visa process.

Passport Upload & Extraction

POST `baseurl/passport-upload`

Uploads passport images for a traveller (front/back) to STP storage.

- Headers: `Authorization` (Token).
- Body (JSON):
 - `imageurlfront` (String, URL of front image in S3)
 - `imageurlback` (String, URL of back image in S3)
 - `primarycustomerid` (Integer)
 - `travellerno` (Integer, traveller index)
 - Optional: direct passport URLs for co-travellers.
- Sample Request:

json

```
{
  "imageurlfront": "https://.../passportfront.jpg",
  "imageurlback": "https://.../passportback.jpg",
  "primarycustomerid": 830,
  "travellerno": 1
}
```

- Sample Response: Confirms storage and mapping to traveller.

POST `baseurl/passport-extraction`

Triggers OCR/extraction on the uploaded passport images.

- Headers: `Authorization` (Token).
- Body (JSON):
 - `imageurlfront / imageurlback` (String URLs)
 - `primarycustomerid` (Integer)
 - `travellerno` (Integer).
- Sample Response (simplified):

json

```
{
  "result": {
    "name": "PANKAJ KUMAR SABOO",
    "passportNumber": "G3781878",
    "birthDate": "10-05-1984",
    "expiryDate": "12-07-2017",
    "nationality": "INDIAN"
  }
}
```

GET `baseurl/passport-extraction?primarycustomerid={id}&travellerno={n}`

Fetches previously extracted passport data for a traveller.

- Headers: `Authorization` (Token).
- Query: `primarycustomerid`, `travellerno`.
- Sample Response: Same structure as above, without re-processing images.

Pre-Purchase & Country Checks

GET

`baseurl/pre-purchase-data-collection?primarycustomerid={id}&travellerno={n}`

Returns pre-purchase questionnaire data for a traveller (used to pre-fill forms before payment).

- Query: `primarycustomerid`, `travellerno`.
- Sample Response: Stored answers and status flags.

GET `baseurl/get-country-warning?productid={id}`

Shows any warnings or advisories related to a product's country (e.g., travel advisories).

- Query: `productid` (Integer).
- Sample Response: Message set with warning text and tags.

GET `baseurl/country-form-check?primarycustomerid={id}`

Indicates whether country-specific forms are required or completed for this visa process.

- Query: `primarycustomerid`.
- Sample Response:

json

```
{"iscountryform": true}
```

Payment & Fees

POST `baseurl/create-payment`

Creates a payment intent/record for the selected product and add-ons.

- Headers:
 - `Authorization` (Token)
 - `Source` (channel, e.g., `stp-web`, `airticket`).
- Body (JSON):
 - `productid` (Integer)
 - `primarycustomerid` (Integer)
 - `diy` (Boolean)
 - `insuranceid` (Integer, optional)
 - `addons` (Array or comma-separated IDs).
- Sample Request:

json

```
{
  "productid": 6,
  "primarycustomerid": 7059,
```



```

    "diy": false,
    "insuranceid": 80,
    "addons": [860, 859, 861, 858]
  }

```

- Sample Response (fees breakdown):

json

```

{
  "visafee": 12500,
  "conveniencefee": 1180,
  "conveniencefeebreakdown": {
    "servicefee": 1000,
    "tax": 180,
    "courier": 0
  },
  "discount": 0,
  "discountpercentage": 0,
  "originalprice": 13680,
  "total": 13680
}

```

GET `baseurl/payment-collection?visaprocessid={id}`

Returns existing payment collection details for a visa process.

- Query: `visaprocessid`.
- Sample Response: Amounts, modes, and statuses per payment attempt.

Application & Status

GET `baseurl/get-application-details?primarycustomerid={id}&productid={pid}`

Fetches full application details for the given primary customer and product.

- Headers: `Authorization` (Token).
- Query: `primarycustomerid`, `productid`.
- Sample Response: Application form data, traveller list, and current status.

GET `baseurl/customer-visaprocess?status={STATUS}`

Lists visa processes for the logged-in user filtered by status such as `IN-PROGRESS` or `UNPAID`.

- Headers: `Authorization` (Token).
- Query: `status`.
- Sample Response: Paginated list of visa processes with basic metadata (product, country, stage).

Feedback & Post-Purchase

POST `baseurl/user-feedback`

Captures user feedback and rating after journey completion.

- Headers: `Authorization` (Token).
- Body (JSON):
 - `rating` (Integer, e.g., 3–5)
 - `feedback` (String, free-text).
- Sample Request:

`json`

```
{  
  "rating": 3,  
  "feedback": "very good"  
}
```

- Sample Response: Acknowledgement with success flag.