PulseLARSEN Antennas

TECHNICAL DATA SHEET

Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006



Features:

- - Omnidirectional radiation
- - Low profile
- - Compact size WxLxH (10 x 3.2 x 1.5 mm)
- - Low weight (240 mg)
- - Fully SMD compatible
- - Lead free soldering compatible
- - Tape and reel packing
- - RoHS Compliant Product
- - Single feed point



Applications:

- - IEEE 802.11a/b/g
- - 5 GHz WLAN
- - 2.4 GHz WLAN
- - 2.4 GHz ISM Band Systems
- - ZigBee IEEE 802.15.4

All dimensions are in mm / inches

Issue: 1624

RoHS COMPLIANT

For more information:

Pulse Worldwide Headquarters
12220 World Trade Drive
San Diego, CA 92128
USA
Tel:1-858-674-8100

Pulse/Larsen Antennas
3611 NE 112th Ave
Vancouver, WA 98682
USA
Tel: 1-360-944-7551

Europe Headquarters
Pulse GmbH & Do, KG
Zeppelinstrasse 15
Herrenberg, Germany
Tel: 49 7032 7806 0

Pulse (Suzhou) Wireless Products Co, Inc.
99 Huo Ju Road(#29 Bldg,4th Phase
Suzhou New District
Jiangsu Province, Suzhou 215009 PR China
Tel: 86 512 6807 9998

PulseLARSEN Antennas

TECHNICAL DATA SHEET

Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

ELECTRICAL SPECIFICATIONS

Frequency1	2.4-2.5GHz
Frequency2	5.15-5.85GHz
Nominal Impedance	50Ω
Return Loss Frequency1	-8 dB max
Return Loss Frequency2	-10 dB max
Efficiency Frequency1	60 %
Efficiency Frequency2	70 %
Peak Gain Frequency1	2.2dBi
Peak Gain Frequency2	4.5dBi
Polarization	Linear
Interface	SMD mount ceramic antenna

RoHS COMPLIANT

Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

MECHANICAL SPECIFICATIONS

Weight	0.24g
Size	10 x 3.2 x 1.5 mm

ENVIRONMENTAL SPECIFICATIONS

Operating temperature	-40~+85° C
Temperature	-40~+85° C
Humidity	Cyclic 6 +25° C/+55° C 95%
Vibration	
Sinusoidal 2-8Hz	7.5 mm
Sinusoidal 8-200Hz	20 m/s²
Shocks	0.5 m/s
Salt mist	96 hours

RoHS COMPLIANT

Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

MECHANICAL DRAWING AND TERMINAL CONFIGURATION



RoHS COMPLIANT

Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

MECHANICAL DRAWING AND TERMINAL CONFIGURATION





No.	Terminal Name	Terminal Dimensions
1	Feed	1.5 x 2.75 mm
2	Support pad	1.5 x 2.75 mm
Antenna feed pad can be identified by looking top surface metallization pattern		

RoHS COMPLIANT

Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

MECHANICAL DRAWING AND TERMINAL CONFIGURATION

Ground cleared under antenna, clearance area 11.60 mm x 6.25 mm



PWB manufacturing requirements according to IPC-A-600 revision G or similar

Shunt matching inductor, 1.5nH with presented setup.

Exact inductor value depends on specific application.



RoHS COMPLIANT

Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

MECHANICAL DRAWING AND TERMINAL CONFIGURATION

Ground clearance area (11.60 x 6.25 mm)



Opening in bottom/inner ground layers



Opening in other layers (no ground/ RF)



RoHS COMPLIANT

Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

MECHANICAL DRAWING AND TERMINAL CONFIGURATION

Recommended Antenna Pad Dimensions on PWB Layout (top surface)



Recommended test board layout for electrical characteristic measurement, test board outline size 80 x 37mm



Issue: 1624

RoHS COMPLIANT

Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

CHARTS

Measured on the 80x37mm test board with matching circuit, 1.5nH shunt inductor
Ground cleared under antenna, clearance area 11.60 mm x 6.25 mm

Free space efficiency and maximum gain for 2.4G





RoHS COMPLIANT

Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

CHARTS

Measured on the 80x37mm test board with matching circuit, 1.5nH shunt inductor
Ground cleared under antenna, clearance area 11.60 mm x 6.25 mm

Free space efficiency and maximum gain for 5G



Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

CHARTS

Measured on the 80x37mm test board with matching circuit, 1.5nH shunt inductor
Ground cleared under antenna, clearance area 11.60 mm x 6.25 mm

2.4 GHz Typical Free Space Radiation Patterns









Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

CHARTS

Measured on the 80x37mm test board with matching circuit, 1.5nH shunt inductor
Ground cleared under antenna, clearance area 11.60 mm x 6.25 mm

5GHz Typical Free Space Radiation Patterns









Description: Dual Band WLAN Ceramic

Series: Ceramic

PART NUMBER: W3006

PACKAGING



CARRIER TAPE H85-00168
width=24,00 depth=2.20
COVER TAPE H85-00159
width=21.20

LENGTH OF TAPE:

- Leader section: min 350 mm before component section
- Trailer section: min 40 mm after component section.

Empty part cavities at leader and trailer section of the tape must be sealed with top cover tape.

BOX H85-00128 (182x182x125)	1 pcs
- LABEL	1 pcs/BOX
REEL H85-00160 (D180,W28)	4 pcs
- REEL LABEL	1 pcs/REEL



MATERIAL					
HANDLINGS					
		RATIO	DRWN	160107 PeHa	H
			DGNER		G
			CHKD		F
			APPRD		E
PRODUCT H90-0Y113-F01P01			APPRD BY		D
					C
					B
DENOMINATION PACKING FORM					A
			VERSION		MOD/DATE/NAME

RoHS COMPLIANT