

PCEP Full Mock Exam – 30 Questions (Practice)

- Q1. What is the output? `print(7 // 3)`
- Q2. Which are valid identifiers? A) `2name` B) `_value` C) `name_1` D) `for`
- Q3. What is printed? `x=5; x+=2; print(x)`
- Q4. Choose all true: A) `and` has higher precedence than `or` B) `not` binds tighter than `and` C) `==` has lower precedence than `and` D) `or` has higher precedence than `not`
- Q5. Output? `print(True and False or True)`
- Q6. Fill: `range(____)` to produce 0,2,4,6 (under 8).
- Q7. What is printed? `for i in range(3): if i==1: continue print(i)`
- Q8. While loop result? `n=3; while n>0: n-=1; print(n)`
- Q9. Choose correct slicing of `[10,20,30,40]` to get `[20,30]`.
- Q10. List method to add element at end?
- Q11. Tuple immutability: which will raise error? A) `t=(1,2); t[0]=9` B) `t=(1,2); u=t+(3,)` C) `a,b=(1,2)`
- Q12. Dictionary safe access with default value uses which method?
- Q13. What is printed? `d={"a":1,"b":2}; print(list(d.keys()))`
- Q14. Strings: pick true. A) Strings are mutable B) `s[0]` is first char C) `"ab"` in `"cabd"` is True D) `s.upper()` mutates `s`
- Q15. Function result? `def f(a,b=3): return a+b print(f(2))`
- Q16. Scope: what prints? `x=5 def g(): x=2 print(x) g(); print(x)`
- Q17. Return semantics: what prints? `def h(): x=1 return x x=9 print(h())`
- Q18. Exception: what prints? `try: print(10/0) except ZeroDivisionError: print("err")`
- Q19. Which except catches a missing key? A) `ValueError` B) `KeyError` C) `IndexError`
- Q20. for-else: what prints? `for x in [1,2,3]: if x==2: break else: print("done")`
- Q21. Evaluate: `bool(0)`, `bool("")`, `bool([])`, `bool("0")`
- Q22. Choose output: `print(2**3**2)` # exponentiation is right-associative
- Q23. What is printed? `s="python"; print(s[1:5:2])`
- Q24. Which statement is True? A) dict preserves insertion order (3.7+) B) list is immutable C) tuple is mutable D) str is mutable
- Q25. Which call errors? `int("10")`, `int(10.5)`, `int("10a")`
- Q26. What is printed? `a=[1,2,3]; b=a; b.append(4); print(a)`
- Q27. Which is valid function definition? A) `def f(a,b=2,c): pass` B) `def f(a,b,c=2): pass` C) `def f(a=1,b=2,c): pass`
- Q28. Exception flow: `try/except/else/finally` – which always executes?
- Q29. Indexing: what happens? `a=[1]; print(a[1])`
- Q30. Comprehension (reasoning only – not required for PCEP coding): Is `[x for x in [1,2,3]]` equivalent to `list([1,2,3])`? (Yes/No)

Answer Key

Q1: 2
Q2: B, C
Q3: 7
Q4: B and C
Q5: True
Q6: range(0,8,2)
Q7: 0□2
Q8: 0
Q9: a[1:3]
Q10: append
Q11: A
Q12: dict.get
Q13: ["a", "b"] (order preserved in 3.7+)
Q14: B and C
Q15: 5
Q16: 2 then 5
Q17: 1
Q18: err
Q19: KeyError
Q20: (prints nothing)
Q21: False, False, False, True
Q22: 512 (since $3**2 = 9$; $2**9 = 512$)
Q23: yt
Q24: A
Q25: int("10a") raises ValueError
Q26: [1,2,3,4]
Q27: B
Q28: finally
Q29: IndexError
Q30: Yes