


Assignment 1: Getting Acquainted with UNIX and C  
Writeup  
Prof Veenstra  
Nguyen Vu  
Jan 22 2023

This is the output of the first plot



UNIX commands I chose to use for this plot:

make clean: uses the command from Makefile to clear up the old data files from previous run

make monte\_carlo: uses command from Makefile to make monte\_carlo.c into clang format and run it and make the monte\_carlo program clang format  
./monte\_carlo -n 1000 ; data.dat: to create a data.dat file with 1000 iterations

awk '{print \$3 " " \$4 " " \$5}' data.dat >monte\_carlo.dat: get column 3, 4 and 5 from data.dat file and put into monte\_carlo.dat file set terminal pdf: to make the output file a pdf

set size square: to make the output layout a square

set key autotitle columnhead: to set the first row into title instead of data

unset key: to remove the x and y axis labels

set output "figure2.pdf": to name the output


set title "Monte Carlo": to set the graph title

set xrange [0:1]: to set the range for x axis

set yrange [0:1]: to set the range for y axis

set palette defined (0 "#FF0000", 1 "#0000FF"): to set the color for dots inside of the quarter circle to be blue and dots outside of the quarter circle to be red  
unset colorbox: to remove the colorbox at the right of the plot  
plot "monte\_carlo.dat" with dots linecolor palette, [x=0:1] sqrt(1-x\*\*2) with lines linecolor rgb "#000000": plot the figure2 plot using the monte\_carlo.dat file and the quarter circle with black line

This is the output of the second plot



./monte\_carlo -n 20000 -r "\$RANDOM" >tempdata1.dat: to create the 1st tempdata.dat file for the output of monte\_carlo.c with 20000 iterations and a random seed  
./monte\_carlo -n 20000 -r "\$RANDOM" >tempdata2.dat: to create the 2nd tempdata.dat file for the output of monte\_carlo.c with 20000 iterations and a random seed  
./monte\_carlo -n 20000 -r "\$RANDOM" >tempdata3.dat: to create the 3rd tempdata.dat file for the output of monte\_carlo.c with 20000 iterations and a random seed  
./monte\_carlo -n 20000 -r "\$RANDOM" >tempdata4.dat: to create the 4th tempdata.dat file for the output of monte\_carlo.c with 20000 iterations and a random seed  
awk '{PI = 3.141592654} NR!=1 {print \$1 " " PI - \$2}' tempdata1.dat

>data1.dat: to remove the first row, get column 1 and pi minus column 2  
 from the 1st tempdata.dat file and put them in the 1st data.dat file  
 awk '{PI = 3.141592654} NR!=1 {print \$1 " " PI - \$2}' tempdata2.dat  
 >data2.dat: to remove the first row, get column 1 and pi minus column 2  
 from the 2nd tempdata.dat file and put them in the 2nd data.dat file  
 awk '{PI = 3.141592654} NR!=1 {print \$1 " " PI - \$2}' tempdata3.dat  
 >data3.dat: to remove the first row, get column 1 and pi minus column 2  
 from the 3rd tempdata.dat file and put them in the 3rd data.dat file  
 awk '{PI = 3.141592654} NR!=1 {print \$1 " " PI - \$2}' tempdata4.dat  
 >data4.dat: to remove the first row, get column 1 and pi minus column 2  
 from the 4th tempdata.dat file and put them in the 4th data.dat file  
 set terminal pdf: to set the output to pdf file  
 set output "figure3.pdf": to name the output  
 set title "Monte Carlo Error Estimation": to set the plot title  
 set logscale x 4: to set the x axis scales to the squares of 4  
 set xrange [1:20000]: to set the range for x axis  
 set ylabel "Error": to label the y axis "Error"  
 set yrange [-1:1]: to set the range for y axis  
 plot "data1.dat" title "" with lines linecolor rgb "#FF0000", "data2.dat"  
 title "" with lines linecolor rgb "#ADD8E6", "data3.dat" title "" with  
 lines linecolor rgb "#0000FF", "data4.dat" title "" with lines linecolor rgb  
 "#FFF000": plot all 4 data sets using lines with different colors for each one