Relational Model for UML Diagram 2

Relation	Attributes	Primary Key	Foreign Keys	Constraints
ItemCategory	categoryId, categoryName, description, activeStatus, parentCategoryId*	categoryId	parentCategoryId → ItemCategory(categoryId)	categoryName UNIQUE and NOT NULL, parentCategoryId may be NULL for the topmost category
SecondHandItem	itemId, title, description, askingPrice, listingDate, Status, brand, model, condition, yearAcquired, categoryId*, sellerId*	itemId	sellerId → User(UserId) categoryId → ItemCategory(categoryId)	sellerId NOT NULL, categoryId NOT NULL, askingPrice >= 0
ItemPhoto	photoId, itemId*, photoURL	photoId	itemId → SecondHandItem(itemId)	itemId NOT NULL, UNIQUE(itemId, photoURL) to prevent duplicate photos for the same item
ItemTag	tagId, tagName	tagId		tagName UNIQUE and NOT NULL
ItemHasTag*	itemId, tagId	(itemId, tagId)	item_id → SecondHandItem(itemId) tagId → ItemTag(tagId)	
SavedItem	dateSaved, itemId*, userId*	(itemId*, userId*)	item_id → SecondHandItem(itemId) userId → User(UserId)	dateSaved NOT NULL
PurchaseRequest	purchaseRequestId, purchaseRequestDate, offeredPrice, message, status, buyerId*, itemId*	purchaseRequestId	item_id → SecondHandItem(itemId) buyerId → User(UserId)	buyerId NOT NULL, itemId NOT NULL, offeredPrice >= 0, buyer must not be the seller of the referenced item
PickupPoint	pickupPointId, pickupPointName, addressId*, description, activeStatus	pickupPointId	addressId → Address(addressId)	addressId NOT NULL, pickupPointName NOT NULL
Address	addressId, streetAddress, city, state, zipCode, longitude, latitude	addressId		UNIQUE(streetAddress, city, state, zipCode) and NOT NULL, latitude between -90 and 90; longitude between -180 and 180
TransactionOrder	transactionId, agreedPrice, transactionDate,	transactionId	purchaseRequestId → PurchaseRequest(purchaseRequestId)	purchaseRequestId UNIQUE and NOT NULL, pickupPointId NOT NULL, agreedPrice >= 0

	pickupDateTime, status, purchaseRequestId*, pickupPointId*		pickupPointId → PickupPoint(pickupPointId)	