

tidyr

---

LearningSpoonsR

2018-05-20

- RMarkdown
- pdf 조판을 위한 texlive 엔진
- slide형태의 pdf를 만드는 beamer 패키지 (R 패키지가 아니라 tex 패키지)
- 한글 및 twocolumn layout을 위한 `latex-topmatter.tex` (베포해드리는 `rmd-beamer.Rmd` 템플릿의 하위 폴더에 있습니다.)

## 0. Let's start!

```
source("infile-tidyr.R")  
library(tidyverse) # Wickham's  
library(sqldf)
```

- Part I. Join
- Part II. Tidy data

## Part I. Join

df1

##	CustomerId	Product
## 1	1	Toaster
## 2	2	Toaster
## 3	3	Toaster
## 4	4	Radio
## 5	5	Radio

df2

##	CustomerId	State
## 1	2	Seoul
## 2	4	Seoul
## 3	6	Busan

- 4 types of join

## I-1. Inner Join

```
inner_join(df1, df2)
merge(x = df1, y = df2, by = "CustomerId")
sqldf("SELECT CustomerId, Product, State
      FROM df1 JOIN df2 USING(CustomerID)")
```

```
## Joining, by = "CustomerId"
##   CustomerId Product State
## 1           2 Toaster Seoul
## 2           4   Radio Seoul
```

## I-2. Left Join

```
left_join(df1, df2)
merge(x = df1, y = df2, by = "CustomerId", all.x = TRUE)
sqldf("SELECT CustomerId, Product, State
      FROM df1 LEFT JOIN df2 USING(CustomerID)")
```

```
## Joining, by = "CustomerId"
##   CustomerId Product State
## 1           1 Toaster  <NA>
## 2           2 Toaster Seoul
## 3           3 Toaster  <NA>
## 4           4   Radio Seoul
## 5           5   Radio  <NA>
```

### I-3. Outer Join (full)

```
full_join(df1, df2)
merge(x = df1, y = df2, by = "CustomerId", all = TRUE)

## Joining, by = "CustomerId"
##   CustomerId Product State
## 1           1 Toaster  <NA>
## 2           2 Toaster Seoul
## 3           3 Toaster  <NA>
## 4           4   Radio Seoul
## 5           5   Radio  <NA>
## 6           6    <NA> Busan
```

## I-4. Right Join

```
right_join(df1, df2)
merge(x = df1, y = df2, by = "CustomerId", all.y = TRUE)
```

```
## Joining, by = "CustomerId"
##   CustomerId Product State
## 1           2 Toaster Seoul
## 2           4   Radio Seoul
## 3           6    <NA> Busan
```



# Summary

- Summary

```
inner_join(df1, df2)
left_join(df1, df2)
full_join(df1, df2)
right_join(df1, df2)
```

- Variations

```
inner_join(df1, df2)
inner_join(x=df1, y=df2)
inner_join(x=df1, y=df2, by = "CustomerId")
inner_join(x=df1, y=df2, by = c("CustomerId"))
inner_join(x=df1, y=df2, by = c("CustomerId"="CustomerId"))
```

blank

## Part II. Tidy data

```
table1
```

##	ISO3	year	cases	popul
## 1	AFG	1999	745	19987071
## 2	AFG	2000	2666	201595360
## 3	BRA	1999	37737	172006362
## 4	BRA	2000	80488	174504898
## 5	CHN	1999	212258	1272915272
## 6	CHN	2000	213766	1280428583

## II-0. Short Review (mutate)

```
table1
```

```
##   ISO3 year  cases    popul
## 1  AFG 1999    745  19987071
## 2  AFG 2000   2666 201595360
## 3  BRA 1999  37737 172006362
## 4  BRA 2000  80488 174504898
## 5  CHN 1999 212258 1272915272
## 6  CHN 2000 213766 1280428583
```

```
table1 %>% mutate(rate = cases / popul * 100)
```

```
##   ISO3 year  cases    popul      rate
## 1  AFG 1999    745  19987071 0.003727410
## 2  AFG 2000   2666 201595360 0.001322451
## 3  BRA 1999  37737 172006362 0.021939305
## 4  BRA 2000  80488 174504898 0.046123634
## 5  CHN 1999 212258 1272915272 0.016674951
## 6  CHN 2000 213766 1280428583 0.016694879
```

## II-0. Short Review (group\_by & summarise)

```
table1
```

```
##   ISO3 year  cases    popul
## 1  AFG 1999   745    19987071
## 2  AFG 2000  2666    201595360
## 3  BRA 1999  37737   172006362
## 4  BRA 2000  80488   174504898
## 5  CHN 1999 212258  1272915272
## 6  CHN 2000 213766  1280428583
```

```
table1 %>% group_by(year) %>% summarise(n = sum(cases))
```

```
table1 %>% count(year, wt = cases) # equivalent to above
```

```
## # A tibble: 2 x 2
```

```
##   year      n
```

```
##   <dbl> <dbl>
```

```
## 1  1999 250740
```

```
## 2  2000 296920
```

blank

## II-1. gather from table4a & table4b

table4a

```
##   IS03   1999   2000
## 1  AFG     745   2666
## 2  BRA  37737  80488
## 3  CHN 212258 213766
```

```
tidy4a <- table4a %>%
  gather(colnames(table4a)[-1],
         key = "year",
         value = "cases")
```

tidy4a

```
##   IS03 year  cases
## 1  AFG 1999    745
## 2  BRA 1999 37737
## 3  CHN 1999 212258
## 4  AFG 2000   2666
## 5  BRA 2000  80488
## 6  CHN 2000 213766
```

table4b

```
##   IS03      1999      2000
## 1  AFG 19987071 201595360
## 2  BRA 172006362 174504898
## 3  CHN 1272915272 1280428583
```

```
tidy4b <- table4b %>%
  gather(colnames(table4b)[-1],
         key = "year",
         value = "popul")
```

tidy4b

```
##   IS03 year      popul
## 1  AFG 1999 19987071
## 2  BRA 1999 172006362
## 3  CHN 1999 1272915272
## 4  AFG 2000 201595360
## 5  BRA 2000 174504898
## 6  CHN 2000 1280428583
```

## II-1. gather from table4a & table4b

```
left_join(tidy4a, tidy4b)
left_join(tidy4a, tidy4b, by = c("IS03", "year"))
left_join(tidy4a, tidy4b, by = c("IS03"="IS03", "year"="year"))
```

```
## Joining, by = c("IS03", "year")
##   IS03 year  cases      popul
## 1  AFG 1999    745   19987071
## 2  BRA 1999  37737  172006362
## 3  CHN 1999 212258 1272915272
## 4  AFG 2000   2666  201595360
## 5  BRA 2000  80488  174504898
## 6  CHN 2000 213766 1280428583
```



## II-2. spread from table2

```
table2
```

```
##   ISO3 year  type      count
## 1  AFG 1999 cases        745
## 2  AFG 1999 popul 19987071
## 3  AFG 2000 cases        2666
## 4  AFG 2000 popul 201595360
## 5  BRA 1999 cases       37737
## 6  BRA 1999 popul 172006362
```

```
table2 %>% spread(key = "type", value = "count")
```

```
##   ISO3 year cases      popul
## 1  AFG 1999    745 19987071
## 2  AFG 2000   2666 201595360
## 3  BRA 1999  37737 172006362
```

## II-3. separate from table3

```
table3
```

```
##   ISO3 year      rate
## 1  AFG 1999    745/19987071
## 2  AFG 2000   2666/201595360
## 3  BRA 1999   37737/172006362
## 4  BRA 2000   80488/174504898
## 5  CHN 1999  212258/1272915272
## 6  CHN 2000  213766/1280428583
```

```
table3 %>% separate(rate, into = c("cases", "popul"), sep = "/")
```

```
##   ISO3 year  cases      popul
## 1  AFG 1999    745    19987071
## 2  AFG 2000   2666   201595360
## 3  BRA 1999   37737  172006362
## 4  BRA 2000   80488  174504898
## 5  CHN 1999  212258 1272915272
## 6  CHN 2000  213766 1280428583
```

### Classic method

```
table3$cases <-
  sapply(strsplit(table3$rate, split = "/"),
        function(x) x[1])
table3$popul <-
  sapply(strsplit(table3$rate, split = "/"),
        function(x) x[2])
```

blank

blank