EXHIBIT C-1.2
MUST BE FILLED OUT IN ENTIRETY TO BE CONSIDERED FOR APPROVAL

Sweet Statement of Quality Data and Product Specifications						
Company:						
Date:						
Crude Stream [α] (define any acronyms):						
Crude Components (define acronyms):						
Product Parameter	**Test Method[β]**	**Unit(s)**	**Specification Min**	**Specification Max**	**Result**	**Method**
API Gravity	D287, D1298 or D5002	[°API]	34	43		
Total Sulfur	D4294, D2622	[Mass %]		0.50		
Pour Point	D97	[°C]		-12		
Salt Content	D6470 or D3230	[mg/kg %]		500		
Viscosity @ 15.6°C	D445, D7042	[cSt]		11		
Viscosity @ 37.8°C	D445, D7042	[cSt]		6		
Vapor Pressure [VPCR4 (100°F)]	D6377	psia (kPa)		9.0(62.1)		
Vapor Pressure [VPCR 0.2 (100°F)] @900 sec.	D6377	psia (kPa)		Report		
Total Acid Number	D664, D8045	[mg KOH/g]		1.00		
Water	D4928 or D4006	[Vol. %]		Report		
Sediment	D473, D4807	[Mass. %]		Report		
Water/Sediment Combined Value		[Vol. %]		1.0		
Asphaltenes	D6560, IP143	[Mass%]		2.0%		
Cleanliness	D4740	ASTM Ref.		2		
Hydrogen Sulfide	UOP163	mg/kg		1ppm		
Mercaptan	UOP163	mg/kg		Report		
Yields [Vol. %][γ]						
Naphtha [28-191°C]	D7169, D7900	[Vol. %]	21	42		
Distillate [191-327°C]	D7169, D7900	[Vol. %]	19	45		
Gas Oil [327-566°C]	D7169, D7900	[Vol. %]	20	42		
Residuum [>566°C]	D7169, D7900	[Vol. %]	-	14		
Light Ends [Liquid Vol. %] [δ]						
Methane (C_1)	D7900 or ITM6008	[Liquid Vol.%]		0.01		
Ethane (C_2)	D7900 or ITM6008	[Liquid Vol.%]		0.10		
Propane (C3)	D7900 or ITM6008	[Liquid Vol.%]		1.0		
Normal Butane (NC4)	D7900 or ITM6008	[Liquid Vol.%]		3.0		
Isobutane (iC4)	D7900 or ITM6008	[Liquid Vol.%]		4.0		
Distillation						
IBP - 25°C	D7169,D7900	Wt.%		3.0%		
IBP - 79°C	D7169,D7900	Wt.%		10.0%		
Contaminants						
Organic Chlorides	D4929 B or C	mg/kg		1		
Vanadium	D5708 (B), D5863, D8252	mg/kg		18		
Nickel	D5708 (B), D5863, D8252	mg/kg		8		
Iron	D5708 (B), D5863, D8252	mg/kg		10		
Methanol	D7059	mg/kg		30		
Total Nitrogen	D4629/D5762	Wt. %		Report		
Basic Nitrogen	UOP269	Wt. %		Report		

Commonly traded crude petroleum suitable for normal U.S. Gulf Coast refinery processing and free of foreign contaminants or chemicals.

Alternate methods may only be used if approved by the contracting officer.

D7169 and D7900 data may be provided in requesting conditional acceptance of a Crude Oil. Distillation data according to D2892 and D5236 will still be necessary for final qualification of a Crude Oil's acceptance.

Light ends content specifications are interim and will be superseded if and when industry standards for light ends evaluation are implemented.

Vapor pressure changed to better reflect current domestic crude standards

NOTE 1: The Strategic Petroleum Reserve reserves the right to refuse to accept any Crude Oil which meets these specifications but is deemed to be incompatible with existing stocks, or which has the potential for adversely affecting handling. In the event the Strategic Petroleum Reserve refuses acceptance it may also exercise its rights under FAR 52.212-4.

NOTE 2: The acceptability of any Crude Oil depends upon any assay, or certificates of analysis for each blend component, typical of current production quality of the stream. Any Crude Oil offered to the Strategic Petroleum Reserve that meets these specifications may be subject to additional testing for acceptance.

NOTE 3: All Crude Oil shipments received by the SPR are tested to ensure they meet specifications.

NOTE 4: All Crude Oil shipments received by the SPR pursuant to this solicitation must be sourced from U.S. production.

NOTE 5: If a blended crude is to be submitted for consideration, then all component streams offered for blend must not exceed 45° API gravity or fall below 27.0° API gravity to be considered suitable for injection into SPR caverns.