

TS Inbox

Show Local/Shared/Global timestamp receipts from inbox

Specialist: Timestamp engineer + JS.

Installation – TS Inbox

Requirements

- Peergos account on a Verae host
- Permissions: STORE_APP_DATA
- For outbox subjects: desktop-host connector running

Steps

1. Copy `peergos-app.json` and `assets/` into Drive (or use OrgTool / gallery).
2. Context menu on `peergos-app.json` → ****Install App****.
3. Open from Apps launcher.
4. Dark theme: Peergos passes `?theme=dark-mode`.

Uninstall

Apps launcher → remove `TS Inbox`. Data remains under `/.apps/` until deleted.

Developer reference – verae-app-timestamp-inbox

Layout

```

```
peergos-app.json
assets/index.html
assets/sdk.js
src/peergos-sdk.mjs
src/lib.mjs
tests/lib.test.mjs
tests/certify-peergos.sh
```
```

Integration

Sandbox `fetch` → `/peergos-api/v0/data`.

Outbox JSON → connector → NATS (`verae-nats-bus/schemas/subjects.json`).

Inbox JSON → app lists `/inbox/`.

Tests

`make test` runs Node unit tests against an in-memory `fetch`.

`make certify` adds Peergos compliance (manifest bounds, no NATS/WebSocket).

Function specs – timestamp-inbox

Specialist: Timestamp + JS.

listInbox(client) → Promise<string[]>
JSON filenames in `/inbox/`.

parseReceipt(obj) → {scope, hash, cube_id, ok}
Defaults scope to local; ok iff hash present.

scopeRank(scope) → 0|1|2|3
local=1 shared=2 global=3 else 0.

Function specs – timestamp-inbox

Specialist: Timestamp + JS.

listInbox(client) → Promise<string[]>
JSON filenames in `/inbox/`.

parseReceipt(obj) → {scope, hash, cube_id, ok}
Defaults scope to local; ok iff hash present.

scopeRank(scope) → 0|1|2|3
local=1 shared=2 global=3 else 0.