

dm25s1

## Topic 02 : Motivating Example

### Part 01 : Introduction to Classification

Preparation

Data Handling

Exploring Data

Dr Bernard Butler

Department of Computing and Mathematics, WIT.  
(bernard.butler@setu.ie)

Preparing Data 2

Building Models

Autumn Semester, 2025

Prediction

#### Outline

- How classification differs from regression
- Classification metrics
- Lazy vs Eager learners

Wrap up

# Data Mining (Week 2)

Introduction



Motivating Example

Preparation

Data Handling

Exploring Data 1

Exploring Data 2

Building Models

Prediction

Clustering


Regression  
1

Classification  
1

Regression  
2

Classification  
2

Wrap up




# Outline

---

1. Introduction	3
1.1. Learning from data	4
1.2. Lazy vs Eager Learners	6
2. Introduction to Classification	7
3. k Nearest Neighbours	11
4. Summary	22

# What does it mean to learn from data?




## Programmed Computation

- Explicit, detailed programming logic

## Learned Computation

- Implicit, learning from examples

# What does it mean to learn from data?




## Programmed Computation

- Explicit, detailed programming logic
- Handle edge cases, messy data

## Learned Computation

- Implicit, learning from examples
- Less brittle, but harder to test

# What does it mean to learn from data?



## Programmed Computation

- Explicit, detailed programming logic
- Handle edge cases, messy data
- Software engineering - unit testing, etc.

## Learned Computation

- Implicit, learning from examples
- Less brittle, but harder to test
- New paradigms - iterative model building

# Machine learning pros and cons

## Benefits

- Less programming effort
- Subtle rules are inferred
- One algorithm works for a range of problems
- Most of the code is in libraries
- Scales better with data complexity

# Machine learning pros and cons

## Benefits

- Less programming effort
- Subtle rules are inferred
- One algorithm works for a range of problems
- Most of the code is in libraries
- Scales better with data complexity

## Challenges

- Need (lots of) data for training
- Training data (sample) needs to represent population
- Algorithms have many configuration settings
- Need to understand and validate
- Prediction error needs to be minimised



# Lazy vs Eager Learners

---

## Lazy learner

Stores training data (or only minor processing) and uses local approximation to predict a value from test data.

## Eager learner

Builds a model from the train set, before receiving new data for prediction

# Lazy vs Eager Learners

## Lazy learner

Stores training data (or only minor processing) and uses local approximation to predict a value from test data.

- Does not generalise until after training

## Eager learner

Builds a model from the train set, before receiving new data for prediction

- Training has an extra goal: to generalise from the data

# Lazy vs Eager Learners

## Lazy learner

Stores training data (or only minor processing) and uses local approximation to predict a value from test data.

- Does not generalise until after training
- Does not produce a standalone model

## Eager learner

Builds a model from the train set, before receiving new data for prediction

- Training has an extra goal: to generalise from the data
- Training has an extra output: standalone model

# Lazy vs Eager Learners

## Lazy learner

Stores training data (or only minor processing) and uses local approximation to predict a value from test data.

- Does not generalise until after training
- Does not produce a standalone model
- Training data must be kept for prediction

## Eager learner

Builds a model from the train set, before receiving new data for prediction

- Training has an extra goal: to generalise from the data
- Training has an extra output: standalone model
- Training data can be discarded after use

# Lazy vs Eager Learners

## Lazy learner

Stores training data (or only minor processing) and uses local approximation to predict a value from test data.

- Does not generalise until after training
- Does not produce a standalone model
- Training data must be kept for prediction
- Local approximations

## Eager learner

Builds a model from the train set, before receiving new data for prediction

- Training has an extra goal: to generalise from the data
- Training has an extra output: standalone model
- Training data can be discarded after use
- Local and/or global approximations

# Lazy vs Eager Learners

## Lazy learner

Stores training data (or only minor processing) and uses local approximation to predict a value from test data.

- Does not generalise until after training
- Does not produce a standalone model
- Training data must be kept for prediction
- Local approximations
- Often based on *search*

## Eager learner

Builds a model from the train set, before receiving new data for prediction

- Training has an extra goal: to generalise from the data
- Training has an extra output: standalone model
- Training data can be discarded after use
- Local and/or global approximations
- Based on *computation*

# Lazy vs Eager Learners

## Lazy learner

Stores training data (or only minor processing) and uses local approximation to predict a value from test data.

- Does not generalise until after training
- Does not produce a standalone model
- Training data must be kept for prediction
- Local approximations
- Often based on *search*
- If new data is just added to the training data, it can respond more easily to changing conditions

## Eager learner

Builds a model from the train set, before receiving new data for prediction

- Training has an extra goal: to generalise from the data
- Training has an extra output: standalone model
- Training data can be discarded after use
- Local and/or global approximations
- Based on *computation*
- Models *drift* with time, so not suited to highly dynamic contexts, as it needs retraining

# Lazy vs Eager Learners

## Lazy learner

Stores training data (or only minor processing) and uses local approximation to predict a value from test data.

- Does not generalise until after training
- Does not produce a standalone model
- Training data must be kept for prediction
- Local approximations
- Often based on *search*
- If new data is just added to the training data, it can respond more easily to changing conditions

Usually an (eager) model requires much less memory than a (lazy) training set.

## Eager learner

Builds a model from the train set, before receiving new data for prediction

- Training has an extra goal: to generalise from the data
- Training has an extra output: standalone model
- Training data can be discarded after use
- Local and/or global approximations
- Based on *computation*
- Models *drift* with time, so not suited to highly dynamic contexts, as it needs retraining



# Outline

---

1. Introduction	3
1.1. Learning from data	4
1.2. Lazy vs Eager Learners	6
2. Introduction to Classification	7
3. k Nearest Neighbours	11
4. Summary	22

# Introduction to Classification

## Definition 1 (Classification)

Classification aims to learn a function that takes attribute values and predicts a categorical/qualitative value, such as membership of a class, existence of an effect, etc.

# Introduction to Classification

## Definition 1 (Classification)

Classification aims to learn a function that takes attribute values and predicts a categorical/qualitative value, such as membership of a class, existence of an effect, etc.

The attributes can be categorical or numeric.

# Introduction to Classification

## Definition 1 (Classification)

Classification aims to learn a function that takes attribute values and predicts a categorical/qualitative value, such as membership of a class, existence of an effect, etc.

The attributes can be categorical or numeric.

Classification is an example of *supervised learning* because it requires a training set of labeled observations.

# Introduction to Classification

## Definition 1 (Classification)

Classification aims to learn a function that takes attribute values and predicts a categorical/qualitative value, such as membership of a class, existence of an effect, etc.

The attributes can be categorical or numeric.

Classification is an example of *supervised learning* because it requires a training set of labeled observations.

- Some *classifiers* generate class membership probabilities en route to predicting class membership (of the most likely class), so the predicted class can be defined by a set of numbers rather than a simple label.

# Introduction to Classification

## Definition 1 (Classification)

Classification aims to learn a function that takes attribute values and predicts a categorical/qualitative value, such as membership of a class, existence of an effect, etc.

The attributes can be categorical or numeric.

Classification is an example of *supervised learning* because it requires a training set of labeled observations.

- Some *classifiers* generate class membership probabilities en route to predicting class membership (of the most likely class), so the predicted class can be defined by a set of numbers rather than a simple label.
- There are many classification algorithms!

# Introduction to Classification

## Definition 1 (Classification)


Classification aims to learn a function that takes attribute values and predicts a categorical/qualitative value, such as membership of a class, existence of an effect, etc.

The attributes can be categorical or numeric.

Classification is an example of *supervised learning* because it requires a training set of labeled observations.

- Some *classifiers* generate class membership probabilities en route to predicting class membership (of the most likely class), so the predicted class can be defined by a set of numbers rather than a simple label.
- There are many classification algorithms!
- We choose one of the simplest today, which works by *voting for the most likely label*.

# Classification Overview



Today's classifier is a lazy learner and so uses local approximation, not a model



# Example Applications

---

➤ In 5 minutes, identify 3 possible applications for classification

# Outline

---

1. Introduction	3
1.1. Learning from data	4
1.2. Lazy vs Eager Learners	6
2. Introduction to Classification	7
3. k Nearest Neighbours	11
4. Summary	22

# Motivation

## Example 2 (Spam Detection)

A new email arrives. Is it spam? We have a large database of previous emails that have been labeled “Spam” or “Ham”. Can we use this information *directly* to say whether the new email is spam or not?

Given each of the following

# Motivation

## Example 2 (Spam Detection)

A new email arrives. Is it spam? We have a large database of previous emails that have been labeled “Spam” or “Ham”. Can we use this information *directly* to say whether the new email is spam or not?

Given each of the following



# Motivation

## Example 2 (Spam Detection)

A new email arrives. Is it spam? We have a large database of previous emails that have been labeled “Spam” or “Ham”. Can we use this information *directly* to say whether the new email is spam or not?

Given each of the following

- 1 database of  $n$  instances  $\{x_i\}$  with  $p$  attribute values per instance



# Motivation

## Example 2 (Spam Detection)

A new email arrives. Is it spam? We have a large database of previous emails that have been labeled “Spam” or “Ham”. Can we use this information *directly* to say whether the new email is spam or not?

Given each of the following

- 1 database of  $n$  instances  $\{x_i\}$  with  $p$  attribute values per instance
- 2 distance function  $D : d(x_i, x_j) : \mathbb{R}^{p \times p} \rightarrow \mathbb{R}$  where  $d(x_i, x_j) > 0$  if  $x_i \neq x_j$  and is zero otherwise



# Motivation

## Example 2 (Spam Detection)

A new email arrives. Is it spam? We have a large database of previous emails that have been labeled “Spam” or “Ham”. Can we use this information *directly* to say whether the new email is spam or not?

Given each of the following

- 1 database of  $n$  instances  $\{x_i\}$  with  $p$  attribute values per instance
- 2 distance function  $D : d(x_i, x_j) : \mathbb{R}^{p \times p} \rightarrow \mathbb{R}$  where  $d(x_i, x_j) > 0$  if  $x_i \neq x_j$  and is zero otherwise
- 3 function  $S$  that searches for instances that “match” an incoming instance based on  $D$



# Motivation

## Example 2 (Spam Detection)

A new email arrives. Is it spam? We have a large database of previous emails that have been labeled “Spam” or “Ham”. Can we use this information *directly* to say whether the new email is spam or not?

Given each of the following

- ① database of  $n$  instances  $\{x_i\}$  with  $p$  attribute values per instance
- ② distance function  $D : d(x_i, x_j) : \mathbb{R}^{p \times p} \rightarrow \mathbb{R}$  where  $d(x_i, x_j) > 0$  if  $x_i \neq x_j$  and is zero otherwise
- ③ function  $S$  that searches for instances that “match” an incoming instance based on  $D$
- ④ function  $R$  that identifies the  $k$  “nearest” (as defined by  $D$ ) instances





# Motivation

## Example 2 (Spam Detection)

A new email arrives. Is it spam? We have a large database of previous emails that have been labeled “Spam” or “Ham”. Can we use this information *directly* to say whether the new email is spam or not?

Given each of the following

- ① database of  $n$  instances  $\{x_i\}$  with  $p$  attribute values per instance
- ② distance function  $D : d(x_i, x_j) : \mathbb{R}^{p \times p} \rightarrow \mathbb{R}$  where  $d(x_i, x_j) > 0$  if  $x_i \neq x_j$  and is zero otherwise
- ③ function  $S$  that searches for instances that “match” an incoming instance based on  $D$
- ④ function  $R$  that identifies the  $k$  “nearest” (as defined by  $D$ ) instances
- ⑤ function  $A$  that aggregates the “labels” of these  $k$  neighbours, yielding one representative value



# Motivation

## Example 2 (Spam Detection)

A new email arrives. Is it spam? We have a large database of previous emails that have been labeled “Spam” or “Ham”. Can we use this information *directly* to say whether the new email is spam or not?

Given each of the following

- ① database of  $n$  instances  $\{x_i\}$  with  $p$  attribute values per instance
- ② distance function  $D : d(x_i, x_j) : \mathbb{R}^{p \times p} \rightarrow \mathbb{R}$  where  $d(x_i, x_j) > 0$  if  $x_i \neq x_j$  and is zero otherwise
- ③ function  $S$  that searches for instances that “match” an incoming instance based on  $D$
- ④ function  $R$  that identifies the  $k$  “nearest” (as defined by  $D$ ) instances
- ⑤ function  $A$  that aggregates the “labels” of these  $k$  neighbours, yielding one representative value
- ⑥ function  $L$  that applies this representative label to the incoming instance



# K-Nearest Neighbours: Practical Considerations

## Implementation

- ❶ The training set needs to be stored in a format (such as a `pandas` dataframe) that is ready for both searching and computation

# K-Nearest Neighbours: Practical Considerations

## Implementation

- 1 The training set needs to be stored in a format (such as a `pandas` dataframe) that is ready for both searching and computation
- 2 The distance function  $D$  needs to take account of all the relevant dimensions/attributes, possibly weighted

# K-Nearest Neighbours: Practical Considerations

## Implementation

- ① The training set needs to be stored in a format (such as a `pandas` dataframe) that is ready for both searching and computation
- ② The distance function  $D$  needs to take account of all the relevant dimensions/attributes, possibly weighted
- ③ The search  $S$  and ranking  $R$  functions needs to work well together

# K-Nearest Neighbours: Practical Considerations

## Implementation

- ① The training set needs to be stored in a format (such as a `pandas` dataframe) that is ready for both searching and computation
- ② The distance function  $D$  needs to take account of all the relevant dimensions/attributes, possibly weighted
- ③ The search  $S$  and ranking  $R$  functions needs to work well together
- ④ The aggregation function  $A$  for  $k$ -nearest neighbours just takes the most frequent value (also known as the *mode*) of the  $k$  existing labels

# K-Nearest Neighbours: Practical Considerations

## Implementation

- 1 The training set needs to be stored in a format (such as a `pandas` dataframe) that is ready for both searching and computation
- 2 The distance function  $D$  needs to take account of all the relevant dimensions/attributes, possibly weighted
- 3 The search  $S$  and ranking  $R$  functions needs to work well together
- 4 The aggregation function  $A$  for  $k$ -nearest neighbours just takes the most frequent value (also known as the *mode*) of the  $k$  existing labels

Conceptually this is a very simple algorithm. It can be tweaked by varying  $k$  and  $D$  (or, very rarely,  $A$ ).

# K-Nearest Neighbours: Practical Considerations


## Implementation

- 1 The training set needs to be stored in a format (such as a `pandas` dataframe) that is ready for both searching and computation
- 2 The distance function  $D$  needs to take account of all the relevant dimensions/attributes, possibly weighted
- 3 The search  $S$  and ranking  $R$  functions needs to work well together
- 4 The aggregation function  $A$  for  $k$ -nearest neighbours just takes the most frequent value (also known as the *mode*) of the  $k$  existing labels


Conceptually this is a very simple algorithm. It can be tweaked by varying  $k$  and  $D$  (or, very rarely,  $A$ ). Implementations exist in python (in `scikit-learn`).




# K-Nearest Neighbours: Example prediction




# Classifying iris species



**Iris Versicolor**




**Iris Setosa**





**Iris Virginica**

Given measurements of sepal and petal lengths and widths, can we distinguish between the 3 species?

# K-Nearest Neighbours: Iris SW-SL




# K-Nearest Neighbours: Iris SW-SL




# K-Nearest Neighbours: Iris SW-SL

k = 3 nearest-neighbours fit to the Iris dataset





- The Iris dataset has 4 descriptive attributes, so there are 6 possible pairs

k = 7 nearest-neighbours fit to the Iris dataset





# K-Nearest Neighbours: Iris SW-SL



- The Iris dataset has 4 descriptive attributes, so there are 6 possible pairs
- Of these, the Sepal-Width  $\times$  Sepal-Length combination is the least effective at distinguishing between the three species


# K-Nearest Neighbours: Iris SW-SL




- The Iris dataset has 4 descriptive attributes, so there are 6 possible pairs
- Of these, the Sepal-Width  $\times$  Sepal-Length combination is the least effective at distinguishing between the three species
- In this plot, *I. setosa* (red) is well separated from *I. versicolor* (green) and *I. virginica* (blue)

# K-Nearest Neighbours: Iris SW-SL

k = 3 nearest-neighbours fit to the Iris dataset





k = 7 nearest-neighbours fit to the Iris dataset



- The Iris dataset has 4 descriptive attributes, so there are 6 possible pairs
- Of these, the Sepal-Width  $\times$  Sepal-Length combination is the least effective at distinguishing between the three species
- In this plot, *I. setosa* (red) is well separated from *I. versicolor* (green) and *I. virginica* (blue)
- However the boundary between *I. versicolor* (green) and *I. virginica* (blue) is unclear





# K-Nearest Neighbours: Iris SW-SL




- The Iris dataset has 4 descriptive attributes, so there are 6 possible pairs
- Of these, the Sepal-Width  $\times$  Sepal-Length combination is the least effective at distinguishing between the three species
- In this plot, *I. setosa* (red) is well separated from *I. versicolor* (green) and *I. virginica* (blue)
- However the boundary between *I. versicolor* (green) and *I. virginica* (blue) is unclear
- $k = 3$  has relatively low bias and (possibly) high variance

# K-Nearest Neighbours: Iris SW-SL





- The Iris dataset has 4 descriptive attributes, so there are 6 possible pairs
- Of these, the Sepal-Width  $\times$  Sepal-Length combination is the least effective at distinguishing between the three species
- In this plot, *I. setosa* (red) is well separated from *I. versicolor* (green) and *I. virginica* (blue)
- However the boundary between *I. versicolor* (green) and *I. virginica* (blue) is unclear
- $k = 3$  has relatively low bias and (possibly) high variance
- $k = 7$  has lower variance, pays less attention to “outliers”, so region boundaries are smoother



# K-Nearest Neighbours: Iris PW-PL



# K-Nearest Neighbours: Iris PW-PL




# K-Nearest Neighbours: Iris PW-PL




- As can be seen, the Petal-Width  $\times$  Petal-Length combination separates Iris species better

# K-Nearest Neighbours: Iris PW-PL

k = 3 nearest-neighbours fit to the Iris dataset




k = 7 nearest-neighbours fit to the Iris dataset




- As can be seen, the Petal-Width  $\times$  Petal-Length combination separates Iris species better
- There are still some difficulties distinguishing between *I. versicolor* (green) and *I. virginica* (blue).

# K-Nearest Neighbours: Iris PW-PL

k = 3 nearest-neighbours fit to the Iris dataset




k = 7 nearest-neighbours fit to the Iris dataset




- As can be seen, the Petal-Width  $\times$  Petal-Length combination separates Iris species better
- There are still some difficulties distinguishing between *I. versicolor* (green) and *I. virginica* (blue).
- The size of  $k$  does have some effect, but not as dramatically as the more difficult SW-SL combination

# K-Nearest Neighbours: Iris PW-PL

k = 3 nearest-neighbours fit to the Iris dataset



k = 7 nearest-neighbours fit to the Iris dataset




- As can be seen, the Petal-Width  $\times$  Petal-Length combination separates Iris species better
- There are still some difficulties distinguishing between *I. versicolor* (green) and *I. virginica* (blue).
- The size of  $k$  does have some effect, but not as dramatically as the more difficult SW-SL combination
- The distance function  $D$  depends on the number of dimensions  $p$




# K-Nearest Neighbours: Iris PW-PL

k = 3 nearest-neighbours fit to the Iris dataset




k = 7 nearest-neighbours fit to the Iris dataset




- As can be seen, the Petal-Width  $\times$  Petal-Length combination separates Iris species better
- There are still some difficulties distinguishing between *I. versicolor* (green) and *I. virginica* (blue).
- The size of  $k$  does have some effect, but not as dramatically as the more difficult SW-SL combination
- The distance function  $D$  depends on the number of dimensions  $p$
- If the regions are well separated, as here, adding more dimensions rarely helps

# K-Nearest Neighbours: Iris PW-PL

k = 3 nearest-neighbours fit to the Iris dataset




k = 7 nearest-neighbours fit to the Iris dataset




- As can be seen, the Petal-Width  $\times$  Petal-Length combination separates Iris species better
- There are still some difficulties distinguishing between *I. versicolor* (green) and *I. virginica* (blue).
- The size of  $k$  does have some effect, but not as dramatically as the more difficult SW-SL combination
- The distance function  $D$  depends on the number of dimensions  $p$
- If the regions are well separated, as here, adding more dimensions rarely helps
- Over- and under-fitting is largely down to the choice of  $k$

## Sidebar: Classification over- and under-fitting




## Sidebar: Classification over- and under-fitting



Generally, under-fitted models do not follow the **training** set closely enough, and so are likely to miss comparable features in the **test** set.


## Sidebar: Classification over- and under-fitting



Generally, under-fitted models do not follow the **training** set closely enough, and so are likely to miss comparable features in the **test** set.

Over-fitted models do the opposite, pay too much attention to peculiarities of the **training** set. They “wobble” too much!

## Sidebar: Classification over- and under-fitting




Generally, under-fitted models do not follow the **training** set closely enough, and so are likely to miss comparable features in the **test** set.

Over-fitted models do the opposite, pay too much attention to peculiarities of the **training** set. They “wobble” too much!

Setting  $k = 1$  ensures that all the training data is correctly labeled (by definition) but it rarely generalises well.

## Sidebar: Classification over- and under-fitting



Generally, under-fitted models do not follow the **training** set closely enough, and so are likely to miss comparable features in the **test** set.

Over-fitted models do the opposite, pay too much attention to peculiarities of the **training** set. They “wobble” too much!

Setting  $k = 1$  ensures that all the training data is correctly labeled (by definition) but it rarely generalises well.

As  $k$  increases the boundary becomes smoother. Often that is what you need.

## Sidebar: Classification result summary: Confusion Matrix

k = 1, training

k = 3, training

k = 3, test



# Sidebar: Classification result summary: Confusion Matrix

k = 1, training

<i>predicted</i>		<i>Actual</i>		
		<b>S</b>	<b>V1</b>	<b>V2</b>
<b>S</b>		50	0	0
<b>V1</b>		0	50	0
<b>V2</b>		0	0	50

k = 3, training

<i>predicted</i>		<i>Actual</i>		
		<b>S</b>	<b>V1</b>	<b>V2</b>
<b>S</b>		50	0	0
<b>V1</b>		0	47	3
<b>V2</b>		0	3	47

k = 3, test

<i>predicted</i>		<i>Actual</i>		
		<b>S</b>	<b>V1</b>	<b>V2</b>
<b>S</b>		10	0	0
<b>V1</b>		0	7	3
<b>V2</b>		0	0	10

# Sidebar: Classification result summary: Confusion Matrix

## k = 1, training

<i>predicted</i>		<i>Actual</i>		
		<b>S</b>	<b>V1</b>	<b>V2</b>
<b>S</b>		50	0	0
<b>V1</b>		0	50	0
<b>V2</b>		0	0	50

Each instance is assigned the correct label. There are no off-diagonal terms. **S** represents *I. setosa*, **V1** represents *I. versicolor* and **V2** represents *I. virginica*.

## k = 3, training

<i>predicted</i>		<i>Actual</i>		
		<b>S</b>	<b>V1</b>	<b>V2</b>
<b>S</b>		50	0	0
<b>V1</b>		0	47	3
<b>V2</b>		0	3	47

## k = 3, test

<i>predicted</i>		<i>Actual</i>		
		<b>S</b>	<b>V1</b>	<b>V2</b>
<b>S</b>		10	0	0
<b>V1</b>		0	7	3
<b>V2</b>		0	0	10

# Sidebar: Classification result summary: Confusion Matrix

## k = 1, training

predicted		Actual		
		S	V1	V2
predicted	S	50	0	0
	V1	0	50	0
	V2	0	0	50

Each instance is assigned the correct label. There are no off-diagonal terms. **S** represents *I. setosa*, **V1** represents *I. versicolor* and **V2** represents *I. virginica*.

## k = 3, training

predicted		Actual		
		S	V1	V2
predicted	S	50	0	0
	V1	0	47	3
	V2	0	3	47

Each training instance of *I. setosa* is assigned the right label. However, of the 50 each of *I. versicolor* and *I. virginica*, 3 of each were incorrectly predicted to be the other.

## k = 3, test

predicted		Actual		
		S	V1	V2
predicted	S	10	0	0
	V1	0	7	3
	V2	0	0	10

# Sidebar: Classification result summary: Confusion Matrix

## k = 1, training

predicted		Actual		
		S	V1	V2
predicted	S	50	0	0
	V1	0	50	0
	V2	0	0	50

Each instance is assigned the correct label. There are no off-diagonal terms. **S** represents *I. setosa*, **V1** represents *I. versicolor* and **V2** represents *I. virginica*.

## k = 3, training

predicted		Actual		
		S	V1	V2
predicted	S	50	0	0
	V1	0	47	3
	V2	0	3	47

Each training instance of *I. setosa* is assigned the right label. However, of the 50 each of *I. versicolor* and *I. virginica*, 3 of each were incorrectly predicted to be the other.

## k = 3, test

predicted		Actual		
		S	V1	V2
predicted	S	10	0	0
	V1	0	7	3
	V2	0	0	10

Each test instance of *I. setosa* and *I. virginica* is assigned the right label. However, of the 10 predicted *I. versicolor* (from a stratified sample), 3 were actually *I. virginica*.

# Sidebar: Classification result summary: Confusion Matrix

## k = 1, training

predicted		Actual		
		S	V1	V2
predicted	S	50	0	0
	V1	0	50	0
	V2	0	0	50

Each instance is assigned the correct label. There are no off-diagonal terms. **S** represents *I. setosa*, **V1** represents *I. versicolor* and **V2** represents *I. virginica*.

## k = 3, training

predicted		Actual		
		S	V1	V2
predicted	S	50	0	0
	V1	0	47	3
	V2	0	3	47

Each training instance of *I. setosa* is assigned the right label. However, of the 50 each of *I. versicolor* and *I. virginica*, 3 of each were incorrectly predicted to be the other.

## k = 3, test

predicted		Actual		
		S	V1	V2
predicted	S	10	0	0
	V1	0	7	3
	V2	0	0	10

Each test instance of *I. setosa* and *I. virginica* is assigned the right label. However, of the 10 predicted *I. versicolor* (from a stratified sample), 3 were actually *I. virginica*.

- k-nearest neighbours works better with “small” dimension  $p$  but can scale well to “large” number of cases  $n$ .

# Sidebar: Classification result summary: Confusion Matrix

## k = 1, training

predicted		Actual		
		S	V1	V2
predicted	S	50	0	0
	V1	0	50	0
	V2	0	0	50

Each instance is assigned the correct label. There are no off-diagonal terms. **S** represents *I. setosa*, **V1** represents *I. versicolor* and **V2** represents *I. virginica*.

## k = 3, training

predicted		Actual		
		S	V1	V2
predicted	S	50	0	0
	V1	0	47	3
	V2	0	3	47

Each training instance of *I. setosa* is assigned the right label. However, of the 50 each of *I. versicolor* and *I. virginica*, 3 of each were incorrectly predicted to be the other.

## k = 3, test

predicted		Actual		
		S	V1	V2
predicted	S	10	0	0
	V1	0	7	3
	V2	0	0	10

Each test instance of *I. setosa* and *I. virginica* is assigned the right label. However, of the 10 predicted *I. versicolor* (from a stratified sample), 3 were actually *I. virginica*.

- k-nearest neighbours works better with “small” dimension  $p$  but can scale well to “large” number of cases  $n$ .
- Unlike most other techniques, decision boundaries are implicit, not explicit.

# Sidebar: Classification result summary: Confusion Matrix

## k = 1, training

predicted		Actual		
		S	V1	V2
predicted	S	50	0	0
	V1	0	50	0
	V2	0	0	50

Each instance is assigned the correct label. There are no off-diagonal terms. **S** represents *I. setosa*, **V1** represents *I. versicolor* and **V2** represents *I. virginica*.

## k = 3, training

predicted		Actual		
		S	V1	V2
predicted	S	50	0	0
	V1	0	47	3
	V2	0	3	47

Each training instance of *I. setosa* is assigned the right label. However, of the 50 each of *I. versicolor* and *I. virginica*, 3 of each were incorrectly predicted to be the other.

## k = 3, test

predicted		Actual		
		S	V1	V2
predicted	S	10	0	0
	V1	0	7	3
	V2	0	0	10

Each test instance of *I. setosa* and *I. virginica* is assigned the right label. However, of the 10 predicted *I. versicolor* (from a stratified sample), 3 were actually *I. virginica*.

- k-nearest neighbours works better with “small” dimension  $p$  but can scale well to “large” number of cases  $n$ .
- Unlike most other techniques, decision boundaries are implicit, not explicit.
- If the decision boundary is also needed, might be better to use a different algorithm.

## k-nearest-neighbours in python

Python's `scikit-learn` libraries provide a general interface to model fitting that abstracts away most of the details.

### Method (Identifying the Iris species)

```
1  # create the model
2  knn = neighbors.KNeighborsClassifier(n_neighbors=5)
3
4  # fit the model
5  knn.fit(X, y)
6
7  # What kind of iris has 3cm x 5cm sepal and 4cm x 2cm petal?
8  result = knn.predict([[3, 5, 4, 2],])
9
10 # it is a versicolor...
11 print(iris.target_names[result])
12
13 # class membership probabilities are [0. , 0.8, 0.2]
14 knn.predict_proba([[3, 5, 4, 2],])
```



# k-nearest-neighbours in python


Python's `scikit-learn` libraries provide a general interface to model fitting that abstracts away most of the details.

## Method (Identifying the Iris species)

```
1  # create the model
2  knn = neighbors.KNeighborsClassifier(n_neighbors=5)
3
4  # fit the model
5  knn.fit(X, y)
6
7  # What kind of iris has 3cm x 5cm sepal and 4cm x 2cm petal?
8  result = knn.predict([[3, 5, 4, 2],])
9
10 # it is a versicolor...
11 print(iris.target_names[result])
12
13 # class membership probabilities are [0. , 0.8, 0.2]
14 knn.predict_proba([[3, 5, 4, 2],])
```

Very few lines of code are needed!

# How might things go wrong?



➤ **K nearest neighbors is very sensitive to unbalanced data, so need to be careful!!**

# Outline

---

1. Introduction	3
1.1. Learning from data	4
1.2. Lazy vs Eager Learners	6
2. Introduction to Classification	7
3. k Nearest Neighbours	11
4. Summary	22

# Summary

---

- Classification is a *supervised learning* operation, where training data is used to configure the classifier

# Summary

- Classification is a *supervised learning* operation, where training data is used to configure the classifier
- k-nearest-neighbours is a *lazy* classifier

# Summary

- Classification is a *supervised learning* operation, where training data is used to configure the classifier
- k-nearest-neighbours is a *lazy* classifier
- Lazy means the **prediction** is based on the training data only - a separate model is not trained or used for prediction

# Summary

- Classification is a *supervised learning* operation, where training data is used to configure the classifier
- k-nearest-neighbours is a *lazy* classifier
- Lazy means the **prediction** is based on the training data only - a separate model is not trained or used for prediction
- The knn algorithm is conceptually simple - vote for the most common label in the local neighbourhood of the unseen data instance

# Summary

- Classification is a *supervised learning* operation, where training data is used to configure the classifier
- k-nearest-neighbours is a *lazy* classifier
- Lazy means the **prediction** is based on the training data only - a separate model is not trained or used for prediction
- The knn algorithm is conceptually simple - vote for the most common label in the local neighbourhood of the unseen data instance
- There are some options in how the classifier is configured, notably choice of distance function and the hyperparameter k



# Summary

- Classification is a *supervised learning* operation, where training data is used to configure the classifier
- k-nearest-neighbours is a *lazy* classifier
- Lazy means the **prediction** is based on the training data only - a separate model is not trained or used for prediction
- The knn algorithm is conceptually simple - vote for the most common label in the local neighbourhood of the unseen data instance
- There are some options in how the classifier is configured, notably choice of distance function and the hyperparameter k
- Classification performance is assessed using a *confusion matrix*

# Summary

- Classification is a *supervised learning* operation, where training data is used to configure the classifier
- k-nearest-neighbours is a *lazy* classifier
- Lazy means the **prediction** is based on the training data only - a separate model is not trained or used for prediction
- The knn algorithm is conceptually simple - vote for the most common label in the local neighbourhood of the unseen data instance
- There are some options in how the classifier is configured, notably choice of distance function and the hyperparameter k
- Classification performance is assessed using a *confusion matrix*
- Predictions do not always match unseen data - ideally they would

# Summary

- Classification is a *supervised learning* operation, where training data is used to configure the classifier
- k-nearest-neighbours is a *lazy* classifier
- Lazy means the **prediction** is based on the training data only - a separate model is not trained or used for prediction
- The knn algorithm is conceptually simple - vote for the most common label in the local neighbourhood of the unseen data instance
- There are some options in how the classifier is configured, notably choice of distance function and the hyperparameter k
- Classification performance is assessed using a *confusion matrix*
- Predictions do not always match unseen data - ideally they would
- Performance on unseen data (used for testing) is the most common quality criterion, but there are others

# Summary

- Classification is a *supervised learning* operation, where training data is used to configure the classifier
- k-nearest-neighbours is a *lazy* classifier
- Lazy means the **prediction** is based on the training data only - a separate model is not trained or used for prediction
- The knn algorithm is conceptually simple - vote for the most common label in the local neighbourhood of the unseen data instance
- There are some options in how the classifier is configured, notably choice of distance function and the hyperparameter k
- Classification performance is assessed using a *confusion matrix*
- Predictions do not always match unseen data - ideally they would
- Performance on unseen data (used for testing) is the most common quality criterion, but there are others
- Later, we will meet some metrics that can be computed from the confusion matrix and used to compare different classifiers

# Summary

- Classification is a *supervised learning* operation, where training data is used to configure the classifier
- k-nearest-neighbours is a *lazy* classifier
- Lazy means the **prediction** is based on the training data only - a separate model is not trained or used for prediction
- The knn algorithm is conceptually simple - vote for the most common label in the local neighbourhood of the unseen data instance
- There are some options in how the classifier is configured, notably choice of distance function and the hyperparameter k
- Classification performance is assessed using a *confusion matrix*
- Predictions do not always match unseen data - ideally they would
- Performance on unseen data (used for testing) is the most common quality criterion, but there are others
- Later, we will meet some metrics that can be computed from the confusion matrix and used to compare different classifiers
- We can use such metrics to validate our classifier choice and search for optimal hyperparameters (*hyperparameter tuning*)