



Optimization algorithms

Quiz, 10 questions



Congratulations! You passed!

Next Item



1 / 1
point

1.
Which notation would you use to denote the 3rd layer's activations when the input is the 7th example from the 8th minibatch?



$a^{[3]\{8\}(7)}$



Correct



$a^{[8]\{7\}(3)}$



$a^{[3]\{7\}(8)}$



$a^{[8]\{3\}(7)}$



1 / 1
point

2.
Which of these statements about mini-batch gradient descent do you agree with?



Training one epoch (one pass through the training set) using mini-batch gradient descent is faster than training one epoch using batch gradient descent.



One iteration of mini-batch gradient descent (computing on a single mini-batch) is faster than one iteration of batch gradient descent.



Correct



You should implement mini-batch gradient descent without an explicit for-loop over different mini-batches, so that the algorithm processes all mini-batches at the same time (vectorization).



1 / 1
point

3.
Why is the best mini-batch size usually not 1 and not m, but instead something in-between?



If the mini-batch size is 1, you end up having to process the entire training set before making any progress.



Un-selected is correct



If the mini-batch size is 1, you lose the benefits of vectorization across examples in the mini-batch.

Optimization algorithms

← Correct

Quiz, 10 questions



If the mini-batch size is m , you end up with stochastic gradient descent, which is usually slower than mini-batch gradient descent.



Un-selected is correct



If the mini-batch size is m , you end up with batch gradient descent, which has to process the whole training set before making progress.




Correct



1 / 1
point

4.

Suppose your learning algorithm's cost J , plotted as a function of the number of iterations, looks like this:



Which of the following do you agree with?



Whether you're using batch gradient descent or mini-batch gradient descent, something is wrong.



If you're using mini-batch gradient descent, this looks acceptable. But if you're using batch gradient descent, something is wrong.



Correct



If you're using mini-batch gradient descent, something is wrong. But if you're using batch gradient descent, this looks acceptable.



Whether you're using batch gradient descent or mini-batch gradient descent, this looks acceptable.



Optimization algorithms

1 point

Quiz, 10 questions

5.

Suppose the temperature in Casablanca over the first three days of January are the same:

Jan 1st: $\theta_1 = 10^\circ C$

Jan 2nd: $\theta_2 = 10^\circ C$

(We used Fahrenheit in lecture, so will use Celsius here in honor of the metric world.)

Say you use an exponentially weighted average with $\beta = 0.5$ to track the temperature: $v_0 = 0$, $v_t = \beta v_{t-1} + (1 - \beta)\theta_t$. If v_2 is the value computed after day 2 without bias correction, and $v_2^{corrected}$ is the value you compute with bias correction. What are these values? (You might be able to do this without a calculator, but you don't actually need one. Remember what is bias correction doing.)

☐ $v_2 = 10$, $v_2^{corrected} = 7.5$

☒ $v_2 = 7.5$, $v_2^{corrected} = 10$



Correct

☐ $v_2 = 7.5$, $v_2^{corrected} = 7.5$

☐ $v_2 = 10$, $v_2^{corrected} = 10$



1 / 1 point

6.

Which of these is NOT a good learning rate decay scheme? Here, t is the epoch number.

☒ $\alpha = e^t \alpha_0$



Correct

☐ $\alpha = 0.95^t \alpha_0$

☐ $\alpha = \frac{1}{1+2*t} \alpha_0$

☐ $\alpha = \frac{1}{\sqrt{t}} \alpha_0$




1 / 1 point

7.

You use an exponentially weighted average on the London temperature dataset. You use the following to track the temperature:

$\hat{v}_t = \beta v_t + (1 - \beta) \hat{v}_{t-1}$. The red line below was computed using $\beta = 0.9$. What would happen to your red curve as you vary β ? (Check the two questions that apply)



☐ Decreasing β will shift the red line slightly to the right.



Un-selected is correct

☐ Increasing β will shift the red line slightly to the right.



Correct

True, remember that the red line corresponds to $\beta = 0.9$. In lecture we had a green line $\beta = 0.98$ that is slightly shifted to the right.

☐ Decreasing β will create more oscillation within the red line.



Correct

True, remember that the red line corresponds to $\beta = 0.9$. In lecture we had a yellow line $\beta = 0.98$ that had a lot of oscillations.

☐ Increasing β will create more oscillations within the red line.



Un-selected is correct




1 / 1
point

8.

Consider this figure:

Quiz, 10 questions

Optimization algorithms



These plots were generated with gradient descent; with gradient descent with momentum ($\beta = 0.5$) and gradient descent with momentum ($\beta = 0.9$). Which curve corresponds to which algorithm?

- ☐ (1) is gradient descent with momentum (small β), (2) is gradient descent with momentum (small β), (3) is gradient descent
- ☐ (1) is gradient descent. (2) is gradient descent with momentum (large β). (3) is gradient descent with momentum (small β)
- ☐ (1) is gradient descent with momentum (small β). (2) is gradient descent. (3) is gradient descent with momentum (large β)
- ☒ (1) is gradient descent. (2) is gradient descent with momentum (small β). (3) is gradient descent with momentum (large β)

Correct

1 / 1
point

9.

Suppose batch gradient descent in a deep network is taking excessively long to find a value of the parameters that achieves a small value for the cost function $\mathcal{J}(W^{[1]}, b^{[1]}, \dots, W^{[L]}, b^{[L]})$. Which of the following techniques could help find parameter values that attain a small value for \mathcal{J} ? (Check all that apply)

- ☐ Try initializing all the weights to zero

Un-selected is correct

- ☐ Try tuning the learning rate α

Correct

- ☐ Try using Adam

Correct



Try better random initialization for the weights



Optimization algorithms

Correct Quiz, 10 questions



Try mini-batch gradient descent

Correct

1 / 1
point

10.

Which of the following statements about Adam is False?

The learning rate hyperparameter α in Adam usually needs to be tuned.

Adam should be used with batch gradient computations, not with mini-batches.

Correct



Adam combines the advantages of RMSProp and momentum

We usually use "default" values for the hyperparameters β_1, β_2 and ε in Adam ($\beta_1 = 0.9, \beta_2 = 0.999, \varepsilon = 10^{-8}$)