



deeplearning.ai

Basics of Neural Network Programming

Vectorizing Logistic Regression

Vectorizing Logistic Regression

$$z^{(1)} = w^T x^{(1)} + b$$

$$a^{(1)} = \sigma(z^{(1)})$$

$$z^{(2)} = w^T x^{(2)} + b$$

$$a^{(2)} = \sigma(z^{(2)})$$

$$z^{(3)} = w^T x^{(3)} + b$$

$$a^{(3)} = \sigma(z^{(3)})$$



deeplearning.ai

Basics of Neural Network Programming

Vectorizing Logistic Regression's Gradient Computation

Vectorizing Logistic Regression

Implementing Logistic Regression

$J = 0, \quad dw_1 = 0, \quad dw_2 = 0, \quad db = 0$

for $i = 1$ to m :

$$z^{(i)} = w^T x^{(i)} + b$$

$$a^{(i)} = \sigma(z^{(i)})$$

$$J += -[y^{(i)} \log a^{(i)} + (1 - y^{(i)}) \log(1 - a^{(i)})]$$

$$dz^{(i)} = a^{(i)} - y^{(i)}$$

$$dw_1 += x_1^{(i)} dz^{(i)}$$

$$dw_2 += x_2^{(i)} dz^{(i)}$$

$$db += dz^{(i)}$$

$J = J/m, \quad dw_1 = dw_1/m, \quad dw_2 = dw_2/m$

$db = db/m$