







deeplearning.ai

One hidden layer
Neural Network

Neural Networks Overview

What is a Neural Network?






deeplearning.ai

One hidden layer
Neural Network

Neural Network
Representation

Neural Network Representation






deeplearning.ai

One hidden layer Neural Network


Computing a
Neural Network's
Output

Neural Network Representation




$$z = w^T x + b$$

$$a = \sigma(z)$$




Neural Network Representation




$$z = w^T x + b$$

$$a = \sigma(z)$$



Neural Network Representation




$$z_1^{[1]} = w_1^{[1]T} x + b_1^{[1]}, \quad a_1^{[1]} = \sigma(z_1^{[1]})$$

$$z_2^{[1]} = w_2^{[1]T} x + b_2^{[1]}, \quad a_2^{[1]} = \sigma(z_2^{[1]})$$

$$z_3^{[1]} = w_3^{[1]T} x + b_3^{[1]}, \quad a_3^{[1]} = \sigma(z_3^{[1]})$$

$$z_4^{[1]} = w_4^{[1]T} x + b_4^{[1]}, \quad a_4^{[1]} = \sigma(z_4^{[1]})$$

Neural Network Representation learning



Given input x :

$$z^{[1]} = W^{[1]}x + b^{[1]}$$

$$a^{[1]} = \sigma(z^{[1]})$$

$$z^{[2]} = W^{[2]}a^{[1]} + b^{[2]}$$

$$a^{[2]} = \sigma(z^{[2]})$$




deeplearning.ai

One hidden layer Neural Network

Vectorizing across multiple examples

Vectorizing across multiple examples



$$z^{[1]} = W^{[1]}x + b^{[1]}$$

$$a^{[1]} = \sigma(z^{[1]})$$

$$z^{[2]} = W^{[2]}a^{[1]} + b^{[2]}$$

$$a^{[2]} = \sigma(z^{[2]})$$

Vectorizing across multiple examples

for $i = 1$ to m :

$$z^{[1]}(i) = W^{[1]}x^{(i)} + b^{[1]}$$

$$a^{[1]}(i) = \sigma(z^{[1]}(i))$$

$$z^{[2]}(i) = W^{[2]}a^{[1]}(i) + b^{[2]}$$

$$a^{[2]}(i) = \sigma(z^{[2]}(i))$$




deeplearning.ai

One hidden layer Neural Network

Explanation
for vectorized
implementation

Justification for vectorized implementation

Recap of vectorizing across multiple examples



$$X = \begin{bmatrix} | & | & & | \\ x^{(1)} & x^{(2)} & \dots & x^{(m)} \\ | & | & & | \end{bmatrix}$$

$$A^{[1]} = \begin{bmatrix} | & | & & | \\ a^{[1]}(1) & a^{[1]}(2) & \dots & a^{[1]}(m) \\ | & | & & | \end{bmatrix}$$

for $i = 1$ to m

$$z^{[1]}(i) = W^{[1]}x^{(i)} + b^{[1]}$$

$$a^{[1]}(i) = \sigma(z^{[1]}(i))$$

$$z^{[2]}(i) = W^{[2]}a^{[1]}(i) + b^{[2]}$$

$$a^{[2]}(i) = \sigma(z^{[2]}(i))$$

$$Z^{[1]} = W^{[1]}X + b^{[1]}$$

$$A^{[1]} = \sigma(Z^{[1]})$$

$$Z^{[2]} = W^{[2]}A^{[1]} + b^{[2]}$$

$$A^{[2]} = \sigma(Z^{[2]})$$




deeplearning.ai

One hidden layer Neural Network

Activation functions

Activation functions



Given x :


$$z^{[1]} = W^{[1]}x + b^{[1]}$$

$$a^{[1]} = \sigma(z^{[1]})$$




$$z^{[2]} = W^{[2]}a^{[1]} + b^{[2]}$$

$$a^{[2]} = \sigma(z^{[2]})$$

Pros and cons of activation functions



sigmoid: $a = \frac{1}{1 + e^{-z}}$






deeplearning.ai

One hidden layer Neural Network

Why do you
need non-linear
activation functions?

Activation function



Given x :

$$z^{[1]} = W^{[1]}x + b^{[1]}$$

$$a^{[1]} = g^{[1]}(z^{[1]})$$

$$z^{[2]} = W^{[2]}a^{[1]} + b^{[2]}$$

$$a^{[2]} = g^{[2]}(z^{[2]})$$




deeplearning.ai

One hidden layer
Neural Network


Derivatives of
activation functions

Sigmoid activation function




$$g(z) = \frac{1}{1 + e^{-z}}$$

Tanh activation function




$$g(z) = \tanh(z)$$

ReLU and Leaky ReLU



ReLU



Leaky ReLU



deeplearning.ai

One hidden layer
Neural Network

Gradient descent for
neural networks

Gradient descent for neural networks

Formulas for computing derivatives




deeplearning.ai

One hidden layer
Neural Network


Backpropagation
intuition (Optional)

Computing gradients

Logistic regression



Neural network gradients



Summary of gradient descent

$$dz^{[2]} = a^{[2]} - y$$

$$dW^{[2]} = dz^{[2]} a^{[1]T}$$

$$db^{[2]} = dz^{[2]}$$

$$dz^{[1]} = W^{[2]T} dz^{[2]} * g^{[1]'}(z^{[1]})$$

$$dW^{[1]} = dz^{[1]} x^T$$

$$db^{[1]} = dz^{[1]}$$

Summary of gradient descent

$$dz^{[2]} = a^{[2]} - y$$

$$dW^{[2]} = dz^{[2]} a^{[1]T}$$

$$db^{[2]} = dz^{[2]}$$

$$dz^{[1]} = W^{[2]T} dz^{[2]} * g^{[1]'}(z^{[1]})$$

$$dW^{[1]} = dz^{[1]} x^T$$

$$db^{[1]} = dz^{[1]}$$

$$dZ^{[2]} = A^{[2]} - Y$$

$$dW^{[2]} = \frac{1}{m} dZ^{[2]} A^{[1]T}$$

$$db^{[2]} = \frac{1}{m} np.sum(dZ^{[2]}, axis = 1, keepdims = True)$$

$$dZ^{[1]} = W^{[2]T} dZ^{[2]} * g^{[1]'}(Z^{[1]})$$

$$dW^{[1]} = \frac{1}{m} dZ^{[1]} X^T$$

$$db^{[1]} = \frac{1}{m} np.sum(dZ^{[1]}, axis = 1, keepdims = True)$$




deeplearning.ai

One hidden layer
Neural Network

Random Initialization

What happens if you initialize weights to zero?



Random initialization

