

LabelFusion: Learning to Fuse LLMs and Transformer Classifiers for Robust Text Classification

Michael Schlee^{1,2}, Chistoph Weisser^{1,2}, Timo Kivimäki¹, Mel¹, and Benjamin Saefken¹

¹ Campus-Institut Data Science, Göttingen, Germany ² Centre for Statistics, Georg-August-Universität Göttingen, Germany

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) ↗
- [Repository](#) ↗
- [Archive](#) ↗

Editor: [Open Journals](#) ↗

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

LabelFusion is a fusion ensemble for text classification that learns to combine a traditional transformer-based classifier (e.g., RoBERTa) with one or more Large Language Models (LLMs) such as OpenAI GPT, Google Gemini, or DeepSeek) to deliver accurate and cost-aware predictions across multi-class and multi-label tasks. The package provides a simple high-level interface (AutoFusionClassifier) that trains the full pipeline end-to-end with minimal configuration, and a flexible API for advanced users. Under the hood, LabelFusion concatenates vector signals from the ML backbone (logits) and LLM(s) (per-class scores) and trains a compact multi-layer perceptron (FusionMLP) to produce the final prediction. This learned fusion approach captures complementary strengths of LLM reasoning and transformer efficiency, yielding robust performance across domains—achieving 92.4% accuracy on AG News topic classification—while enabling practical trade-offs between accuracy, latency, and cost.

Statement of Need

Modern text classification spans diverse scenarios—from sentiment and topic tagging to policy enforcement and routing—often under constraints that vary per deployment (throughput, cost ceilings, data privacy). While transformer classifiers such as BERT/RoBERTa achieve strong supervised performance (Devlin et al., 2018; Liu et al., 2019), frontier LLMs can excel in low-data, ambiguous, or cross-domain settings (OpenAI, 2023). No single model family is uniformly best: LLMs are powerful yet comparatively costly and rate-limited, whereas fine-tuned transformers are efficient but may struggle with out-of-distribution cases.

LabelFusion addresses this gap by: (1) exposing a minimal “AutoFusion” interface that trains a learned combination of an ML backbone and one or more LLMs; (2) supporting both multi-class and multi-label classification; (3) providing a lightweight fusion learner that directly fits on LLM scores and ML logits; and (4) integrating cleanly with existing ensemble utilities. Researchers and practitioners can therefore leverage LLMs where they add value while retaining the speed and determinism of transformer models.

State of the Field

Ensembles improve robustness by aggregating diverse predictors (Dietterich, 2000; Hansen & Salamon, 1990). Mixture-of-experts approaches further specialize components and learn to combine their outputs (Jacobs et al., 1991). In applied NLP, common tools such as scikit-learn (Pedregosa et al., 2011) and Hugging Face Transformers (Wolf et al., 2019) offer strong baselines but do not provide a turnkey, learned fusion of LLMs with supervised transformers. Orchestration frameworks (e.g., LangChain) focus on tool use rather than classification ensembles. LabelFusion contributes a focused, production-minded implementation of a small learned combiner that operates on per-class signals from both model families.

42 Functionality and Design

43 LabelFusion consists of three layers:

- 44 ■ ML component: a RoBERTa-style classifier produces per-class logits for input texts.
- 45 ■ LLM component(s): provider-specific classifiers (OpenAI, Gemini, DeepSeek) return
- 46 per-class scores via prompting. Scores can be cached to minimize API calls when cache
- 47 locations are provided.
- 48 ■ Fusion component: a compact MLP concatenates ML logits and LLM scores and outputs
- 49 fused logits. The ML backbone is trained/fine-tuned with a small learning rate; the fusion
- 50 MLP uses a higher rate, enabling rapid adaptation without destabilizing the encoder.

51 Key features:

- 52 ■ **Multi-class and multi-label support** with consistent data structures and unified training
- 53 pipeline.
- 54 ■ **Optional LLM response caching** reuses on-disk predictions when cache paths are supplied,
- 55 with dataset-hash validation to guard against stale files.
- 56 ■ **Batched scoring** processes multiple texts efficiently with configurable batch sizes for both
- 57 ML tokenization and LLM API calls.
- 58 ■ **Results management** via ResultsManager tracks experiments, stores predictions, com-
- 59 puts metrics, and enables reproducible research workflows.
- 60 ■ **Flexible interfaces:** Command-line training via `train_fusion.py` with YAML configs for
- 61 research; or minimal AutoFusion API for quick deployment.
- 62 ■ **Composable design:** LabelFusion can serve as a strong base learner in higher-level
- 63 ensembles (e.g., voting/weighted combinations of multiple fusion models).

64 Minimal Example (AutoFusion)

```
from textclassify import AutoFusionClassifier
```

```
config = {  
    'llm_provider': 'deepseek',  
    'label_columns': ['positive', 'negative', 'neutral']  
}
```

```
clf = AutoFusionClassifier(config)
```

```
clf.fit(train_dataframe)
```

trains ML backbone, gathers LLM scores, fits fus

```
pred = clf.predict(["This is amazing!"]) # fused prediction
```

65 CLI and Configuration

66 Users can generate a starter config and train via the command line:

- 67 ■ Create config: `python train_fusion.py --create-config fusion_config.yaml`
- 68 ■ Train: `python train_fusion.py --config fusion_config.yaml`
- 69 ■ Optional test data and output artifacts are also supported.

70 Quality Control

71 The repository ships legacy unit tests under `tests/evaluation/old/` that cover configuration

72 handling, core types, and package integration. Fusion-specific logic is currently exercised

73 through CLI-driven workflows and notebooks that run end-to-end training with deterministic

74 seeds where applicable.

75 Evaluation scripts (`tests/evaluation/`) provide comprehensive benchmarking on standard

76 datasets: - **AG News** (Zhang et al., 2015): 4-class topic classification with experiments

77 across varying training data sizes (20%–100%) - **GoEmotions** (Demszky et al., 2020): 28-class

78 multi-label emotion classification for validating multi-label fusion performance

LLM scoring paths implement retries and disk caching; transformer training supports standard sanity checks (overfit a small batch, reduced batch sizes for constrained hardware). Metrics (accuracy/F1, per-label scores) are computed automatically and stored with run artifacts to facilitate regression tracking and reproducibility.

Availability and Installation

LabelFusion is distributed as part of the `textclassify` package under the MIT license and is available at <https://github.com/DataandAIResearch/LabelFusion>. The fusion components require Python 3.8+ and common scientific Python dependencies (PyTorch, transformers, scikit-learn, numpy, pandas, PyYAML). Optional plotting depends on matplotlib/seaborn. Installation and quick-start snippets are provided in the README and FUSION_README.md.

Production-Ready Features

Beyond the core fusion methodology, LabelFusion includes features for practical deployment:

- **LLM Response Caching:** Optional disk-backed caches reuse prior predictions when cache paths are supplied, with dataset hashes to flag inconsistent inputs.
- **Results Management:** Built-in ResultsManager tracks experiments, stores predictions, and computes metrics automatically. Supports comparison across runs and configuration tracking.
- **Batch Processing:** Efficient batched scoring of texts with configurable batch sizes for both ML and LLM components.

Impact and Use Cases

Empirical Performance

LabelFusion has been evaluated on standard benchmark datasets to validate its effectiveness. Key findings demonstrate consistent improvements over individual model components:

AG News Topic Classification

Evaluation on the AG News dataset (Zhang et al., 2015) (4-class topic classification) with 5,000 test samples shows:

Training Data	Model	Accuracy	F1-Score	Precision	Recall
20% (800)	Fusion	92.2%	0.922	0.923	0.922
20% (800)	RoBERTa	89.8%	0.899	0.902	0.898
20% (800)	OpenAI	84.4%	0.844	0.857	0.844
40% (1,600)	Fusion	92.2%	0.922	0.924	0.922
40% (1,600)	RoBERTa	91.0%	0.911	0.913	0.910
40% (1,600)	OpenAI	84.4%	0.844	0.857	0.844
100% (4,000)	Fusion	92.4%	0.924	0.926	0.924
100% (4,000)	RoBERTa	92.2%	0.922	0.923	0.922
100% (4,000)	OpenAI	84.4%	0.844	0.857	0.844

Key Observations: - Fusion consistently outperforms individual models across all training data sizes - With only 20% training data, Fusion achieves 92.2% accuracy—matching its performance with full data - Demonstrates superior **data efficiency**: fusion learning extracts maximum value from limited examples - RoBERTa alone requires 100% of data to approach Fusion's 20% performance - LLM (OpenAI) shows stable but lower performance, highlighting the value of combining approaches

111 These results validate that learned fusion captures complementary strengths: the LLM provides
 112 robust reasoning even with limited training data, while the ML backbone adds efficiency and
 113 domain-specific patterns.

114 Application Domains

115 Learned fusion excels in scenarios where model strengths complement each other:

- 116 ■ **Customer feedback analysis** with nuanced multi-label taxonomies where LLMs handle
 117 ambiguous sentiment while ML models efficiently process clear cases
- 118 ■ **Content moderation** where uncertain cases benefit from LLM reasoning while rou-
 119 tine items rely on the fast ML backbone, enabling real-time processing with accuracy
 120 guarantees
- 121 ■ **Scientific literature classification** across heterogeneous topics where domain shift is
 122 common and LLMs provide robustness to new terminology
- 123 ■ **Low-resource settings** where limited training data is available but task complexity requires
 124 sophisticated reasoning

125 The approach enables pragmatic cost control (e.g., the fusion layer learns when to rely more
 126 heavily on the efficient ML backbone versus the more expensive LLM signal) while retaining a
 127 single trainable decision surface that optimizes for the specific deployment constraints.

128 Acknowledgements

129 We thank contributors and users who reported issues and shared datasets. LabelFusion
 130 builds on the open-source ecosystem, notably Hugging Face Transformers (Wolf et al., 2019),
 131 scikit-learn (Pedregosa et al., 2011), PyTorch (Paszke et al., 2019), and LLM provider SDKs.
 132 We acknowledge the use of the AG News and GoEmotions benchmark datasets for evaluation.

133 References

- 134 Demszky, D., Movshovitz-Attias, D., Ko, J., Cowen, A., Nemade, G., & Ravi, S. (2020).
 135 GoEmotions: A dataset of fine-grained emotions. *Proceedings of the 58th Annual Meeting*
 136 *of the Association for Computational Linguistics*, 4040–4054.
- 137 Devlin, J., Chang, M.-W., Lee, K., & Toutanova, K. (2018). BERT: Pre-training of deep
 138 bidirectional transformers for language understanding. *arXiv Preprint arXiv:1810.04805*.
- 139 Dietterich, T. G. (2000). Ensemble methods in machine learning. *International Workshop on*
 140 *Multiple Classifier Systems*, 1–15.
- 141 Hansen, L. K., & Salamon, P. (1990). Neural network ensembles. *IEEE Transactions on*
 142 *Pattern Analysis and Machine Intelligence*, 12(10), 993–1001.
- 143 Jacobs, R. A., Jordan, M. I., Nowlan, S. J., & Hinton, G. E. (1991). Adaptive mixtures of
 144 local experts. *Neural Computation*, 3(1), 79–87.
- 145 Liu, Y., Ott, M., Goyal, N., Du, J., Joshi, M., Chen, D., Levy, O., Lewis, M., Zettlemoyer,
 146 L., & Stoyanov, V. (2019). RoBERTa: A robustly optimized BERT pretraining approach.
 147 *arXiv Preprint arXiv:1907.11692*.
- 148 OpenAI. (2023). GPT-4 technical report. *arXiv Preprint arXiv:2303.08774*.
- 149 Paszke, A., Gross, S., Massa, F., Lerer, A., Bradbury, J., Chanan, G., Killeen, T., Lin,
 150 Z., Gimelshein, N., Antiga, L., & others. (2019). PyTorch: An imperative style, high-
 151 performance deep learning library. *Advances in Neural Information Processing Systems*,
 152 32.
- 153 Pedregosa, F., Varoquaux, G., Gramfort, A., Michel, V., Thirion, B., Grisel, O., Blondel, M.,
 154 Prettenhofer, P., Weiss, R., Dubourg, V., & others. (2011). Scikit-learn: Machine learning

- 155 in python. *Journal of Machine Learning Research*, 12(Oct), 2825–2830.
- 156 Wolf, T., Debut, L., Sanh, V., Chaumond, J., Delangue, C., Moi, A., Cistac, P., Rault, T.,
157 Louf, R., Funtowicz, M., & others. (2019). HuggingFace's transformers: State-of-the-art
158 natural language processing. *arXiv Preprint arXiv:1910.03771*.
- 159 Zhang, X., Zhao, J., & LeCun, Y. (2015). Character-level convolutional networks for text
160 classification. *Advances in Neural Information Processing Systems*, 28, 649–657.

DRAFT