DATA SHEET

74LVC16245A/ 74LVCH16245A

16-bit bus transceiver with direction pin; 5V tolerant (3-State)

Product specification
Supersedes data of 1997 Aug 1
IC24 Data Handbook

1997 Sep 25

Philips
Semiconductors

PHILIPS

16-bit bus transceiver with direction pin; 5V tolerant (3-State)

74LVC16245A/ 74LVCH16245A

FEATURES

- 5 volt tolerant inputs/outputs for interfacing with 5V logic
- Wide supply voltage range of 1.2V to 3.6V
- Complies with JEDEC standard no. 8-1A
- CMOS low power consumption
- MULTIBYTE™ flow-through standard pin-out architecture
- Low inductance multiple power and ground pins for minimum noise and ground bounce
- Direct interface with TTL levels
- High impedance when V_{CC} = 0
- All data inputs have bus hold (74LVCH16245A only)

DESCRIPTION

The 74LVC(H)16245A is a high-performance, low-power, low-voltage, Si-gate CMOS device, superior to most advanced CMOS compatible TTL families. Inputs can be driven from either 3.3V or 5V devices. In 3-State operation, outputs can handle 5V. These features allow the use of these devices in a mixed 3.3V/5V environment.

The 74LVC(H)16245A is a 16-bit transceiver featuring non-inverting 3-State bus compatible outputs in both send and receive directions. The 74LVC(H)16245A features two output enable ($n\overline{OE}$) inputs for easy cascading and two send/receive (nDIR) inputs for direction control. $n\overline{OE}$ controls the outputs so that the buses are effectively isolated. This device can be used as two 8-bit transceivers or one 16-bit transceiver.

The 74LVCH16245A bus hold data inputs eliminates the need for extreme pull up resistors to hold unused inputs.

PIN CONFIGURATION



ORDERING INFORMATION

PACKAGES	TEMPERATURE RANGE	OUTSIDE NORTH AMERICA	NORTH AMERICA	DWG NUMBER
48-Pin Plastic SSOP Type III	–40°C to +85°C	74LVC16245A DL	VC16245A DL	SOT370-1
48-Pin Plastic TSSOP Type II	–40°C to +85°C	74LVC16245A DGG	VC16245A DGG	SOT362-1
48-Pin Plastic SSOP Type III	–40°C to +85°C	74LVCH16245A DL	VCH16245A DL	SOT370-1
48-Pin Plastic TSSOP Type II	–40°C to +85°C	74LVCH16245A DGG	VCH16245A DGG	SOT362-1

QUICK REFERENCE DATA

GND = 0V; T_{amb} = 25°C; $t_r = t_f \leq 2.5$ns

SYMBOL	PARAMETER	CONDITIONS	TYPICAL	UNIT
t_{PHL}/t_{PLH}	Propagation delay An to Bn; Bn to An	C_L = 50pF V_{CC} = 3.3V	3.0	ns
C_I	Input capacitance		5.0	pF
$C_{I/O}$	Input/output capacitance		10	pF
C_{PD}	Power dissipation capacitance per buffer	V_I = GND to V_{CC}[1]	30	pF

NOTES:

1. C_{PD} is used to determine the dynamic power dissipation (P_D in μW):
   $P_D = C_{PD} \times V_{CC}^2 \times f_i + \Sigma (C_L \times V_{CC}^2 \times f_o)$ where:
   f_i = input frequency in MHz; C_L = output load capacity in pF;
   f_o = output frequency in MHz; V_{CC} = supply voltage in V;
   $\Sigma (C_L \times V_{CC}^2 \times f_o)$ = sum of the outputs.

PIN DESCRIPTION

PIN NUMBER	SYMBOL	NAME AND FUNCTION
1	1DIR	Direction control
2, 3, 5, 6, 8, 9, 11, 12	1B0 to 1B7	Data inputs/outputs
4, 10, 15, 21, 28, 34, 39, 45	GND	Ground (0V)
7, 18, 31, 42	V_{CC}	Positive supply voltage
13, 14, 16, 17, 19, 20, 22, 23	2B0 to 2B7	Data inputs/outputs
24	2DIR	Direction control
25	$2\overline{OE}$	Output enable input (active LOW)
36, 35, 33, 32, 30, 29, 27, 26	2A0 to 2A7	Data inputs/outputs
47, 46, 44, 43, 41, 40, 38, 37	1A0 to 1A7	Data inputs/outputs
48	$1\overline{OE}$	Output enable input (active LOW)

LOGIC SYMBOL



FUNCTION TABLE

INPUTS		INPUTS/OUTPUT	
$n\overline{OE}$	nDIR	nAn	nBn
L	L	A = B	inputs
L	H	inputs	B = A
H	X	Z	Z

H = HIGH voltage level
L = LOW voltage level
X = don't care
Z = high impedance OFF-state

LOGIC SYMBOL (IEEE/IEC)



BUS HOLD CIRCUIT



RECOMMENDED OPERATING CONDITIONS

SYMBOL	PARAMETER	CONDITIONS	LIMITS		UNIT
			MIN.	MAX.	
V_{CC}	DC supply voltage (for max. speed performance)		2.7	3.6	V
V_{CC}	DC supply voltage (for low-voltage applications)		1.2	3.6	V
V_I	DC Input voltage range		0	5.5	V
V_O	DC output voltage range; output HIGH or LOW state		0	V_{CC}	V
V_O	DC output voltage range; output 3-State		0	5.5	V
T_{amb}	Operating ambient temperature range in free air		–40	+85	°C
t_r, t_f	Input rise and fall times	V_{CC} = 1.2 to 2.7V V_{CC} = 2.7 to 3.6V	0 0	20 10	ns/V

ABSOLUTE MAXIMUM RATINGS[1]

In accordance with the Absolute Maximum Rating System (IEC 134) Voltages are referenced to GND (ground = 0V)

SYMBOL	PARAMETER	CONDITIONS	LIMITS		UNIT
			MIN	MAX	
V_{CC}	DC supply voltage		–0.5	+6.5	V
I_{IK}	DC input diode current	$V_I < 0$	–	–50	mA
V_I	DC input voltage	Note 2	–0.5	+6.5	V
I_{OK}	DC output diode current	$V_O > V_{CC}$ or $V_O < 0$	–	±50	mA
V_O	DC output voltage; output HIGH or LOW state	Note 2	–0.5	V_{CC} + 0.5	V
V_O	DC output voltage; output 3-State	Note 2	–0.5	6.5	V
I_O	DC output source or sink current	V_O = 0 to V_{CC}	–	±50	mA
I_{GND}, I_{CC}	DC V_{CC} or GND current		–	±100	mA
T_{stg}	Storage temperature range		–65	+150	°C
P_{tot}	Power dissipation per package – SO package – SSOP and TSSOP package	 Above +70°C derate linearly 8mW/K Above +60°C derate linearly 5.5mW/K		 500 500	mW

NOTES:

1. Stresses beyond those listed may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
2. The input and output voltage ratings may be exceeded if the input and output clamp current ratings are observed.

DC ELECTRICAL CHARACTERISTICS

Over recommended operating conditions. Voltages are referenced to GND (ground = 0V)

SYMBOL	PARAMETER	TEST CONDITIONS	LIMITS			UNIT
			Temp = -40°C to +85°C			
			MIN	TYP[1]	MAX	
V_{IH}	HIGH level Input voltage	V_{CC} = 1.2V	V_{CC}			V
		V_{CC} = 2.7 to 3.6V	2.0			
V_{IL}	LOW level Input voltage	V_{CC} = 1.2V			GND	V
		V_{CC} = 2.7 to 3.6V			0.8	
V_{OH}	HIGH level output voltage	V_{CC} = 2.7V; V_I = V_{IH} or V_{IL}; I_O = –12mA	V_{CC} – 0.5			V
		V_{CC} = 3.0V; V_I = V_{IH} or V_{IL}; I_O = –100µA	V_{CC} – 0.2	V_{CC}		
		V_{CC} = 3.0V; V_I = V_{IH} or $V_{IL;}$ I_O = –18mA	V_{CC} – 0.6			
		V_{CC} = 3.0V; V_I = V_{IH} or $V_{IL;}$ I_O = –24mA	V_{CC} – 0.8			
V_{OL}	LOW level output voltage	V_{CC} = 2.7V; V_I = V_{IH} or V_{IL}; I_O = 12mA			0.40	V
		V_{CC} = 3.0V; V_I = V_{IH} or V_{IL}; I_O = 100µA			0.20	
		V_{CC} = 3.0V; V_I = V_{IH} or $V_{IL;}$ I_O = 24mA			0.55	
I_I	Input leakage current	V_{CC} = 3.6V; V_I = 5.5V or GND		±0.1	±5	µA
I_{OZ}	3-State output OFF-state current[7]	V_{CC} = 3.6V; V_I = V_{IH} or V_{IL}; V_O = 5.5V or GND		0.1	±5	µA
I_{off}	Power off leakage supply	V_{CC} = 0.0V; V_I or V_O = 5.5V		0.1	±10	µA
I_{CC}	Quiescent supply current	V_{CC} = 3.6V; V_I = V_{CC} or GND; I_O = 0		0.1	20	µA
ΔI_{CC}	Additional quiescent supply current per input pin	V_{CC} = 2.7V to 3.6V; V_I = V_{CC} –0.6V; I_O = 0		5	500	µA
I_{BHL}	Bus hold LOW sustaining current	V_{CC} = 3.0V; V_I = 0.8V[2, 3, 4]	75			µA
I_{BHH}	Bus hold HIGH sustaining current	V_{CC} = 3.0V; V_I = 2.0V[2, 3, 4]	–75			µA
I_{BHLO}	Bus hold LOW overdrive current	V_{CC} = 3.6V[2, 3, 5]	500			µA
I_{BHHO}	Bus hold HIGH overdrive current	V_{CC} = 3.6V[2, 3, 5]	–500			µA

NOTES:
1. All typical values are at V_{CC} = 3.3V and T_{amb} = 25°C.
2. Valid for data inputs of bus hold parts (LVCH16-A) only.
3. For data inputs only, control inputs do not have a bus hold circuit.
4. The specified sustaining current at the data input holds the input below the specified V_I level.
5. The specified overdrive current at the data input forces the data input to the opposite logic input state.
6. For bus hold parts, the bus hold circuit is switched off when V_i exceeds V_{CC} allowing 5.5V on the input terminal.
7. For I/O ports the parameter I_{OZ} includes the input leakage current.

AC CHARACTERISTICS

GND = 0V; t_R = t_F = 2.5ns; C_L = 50pF; R_L = 500Ω; T_{amb} = –40°C to +85°C.

SYMBOL	PARAMETER	WAVEFORM	LIMITS						UNIT
			V_{CC} = 3.3V ±0.3V			V_{CC} = 2.7V		V_{CC} = 1.2V	
			MIN	TYP[1]	MAX	MIN	MAX	TYP	
t_{PHL} t_{PLH}	Propagation delay nAn to nBn; nBn to nAn	1	1.5	3	4.5	1.5	5.5	13	ns
t_{PZH} t_{PZL}	3-State output enable time n$\overline{OE}$ to nAn; n$\overline{OE}$ to nBn	2, 3	1.5	4	6.1	1.5	7.1	15	ns
t_{PHZ} t_{PLZ}	3-State output disable time n$\overline{OE}$ to nAn; n$\overline{OE}$ to nBn	2, 3	1.5	4	5.6	1.5	6.6	11	ns

NOTE:
1. All typical values are at V_{CC} = 3.3V and T_{amb} = 25°C.

AC WAVEFORMS

V_M = 1.5V at $V_{CC} \geq$ 2.7V; V_M = 0.5 V_{CC} at $V_{CC} <$ 2.7V.
V_{OL} and V_{OH} are the typical output voltage drop that occur with the output load.
$V_X = V_{OL}$ + 0.3V at $V_{CC} \geq$ 2.7V; $V_X = V_{OL}$ + 0.1 V_{CC} at $V_{CC} <$ 2.7V
$V_Y = V_{OH}$ –0.3V at $V_{CC} \geq$ 2.7V; $V_Y = V_{OH}$ – 0.1 V_{CC} at $V_{CC} <$ 2.7V



Waveform 1. Input (nAn, nBn) to output (nBn, nAn) propagation delay times



Waveform 2. 3-State enable and disable times

TEST CIRCUIT



Test Circuit for 3-State Outputs

SWITCH POSITION

TEST	SWITCH
t_{PLH}/t_{PHL}	Open
t_{PLZ}/t_{PZL}	2 * V_{CC}
t_{PHZ}/t_{PZH}	GND

V_{CC}	V_{IN}
< 2.7V	V_{CC}
2.7 – 3.6V	2.7V

DEFINITIONS

R_L = Load resistor
C_L = Load capacitance includes jig and probe capacitance
R_T = Termination resistance should be equal to Z_{OUT} of pulse generators.

SW00047

Waveform 3. Load circuitry for switching times

SSOP48: plastic shrink small outline package; 48 leads; body width 7.5 mm **SOT370-1**





DIMENSIONS (mm are the original dimensions)

UNIT	A max.	A_1	A_2	A_3	b_p	c	D (1)	E (1)	e	H_E	L	L_p	Q	v	w	y	Z (1)	θ
mm	2.8	0.4 0.2	2.35 2.20	0.25	0.3 0.2	0.22 0.13	16.00 15.75	7.6 7.4	0.635	10.4 10.1	1.4	1.0 0.6	1.2 1.0	0.25	0.18	0.1	0.85 0.40	8° 0°

Note

1. Plastic or metal protrusions of 0.25 mm maximum per side are not included.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT370-1		MO-118AA				~~93-11-02~~ 95-02-04

TSSOP48: plastic thin shrink small outline package; 48 leads; body width 6.1mm **SOT362-1**



Dimensions in mm.

NOTES

DEFINITIONS

Data Sheet Identification	Product Status	Definition
Objective Specification	Formative or in Design	This data sheet contains the design target or goal specifications for product development. Specifications may change in any manner without notice.
Preliminary Specification	Preproduction Product	This data sheet contains preliminary data, and supplementary data will be published at a later date. Philips Semiconductors reserves the right to make changes at any time without notice in order to improve design and supply the best possible product.
Product Specification	Full Production	This data sheet contains Final Specifications. Philips Semiconductors reserves the right to make changes at any time without notice, in order to improve design and supply the best possible product.

Philips Semiconductors
811 East Arques Avenue
P.O. Box 3409
Sunnyvale, California 94088–3409
Telephone 800-234-7381

print code Date of release: 05-96

Document order number: 9397-750-04531

Let's make things better.

Philips Semiconductors

PHILIPS