

Contents

Copeland EDI API v2 (API Version 1.21) 1

 Access 1

 Dates 1

 Temperature 1

 Conventions 1

 Method Descriptions 2

Authentication..... 2

Core API for Real-Time Trackers..... 2

 Get Sensor Readings 2

 Get Alerts 5

 Get Trip Status 6

 Define Trip..... 9

 Close Trip..... 13

 Cancel Trip..... 15

 Get Trip End Summary 16

 Update Trip 18

 Get Available Trackers 19

Copeland EDI API v2 (API Version 1.21)

The Copeland EDI API v2 is a publicly available API interface allowing Copeland customers access to the methods required to perform EDI operations such as launching a trip and retrieving tracker status information.

Access

Authentication requires a subscription ID and an Api Key, both provided from Copeland Customer Service. These keys are added to the headers collection of the request being made.

Dates

All dates and times follow the ISO 8601 standard. Here are a few examples:

```
2023-06-18T00:00:00
2024-12-30T17:08:56
2024-08-23T15:46:20
```

All of the API methods with date and time arguments expect UTC values; all returned date and time data will be in UTC as well.

Temperature

All temperature properties passed to API or returned from API are in °C.

Conventions

The Copeland EDI API conforms to standard HTTP verbs for all operations, as follows:

- GET** Used for retrieving data from the Oversight system
- POST** Used for creating new records or performing custom operations
- PUT** Used for updating existing records

In all method definitions, required fields are preceded with an asterisk (*).

Method Descriptions

All of the methods described in this document are broken into the following sections:

Definition: The URL of the API method

Header Fields: HTTP header fields required by the method

Parameters: HTTP Request Body in JSON format

Response: HTTP Response Body in JSON format

Error Codes: Error codes that may be returned in the Response data

Description: Detailed notes about the method

All specified **HEADER FIELDS** are required in each method call. In the **PARAMETERS** section, required arguments are identified with an *asterisk*. Unless noted as such, all other **PARAMETERS** section arguments are optional.

Authentication

A Subscription ID and Api Key are required for access to all of the Copeland EDI API methods. Copeland customers may request these keys from Copeland Customer Service.

Core API for Real-Time Trackers

Get Sensor Readings

DEFINITION:

POST <https://api.oversight.copeland.com/edi/GetSensorReadings>

HEADER FIELDS:

*Content-Type: *application/json*

*X-LT-ApiKey: **String** *API Key (provided by Copeland)*

*Ocp-Apim-Subscription-Key: **String** *Subscription Key (provided by Copeland)*

PARAMETERS:

*Request: GetSensorReadingsRequest *see definition below*

GetSensorReadingsRequest

PageSize: Int	1 – 1000; default to 500 if not provided
LastGUID Guid	Optional; GUID of the last sensor reading requested/returned

RESPONSE:

Response **GetSensorReadingsResponse** (see below)

HasMoreResults **Boolean**; indicates more sensor readings still available for download

MaxGUIDReturned **Guid**; the Guid of the last sensor reading returned

ErrorCode: **Int**

ErrorDescription: **String**

Count: **int**

GetSensorReadingsReponse

Guid: string (50 char max)	unique identifier for sensor reading
TrackerId string (255 char max)	GO unit serial number
DateTimeAcquiredUTC: string (ISO 8601)	UTC date and time of report
Latitude: double	Latitude of tracker at time of reporting
Longitude: double	Longitude of tracker at time of reporting
Sensors: Sensor[]	See definition below

ERROR CODES:

0	Success
100	internal Error
401	Access denied due to missing subscription key. Make sure to include subscription key when making requests to an API.
601280	RESTAPIKey is required.
601281	The RESTAPIKey provided does not map to a valid CustomerID.
601282	Username does not have access to RESTAPIKey.
601283	Not enough time has elapsed since previous request
601284	LastGUID is not valid.
601285	LastGUID specified is too old.
601286	PageSize specified is too large.

SENSOR

SensorId: **string** see definition below
SensorValue: **double** Sensor value in unit of measure defined for SensorId
BatteryPct: **int** Tracker battery level (%)
TripId: string Trip name provided in DefineTrip

SensorId values
"G0" Temperature in °C
"PRB" Probe temperature in °C
"HU" Humidity as % (0 - 100)
"CO2" Carbon dioxide in PPM (parts per million)

DESCRIPTION:
The **GetSensorReadings** API will return the next batch of sensor readings based on the last batch sent so subsequent calls will get the next results until all current readings have been returned. The consumer will know additional records exist based on the HasMoreResults flag. In order to get all current readings, the consumer would continue making calls until the HasMoreResults flag is false.

The number of records returned in each call will be 500 by default but the PageSize can be set to a value of 1 to 1,000 to adjust this number. The number of readings returned in the call is denoted by the Count field so that a call with a PageSize of 500 that returns only 7 readings would have a Count of 7 and a HasMoreResults of false. Subsequent calls made until new readings are generated with have a Count of 0 and HasMoreResults of false.

The first call made against the API will return data starting with the oldest record received in the last 24 hours.

Users can optionally use the LastGUID parameter to pull starting from a specific sensor reading. The MaxGUIDReturned in the response provides that last sensor reading which can be used to denote the placeholder of the last results requested. If the LastGUID parameter is not provided in the request the results will returned using the above logic.

EXAMPLE REQUEST:
HEADERS:

*Content-Type: application/json
*X-LT-ApiKey: 78589B11-8DC3-4BEF-B227-723C566AA87B
*Ocp-Apim-Subscription-Key: DFB873DC-69B1-4D6B-8552-E9302A472C40

Body:
{ "PageSize":2 }

EXAMPLE ERROR RESPONSES:
{ "ErrorCode":1011,"ErrorDescription":"Error getting sensor Readings: Not enough time has elapsed since previous request."}
{ "ErrorCode": null,"ErrorDescription":"Error getting sensor Readings: PageSize specified is too large."}

EXAMPLE SUCCESS RESPONSE:
"SensorReadings":[{"Guid":"f8ea2fca-18ba-ee11-aa0e-ad2ba16ff3b6","TrackerId":"1901088888","DateTimeAcquiredUTC":"2024-01-23T17:56:45","Latitude":26.835396,"Longitude":-80.133785,"IsinThrottleMinutes":false,"Sensors":[{"SensorId":"G0","SensorValue":22.62}], "BatteryPct":92},{ "Guid":"e15a7143-1bba-ee11-aa0e-ad2ba16ff3b6","TrackerId":"1901088888","DateTimeAcquiredUTC":"2024-01-23T18:02:42","Latitude":26.835687,"Longitude":-80.133778,"IsinThrottleMinutes":false,"Sensors":[{"SensorId":"G0","SensorValue":22.5}], "BatteryPct":92,"TripId":"ShipmentA3-9"}], "HasMoreResults":true, "ErrorCode":0, "ErrorDescription":null, "Count":2}

Get Alerts

DEFINITION:
POST <https://api.oversight.copeland.com/edi/GetAlerts>

HEADER FIELDS:

*Content-Type:	application/json	
*X-LT-ApiKey:	String	API Key (provided by Copeland)
*Ocp-Apim-Subscription-Key:	String	Subscription Key (provided by Copeland)

PARAMETERS:

*Request:	GetAlertsRequest see below
-----------	----------------------------

<i>GetAlertsRequest</i>	
*LastTripStatusSequenceID:	int
*LastTripStatusSequenceID:	

RESPONSE:

Response	GetAlertsResponse	see definition below
----------	-------------------	----------------------

<i>GetAlertsResponse</i>	
ErrorCode:	int
ErrorDescription:	string
Memo	string
TripStatusList:	TripStatus[]
	See definition below

<i>TripStatusList</i>	
TripStatusSequenceID:	int
	sequential identifier for TripStatus records
TrackerID:	string
	GO unit serial number
EMRCustomerID:	int
	Copeland Customer Identifier
LaneDescription	string
	lane description
Latitude:	double
	latitude of tracker at time of reporting
Longitude:	double
	longitude of tracker at time of reporting
DateTimeAcquiredUTC:	string (ISO 8601)
	UTC date and time of report
TripID:	string
	from DefineTripRequest record
CarrierTcode:	string
	optional customer data, from DefineTripRequest
CustomerCode:	string
	optional customer data, from DefineTripRequest
ShipmentStatusCode:	string
	defined below
StopNumber:	int
	from DefineTripRequest record (-1 if not at a stop)
EventCity:	string
	city at time of reporting
EventState:	string
	state at time of reporting
EventZip:	string
	zip code at time of reporting
BatteryPct	int
	tracker battery level (%)
AlertCode:	int
	defined below

AlertID: long	Copeland internal alert ID
AlertDesc: string	description of alert, if any
AlertValue: double	temperature value, if there is an alert (°C)
AlertThresholdLowCritical: double	temperature range from DefineTripRequest (°C)
AlertThresholdHighCritical: double	temperature range from DefineTripRequest (°C)
Sensors: Sensor[]	<i>see definition below</i>
PlateNum: string	Optional Plate number, from DefineTripRequest
ContainerNum: string	Optional Container number, from DefineTripRequest
DriverPhone: string	Optional Driver phone number, from DefineTripRequest
ReturnCode int	if included, error code from previous Define Trip request
ExceptionMessage string	if included, error description from previous Define Trip request

Sensor

SensorId: string	<i>see definition below</i>
SensorValue: double	Sensor value in unit of measure defined for SensorId

ShipmentStatusCode values

AFO	<i>Trip Started</i>
X3	<i>Pick Stop Entered</i>
AF	<i>Pick Stop Exited</i>
X1D	<i>Trip Ended</i>
X1	<i>Delivery Stop Entered</i>
CD	<i>Delivery Stop Exited</i>
X6	<i>General Status, No Event</i>
EN	<i>General Stop Entered</i>
EX	<i>General Stop Exited</i>

AlertCode values

201	<i>Temperature Alert</i>
416	<i>Tracker battery below threshold</i>
803	<i>Tracker entered end location proximity</i>
806	<i>Tracker entered trip stop proximity</i>
906	<i>Light detected</i>
909	<i>Shock detected [default is off]</i>

SensorId values

"G0"	<i>Temperature in °C</i>
"PRB"	<i>Probe temperature in °C</i>
"HU"	<i>Humidity as % (0 - 100)</i>
"CO2"	<i>Carbon dioxide in PPM (parts per million)</i>

ERROR CODES:

0	<i>success</i>
100	<i>internal Error</i>

401 Access denied due to missing subscription key. Make sure to include subscription key when making requests to an API."

1011 Not enough time has elapsed since previous request

DESCRIPTION:
The **GetAlerts** method requests alert generated by a tracker.

EXAMPLE REQUEST:
HEADERS:

*Content-Type: application/json
*X-LT-ApiKey: 78589B11-8DC3-4BEF-B227-723C566AA87B
*Ocp-Apim-Subscription-Key: DFB873DC-69B1-4D6B-8552-E9302A472C40

Body:
{ "LastTripStatusSequenceID":12345 }

EXAMPLE ERROR RESPONSE:
{ "ErrorCode":1001,"ErrorDescription":"InvalidApiKey" }

EXAMPLE SUCCESS RESPONSE:
{ "TripStatusList":[{ "TripStatusSequenceID":72076754,"TrackerID":"T192580225","Latitude":37.173659879,"Longitude":-77.49579359,"DeviceTemp":-20.5,"DateTimeAcquiredUTC":"2023-06-30T06:45:00","TripID":"MT CM Temp 1 -1","ShipmentStatusCode":"X6","StopNumber":-1,"BatteryPct":100,"AlertCode":201,"AlertID":20001,"AlertDesc":"Alert! The temperature is too low. Immediate action is required to prevent damage to your product.","AlertValue":-20.5,"AlertThresholdLowCritical":5,"AlertThresholdHighCritical":95,"Sensors":[{ "SensorId":"G0","SensorValue":-20.5}], "EMRCustomerID":19258}], "ErrorCode":0,"ErrorDescription":null,"Memo":null }

Get Trip Status

DEFINITION:
POST <https://api.oversight.copeland.com/edi/GetTripStatus>

HEADER FIELDS:

*Content-Type:	application/json
*X-LT-ApiKey:	String API Key (provided by Copeland)
*Ocp-Apim-Subscription-Key:	String Subscription Key (provided by Copeland)

PARAMETERS:
Request: **GetTripStatusRequest** see below

GetTripStatusRequest
*LastTripStatusSequenceID: int

RESPONSE:
Response **GetTripStatusResponse** see definition below

GetTripStatusResponse

ErrorCode:	int
ErrorDescription:	string
TripStatus:	TripStatus[] see definition below

TripStatus

TripStatusSequenceID:	int sequential identifier for TripStatus records
TrackerID:	string GO unit serial number

EMRCustomerID: int	Copeland Customer Identifier
LaneDescription string	lane description
Latitude: double	latitude of tracker at time of reporting
Longitude: double	longitude of tracker at time of reporting
DateTimeAcquiredUTC: string (ISO 8601)	UTC date and time of report
TripID: string	from DefineTripRequest record
CarrierTcode: string	optional customer data, from DefineTripRequest
CustomerCode: string	optional customer data, from DefineTripRequest
ShipmentStatusCode: string	defined below
StopNumber: int	from DefineTripRequest record (-1 if not at a stop)
EventCity: string	city at time of reporting
EventState: string	state at time of reporting
EventZip: string	zip code at time of reporting
BatteryPct int	tracker battery level (%)
AlertCode: int	defined below
AlertID: long	Copeland internal alert ID
AlertDesc: string	description of alert, if any
AlertValue: double	temperature value, if there is an alert (°C)
AlertThresholdLowCritical: double	temperature range from DefineTripRequest (°C)
AlertThresholdHighCritical: double	temperature range from DefineTripRequest (°C)
Sensors: Sensor[]	<i>see definition below</i>
PlateNum: string	Optional Plate number, from DefineTripRequest
ContainerNum: string	Optional Container number, from DefineTripRequest
DriverPhone: string	Optional Driver phone number, from DefineTripRequest
ReturnCode int	if included, error code from previous Define Trip request
ExceptionMessage string	if included, error description from previous Define Trip request

Sensor

SensorId: string	<i>see definition below</i>
SensorValue: double	Sensor value in unit of measure defined for SensorId

ShipmentStatusCode values

AFO Trip Started
X3 Pick Stop Entered
AF Pick Stop Exited
X1D Trip Ended
X1 Delivery Stop Entered
CD Delivery Stop Exited
X6 General Status, No Event
EN General Stop Entered
EX General Stop Exited

AlertCode values

EXAMPLE SUCCESS RESPONSE (BAD DEFINE TRIP REQUESTS):
{
 "ErrorCode":0,"ErrorDescription":null,"TripStatusList":[{"ExceptionMessage":"Cannot change Tracker after Trip start",
 "ReturnCode":3201,"TrackerID":"1200008892", "TripID":"MyTrip", "TripStatusSequenceID":27540692},
 {"ExceptionMessage":"DeviceID is already assigned to another Trip",
 "ReturnCode":3102,"TrackerID":"1200008892", "TripID":"MyTrip222", "TripStatusSequenceID":27540693}]}
}

EXAMPLE SUCCESS RESPONSE:
{
 "ErrorCode":0,"ErrorDescription":null, "TripStatusList":[
 {"BatteryPct":95, "DateTimeAcquiredUTC":"2017-10-31T14:01:36", "DeviceTemp":14.6, "EventCity":"Charlwood",
 "EventState":"England", "EventZip":"RH6", "Latitude":51.15134, "Longitude":-0.212221,
 "TrackerID":"8901001423", "TripID":"LLAC/8901001423", "TripStatusSequenceID":27498556},
 {"BatteryPct":95, "DateTimeAcquiredUTC":"2017-10-31T14:37:25", "DeviceTemp":14.6, "EventCity":"Charlwood",
 "EventState":"England", "EventZip":"RH6", "Latitude":51.15134, "Longitude":-0.212221,
 "TrackerID":"8901001423", "TripID":"LLAC/8901001423", "TripStatusSequenceID":27500043},
 {"BatteryPct":95, "DateTimeAcquiredUTC":"2017-10-31T15:13:27", "DeviceTemp":14.4,
 "EventCity":"Bletchingley", "EventState":"England", "EventZip":"RH9 8ND", "Latitude":51.25153, "Longitude":-0.074731, "TrackerID":"8901001423", "TripID":"LLAC/8901001423",
 "TripStatusSequenceID":27502648,"PlateNum":"ABC123","ContainerNum":"E929","DriverPhone":"(333)444-5555"}]}
}

Define Trip

DEFINITION:
POST <https://api.oversight.copeland.com/edi/DefineTrip>

HEADER FIELDS:

*Content-Type:	<i>application/json</i>	
*X-LT-ApiKey:	String	<i>API Key (provided by Copeland)</i>
*Ocp-Apim-Subscription-Key:	String	<i>Subscription Key (provided by Copeland)</i>

PARAMETERS:

*Request: DefineTripRequest see *below*

DefineTripRequest

*TripID:	string (50 char max)	unique identifier for this trip/shipment
TripAction:	string (50 char max)	“cancel” = cancel trip, else NULL
*TrackerID:	string (50 char max)	GO unit serial number
LaneDescription	string (255 char max)	optional lane description
CarrierTcode:	string (50 char max)	optional customer data
CustomerCode:	string (50 char max)	optional customer data
TempLowCritical:	float	low temperature critical threshold (°C)
TempHighCritical:	float	high temperature critical threshold (°C)
*Locations:	StopLocation[]	defined below – at least two Locations required
RepID:	string (50 char max)	optional customer data
RepFirstName:	string (100 char max)	optional customer data
RepLastName:	string (100 char max)	optional customer data
RepPhone:	string (50 char max)	optional customer data
RepEmail:	string (250 char max)	optional customer data
ShipperName:	string (100 char max)	optional customer data
ReceiverName:	string (100 char max)	optional customer data
CarrierName:	string (100 char max)	optional customer data
CarrierEmails:	string[]	array of email addresses to notify of alerts
ShipperEmails:	string[]	optional customer data
ReceiverEmails:	string[]	optional customer data

RetailerID:	string	optional unique ID of Retailer that will receive a copy of this shipment.
DriverName:	string (100 char max)	optional customer data
DriverPhone:	string (50 char max)	optional customer data
EstimatedFlightMinutes:	int	Estimated time traveling by airplane (minutes)
EstimatedLoadingMinutes:	int	Estimated time to load shipment onto airplane
PlateNum	String (20 character max)	Optional Plate number
ContainerNum	String (50 character max)	Optional Container number
ReceiverPONum	String (50 character max)	Optional Container number

StopLocation

*LocationName:	string (50 char max)	customer defined location name, required
*LocationID:	string (50 char max)	customer defined unique location ID, required
*Address1:	string (100 char max)	Required
Address2:	string (100 char max)	Optional
*City:	string (50 char max)	Required
*State:	string (50 char max)	Optional
*Zip:	string (50 char max)	Required
*Country:	string (50 char max)	Required
LocationContact:	string (100 char max)	Optional
LocationPhoneNumber:	string (50 char max)	Optional
*LocationType:	string (50 char max)	must be either pick (0) or delivery (1)
		for an Origin StopLocation, this is the estimated time the truck will leave the location.
StopDateUTC:	string (ISO 8601)	for a Destination StopLocation, this is the estimated time the truck will arrive at the location.
		for AdditonalStops StopLocations, this is not used.

StopTypeCode	int	Used to designate airport departure (100) or arrival (101) Only ONE airport arrival and departure per trip/shipment should be specified
--------------	------------	--

RESPONSE:

Response	TripNotificationResponse	<i>see definition below</i>
----------	---------------------------------	-----------------------------

TripNotificationResponse

ErrorCode:	int
ErrorDescription:	string

ERROR CODES:

0	<i>success</i>
100	<i>internal Error</i>
1001	<i>invalid apiKey</i>

1004	<i>origin and destination Locations must be specified - you must provide at least 2 Locations</i>
1005	<i>missing sensor range values - if specified, at least one high & one low must be provided</i>
1006	<i>invalid sensor range values - high values must be greater than low values</i>
1007	<i>specified tracker is inactive</i>
1008	<i>missing API key</i>
1010	<i>invalid parameter</i>
1011	<i>Not enough time has elapsed since previous request</i>

DESCRIPTION:

The **DefineTrip** method defines a new Trip for processing by the Oversight system and subsequent notifications via the **GetTripStatus** method. The *DefineTripRequest* object is a required parameter which defines the details about a trip to be created or updated. To create a new trip, pass in a new *DefineTripRequest* object with a unique TripID. To update an existing trip, pass in a *DefineTripRequest* object with the TripID to be updated, along with all of the fields as they were passed in originally, and any changed fields set to their updated values. To cancel a trip, pass in a new *DefineTripRequest* with the *TripAction* field set to "cancel". No other fields are required to cancel a trip.

Note: You do not have to specify any temperature ranges for a trip. However, if you would like to specify a temperature range, then you MUST provide both TempLowCritical and TempHighCritical. In summary, with respect to temperature range settings, you must provide none or both. All temperatures specified need to be in °C.

Note: There must be at least two *StopLocations* specified; the first *StopLocation* is the Trip Start Location and the last *StopLocation* is the Trip End Location. Any other planned stops for this trip must be specified between the Trip Start *StopLocation* and the Trip End *StopLocation*, in sequential order.

EXAMPLE REQUEST:
HEADERS:

*Content-Type: application/json
*X-LT-ApiKey: 78589B11-8DC3-4BEF-B227-723C566AA87B
*Ocp-Apim-Subscription-Key: DFB873DC-69B1-4D6B-8552-E9302A472C40

Body:

```
{
  "CarrierEmails":[""],
  "CarrierName": "",
  "CarrierTcode": "",
  "CustomerCode": "",
  "DriverName": "",
  "EstimatedFlightMinutes": null,
  "EstimatedLoadingMinutes": null,
  "LaneDescription": null,
  "Locations": [
    {
      "Address1": "5210 Windward Pkwy",
      "Address2": "",
      "City": "Alpharetta",
      "Country": "USA",
      "LocationContact": "",
      "LocationID": "101",
      "LocationName": "Warehouse",
      "LocationPhoneNumber": "",
      "LocationType": 0,
      "State": "GA",
      "StopDateUTC": "2015-12-08T00:00:00",
      "StopTypeCode": null,
      "Zip": "30004"},
    {
      "Address1": "330 S Hope St",
      "Address2": "",
      "City": "Los Angeles",
      "Country": "USA",
      "LocationContact": "Joey",
      "LocationID": "223",
      "LocationName": "Store 101",
      "LocationPhoneNumber": "(213) 626-0709",
```

```
        "LocationType":1,
        "State":"CA",
        "StopDateUTC":"2015-12-15T13:00:00",
        "StopTypeCode":null,
        "Zip":"90071"}
    ],
    "ReceiverEmails":[""],
    "ReceiverName":"","
    "RepEmail":"John@Smith.com",
    "RepFirstName":"John",
    "RepID":"","
    "RepLastName":"Smith",
    "RepPhone":"555-555-5555",
    "RetailerID":null,
    "ShipperEmails":[""],
    "ShipperName":"","
    "TempHighCritical":5.5,
    "TempLowCritical":0.5,
    "TrackerID":"1800884890",
    "TripAction":0,
    "TripID":"MyTestTrip",
    "PlateNum":"ABC123",
    "ContainerNum":"E929",
    "ReceiverPONum":"RPO",
    "DriverPhone":"(333)444-5555"
}
```

EXAMPLE ERROR RESPONSE:

```
{ "ErrorCode":1007,"ErrorDescription":"DeviceID specified is an inactive Tracker"}
```

EXAMPLE SUCCESS RESPONSE:

```
{ "ErrorCode":0,"ErrorDescription":""}
```

Close Trip

DEFINITION:

POST <https://api.oversight.copeland.com/edi/CloseTrip>

HEADER FIELDS:

*Content-Type:	<i>application/json</i>	
*X-LT-ApiKey:	String	<i>API Key (provided by Copeland)</i>
*Ocp-Apim-Subscription-Key:	String	<i>Subscription Key (provided by Copeland)</i>

PARAMETERS:

*Request: CloseTripRequest *see below*

CloseTripRequest

*TripID:	string (50 char max)	unique identifier for this trip/shipment
*TrackerID:	string (50 char max)	GO unit serial number
EndTripDateTimeUTC	string (ISO 8601)	if included, time that the trip ended

RESPONSE:

Response **ErrorResponse** *see definition below*

ErrorResponse

ErrorCode:	int
ErrorDescription:	string

ERROR CODES:

0	<i>success</i>
100	<i>internal Error</i>
1001	<i>invalid apiKey</i>
2001	<i>TrackerID specified does not exist as a Tracker</i>
2002	<i>TrackerID specified is an inactive Tracker</i>
2003	<i>TrackerID specified exists, but has never been assigned to a customer</i>
2020	<i>EndTripDateTimeUTC cannot be in the future</i>
9002	<i>Trip does not exist</i>

DESCRIPTION:

The **CloseTrip** method forces a trip, previously defined by a call to **DefineTrip**, to end.

EXAMPLE REQUEST:

HEADERS:

*Content-Type:	<i>application/json</i>
*X-LT-ApiKey:	<i>78589B11-8DC3-4BEF-B227-723C566AA87B</i>
*Ocp-Apim-Subscription-Key:	<i>DFB873DC-69B1-4D6B-8552-E9302A472C40</i>

Body:

`{"TrackerID":"2000017125","TripID":"MyTrip"}`

EXAMPLE ERROR RESPONSE:

`{"ErrorCode":-1,"ErrorDescription":"DeviceID specified is an inactive Tracker"}`

EXAMPLE SUCCESS RESPONSE:`{"ERRORCODE":0,"ERRORDescription":""}`

Cancel Trip

DEFINITION:

POST <https://api.oversight.copeland.com/edi/CancelTrip>

HEADER FIELDS:

*Content-Type:	<i>application/json</i>	
*X-LT-ApiKey:	String	<i>API Key (provided by Copeland)</i>
*Ocp-Apim-Subscription-Key:	String	<i>Subscription Key (provided by Copeland)</i>

PARAMETERS:

*Request: CancelTripRequest *see below*

CancelTripRequest

*TripID:	string (50 char max)	unique identifier for this trip/shipment
*TrackerID:	string (50 char max)	GO unit serial number

RESPONSE:

Response **ErrorResponse** *see definition below*

ErrorResponse

ErrorCode: **int**
ErrorDescription: **string**

ERROR CODES:

0	<i>success</i>
100	<i>internal Error</i>
1001	<i>invalid apiKey</i>
2001	<i>TrackerID specified does not exist as a Tracker</i>
2002	<i>TrackerID specified is an inactive Tracker</i>
2003	<i>TrackerID specified exists, but has never been assigned to a customer</i>
9002	<i>Trip does not exist</i>

DESCRIPTION:

The **CancelTrip** method forces a trip, previously defined by a call to **DefineTrip**, to end.

EXAMPLE REQUEST:

HEADERS:

*Content-Type: *application/json*
*X-LT-ApiKey: 78589B11-8DC3-4BEF-B227-723C566AA87B
*Ocp-Apim-Subscription-Key: DFB873DC-69B1-4D6B-8552-E9302A472C40

Body:

`{"TrackerID":"2000017125","TripID":"MyTrip"}`

EXAMPLE ERROR RESPONSE:

`{"ErrorCode":-1,"ErrorDescription":"DeviceID specified is an inactive Tracker"}`

EXAMPLE SUCCESS RESPONSE:{"ERRORCODE":0,"ERRORDESCRIPTION":""}

Get Trip End Summary

DEFINITION:

POST <https://api.oversight.copeland.com/edi/GetTripEndSummary>

HEADER FIELDS:

*Content-Type:	<i>application/json</i>	
*X-LT-ApiKey:	String	<i>API Key (provided by Copeland)</i>
*Ocp-Apim-Subscription-Key:	String	<i>Subscription Key (provided by Copeland)</i>

PARAMETERS:

Request: **GetTripEndSummaryRequest** *see below*

GetTripEndSummaryRequest

*From:	string (ISO 8601)	UTC period start <i>Time trip completed or time marked completed</i>
*Thru:	string (ISO 8601)	UTC period end <i>Period must not exceed 24 hours</i>

RESPONSE:

Response **GetTripEndSummaryResponse** *see definition below*

GetTripEndSummaryResponse

ErrorCode:	int	
ErrorDescription:	string	
TripEndSummary:	TripEndSummary[]	<i>see definition below</i>
ResultsTruncated	bool	True if number of trackers in specified date range exceed the per call limit
TotalTrackers	int	Total number of trackers in specified date range
Memo	string	Not implemented

TripEndSummary

CustomerCode:	string	From DefineTripRequest
TripID:	string	From DefineTripRequest
TrackerID:	string	GO unit serial number
MKT:	double	Mean Kinetic Temperature °C
SensorStandardDeviation:	double	Sensor standard deviation
CarrierName:	string	From DefineTripRequest
ActualTripStart:	string (ISO 8601)	UTC actual trip start time
ActualTripEnd:	string (ISO 8601)	UTC actual trip end time
TripStateChanged:	string (ISO 8601)	UTC time trip ended or time marked completed
OriginAddress	string	Origin address
OriginCity	string	Origin city
OriginState	string	Origin state
OriginCountry	string	Origin country
DestinationAddress	string	Destination address
DestinationCity	string	Destination city
DestinationState	string	Destination state
DestinationCountry	string	Destination country
MaxSensorValue	double	Maximum sensor value °C
MinSensorValue	double	Minimum sensor value °C
LowCriticalAlertCount	int	Number of low critical alerts

LowWarningAlertCount	Int	Number of low warning alerts
HighWarningAlertCount	Int	Number of high warning alerts
HighCriticalAlertCount	Int	Number of high critical alerts
TotalTemperatureAlertCount	int	Number of all temperature alerts
ScheduledStartTime:	string (ISO 8601)	UTC scheduled trip start time
ScheduledEndTime:	string (ISO 8601)	UTC scheduled trip end time

ERROR CODES:

0	success
50000	internal Error
50002	API key is required
50003	The API key provided does not map to a valid CustomerID
50004	From and Thru are required
50005	Invalid Date range specified
50006	Date range specified exceeds maximum allowed days
50007	Not enough time has elapsed since previous request
51000	Error getting Trip data

DESCRIPTION:

The **GetTripEndSummary** API is intended to be called on a rolling basis (e.g. once per day or every few hours). For each call, **From** should be the **Thru** of the previous call, to retrieve all newly completed trips since the last call, with no gaps. This will return summaries of all trips that completed in the specified period (**ActualTripEnd**), or that were *marked* as completed in that period (**TripStateChanged**).

Tracker data does not always transmit in real-time (e.g. no cell service). **TripStateChanged** is used to return trips that were *marked* as completed in selected date range, even if the **ActualTripEnd** was *before* the requested date range.

Note: An error will be returned if this API is called too frequently

Note: An error will be returned if the period from **From** to **Thru** exceeds 24 hours

EXAMPLE REQUEST:

HEADERS:

*Content-Type: application/json

*X-LT-ApiKey: 78589B11-8DC3-4BEF-B227-723C566AA87B

*Ocp-Apim-Subscription-Key: DFB873DC-69B1-4D6B-8552-E9302A472C40

Body:

{"From":"2020-12-01T00:00:00","Thru":"2020-12-01T02:00:00"}

EXAMPLE ERROR RESPONSE:

{"ErrorCode":1009,"ErrorDescription":"No records found","TripEndSummary":null}

EXAMPLE SUCCESS RESPONSE:

{"TripEndSummaryList":[{"CustomerCode":null,"TripID":"Test trip 36","TrackerID":"4800030217","MKT":null,"SensorStandardDeviation":null,"CarrierName":"","ActualTripStart":"2017-09-27T13:38:11","ActualTripEnd":"2020-07-17T19:06:27","TripStateChanged":"2020-07-17T19:06:27","ScheduledStartTime":"2018-03-15T05:09:00","ScheduledEndTime":"2018-03-31T05:10:00"}],"ResultsTruncated":false,"TotalTrackers":1,"ErrorCode":0,"ErrorDescription":null,"Memo":null}

Update Trip

DEFINITION:

POST <https://api.oversight.copeland.com/edi/UpdateTrip>

HEADER FIELDS:

*Content-Type:	application/json	
*X-LT-APIKey:	String	API Key (provided by Copeland)
*Ocp-Apim-Subscription-Key:	String	Subscription Key (provided by Copeland)

PARAMETERS:

Request:	UpdateTripRequest	see below
----------	-------------------	-----------

UpdateTripRequest

*TrackerID:	string (ISO 8601)	GlobalDeviceID
*TripName:	string (ISO 8601)	Trip name
*CustomerIDTracker:	int	Customer ID tracker belongs to
*RESTAPIKey:	string (ISO 8601)	REST Api key [this or CustomerID required]

RESPONSE:

Response	UpdateTripResponse	see definition below
----------	--------------------	----------------------

UpdateTripResponse

ErrorCode:	int	
ErrorDescription:	string	
TripName:	string	Updated trip name

ERROR CODES:

0	success
100	internal Error
50001	You must provide @RESTAPIKey or @CustomerID
50002	Can only specify either CustomerID OR RESTAPIKey
50003	The RESTAPIKey provided does not map to a valid CustomerID
50004	Sent-from Customer is not EDIEnabled
50006	Username is required
50007	TrackerID is required
50008	TripName is required
50009	CustomerIDTracker is required
50010	CustomerIDTracker does not map to a valid Customer
50011	TrackerID does not exist as a Tracker
50013	TrackerID does not have an active customer assignment
50014	TrackerID does not map to the CustomerIDTracker specified
50015	Customer does not have permission to update trips for the Tracker's Customer

DESCRIPTION:

The **UpdateTrip** API is intended to be called when the trip name needs to be updated on as as-needed basis. The original trip name is appended to the trip description field (prefixed with “[OldName=”) and the trip name is replaced with the new value. Expected usage is to provide the end user with the RestApiKey for the target customer so that they may update trip names in the target customer [permissions via EDITransmissionPermissions relation].

Both the CustomerIDTracker and RESTAPIKey refer to the customer who owns the tracker. Please contact your account representative to obtain a RESTAPIKey for any customer sites you wish have permission to update trackers with.

EXAMPLE REQUEST:
HEADERS:

*Content-Type: application/json
*X-LT-ApiKey: 78589B11-8DC3-4BEF-B227-723C566AA87B
*Ocp-Apim-Subscription-Key: DFB873DC-69B1-4D6B-8552-E9302A472C40

Body:
{ "CustomerIDTracker":11671,"RestApiKey":"90ABE92D-66A7-49BF-AEBC-0ED8C737FD73","TrackerID":"1801234772-11671","TripName":"Update#5" }

EXAMPLE ERROR RESPONSE:
{ "ErrorCode":50015,"ErrorDescription":" Customer does not have permission to update trips for the Tracker's Customer ", "TripName":null }

EXAMPLE SUCCESS RESPONSE:
{ "TripName":"Update#5","ErrorCode":0,"ErrorDescription":null }

Get Available Trackers

DEFINITION:
POST <https://api.oversight.copeland.com/edi/GetAvailableTrackers>

HEADER FIELDS:
*Content-Type: application/json
*X-LT-ApiKey: String API Key (provided by Copeland)
*Ocp-Apim-Subscription-Key: String Subscription Key (provided by Copeland)

PARAMETERS:
Request: GetAvailableTrackersRequest see below

GetAvailableTrackersRequest

*CustomerID: int	Customer ID trackers assigned to
------------------	----------------------------------

RESPONSE:
Response GetAvailableTrackersResponse see definition below

GetAvailableTrackersResponse

ErrorCode: int
ErrorDescription: string
AvailableTrackers: AvailableTrackers[] Collection of trackers (see below)

TrackerSerialNumber:	string	ID used to identify the tracker
GroupName:	string	User-friendly name for the group the tracker belongs to
GroupID:	int	ID identifying the Group

ERROR CODES:

0	success
100	internal Error
1010	Customer ID required
1011	User does not have permissions to view trackers for this customer

DESCRIPTION:

The **GetAvailableTrackers** API is intended to be called when a user needs to know the trackers available for shipment creation priori to calling create shipment. The user will need to have permissions to view trackers for the customer they provide the CustomerID for.

EXAMPLE REQUEST:

HEADERS:

*Content-Type: application/json
*X-LT-ApiKey: 78589B11-8DC3-4BEF-B227-723C566AA87B
*Ocp-Apim-Subscription-Key: DFB873DC-69B1-4D6B-8552-E9302A472C40

Body:

{"CustomerID":10073}

EXAMPLE ERROR RESPONSE:

{"ErrorCode":1011,"ErrorDescription":"User does not have permissions to view trackers for this customer"}

EXAMPLE SUCCESS RESPONSE:

{"AvailableTrackers":[{"TrackerSerialNumber":"1000338713","GroupName":"MultiTrip Serial #s","GroupID":101},{"TrackerSerialNumber":"1201142211","GroupName":"Active Serial #s without a trip assigned","GroupID":103}],"ErrorCode":0,"ErrorDescription":null}

An AvailableTracker consists of the following three fields:

- 1. TrackerSerialNumber
- 2. GroupName
- 3. GroupID

*Group classifications are defined below

GroupID	GroupName
101	MultiTrip Serial #s
102	Inactive Serial #s
103	Active Serial #s without a trip assigned