




Big Data



Big Data



Big Data Flow




Big Data Flow

Ingestion

Huge load
Reliable
Scalable

Σ
Data
Aggregators


Log
aggregators


Load
Balancers

Storage

Processing

Insights

Data Aggregators

- Listens to events from servers and:
 - Aggregates values for counters
 - Generates stats for timers (max, min, mean, std_dev, percentiles)
 - Maintains sets of values
- Memory efficient (stores only counters/variables to calculate stats)
- Instead of sending millions requests to database, only aggregated statistics are sent

Load balancers

- Distribute load across multiple servers
- Add/Remove servers as load increases/decreases
- No need for over-provisioning

Log Aggregators

- Front layer before actual data storage
- Dedicated to process and stream logs to destination
- Scalable to cope with the load
- Some systems enable real-time analytics on the stream of incoming data

Probabilistic Data Structures

- They do not provide definite answer
 - Can return false positive or false negative
 - But will be firm on True Positives or True Negatives
- Used to avoid costly checks
- Example: Bloom filter
 - Checks if an item is in a set
 - "possibly in set" or "definitely not in set"
 - Chrome Browser - checks locally if url could be malicious, if yes then perform second online check that will detect false positives
 - Some databases checks if rows exist
 - Caching servers use it to prevent caching one-hit websites

ETL / ELT

- Extract
 - pull data from source (other databases, data lake, websites, etc.)
- Transform
 - clean, filter, map, join, apply business rules
- Load
 - load data to destination data storage
- With new, scalable, cloud-based databases a valid choice is often to load “raw” data and then do transformations using SQL
 - This process is often still referred as ELT

Big Data Flow

Ingestion

Huge load
Reliable
Scalable


Σ
Data
Aggregators

Log
aggregators

Load
Balancers

Storage

Fast access
Fault tolerant
Scalable



Data lake



Cache



Data
Warehouse



Distributed
databases

Processing

Insights

Data lake

- Vast storage of raw data
 - Data usually stored in files
 - Multiple rows/units of data in one file
 - Some basic grouping (by log type, date, etc.)
 - Excellent to dump all incoming data
 - Should be further processed to be useful
-
- Still should have some design in mind not to turn into data swamp

HDFS

- Hadoop Distributed File System
- A file system to store files across cluster
 - Divides files into chunks
 - Stores chunks at different nodes
 - Duplicates chunks (to prevent data loss in case a node goes down)
- Enables to store large amount of data
 - Low possibility of data loss
 - Fast access

No-SQL


- Databases able to store unstructured data
- SQL is still important and have multum use cases
 - NO should corresponds rather to Not Only
- Popular for many big data applications
 - Simple design
 - Easier to scale horizontally (by adding more servers vs making server bigger)
- Different types of storage
 - Key-value storage
 - Wide column (each row may have different columns)
 - Graph
 - Document


Big Data Flow

Ingestion

Huge load
Reliable
Scalable


Σ
Data
Aggregators


Log
aggregators


Load
Balancers

Storage

Fast access
Fault tolerant
Scalable



Data lake



Cache



Data
Warehouse



Distributed
databases

Processing

Parallel
Distributed
Scalable


Spark



Flink



Apache PIG

Insights

Hadoop

- A collection of software packages to facilitate orchestration of network of computers
- Hadoop cluster consist of multiple nodes (one being a master node)
- Components:
 - HDFS - distributed file system
 - MapReduce - programming model for handling large amount of data
 - YARN - Yet Another Resource Negotiator - cluster management
- Thanks for distributed files jobs can run in parallel working on data that is on a given node

Aggregating data (group - map - reduce)

Spark/PIG program loads logs:

```
{ "store_id":1, "date":"2016-10-31 00:00:00", "user_id":"x1", "entry_page":"home", ... }  
{ "store_id":2, "date":"2016-10-31 00:00:01", "user_id":"x2", "entry_page":"product", ... }  
...  
{ "store_id":1, "date":"2016-10-31 00:15:31", "user_id":"x1", "revenue":500.00, ... }  
...
```

Use **store_id**, **date**, and **user_id** to group and maps logs into sessions:

```
{ "store_id":1, "session_start_date":"2016-10-31 00:00:00", "user_id":"x1",  
  "entry_page":"home", "revenue":500.00, ... }  
{ "store_id":2, "session_start_date":"2016-10-31 00:00:01", "user_id":"x2",  
  "entry_page":"product", "revenue":null, ... }  
...
```


Aggregating data (group - map - reduce)

Aggregate sessions using **store_id**, **day(session_start_date)**, **entry_page**, and other relevant fields*:

```
{ "store_id":1, "date":"2016-10-31", "entry_page":"home", "num_sessions": 154304,
  "num_transaction":11446, "revenue":1022770.23, ... }
{ "store_id":1, "date":"2016-10-31", "entry_page":"product", "num_sessions": 93070,
  "num_transaction":6327, "revenue":520129.45, ... }
...
{ "store_id":2, "date":"2016-10-31", "entry_page":"home", "num_sessions": 127829,
  "num_transaction":2243, "revenue":452317.34, ... }
...
```

* Some fields may need special processing (e.g. translating **user_agent** string to human readable form)


Big Data Flow

Ingestion

Huge load
Reliable
Scalable

Σ
Data
Aggregators


Log
aggregators


Load
Balancers

Storage

Fast access
Fault tolerant
Scalable



Data lake



Cache



Data
Warehouse



Distributed
databases

Processing

Parallel
Distributed
Scalable


Spark



Flink




Apache PIG

Insights

Automated
On-demand
Actionable

 **tableau**
SOFTWARE



ML

