

1. We need to tell AngularJS what part of our HTML page contains the AngularJS app. You do so by adding the attribute to the root HTML element of the AngularJS app.

- A) ng-app
- B) ag-app
- C) js-app
- D) aj-app

Ans: A

2. AngularJS can show or hide HTML depending on the state of data in the model. You do so using a set of AngularJS directives such as which are created specifically for that purpose.

- A) ng-shown, ng-hidden
- B) ng-show, ng-hide
- C) nt-show, nt-hide
- D) ng-shows, ng-hides

Ans: B

3. EventEmitter class's simple interface, which basically encompass two methods can therefore be used to trigger custom events and listen to events as well, both synchronously or asynchronously.

- A) exit()
- B) superscript()
- C) subscribe()
- D) emit()

Ans: C

4. The directive substitutes the normal href property and makes it easier to work with route links in Angular 2. Moreover if we want to navigate between routes, we use the directive.

- A) RouterLinks
- B) RouterLinking
- C) RouterLink
- D) RouterLinq

Ans: C

5. Three main components of Routing are

- A) RouteObject
- B) RouterOutlet
- C) RouterState
- D) RouterLink

Ans: A,B,D

6. Route allow us to pass values in our url to our component so we can dynamically change our view content.

- A) pipes
- B) modules
- C) variables
- D) parameters

Ans: D

7. To use observables, Angular uses a third-party library called

- A) ng2-bootstrap
- B) angular-cli
- C) numeral
- D) Reactive Extensions (RxJS)

Ans: D

8. Observables help you manage data.

- A) synchronous
- B) asynchronous
- C) Both asynchronous & synchronous
- D) None of above

Ans: B

9. We subscribe to the observable ourselves using the actual method. The downside is that you have to manage the subscription yourself.

- A) subscribe()
- B) subs()
- C) subscribed()
- D) None of above

Ans: A

10. A promise represents the final result of an operation.

- A) asynchronous
- B) synchronous

Ans: A

11. The promise becomes after resolving or rejecting.

- A) mutable
- B) ignored
- C) immutable
- D) recurring

Ans: C

12. Which of the following is not built-in pipe in Angular

- A) DatePipe

- B) CurrencyPipe
- C) DataPipe
- D) PercentPipe

Ans: C

13. If you chain multiple pipes together, they are executed

- A) in parallel
- B) LIFO order
- C) in the order in which you specify them
- D) none of above

Ans: C

14.The filter waits for a promise and returns the most recent value received. It then updates the view.

- A) sync
- B) async
- C) promise
- D) custom

Ans: B

15.The decorator allows us to define the pipe name that is globally available for use in any template in the across application.

- A) @pipeName
- B) @pipeDeco
- C) \$Pipe
- D) @Pipe

Ans: D

16. Data bindings are applied as or as special sequences of characters in strings.

- A) expressions
- B) attributes on HTML elements
- C) elements itself
- D) none of above

Ans: B

17. A data binding has these four parts:

- A) host element, curly brackets, target, expression
- B) host element, square brackets, target, evaluation
- C) host element, square brackets, target, expression
- D) host element, parentheses, target, expression

Ans: C

18. Attribute binding is similar to property binding but is tied to the rather than the DOM property.

- A) Page attribute
- B) DOM attribute
- C) Root attribute
- D) HTML attribute

Ans: D

19. To make your applications ready for animations, you must include the AngularJS Animate library and then you must refer to the module in your application.

- A) ng-repeat
- B) ngAnimation
- C) ngAnimate
- D) None of above

Ans: C

20. Using the animation function, the parent animation can allow the child animation to run at the exact correct time.

- A) animateChild
- B) childAnimate
- C) animateInner
- D) innerChild

Ans: A

21. Animations are fired using animation property bindings which are prefixed with an symbol.

- A) &
- B) #
- C) \$
- D) @

Ans: D

22.. is an animation-specific function that is designed to be used inside of Angular's animation DSL language. It is used to kick off a reusable animation that is created using animation().

- A) useAnimation
- B) reuseAnimation
- C) in-useAnimation
- D) All of above

Ans: A

23. It's always possible to make use of animation input parameters by setting even more data via the property.

- A) options.param
- B) option.params

- C) option.param
- D) options.params

Ans: D

24. Which of the following bootstrap styles are used to create a vertical pills navigation?

- A. .nav, .nav-tabs
- B. .nav, .nav-pills
- C. .nav, .nav-pills, .nav-stacked
- D. .nav, .nav-tabs, .nav-justified

Ans: C

97). Which of the following bootstrap styles are used to create a justified tabs navigation?

- A.nav, .nav-tabs
- B.nav, .nav-pills
- C.nav, .nav-pills, .nav-stacked
- D.nav, .nav-tabs, .nav-justified

Answer : D

25.Which class indicates a dropdown menu?

- a) .dropdown-list
- b) .select
- c) .dropdown

Ans: C

26. Ques. Bootstrap's grid system allows up to

- a. 6 columns across the page
- b. 12 columns across the page
- c. columns across the page
- d. columns across the page

Ans: B

27. Which of the following class makes round corner image for automatically adjust to fit the size of the screen?

- a. .img-res-image
- b. .img-responsive-image * img-fluid (for full width responsible)
- c. .img-responsive
- d. .img-res

Ans: C

28. Which class should be used to indicate a button group?

- a. btn-group-buttons
- b. btn-group
- c. btn-grp
- d. btn-buttons

Ans: B

29. On the opposite side of event bindings (()) lie Angular's square-bracket syntax ([[]]) which signify a

- A) property binding
- B) class binding
- C) style binding
- D) both A & B

Ans: A

30. Which object oriented terms are supported by Typescript?

- A. Modules B. Classes C. Interfaces D. All of these

Ans: D

31. What are the types of access modifiers supported by TypeScript?

- A. Public B. Private C. Protected D. All of these

Ans: D

31) Which of the following code will not throw an error?

- A. `JSON.parse("");`
- B. `JSON.parse(null);`
- C. `JSON.parse();`
- D. `JSON.parse({});`

Ans: B

32) What does JSONP stand for?

- A. JSON Procedures
- B. JSON Parsing
- C. JSON with padding
- D. JSON Programming

Ans: C

33) What is the value of json in the following code?

```
var obj = { fruit: 'apple', toJSON: function () { return 'orange'; } }; var json = JSON.stringify({x: obj});
```

- A. `{"x": "orange"}`
- B. `{"fruit": "apple"}`
- C. `{"x": "apple"}`
- D. `{"fruit": "orange"}`

Ans: A

34) What is the MIME type of JSON?

- A. `application/x-json`
- B. `text/json`
- C. `application/json`
- D. `application/javascript`

Ans: C

35)What function will convert a JavaScript object to a JSON string?

- A. JSON.text()
- B. JSON.serialize()
- C. JSON.toString()
- D. JSON.stringify()

Ans: D

36)In the below notation, Student is of type { “Student”: [“Amy”, “Bob”, “John”] }

- A. Not a valid JSON string
- B. Array
- C. Class
- D. Object

Ans:B

37)JSON-RPC is a remote procedure call protocol

38) To use observables, Angular uses a third-party library called

- A) ng2-bootstrap
- B) angular-cli
- C) numeral
- D) Reactive Extensions (RxJS)

Ans:D

39) We subscribe to the observable ourselves using the actual method. The downside is that you have to manage the subscription yourself.

- A) subscribe()
- B) subs()
- C) subscribed()
- D) None of above

Ans: A

40)Which of the following is not built-in pipe in Angular

- A) DatePipe
- B) CurrencyPipe
- C) DataPipe
- D) PercentPipe

Ans: C

41)The filter waits for a promise and returns the most recent value received. It then updates the view.

- A) sync
- B) async
- C) promise

D) custom

Ans: B

42)If you chain multiple pipes together, they are executed

- A) in parallel
- B) LIFO order
- C) in the order in which you specify them
- D) none of above

Ans:D

43)Observables help you manage data.

- A. synchronous
- B. asynchronous
- C. Both asynchronous & synchronous
- D. None of above

Ans: B

44) The decorator allows us to define the pipe name that is globally available for use in any template in the across application.

- A. pipeName
- B. pipeDeco
- C. Pipe
- D. None

Ans: C

45)console.log(x);
var x = 5;

Ans: 5

46) RPC:-Remote Procedure call

47). Three main components of Routing are

- A) RouteObject
- B) RouterOutlet
- C) RouterState
- D) RouterLink

Ans: A,B,D

48). Route allow us to pass values in our url to our component so we can dynamically change our view content.

- A) pipes
- B) modules
- C) variables
- D) parameters

Ans: D

49). Promises are more advanced than Observables.

- A) True
- B) False

Ans: B

50). Which class is used to create a black navigation bar?

- a. .navbar-default
- b. .navbar-black
- c. .navbar-dark
- d. .navbar-inverse

Ans: D

51). The .container-fluid class provides

- a. Fixed width container
- b. Table format
- c. To create a Form
- d. Full width container

Ans: D

52). $1+2+"3" = 33$ (Ans)

53.) CSS validator: -- csslint

54.) Create responsive images by adding an .img-responsive class to the tag.

55.) img-responsive was in Bootstrap 3, img-fluid is in Bootstrap 4 since beta version.

56.) Bootstrap provides the .img-fluid class to make an image scale appropriately across devices. This class applies `max-width: 100%` and `height: auto` to the image. ... Resize your browser to see the image scale as the viewport becomes smaller.

57.) `<script src="myscripts.js">`

58.) Typescript uses which datatype?

- a) boolean
- b) string
- c) Number
- d) void
- e) All the above

Ans: e

59.) typescript support function overloading

60. css preprocessor

- less
- sass
- both (ans)

61. which prefix is used to add animation

@(ans)

62. default access modifier of typescript

-public(ans)

63. POP()

-Decrement by 1

64. how to implement inheritance in typescript

-extends(ans)

65. What keywords are reserved in JSON and cannot be used as keys?

- A. Value
- B. Object
- C. There are none.
- D. Key

Ans: C

66.) How to get information about browser?

- a) Browser
- b) version
- c) navigator

Ans: C

67.) which event will trigger if button will lost its focus?

:- onblur

68.) Display property?

- A) None
- B) inline
- c) inline-block
- d) block

Ans: All

69.) Shorthand method to represent background of (common)

Ans: background

70.) ----- is an HTML specification used to add more information to HTML tags.

- A) Macrodata
- B) Microdata
- c) Minidata
- d) Modifydata

Ans: B

71.) What is the purpose of the mimeType property of a plug-in entry?

- a) Contains MIME properties
- b) Contains MIME sizes
- c) Contains MIME types
- d) Contains MIME methods

Ans: C

72.) Which of the following can be implemented using animation?

- A) Fireworks
- B) fade Effect

- C) Roll-in or Roll-out
- D) All of the mentioned

Ans: D

- 73.) Which is the property that represents the content displayed in the window?
- A) document
 - B) content
 - C) window
 - D) frame

Ans: A

- 74.) How can we make methods available on all objects?
- A) Object.add(methods)
 - B) Object.methods(add)
 - C) Object.add.methods(...)
 - D) Object.prototype

Ans: D

- 75.) The four kinds of class members are_____

- a) Instance methods, Instance fields, Static method, Dynamic method
- b) Instance fields, Instance methods, Class fields, class methods
- c) Instance fields, non-Instance fields, Dynamic methods, Global methods
- d) Global methods, Local methods, Dynamic methods, Static methods

Ans: B

- 76.) Video tag :-- <video>

- 77.) Full Form of Angular CLI?

Ans: command-line interface.

- 78.) TYpe of binding:-

Ans: 4 Type: 1) Property Binding []
2) Interpolation {{}}
3) Event Binding ()
4) Two way Binding {[]}

- 79.) Javascript is used for:- Interactivity

- 80.) How to declare variable in Typescript?

- A) Var
- B) Let
- C) Both

Ans: C

- 81.) Typescript uses which datatype?

- A) String
- B) Number
- C) Boolean
- D) All above option

Ans: D

82.) Default access modifier typescript?

- A) public
- B) private
- c)protected

Ans: A

83.) Super() in typescript?

Ans: Super Constructor

84.)Which field is required in <input>

- A)required
- B) minlength
- c)Both

Ans: A

84.)How to implements inheritance in typescript?

- A) implements
- B) extends

Ans: B

85.) Which keyword we can't use in JSON?

- A) Object
- B) key
- c) value
- D)None

Ans: D

86.) How can we add/ delete in array and returns the removed item.

- A)slice
- B) shift
- c)reverse
- D)splice

Ans: D.splice

87.) How to get information about browser

- A)Browser
- B)Version
- C)navigator

Ans:C

88.)Display property:

- 1)None
- 2)inline
- 3)inline-block
- 4)block

Ans: all 4

89.) Which event will trigger if (button..) will lost its focus:

Ans: onblur

90.) ans: prototype

91.) Drawback of typescript?

ans: all of the above

92.) Ans: 1row-2col

93.) Ans: Carosec

94.) Typescript is co.....

a) It supports overloading

b) partial

c) No

Ans: A

95.) Ans: HTML Attribute

96.) Ans::: n:child (nth)

97.) option: A)owner B)admin c)Both Ans: C

****NOTES** Pipe**

1.) You use your custom pipe the same way you use built-in pipes.

2.) You must include your pipe in the declarations array of the AppModule.

3.) You must manually register custom pipes. If you don't, Angular reports an error.

4.) "Power Boost Calculator" that combines your pipe and two-way data binding with ngModel.

5.) There are two categories of pipes: pure and impure. Pipes are pure by default.

pipe impure by setting its pure flag to false.

6.) The Angular AsyncPipe is an interesting example of an impure pipe. The AsyncPipe accepts a Promise or Observable as input and subscribes to the input automatically, eventually returning the emitted values.

7.) The JsonPipe provides an easy way to diagnosis a mysteriously failing data binding or inspect an object for future binding.

**** Animation**

1.) Angular animations are built on top of the standard Web Animations API and run natively on browsers that support it.

For other browsers, a polyfill is required.

2.) Animations are defined inside @Component metadata. Before you can add animations, you need to import a few animation-specific functions:

- 3.) It uses animations to transition between two states: active and inactive. When a hero is active, the element appears in a slightly larger size and lighter color.
- 4.) Angular animations are defined as logical states and transitions between states.
- 5.) When both directions of a transition have the same timing, you can use the shorthand syntax `<=>`:
- 6.) a) The `active => *` transition applies when the element's state changes from active to anything else.
b) The `* => *` transition applies when any change between two states takes place.
- 7.) There are three timing properties you can tune for every animated transition: the duration, the delay, and the easing function. They are all combined into a single transition timing string.

Q. `JSON.parse()` function was developed as a safer alternative to

`Go function()`
`eval()`
`Function() eval`
`call function()`

Ans: `eval()`

- * fixed width `.container`
- * full width `.container-fluid`