

Exercise 5

Codes :

Server :

```
#include <netdb.h>
#include <netinet/in.h>
#include <stdio.h>
#include <string.h>
#include <sys/socket.h>
#include <sys/types.h>
#include <time.h>
#include <unistd.h>
int main(int argc, char *argv[])
{
    int sd, ad;
    char buff[1024];
    struct sockaddr_in servaddr, cliaddr;
    time_t t1;
    bzero(&servaddr, sizeof(servaddr));
    servaddr.sin_family = AF_INET;
    servaddr.sin_addr.s_addr = htonl(INADDR_ANY);
    servaddr.sin_port = htons(1507);

    bind(sd, (struct sockaddr *)&servaddr, sizeof(servaddr));
    listen(sd, 5);
    printf("Server is running...\n");
    ad = accept(sd, (struct sockaddr *)NULL, NULL);
    while (1)
    {
        bzero(&buff, sizeof(buff));
        t1 = time(NULL);
        snprintf(buff, sizeof(buff), "%24s\r\n", ctime(&t1));
        send(ad, buff, sizeof(buff), 0);
    }
}
```


Client:

```
#include <netdb.h>
#include <netinet/in.h>
#include <stdio.h>
#include <sys/socket.h>
#include <sys/types.h>
#include <time.h>
#include <unistd.h>
int main(int argc, char *argv[])
{
    int sd, ad;
    char buff[1024];
    struct sockaddr_in cliaddr, servaddr;
    struct hostent *h;
    h = gethostbyname(argv[1]);
    bzero(&servaddr, sizeof(servaddr));


    servaddr.sin_family = AF_INET;
    memcpy((char *)&servaddr.sin_addr.s_addr, h->h_addr_list[0], h->h_length);
    servaddr.sin_port = htons(1507);
    sd = socket(AF_INET, SOCK_STREAM, 0);
    connect(sd, (struct sockaddr *)&servaddr, sizeof(servaddr));
    recv(sd, buff, sizeof(buff), 0);
    printf("Day time of server is: %s\n", buff);
    return 0;
}
```

Output:

Server:



Client:



The screenshot shows a VS Code editor with a file explorer on the left and a terminal on the right. The file explorer shows a project structure with folders for 'Client' and 'Server'. The terminal shows the compilation and execution of a C client program.

```
Psaravanan:~/environment/RA1911026010033/Exp5/Client $ gcc dtClient.c -o dtc
dtClient.c: In function 'main':
dtClient.c:15:5: warning: implicit declaration of function 'bzero' [-Wimplicit-function-declaration]
    bzero(&servaddr, sizeof(servaddr));
    ^~~~~
dtClient.c:15:5: warning: incompatible implicit declaration of built-in function 'bzero'
dtClient.c:18:5: warning: implicit declaration of function 'memcpy' [-Wimplicit-function-declaration]
    memcpy((char *) &servaddr.sin_addr.s_addr, h->h_addr_list[0], h->h_length);
    ^~~~~~
dtClient.c:18:5: warning: incompatible implicit declaration of built-in function 'memcpy'
Psaravanan:~/environment/RA1911026010033/Exp5/Client $ ./dtc 172.31.14.10
Day time of Server is: Mon Aug 16 09:38:57 2021

Psaravanan:~/environment/RA1911026010033/Exp5/Client $
```