

## Randomized Algorithms

- Deterministic and (Las Vegas & Monte Carlo) Randomized Algorithms
- Probability Review
- Probabilistic Analysis of deterministic QUICK-SORT Algorithm
- RANDOMIZED-SELECT and RANDOMIZED-QUICK-SORT
- Max-Cut
- Min-Cut
- MAX-3-SAT and Derandomization
- Closest pair
- Hashing, Bloom filters, Streams, Sampling, Reservoir sampling, Sketch

IMDAD ULLAH KHAN

# The MAX-3-SAT Problem

- Given  $n$  Boolean variables  $x_1, \dots, x_n$
- Each can take a value of 0/1 (true/false)
- A literal is a variable appearing in some formula as  $x_i$  or  $\bar{x}_i$
- A clause of size 3 is an OR of three literals
- A 3-CNF formula is AND of one or more clauses of size  $\leq 3$
- A formula is satisfiable if there is an assignment of 0/1 values to the variables such that the formula evaluates to 1 (or true)

3-SAT( $f$ ) problem: Is there a satisfying assignment for 3-CNF formula  $f$ ?

MAX-3-SAT( $f$ ) problem: Find an assignment for 3-CNF formula  $f$  that satisfies the maximum number of clauses

**MAX-3-SAT( $f$ )** problem: Find an assignment for 3-CNF formula  $f$  that satisfies the maximum number of clauses

- The problem is NP-HARD
- Brute Force: Try all  $2^n$  possible assignments in  $\mathcal{O}(m2^n)$ 
  - ▷  $m$  is the number of clauses

MAX-3-SAT( $f$ ) problem: Find an assignment for 3-CNF formula  $f$  that satisfies the maximum number of clauses

## Randomized Algorithm

- Simple Idea: Toss a coin, and independently set each variable true with probability  $1/2$
- What is the expected number of clauses satisfied by a random assignment?

A random assignment to variables satisfies in expectation  $7m/8$  clauses of a 3-CNF formula  $f$  with  $m$  clauses

Let random variable  $Z_j = \begin{cases} 1 & \text{if clause } C_j \text{ is satisfied} \\ 0 & \text{otherwise} \end{cases}$

$$E[Z_j] = \Pr[C_j \text{ is satisfied}] = 1 - \Pr[C_j \text{ is not satisfied}]$$

$C_j$  is not satisfied when all literals in  $C_j$  are set to FALSE (independently)

$$\text{Thus, } \Pr[C_j \text{ is not satisfied}] = (1/2)^3 = 1/8 \quad \triangleright \quad E[Z_j] = 7/8$$

Let  $Z$  be the number of clauses satisfied by random assignment

$$E[Z] = \sum_{j=1}^m E[Z_j] = \sum_{j=1}^m \frac{7}{8} = \frac{7m}{8} \quad \triangleright \text{linearity of expectation}$$

## MAX-3-SAT Las Vegas $7/8$ -Approximation

For any instance of MAX-3-SAT with  $m$  clauses, there exists a truth assignment which satisfies at least  $7m/8$  clauses

- There is a non-zero probability that a random variable takes the value of its expectation
- $Pr[Z \geq E[Z] - 7k/8] > 0$

Probabilistic Method:

Prove the existence of a non-obvious property by showing that a random construction produces it with positive probability

- Is there a  $7/8$  Las Vegas approximation algorithm for MAX-3-SAT?
  - guaranteed to find an assignment satisfying at least  $7m/8$  clauses
  - expected runtime is polynomial
- Standard trick: Repeatedly generate a random assignment  $A$  to variables until  $A$  satisfies at least  $7m/8$  clauses
- Suppose  $\Pr[A \text{ satisfies } \geq 7m/8 \text{ clauses}] \geq p$
- Then, expected number of trials to find this assignment is  $1/p$ 
  - ▷ Expectation of geometric random variable
- If  $p$  is polynomial, then expected running time is polynomial

## MAX-3-SAT Las Vegas ( $7/8$ )-Approximation

Probability  $p$  that a random assignment satisfies  $\geq 7m/8$  clauses is  $\geq 1/8m$

$p_j$  : probability that the random assignment satisfies exactly  $j$  clauses

▷  $j = 1, 2, \dots, m$

Lower bound on  $p$  using  $E[Z] = 7m/8$

$$E[Z] = \sum_{j=0}^m j p_j = \sum_{j < 7m/8} j p_j + \sum_{j \geq 7m/8} j p_j \leq \frac{7m-1}{8} \sum_{j < 7m/8} p_j + m \sum_{j \geq 7m/8} p_j$$

$$\implies E[Z] \leq 7m-1/8 \cdot 1 + m \cdot p \implies 7m/8 \leq 7m-1/8 + mp \implies p \geq 1/8m$$

MAX-3-SAT cannot be approximated in polynomial time to within a ratio greater than  $7/8$ , unless  $P=NP$

▷ [Håstad 1997]



## MAX-3-SAT: Derandomization

---

- Random choices by an algorithm sometimes happen to be 'good' i.e.
  - The randomized algorithm output is close to the optimal
- Can these 'good' choices be made deterministically?
- Derandomization: Transforming a randomized algorithm into a deterministic algorithm
- Can the  $7/8$ -approx Las Vegas Algorithm for MAX-3-SAT be derandomized?
- How do we know which set of choices for variable assignments is 'good'? i.e. satisfies greater number of clauses
- Idea: Consider the choice for each variable (True/False) one by one

## MAX-3-SAT : Derandomization

- Let  $Z$  be the number of clauses satisfied

Given assignments for the “first  $i$ ” variables  $x_1 = a_1 \cdots, x_i = a_i$ , the expected value of  $Z$  with random assignment of the unassigned variables  $x_{i+1}, \cdots, x_n$  can be computed in polynomial time

- Given assignment to a variable, for each clause  $C_j$  if the corresponding literal evaluates to
  - FALSE, then remove it from  $C_j$
  - TRUE, then ignore the clause as it is satisfied
- Conditional expectation of  $Z$  is the unconditional expectation of  $Z$  in the reduced set of clauses plus the number of already satisfied clauses
- This yields a polynomial time deterministic algorithm for MAX-3-SAT

## MAX-3-SAT : Derandomization

- Let  $Z$  be the number of clauses satisfied
- Fix an order of variables  $x_1, x_2, \dots, x_n$
- For  $i = 1$  to  $n$ 
  - If  $E[Z | x_1 = a_1, \dots, x_{i-1} = a_{i-1}, x_i = \text{TRUE}] > E[Z | x_1 = a_1, \dots, x_{i-1} = a_{i-1}, x_i = \text{FALSE}]$ ,
    - then set  $x_i$  to TRUE
    - else set  $x_i$  to FALSE
- Since  $E[Z | x_1 = a_1, \dots, x_i = a_i] \geq E[Z]$  for  $1 \leq i \leq n$
- And  $E[Z] = 7m/8$
- Thus,  $E[Z | x_1 = a_1, \dots, x_i = a_i] \geq 7m/8$
- Derandomized algorithm satisfies at least  $7m/8$  clauses